

Design Rules Summary


for Drawing Layers

2026/01/01

Drawing Layer Table

	Original MASK layers				Proposed Drawing layers					
	Name	NUM	TYPE		Name	NUM	TYPE			
1	PSUB	140	0		WN	140	0			
2	NW	36	0					MDP generatioed		
3	HVNW	141	0					MDP generatioed		
4	L	3	0					MDP generatioed		
					AP	3	1	Active for P+		
					AN	3	2	Active for N+		
					AR	3	3	Active for resistor		
					AC	3	4	Active for capacitance		
5	NF	25	0					MDP generatioed		
6	PF	26	0					MDP generatioed		
7	CL	143	0					MDP generatioed		
8	HPBE	144	0					No USE		
9	HNBE	145	0					No USE		
10	PBE	146	0					MDP generatioed		
11	NBE	147	0					MDP generatioed		
12	HPM	33	0					MDP generatioed		
13	RHP	148	0					No USE		
14	SG	8	0							
					PO	8	1	POLY transistor		
					PR	8	2	POLY resistor		
15	PM	35	0					MDP generatioed		
16	NM	7	0					MDP generatioed		
17	R	12	0					MDP generatioed		
18	PSD	9	0					MDP generatioed		
19	NSD	28	0					MDP generatioed		
20	CONT	11	0		CO	11	0			
21	M1	13	0		M1	13	0			
22	TC	19	0		V1	19	0			
23	M2	20	0		M2	20	0			
24	PRO	14	0		PE	14	0			
	TXM1	48	0		TXM1	48	0	M1 Label		
	PIN	48	1		PIN	48	1	M1 Pin		
	TXM2	49	0		TXM2	49	0	M2 Label		
	MASK	63	0		MASK	63	0	Waiver region		
	MEAS	63	1		MEAS	63	1	Measurement region		
	SCRIBE	80	0		SCRIBE	80	0	Waiver region (EDGE SEAL)		
	prBoundary	235	0		prBoundary	235	0	Cell boundary		

Prohibited




Rule	L1	L2	Func	MIN	MAX
WN.Z1	WN (R)	AP+AC	None	0.0	
WN.Z2	WN (C)	AP+AR	None	0.0	
CO.Z1	CO	AA+PO+PR	None	0.0	
CO.Z3	CO	M1	None	0.0	
V1.Z1	V1	M1	None	0.0	
V1.Z2	V1	M2	None	0.0	

Function:


Wmin/max: L1 Width min/max
Smin/max: L1 Space min/max (L1=L2)
Smin/max: L1 Separate L2 min/max
Emin/max: L1 Enclosed L2 min/max
Fmin/max: L1 Enclosing L2 min/max
ECmin: MOS Endcap min
Wfix: L1 Windth equal
Sfix: Space equal
Donut: L1 Souuounded by L2
None: Not Exist

WN to AP/AN/AR/AC related




Rule	L1	L2	Func	MIN	MAX
WN.W1	WN		Wmin	8.0	
WN.S1	WN	WN	Smin	12.0	
WN.S2	WN	WN (R)	Smin	9.5	
WN.S3	WN	WN (C)	Smin	12.0	
WN.S4	WN (R)	WN (C)	Smin	9.5	
WN.S5	WN (R)	WN (R)	Smin	8.0	
WN.S6	WN (C)	WN (C)	Smin	12.0	
WN.AP	WN	AP	Smin	5.0	
WN.AN	WN	AN	Smin	10.0	
AR.S1	AR	AR	Smin	4.0	
AR.WR	AR	WN (R)	Emin	10.0	
AN.WR	AN	WN (R)	Emin	5.0	
AR.AN	AR	AN	Smin	4.0	
AC.W1	AC		Wmin/max	28.5	120.0
AC.S1	AC	AC	Smin	???	???
AC.WC	AC	WN (C)	Emin	???	???
AN.WC	AN	WN (C)	Emin	3.0	
AC.AN	AC	AN	Smin	2.8	
AC.R1	AC	AN (C)	Donut	0.0	

MOS transistor related







Rule	L1	L2	Func	MIN	MAX
AP.W1	AP		Wmin	1.4	
AP.S1	AP	AP	Smin	1.4	
AP.AN	AP	AN	Smin	2.8	
AP.WM	PMOS	AP-PO	Wmin/max	3.4	60.0
AP.LM	PMOS	PO-AN	Lmin/max	1.0	30.0
AP.WN	AP	WN	Emin	7.0	
DP.W1	DP		Wmin	2.8	
DP.S1	DP	DP	Smin	???	???
DP.AP	DP	AP	Smin	2.8	
DP.AN	DP	AN	Smin	2.8	
AN.W1	AN		Wmin	1.4	
AN.S1	AN	AN	Smin	1.4	
AN.AP	AN	AP	Smin	2.8	
AN.WM	NMOS	AN-PO	Wmin/max	3.4	60.0
AN.LM	NMOS	PO-AN	Lmin/max	1.0	30.0
AN.WN	AN	WN (M)	Emin	5.0	
DN.W1	DN		Wmin	2.8	
DN.S1	DN	DN	Smin	???	???
DN.AP	DN	AP	Smin	2.8	
DN.AN	DN	AN	Smin	2.8	

Contact and Poly related




Rule	L1	L2	Func	MIN	MAX
PO.W1	PO		Wmin	1.0	30.0
PO.S1	PO	PO	Smin	1.2	
PO.AP	PO	AP	Smin	0.4	
PO.AN	PO	AN	Smin	0.4	
PO.EP	PMOS	PO	ECmin	1.2	
PO.EN	NMOS	PO	ECmin	1.2	
CO.W1	CO		Wmin	1.0	
CO.S1	CO	CO	Smin	1.0	
CO.WD	CO(D)		Wfix	1.2	
CO.AD	CO(D)	AP+AN	Emin	1.2	
CO.AP	CO	AP	Emin	0.8	
CO.AN	CO	AN	Emin	0.8	
CO.PG	CO	PO(G)	Smin	1.0	
CO.PO	CO	PO	Emin	0.8	

Resistor(AR/RS) and Capacitor(AC) related



Rule	L1	L2	Func	MIN	MAX
AR.W1	RR	RR (L)	Wmin/max	2.8	20.0
AR.L1	RR	RR (W)	Lmin/max	13.0	100.0
AR.PO	PO	AR	Smin	1.0	
AR.PW	PO (AR)		Wmin	2.0	
AR.XY	AR	Bevel	XYmin	1.0	
PO.AN	PO (AR)	AN	Smin	???	???
PO.R1	AR	PO (AR)	Donut	0.0	
PO.R2	PO	TieDown		0.0	
PR.W1	RS	RS (L)	Wmin/max	4.0	20.0
PR.L1	RS	RS (W)	Lmin/max	20.0	100.0
PR.S1	RS	RS	Smin	2.0	
CR.W1	CO (RR)		Wmin	1.0	
CR.W2	CL (RR)		Wmin/max	1.0	97.5
CR.AT	CO (RR)	AR (T)	Emin	1.5	
CR.AS	CO (RR)	AR (S)	Emin	1.0	
CC.W1	CO (C)		Wmin	1.2	
CC.S1	CO (C)	CO (C)	Smin	1.2	
CC.AC	CO (C)	AC	Emin	2.9	
CC.AN	CO (C)	AN	Emin	1.2	

M1 / V1 / M2 related



Rule	L1	L2	Func	MIN	MAX
M1.W1	M1		Wmin	1.8	
M1.S1	M1	M1	Smin	1.4	
M1.SC	M1 (C)	M1 (C)	Smin	10.0	
M1.CO	M1	CO (S)	Fmin	0.8	
M1.CC	M1	CO (C)	Fmin	1.2	
M1.CL	M1	CO (L)	Fmin	1.2	
M1.SW	M1 (W)	M1	Smin	2.0	
V1.W1	V1		Wfix	1.4	
V1.S1	V1	V1	Smin	1.5	
V1.M1	V1	M1	Emin	1.0	
V1.PO	V1	PO	Smin	1.2	
V1.CO	V1	CO	Smin	1.0	
V1.CL	V1	CO (L)	Smin	1.4	
M2.W1	M2		Wmin	3.0	
M2.S1	M2	M2	Smin	2.0	
M2.V1	M2	V1	Fmin	1.0	


Design Rule control

DRC integrity

DRC

Document

PCell




ALL Critical Dimension parameters are referenced by 'XX.YY' rule's name.


Design to Tapeout Process

Mask Data Preparation

Designer



OpenSUSI



Fab

