

Text Properties in CSS:

-> CSS Text Properties are used to control the appearance, alignment, spacing, and decoration of text.

-> Following are some important text properties:

1. text-align: Used to align text horizontally.

syntax: text-align: left(default) | start | center | right | end | justify;

2. text-align-last: Used to align the last line of text.

syntax: text-align-last: center;

3. word-spacing: Used to increase or decrease space between words.

syntax: word-spacing: 20px;

4. letter-spacing: Used to increase or decrease space between letters.

syntax: letter-spacing: 5px;

5. text-decoration: Used to add decoration to text.

syntax: text-decoration: line-type style color width;

example: text-decoration: underline wavy red 5px;

6. Remove Underline From Anchor Tag:

```
syntax: a {  
    text-decoration: none;  
}
```

7. text-transform: Used to change letter case.

syntax: text-transform: uppercase | lowercase | capitalize;

8. text-shadow: Used to add shadow to text.

syntax: text-shadow: x-axis y-axis blur color;

example: text-shadow: 2px 2px 5px red;

9. line-height: Used to control spacing between lines.

syntax: line-height: 40px;

Font Properties in CSS:

-> CSS Font Properties are used to change the style, size, thickness, and appearance of text.

-> Font is the style provided for the text.

1. font-size: Used to change the size of the text.

syntax: font-size: 40px;

2. font-weight: Used to make text bold or thin.

syntax: font-weight: bold | 100 to 900;

3. font-family: Used to change the font style of text.

syntax: font-family: font-name;

How to add Google Fonts:

-> Google Fonts provides free stylish fonts.

-> There are 2 ways to add google fonts:

Method-1: Using <link> Tag

Step-1: Go to Google Fonts and select a font. Example: Poppins

Step-2: Copy the <link> tag and paste inside <head>.

Step-3: Use the font-family in CSS.

Example: font-family: "Poppins", sans-serif;

Method-2: Using @import Statement

Step-1: Go to Google Fonts and select a font. Example: Poppins

Step-2: Copy import code from Google Fonts.

For Example: @import
url('https://fonts.googleapis.com/css2?family=Poppins:wght@100;400;700&display=swap');

Step-3: Use font-family.

Example: font-family: "Poppins", sans-serif;