An established traffic backbone for an elementary VSL task

Literature comparison and formed modeling backbone — source hierarchy, 22 October 2026

1. What a suitable backbone must provide

Can an established variable speed limit (VSL) model support the information, control and gradient questions with few traffic-model changes? Consider an ending lane E, its adjacent continuing lane A and farther lane B. Initial states can share the same E and combined A+B traffic at every road position while differing in A/B loading. We ask whether that difference changes merge service, useful common-speed advice and its sensitivity. A suitable backbone must represent the distinction, conserve traffic, respect receiving space and count every initial unit's time until exit. Simplicity concerns the traffic rules we must author and justify, not citation count.

2. What the closest published models offer

Aggregate VSL models support questions about traffic location or history; lane models additionally resolve A/B loading. The inspected starting points offer the following tradeoff.

Table 1. Published starting points and their fit to the question

Published model	What is already supplied	Direct finding for this review
Jin and Jin [1]	Spatial and link-average traffic; VSL entry control, capacity drop and upstream holding queues.	Simpler if the question concerns *where* traffic lies along the road. It changes the A/B information question.
Wei, Han and Wang [2]	Link traffic retaining entry/speed history, interacting speed cohorts and capacity drop.	A strong aggregate alternative, but no explicit A/B loading. Native advice acts on entering traffic.
Nagalur Subraveti et al. [3]	Successive lane-cell densities, lane-change incentives and a lane-drop case; Han congestion lineage [4].	Selected lane backbone. Adopt Han's VSL sending restriction [5] and explicitly replace movement realization.
Carey et al. [6]	Multilane cell transmission, mandatory movements and receiving-allocation alternatives.	Supports conservative service and forward fallback. More VSL/lane-end task closure would be needed as the main backbone.

Few-dependency construction. Use Subraveti's lane framework as the backbone and follow its adoption of Han's congestion approach, completing and adapting that formulation for the VSL task. Replace movement realization with one Carey-led adaptation; Wright supports its allocation rule. The thesis clarifies the backbone. Thus *one principal framework with inherited budgets and one adapted movement component* carries the traffic model. Our scenario and composition remain explicit. This concentrates independent additions within the inspected literature; global minimality is not proved. Jin–Jin is simpler if the information question changes to spatial traffic differences.

Source hierarchy and relationship key. Columns show architectural roles; colors credit rules and references, not ownership of symbols.

Principal framework	**Inherited budget lineage**	**Movement adaptation**
Subraveti article [3]	Han 2016 [4] (adopted in [3])	Carey et al. [6] (principal)
Subraveti thesis [7] (clarification)	Han 2017 [5] (VSL extension)	Wright et al. [8] (supporting)

Comparison only: Jin–Jin [1]; Wei et al. [2]. This study: scenario, composition and task (**D**).

B: source form retained/re-expressed; **A**: adapted/composed from the colored source; **D**: defined/derived here, including member choices (not a novelty claim); S: standard algebra, conservation or calculus.

3. The formed modeling backbone

3.1. Physical picture, task and root assumptions. The lane-density architecture (B) forms a *lane-resolved cell-transmission-type (CTM) model* with inherited Han budgets. Physical cells retain density and finite storage throughout the road; there is no separate link transmission model (LTM) link. E can change into A at upstream cell boundaries; traffic in the final E cell must merge at the exit. Unserved mass stays in its current cell, so congestion can extend upstream. The causal chain is:



Member choices (**D**): $N = 10$, $\Delta x = 0.1\,\mathrm{km}$ and $\Delta t = 1/600\,\mathrm{h}$ (6 s). At step k, density $\rho_{i\ell}^k$ and continuous stock $n_{i\ell}^k = \Delta x \rho_{i\ell}^k$ describe section i, lane $\ell \in \{E, A, B\}$. Initialize a finite cohort independently of constant common

advice $v \in [30, 60]$ km/h, with no later arrivals. Trips end when traffic leaves the modeled road through A or B. We assume no downstream congestion blocks the exit. Member assumptions (**D**): common lane flow–density parameters, fixed geometry, old traffic/space for every movement, equal positive priorities and no extra merging-headway multiplier. The step satisfies $u_0\Delta t, w\Delta t \le \Delta x$; u_0 is nominal free speed and w the backward-wave speed magnitude.

3.2. How much traffic can move or be received? Subraveti adopts Han for capacity drop [3]; we follow that inherited formulation (B) [4] with nominal/VSL caps (B) [5] to give D and R. Our completion (**D**) uses the full ceiling without the summary's additional density-order switch on sending. The exact assembled variant remains ours. FD identities are standard (S). The discharge ceiling $Q(x)$ equals nominal capacity C below critical density ρ_c, then falls linearly to $(1-\delta)C$ at jam density k_J:

$$C = \frac{u_0 w k_J}{u_0 + w}, \quad \rho_c = C/u_0, \quad Q(x) = \min\left\{C, C\left[1 - \delta\frac{x-\rho_c}{k_J-\rho_c}\right]\right\}, \tag{1}$$

$$D_{i\ell} = \min\{v\rho_{i\ell}, Q(\rho_{i-1,\ell})\}, \quad R(x,y) = \min\{Q(x), w(k_J-y), w(k_J-x)+w_d(x-y)\}. \tag{2}$$

Here x, y are the current upstream/downstream densities in the receiving lane. The three receiving bounds express discharge capacity, downstream space and Han's additional congestion-wave constraint. Its fixed recovery slope is $w_d = Q_J/(k_J - Q_J/u_0)$, $Q_J = (1-\delta)C$. Member parameters (**D**): $u_0 = 60$, $w = 20$ km/h, $k_J = 150$ veh/km/lane and $\delta = 0.1$; initial densities lie in $[0, k_J]$. Our lane-wise budget mapping (**A**) gives $d_{i\ell} = \Delta t D_{i\ell}$ and $r_{ij} = \Delta t R(\rho_{ij}, \rho_{i+1,j})$: all straight and diagonal arrivals to target j share that *one* r_{ij}. At the outlets use $r_{Nj} = \Delta t R(\rho_{Nj}, 0)$, $j = A, B$; upstream boundary densities are zero with no inflow. Advice caps sending; receiving changes through the evolving densities, not directly through v.

3.3. Why and where does early merging occur? Retained desires (B) [3] compare perceived densities K, with current/two-cell lookahead, weights 2:2:1 (B) [7]. For a nonempty origin and adjacent destination,

$$P_{i,\ell j} = \left[\frac{I_{i,\ell j}K_{i\ell} - K_{ij}}{K_{i\ell} + K_{ij}}\right]_+, \qquad I = 1 + I^r + I^{kr} + I^{coop}, \qquad [x]_+ = \max(x, 0). \tag{3}$$

Less crowded destinations attract traffic. Within the last $D_r = 0.75$ km, E-to-A route bias (B) grows as $I^r = (1 - g_i/D_r)^3$, where $g_i = (N-i)\Delta x$; it is zero farther upstream. This adds urgency, not a fixed merge fraction or a hard start line: density incentives can cause earlier E-to-A movement. Member conventions (**D**) select mode/direction branches for keep-right/cooperation; free A can be encouraged toward B to make room. Missing downstream E cells are omitted and weights renormalized; A/B lookahead extends with zero outlet density. Empty origins make no requests. E, A and B name current lanes, so early-merged traffic becomes A.

3.4. Which attempts succeed, and what happens at the choke? Movement adaptation (**A**) [6] replaces native same-cell lateral/adjusted-forward coupling. Our composition (**D**) separates desire from service. Requests use existing forward or adjacent cells/outlets. At one boundary, temporarily omit i. Normalize lateral desires (**D**), leave the rest for straight travel, and form requests m from each donor's one sending amount:

$$b_{\ell j} = \frac{P_{\ell j}}{\max(1, \sum_{h\neq\ell} P_{\ell h})} \ (j \neq \ell), \quad b_{\ell\ell} = 1 - \sum_{j\neq\ell} b_{\ell j}, \quad m_{\ell j} = d_\ell b_{\ell j}. \tag{4}$$

R3/A3 sharing and forward fallback (**A**) [6] underpin the replacement. We extend its two-stream sharing to all target requests; Wright's priority formulation [8] provides supporting justification, without importing its general junction model. Each target serves requests at a common capped level:

$$z_{\ell j} = \min(m_{\ell j}, \lambda_j), \qquad \sum_\ell z_{\ell j} = \min\left(r_j, \sum_\ell m_{\ell j}\right). \tag{5}$$

Requests below the shared level are fully served; unused entitlement returns to the others. Residual donor traffic gets one straight fallback y_ℓ (**A**), the minimum of its unused sending and its own lane's unused receiving amount. Thus $f_{\ell j} = z_{\ell j} + \mathbf{1}_{\{j=\ell\}} y_\ell$ (**D**) is realized movement. An unsuccessful E-to-A attempt can therefore continue in E if space remains. Final-E rule (**D**): $b_{EA} = 1$, $y_E = 0$; E must use A's outlet or wait. It competes with A and any B-to-A request for the same outlet budget. Equal priorities are not a constant realized merge proportion; demand and receiving state determine the flow. E's use leaves less service for the other requests, whose retained stock can restrict later receiving. There is no separate speed-mismatch or acceleration-recovery meter. Our normalization and three-lane sequencing remain behavioral adaptations beyond the lane-end geometry.

Diagonal transport (**A**) advances one section when changing lanes. Apply old-state flows simultaneously using standard conservation (S):

$$n_{i\ell}^{k+1} = n_{i\ell}^k - \sum_j f_{i,\ell j}^k + \sum_h f_{i-1,h\ell}^k. \tag{6}$$

Set $f_0 = 0$; f_N counts traffic leaving the modeled road. Matched additions/subtractions conserve mass, while donor/receiver limits protect stock and storage.

3.5. Complete objective, information comparison and sensitivity. Minimize total system time J, counting all initial mass until exit. Once remaining mass is below $\Delta x \rho_c$, all requests receive service and a unit in section i has remaining mean time $(N-i+1)\Delta x/v$. Choose a fixed index K_* inside that regime. With $h_{i\ell} = N - i + 1$ and $\mathbf{1}^\top n^k$ the total unfinished mass, the exact prefix-plus-residual objective is

$$J(v) = \Delta t \sum_{k<K_*} \mathbf{1}^\top n^k + \frac{\Delta x}{v} h^\top n^{K_*}. \tag{7}$$

Population-time accounting is standard (S); the exact residual is derived here (**D**). Write the complete update as $n^{k+1} = F(n^k, v)$. Between branch switches, $s^0 = 0$, $s^{k+1} = F_n^{[k]} s^k + F_v^{[k]}$ (S) propagates $s^k = \partial n^k / \partial v$ through budgets, desires, allocation and stock. Then

$$J'(v) = \Delta t \sum_{k<K_*} \mathbf{1}^\top s^k + \frac{\Delta x}{v} h^\top s^{K_*} - \frac{\Delta x}{v^2} h^\top n^{K_*}. \tag{8}$$

This model's full derivative (**D**) uses standard chain rule (S). Terms measure earlier traffic changes, residual-stock changes and direct residual travel time. Hold a valid K_* fixed locally; at native mode or active-constraint switches a two-sided derivative can fail.

Our information/control comparison (**D**) uses this same model and objective: one observer sees E and A+B at each section, another sees each lane. Admit model-aware inference from allowed histories; choose advice before the subsequent revealing discharge. A compact observer adds the final-A density, sufficient on the existing two-state diagnostic. Separately, compare gradients with bounded scalar search using the same information, and retain maximum advice as a reference. These definitions isolate what information is needed from how the advice is optimized. The companion formulation specifies all bias branches and finite-domain conventions.

References

[1] H.-Y. Jin and W.-L. Jin, "Control of a lane-drop bottleneck through variable speed limits," arXiv:1310.2658, 2013 (archived manuscript dated Oct. 29, 2018). [Online]. Available: `https://arxiv.org/abs/1310.2658`.

[2] L. Wei, Y. Han, and M. Wang, "A first-order link-based flow model with variable speed limits and capacity drops for freeway networks," *Comput.-Aided Civ. Infrastruct. Eng.*, vol. 40, no. 21, pp. 3200–3217, 2025, doi: 10.1111/mice.13492.

[3] H. H. S. Nagalur Subraveti, V. L. Knoop, and B. van Arem, "First order multi-lane traffic flow model—an incentive based macroscopic model to represent lane change dynamics," *Transportmetrica B, Transp. Dyn.*, vol. 7, no. 1, pp. 1758–1779, 2019 (archived article header: 2020), doi: 10.1080/21680566.2019.1700846.

[4] Y. Han, Y. Yuan, A. Hegyi, and S. P. Hoogendoorn, "New extended discrete first-order model to reproduce propagation of jam waves," *Transp. Res. Rec.*, vol. 2560, pp. 108–118, 2016, doi: 10.3141/2560-12.

[5] Y. Han, A. Hegyi, Y. Yuan, S. Hoogendoorn, M. Papageorgiou, and C. Roncoli, "Resolving freeway jam waves by discrete first-order model-based predictive control of variable speed limits," *Transp. Res. C, Emerg. Technol.*, vol. 77, pp. 405–420, 2017, doi: 10.1016/j.trc.2017.02.009.

[6] M. Carey, C. Balijepalli, and D. Watling, "Extending the cell transmission model to multiple lanes and lane-changing," *Netw. Spat. Econ.*, vol. 15, pp. 507–535, 2015, doi: 10.1007/s11067-013-9193-7.

[7] H. H. S. Nagalur Subraveti, *Lane-specific Traffic Flow Control*, Ph.D. dissertation, Delft Univ. Technol., Delft, The Netherlands, 2021, ch. 4, doi: 10.4233/uuid:e405a549-b1fe-4fa1-8090-4429612359d9.

[8] M. A. Wright, G. Gomes, R. Horowitz, and A. A. Kurzhanskiy, "On node models for high-dimensional road networks," *Transp. Res. B, Methodol.*, vol. 105, pp. 212–234, 2017, doi: 10.1016/j.trb.2017.09.001.