

QUIZ-01

1. A(n) _____ is a word that is predefined by the programming language for a special purpose and can only be used in a specified manner for its intended purpose.
 - 1) variable
 - 2) identifier
 - 3) reserved word
 - 4) data type
2. Main memories combine 1 or more bytes into a single unit, referred to as a(n) _____.
 - 1) bit
 - 2) character
 - 3) opcode
 - 4) word
3. _____ identifiers are words that are predefined in C.
 - 1) Standard
 - 2) Programmer-created
 - 3) Reserved
 - 4) Primitive
4. The collections of patterns consisting of 0s and 1s used to represent letters, single digits, and other single characters are called _____.
 - 1) bytes
 - 2) character codes
 - 3) words
 - 4) opcodes
5. The names of functions, as well as all of the words that are permitted in a program, that have special meaning to the compiler are collectively referred to as _____.
 - 1) variables
 - 2) identifiers
 - 3) reserved words
 - 4) keywords
6. Messages are known as _____ in C.
 - 1) characters
 - 2) text
 - 3) banners
 - 4) strings
7. A _____ is placed at the top of a C program using the `#include` command.
 - 1) header file
 - 2) `main()` function
 - 3) return statement
 - 4) data type
8. A repetition structure is also known as a(n) _____ structure.
 - 1) sequence
 - 2) selection
 - 3) looping
 - 4) invocation
9. An expression containing only floating-point values as operands is called a floating-point expression, and the result of such an expression is a(n) _____ value.
 - 1) single-precision
 - 2) double-precision
 - 3) integer
 - 4) long integer
10. Built-in types are also known as _____.
 - 1) data types
 - 2) primitive types
 - 3) literals
 - 4) basic

11. A(n) _____ is any combination of operators and operands that can be evaluated to yield a value.
- 1) **expression**
 - 2) statement
 - 3) operation
 - 4) argument
12. The grouping of 8 bits to form a larger unit is an almost universal computer standard and is referred to as a _____.
- 1) **byte**
 - 2) character
 - 3) word
 - 4) opcode
13. A(n) _____ is an acceptable value for a data type.
- 1) identifier
 - 2) variable
 - 3) escape sequence
 - 4) **literal**
14. A _____ value is sometimes referred to as a single-precision number.
- 1) **float**
 - 2) double
 - 3) int
 - 4) short int
15. The program that translates a high-level source program as a complete unit before any individual statement is executed is called a(n) _____.
- 1) interpreter
 - 2) assembler
 - 3) **compiler**
 - 4) linker
16. _____ is the order in which operators of the same precedence are evaluated.
- 1) **Associativity**
 - 2) Priority
 - 3) Syntax
 - 4) Precision
17. A(n) _____ value can be the number zero or any positive or negative number that contains a decimal point.
- 1) integer
 - 2) **floating-point**
 - 3) boolean
 - 4) character
18. Translator programs that translate assembly language programs into machine language programs are known as _____.
- 1) **assemblers**
 - 2) linkers
 - 3) compilers
 - 4) interpreters
19. When writing a program, a(n) _____ structure defines the order in which instructions are executed by the program.
- 1) **sequence**
 - 2) selection
 - 3) iteration
 - 4) invocation
20. A(n) _____ is defined as a set of values and a set of operations that can be applied to these values.
- 1) variable
 - 2) identifier
 - 3) **data type**
 - 4) literal

QUIZ-02

Multiple Choice

Identify the choice that best completes the statement or answers the question.

1. ____ statements are also called equivalence statements.
 - 1) Assignment
 - 2) Prompt
 - 3) #include
 - 4) #define
2. Programs that detect and respond effectively to unexpected user input are formally referred to as ____ programs.
 - 1) standard
 - 2) robust
 - 3) cost-effective
 - 4) abstract
3. If you are using a Unix or Linux operating system, you must include the ____ option when compiling a C program that uses the mathematical functions like log and sqrt.
 - 1) -lm
 - 2) -l math.h
 - 3) -math
 - 4) -lib = math
4. The ____ sign is a signal to a C preprocessor.
 - 1) !
 - 2) &
 - 3) ;
 - 4) #
5. To access the mathematical functions such as log and sqrt, you must include the following preprocessor statement in your program: ____.
 - 1) #define <mathematical.h>
 - 2) #include <mathematical.h>
 - 3) #define <math.h>
 - 4) #include <math.h>
6. The term ____ refers to any quantity that is valid on the left side of an assignment operator.
 - 1) leftv
 - 2) lval
 - 3) variable
 - 4) lvalue
7. The C function ____ yields the result of a value raised to the power of another value.
 - 1) pow
 - 2) exp
 - 3) abs
 - 4) sqrt
8. On most computer systems characters read by the keyboard are stored in a temporary holding area called a ____ immediately after they are pressed.
 - 1) register
 - 2) buffer
 - 3) stack
 - 4) RAM
9. The statement ____ shows an implicit conversion.
 - 1) int total = (int) sum;
 - 2) double avg = 0.0;
 - 3) float price = 9.90f;
 - 4) int answer = 2.745;
10. Which of the following statements about rvalues and lvalues is NOT true?
 - 1) Any expression that yields a value can be an rvalue.
 - 2) A variable declared for an array cannot be an rvalue, but individual array variables can be.
 - 3) A variable declared for an array can be an lvalue.

- 4) Individual numbers can only be an rvalue.
11. The expression `sum = sum + 10` can be written as ____.
- 1) `sum += 10`
 - 2) `sum += 10`
 - 3) `sum = sum ++ 10`
 - 4) `sum ++ 10`
12. ____ is a valid statement in C.
- 1) `a = 10 = c = 25;`
 - 2) `a = b = c = 25;`
 - 3) `2 = b;`
 - 4) `a - 1 = c;`
13. The operator used to force the conversion of a value to another type is the ____ operator.
- 1) conversion
 - 2) cast
 - 3) assignment
 - 4) increment
14. The ____ function requires a control string as the first argument inside the function name parentheses.
- 1) `sqrt()`
 - 2) `pow()`
 - 3) `scanf()`
 - 4) `log()`
15. Literal values that appear many times in the same program are referred to by programmers as ____ numbers.
- 1) symbolic
 - 2) magic
 - 3) constant
 - 4) literal
16. The increment operator is ____.
- 1) `+=`
 - 2) `=+`
 - 3) `++`
 - 4) `--`
17. In C, the ____ symbol is called the assignment operator.
- 1) `=`
 - 2) `++`
 - 3) `--`
 - 4) `()`
18. The cast operator has the syntax ____.
- 1) `(dataType expression)`
 - 2) `(expression dataType)`
 - 3) `(dataType) expression`
 - 4) `expression (dataType)`
19. The conversion control sequence ____ would cause an integer number to both display its sign and be left-justified in a field width of 10 spaces.
- 1) `%-+10d`
 - 2) `%-10d`
 - 3) `%+10d`
 - 4) `%*10d`
20. A previously stored number, if it has not been initialized to a specific and known value, is frequently referred to as a ____.
- 1) garbage value
 - 2) literal
 - 3) bogus value
 - 4) buffer
21. A(n) ____ is a message that tells the person at the screen what should be typed.
- 1) prompt
 - 2) input statement
 - 3) `scanf`
 - 4) `printf`
22. Format modifiers, if used, must always be placed immediately after the ____ symbol.
- 1) `!`
 - 2) `=`
 - 3) `%`
 - 4) `.`
23. When the `++` operator appears before a variable, it is called a ____ increment operator.
- 1) basic
 - 2) standard
 - 3) postfix
 - 4) prefix
24. The expression `price *= rate + 1` is equivalent to the expression ____.
- 1) `price = price * (rate + 1)`
 - 3) `price = (price * rate) + 1`

2) `price = price * rate + 1` 4) `price = price ^ (rate + 1)`

25. Formatted floating-point numbers require _____field width specifier(s).

- | | |
|--------|----------|
| 1) one | 3) three |
| 2) two | 4) four |

QUIZ-03

Multiple Choice

Identify the letter of the choice that best completes the statement or answers the question.

1. The ____ operator is used to change an expression to its opposite state.
1) || 3) !
2) && 4) %%
2. Which of the following operators has the lowest precedence?
1) ! 3) &&
2) * 4) ||
3. The logical OR operator is ____.
1) || 3) !
2) && 4) %%
4. A(n) ____ loop is a condition-controlled loop that terminates when a value within a valid range is entered.
1) input-validation 3) condition-controlled
2) sentinel-controlled 4) counter-controlled
5. It is a good practice to terminate the last case in a switch statement with a ____.
1) switch 3) default
2) break 4) case
6. The ____ statement literally loops back on itself to recheck the expression until it evaluates to 0 (becomes false).
1) for 3) do-while
2) switch 4) while
7. Omitting the ____ expression in a for statement results in an infinite loop.
1) initializing 3) tested
2) altering 4) break

8. What will the following program print on screen?

```
int age = 0;
if (age = 40)
    printf("Happy Birthday!");
else
    printf("Sorry");
```

- 1) Happy Birthday!
- 2) Sorry
- 3) Runtime error.
- 4) Nothing; the program will not compile.

9. In Unix operating systems, the EOF mark is generated whenever the ____keys are pressed simultaneously.

- 1) Ctrl and D
- 2) Ctrl and E
- 3) Ctrl and F
- 4) Ctrl and Z

10. In computer programming, data values used to signal either the start or end of a data series are called ____.

- 1) input values
- 2) limits
- 3) sentinels
- 4) iterators

11. In IBM-compatible computers, the EOF mark is generated whenever the ____keys are pressed simultaneously.

- 1) Ctrl and D
- 2) Ctrl and E
- 3) Ctrl and F
- 4) Ctrl and Z

12. The use of ____in a C program will result in a compiler error.

- 1) if (age == 40)
- 2) if (40 == age)
- 3) if (age = 40)
- 4) if (40 = age)

13. The logical AND operator is ____.

- 1) ||
- 2) &&
- 3) !
- 4) %%

14. In a switch statement, the word ____ is optional and operates the same as the last else in an if-else chain.

- 1) if
- 2) break
- 3) case
- 4) default

15. A ____statement is a specialized selection statement that can be used in place of an if-else chain where exact equality to one or more integer constants is required.

- 1) case
- 2) break
- 3) switch
- 4) nested if

16. Which of the following operators has right to left associativity?

- 1) !
- 2) *
- 3) &&
- 4) ||

17. What will the following program print on screen?

```
int tenure = -5;
if (tenure + 5)
    printf("Congratulations!");
else
    printf("Sorry");
```

- | | |
|---------------------|---|
| 1) Congratulations! | 3) Runtime error. |
| 2) Sorry | 4) Nothing; the program will not compile. |

18. _____ is an accumulating statement.

- | | |
|------------------|------------------|
| 1) total += num; | 3) ++total; |
| 2) total++; | 4) total *= num; |

19. The second loop of a nested loop is called the _____ loop.

- | | |
|----------|----------------|
| 1) inner | 3) slave |
| 2) outer | 4) conditioned |

20. A(n) _____ is a condition-controlled loop where one specific value is required to terminate the loop.

- | | |
|------------------------|-------------------------|
| 1) input-validation | 3) condition-controlled |
| 2) sentinel-controlled | 4) counter-controlled |

QUIZ-04

Multiple Choice

Identify the choice that best completes the statement or answers the question.

1. The purpose of a _____ is to operate on the passed data and return, at most, one value directly back to the calling function.
 - 1) function declarator
 - 2) prototype
 - 3) **function body**
 - 4) function header
2. Scaling a random number as an integer value between 1 and N is accomplished using the expression _____.
 - 1) $1 + (\text{int})\text{rand}() / N$
 - 2) **$1 + (\text{int})\text{rand}() \% N$**
 - 3) $(\text{int})\text{rand}() / N$
 - 4) $(\text{int})\text{rand}() \% N$
3. _____ is a prototype of a function that returns no value.
 - 1) **`void funcA();`**
 - 2) `funcA();`
 - 3) `int funcA();`
 - 4) `null funcA();`
4. The function _____ converts an ASCII string to an integer.
 - 1) `string itoa(int)`
 - 2) `double atof(string)`
 - 3) **`int atoi(string)`**
 - 4) `int toupper(int)`
5. The portion of the function header that contains the function name and parameters is known as a _____.
 - 1) function body
 - 2) prototype
 - 3) **function declarator**
 - 4) stub
6. A _____ is the beginning of a final function that is used as a placeholder for the final function until the function is completed.
 - 1) function header
 - 2) function declarator
 - 3) prototype
 - 4) **stub**

7. ____ is an example of a calling statement.
- 1) `float roi(int, double);`
 - 2) `printf("%f", roi(3, amt));`
 - 3) `float roi(int yrs, double rate);`
 - 4) `float roi(int yrs, double rate)`
8. ____ reads the computer's internal clock time, in seconds.
- 1) `stime()`
 - 2) `time(SECONDS)`
 - 3) `time()`
 - 4) `time(NULL)`
9. ____ is an example of a function prototype.
- 1) `float roi(int, double);`
 - 2) `printf("%f", roi(3, amt));`
 - 3) `roi(3, amt);`
 - 4) `float roi(int yrs, double rate)`
10. A function that is called or summoned into action by its reference in another function is a ____.
- 1) function prototype
 - 2) **called function**
 - 3) calling function
 - 4) function declarator
11. The function ____ returns a non-0 number if the argument is a letter or a digit; otherwise it returns a 0.
- 1) `int isalnum(int)`
 - 2) `int isalpha(int)`
 - 3) `int isdigit(int)`
 - 4) `int isxdigit(int)`
12. To return a value, a function must use a(n) ____ statement.
- 1) `exit`
 - 2) `throw`
 - 3) `break`
 - 4) **`return`**
13. When a function simply receives copies of the values of the arguments and must determine where to store these values before it does anything else, this is known as a ____.
- 1) **pass by value**
 - 2) pass by reference
 - 3) stub
 - 4) function declarator
14. ____ is an example of a function header line.
- 1) `float roi(int, double);`
 - 2) `printf("%f", roi(3, amt));`
 - 3) **`float roi(int yrs, double rate);`**
 - 4) `float roi(int yrs, double rate)`
15. The method for adjusting the random numbers produced by a random-number generator to reside within a specified range is called ____.
- 1) **scaling**
 - 2) stubbing
 - 3) prototyping
 - 4) converting
16. The ____ function can be used to generate a random number in C.
- 1) **`rand()`**
 - 2) `srand()`
 - 3) `random()`
 - 4) `rnd()`

17. All C compilers provide ____function(s) for creating random numbers, defined in the `stdlib.h` header file.
- 1) one
 - 2) two
 - 3) three
 - 4) four
18. A function that calls another function is referred to as the ____.
- 1) function prototype
 - 2) called function
 - 3) calling function
 - 4) function declarator
19. The purpose of a ____is to identify the data type of the value returned by the function, if any, provide the function with a name, and specify the number, order, and type of values expected by the function.
- 1) function declarator
 - 2) prototype
 - 3) function body
 - 4) function header
20. ____is the correct way to include a header file in your program.
- 1) `#include <header-file-name>`
 - 2) `#include <header-file-name>;`
 - 3) `#include header-file-name`
 - 4) `#include header-file-name;`
21. The items enclosed within the parentheses in a function call statement are called ____ of the function.
- 1) parameters
 - 2) formal parameters
 - 3) arguments
 - 4) formal arguments
22. The function ____returns the absolute value of its double-precision argument.
- 1) `double ceil(double)`
 - 2) `double fmod(double)`
 - 3) `double fabs(double)`
 - 4) `double abs(double)`
23. The argument names in the header line of a function are known as ____.
- 1) arguments
 - 2) parameters
 - 3) actual arguments
 - 4) actual parameters
24. The minimum requirement of a ____is that it compile and link with its calling module.
- 1) function body
 - 2) function prototype
 - 3) stub function
 - 4) function declarator
25. The function ____returns the common logarithm of its argument.
- 1) `double exp(double)`
 - 2) `double log(double)`
 - 3) `double log10(double)`
 - 4) `double fmod(double)`

QUIZ-05

Multiple Choice

Identify the choice that best completes the statement or answers the question.

1. In ____ initialization, initialization occurs each time the declaration statement is encountered.
 - 1) dynamic
 - 2) static
 - 3) compile-time
 - 4) **run-time**
2. Coding a function prototype as ____ makes sense when the function is used by a number of other functions in a source code file.
 - 1) private
 - 2) **global**
 - 3) local
 - 4) void
3. If numAddr is a pointer, ____ means the variable whose address is stored in numAddr.
 - 1) ***numAddr**
 - 2) numAddr*
 - 3) &numAddr
 - 4) *&numAddr
4. To use a stored address, C provides us with an indirection operator, ____.
 - 1) %
 - 2) ^
 - 3) &
 - 4) *****
5. A local variable that is declared as ____ causes the program to keep the variable and its latest value even when the function that declared it is through executing.
 - 1) auto
 - 2) **static**
 - 3) extern
 - 4) register
6. Variables created inside a function are ____ variables.
 - 1) recursive
 - 2) private
 - 3) **local**
 - 4) global
7. ____ is a high-speed storage area physically located in the computer's processing unit.
 - 1) A reserved variable
 - 2) RAM
 - 3) **A register**
 - 4) A stack
8. The variable secnum is ____.

```
int main()  
{  
    int secnum;  
    . . .  
}
```

 - 1) **local to main()**
 - 3) local to the program

- 2) global to main ()
- 4) global to the program
9. A declaration statement that specifically contains the word `__` is different from every other declaration statement in that it does not cause the creation of a new variable by reserving new storage for the variable.
 - 1) auto
 - 2) static
 - 3) **extern**
 - 4) register
10. A variable that can store an address is known as a(n) `__` variable.
 - 1) register
 - 2) **pointer**
 - 3) static
 - 4) extern
11. The `__` of a variable defines the location within a program where that variable can be used.
 - 1) storage class
 - 2) time dimension
 - 3) **scope**
 - 4) data type
12. Where and how long a variable's storage locations are kept before they are released can be determined by the `__` of the variable.
 - 1) **storage class**
 - 2) time-dimension
 - 3) scope
 - 4) data type
13. `__` can only be members of the auto, static, or register storage classes.
 - 1) Constants
 - 2) int variables
 - 3) **Local variables**
 - 4) Global variables
14. The declaration statement `__` declares milesAddr to be a pointer variable that can store the address of (that is, will point to) an integer variable.
 - 1) int milesAddr&;
 - 2) int milesAddr*;
 - 3) **int *milesAddr;**
 - 4) int &milesAddr;
15. When a function invokes itself, the process is called `__` recursion.
 - 1) **direct**
 - 2) mutual
 - 3) self-referential
 - 4) indirect
16. The purpose of the `__` storage class is to extend the scope of a global variable declared in one source code file into another source code file.
 - 1) auto
 - 2) static
 - 3) **extern**
 - 4) register
17. A `__` variable is one whose storage has been created for it by a declaration statement located outside any function.
 - 1) local
 - 2) **global**
 - 3) module
 - 4) function
18. `__` variables have the same time duration as automatic variables.
 - 1) Static
 - 2) **Register**
 - 3) Extern
 - 4) Global
19. The four available storage classes are called auto, static, extern, and `__`.
 - 1) stack
 - 2) intern
 - 3) void
 - 4) **register**

20. When the function returns control to its calling function, its ____ variables “die”.
- 1) local static
 - 2) extern
 - 3) local extern
 - 4) local auto
21. ____ variables allow the programmer to “jump around” the normal safeguards provided by functions.
- 1) Global
 - 2) Local
 - 3) Static
 - 4) void
22. Functions that call themselves are referred to as ____ functions.
- 1) nested
 - 2) recursive
 - 3) loop-back
 - 4) rolling
23. A function can invoke a second function, which in turn invokes the first function; this type of recursion is referred to as ____ recursion.
- 1) direct
 - 2) mutual
 - 3) self-referential
 - 4) tail
24. A variable with a ____ scope is simply one that has had storage locations set aside for it by a declaration statement made within a ____ body.
- 1) function
 - 2) module
 - 3) local
 - 4) global
25. ____ is defined as the section of the program where the variable is valid or “known.”
- 1) Scope
 - 2) Resolution
 - 3) Domain
 - 4) Reach

QUIZ-06

Multiple Choice

Identify the choice that best completes the statement or answers the question.

1. _____ refers to the first grade stored in the grades array.
1) `grades[0]` 3) `grades(0)`
2) `grades[1]` 4) `grades{1}`
2. In C, the array name and index of the desired element are combined by listing the index in _____ after the array name.
1) parentheses 3) curly braces
2) square braces 4) dashes
3. The individual elements of all global and `static` arrays are, by default, set to _____ at compilation time.
1) NULL 3) `0`
2) -1 4) 1
4. The _____ character is automatically appended to all strings by the C compiler.
1) `'\NULL'` 3) `'\n'`
2) `'\1'` 4) `'\0'`
5. A(n) _____ is a data type with two main characteristics: (1) its values can be decomposed into individual data elements, and (2) it provides an access scheme for locating individual data elements.
1) data structure 3) array
2) scalar data type 4) atomic data type
6. The initialization of a two-dimensional array is done in _____ order.
1) ascending 3) row
2) descending 4) column
7. _____ declares an array of three rows and four columns.
1) `int val[3,4];` 3) `int val[3][4];`
2) `int val[4,3];` 4) `int val[4][3];`
8. In a one-dimensional array in C, the first element has an index of _____.
1) NULL 3) `0`
2) -1 4) 1
9. All _____ arrays are created and destroyed each time the function they are local to is called and completes its execution.
1) global 3) `auto`

- 2) static 4) extern
10. char codes[] = "sample"; sets aside _____elements in the codes array.
1) 5 3) 7
2) 6 4) 8
11. A(n) _____, is used to store and process a set of values, all of the same data type, that forms a logical group.
1) data structure 3) array
2) scalar variable 4) atomic variable
12. A two-dimensional array is sometimes referred to as a _____.
1) list 3) queue
2) vector 4) table
13. Any individual element in an array can be accessed by giving the name of the array and the element's position; this position is called the element's _____value.
1) component 3) index
2) variable 4) element
14. A(n) _____variable, is a variable whose value cannot be further subdivided or separated into a built-in data type.
1) data structure 3) array
2) scalar 4) class
15. A _____is a list of values of the same data type that is stored using a single group name.
1) one-dimensional array 3) three-dimensional array
2) two-dimensional array 4) matrix
16. The term _____uniquely identifies the element in row 1, column 3.
1) val[3][1] 3) val[3,1]
2) val[1][3] 4) val[1,3]
17. _____shows a correct array initialization statement.
1) char codes[6] = ['s', 'a', 'm', 'p', 'l', 'e'];
2) char codes[] = ('s', 'a', 'm', 'p', 'l', 'e');
3) char codes[] = "sample";
4) char codes[*] = {'s', 'a', 'm', 'p', 'l', 'e'};
18. In a function prototype that has a two-dimensional argument, the _____size is optional.
1) column 3) array
2) row 4) subscript
19. A _____loop is very convenient for cycling through array elements.
1) while 3) switch
2) do-while 4) for
20. _____is a correct statement.
1) int grades[5] = {98, 87, 92, 79, 85};
2) int grades[5] = 98, 87, 92, 79, 85;
3) int grades[5] = (98, 87, 92, 79, 85);
4) int grades[5] = [98, 87, 92, 79, 85];

21. For one-dimensional arrays, the offset to the element with index i is calculated as ____.
- 1) Offset = i * the size of the array
 - 2) Offset = i * the size of the subscript
 - 3) Offset = i * the size of a component + 1
 - 4) Offset = i * the size of an individual element
22. A ____-dimensional array can be viewed as a book of data tables.
- 1) one
 - 2) two
 - 3) three
 - 4) four
23. Any expression that evaluates a(n) ____ may be used as a subscript.
- 1) character
 - 2) double
 - 3) boolean
 - 4) integer
24. ____ shows a correct array initialization statement.
- 1) `char codes[4] = {'s', 'a', 'm', 'p', 'l', 'e'};`
 - 2) `char codes[] = {'s', 'a', 'm', 'p', 'l', 'e'};`
 - 3) `char codes = {'s', 'a', 'm', 'p', 'l', 'e'};`
 - 4) `char codes[*] = {'s', 'a', 'm', 'p', 'l', 'e'};`
25. Each item in an array is called a(n) ____ of the array.
- 1) subscript
 - 2) variable
 - 3) index
 - 4) element

QUIZ-07

Multiple Choice

Identify the letter of the choice that best completes the statement or answers the question.

1. The maximum allowable filename in the DOS operating system is ____.

- 1) 8 characters plus an optional period and 3-character extension
- 2) 14 characters
- 3) 155 characters
- 4) 255 characters

2. Line ____ in the following section of code checks for the end-of-string character.

```
1 void strcpy (char string1[], char string2[])
2 {
3     int i = 0;
4
5     while (string2[i] != '\0')
6     {
7         string1[i] = string2[i];
8         i++;
9     }
10    string1[i] = '\0';
11 }
```

- 1) 3
- 2) 5
- 3) 7
- 4) 10

3. ____ causes the same display as the statement `printf("Hello World!");`.

- 1) `fprintf(stdout, "Hello World!");`
- 2) `fprintf(stdin, "Hello World!");`
- 3) `fprintf(stderr, "Hello World!");`
- 4) `fprintf(NULL, "Hello World!");`

4. To write to a binary file you use the ____ function.

- 1) `fput()`
- 2) `fputb()`
- 3) `fwrite()`
- 4) `write()`

5. The actual declaration of the `FILE` structure is contained in the ____ standard header file.

- 1) `stdio.h`
- 2) `stdlib.h`
- 3) `file.h`
- 4) `stream.h`

6. A ____ is a one-way transmission path that is used to connect a file stored on a physical device, such as a disk or CD-ROM, to a program.
- 1) data file
 - 2) text file
 - 3) binary file
 - 4) **file stream**
7. The statement ____ displays the message Have a Happy Day, right-justified, in a field of 25 characters.
- 1) `printf("%s25", "Have a Happy Day");`
 - 2) `printf("%s-25", "Have a Happy Day");`
 - 3) **`printf("%25s", "Have a Happy Day");`**
 - 4) `printf("%-25s", "Have a Happy Day");`
8. The array `char message[81];` can be used to store a string of up to ____ characters.
- 1) 79
 - 2) **80**
 - 3) 81
 - 4) 82
9. The string "Good Morning!" is stored in memory using a character array of size ____.
- 1) 13
 - 2) **14**
 - 3) 15
 - 4) 16
10. Programs that use the `gets()` routine must include the ____ header file.
- 1) **`stdio.h`**
 - 2) `stdlib.h`
 - 3) `string.h`
 - 4) `ctype.h`
11. Typically, the ____ function is used to "assemble" a string from smaller pieces until a complete line of characters is ready to be written, either to the standard output device or to a file.
- 1) `strcpy()`
 - 2) `strcat()`
 - 3) `sscanf()`
 - 4) **`sprintf()`**
12. Programs that use the `atoi()` routine must include the ____ header file.
- 1) `stdio.h`
 - 2) **`stdlib.h`**
 - 3) `string.h`
 - 4) `ctype.h`
13. The value assigned to the NULL constant is ____.
- 1) `'\n'`
 - 2) **`'\0'`**
 - 3) `'\NULL'`
 - 4) `"NULL"`
14. Data that is stored together under a common name on a storage medium other than the computer's main memory is called a ____.
- 1) database
 - 2) **data file**
 - 3) text file
 - 4) binary file
15. Notice that each file stream name, when it is declared, is preceded by a(n) ____.
- 1) pipe
 - 2) underscore
 - 3) ampersand
 - 4) **asterisk**
16. ____ reads values for the listed arguments from the file, according to the format.
- 1) `fgetc()`
 - 2) `fgets()`
 - 3) `fprintf()`
 - 4) **`fscanf()`**

17. When using `#include`, the characters _____, tell the compiler to start looking in the default directory where the program file is located.

- 1) `""`
- 2) `<>`
- 3) `//`
- 4) `\\`

18. _____ files store each individual character, such as a letter, digit, dollar sign, decimal point, and so on, using an individual character code.

- 1) Data
- 2) `Text`
- 3) Binary
- 4) ASCII

19. A file stream is closed using the _____ function.

- 1) `exit()`
- 2) `osclose()`
- 3) `fclose()`
- 4) `close()`

20. `fputc()` is the general form of _____.

- 1) `fput()`
- 2) `putc()`
- 3) `putchar()`
- 4) `fputchar()`

QUIZ-08

Multiple Choice

Identify the choice that best completes the statement or answers the question.

- The expression ____ adds 3 to “the variable pointed to by gPtr.”
 - * (gPtr + 3)
 - *gPtr + 3
 - gPtr + 3
 - &gPtr + 3
- The ____ in the expression * (gPtr + 1) is an offset.
 - *
 - gPtr
 - +
 - 1
- Assuming grade is an array of ten integers, the statement ____ is invalid.
 - grade = &grade[2];
 - *grade = *(grade + 2);
 - *grade = *grade + 2;
 - *grade = *(&grade[2]) + 2;
- The indirection operator in C is ____.
 - &
 - *
 - >
 - .
- After creating two variables as follows:
char message1[81] = "this is a string";
char *message2 = "this is a string";
The statement ____ is not valid in C.
 - message1 = "A new message";
 - message2 = "A new message";
 - message2 = message1;
 - message2[0] = 'T';
- The header line ____ declares calc to be a pointer to a function that returns an integer.
 - int *calc()
 - int (*calc) ()
 - int &calc()
 - int calc(*)
- A suitable equivalent to the function header calc(int pt[2][3]) is ____.
 - calc(int *(*pt))
 - calc(int (*pt)[2])
 - calc(int (*pt)[])
 - calc(int (**pt)[3])
- When working with pointers, the ____ tells the number of variables that are to be skipped over.
 - indirection operator
 - address operator
 - offset
 - address

9. You can replace lines 5 and 6 in the following function with ____.

```
1 /* copy string2 to string1 */
2 void strcpy(char string1[], char string2[])
3 {
4     int i = 0;
5     while (string1[i] = string2[i])
6         i++;
7 }
1) while (*string1 = *string2) ;
2) while (*string1 = string2) ;
3) while (*string1++ = *string2++);
4) while (++string1 = ++string2) ;
```

10. When an array is created, the compiler automatically creates an internal ____ for it and stores the base address of the array in it.

- 1) pointer constant
- 2) pointer
- 3) symbolic constant
- 4) location

11. Consider the declarations

```
int nums[100];
int *nPtr;
```

The statement ____ produces the same result as `nPtr = nums;`.

- 1) `nPtr = &nums[0];`
- 2) `nPtr = nums[0];`
- 3) `nPtr = *nums[0];`
- 4) `nPtr = &nums;`

12. `&grade[3]` is equivalent to ____; assume that `grade` is an array of integers, and each integer requires 4 bytes of storage..

- 1) `&grade[0] + 3`
- 2) `&grade[0] + 4`
- 3) `&grade[0] + (3 * 4)`
- 4) `&grade[0] + (3 / 4)`

13. The address operator in C is ____.

- 1) `&`
- 2) `*`
- 3) `->`
- 4) `.`

14. If `nums` is a two-dimensional integer array, ____ refers to element `nums[0][0]`.

- 1) `*nums`
- 2) `*(*nums)`
- 3) `*(&nums)`
- 4) `&(*nums)`

15. ____ uses the pointer and then increments it.

- 1) `*ptNum--`
- 2) `*--ptNum`
- 3) `*ptNum++`
- 4) `*++ptNum`

16. If `numPtr` is declared as a pointer variable, the expression ____ can also be written as `numPtr[i]`.

- 1) `*numPtr + i`
- 2) `(numPtr + i)`
- 3) `*numPtr`
- 4) `*(numPtr + i)`

17. Consider the following declarations of a function that receives an array of integers and finds the element with the maximum value:

- (i) `findMax(int *vals, int numEls)`
- (ii) `findMax(int vals[], int numEls)`

The address in `vals` may be modified ____.

- 1) only if the function is declared as in (i)
- 2) only if the function is declared as in (ii)
- 3) if either (i) or (ii) is used
- 4) in neither case because an array variable cannot be modified (it is a pointer constant)

18. Of the following expressions, ____ is the most commonly used. This is because such an expression allows each element in an array to be accessed as the address is “marched along” from the starting address of the array to the address of the last array element.

- 1) `*ptNum--`
- 2) `*--ptNum`
- 3) `*ptNum++`
- 4) `*++ptNum`

19. If `nums` is a two-dimensional integer array, ____ refers to element `nums[1][0]`.

- 1) `*nums[1]`
- 2) `*nums[0]`
- 3) `*nums + 1`
- 4) `*nums++`

20. `int *ptNum = &miles;` is ____.

- 1) always valid
- 2) never valid
- 3) only valid if `miles` is declared as an integer variable before `ptNum` is declared
- 4) only valid if `miles` is declared as an array of integers before `ptNum` is declared

21. Pointers ____ be initialized when they are declared.

- 1) must
- 2) must not
- 3) can
- 4) cannot

22. If `gPtr` is a pointer that points to the first element of an integer array (and each integer requires four bytes of storage), ____ references the variable that is three integers beyond the variable pointed to by `gPtr`.

- 1) `*gPtr + 3`
- 2) `*(gPtr + 3)`
- 3) `*(gPtr + 3 * 4)`
- 4) `*(gPtr + 3 / 4)`

23. If we store the address of `grade[0]` in a pointer named `gPtr` (using the assignment statement `gPtr = &grade[0];`), then, the expression ____ references `grade[0]`.

- 1) `gPtr(0)`
- 2) `gPtr`
- 3) `&gPtr`
- 4) `*gPtr`

24. Adding ____ to a pointer causes the pointer to point to the next element of the original data type being pointed to.

- 1) 1
- 2) `1 * sizeof(data type being pointed to)`
- 3) 2
- 4) `2 * sizeof(data type being pointed to)`

25. In performing _____ on pointers, we must be careful to produce addresses that point to something meaningful.

1) comparisons

3) subscript operations

2) arithmetic

4) duplication

QUIZ-09

Multiple Choice

Identify the letter of the choice that best completes the statement or answers the question.

1. Structures that are “linked” together by including the address of the next structure in the structure immediately preceding it are known as ____ structures.
 - 1) linked
 - 2) self-referencing
 - 3) dynamic
 - 4) sequential
2. ____ arrays are two or more arrays, where each array has the same number of elements and the elements in each array are directly related by their position in the arrays.
 - 1) Two-dimensional
 - 2) Multi-dimensional
 - 3) Parallel
 - 4) Complex
3. If `pt` is declared as a pointer to a structure of type `Employee`, ____ refers to the variable whose address is in the `pt.idNum` variable.
 - 1) `(*pt).idNum`
 - 2) `*pt.idNum`
 - 3) `pt->idNum`
 - 4) `(*pt.)idNum`
4. ____ is not a valid C statement.
 - 1) `struct {int month; int day; int year;} birth;`
 - 2) `struct {int month; int day; int year;} birth, current;`
 - 3) `struct Date {int month; int day; int year;};`
 - 4) `struct {int month, int day, int year} birth;`
5. Stacks and queues are two special forms of a more general data object called a(n) ____.
 - 1) array
 - 2) table
 - 3) deque
 - 4) heap
6. ____ memory allocation makes it unnecessary to reserve a fixed amount of memory for a scalar, array, or structure variable in advance.
 - 1) Dynamic
 - 2) Static
 - 3) Partial
 - 4) Advanced
7. The operation of removing a structure from a stack is called a ____.
 - 1) PUSH
 - 2) POP
 - 3) DELETE
 - 4) REMOVE
8. A ____ is a special type of linked list in which objects can only be added to and removed from the top of the list.
 - 1) heap
 - 2) stack
 - 3) queue
 - 4) set

9. The function call ____ passes a copy of the complete emp structure to calcNet().

- 1) calcNet(struct emp); 3) calcNet(&emp);
- 2) calcNet(*emp); 4) calcNet(emp);

10. The following function cycles through a linked list and displays its contents. Line 3 can be replaced with ____.

```
1 void display(struct myStruct *contents)
2 {
3     while (contents != NULL)
4     {
5         printf("%-30s\n", contents->name, contents->phoneNum);
6         contents = contents->nextaddr;
7     }
8 }
```

- 1) while (isValid(contents)) 3) while (!contents)
- 2) while (contents != EOF) 4) while (contents != NIL)

11. ____ is equivalent to (*pointer).member.

- 1) *pointer.member 3) pointer->member
- 2) pointer>member 4) pointer@member

12. Each member of a structure is accessed by giving both the structure name and individual data item name, separated by a ____.

- 1) @ 3) :
- 2) -> 4) .

13. If you have declared a structure named Date, you can then make the name DATE a synonym for the terms struct Date, by using the statement ____.

- 1) typedef struct Date DATE; 3) #define struct Date DATE
- 2) typedef DATE struct Date; 4) #define DATE struct Date

14. The expression t1.nextaddr->name can be replaced by the equivalent expression ____.

- 1) (*t1.nextaddr).name 3) *(*t1.nextaddr).name
- 2) (&t1.nextaddr).name 4) *((*t1.nextaddr).name)

15. ____ reserves space for an array of n elements of the specified size.

- 1) malloc() 3) realloc()
- 2) calloc() 4) nalloc()

16. A(n) ____ is a set of structures in which each structure contains at least one member whose value is the address of the next logically ordered structure in the list.

- 1) array 3) queue
- 2) stack 4) linked list

17. The operation of removing a structure from a dynamically linked list is called a(n) ____.

- 1) POP 3) REMOVE
- 2) SERVE 4) DELETE

18. In C, a record is referred to as a(n) ____.
- 1) data field
 - 2) union
 - 3) **structure**
 - 4) tuple
19. A union reserves sufficient memory locations to accommodate ____.
- 1) its smallest member's data type
 - 2) **its largest member's data type**
 - 3) all of its members' data types
 - 4) none of its members' data types
20. ____ reserves the number of bytes requested by the argument passed to the function.
- 1) **malloc()**
 - 2) calloc()
 - 3) realloc()
 - 4) balloc()

QUIZ-10

Multiple Choice

Identify the choice that best completes the statement or answers the question.

1. The conditional preprocessor directive _____ means “if not defined”.
1) `#ifdef` 3) `#ifnotdef`
2) `#ifndef` 4) `#ifnotdefined`
2. The operator _____ is a ternary operator.
1) `?:` 3) `&`
2) `->` 4) `[]`
3. `ARRAY first, second;` is equivalent to the two definitions `int first[100];` and `int second[100];` if _____.
1) you are using a pre-ANSI C compiler
2) you are using a C/C++ compiler
3) `the statement typedef int ARRAY[100]; is used before`
4) the statement `#define ARRAY int[100];` is used before
4. For unsigned integers, each left shift (using the `<<` operator) corresponds to _____.
1) `multiplication by 2` 3) multiplication by 4
2) division by 2 4) division by 4
5. Enumerated lists are identified by the reserved word _____ followed by an optional, user-selected name and a required list of one or more constants.
1) `list` 3) `enumerate`
2) `typedef` 4) `enum`
6. A conditional expression uses the conditional operator, _____, and provides an alternate way of expressing a simple `if-else` statement.
1) `->` 3) `?`
2) `?:` 4) `:`
7. The equivalence produced by a `typedef` statement can frequently be produced equally well by a _____ statement.
1) `enum` 3) `struct`
2) `#define` 4) `alias`
8. _____ bit operations are extremely useful in masking, or eliminating, selected bits from an operand.
1) `&` 3) `>>`
2) `|` 4) `<<`

9. Explicit values can be assigned to each enumerated constant, with unspecified values automatically continuing the integer sequence from the last specified value. For example, ____.
- 1) `enum {Mon: 1, Tue, Wed, Thr, Fri, Sat, Sun};`
 - 2) `enum {Mon, Tue, Wed, Thr, Fri, Sat, Sun};`
`Mon = 1;`
 - 3) `enum {Mon = 1, Tue, Wed, Thr, Fri, Sat, Sun};`
 - 4) `enum {Mon 1, Tue, Wed, Thr, Fri, Sat, Sun};`
10. ____ is the most frequently used conditional preprocessor directive.
- 1) `#define`
 - 2) `#else`
 - 3) `#ifdef`
 - 4) `#ifndef`
11. In an arithmetic right shift (using the `>>` operator), each right shift corresponds to ____.
- 1) multiplication by 2
 - 2) division by 2
 - 3) multiplication by 4
 - 4) division by 4
12. `1 0 1 1 0 0 1 1 ____ 1 1 0 1 0 1 0 1` results in `1 0 0 1 0 0 0 1`.
- 1) `&`
 - 2) `|`
 - 3) `>>`
 - 4) `<<`
13. `1 0 1 1 0 0 1 1 ____ 1 1 0 1 0 1 0 1` results in `1 1 1 1 0 1 1 1`.
- 1) `&`
 - 2) `|`
 - 3) `>>`
 - 4) `<<`
14. The definition `REAL val;` is ____.
- 1) not valid in C
 - 2) will generate a compiler warning
 - 3) is equivalent to `double val;` if it comes after `typedef double REAL;`
 - 4) defines a macro instance if it comes after `#define REAL double`
15. The ____ statement provides an unconditional transfer of control to some other statement in a program.
- 1) `jump`
 - 2) `goto`
 - 3) `label`
 - 4) `transfer`
16. `#define SQUARE(x) x * x`
`val = SQUARE(num1 + num2);`
- results in the equivalent statement ____.
- 1) `val = num1 + (num2 * num1 + num2);`
 - 2) `val = (num1 + num2 * num1) + num2;`
 - 3) `val = (num1 + num2) * (num1 + num2);`
 - 4) `val = num1 + num2 * num1 + num2;`
17. ____ is the exclusive OR operator.
- 1) `&`
 - 2) `|`
 - 3) `^`
 - 4) `~`
18. The conditional preprocessor directive ____ means "if defined".
- 1) `#ifdef`
 - 2) `#ifndef`
 - 3) `#ifdefined`
 - 4) `#if_def`

19. Upon encountering the command line `pgm14.3 three blind mice`, the operating system stores it as a sequence of ____ strings.
- 1) one
 - 2) three
 - 3) four
 - 4) five
20. The ____ operator causes a bit-by-bit AND comparison between its two operands.
- 1) `~`
 - 2) `^`
 - 3) `&&`
 - 4) `&`
21. `1 0 1 1 0 0 1 1 ____ 1 1 0 1 0 1 0 1` results in `0 1 1 0 0 1 1 0`.
- 1) `&`
 - 2) `|`
 - 3) `^`
 - 4) `~`
22. `typedef` can be used to create ____.
- 1) structures
 - 2) variables
 - 3) aliases
 - 4) macros
23. Using even one ____ statement in a program is almost always a sign of bad programming structure.
- 1) `enum`
 - 2) `typedef`
 - 3) `goto`
 - 4) `#define`
24. The statement ____ makes the name `REAL` a synonym for `double`.
- 1) `typedef double REAL;`
 - 2) `#define double REAL`
 - 3) `enum REAL double`
 - 4) `typedef REAL double;`
25. In the equivalence statement `#define SQUARE(x) x * x`, `x` is ____.
- 1) fixed
 - 2) an error
 - 3) a variable
 - 4) an argument