



## Cheat Sheet



More of zenml.io

docs.zenml.io

## Essential ZenML CLI commands in one place!

| Setting Up    |   |  |
|---------------|---|--|
| zenml init    | Initialize a ZenML workspace.                         |  |
| zenml version | Show installed ZenML version.                         |  |
| zenml go      | Pulls and opens the Quickstart example in a notebook. |  |

zenml integration

zenml integration list

zenml integration
install pytorch
install pytorch
integration
uninstall sklearn

List all integrations.

Install PyTorch
integration.

Uninstall Scikit-learn
integration.

| zenml example                   |                              |  |
|---------------------------------|------------------------------|--|
| zenml example list              | Lists all examples.          |  |
| zenml example run<br>quickstart | Runs the Quickstart example. |  |
|                                 |                              |  |

zenml <STACK\_COMPONENT> zenml model-deployer List all registered model list deployer stack component. zenml model-deployer Show details for the model describe deployer stack component. zenml experiment-Register the mlflow tracker register experiment tracker as a mlflow\_tracker -stack component. flavor=mlflow zenml experiment-Delete registered tracker delete experiment tracker named myexptracker myexptracker.

Get the active stack.

Provision resources for

zenml stack

zenml stack set mystackname

zenml stack list

zenml stack list

List all stacks.

Describe the current active stack.

zenml stack copy
mycurrentstack mynewstack

zenml stack rename
oldstackname newstackname

zenml stack delete
myoldstack

Delete myoldstack.

the active stack. Suspend resources for the zenml stack down active stack. zenml stack export Export a stack to a YAML file. mystack.yaml zenml stack import Import a stack from a mystack.yaml YAML file. zenml stack recipe Deploys a recipe called deploy myrecipename myrecipename.

zenml stack get

zenml stack up

 zenml secrets-manager secret

 --example\_secret\_key=example\_secret\_value
 Create a secret called example\_secret which contains a single key-value pair: {example\_secret\_key: example\_secret\_value}.

 zenml secrets-manager secret delete example\_secret
 Delete the secret called example secret.

 zenml secrets-manager secret get example\_secret
 Get a secret called example\_secret.

 zenml secrets-manager secret get example\_secret
 List all secrets.

| zenml model-deployer models                        |  |  |  |  |
|--|--|--|--|--|
| zenml model-deployer models list                   | Get a list of all served models within the model-deployer stack component. |  |  |  |
| zenml model-deployer models start 5vje341b-125g    | Start a model server with UUID 5vje341b-125g.                              |  |  |  |
| zenml model-deployer models describe 5vje341b-125g | Describe a served model with the UUID 5vje341b-125g.                       |  |  |  |
| zenml model-deployer models get-url 5vje341b-125g  | Get the prediction URL of a model server with UUID 5vje341b-125g.          |  |  |  |
| zenml model-deployer models stop 5vje341b-125g     | Stop a model server with UUID 5vje341b-125g.                               |  |  |  |
| zenml model-deployer models delete 5vje341b-125g   | Delete a model server with UUID 5vje341b-125g.                             |  |  |  |

| zenml annotator                  |                 |  |
|----------------------------------|-----------------|--|
| zenml annotator u                | p               | Spins up the annotation server.                  |
| zenml annotator datase           | t list          | List available datasets.                         |
| zenml annotator dataset stats :  | ny_cats_dataset | Show stats on my_cats_dataset.                   |
| zenml annotator dataset annotate | my_dogs_dataset | Launch annotation interface for my_dogs_dataset. |