



Version: 20220715-A



# ZenML 🙏 Cheat Sheet

Essential ZenML CLI commands in one place!

## Setting Up

<b>zenml init</b>	Initialize a ZenML workspace.
<b>zenml version</b>	Show installed ZenML version.
<b>zenml go</b>	Run the quickstart example.

## zenml integration

<b>zenml integration list</b>	List all integrations.
<b>zenml integration install pytorch</b>	Install PyTorch integration.
<b>zenml integration uninstall sklearn</b>	Uninstall Scikit-learn integration.

## zenml example

<b>zenml example list</b>	Lists all examples.
<b>zenml example run quickstart</b>	Runs the quickstart example.

## zenml profile

<b>zenml profile create myzenprofile</b>	Create a profile with the name myzenprofile.
<b>zenml profile set myzenprofile</b>	Set the active profile to myzenprofile.

## zenml <STACK\_COMPONENT>

<b>zenml model-deployer list</b>	List all registered model deployer stack component.
<b>zenml model-deployer describe</b>	Show details for the model deployer stack component.
<b>zenml experiment-tracker register mlflow_tracker --flavor=mlflow</b>	Register the mlflow experiment tracker as a stack component.
<b>zenml experiment-tracker delete myexptracker</b>	Delete registered experiment tracker named myexptracker.

## zenml stack

<b>zenml stack set mystackname</b>	Set the mystackname as the active stack.
<b>zenml stack list</b>	List all stacks.
<b>zenml stack describe</b>	Describe the current active stack.

<b>zenml stack get</b>	Get the active stack.
<b>zenml stack up</b>	Provision resources for the active stack.
<b>zenml stack down</b>	Suspend resources for the active stack.

<b>zenml stack copy mycurrentstack mynewstack</b>	Copy mycurrentstack stack to mynewstack.
<b>zenml stack rename oldstackname newstackname</b>	Rename a stack from oldstackname to newstackname.
<b>zenml stack delete myoldstack</b>	Delete myoldstack

<b>zenml stack export mystack.yaml</b>	Export a stack to a YAML file.
<b>zenml stack import mystack.yaml</b>	Import a stack from a YAML file.
<b>zenml stack recipe deploy myrecipeName</b>	Deploys a recipe called myrecipeName.

## zenml secret

<b>zenml secret register example_secret --example_secret_key=example_secret_value</b>	Create a secret called example_secret which contains a single key-value pair: {example_secret_key: example_secret_value}
<b>zenml secret delete example_secret</b>	Delete the secret called example secret.
<b>zenml secret get example_secret</b>	Get a secret called example_secret.
<b>zenml secret list</b>	List all secrets.

## zenml served-models

<b>zenml served-models list</b>	Get a list of all served models within the model-deployer stack component.
<b>zenml served-models start 5vje341b-125g</b>	Start a model server with UUID 5vje341b-125g
<b>zenml served-models describe 5vje341b-125g</b>	Describe a served model with the UUID 5vje341b-125g.
<b>zenml served-models get-url 5vje341b-125g</b>	Get the prediction URL of a model server with UUID 5vje341b-125g.
<b>zenml served-models stop 5vje341b-125g</b>	Stop a model server with UUID 5vje341b-125g
<b>zenml served-models delete 5vje341b-125g</b>	Delete a model server with UUID 5vje341b-125g

More  [docs.zenml.io](https://docs.zenml.io)