

# Lecture 7

# Constraint-based search


*Nadia Polikarpova*

# The problem statement

---

## Search strategy?

Enumerative  
Stochastic  
Representation-based  
Constraint-based




# Constraint-based search

---

**Idea:** encode the synthesis problem as a SAT/SMT problem and let a solver deal with it

# What is an encoding?



# How to define an encoding

---

Define the parameter space  $\mathcal{C} = \{c_1, \dots, c_n\}$

- **encode** :  $\text{Prog} \rightarrow \mathcal{C}$
- **decode** :  $\mathcal{C} \rightarrow \text{Prog}$  (might not be defined for all  $\mathcal{C}$ )

Define a formula  $\text{wf}(c_1, \dots, c_n)$


- that holds iff **decode**[ $\mathcal{C}$ ] is a “well-formed” program

Define a formula  $\varphi(c_1, \dots, c_n, i, o)$


- that holds iff  $(\text{decode}[\mathcal{C}])(i) = o$

# Constraint-based search

---

```
constraint-based (wf,  $\varphi$ ,  $E = [i \rightarrow o]$ ) {  
  match SAT(wf( $C$ )  $\wedge \bigwedge_{\langle i, o \rangle \in E} \varphi(C, i, o)$ ) with  Find a satisfying assignment  
    Unsatisfiable -> return "No solution" for  $c_1, \dots, c_n$   
    Model  $C^*$  -> return decode[ $C^*$ ] ( $i$  and  $o$  are fixed)  
}
```

# SAT encoding: example



$$\text{wf}(c) \equiv \top$$

$$\begin{aligned} \varphi(c, i, o) &\equiv (\neg c \Rightarrow o_h = i_h \wedge o_l = i_l) \\ &\wedge (c \Rightarrow o_h = 0 \wedge o_l = i_l) \end{aligned}$$

$$\text{SAT}(\varphi(c, 11, 01))$$

$$\text{SAT}((\neg c \Rightarrow 0 = 1 \wedge 1 = 1) \wedge (c \Rightarrow 0 = 0 \wedge 1 = 1)) \xrightarrow{\text{SAT solver}} \text{Model } \{c \rightarrow 1\}$$

x is a two-bit word  
( $x = x_h x_l$ )

$$E = [11 \rightarrow 01]$$

parameter space


$$C = \{c: \text{Bool}\}$$

$$\text{decode}[0] \rightarrow x$$

$$\text{decode}[1] \rightarrow x \& 1$$

return decode[1] i.e.  $x \& 1$

# SMT encoding: example



$$\text{wf}(c) \equiv \top$$

$$\varphi(c_{op}, c_N, i, o) \equiv (\neg c_{op} \Rightarrow o = i + c_N) \\ \wedge (c_{op} \Rightarrow o = i * c_N)$$

$$\text{SAT}(\varphi(c, 2, 9))$$

$$\text{SAT}((\neg c_{op} \Rightarrow 9 = 2 + c_N) \wedge (c_{op} \Rightarrow 9 = 2 * c_N))$$

return decode[0,7] i.e.  $x + 7$

$N$  is an integer literal  
 $x$  is an integer

$$E = [2 \rightarrow 9]$$

parameter space

$$\mathcal{C} = \{c_{op}: \text{Bool}, c_N: \text{Int}\}$$

$$\text{decode}[0, N] \rightarrow x + N$$

$$\text{decode}[1, N] \rightarrow x * N$$

SMT solver



Model  $\{c_{op} \rightarrow 0, \\ c_N \rightarrow 7\}$



# What is a good encoding?

---

Sound

- if  $\text{wf}(C) \wedge \text{sem}(C)$  then  $\text{decode}[C]$  is a solution

Complete

- if  $\text{decode}[C]$  is a solution then  $\text{wf}(C) \wedge \text{sem}(C)$

Small parameter space

- avoid symmetries

Solver-friendly

- decidable logic, compact constraint

# DSL limitations

---

Program space can be parameterized with a finite set of parameters

- Counterexample: 
$$\begin{array}{lcl} L ::= & \text{sort}(L) & | \quad L[N..N] \\ & | \quad L + L & | \quad [N] \quad | \quad x \\ N ::= & \text{find}(L, N) & | \quad \emptyset \end{array}$$


- Workaround 
$$\begin{array}{lcl} L0 ::= & x & L1 ::= \text{sort}(L0) \quad | \quad L0[N0..N0] \\ N0 ::= & \emptyset & \quad | \quad L0 + L0 \quad | \quad [N0] \quad | \quad L0 \\ & & N1 ::= \text{find}(L0, N0) \quad | \quad N0 \end{array}$$

Program semantics  $\varphi(C, i, o)$  is expressible as a (decidable) SAT/SMT formula

- Counterexample

# Brahma


---



# Brahma encoding


[Jha et al. '10]

program space = DAG




parameter space

$$C = \{c_o : N\} \cup \bigcup_{f \in F} \{c_1^f, c_2^f : N\}$$




# Brahma encoding: take 2

[Jha et al. '10]



parameter space

$$C = \{c_o: \text{Int}\} \cup \bigcup_{f \in F} \{c_{o_f}, c_{I_f}, c_{J_f}: \text{Int}\}$$




$$\text{wf}(C) \equiv c_o \in M \wedge \bigwedge_{f \in F} c_{o_f} \in N \wedge c_{I/J_f} \in M$$

$$\wedge \bigwedge_{f, g \in F, f \neq g} c_{o_f} \neq c_{o_g} \wedge \bigwedge_{f \in F} c_{I/J_f} < c_{o_f}$$

# Brahma encoding: take 2

[Jha et al. '10]



parameter space


$$C = \{c_o: \text{Int}\} \cup \bigcup_{f \in F} \{c_{o_f}, c_{I_f}, c_{J_f}: \text{Int}\}$$

$$P = \bigcup_{f \in F} \{I_f, J_f\} \quad R = \bigcup_{f \in F} \{O_f\}$$

$$\varphi(C, I, o) \equiv \exists P, R. \bigwedge_{f \in F} O_f = F(I_f, J_f)$$

$$\wedge \bigwedge_{x \in P \cup R \cup I \cup \{O\}} c_x = c_y \Rightarrow x = y$$

# Limit #components to K?



parameter space

$$C = \{c_o: \text{Int}\} \cup \bigcup_{f \in F} \{c_{o_f}, c_{I_f}, c_{J_f}: \text{Int}\}$$

$$\text{wf}(C) \equiv c_o \in M \wedge \bigwedge_{f \in F} c_{o_f} \in N \wedge c_{I/J_f} \in M$$

$\wedge \dots$

$$\text{wf}'(C) \equiv \text{wf}(C) \wedge c_o < |I| + K$$

# Comparison of search strategies

---

