Structured KV Cache Quantization for Mobile NPUs

Jeongwoo Han
Working draft: author list, affiliations, and contact information to be confirmed

***Abstract*—Key–value cache quantization reduces storage requirements but can introduce substantial encoding and restoration overhead on mobile neural processing units. This paper presents a hardware-oriented implementation and evaluation of Structured K8, a two-region piecewise-uniform key quantizer with arithmetic indexing and a lookup-free Hexagon Vector eXtensions decoder. The design uses four shared coefficients and preserves explicit half-precision rounding. We integrate it into a mixed-precision cache with eight-bit keys in half of the layers, four-bit keys elsewhere, and two-bit values throughout. On a Galaxy S26 Ultra running Qwen3-1.7B in a W4A16 configuration, the cache occupies 28.875 MiB at a context capacity of 1024 tokens. Across ten warmed measurements per configuration, Structured K8 reduces mean time to first token by 32.62 percent and increases mean decoding throughput by 13.61 percent relative to converged Lloyd–Max under Odd placement; matched Boundary placement yields 31.12 percent and 14.41 percent, respectively. A separate teacher-forced evaluation on four previously used WikiText-2 windows finds 1.81 percent higher perplexity under Odd placement but 0.45 percent lower perplexity under Boundary placement, indicating placement-dependent quality ordering. A separate three-run uniform-quantizer comparison shows similar observed throughput and lower aggregate perplexity on a different held-out set. A same-codebook decoder probe records 39.56 percent fewer physical vector-unit busy cycles. These results support an implementation-level quality–efficiency trade-off within the tested conditions, not broad-domain or cross-device generalization.**

***Index Terms*—KV cache, quantization, mobile NPU, piecewise-uniform quantization, Hexagon HVX**

I. Introduction

Key–value (KV) cache quantization reduces storage and data movement, but encoding and restoration overhead can limit its benefits for mobile inference. KIVI motivates asymmetric key/value quantization [1], while TurboQuant explores rotation-based scalar quantization [2]. Practical deployment therefore requires evaluating codec costs alongside quantization error.

Our work builds on a TurboQuant implementation in the Qualcomm AI Hub Models pipeline [3]. Its inherited Lloyd–Max (LM) encoder uses comparison trees and reconstruction-level selection subgraphs, while LUT-based decoding requires table lookup and layout conversion. We investigate whether structured reconstruction levels can simplify both paths while maintaining useful language-model quality.

Building on piecewise quantization approaches such as PWLQ [4] and PTQ4ViT [5], we present Structured K8, a two-region piecewise-uniform key quantizer with arithmetic indexing and HVX restoration. Our contribution is its hardware-oriented implementation for a rotated KV cache, preserving the existing byte format and explicit FP16 rounding, together with controlled on-device comparisons against converged LM8 and a single-spacing uniform baseline. Mixed key/value precision and layer placement support this implementation. Figure 1 summarizes the overall design.

II. Background and Motivation

A. Key and Value Quantization Errors

Scaled dot-product attention is [6]

$$O = \mathrm{softmax}\left(\frac{QK^\top}{\sqrt{d}}\right)V, \tag{1}$$

where Q, K, and V are queries, keys, and values, and d is the key dimension; causal masking is omitted. Key quantization changes the dot products and thus the normalized exponential softmax weights. In contrast, value errors enter the weighted sum linearly for fixed Q and K. This motivates asymmetric K/V precision, without implying that key errors always dominate.

B. Layer-Wise Quantization Sensitivity

KV quantization sensitivity varies across layers [7], motivating higher precision in selected layers under a fixed cache budget. We mix K8 and K4 to maintain average K6 precision, with V2 throughout. Odd and Boundary are tested placements, not presumed optima; comparisons use matched masks.

C. Packing and Scalar-Index Costs

Two- and four-bit codes divide a byte evenly, whereas eight-bit codes use direct byte storage. Three-, five-, six-, and seven-bit codes may cross byte boundaries and need fragment assembly. Separately, the inherited LM encoder incurs bit-width-dependent comparison-tree and reconstruction-level selection costs [3]. Structured K8 uses byte storage and arithmetic indexing/restoration; K4/V2 retain packing overhead. Thus, nominal bit width alone does not determine execution cost.

III. Structured Quantization and Implementation

A. Overview

The three panels in Fig. 1 connect the storage budget to the deployed codecs. In the left panel, B_K and B_V denote key and value index-storage budgets, so $B_{KV} = B_K + B_V$ excludes FP16 scales. The cache dimensions are token count T, KV-head count n_{heads}, and head dimension d_{head}. Assigning K8 to half of the layers and K4 to the rest gives an average key precision of six bits; values use V2 throughout.




Fig. 1. Conceptual overview of the mixed-precision KV cache, illustrated with Boundary placement. Left: asymmetric key/value index budgeting. Center: layerwise K4/K8 allocation. Right: Lloyd–Max K4/V2 and Structured K8 quantization. Distributions, block proportions, and level markers are schematic; K4, K8, and V2 use 16, 256, and 4 signed reconstruction levels, respectively. Sensitivity and importance labels express the design motivation rather than a measured universal ranking.

The center panel illustrates Boundary placement, with K8 assigned to the first and last seven of 28 layers. The drawing numbers layers from 1 to L; our experimental masks use zero-based indices. Odd placement is also evaluated under the same storage budget. These placements instantiate the precision allocation used to compare quantizer implementations.

The right panel selects LM for K4/V2 and Structured quantization for K8. Its scalar axis x represents a normalized, rotated coordinate, denoted y below, and $c_{r,k}$ denotes a positive reconstruction level. The following subsections specify arithmetic indexing and native HVX restoration.

B. Quantization Levels and Arithmetic Indexing

The proposed key cache uses LM K4 and Structured K8. For bit width p, the positive reconstruction levels are

$$\ell_p^+(j) = \begin{cases} \mathcal{L}_4^+[j], & p = 4, \\ a_r + k\Delta_r, & p = 8. \end{cases} \tag{2}$$

For K4, $\mathcal{L}_4^+$ contains eight positive LM levels indexed by $j \in \{0, \ldots, 7\}$; the threshold-based encoder is retained. For K8, $j = 64r + k$, with region $r \in \{0, 1\}$, local index $k \in \{0, \ldots, 63\}$, offset a_r, and spacing Δ_r. Negative levels follow by sign reflection. The K8 expression describes the grid before rounding; its multiplication and addition are separately rounded to FP16.

The four coefficients are fitted offline to minimize scalar MSE under the Gaussian approximation $\mathcal{N}(0, 1/d)$, without KV samples or PPL-based tuning. The frozen coefficients and fitting procedure are provided in the implementation [3].

Arithmetic indexing. For a normalized, rotated coordinate y, let $m = |y|$. The boundary τ is the midpoint between the FP16-rounded levels at $(r, k) = (0, 63)$ and $(1, 0)$. Select the region as

$$r = \begin{cases} 0, & m \le \tau, \\ 1, & m > \tau. \end{cases} \tag{3}$$

The local index is

$$k = \mathrm{clip}\left(\left\lfloor (m - a_r)\frac{1}{\Delta_r} + 0.5 \right\rfloor, 0, 63 \right) \tag{4}$$

The logical floor rule rounds half-step ties upward. Execution uses a stored reciprocal with intermediate FP16 rounding, which can shift decisions near index boundaries.

Byte encoding. The magnitude index j and the sign of y are stored in one UINT8 code:

$$b = \begin{cases} 128 + j, & y \ge 0, \\ 127 - j, & y < 0. \end{cases} \tag{5}$$

For negative values, the magnitude index is reflected to preserve compatibility with the existing ascending LUT layout. The decoder recovers $j = b - 128$ for $b \ge 128$ and $j = 127 - b$ otherwise.

C. HVX Arithmetic Decoder

The native HVX decoder recovers r and k from each stored byte and reconstructs $a_r + k\Delta_r$ using separate FP16 multiply and add operations. It then applies the sign and the effective FP16 scale used for norm correction, producing FP16 tiles for the existing attention path. Vectorized restoration avoids level-table loads and per-coordinate scalar loops. The coefficient payload is four FP16 values (8 bytes), replacing a 256-entry FP16 codebook (512 bytes).

IV. Experimental Methodology

We use Qwen3-1.7B [8] in a fixed W4A16 configuration on a Galaxy S26 Ultra (SM8850), using QAIRT 2.48.0.260626 and the HTP backend in burst mode. Inference uses a single sequence with context capacity 1024. Dense QR-generated rotations use seeds 42 and 542 for keys and values, respectively, with norm correction enabled. The quantized Johnson–Lindenstrauss (QJL) residual stage is disabled, so the evaluated codec is not the full inner-product-unbiased TurboQuant construction [2]. Model weights, activation encodings, rotation seeds, norm correction, and K4/V2 paths are held fixed within each quantizer comparison; no weight training or activation recalibration is performed. The implementation and recorded experiments are identified by immutable commits [3]. Table I summarizes the repeated performance comparison.

Quality is teacher-forced perplexity on selected WikiText-2 documents [9]. A 1024-token window has 1023 scored targets. Aggregate perplexity is $\exp(\sum_j \mathrm{NLL}_j / \sum_j N_j)$, where NLL_j is a window's summed negative log-likelihood. It is not an average of window perplexities or a full-corpus WikiText-2 result.

A separate quality follow-up evaluates the four unchanged binaries from Table I on the same four previously used WikiText-2 reference windows. The existing AR128 teacher-forced scorer runs once per window and configuration in a fresh process/session: 16 passes in total and 4092 scored targets per configuration. No warm-up, repeated scoring, logit dump, profiling, or generation-speed measurement is added. Host/device binary, runtime, configuration, and input hashes are checked against the performance experiment's frozen artifacts before and after scoring. These windows are reused references, not a new independent held-out test.

The earlier LM and uniform quality experiments also include four held-out documents each, fixed by content-hash order with exclusions for previously recorded titles and 16-token overlaps. Their held-out sets A and B differ, so absolute held-out PPL must not be compared across those experiments. Held-out status refers to those experiments, not pretraining. Neither held-out set is rescored in the follow-up; the earlier Odd-placement results remain separately labeled, and no matched Boundary held-out comparison is available.

Uninstrumented performance uses 897 prompt tokens and 128 generated tokens. The first generated token is produced during prefill; the subsequent 127 autoregressive (AR1) steps bring the cache to $897 + 127 = 1024$ tokens. Decode throughput is 127 divided by the summed durations of those steps. TTFT excludes model loading. Each invocation performs a full warm-up sequence, resets the KV cache, and then measures a second session on the same loaded model and input. Warm-up is excluded from the reported timing.

The repeated LM comparison covers four configurations: Structured and converged LM8 under Odd and Boundary placement. Ten counterbalanced rounds yield ten measured sessions per configuration, or 40 in total, plus 40 excluded warm-ups. Two Williams blocks and two reversed orders balance each pair's execution precedence five to five; each configuration occupies each within-round position two or three times. A fixed ten-second pause follows each invocation. All measured samples are retained, with no failures or replacements. We report means and sample standard deviations; improvements are ratios of group means, not averages of per-run ratios.

All four configurations use the same runner and Native package. Existing binaries are reused except for the missing Boundary converged-LM control, built before measurement. All 24 compiled AR1/AR128 graphs pass the I/O, rotation, and FP16-attention audit; paired non-codec initializers and activation encodings match. SHA-256 checks pass before and after measurement. No QNN optrace or detailed profiling is enabled. Current HAL temperatures and Android thermal status are sampled identically across configurations, spanning loading, warm-up, and measurement; they do not directly expose HTP clocks or throttling.

The earlier uniform comparison retains its three sessions per configuration in the order Uniform, Structured, Structured, Uniform, Uniform, Structured. Its timing, the earlier layer-placement study, and single-session codec probes remain separate experiments; their samples are not pooled with the new warmed LM measurements.

V. Results and Analysis

A. Comparison with Converged Lloyd–Max

LM100 is the inherited codebook generated with 100 Lloyd iterations; it is not a converged optimum. A stronger baseline runs four deterministic initializations until both reconstruction-level movement and relative MSE change satisfy strict convergence criteria for ten consecutive iterations. All four yield the same FP16 table. The minimum integrated Gaussian MSE falls from 1.3054680×10^{-6} to 3.2175846×10^{-7}; Structured's nearest-level MSE is 4.7935449×10^{-7}. Hence Structured is not superior in scalar reconstruction error to converged LM.

Table I reports the repeated measurements. Under Odd placement, Structured reduces mean TTFT by 32.62% and increases mean prefill/decode throughput by 48.49%/13.61% relative to converged LM8. Under Boundary placement, the corresponding changes are 31.12%, 45.22%, and 14.41%. Thus, the observed performance advantage persists under both tested masks, but is not established for every placement. This comparison changes both encoder structure and decoder, measuring complete implementations rather than the decoder alone.

Supplemental paired-round bootstrap 95% intervals for TTFT reduction are [31.51, 33.71]% for Odd and [30.01, 32.23]% for Boundary; decode-increase intervals are [13.23, 13.91]% and [14.23, 14.57]%, respectively. These small-sample, single-device intervals describe this experiment; shared thermal drift may affect them. Earlier single-session timings lacked the same-process warm-up and are not pooled with these results. No quantizer, kernel, or runner optimization was introduced by this repetition, so changes from historical absolute timings are not attributed to algorithm changes.

TABLE I

REPEATED ON-DEVICE PERFORMANCE WITH MATCHED LAYER MASKS. VALUES ARE MEAN ± SAMPLE SD ACROSS TEN MEASURED SESSIONS PER CONFIGURATION, EXCLUDING WARM-UP. IMPROVEMENTS DENOTE LOWER TTFT OR HIGHER THROUGHPUT RELATIVE TO CONVERGED LM8, COMPUTED FROM GROUP MEANS. EVERY CONFIGURATION ALLOCATES 28.875 MIB OF HOST KV STORAGE.

Placement	Metric	Converged LM8	Structured K8	Improvement (%)
Odd	TTFT (ms)	745.990 ± 11.668	502.653 ± 12.595	32.62
	Prefill (tokens/s)	1203.854 ± 19.009	1787.642 ± 44.911	48.49
	Decode (tokens/s)	33.249 ± 0.053	37.775 ± 0.232	13.61
Boundary	TTFT (ms)	726.580 ± 13.099	500.487 ± 9.512	31.12
	Prefill (tokens/s)	1236.104 ± 22.874	1795.119 ± 34.854	45.22
	Decode (tokens/s)	33.101 ± 0.051	37.870 ± 0.121	14.41

TABLE II

MATCHED REFERENCE-WINDOW QUALITY FOLLOW-UP USING THE UNCHANGED PERFORMANCE BINARIES. ONE TEACHER-FORCED PASS PER WINDOW AND CONFIGURATION; 4092 SCORED TARGETS PER CONFIGURATION. THESE FOUR WIKITEXT-2 WINDOWS ARE REUSED, NOT INDEPENDENTLY HELD OUT.

Placement	K8 codec	Mean NLL	PPL ↓
Odd	LM-conv.	3.143864	23.19332
	Structured	3.161763	23.61219
Boundary	LM-conv.	3.008651	20.26006
	Structured	3.004137	20.16881

TABLE III

EARLIER ODD-PLACEMENT QUALITY RETAINED SEPARATELY. HELD-OUT SET A IS NOT RESCORED IN THE FOLLOW-UP; ITS RESULTS ARE NOT TRANSFERRED TO BOUNDARY PLACEMENT. REFERENCE ROWS ALSO RETAIN THE HISTORICAL LM100 CONTROL.

Metric	LM100	LM-conv.	Structured
Reference PPL	23.9835	23.1933	23.6122
Held-out PPL (A)	16.3974	16.2165	16.4049

TABLE IV

UNIFORM VERSUS STRUCTURED K8 WITH FIXED ODD PLACEMENT. TIMING IS MEAN ± SAMPLE SD OVER THREE CROSSED RUNS. HELD-OUT SET B DIFFERS FROM A IN TABLE III.

Metric	Uniform	Structured
Reference PPL	23.7939	23.6122
Held-out PPL (B)	37.6154	33.3710
TTFT (ms)	536.446 ± 7.752	539.084 ± 5.060
Prefill (tokens/s)	1675.3 ± 23.9	1666.8 ± 15.7
Decode (tokens/s)	37.177 ± 0.024	37.112 ± 0.057

Table II adds the matched quality comparison. Structured has 1.8060% higher PPL than converged LM8 under Odd placement, but 0.4504% lower PPL under Boundary placement. Converged LM has lower NLL on three of four Odd windows; under Boundary placement, each quantizer wins on two windows. Thus, the quality ordering depends on placement in these reference windows; the small Boundary aggregate advantage is not evidence of broad-domain or statistically significant superiority.

Moving from Odd to Boundary lowers reference PPL by 14.5831% for Structured and 12.6470% for converged LM. Per-window NLL sums and input token hashes reproduce the historical Odd Structured, Odd converged-LM, and Boundary Structured results at stored JSON precision. Boundary converged LM is the new matched quality control. No codebook, kernel, runner, or layer-selection rule is changed by this follow-up, and the scores are not additional timing samples.

Table III retains the earlier LM100 control and held-out set A findings. Structured's held-out PPL is 1.16% higher than converged LM under Odd placement. This remains historical evidence, not a new held-out score from the follow-up. Together, the repeated timings, matched reference PPL, and separately reported held-out results characterize the evaluated quality–efficiency trade-offs without assuming that the quality ordering generalizes across placements or documents.

The LM encoder retains an implementation-specific FP16 affine interpolation path: rounding can differ from a direct decoder-LUT lookup. The earlier convergence experiment changed only LM constants, and the repeated experiment leaves this path unchanged. The results characterize the evaluated implementations, not implementation-independent superiority over Lloyd–Max quantization.

B. Comparison with a Single-Spacing Uniform Quantizer

The uniform baseline uses a symmetric 256-level mid-rise grid. A single spacing is fitted under the same Gaussian model without KV- or PPL-based tuning, then frozen to FP16. Both uniform and Structured variants use arithmetic HVX decoders, the same Odd placement, and identical cache storage. This comparison tests whether a second spacing provides a useful quality–cost trade-off.

In Table IV, Structured reduces held-out PPL by 11.28% relative to Uniform. The measured throughput differences are small and ranges overlap, so the results do not demonstrate a meaningful end-to-end speed advantage for either variant. Structured improves NLL on three of four held-out documents, but one document accounts for approximately 79.65% of the net NLL gain. This limited result must not be extrapolated to every document or domain.

C. Encoder Cost

The standalone Structured K8 encoder has 76 ONNX nodes, versus 837 in the inherited LM8 encoder; scalar indexing and level/scale reconstruction account for most of this difference.

TABLE V
AR128 ENCODER PROBE ON THE SAME CAPTURED INPUT. NAMED-OP CYCLE COUNTERS ARE NOT DISJOINT PHYSICAL OCCUPANCY OR ELAPSED TIME. EACH RESULT IS A SINGLE INSTRUMENTED PROBE.

Metric	LM-conv.	Structured
Scalar-index cycles	15,666,367	1,146,338
Norm/scale cycles	12,195,259	822,695
SDK execute (μs)	3,187	1,523

TABLE VI
SAME-CODEBOOK STRUCTURED DECODER PROBE: ONE INSTRUMENTED 256-TOKEN INVOCATION PER VARIANT.

Metric	LUT control	Arithmetic
Physical HVX busy cycles	593,957	358,972
SDK execute (μs)	4,469	4,429
Execute excluding wait (μs)	769	653

Node counts describe graph structure, not a proportional reduction in runtime. A more direct diagnostic uses a shared captured layer-0 input and 128-token encoder probes, summarized in Table V. The converged LM codebook retains the same tree and reconstruction-level selection structure as LM100, whereas Structured replaces them with arithmetic operations.

The observed decrease in index and scale-reconstruction work is consistent with the simplified representation. However, these named-op counters cannot be added as independent stage latencies, nor can the isolated execute times be substituted for full-model TTFT. Normalization, rotation, output casting, and runtime scheduling remain part of the complete path. The result supports the implementation mechanism rather than a hardware-independent complexity-to-speedup conversion.

D. Same-Codebook Decoder Ablation

To isolate restoration, Table VI compares the Structured LUT control and arithmetic decoder using identical codes, scales, and reconstruction levels for a 256-token probe. Their outputs are bit-exact against the FP16 reference. Arithmetic uses 39.56% fewer physical HVX busy cycles, while SDK execute time changes much less. Busy work, overlapping vector-lane activity, and elapsed execution time are distinct quantities; 39.56% is not a whole-model decoding speedup. Decoder validation additionally covers all byte codes, edge scales, and partial tiles at multiple token lengths.

E. Supporting Layer-Placement and Profiling Results

A separate placement experiment keeps exactly 14 Structured K8 layers and 14 LM K4 layers, with V2 unchanged. It uses 12 search windows, four selection-validation windows, and eight previously unused documents from the official WikiText validation partition as an independent test. The final mask is frozen by HTP validation NLL before test scoring; the test does not retrospectively select a winner.

Table VII summarizes this separate experiment. Its performance measurements use three crossed rounds, with all 21 sessions retained. The selected Multi-start Beam/Swap candidate obtains test PPL 19.7872, compared with 25.0496 for Odd and 20.3067 for the legacy Odd-start Greedy search. However, static Early placement reaches 19.6484 and Multi-start Greedy reaches 19.7279. Moreover, 19 of 196 checked single-swap neighbors improve the selected candidate's offline search NLL. We therefore claim neither optimal placement nor an accuracy/efficiency advantage for Beam search. These results illustrate placement sensitivity and are not substituted for the fixed-placement quantizer comparisons.

TABLE VII
EARLIER SUPPORTING PLACEMENT EXPERIMENT, SEPARATE FROM TABLE I. TEST C HAS EIGHT DOCUMENTS AND DIFFERS FROM A/B. TTFT IS MEAN $\pm$ SAMPLE SD FROM THREE CROSSED ROUNDS. ALL ROWS ALLOCATE 28.875 MIB HOST KV.

Configuration	Test PPL (C)	TTFT (ms)
Odd	25.0496	510.14 ± 25.25
Early	19.6484	491.01 ± 2.72
Boundary	20.0705	490.69 ± 3.33
Legacy Greedy	20.3067	503.11 ± 28.62
Multi-start Greedy	19.7279	510.99 ± 20.81
Beam/Swap (selected)	19.7872	508.78 ± 26.64
LM K6/V2	20.7267	626.00 ± 13.43

Against the uniform-across-layers LM K6/V2 configuration in this experiment, the selected candidate has 18.73% lower mean TTFT and 7.17% higher mean decode throughput (37.272 versus 34.777 tokens/s). This comparison changes both layerwise precision and quantizer implementation, so it is not an isolated layer-search speedup. Search methods also use unequal offline budgets: the observed Beam search takes more time than Multi-start Greedy while producing worse test NLL. We retain the validation-selected candidate instead of promoting Early after observing its test result.

A separate single instrumented session indicates that V2 accounts for 75.98% of attributed prefill packing/output-cast work, while past-KV restoration accounts for 33.065% of final-step compute busy cycles. This identifies remaining optimization targets rather than eliminating them. The trace attributes Dense rotation to HMX and native restoration to HVX. Its historical controls use different runner/native-library hashes; comparisons across those traces are descriptive, not paired isolated-kernel speedup measurements.

VI. LIMITATIONS AND CONCLUSION

The repeated LM comparison covers one model, one device, one prompt, context capacity 1024, and two masks in one measurement campaign. Ten warmed runs per configuration characterize within-experiment variability, not variation across devices, days, or workloads. The quality follow-up adds a matched Boundary PPL comparison, but uses only four previously evaluated reference windows, scored once each. It introduces neither an independent held-out test nor a statistical-significance claim; the earlier held-out evidence remains limited to small document subsets. The earlier three-run uniform comparison and single-session codec probes retain their own sampling limitations.

Recorded current AP temperatures range from 26.0 to 44.4 degrees Celsius, with Android thermal status and reported sensor severity zero throughout. These observations do not prove the absence of HTP throttling: no direct HTP clock/throttle counter was available. Temperature/order associations remain despite counterbalancing, and no adjustment or sample filtering is applied. We claim no energy, sustained thermal-performance, long-context task, or total accelerator-memory result. The 28.875 MiB figure is allocated host KV storage; separate runtime I/O buffers occupy approximately 96.929 MiB.

Numerical validation also has limits. The inherited LM100 AR128 encoder scale check and a standalone V4 probe exceed the unchanged 0.2% tolerance. The V4 probe is not the full-model V2 path. Graph/hash audits and repeated timings do not re-certify these numerical tolerances, and the failures are not waived by decoder bit-exactness or acceptable PPL.

Within this scope, Structured K8 provides a practical specialization of piecewise-uniform quantization for mobile KV caching. Arithmetic indexing and HVX restoration preserve a compact cache while reducing mean TTFT by 32.62%/31.12% and increasing mean decode throughput by 13.61%/14.41% under Odd/Boundary placement. On the four reused reference windows, Structured's PPL is 1.8060% higher than converged LM under Odd placement and 0.4504% lower under Boundary placement. Quality ordering is therefore placement-dependent within this evaluation, while the speed advantage is observed under both tested masks. The historical held-out and uniform comparisons remain separate, limited evidence. Future work should prioritize V2 packing, layout conversion, past-KV restoration, and evaluation across models, contexts, workloads, and independent measurement campaigns.

REFERENCES

[1] Z. Liu *et al.*, "KIVI: A tuning-free asymmetric 2bit quantization for KV cache," arXiv:2402.02750, 2024.

[2] A. Zandieh, M. Daliri, M. Hadian, and V. Mirrokni, "TurboQuant: Online vector quantization with near-optimal distortion rate," arXiv:2504.19874, 2025.

[3] J. Han, "ai-hub-models: TurboQuant KV-cache implementation and experiment records," 2026. Snapshot `b438a098c` (matched PPL follow-up); repeated timing commit `565acc7b1`; earlier experiment commits `70b8b006e`, `cdd68c447`, `8e35f0995`, and `dc629e6d6`. [Online]. Available: https://github.com/HANJEONGWOO/ai-hub-models

[4] J. Fang, A. Shafiee, H. Abdel-Aziz, D. Thorsley, G. Georgiadis, and J. Hassoun, "Post-training piecewise linear quantization for deep neural networks," arXiv:2002.00104, 2020.

[5] Z. Yuan, C. Xue, Y. Chen, Q. Wu, and G. Sun, "PTQ4ViT: Post-training quantization for vision transformers with twin uniform quantization," in *Proc. ECCV*, 2022.

[6] A. Vaswani *et al.*, "Attention is all you need," in *Advances in Neural Information Processing Systems*, vol. 30, 2017.

[7] X. Li *et al.*, "KVTuner: Sensitivity-aware layer-wise mixed-precision KV cache quantization for efficient and nearly lossless LLM inference," in *Proc. ICML*, PMLR, vol. 267, pp. 36451–36485, 2025.

[8] A. Yang *et al.*, "Qwen3 technical report," arXiv:2505.09388, 2025.

[9] S. Merity, C. Xiong, J. Bradbury, and R. Socher, "Pointer sentinel mixture models," arXiv:1609.07843, 2016.