


**EXP NO: 9**

## IMPLEMENT CLUSTERING TECHNIQUES – HIERARCHICAL AND K- MEANS

### a) Hierarchical Clustering

```
# Load the iris dataset
data(iris)
# Use only the numeric columns for clustering (exclude the Species
column)
iris_data <- iris[, -5]
# Standardize the data
iris_scaled <- scale(iris_data)
# Compute the distance matrix
distance_matrix <- dist(iris_scaled, method = "euclidean")
# Perform hierarchical clustering using the "complete" linkage method
hc_complete <- hclust(distance_matrix, method = "complete")
# Plot the dendrogram
plot(hc_complete, main = "Hierarchical Clustering Dendrogram", xlab = "",
sub = "", cex = 0.6)
# Cut the tree to form 3 clusters
clusters <- cutree(hc_complete, k = 3)
# Print the cluster memberships
print(clusters)
# Add the clusters to the original dataset
iris$Cluster <- as.factor(clusters)
# Display the first few rows of the updated dataset
head(iris)
```

**Output:**



## b) K-Means Clustering

```
# Load the iris dataset
data(iris)
# Use only the numeric columns for clustering (exclude the Species
column)
iris_data <- iris[, -5]
# Standardize the data
iris_scaled <- scale(iris_data)
# Set the number of clusters
set.seed(123) # For reproducibility
k <- 3 # Number of clusters
# Perform K-Means clustering
kmeans_result <- kmeans(iris_scaled, centers = k, nstart = 25)
# Print the K-Means result
print(kmeans_result)
# Print the cluster centers
print(kmeans_result$centers)
# Add the cluster assignments to the original dataset
iris$Cluster <- as.factor(kmeans_result$cluster)
# Display the first few rows of the updated dataset
head(iris)
# Plot the clusters
library(ggplot2)
ggplot(iris, aes(x = Sepal.Length, y = Sepal.Width, color = Cluster)) +
  geom_point(size = 3) +
  labs(title = "K-Means Clustering of Iris Dataset", x = "Sepal Length",
y = "Sepal Width")
```

## Output:

