Due on 2020-03-18, 23:59 IST.

NPTEL » Introduction to algorithms and analysis

1 point

1 point

1 point

Jnit 9 - Week 7
Course outline
How does an NPTEL online course work?
Week 0
Week 1
Week 2
Week 3
Week 4
Week 5
Week 6
Week 7
 Lecture 31 : Fixed universe successor
Lecture 32 : Van Emde Boas data structure
Lecture 33: Amortized analysis
Cecture 34: Computational Geometry
Lecture 35: Computational Geometry (cont)
Week 7: Lecture Notes
O Quiz : Assignment 7
Week 7 Feedback Form Waste 9
Week 8
Week 9
Week 10
Week 11
Week 12
Details Solution
Download videos
Text Transcripts

Assignment 7 The due date for submitting this assignment has passed.

As per our records you have not submitted this assignment. 1) "In an amortized analysis, the time required to perform a sequence

of data-structure operations is summed over all the operations performed". This statement is (a) True

(b) False

○ a.

○ b. No, the answer is incorrect.

Score: 0 Accepted Answers: b.

If red black tree is used to store the dynamic set S in sweep-line algorithm, then the total running time of the algorithm is

(a) $\mathcal{O}(\log n)$

(b) $\mathcal{O}(n \log n)$

(c) O(n)

(d) $\mathcal{O}(\log \log n)$

○ b. ○ c. d.

Score: 0 Accepted Answers:

No, the answer is incorrect.

Suppose we perform a sequence of n operations on a data structure

(a) O(n) (b) $\mathcal{O}(n \log n)$

in which the i^{th} operation costs i if i is an exact power of 2, and 1

otherwise. Using aggregate analysis the amortized cost per operation

(c) O(1) (d) $\mathcal{O}(\log n)$

○ a.

○ d. No, the answer is incorrect.

○ c.

Accepted Answers:

The space complexity of a 2-D range tree is

(b) $\mathcal{O}(\log n)$

No, the answer is incorrect.

(c) $\mathcal{O}(\log \log n)$ (d) $\mathcal{O}(n \log n)$

(a) O(n)

O c. ○ **d**.

○ b.

Accepted Answers:

○ a.

○ b.

Ос.

○ d.

 $\mathcal{O}(\log \log u)$ is the worst case time complexity of

(b) Finding Predecessor in Van Emde Boas Data Structure (c) Inserting into Van Emde Boas Data Structure

(d) All of the above

(a) Finding Successor in Van Emde Boas Data Structure

No, the answer is incorrect.

Accepted Answers:

In Van Emde Boas Data Structure, if size of the universe is 16, how many widgets (blocks) will the universe be split into? (a) 3

(b) 4

(c) 5 (d) 2

○ a. ○ b. ○ c.

○ **d**. No, the answer is incorrect. Score: 0

Accepted Answers:

7) Given the dynamic set $S = \{1, 7, 11, 13\}$ and the size of the universe is 16, What will the call Predecessor(9) return?

(a) 7 (b) 1

(d) 0 ○ a.

(c) 11

○ b. ○ c.

Score: 0 Accepted Answers:

8) A sequence of n insertions into a dynamic table will have a worst case runtime of

(a) $\theta(n \log n)$

○ a. ○ b. ○ c.

Accepted Answers:

Score: 0

(a) 1, 5, 1, 17, 1

and 9^{th} insertion, respectively?

(d) 1, 5, 12, 17, 9

○ b. ○ c.

Accepted Answers:

Score: 0

10) In Table Doubling, to store 56 elements, how many tables will need to

be dynamically allocated?

(d) 9

○ b. ○ c.

(c) 4

Score: 0 Accepted Answers:

○ a.

No, the answer is incorrect.

1 point

○ d. No, the answer is incorrect.

(b) $\theta(n)$ (c) $\theta(1)$ (d) None of these

○ **d**. No, the answer is incorrect.

> (b) 6, 1, 12, 1, 9 (c) 1, 5, 1, 17, 9

In amortized analysis, what will be the cost of insertion of the 6^{th} , 5^{th} , 12^{th} , 17^{th} ,

○ a.

○ d. No, the answer is incorrect.

> (a) 7 (b) 8

 \bigcirc d.