



Configuration

[✎ Improve this page](#)

Jekyll gives you a lot of flexibility to customize how it builds your site.

These options can either be specified in a `_config.yml` or `_config.toml` file placed in your site's root directory, or can be specified as flags for the `jekyll` executable in the terminal.

- [Configuration Options](#)
- [Default Configuration](#)
- [Front Matter Defaults](#)
- [Environments](#)
- [Markdown Options](#)
- [Liquid Options](#)
- [Sass/SCSS Options](#)
- [Webrick Options](#)

GETTING STARTED

- [Quickstart](#)
- [Installation](#)
- [Ruby 101](#)
- [Community](#)
- [Step by Step Tutorial](#)

BUILD

- [Command Line Usage](#)
- [Configuration](#)
- [Rendering Process](#)

CONTENT

- [Pages](#)
- [Posts](#)
- [Front Matter](#)
- [Collections](#)
- [Data Files](#)
- [Assets](#)

- [Incremental Regeneration](#)

[Static Files](#)

SITE STRUCTURE

[Directory Structure](#)

[Liquid](#)

[Variables](#)

[Includes](#)

[Layouts](#)

[Permalinks](#)

[Themes](#)

[Pagination](#)

GUIDES

[Plugins](#)

[Blog Migrations](#)

[Upgrading](#)

[Deployment](#)

Jekyll is lovingly maintained by the core team of volunteers.

The contents of this website are
© 2021 under the terms of the

Proudly hosted by **GitHub**

MIT License.

Jekyll is funded thanks to its sponsors!