

Rajalakshmi Engineering College

Name: Harivarsha s
Email: 240801109@rajalakshmi.edu.in
Roll no:
Phone: 6380939059
Branch: REC
Department: I ECE FA
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Priya is developing a simple student management system. She wants to store roll numbers in a hash table using Linear Probing, and later search for specific roll numbers to check if they exist.

Implement a hash table using linear probing with the following operations:

Insert all roll numbers into the hash table. For a list of query roll numbers, print "Value x: Found" or "Value x: Not Found" depending on whether it exists in the table.

Input Format

The first line contains two integers, n and $table_size$ — the number of roll numbers to insert and the size of the hash table.

The second line contains n space-separated integers — the roll numbers to insert.

The third line contains an integer q — the number of queries.

The fourth line contains q space-separated integers — the roll numbers to search for.

Output Format

The output print q lines — for each query value x, print: "Value x: Found" or "Value x: Not Found"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5 10
21 31 41 51 61
3
31 60 51

Output: Value 31: Found
Value 60: Not Found
Value 51: Found

Answer

```
#include <stdio.h>

#define MAX 100

void initializeTable(int table[], int table_size) {
    for (int i = 0; i < table_size; i++)
        table[i] = -1;
}

void insertIntoHashTable(int table[], int table_size, int arr[], int n) {
    for (int i = 0; i < n; i++) {
        int index = arr[i] % table_size;
        while (table[index] != -1) {
            index = (index + 1) % table_size;
        }
    }
}
```

```

        table[index] = arr[i];
    }
}

int searchInHashTable(int table[], int table_size, int key) {
    int index = key % table_size;
    int start_index = index;
    while (table[index] != -1) {
        if (table[index] == key)
            return 1;
        index = (index + 1) % table_size;
        if (index == start_index)
            break;
    }
    return 0;
}

int main() {
    int n, table_size;
    scanf("%d %d", &n, &table_size);

    int arr[MAX], table[MAX];
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);

    initializeTable(table, table_size);
    insertIntoHashTable(table, table_size, arr, n);

    int q, x;
    scanf("%d", &q);
    for (int i = 0; i < q; i++) {
        scanf("%d", &x);
        if (searchInHashTable(table, table_size, x))
            printf("Value %d: Found\n", x);
        else
            printf("Value %d: Not Found\n", x);
    }

    return 0;
}

```

Status : Correct

Marks : 10/10