

Week-2

1. a) Create and attach an EBS volume to an EC2 instance, and
b) scale the instance by increasing CPU and RAM by changing the instance type.

2. Attach and permanently mount an EBS volume to a Linux EC2 instance to ensure data persistence across reboots.

3. Create a snapshot of the attached EBS volume and use it to create and attach a new volume to an EC2 instance in another AWS region.

1. a) Create and attach an EBS volume to an EC2 instance, and
b) scale the instance by increasing CPU and RAM by changing the instance type.

a) Creating and attaching an EBS volume to an EC2 instance

Step 1: Create a New EBS Volume

Open the EC2 Dashboard.

From the left-hand menu, select Volumes under Elastic Block Store (EBS).

Click Create Volume.

Choose:

Volume type (gp3/gp2)

Size of the volume

Availability Zone (must be the same as the EC2 instance)

Click Create Volume.

Step 2: Attach the EBS Volume to the Existing EC2 Instance

In the Volumes section, select the newly created volume.

Click Actions → Attach Volume.

Select the target EC2 instance from the list.

Specify the device name (example: /dev/xvdf).

Click Attach.

Step 3: Verify the Volume on the EC2 Instance

Connect to the EC2 instance using SSH.

Check the attached disks:

lsblk

Identify the new volume (e.g., /dev/xvdf).

Note: Ensure that the EBS volume and the EC2 instance belong to the **same Availability Zone**, as cross-AZ attachment is not supported.

b)Procedure: increasing/decreasing of CPU and RAM

Step 1. - Navigate to the EC2 dashboard.

Step 2. - Stop the EC2 instance associated with the EBS volume.

Step 3. - Click "Actions" and then—instance settings—change the instance type"Modify Volume".

Step 4. -Increase/ decrease the size or change the volume type to a higher performance specification.

Step 5. - Click "Modify" to apply the changes.

Step 6: Now the start the machine you see with increase /decrease of size and performance

2.Attach and permanently mount an EBS volume to a Linux EC2 instance to ensure data persistence across reboots.

Objective

Attach an additional EBS volume (example: 20 GB) to a Linux EC2 instance and mount it using the **system-default device names** that appear on modern EC2 (Nitro) instances.

Note: Although you select a device name like /dev/xvdf in the AWS Console, the OS typically shows the disk as **NVMe** devices such as /dev/nvme1n1 and partitions as /dev/nvme1n1p1.

Step 1: Create an EBS Volume

1. Log in to **AWS Management Console**
 2. Go to **EC2 → Volumes**
 3. Click **Create volume**
 4. Choose:
 - **Volume type:** gp3 (recommended)
 - **Size:** 20 GB (example)
 - **Availability Zone:** Same AZ as the EC2 instance
 5. Click **Create volume**
-

Step 2: Attach the EBS Volume to EC2

1. Select the newly created EBS volume
2. Click **Actions** → **Attach volume**
3. Choose:
 - **Instance:** Your Linux EC2 instance
 - **Device name (console level):** /dev/xvdf
4. Click **Attach**

Internally, Linux will expose this as an NVMe device (for example /dev/nvme1n1).

Step 3: Connect to the EC2 Instance

Connect using SSH:

```
ssh -i key.pem ec2-user@<public-ip>
```

Step 4: Verify the Attached Disk

List all block devices:

```
lsblk
```

You will typically see:

- Root volume: /dev/nvme0n1 (with partitions like nvme0n1p1)
- New EBS volume: /dev/nvme1n1 (**no partition yet**)

Check filesystem information:

```
lsblk -fs
```

Step 5: Create a Partition on the New Volume

Create a partition on the **unpartitioned disk**:

```
fdisk /dev/nvme1n1
```

Inside fdisk:

- Press **m** → Help menu
- Press **n** → New partition
- Press **p** → Primary partition
- Press **Enter** → Default partition number
- Press **Enter** → Default first sector
- Press **Enter** → Default last sector (use full disk)
- Press **w** → Write changes and exit

Notify the kernel:

```
partprobe
```

Step 6: Verify the New Partition

```
lsblk -fs
```

You should now see:

- `/dev/nvme1n1p1`
-

Step 7: Format the Partition

Format the partition with **XFS** filesystem:

```
mkfs.xfs /dev/nvme1n1p1
```

Verify:

```
lsblk -fs
```

Step 8: Create a Mount Directory

```
mkdir /mnt/archana
```

Step 9: Mount the Volume

```
mount /dev/nvme1n1p1 /mnt/archana
```

Verify:

```
df -h
```

Step 10: Make the Mount Persistent (fstab)

Get the UUID:

```
blkid /dev/nvme1n1p1
```

Example output:

```
UUID="f1e294e6-7657-4761-bba5-bb2d0eab3936"
```

Edit /etc/fstab:

```
nano /etc/fstab
```

Add this line at the end:

```
UUID=f1e294e6-7657-4761-bba5-bb2d0eab3936 /mnt/archana xfs defaults,nofail 0 0
```

Save and exit.

Test the entry:

```
mount -a
```

navigate to cd /mnt/archana

create the files here

```
touch fl
```

Step 11: Verify Persistence

1. Reboot the instance:

```
reboot
```

2. Reconnect and check:

```
df -h
```

➡ The volume should mount automatically.

Step 12: Detach and Reattach Volume (Data Recovery Scenario)

Detach the Volume

- EC2 → Volumes → Select volume
- Actions → Detach volume

Attach to Another EC2 Instance (Same AZ)

1. Attach the volume to a new instance
2. Log in to the new instance
3. Create mount directory:

```
mkdir /mnt/archana
```

4. Mount the existing partition:

```
mount /dev/nvme1n1p1 /mnt/archana
```

✅ All previously stored data will be available.

Summary Flow

Create Volume → Attach → lsblk → fdisk → mkfs → mkdir → mount → fstab → reboot

3. Create a snapshot of the attached EBS volume and use it to create and attach a new volume to an EC2 instance in another AWS region.

Attaching Volumes across regions of EC2 using the snapshot

To create a snapshot of an EBS volume and attach it to an instance in another region in AWS, you'll need to follow these steps:

Step 1. Create a Snapshot:

- a. Sign in to the AWS Management Console.
- b. Navigate to the EC2 Dashboard.

- c. Click on "Volumes" in the left-hand navigation pane.
- d. Select the EBS volume you want to create a snapshot of.
- e. Click on the "Actions" dropdown menu above the volume list and select "Create Snapshot."
- f. Provide a name and description for the snapshot.
- g. Click on the "Create Snapshot" button to initiate the snapshot creation process.

Step 2. Copy the Snapshot to Another Region:

- a. Once the snapshot is created, go to the "Snapshots" section in the EC2 Dashboard.
- b. Select the snapshot you just created.
- c. Click on the "Actions" dropdown menu above the snapshot list and select "Copy Snapshot."
- d. Choose the destination region where you want to copy the snapshot.
- e. Click on the "Copy Snapshot" button to initiate the copy process. This may take some time depending on the size of the snapshot and the network speed.

Step 3. Monitor the Snapshot Copy Progress:

- a. You can monitor the progress of the snapshot copy by navigating to the "Snapshots" section in the EC2 Dashboard of the source region.
- b. Look for the snapshot you copied and check its status. It will change from "pending" to "completed" once the copy process is finished.

Step 4. Switch to the Destination Region:

- a. Use the region selector in the top-right corner of the AWS Management Console to switch to the destination region where you copied the snapshot.

Step 5. Create a Volume from the Snapshot:

- a. In the EC2 Dashboard of the destination region, go to the "Snapshots" section.
- b. Find the snapshot you copied from the source region.
- c. Click on the snapshot, then click on the "Actions" dropdown menu and select "Create Volume."
- d. Configure the volume settings, such as volume type, size, and availability zone.
- e. Click on the "Create Volume" button to create the volume from the snapshot.

Step 6. Create the ec2 instance & Attach the Volume to an Instance:

- a. Once the volume is created, navigate to the "Volumes" section in the EC2 Dashboard.
- b. Find the newly created volume and select it.
- c. Click on the "Actions" dropdown menu and select "Attach Volume."
- d. Select the EC2 instance to which you want to attach the volume and specify the device name.
- e. Click on the "Attach" button to attach the volume to the instance.

We have created a snapshot of an EBS volume, copied it to another region, created a volume from the snapshot, and attached it to an instance in the destination region.

SENARIO BASED QUESTIONS

1. A production database running on EC2 is facing high IOPS latency. Which EBS volume type would you migrate to and why?
2. You are hosting a boot volume for an EC2 instance used only for testing. Which EBS volume type is most cost-effective?
3. An analytics application requires high throughput for large sequential reads. Which EBS volume type should be chosen?
4. Your application workload is unpredictable and needs burst performance occasionally. Which EBS volume fits?
5. You attached an st1 volume to a database server and performance dropped. Why?
6. How do you identify which volume is mounted to /data?
7. After reboot, application fails because volume is missing. Why?
8. Why does manual mount disappear after reboot?
9. How do you auto-mount after reboot?
10. Wrong fstab entry caused emergency mode. What mistake?
11. EC2 terminated but data volume exists. Why?
12. Root volume deleted automatically. Why?
13. How to protect data from accidental EC2 deletion?
14. What happens when EBS is detached?
15. EC2 crashed. How do you restore?
16. Can you create a volume from snapshot while EC2 is running?
17. How does EBS help in DR across regions?
18. Can EBS be attached across regions?
19. What to use for shared storage?
20. How to share snapshot with another account?