

Basic python program---sample

◆ Step 1: aws – services-compute - lamdba

Step 2: Create a New Lambda Function

1. Click **Create function**
 2. Choose **Author from scratch**
 3. Fill the details:
 - **Function name:** basic-python-lambda
 - **Runtime:** Python 3.9 (or latest available)
 - **Architecture:** x86_64
 4. Under **change the default rule:**
 - Select **use the existing rule- Lab Role**
 5. Click **Create function**
-

◆ Step 3: Understand the Default Lambda Code

AWS provides a default Python template:

```
import json
def lambda_handler(event, context):
    return {
        'statusCode': 200,
        'body': json.dumps('Hello from Lambda!')
    }
```

Explanation:

Component	Meaning
event	Input data passed to Lambda
context	Runtime info (memory, request ID, etc.)
lambda_handler	Entry point function
statusCode	HTTP response code
body	Output response

◆ Step 4: Write a Simple Python Lambda Program

Example: Add Two Numbers

```
import json
def lambda_handler(event, context):
    a = event.get('num1', 0)
    b = event.get('num2', 0)
    result = a + b
    return {
        'statusCode': 200,
        'body': json.dumps({
            'sum': result
        })
    }
```

◆ Step 5: Deploy the Function

1. Click **Deploy**

2. Wait for the **Successfully deployed** message

◆ **Step 6: Create a Test Event**

1. Click **Test**
2. Choose **Create new event**
3. Event name: testInput
4. Use this JSON input:

```
{  
  "num1": 10,  
  "num2": 20  
}
```

5. Click **Test**

◆ **Step 7: View Output**

You will see output like:

```
{  
  "statusCode": 200,  
  "body": "{\"sum\": 30}"  
}
```

✓ This means your Lambda executed successfully.

◆ **Step 8: Set General Configuration**

1. Click **General configuration → Edit**
2. Set the following values:

Setting	Value
Memory	128 MB
Timeout	3 seconds
Architecture	x86_64

3. Click **Save**

✓ These values are sufficient for simple arithmetic operations.
