Task Hub
System Guide

A practical guide to scheduled email and ExcelFlow reports

Task Hub is a Windows desktop app that saves recurring email tasks. Users connect an email account, maintain a recipient list, write a reusable message, attach files and choose when the routine should run.

What the current system supports

Gmail and mail-server accounts using IMAP or POP3 for receiving, with SMTP for sending. Google Calendar reminders are optional for Gmail routines. ExcelFlow generates DISC and FTG reports that can be selected for email routines.

Microsoft 365, Microsoft Graph and Outlook Classic integrations are not part of this version. An email address used in Outlook may still work through the supported mail-server connection when its provider supplies compatible settings.

The system flow

1. Connect the sender account in **Connect**.

2. Scan email addresses or add contacts in **Recipients**.

3. Create an **Email routine**: sender, To, CC/BCC, message, attachments and schedule.

4. Task Hub checks due routines while running. A draft-only routine waits for the user to prepare it; an automatic routine sends when due.

5. Check **Email history** for the recorded result.

Before relying on an automatic routine

Use a test routine first. Confirm the sender, recipient addresses, CC/BCC, message, attachment copies and schedule. The app must remain running, including in the system tray, with the computer awake and online. It does not run from the cloud when the computer is off.

This guide describes v0.7.7, including its more compact interface. The page order is: connection and contacts; routine setup; architecture and reports; maintenance and troubleshooting.

1. Connect and manage recipients

Connect an email account

Gmail: choose Google sign-in and authorize the requested features. To scan recipients or read ExcelFlow email sources, enable **Read email addresses and attachments**. Calendar access is a separate option. Reconnect if the required permission was not previously granted. Publisher OAuth setup belongs to the developer; end users use the supplied app configuration when available.

IMAP / POP3: enter the provider's server, port, username, password and encryption settings. Outgoing SMTP settings are needed to send. POP3 supports configured SSL/TLS, STARTTLS or None; None is unencrypted. Use settings confirmed by the mail administrator. Task Hub does not inherit Outlook Control Panel settings automatically.

Recipients page

Click **Scan emails** to read From, To, CC and Reply-To headers from up to 50 recent messages. Gmail includes sent and received mail. IMAP uses the configured folder; POP3 sees messages still on the server. The scan does not read message bodies or attachments, send messages, mark them read or delete them.

Use **Add recipient** for a manual email address and optional name. Search filters the list. Delete removes an address from the saved list; scanning can restore it if it is found again. Deleting a contact does not rewrite existing routines.

Provider tabs and account dropdowns

Saved recipients are separated into **Gmail** and **IMAP / POP3** tabs. Each tab has an account dropdown for connected or previously scanned mailboxes. One address can belong to several scanned accounts. Manual contacts are shared between tabs.

Older contacts without mailbox information appear under **Earlier scans - account unknown**. Rescanning associates matching addresses with the current account. Account filters do not sign in several mailboxes simultaneously; reconnect an earlier account in Connect to scan it again.

Address choices inside a routine

Saved choices match the selected sender's provider and exact scanned mailbox, plus manually added contacts. This applies to To, CC, BCC and replacement recipients. Unknown-account contacts need rescanning. Users can always type an address. Changing sender refreshes the choices but keeps previously entered addresses for the user to review.

2. Set up an email routine

1. Select the **Sender account** and enter a routine name.

2. Choose or type the **Recipient**. Multiple regular recipients can be separated by commas.

3. Optionally choose or type **CC** and **BCC**. Selecting another saved CC/BCC address adds it to that field. BCC recipients are not listed to other recipients.

4. Write the subject and message templates.

5. Use **Add files** to attach the exact files to send.

6. Choose the first date, local time and repeat setting: once, daily, selected weekdays or monthly. Save the routine.

Message templates

Available date fields are **{{month}}**, **{{year}}**, **{{date}}**, **{{previous_month}}** and **{{previous_year}}**. They resolve using the scheduled occurrence. Templates reuse saved text; they do not calculate report figures or interpret document contents.

Attachments

Attachments are saved copies, limited to **10 files and 18 MB total**. Changing the original file later does not update its saved copy. Remove the old attachment and add the revised file. Recipient-file import, report-rule controls and the previous email/file suggestion panel have been removed.

Temporary or permanent recipient changes

Choose **Recipient change**, select or type a replacement address and set its effective date. A temporary change includes its end date and then returns to the regular Recipient. A permanent change applies from its start date onward. The scheduled occurrence date determines the address used. Click **Remove recipient change** and save to clear the override. CC and BCC remain separate fields.

Drafts, automatic sending and calendar reminders

Leave automatic sending off to prepare a draft when ready. Enable **Automatically send when due** to authorize scheduled sending without a later approval click. Keep the routine enabled. For Gmail, optional Calendar sync creates a private reminder in the connected account's primary calendar; it is not the email-sending engine.

Monthly schedules use the last day when a month is shorter. Occurrences more than five minutes late need attention or rescheduling rather than automatic catch-up sending. Never retry an uncertain send before checking the provider's Sent mail and history.

3. Architecture and report workflow

Technology stack

Desktop shell: Tauri 2 and Rust.
Interface: React, TypeScript and CSS, built with Vite.
Mail: Gmail API with Google OAuth; Python mail adapters for IMAP, POP3 and SMTP.
Reports: a bundled Python runtime with the ExcelFlow engine and openpyxl.
Distribution: Windows NSIS installer and signed Tauri update artifacts hosted through GitHub Releases.

How components work together

The React interface gathers inputs and calls registered Tauri commands. Rust validates requests, manages local state, claims scheduled occurrences and records execution history. Gmail operations use the Gmail API. Mail-server and report operations use a bounded JSON request to the bundled Python worker. Task Hub does not execute arbitrary commands found in email.

Routine definitions and execution state are stored locally in **state.json** under the app data directory. The address book and account memberships are included there. Outgoing attachment snapshots are stored in an **attachments** subfolder. OAuth tokens and mail passwords use the app's credential-vault integration, rather than routine message fields.

ExcelFlow

1. Open **ExcelFlow** in the sidebar. Choose the supported DISC/FTG input workbooks or use its connected email source workflow.

2. Select the reporting period and processing options, validate the input and generate reports.

3. Choose the required generated reports for a new or existing email routine, then verify the attachment list and save.

ExcelFlow creates reports; the email routine sends selected saved copies. It does not automatically replace them with next month's files. Customer Ageing / D365 import and Microsoft desktop automation are not part of the current workflow.

Where delivery happens

Gmail creates drafts or submits mail through its API. IMAP can save a draft in the configured Drafts folder. POP3 cannot upload drafts, so the app saves a local .eml draft. SMTP submits mail but does not automatically create a Sent Items copy. BCC is included in the delivery envelope and removed from SMTP wire headers; drafts keep it for the sender's review.

4. Operation, updates and maintenance

Keeping schedules running

Closing the main window keeps Task Hub in the system tray. Reopen or fully quit it from the tray menu. Scheduled delivery requires an awake computer, internet access and a valid account connection. An installed app that has fully quit, or a switched-off computer, cannot send scheduled mail. It does not use a hosted cloud scheduler.

Troubleshooting

Missing contacts: select the correct provider/account tab. Rescan old account-unknown contacts. Routine dropdowns show only the selected sender's scanned addresses plus manual contacts.
Deleted address returns: this is expected after rescanning a message that contains it.
Sign-in rejected: check username, password, protocol and encryption. Read the sanitized server reply; test incoming and outgoing settings separately.
No Sent Items copy: SMTP submission alone does not save one. Check delivery results and the provider before retrying.
Wrong report version: inspect the routine's saved attachment copy; adding a file does not create a live link to the original.

Software releases

Developers commit and test the source, increment matching version fields, build with the existing updater signing key and publish a new versioned GitHub release. Upload the installer, its .sig file, latest.json, SHA256SUMS.txt and release-notes.txt as five separate assets. The ZIP is a delivery convenience, not a substitute for those assets.

The installed app checks the configured update feed for a newer signed version. Local source changes do not update installed copies in real time. Never overwrite a published version or commit the private signing key. Updater signing is separate from Windows publisher/Authenticode signing.

Developer checks and backups

Run the frontend checks, relevant Rust and Python tests, and UI checks after changes. Source development needs the Tauri Windows toolchain, Node.js and Python for building the bundled worker; installer users do not need a separate Python installation. Fully quit the tray app before launching a development copy.

Back up the local app data, required reports and publisher signing key using appropriate protected storage. Check sender accounts, recipient changes, CC/BCC, attachment copies and upcoming dates before each reporting period.

Document basis: local Task Hub 0.7.7 source and release configuration reviewed on 12 November 2026. No production email was sent while updating this guide.