Run | Debug | Stop | Share | Save | { } Beautify | Language C

main.c

```c
#include <stdio.h>
#include <string.h>
int main(void)
{
    int distance;
    char memberStr[16];
    scanf("%d", &distance);
    scanf("%15s", memberStr);
    int isMember = (strcmp(memberStr, "true") == 0 || strcmp(memberStr, "1") == 0);
    int fare = 100;
    if (distance > 10)
        fare += 20 * (distance - 10);
    if (isMember)
        fare = fare - fare / 10;
    printf("Final Fare: \u20B9%d\n", fare);
    return 0;
}
```

input

```
15
true
Final Fare: ₹180


...Program finished with exit code 0
Press ENTER to exit console.
```

3LCAYDKZ3JCAAI4KJUCT7D553KC6BIL...

Run | Debug | Stop | Share | Save | { } Beautify | Language C

main.c

```c
#include <stdio.h>
int main(void)
{
    int answered, remaining, alreadySubmitted;
    scanf("%d %d %d", &answered, &remaining, &alreadySubmitted);
    if (answered >= 1 && remaining > 0 && alreadySubmitted == 0)
        printf("Submission Allowed\n");
    else
        printf("Submission Not Allowed\n");
    return 0;
}
```

input

```
45
12
0
Submission Allowed


...Program finished with exit code 0
Press ENTER to exit console.
```

Run | Debug | Stop | Share | Save | { } Beautify | Language C

main.c

```c
#include <stdio.h>
int main(void)
{
    long long total, x, y;
    scanf("%lld %lld %lld", &total, &x, &y);
    long long longBen = total * x / 100;
    long long remaining = total - longBen;
    long long blackbeard = remaining * y / 100;
    remaining -= blackbeard;
    long long each = remaining / 3;
    printf("%lld\n%lld\n%lld\n", longBen, blackbeard, each);
    return 0;
}
```

input

```
729
65
87
473
222
11


...Program finished with exit code 0
Press ENTER to exit console.
```

Run | Debug | Stop | Share | Save | { } Beautify | Language C

main.c

```c
#include <stdio.h>
int main(void)
{
    int d1, c1, d2, c2;
    scanf("%d %d %d %d", &d1, &c1, &d2, &c2);
    int cents = c1 + c2;
    int dollars = d1 + d2 + cents / 100;
    cents = cents % 100;
    printf("%d\n%d\n", dollars, cents);
    return 0;
}
```

input

```
30
10
140
99
171
9


...Program finished with exit code 0
Press ENTER to exit console.
```

Run | Debug | Stop | Share | Save | { } Beautify | Language C

main.c

```c
#include <stdio.h>
int main(void)
{
    float mileage;
    int petrol, distance;
    scanf("%f %d %d", &mileage, &petrol, &distance);
    if (mileage * petrol >= distance)
        printf("Can reach\n");
    else
        printf("Cannot reach\n");
    return 0;
}
```

input

```
11
6
67
Cannot reach


...Program finished with exit code 0
Press ENTER to exit console.
```

Run | Debug | Stop | Share | Save | { } Beautify | Language C

main.c

```c
#include <stdio.h>
int main() {
    int n, binary[32], i = 0;
    scanf("%d", &n);
    if (n == 0) {
        printf("0");
        return 0;
    }
    while (n > 0) {
        binary[i] = n % 2;
        n = n / 2;
        i++;
    }
    for (int j = i - 1; j >= 0; j--) {
        printf("%d", binary[j]);
    }
    return 0;
}
```

input

```
1010

...Program finished with exit code 0
Press ENTER to exit console.
```

Run | Debug | Stop | Share | Save | { } Beautify | Language C

main.c

```c
#include <stdio.h>
int main(void)
{
    int principal, rate, years;
    scanf("%d %d %d", &principal, &rate, &years);
    double interest = principal * rate * years / 100.0;
    double amount = principal + interest;
    double discount = interest * 0.02;
    double settlement = amount - discount;
    printf("%.2f\n%.2f\n%.2f\n%.2f\n", interest, amount, discount, settlement);
    return 0;
}
```

input

```
100
1
10
10.00
110.00
0.20
109.80


...Program finished with exit code 0
Press ENTER to exit console.
```

Run | Debug | Stop | Share | Save | { } Beautify | Language C

main.c

```c
#include <stdio.h>
int main(void)
{
    int experience, performance;
    scanf("%d %d", &experience, &performance);
    if (experience < 3)
        printf("Level: Junior\n");
    else if (experience <= 7) {
        if (performance >= 80)
            printf("Level: Mid-Level\n");
        else
            printf("Level: Junior\n");
    } else {
        if (performance >= 85)
            printf("Level: Senior\n");
        else if (performance >= 80)
            printf("Level: Mid-Level\n");
        else
            printf("Level: Junior\n");
    }
    return 0;
}
```

input

```
9
88\
Level: Senior


...Program finished with exit code 0
Press ENTER to exit console.
```

Run | Debug | Stop | Share | Save | { } Beautify | Language C

main.c

```c
#include <stdio.h>
int main(void)
{
    int year, month;
    scanf("%d %d", &year, &month);
    if (year < 1900 || year > 9999 || month < 1 || month > 12) {
        printf("0\n");
        return 0;
    }
    int leap = (year % 4 == 0 && year % 100 != 0) || (year % 400 == 0);
    int days;
    switch (month) {
        case 2:
            days = leap ? 29 : 28;
            break;
        case 4: case 6: case 9: case 11:
            days = 30;
            break;
        default:
            days = 31;
    }
    printf("%d Days\n", days);
    return 0;
}
```

input

```
2000
2
29 Days


...Program finished with exit code 0
Press ENTER to exit console.
```