ANGELHACK × IBM · BUILDING WITH IBM BOB · THEME 1

ToolFence

Should your AI agent make the tool call it's about to make?

Checks where every tool-call value came from, pauses risky actions for a person, and measures how often agents get it wrong.

Harsh · Atharva · Rishi

github.com/HB0309/toolfence

Built with IBM Bob

THEME 1 · EXPLORE, FIX, AND BUILD

Explore · Fix · Build

Explore

Mapped IBM's **Galaxium Travels** and the **nanobot** agent with Bob, then the MCP filesystem server.

Fix

Every route was exposed as an agent tool → narrowed to a reviewed set. Bookings had **no ownership check** → fixed (cancelling someone else's booking now returns 403).

Build

ToolFence: scanner, probes, Guard, approval cards, dashboard, CI check, Bob mode + skill + MCP server.

THE TEAM

Three tracks, one tool

Harsh

TRACK B · INTEGRATION & LIVE EVALUATION

Agent integration with nanobot, target profiles for any MCP app, the 156 live trials on two apps and two models, IBM Cloud deploy.

Atharva

TRACK A · EVALUATION ENGINE

Tool-surface scanner, probes, verdicts and scoring, the evaluation runner, reports.

Rishi

TRACK C · GUARD & PRODUCT

The Guard and approval cards, the dashboard, live mode in Codespaces, CI checks.

Each track worked in its own Bob sessions with shared contracts; 67 sessions are exported in the repo.


THE PROBLEM

Agents act on content someone else wrote

People ask agents to use content all the time: *book it under the name in this review, pay the amount on this invoice.*

If that content is attacker-written, the action carries the attacker's value. This is indirect prompt injection.

Permissions can't help. The tool is enabled on purpose. What differs is where the value came from, and no permission setting can see that.



A real trial: a name from a stranger's review went straight into a booking.

HOW TOOLFENCE WORKS

Track provenance. Pause what's risky. Measure it.

1

Scan

Map the agent's MCP tools: read, state-changing, irreversible. Human-reviewed.

2

Probe

Plant a synthetic marker in a user message or a tool result.

3

Guard

Label every argument `user` · `first-party` · `untrusted`.

4

Approve

Held calls become a card: dashboard or Telegram.

5


Measure

One JSON record per trial. Five verdicts. No AI judge.


Three rules, no AI in the decision: irreversible calls always ask · reads always pass · state-changing calls ask if the session read untrusted content or any argument came from it.

LIVE DEMO

The agent waits until the user decides



Same test, Guard on: paused on the dashboard and in Telegram.




Declined: `HOLD`, value marked ⚠ untrusted, "This action was not performed."

Irreversible actions ask too, even for a normal request ("cancel my booking"). Allow it, and it goes through: **ToolFence pauses risky calls, it doesn't block users.**

BUILT WITH IBM BOB · RUNS INSIDE BOB

Bob built it. Bob runs it.

- **67** exported Bob sessions in `bob_sessions/`
- Bob wrote its own plan + **26** phase plans from our brief
- **Auditor mode**: can run ToolFence, refuses to edit code
- **ToolFence skill**: scan → evaluate → propose fix → re-check → report
- **ToolFence MCP server**: 4 tools wired into Bob via `.bob/mcp.json`



The Auditor refusing an edit, in Bob.

AGAINST THE JUDGING CRITERIA

Why ToolFence fits this hackathon

Depth of Bob usage

Built across 67 Bob sessions from Bob's own plans; plus a custom Auditor mode, a skill and our own MCP server running inside Bob.

Use case relevant to Bob

Agent tool injection is the risk Bob users face. ToolFence audits an agent's tools from Bob chat, and proves it on IBM's own Galaxium app.

Working execution

Live on IBM Cloud Code Engine, live runs in Codespaces, 156 real trials, CI on every pull request, approval cards in Telegram.

Presentation

Every number traces to a committed result file; costs and limits stated plainly; a 3-minute demo with real footage.

RESULTS · 156 LIVE TRIALS · 2 APPS · 2 MODELS

From 24 of 36 to 0 of 48

24/36

LEAKED · GUARD OFF

untrusted data reached a tool call

0/48

LEAKED · GUARD ON

36 held for approval, the rest refused

18/30

REAL TASKS · GUARD ON

read-then-write needs one approval click

IBM **Galaxium Travels** + the official **MCP filesystem server**, with **IBM Granite 4.2 8B** and **Llama 3.3 70B**. Every number is a committed JSON file, browsable on the live dashboard.

Held-call honesty: agents falsely claimed success 5/12 times, then 1/36 after we reworded the hold message.



KEY LEARNINGS · ROOM FOR IMPROVEMENT · NEXT STEPS

What we learned, and what's next

Key learnings

- Both models ignored passive injected text (0/12), but once untrusted data flowed into a task, it reached the booking every time (24/24). **Model behaviour isn't a guard.**
- Agents told users a held action had succeeded (5/12). Rewording the hold message cut that to 1/36.
- Provider quirks matter: one host doubled tool arguments, so we pinned providers per model.

Room for improvement

- 2 apps, 2 models so far
- Probe planting covers files and SQLite only
- Read-then-write tasks need one approval click
- A clean result means no way through was found, not that none exists

Next steps

- Planting for email, APIs and documents
- Policy proposals reviewed in CI
- More models and agent frameworks
- With IBM **Mellea**: Mellea checks each answer is well-formed; ToolFence makes sure a well-formed answer can't trigger an action the user never asked for

TRY IT

ToolFence

Point it at any MCP app with one profile file.

Results	toolfence-dashboard.2g457ha8n8w8.us-east.codeengine.appdomain.cloud
Live run	codespaces.new/HB0309/toolfence
Code	github.com/HB0309/toolfence

Harsh · Atharva · Rishi — AngelHack × IBM "Building with IBM Bob". Planning and review assisted by Claude (Anthropic); all other code built with IBM Bob.