



1. Description

1.1. Project

Project Name	STM32H735G-DK
Board Name	custom
Generated with:	STM32CubeMX 6.12.0
Date	08/13/2024


1.2. MCU

MCU Series	STM32H7
MCU Line	STM32H725/735
MCU name	STM32H735IGKx
MCU Package	UFBGA176
MCU Pin number	201

1.3. Core(s) information

Core(s)	Arm Cortex-M7
---------	---------------

2. Pinout Configuration



UFBGA176 +25 (Top view)

3. Pins Configuration

Pin Number UFBGA176	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
A1	VSS	Power		
A2	PB8	I/O	LTDC_B6	
A3	VDDLDO	Power		
A4	VCAP	Power		
A7	PG11	I/O	OCTOSPIM_P2_IO7	
A8	PG9	I/O	OCTOSPIM_P1_IO6	
A9	PD3	I/O	LTDC_G7	
A12	PA14(JTCK/SWCLK)	I/O	DEBUG_JTCK-SWCLK	
A13	VDDLDO	Power		
A14	VCAP	Power		
A15	VSS	Power		
B3	PB9	I/O	LTDC_B7	
B4	PE0	I/O	LTDC_R0	
B8	PD7	I/O	OCTOSPIM_P1_IO7	
B9	PD5	I/O	OCTOSPIM_P1_IO5	
B13	PA13(JTMS/SWDIO)	I/O	DEBUG_JTMS-SWDIO	
B14	PA8	I/O	LTDC_B3	
C2	VSS	Power		
C3	PE2	I/O	OCTOSPIM_P1_IO2	
C4	PE1	I/O	LTDC_R6	
C5	BOOT0	Boot		
C7	PG14	I/O	LTDC_B0	
C8	PG10	I/O	OCTOSPIM_P2_IO6	
C9	PD4	I/O	OCTOSPIM_P1_IO4	
C10	PD0	I/O	LTDC_B1	
D4	PDR_ON	Power		
D5	VDD	Power		
D6	VSS	Power		
D7	PG15 *	I/O	GPIO_Output	LCD_BL_CTRL
D8	PG12	I/O	OCTOSPIM_P2_NCS	
D9	PD6	I/O	LTDC_B2	
D10	VSS	Power		
D11	VDD	Power		
D12	PH15	I/O	LTDC_G4	
D15	PC7	I/O	LTDC_G6	
E1	VSS	Power		


Pin Number UFBGA176	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
E2	VBAT	Power		
E4	VDD	Power		
E12	VDD	Power		
E14	PC6	I/O	LTDC_HSYNC	
E15	VDD50USB	Power		
F1	VLXSMPS	Power		
F2	VSSMPS	Power		
F3	PF1	I/O	OCTOSPIM_P2_IO1	
F4	PF0	I/O	OCTOSPIM_P2_IO0	
F6	VSS	Power		
F7	VSS	Power		
F8	VSS	Power		
F9	VSS	Power		
F10	VSS	Power		
F12	VSS	Power		
F13	VDD33USB	Power		
F14	PG6	I/O	OCTOSPIM_P1_NCS	
G1	VDDSMPS	Power		
G2	VFBSMPS	Power		
G3	PF2	I/O	OCTOSPIM_P2_IO2	
G4	VDD	Power		
G6	VSS	Power		
G7	VSS	Power		
G8	VSS	Power		
G9	VSS	Power		
G10	VSS	Power		
G13	PG7	I/O	LTDC_CLK	
H2	PF4	I/O	OCTOSPIM_P2_CLK	
H4	PF3	I/O	OCTOSPIM_P2_IO3	
H6	VSS	Power		
H7	VSS	Power		
H8	VSS	Power		
H9	VSS	Power		
H10	VSS	Power		
H12	VDD	Power		
H13	PG3 *	I/O	GPIO_Output	RENDER_TIME
H15	PD13	I/O	OCTOSPIM_P1_IO3	
J1	PH0-OSC_IN	I/O	RCC_OSC_IN	
J6	VSS	Power		

Pin Number UFBGA176	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
J7	VSS	Power		
J8	VSS	Power		
J9	VSS	Power		
J10	VSS	Power		
J13	PD11	I/O	OCTOSPIM_P1_IO0	
J14	VSS	Power		
J15	PD12	I/O	OCTOSPIM_P1_IO1	
K1	PH1-OSC_OUT	I/O	RCC_OSC_OUT	
K2	VSS	Power		
K3	PF10	I/O	OCTOSPIM_P1_CLK	
K4	VDD	Power		
K6	VSS	Power		
K7	VSS	Power		
K8	VSS	Power		
K9	VSS	Power		
K10	VSS	Power		
K12	VSS	Power		
K14	PB15 *	I/O	GPIO_Output	MCU_ACTIVE
K15	PB14 *	I/O	GPIO_Output	FRAME_RATE
L1	NRST	Reset		
L4	VREF-	Power		
L12	VDD	Power		
L13	PD10 *	I/O	GPIO_Output	LCD_DISP
M4	VDDA	Power		
M5	VDD	Power		
M6	VSS	Power		
M8	PB1	I/O	LTDC_G0	
M9	VDD	Power		
M10	VSS	Power		
M13	PH11	I/O	LTDC_R5	
M14	PH9	I/O	LTDC_R3	
N3	VSSA	Power		
N5	PA3	I/O	LTDC_B5	
N9	PG1	I/O	OCTOSPIM_P2_IO5	
N13	PH8	I/O	LTDC_R2	
N14	PH10	I/O	LTDC_R4	
P1	PA0 *	I/O	GPIO_Output	VSYSN_FREQ
P4	PH4	I/O	LTDC_G5	
P5	PA4	I/O	LTDC_VSYN	

Pin Number UFBGA176	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
P7	PB2	I/O	OCTOSPIM_P1_DQS	
P8	PG0	I/O	OCTOSPIM_P2_IO4	
P11	PF12	I/O	OCTOSPIM_P2_DQS	
P12	PE12	I/O	LTDC_B4	
P13	PE13	I/O	LTDC_DE	
P14	PE15	I/O	LTDC_R7	
R1	VSS	Power		
R4	PH3	I/O	LTDC_R1	
R7	PA6	I/O	LTDC_G2	
R8	PB0	I/O	LTDC_G1	
R12	PE11	I/O	LTDC_G3	
R13	VCAP	Power		
R14	VDDLDO	Power		
R15	VSS	Power		

* The pin is affected with an I/O function

4. Clock Tree Configuration



1. Power Consumption Calculator report

1.1. Microcontroller Selection

Series	STM32H7
Line	STM32H725/735
MCU	STM32H735IGKx
Datasheet	DS13312_Rev1

1.2. Parameter Selection

Temperature	25
Vdd	3.0

1.3. Battery Selection

Battery	Alkaline(9V)
Capacity	625.0 mAh
Self Discharge	0.3 %/month
Nominal Voltage	9.0 V
Max Cont Current	200.0 mA
Max Pulse Current	0.0 mA
Cells in series	1
Cells in parallel	1


1.4. Sequence

Step	Step1	Step2
Mode	RUN	STOP
Vdd	3.0	3.0
Voltage Source	Battery	Battery
Range	VOS0: Scale0/Boost	SVOS3: System-Scale3/SMPS-LDO
D1 Mode	DRUN	DSTANDBY
D2 Mode	DRUN	DSTANDBY
D3 Mode	DRUN	DSTOP
Fetch Type	SRAM1/FlashMode-ON/Cache	NA
CPU Frequency	550 MHz	0 Hz
Clock Configuration	HSE BYP PLL	LSE LowDrive RTC
Clock Source Frequency	8 MHz	32.768 kHz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	150 mA	2.5 μ A
Duration	0.1 ms	0.9 ms
DMIPS	1177.0	0.0
Ta Max	107.9	125
Category	In DS Table	In DS Table

1.5. Results

Sequence Time	1 ms	Average Current	15 mA
Battery Life	1 day, 17 hours	Average DMIPS	1177.0 DMIPS

1.6. Chart



2. Software Project

2.1. Project Settings

Name	Value
Project Name	STM32H735G-DK
Project Folder	C:\ProjectsOnC\PhasorRadio\CustomSTM32H735Board\CustomSTM32H735Tes
Toolchain / IDE	STM32CubeIDE
Firmware Package Name and Version	STM32Cube FW_H7 V1.11.2
Application Structure	Advanced
Generate Under Root	No
Do not generate the main()	No
Minimum Heap Size	0x1000
Minimum Stack Size	0x1000

2.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Copy only the necessary library files
Generate peripheral initialization as a pair of '.c/.h' files	No
Backup previously generated files when re-generating	No
Keep User Code when re-generating	Yes
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power consumption)	No
Enable Full Assert	No

2.3. Advanced Settings - Generated Function Calls

Rank	Function Name	Peripheral Instance Name
1	MX_GPIO_Init	GPIO
2	SystemClock_Config	RCC
3	MX_CRC_Init	CRC
4	MX_DMA2D_Init	DMA2D
5	MX_LTDC_Init	LTDC
6	MX_OCTOSPI1_Init	OCTOSPI1
7	MX_OCTOSPI2_Init	OCTOSPI2
8	MX_LIBJPEG_Init	LIBJPEG
10	MX_TouchGFX_Init	STMicroelectronics.X-CUBE-TOUCHGFX.4.23.0
11	MX_TouchGFX_Process	STMicroelectronics.X-CUBE-TOUCHGFX.4.23.0

3. Peripherals and Middlewares Configuration

3.1. CORTEX_M7

3.1.1. Parameter Settings:

Speculation default mode Settings:

Speculation default mode Disabled

Cortex Interface Settings:

CPU ICache Enabled *

CPU DCache Enabled *

Cortex Memory Protection Unit Control Settings:

MPU Control Mode Background Region Privileged accesses only + MPU Disabled during hard fault, NMI and FAULTMASK handlers *

Cortex Memory Protection Unit Region 0 Settings:

MPU Region Enabled *

MPU Region Base Address 0x24000000 *

MPU Region Size 512KB *

MPU SubRegion Disable 0x0 *

MPU TEX field level level 0

MPU Access Permission ALL ACCESS PERMITTED *

MPU Instruction Access DISABLE *

MPU Shareability Permission DISABLE

MPU Cacheable Permission ENABLE *

MPU Bufferable Permission ENABLE *

Cortex Memory Protection Unit Region 1 Settings:

MPU Region Enabled *

MPU Region Base Address 0x70000000 *

MPU Region Size 512MB *

MPU SubRegion Disable 0x0 *

MPU TEX field level level 0

MPU Access Permission ALL ACCESS NOT PERMITTED

MPU Instruction Access DISABLE *

MPU Shareability Permission DISABLE

MPU Cacheable Permission DISABLE

MPU Bufferable Permission DISABLE

Cortex Memory Protection Unit Region 2 Settings:

MPU Region Enabled *

MPU Region Base Address 0x70000000 *

MPU Region Size	8MB *
MPU SubRegion Disable	0x0 *
MPU TEX field level	level 0
MPU Access Permission	ALL ACCESS PERMITTED *
MPU Instruction Access	DISABLE *
MPU Shareability Permission	DISABLE
MPU Cacheable Permission	ENABLE *
MPU Bufferable Permission	ENABLE *

Cortex Memory Protection Unit Region 3 Settings:

MPU Region	Enabled *
MPU Region Base Address	0x90000000 *
MPU Region Size	512MB *
MPU SubRegion Disable	0x0 *
MPU TEX field level	level 0
MPU Access Permission	ALL ACCESS NOT PERMITTED
MPU Instruction Access	DISABLE *
MPU Shareability Permission	DISABLE
MPU Cacheable Permission	DISABLE
MPU Bufferable Permission	DISABLE

Cortex Memory Protection Unit Region 4 Settings:

MPU Region	Enabled *
MPU Region Base Address	0x90000000 *
MPU Region Size	64MB *
MPU SubRegion Disable	0x0 *
MPU TEX field level	level 0
MPU Access Permission	ALL ACCESS PERMITTED *
MPU Instruction Access	DISABLE *
MPU Shareability Permission	DISABLE
MPU Cacheable Permission	ENABLE *
MPU Bufferable Permission	DISABLE

Cortex Memory Protection Unit Region 5 Settings:

MPU Region	Disabled
------------	----------

Cortex Memory Protection Unit Region 6 Settings:

MPU Region	Disabled
------------	----------

Cortex Memory Protection Unit Region 7 Settings:

MPU Region	Disabled
------------	----------

Cortex Memory Protection Unit Region 8 Settings:

MPU Region	Disabled
------------	----------

Cortex Memory Protection Unit Region 9 Settings:

MPU Region Disabled

Cortex Memory Protection Unit Region 10 Settings:

MPU Region Disabled

Cortex Memory Protection Unit Region 11 Settings:

MPU Region Disabled

Cortex Memory Protection Unit Region 12 Settings:

MPU Region Disabled

Cortex Memory Protection Unit Region 13 Settings:

MPU Region Disabled

Cortex Memory Protection Unit Region 14 Settings:

MPU Region Disabled

Cortex Memory Protection Unit Region 15 Settings:

MPU Region Disabled

3.2. CRC

mode: Activated

3.2.1. Parameter Settings:

Basic Parameters:

Default Polynomial State Enable

Default Init Value State Enable

Advanced Parameters:

Input Data Inversion Mode None

Output Data Inversion Mode Disable

Input Data Format Bytes

3.3. DEBUG

Debug: Serial Wire

3.4. DMA2D

mode: Activated

3.4.1. Parameter Settings:

Basic Parameters:

Transfer Mode Register to Memory *

Color Mode	RGB888 *
Output Offset	0

3.5. LTDC

Display Type: RGB888 (24 bits)

3.5.1. Parameter Settings:

Synchronization for Width:

Horizontal Synchronization Width	41 *
Horizontal Back Porch	13 *
Active Width	480 *
Horizontal Front Porch	32 *
HSync Width	40
Accumulated Horizontal Back Porch Width	53
Accumulated Active Width	533
Total Width	565

Synchronization for Height:

Vertical Synchronization Height	10 *
Vertical Back Porch	2
Active Height	272 *
Vertical Front Porch	2
VSyn Height	9
Accumulated Vertical Back Porch Height	11
Accumulated Active Height	283
Total Height	285

Signal Polarity:

Horizontal Synchronization Polarity	Active Low
Vertical Synchronization Polarity	Active Low
Data Enable Polarity	Active Low
Pixel Clock Polarity	Normal Input

Layer Default Color:

Red	0
Green	0
Blue	0

3.5.2. Layer Settings:

Layer Default Color:

Layer 0 - Alpha	0
Layer 0 - Blue	0
Layer 0 - Green	0
Layer 0 - Red	0

Number of Layers:

Number of Layers	1 layer *
------------------	------------------

Windows Position:

Layer 0 - Window Horizontal Start	0
Layer 0 - Window Horizontal Stop	480 *
Layer 0 - Window Vertical Start	0
Layer 0 - Window Vertical Stop	272 *

Pixel Parameters:

Layer 0 - Pixel Format	RGB888 *
------------------------	-----------------

Blending:

Layer 0 - Alpha constant for blending	255 *
Layer 0 - Blending Factor1	Alpha constant
Layer 0 - Blending Factor2	Alpha constant

Frame Buffer:

Layer 0 - Color Frame Buffer Start Address	0x70000000 *
Layer 0 - Color Frame Buffer Line Length (Image Width)	480 *
Layer 0 - Color Frame Buffer Number of Lines (Image Height)	272 *

3.6. MEMORYMAP

mode: Activated

3.7. OCTOSPI1

Mode: Octo SPI

Clock: Port1 CLK

Chip Select: Port1 NCS

Data Strobe: Port1 DQS (RWDS)

Data [3:0]: Port1 IO[3:0]

Data [7:4]: Port1 IO[7:4]

3.7.1. Parameter Settings:

Generic:

Fifo Threshold	4 *
Dual Quad mode	Disable
Memory Type	Macronix *
Device Size	32
Device Type	Not defined
Chip Select High Time	2 *
Free Running Clock	Disable
Clock Mode	Low
Wrap Size	Not Supported
Clock Prescaler	2 *
Sample Shifting	None
Delay Hold Quarter Cycle	Disable
Chip Select Boundary	0
Delay Block	Disable
Maximum Transfer	0
Refresh Rate	0

3.8. OCTOSPI2

Mode: HyperBus(TM)

Clock: Port2 CLK

Chip Select: Port2 NCS

Data Strobe: Port2 DQS (RWDS)

Data [3:0]: Port2 IO[3:0]

Data [7:4]: Port2 IO[7:4]

3.8.1. Parameter Settings:

Generic:

Fifo Threshold	4 *
Dual Quad mode	Disable
Memory Type	HyperBus(TM)
Device Size	24 *
Device Type	Not defined
Chip Select High Time	4 *
Free Running Clock	Disable
Clock Mode	Low
Wrap Size	Not Supported
Clock Prescaler	2 *
Sample Shifting	None

Delay Hold Quarter Cycle	Enable *
Chip Select Boundary	23 *
Delay Block	Enable *
Maximum Transfer	0
Refresh Rate	400 *
HyperBus(TM):	
RW Recovery Time	3 *
Access Time	6 *
Write Access Latency	Enable *
Latency Mode	Fixed *

3.9. RCC

High Speed Clock (HSE): Crystal/Ceramic Resonator

3.9.1. Parameter Settings:

Power Parameters:

SupplySource	PWR_DIRECT_SMPS_SUPPLY
Power Regulator Voltage Scale	Power Regulator Voltage Scale 0

RCC Parameters:

TIM Prescaler Selection	Disabled
HSE Startup Timeout Value (ms)	100
LSE Startup Timeout Value (ms)	5000
CSI Calibration Value	16
HSI Calibration Value	64

System Parameters:

VDD voltage (V)	3.3
Flash Latency(WS)	3 WS (4 CPU cycle)

PLL range Parameters:

PLL1 input frequency range	Between 8 and 16 MHz
PLL2 input frequency range	Between 4 and 8 MHz
PLL3 input frequency range	Between 1 and 2 MHz
PLL1 clock Output range	Wide VCO range
PLL2 clock Output range	Wide VCO range
PLL3 clock Output range	MEDIUM VCO range

3.10. SYS

Timebase Source: TIM6

3.11. FREERTOS

Interface: CMSIS_V2

3.11.1. Config parameters:

API:

FreeRTOS API CMSIS v2

Versions:

FreeRTOS version 10.3.1

CMSIS-RTOS version 2.00

MPU/FPU:

ENABLE_MPU Disabled

ENABLE_FPU Disabled

Kernel settings:

USE_PREEMPTION Enabled

CPU_CLOCK_HZ SystemCoreClock

TICK_RATE_HZ 1000

MAX_PRIORITIES 56

MINIMAL_STACK_SIZE 128

MAX_TASK_NAME_LEN 16

USE_16_BIT_TICKS Disabled

IDLE_SHOULD_YIELD Enabled

USE_MUTEXES Enabled

USE_RECURSIVE_MUTEXES Enabled

USE_COUNTING_SEMAPHORES Enabled

QUEUE_REGISTRY_SIZE 8

USE_APPLICATION_TASK_TAG **Enabled ***

ENABLE_BACKWARD_COMPATIBILITY Enabled

USE_PORT_OPTIMISED_TASK_SELECTION Disabled

USE_TICKLESS_IDLE Disabled

USE_TASK_NOTIFICATIONS Enabled

RECORD_STACK_HIGH_ADDRESS Disabled

Memory management settings:

Memory Allocation Dynamic / Static

TOTAL_HEAP_SIZE **75000 ***

Memory Management scheme heap_4

Hook function related definitions:

USE_IDLE_HOOK **Enabled ***

USE_TICK_HOOK	Disabled
USE_MALLOC_FAILED_HOOK	Disabled
USE_DAEMON_TASK_STARTUP_HOOK	Disabled
CHECK_FOR_STACK_OVERFLOW	Disabled

Run time and task stats gathering related definitions:

GENERATE_RUN_TIME_STATS	Disabled
USE_TRACE_FACILITY	Enabled
USE_STATS_FORMATTING_FUNCTIONS	Disabled

Co-routine related definitions:

USE_CO_ROUTINES	Disabled
MAX_CO_ROUTINE_PRIORITIES	2

Software timer definitions:

USE_TIMERS	Enabled
TIMER_TASK_PRIORITY	2
TIMER_QUEUE_LENGTH	10
TIMER_TASK_STACK_DEPTH	256

Interrupt nesting behaviour configuration:

LIBRARY_LOWEST_INTERRUPT_PRIORITY	15
LIBRARY_MAX_SYSCALL_INTERRUPT_PRIORITY	5

Added with 10.2.1 support:

MESSAGE_BUFFER_LENGTH_TYPE	size_t
USE_POSIX_ERRNO	Disabled

CMSIS-RTOS V2 flags:

USE_OS2_THREAD_SUSPEND_RESUME	Enabled
USE_OS2_THREAD_ENUMERATE	Enabled
USE_OS2_EVENTFLAGS_FROM_ISR	Enabled
USE_OS2_THREAD_FLAGS	Enabled
USE_OS2_TIMER	Enabled
USE_OS2_MUTEX	Enabled

3.11.2. Include parameters:

Include definitions:

vTaskPrioritySet	Enabled
uxTaskPriorityGet	Enabled
vTaskDelete	Enabled
vTaskCleanUpResources	Disabled
vTaskSuspend	Enabled
vTaskDelayUntil	Enabled
vTaskDelay	Enabled
xTaskGetSchedulerState	Enabled

mode: GraphicsJjApplication

3.13.1. TouchGFX Generator:

Display:

Interface

Framebuffer Pixel Format (LTDC)

Width (LTDC)

Height (LTDC)

Framebuffer Strategy

Buffer Location

Driver:

Application Tick Source

Use DMA2D Accelerator (ChromART)

Real-Time Operating System

Additional Features:

Vector Rendering

Vector Font Rendering

Video Decoding:

Type

Concurrent videos

Strategy

Decode Format

Buffer Width

Buffer Height

Parallel RGB (LTDC) *

RGB888

480

272

Double Buffer *

By Allocation

LTDC *

Yes *

CMSIS_RTOS_V2

Software *

Enabled *

Software *

1

Single buffer *

RGB888 *

480 *

272 *

* User modified value

4. System Configuration

4.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
DEBUG	PA14(JTCK/SWCLK)	DEBUG_JTCK-SWCLK	n/a	n/a	n/a	
	PA13(JTMS/SWDIO)	DEBUG_JTMS-SWDIO	n/a	n/a	n/a	
LTDC	PB8	LTDC_B6	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PD3	LTDC_G7	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PB9	LTDC_B7	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PE0	LTDC_R0	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PA8	LTDC_B3	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PE1	LTDC_R6	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PG14	LTDC_B0	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PD0	LTDC_B1	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PD6	LTDC_B2	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PH15	LTDC_G4	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PC7	LTDC_G6	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PC6	LTDC_HSYNC	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PG7	LTDC_CLK	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PB1	LTDC_G0	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PH11	LTDC_R5	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
	PH9	LTDC_R3	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PA3	LTDC_B5	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PH8	LTDC_R2	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PH10	LTDC_R4	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PH4	LTDC_G5	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PA4	LTDC_VSYNC	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PE12	LTDC_B4	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PE13	LTDC_DE	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PE15	LTDC_R7	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PH3	LTDC_R1	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PA6	LTDC_G2	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PB0	LTDC_G1	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
	PE11	LTDC_G3	Alternate Function Push Pull	No pull-up and no pull-down	Very High *	
OCTOSPI1	PG9	OCTOSPIM_P1_IO6	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PD7	OCTOSPIM_P1_IO7	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PD5	OCTOSPIM_P1_IO5	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PE2	OCTOSPIM_P1_IO2	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PD4	OCTOSPIM_P1_IO4	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PG6	OCTOSPIM_P1_NCS	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PD13	OCTOSPIM_P1_	Alternate Function Push Pull	No pull-up and no pull-down	Very High	

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
		IO3				
	PD11	OCTOSPIM_P1_IO0	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PD12	OCTOSPIM_P1_IO1	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PF10	OCTOSPIM_P1_CLK	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PB2	OCTOSPIM_P1_DQS	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
OCTOSPI2	PG11	OCTOSPIM_P2_IO7	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PG10	OCTOSPIM_P2_IO6	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PG12	OCTOSPIM_P2_NCS	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PF1	OCTOSPIM_P2_IO1	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PF0	OCTOSPIM_P2_IO0	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PF2	OCTOSPIM_P2_IO2	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PF4	OCTOSPIM_P2_CLK	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PF3	OCTOSPIM_P2_IO3	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PG1	OCTOSPIM_P2_IO5	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PG0	OCTOSPIM_P2_IO4	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PF12	OCTOSPIM_P2_DQS	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
RCC	PH0-OSC_IN	RCC_OSC_IN	n/a	n/a	n/a	
	PH1-OSC_OUT	RCC_OSC_OUT	n/a	n/a	n/a	
GPIO	PG15	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LCD_BL_CTRL
	PG3	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Very High *	RENDER_TIME
	PB15	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Very High *	MCU_ACTIVE
	PB14	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Very High *	FRAME_RATE
	PD10	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LCD_DISP

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
	PA0	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Very High *	VSYNC_FREQ

4.2. DMA configuration

nothing configured in DMA service

4.3. BDMA configuration

nothing configured in DMA service

4.4. MDMA configuration

nothing configured in DMA service

4.5. NVIC configuration

4.5.1. NVIC

Interrupt Table	Enable	Preenmption Priority	SubPriority
Non maskable interrupt	true	0	0
Hard fault interrupt	true	0	0
Memory management fault	true	0	0
Pre-fetch fault, memory access fault	true	0	0
Undefined instruction or illegal state	true	0	0
System service call via SWI instruction	true	0	0
Debug monitor	true	0	0
Pendable request for system service	true	15	0
System tick timer	true	15	0
TIM6 global interrupt, DAC1_CH1 and DAC1_CH2 underrun error interrupts	true	0	0
LTDC global interrupt	true	5	0
DMA2D global interrupt	true	5	0
PVD/AVD through EXTI Line detection Interrupt	unused		
Flash global interrupt	unused		
RCC global interrupt	unused		
FPU global interrupt	unused		
LTDC Error global Interrupt	unused		
OCTOSPI1 global interrupt	unused		
HSEM1 global interrupt	unused		
OCTOSPI2 global interrupt	unused		

4.5.2. NVIC Code generation

Enabled interrupt Table	Select for init sequence ordering	Generate IRQ handler	Call HAL handler
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false
Pre-fetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false
System service call via SWI instruction	false	false	false
Debug monitor	false	true	false
Pendable request for system service	false	false	false
System tick timer	false	false	true
TIM6 global interrupt, DAC1_CH1 and DAC1_CH2 underrun error interrupts	false	true	true
LTDC global interrupt	false	true	true

Enabled interrupt Table	Select for init sequence ordering	Generate IRQ handler	Call HAL handler
DMA2D global interrupt	false	true	true

* User modified value

5. System Views

5.1. Category view

5.1.1. Current

Middleware

FREERTOS ✓

LIBJPEG ✓

Software Packs

X-CUBE-TOUCHGFX ✓

System Core	Analog	Timers	Connectivity	Multimedia	Security	Computing	Trace and Debug	Power and Thermal	Other
<div>BDMA</div>			<div>OCTOSPI1 ✓</div>	<div>DMA2D ✓</div>		<div>CRC ✓</div>	<div>DEBUG ✓</div>		
<div>CORTEX_M7 ✓</div>			<div>OCTOSPI2 ✓</div>	<div>LTDC ✓</div>					
<div>DMA</div>									
<div>GPIO ✓</div>									
<div>MDMA</div>									
<div>NVIC ✓</div>									
<div>RCC ✓</div>									
<div>SYS ✓</div>									

6. Software Pack Report

6.1. Software Pack selected

Vendor	Name	Version	Component
STMicroelectronics	X-CUBE-TOUCHGFX	4.23.0	Class : Graphics Group : Application Variant : TouchGFX Generator Version : 4.23.0

7. Docs & Resources

Type	Link
BSDL files	https://www.st.com/resource/en/bsdl_model/stm32h7_bsd1.zip
IBIS models	https://www.st.com/resource/en/ibis_model/stm32h7_ibis.zip
System View Description	https://www.st.com/resource/en/svd/stm32h7-svd.zip
System View Description	https://www.st.com/resource/en/svd/stm32h7rs-svd.zip
Presentations	https://www.st.com/resource/en/product_presentation/microcontrollers_stm32h7_series_product_overview.pdf
Presentations	https://www.st.com/resource/en/product_presentation/stm32-stm8_embedded_software_solutions.pdf
Presentations	https://www.st.com/resource/en/product_presentation/stm32_eval-tools_portfolio.pdf
Presentations	https://www.st.com/resource/en/product_presentation/stm32_stm8_functional-safety-packages.pdf
Presentations	https://www.st.com/resource/en/product_presentation/stm32-stm8_software_development_tools.pdf
Presentations	https://www.st.com/resource/en/product_presentation/microcontrollers_stm32h72x-3x_line_product-overview.pdf
Presentations	https://www.st.com/resource/en/product_presentation/microcontrollers-stm32-family-overview.pdf
Presentations	https://www.st.com/resource/en/product_presentation/microcontrollers-stm32h7rs-lines-overview.pdf
Brochures	https://www.st.com/resource/en/brochure/brstm32h7.pdf
Brochures	https://www.st.com/resource/en/brochure/products-and-solutions-for-plcs-and-smart-i-os.pdf
Flyers	https://www.st.com/resource/en/flyer/flstm32nucleo.pdf
Flyers	https://www.st.com/resource/en/flyer/flstm32trust.pdf
Flyers	https://www.st.com/resource/en/flyer/flstm32h7rs.pdf
Application Notes	https://www.st.com/resource/en/application_note/an1709-emc-design-

guide-for-stm8-stm32-and-legacy-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2606-stm32-microcontroller-system-memory-boot-mode-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2639-soldering-recommendations-and-package-information-for-leadfree-ecopack-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3126-audio-and-waveform-generation-using-the-dac-in-stm32-products-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3155-usart-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3156-usb-dfu-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4221-i2c-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4229-how-to-implement-a-vocoder-solution-using-stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4286-spi-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4566-extending-the-dac-performance-of-stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4655-virtually-increasing-the-number-of-serial-communication-peripherals-in-stm32-applications-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4750-handling-of-soft-errors-in-stm32-applications-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4776-generalpurpose-timer-cookbook-for-stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4803-highspeed-si-simulations-using-ibis-and-boardlevel-simulations-using-hyperlynx-si-on-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4839-level-1-cache-

on-stm32f7-series-and-stm32h7-series-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4891-stm32h72x-stm32h73x-and-singlecore-stm32h74x75x-system-architecture-and-performance-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4989-stm32-microcontroller-debug-toolbox-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4990-getting-started-with-sigmadelta-digital-interface-on-applicable-stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5020-digital-camera-interface-dcml-on-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5027-interfacing-pdm-digital-microphones-using-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5033-stm32cube-mcu-package-examples-for-stm32h7-series-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5073-receiving-spdif-audio-stream-with-the-stm32f4f7h7-series-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5281-how-to-use-otfdec-for-encryptiondecryption-in-trusted-environment-on-stm32h7bxxx-and-stm32h73xx-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5337-stm32h7-series-lifetime-estimates-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5419-getting-started-with-stm32h723733-stm32h725735-and-stm32h730-value-line-hardware-development-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4899-stm32-microcontroller-gpio-hardware-settings-and-lowpower-consumption-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5612-esd-protection-of-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5293-migration-guide-from-stm32f7-series-to-stmh74x75x-stm32h72x73x-and-stmh7a37bx-devices-stmicroelectronics.pdf

- Application Notes https://www.st.com/resource/en/application_note/an4838-introduction-to-memory-protection-unit-management-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5325-how-to-use-the-cordic-to-perform-mathematical-functions-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5348-introduction-to-fdcan-peripherals-for-stm32-product-classes-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5927-i3c-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5225-introduction-to-usb-typec-power-delivery-for-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5342--how-to-use-error-correction-code-ecc-management-for-internal-memories-protection-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2834-how-to-optimize-the-adc-accuracy-in-the-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5537-how-to-use-adc-oversampling-techniques-to-improve-signal-to-noise-ratio-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5036-guidelines-for-thermal-management-on-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4992-introduction-to-secure-firmware-install-sfi-for-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5405-how-to-use-fdcan-bootloader-protocol-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5690-how-to-use-vrefbuf-peripheral-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4230-introduction-to-random-number-generation-validation-using-the-nist-statistical-test-suite-for-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2867-guidelines-for-

oscillator-design-on-stm8afals-and-stm32-mcusmpus-
stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4013-introduction-to-timers-for-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4277-how-to-use-pwm-shutdown-for-motor-control-and-digital-power-conversion-on-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4635-how-to-optimize-lpuart-power-consumption-on-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4759-introduction-to-using-the-hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4861-introduction-to-lcdtft-display-controller-ltcd-on-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4908-getting-started-with-usart-automatic-baud-rater-detection-for-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4943-how-to-use-chromart-accelerator-to-refresh-an-lcdtft-display-on-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5156-introduction-to-security-for-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5200-getting-started-with-stm32h7-mcus-sdmmc-host-controller-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5224-introduction-to-dmamux-for-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5507-how-to-use-crc-to-check-the-integrity-of-the-internal-flash-memory-on-stm32h7-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5543-guidelines-for-enhanced-spi-communication-on-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5050-getting-started-with-octospi-hexadecapi-and-xspi-interface-on-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an1202_freertos_guide-for_related_Tools_freertos-guide-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application_note/an1602_semihosting_in_for_related_Tools_truestudio-how-to-do-semihosting-in-truestudio-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application_note/an1801_stm32cubeprog_for_related_Tools_rammer_in_truestudio-installing-stm32cubeprogrammer-in-truestudio-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application_note/atollic_editing_keyboard_for_related_Tools_shortcuts-atollic-editing-keyboard-shortcuts-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application_note/iar_to_atollic_truestudio_for_related_Tools_migration_guide-truestudio-for-arm-migration-guide-iar-embedded-workbench-to-truestudio-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application_note/stm32cubemx_installatio_for_related_Tools_n_in_truestudio-stm32cubemx-installation-in-truestudio-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application_note/an4323-getting-started-for_related_Tools_with-stemwin-library-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application_note/an4435-guidelines-for-for_related_Tools_obtaining-ulcsaiec-607301603351-class-b-certification-in-any-stm32-application-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application_note/an4657-stm32-for_related_Tools_inapplication-programming-iap-using-the-usart-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application_note/an4841-digital-signal-for_related_Tools_processing-for-stm32-microcontrollers-using-cmsis-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application_note/an4891-stm32h72x-

for related Tools & Software	stm32h73x-and-singlecore-stm32h74x75x-system-architecture-and-performance-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an5001-stm32cube-expansion-package-for-stm32h7-series-mdma-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an5014-stm32h7x3-smart-power-management-expansion-package-for-stm32cube-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an5033-stm32cube-mcu-package-examples-for-stm32h7-series-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an5056-integration-guide-for-the-xcubesbsfu-stm32cube-expansion-package-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an5360-getting-started-with-projects-based-on-the-stm32mp1-series-in-stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an5361-getting-started-with-projects-based-on-dualcore-stm32h7-microcontrollers-in-stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an5394-getting-started-with-projects-based-on-the-stm32l5-series-in-stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an5418-how-to-build-a-simple-usbp-d-sink-application-with-stm32cubemx-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an5426-migrating-graphics-middleware-projects-from-stm32cubemx-540-to-stm32cubemx-550-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an5534-stm32h735gdk-firmware-upgrade-for-atbased-emw3080-wifi-module-stmicroelectronics.pdf
Application Notes for related Tools	https://www.st.com/resource/en/application_note/an5564-getting-started-with-projects-based-on-dualcore-stm32wl-microcontrollers-in-

& Software	stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools	https://www.st.com/resource/en/application_note/an4865-lowpower-timer-for-related-tools-lptim-applicative-use-cases-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
& Software	stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools	https://www.st.com/resource/en/application_note/an5698-adapting-the-xcubestl-functional-safety-package-for-stm32-iec-61508-compliant-to-other-safety-standards-stmicroelectronics.pdf
& Software	stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools	https://www.st.com/resource/en/application_note/an5731-stm32cubemx-and-stm32cubeide-threadsafe-solution-stmicroelectronics.pdf
& Software	stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools	https://www.st.com/resource/en/application_note/an5450-stm32h7a37b3-lines-and-stm32h7b0-value-line-smart-power-management-expansion-package-for-stm32cube-stmicroelectronics.pdf
& Software	stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools	https://www.st.com/resource/en/application_note/an4502-stm32-smbuspmbus-expansion-package-for-stm32cube-stmicroelectronics.pdf
& Software	stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools	https://www.st.com/resource/en/application_note/an5952-how-to-use-cmake-in-stm32cubeide-stmicroelectronics.pdf
& Software	stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools	https://www.st.com/resource/en/application_note/an4635-how-to-optimize-lpuart-power-consumption-on-stm32-mcus-stmicroelectronics.pdf
& Software	stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools	https://www.st.com/resource/en/application_note/an5054-how-to-perform-secure-programming-using-stm32cubeprogrammer-stmicroelectronics.pdf
& Software	stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools	https://www.st.com/resource/en/application_note/an6088-how-to-use-mce-for-encryptiondecryption-on-stm32-mcus-stmicroelectronics.pdf
Design Notes & Tips	https://www.st.com/resource/en/design_tip/dt0117-microphone-array-beamforming-in-the-pcm-and-pdm-domain-stmicroelectronics.pdf
Errata Sheets	https://www.st.com/resource/en/errata_sheet/es0491-stm32h72xx73xx-device-errata-stmicroelectronics.pdf
Datasheet	https://www.st.com/resource/en/datasheet/dm00701023.pdf

Programming Manuals	https://www.st.com/resource/en/programming_manual/pm0253-stm32f7-series-and-stm32h7-series-cortexm7-processor-programming-manual-stmicroelectronics.pdf
Reference Manuals	https://www.st.com/resource/en/reference_manual/rm0468-stm32h723733-stm32h725735-and-stm32h730-value-line-advanced-armbased-32bit-mcus-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1163-description-of-wlcsp-for-microcontrollers-and-recommendations-for-its-use-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1204-tape-and-reel-shipping-media-for-stm32-microcontrollers-in-bga-packages-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1205-tape-and-reel-shipping-media-for-stm8-and-stm32-microcontrollers-in-fpn-packages-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1206-tape-and-reel-shipping-media-for-stm8-and-stm32-microcontrollers-in-qfp-packages-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1207-tape-and-reel-shipping-media-for-stm8-and-stm32-microcontrollers-in-so-packages-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1208-tape-and-reel-shipping-media-for-stm8-and-stm32-microcontrollers-in-tssop-and-ssop-packages-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1433-reference-device-marking-schematics-for-stm32-microcontrollers-and-microprocessors-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1489-security-bulletin-tn1489stpsirt-physical-attacks-on-stm32-and-stm32cube-firmware-stmicroelectronics.pdf
User Manuals	https://www.st.com/resource/en/user_manual/um2840-stm32h7-dualcore-series-safety-manual-stmicroelectronics.pdf
User Manuals	https://www.st.com/resource/en/user_manual/um2331-stm32h7-singlecore-series-safety-manual-stmicroelectronics.pdf

User Manuals https://www.st.com/resource/en/user_manual/um3252-stm32h7-series-ulcsaiec-607301603351-selftest-library-user-guide-stmicroelectronics.pdf