

- **force\_interactive** (*Optional[bool]*, *optional*) – Enable/disable interactive mode, or None to auto detect. Defaults to None.
- **soft\_wrap** (*Optional[bool]*, *optional*) – Set soft wrap default on print method. Defaults to False.
- **theme** (*Theme*, *optional*) – An optional style theme object, or None for default theme.
- **stderr** (*bool*, *optional*) – Use stderr rather than stdout if **file** is not specified. Defaults to False.
- **file** (*IO*, *optional*) – A file object where the console should write to. Defaults to stdout.
- **quiet** (*bool*, *Optional*) – Boolean to suppress all output. Defaults to False.
- **width** (*int*, *optional*) – The width of the terminal. Leave as default to auto-detect width.
- **height** (*int*, *optional*) – The height of the terminal. Leave as default to auto-detect height.
- **style** (*StyleType*, *optional*) – Style to apply to all output, or None for no style. Defaults to None.
- **no\_color** (*Optional[bool]*, *optional*) – Enabled no color mode, or None to auto detect. Defaults to None.
- **tab\_size** (*int*, *optional*) – Number of spaces used to replace a tab character. Defaults to 8.
- **record** (*bool*, *optional*) – Boolean to enable recording of terminal output, required to call `export_html()`, `export_svg()`, and `export_text()`. Defaults to False.
- **markup** (*bool*, *optional*) – Boolean to enable *Console Markup*. Defaults to True.
- **emoji** (*bool*, *optional*) – Enable emoji code. Defaults to True.
- **emoji\_variant** (*str*, *optional*) – Optional emoji variant, either “text” or “emoji”. Defaults to None.
- **highlight** (*bool*, *optional*) – Enable automatic highlighting. Defaults to True.
- **log\_time** (*bool*, *optional*) – Boolean to enable logging of time by `log()` methods. Defaults to True.
- **log\_path** (*bool*, *optional*) – Boolean to enable the logging of the caller by `log()`. Defaults to True.
- **log\_time\_format** (*Union[str, TimeFormatterCallable]*, *optional*) – If `log_time` is enabled, either string for strftime or callable that formats the time. Defaults to “[%X]”.
- **highlighter** (*HighlighterType*, *optional*) – Default highlighter.
- **legacy\_windows** (*bool*, *optional*) – Enable legacy Windows mode, or None to auto detect. Defaults to None.
- **safe\_box** (*bool*, *optional*) – Restrict box options that don’t render on legacy Windows.
- **get\_datetime** (*Callable[[], datetime]*, *optional*) – Callable that gets the current time as a `datetime.datetime` object (used by `Console.log`), or None for `datetime.now`.
- **get\_time** (*Callable[[], time]*, *optional*) – Callable that gets the current time in seconds, default uses `time.monotonic`.
- **\_environ** (*Mapping[str, str]*)