

## 23.12 rich.logging

```
class rich.logging.RichHandler(level=0, console=None, *, show_time=True, omit_repeated_times=True,
                                show_level=True, show_path=True, enable_link_path=True,
                                highlighter=None, markup=False, rich_tracebacks=False,
                                tracebacks_width=None, tracebacks_code_width=88,
                                tracebacks_extra_lines=3, tracebacks_theme=None,
                                tracebacks_word_wrap=True, tracebacks_show_locals=False,
                                tracebacks_suppress=(), tracebacks_max_frames=100,
                                locals_max_length=10, locals_max_string=80, log_time_format='[%x
                                %X]', keywords=None)
```

A logging handler that renders output with Rich. The time / level / message and file are displayed in columns. The level is color coded, and the message is syntax highlighted.

### Note

Be careful when enabling console markup in log messages if you have configured logging for libraries not under your control. If a dependency writes messages containing square brackets, it may not produce the intended output.

### Parameters

- **level** (*Union[int, str]*, optional) – Log level. Defaults to logging.NOTSET.
- **console** (*Console*, optional) – Optional console instance to write logs. Default will use a global console instance writing to stdout.
- **show\_time** (*bool*, optional) – Show a column for the time. Defaults to True.
- **omit\_repeated\_times** (*bool*, optional) – Omit repetition of the same time. Defaults to True.
- **show\_level** (*bool*, optional) – Show a column for the level. Defaults to True.
- **show\_path** (*bool*, optional) – Show the path to the original log call. Defaults to True.
- **enable\_link\_path** (*bool*, optional) – Enable terminal link of path column to file. Defaults to True.
- **highlighter** (*Highlighter*, optional) – Highlighter to style log messages, or None to use ReprHighlighter. Defaults to None.
- **markup** (*bool*, optional) – Enable console markup in log messages. Defaults to False.
- **rich\_tracebacks** (*bool*, optional) – Enable rich tracebacks with syntax highlighting and formatting. Defaults to False.
- **tracebacks\_width** (*Optional[int]*, optional) – Number of characters used to render tracebacks, or None for full width. Defaults to None.
- **tracebacks\_code\_width** (*int*, optional) – Number of code characters used to render tracebacks, or None for full width. Defaults to 88.
- **tracebacks\_extra\_lines** (*int*, optional) – Additional lines of code to render tracebacks, or None for full width. Defaults to None.
- **tracebacks\_theme** (*str*, optional) – Override pygments theme used in traceback.
- **tracebacks\_word\_wrap** (*bool*, optional) – Enable word wrapping of long tracebacks lines. Defaults to True.