

- **total** (*Optional[float]*) – (float, optional): Total number of steps. Default is `len(sequence)`.
- **completed** (*int, optional*) – Number of steps completed so far. Defaults to 0.
- **auto_refresh** (*bool, optional*) – Automatic refresh, disable to force a refresh after each iteration. Default is True.
- **transient** (*bool*) – (bool, optional): Clear the progress on exit. Defaults to False.
- **console** (*Console, optional*) – Console to write to. Default creates internal Console instance.
- **refresh_per_second** (*float*) – Number of times per second to refresh the progress information. Defaults to 10.
- **style** (*StyleType, optional*) – Style for the bar background. Defaults to “bar.back”.
- **complete_style** (*StyleType, optional*) – Style for the completed bar. Defaults to “bar.complete”.
- **finished_style** (*StyleType, optional*) – Style for a finished bar. Defaults to “bar.finished”.
- **pulse_style** (*StyleType, optional*) – Style for pulsing bars. Defaults to “bar.pulse”.
- **update_period** (*float, optional*) – Minimum time (in seconds) between calls to `update()`. Defaults to 0.1.
- **disable** (*bool, optional*) – Disable display of progress.
- **show_speed** (*bool, optional*) – Show speed if total isn’t known. Defaults to True.
- **get_time** (*Optional[Callable[[], float]]*)

Returns

An iterable of the values in the sequence.

Return type

`Iterable[ProgressType]`

```
rich.progress.wrap_file(file, total, *, description='Reading...', auto_refresh=True, console=None,
                        transient=False, get_time=None, refresh_per_second=10, style='bar.back',
                        complete_style='bar.complete', finished_style='bar.finished', pulse_style='bar.pulse',
                        disable=False)
```

Read bytes from a file while tracking progress.

Parameters

- **file** (*Union[str, PathLike[str], BinaryIO]*) – The path to the file to read, or a file-like object in binary mode.
- **total** (*int*) – Total number of bytes to read.
- **description** (*str, optional*) – Description of task show next to progress bar. Defaults to “Reading”.
- **auto_refresh** (*bool, optional*) – Automatic refresh, disable to force a refresh after each iteration. Default is True.
- **transient** (*bool*) – (bool, optional): Clear the progress on exit. Defaults to False.
- **console** (*Console, optional*) – Console to write to. Default creates internal Console instance.