- **refresh_per_second** (*float*) – Number of times per second to refresh the progress information. Defaults to 10.

- **style** (*StyleType, optional*) – Style for the bar background. Defaults to "bar.back".

- **complete_style** (*StyleType, optional*) – Style for the completed bar. Defaults to "bar.complete".

- **finished_style** (*StyleType, optional*) – Style for a finished bar. Defaults to "bar.finished".

- **pulse_style** (*StyleType, optional*) – Style for pulsing bars. Defaults to "bar.pulse".

- **disable** (*bool, optional*) – Disable display of progress.

- **get_time** (*Optional[Callable[[], float]]*)

> **Returns**
> A context manager yielding a progress reader.

> **Return type**
> ContextManager[BinaryIO]

# 23.21 rich.prompt

**class** rich.prompt.**Confirm**(*prompt='', \*, console=None, password=False, choices=None, case_sensitive=True, show_default=True, show_choices=True*)

> A yes / no confirmation prompt.

> **Example**

```
>>> if Confirm.ask("Continue"):
        run_job()
```

> **Parameters**
>
> - **prompt** (*str | Text*)
> - **console** (*Console | None*)
> - **password** (*bool*)
> - **choices** (*List[str]*)
> - **case_sensitive** (*bool*)
> - **show_default** (*bool*)
> - **show_choices** (*bool*)

**process_response**(*value*)

> Convert choices to a bool.

> **Parameters**
> **value** (*str*)

> **Return type**
> bool