

Parameters

- **pager** (*Pager*, *optional*) – A pager object, or None to use `SystemPager`. Defaults to None.
- **styles** (*bool*, *optional*) – Show styles in pager. Defaults to False.
- **links** (*bool*, *optional*) – Show links in pager. Defaults to False.

Return type*PagerContext***Example**

```
>>> from rich.console import Console
>>> from rich.__main__ import make_test_card
>>> console = Console()
>>> with console.pager():
>>>     console.print(make_test_card())
```

Returns

A context manager.

Return type*PagerContext***Parameters**

- **pager** (*Pager* | *None*)
- **styles** (*bool*)
- **links** (*bool*)

pop_render_hook()

Pop the last renderhook from the stack.

Return type

None

pop_theme()

Remove theme from top of stack, restoring previous theme.

Return type

None

```
print(*objects, sep=' ', end='\n', style=None, justify=None, overflow=None, no_wrap=None, emoji=None,
markup=None, highlight=None, width=None, height=None, crop=True, soft_wrap=None,
new_line_start=False)
```

Print to the console.

Parameters

- **objects** (*positional args*) – Objects to log to the terminal.
- **sep** (*str*, *optional*) – String to write between print data. Defaults to “ ”.
- **end** (*str*, *optional*) – String to write at end of print data. Defaults to “\n”.
- **style** (*Union[str, Style]*, *optional*) – A style to apply to output. Defaults to None.