Opening the Black Box of Large Language Models in Text-based Measurement: Staged Pipelines with Verifiable Checkpoints

Milan Miric, Albert Roh, Nan Jia

University of Southern California, Marshall School of Business

Proposal for Special Issue: AI-Enabled Frontiers in Organizational Science (*Organization Science*)

Repository: https://github.com/HC-Geopolitics-Innovation/LLM-Text-Analysis-and-Synthesis

1. The Data Opportunity and Black-box Risk in LLM-based Measurement: A Staged Pipeline Approach

Researchers increasingly use large language models (LLMs) to construct variables from text (Gilardi et al. 2023, Rathje et al. 2024, Asirvatham et al. 2026, Dell and Rambachan 2026). The appeal is clear: long noisy documents which have typically been unsuitable for processing with traditional techniques such as topic models or embeddings (Grimmer and Stewart 2013, Hannigan et al. 2019, Dell 2025), such as 10-K filings and policy reports, can be processed by LLMs (Kim et al. 2023, Jha et al. 2024, de Kok 2025, Benoit et al. 2026). This opens research contexts that were previously impractical to study at very large scale. However, when LLMs are used as an end to end solution: by providing a model with entire documents and asking it to return a numerical quantity, the LLM becomes a black box in that the final output is the only observable checkpoint. Researchers cannot see which parts of a document a measure rests on, what was omitted, or how judgments are made at intermediate stages. In addition, the outcome is sensitive to unobserved choices, making it difficult to reproduce.

This opacity creates three risks. (1) *Validation.* Validating only the final output shows how often a measure is accurate in specific cases, but provides no systematic indication why it may have not been accurate. These aggregate measures can mask systematic errors: Carlson and Burbano (2026) show how these measures need to be validated by creating a heterogeneous set of approaches and then validating the outcomes on those approaches. (2) *Reproducibility.* Rerunning an end-to-end process may not return the same measure when proprietary models are updated or retired; and because the process produces no intermediate outputs, other researchers cannot leverage the intermediate outputs generated by that process, and instead must re-create the entire effort. (3) *Heterogeneity within documents.* An end-to-end measure collapses each document into a single output, concealing variation inside it. Researchers do not have control over which portion of a text document is driving the final outputs of the large language models, or whether for some parts of the model, the model is creating summaries and not processing these document equally. Because these measures enter subsequent analyses as variables, the risk is not merely noisy measurement but biased analysis: when errors are systematic, a finding may reflect how a measure was produced rather than the phenomenon it is meant to capture. One might expect these risks to fade as models gain longer context windows and stronger reasoning. However, many of these concerns will remain. A more capable end-to-end model will only expose the final output, but the concerns will emerge from opacity and a lack of control over design choices, rather than from a limited capability.

Recent work has acknowledged and begun to devise methodologies to overcome these risks. Carlson and Burbano (2026) propose a way of mitigating these concerns by systematic sensitivity analysis, including generating families of prompt variations, running them across models, and reporting the range of resulting downstream estimates. This approach reveals how much conclusions depend on implementation choices, but also focuses on a single albeit common task of textual classification. Processing long text documents and extracting specific insights nests a text classification choice within a black box of other data parsing, processing and synthesis functions. Using large language models for these other more complex textual analysis tasks, creates more opportunities for the models to make choices. This is part of a broader literature which has emerged showing the idiosyncrasies of how these models can make individual choices, but when combined as part of a carefully crafted workflow can mimic at scale or improve what human workers would have achieved (Csaszar et al. 2024, Doshi et al. 2025, Dell'Acqua et al. 2026). These studies have demonstrated important AI use in specific tasks, many of which could be easily integrated into an AI pipeline. However, the LLM processing of large information rich text documents which could enable researchers to answer new and important questions, requires finding a way to integrate and apply these methodologies as part of a pipeline which could in turn avoid introducing systematic noise and bias through black box algorithms. We propose a complementary approach.

Instead of using an end-to-end approach (e.g. using an LLM to parse, summarize and process an entire document) and varying the input (prompt text), we propose opening up the black-box algorithm and decomposing LLM-based measurement generation into a pipeline of discrete stages, each producing an inspectable intermediate output. This design addresses each risk. For validation, each stage can be checked against its own benchmark, allowing researchers to detect systematic error and locate where it arises. For reproducibility, a change in model, or a new construct definition, is confined to one stage, so researchers can reuse the outputs of earlier stages and revalidate only what changed; the same structure lets sensitivity analysis vary one stage at a time and attribute any change in results to it. For heterogeneity, intermediate outputs are retained for individual passages rather than whole documents, so aggregate measures can be traced back to their components and re-aggregated by contributor, section, or other conditions of interest.

Decomposing the process also allows each stage to use the tool best suited to it. LLMs excel at two types of tasks: (1) Synthesizing text, that is, reading long, noisy passages and condensing them into short, information-dense outputs such as summaries or statements of position; and (2) Generating code, that is, producing machine-readable instructions that can be systematically executed and tested. We use LLMs for synthesis and rely on established methods, such as embeddings and similarity measures, where they have proven routines, validation standards, and verifiable properties, applying them to condensed or sentence-level text rather than to whole documents. The pipeline thus combines the core strengths of LLMs with the known properties of established tools rather than replacing one with the other. Code generation also makes the pipeline easier to extend to other use cases: because the pipeline's code is available in a public repository, other researchers can use coding agents to adapt it to their own data and questions (Appendix D).

We demonstrate the application of this approach in a setting relevant for organization researchers: how congressional debate over regulating a technology relates to changes in the innovation trajectories of firms exposed to it. Studying this question requires understanding and quantifying the nature of the policy debate which exists and how it might be leveraged by researchers. This also requires measuring the extent to which the issues being discussed in the debate represent threats or opportunities for firms.

We focus on the policy debate over user data privacy that emerged in the mid 2010's related to technology

companies collecting customer data, the Cambridge Analytica scandal related to the use of Facebook data by third party companies, and document the relationship between the debate of policy makers which coincided with shifts in the innovation policy of firms. Studying this question requires identifying which firms were likely impacted by this debate, so they can be compared with firms that credibly were not. That information is embedded in two kinds of long, noisy documents: congressional hearing transcripts, which average roughly 40,000 words and alternate between testimony and questioning from many participants, and firms' 10-K filings. The setting puts all three risks at stake: Because the exposure measure assigns firms to treatment and control groups, systematic error in it would bias the estimated effect; because other researchers may want to extend the measure to studying other policies, it must be reproducible in parts; and because a committee's stance may reflect its members broadly or only a few vocal participants, heterogeneity within hearings matters for interpretation.

2. Our Framework: A Staged Pipeline for LLM-based Measurement

We develop a framework that illustrates how LLMs can be used within a data pipeline without ceding full control to them. After data preparation, the pipeline proceeds through three stages (text summarization, stance extraction, and relevance to firms' business areas), each composed of discrete steps that produce intermediate outputs. Each output can be validated, reused, and disaggregated, addressing the three risks above. Researchers can adapt these stages to extract different insights or apply them to data of their choice.

2.1. Overview of Data Pipeline and Processing Stages

- **Stage 1 – Data Preparation:** Assembling and structuring the corpora before any LLM is applied. We parse congressional hearing transcripts from the U.S. Government Publishing Office into speaker-attributed turns, extract business descriptions (Item 1) from S&P 500 firms' 10-K filings, and retrieve independent C-SPAN hearing abstracts as a validation benchmark. Defects such as undigitized transcripts are flagged rather than dropped, so every exclusion can be inspected.

- **Stage 2 – Text Summarization:** Taking large, complex textual documents that contain considerable noise alongside embedded data, partitioning them into chunks, and using LLMs to generate, synthesize, and aggregate textual summaries. We demonstrate this approach on congressional hearing transcripts (see Appendix B for data sources and processing), summarizing long and convoluted documents into concise summaries that can subsequently be used for text classification, topic modeling, or semantic distance estimation in more reliable ways.

- **Stage 3 – Stance Extraction:** Using LLMs to identify the positions of different actors (e.g., members of Congress, firms, government agencies) on specific topics, allowing researchers to distill the nuances of arguments and positions that each individual takes on an issue. We apply this to congressional hearings to identify the stances of members of Congress on key issues, classified as support, concern, or neutral, in a format that can be utilized in subsequent research.

- **Stage 4 – Debate Relevance to Firm Business Areas:** Using the distilled stances of individuals within the debate, we create a synthesis of the policy debate. This synthesis, or an embedding of the underlying statements, can then be compared to the business descriptions of firms to identify which firms are exposed to the debate. In our empirical context, this means framing the key issues that policymakers are debating and

attempting to regulate. We then compare this to the business descriptions (Item 1) in firms' 10-K filings. This allows us to identify and study firms that are exposed to the debate versus those that are not.

2.2. Adapting the Pipeline for Other Research Questions

Because each stage is modular and its code is available in our repository, researchers can reuse the pipeline in part or in full. For example, they can apply the same stages to hearings of other committees or to other policy topics, or replace the stance-extraction stage to measure a different construct while keeping data preparation and summarization fixed.

Furthermore, LLMs' ability to generate code lowers the cost of such adaptation: these models also excel at writing code that is automatically tested, verified, and validated. By providing our pipeline's code and methodologies in a GitHub repository where the codebase is available, researchers can use their own coding agents to either improve upon our methodology or apply this methodology to their own setting and data.

We believe this provides a framework that can guide how large language models can be used to adapt and deploy research pipelines in the future.

3. Current Status of Project

We have currently developed a research pipeline, focused on the specific question outlined above: the relationship between congressional debate about user data privacy and the innovation trajectory of technology companies, made available on the associated GitHub repository for this project. This pipeline demonstrates the transformation from raw transcripts of congressional hearings to a series of research outputs: textual summaries, summaries of perceived priorities (support/concerns identified by policymakers), and an index for policy relevance for publicly listed firms. This is a prototype of what can be done (using one set of approaches and design choices in the LLM pipeline). However, as we aim to show, and much like we are advocating, that this pipeline could be verified, adopted or adapted to other projects and applications.

3.1. Expected Deliverables

- **Reproducible LLM Data Pipeline for Text Summarization, Stance Extraction, and Topic Relevance**
- **Public Datasets for Subsequent Research:** From the data of 36K Congressional Hearings from 1995–2025 (currently 2,352 hearings for the House and Senate Science Committees): full chunked text, intermediate summaries, list of topics discussed, summarized stances, an index of committee stances on topics discussed in hearings, and an index of relevance of those topics for publicly listed firms based on Item 1 business descriptions (1995–2025).
- **Illustrative Empirical Results:** Demonstration of the empirical results of the privacy regulation applied to investigate the impact of privacy regulation on the trajectory of corporate innovation.
- **Instructions and Framework for Deployment for Follow-on Research**

3.2. Datasets (Outputs from Focal Research Project)

- **Text Summaries for Congressional Testimony from 1995 to 2025:** – Intermediate outputs for verification and replication: Cleaned and chunked testimony, summarized testimony chunks, finalized text summaries.

- **Index of Committee Stances in Congressional Debate:** – Intermediate outputs for verification and replication: Topics within congressional debate, filtered chunks focused with a stance on a focal topic, summarized positions on a focal topic, and an aggregated index of committee stances on topics discussed.

- **Index of Relevance of Congressional Debate for Publicly Listed Firms:** – Intermediate outputs for verification and replication: Summarized congressional stances and company business descriptions based on 10-K filings, relevance index for individual company filings and congressional topic stances, and an aggregated index for topical relevance.

3.3. Example of Empirical Application

- **Demonstration of the Policy Relevance Index:** Demonstrating the use of the constructed policy relevance index regarding the impact of congressional debate on the innovative trajectories of publicly listed firms. Using the context of the Cambridge Analytica scandal, we demonstrate how these tools can be used to identify firms that were in treated or control groups, allowing for an event study design to examine changes in innovation trajectories following these events.

3.4. Key Risks and Limitations in Implementation

We have tested the viability of our empirical strategy and have developed a working prototype of its deployment. We have confidence that this methodology will provide useful outputs. We have a goal of demonstrating this with as large a dataset as possible (the population of congressional testimony, public firm 10-Ks, and major policy topics discussed). We also recognize the potential for different ways of constructing and aggregating data. Because each of these approaches is time-consuming, we are committed to implementing all of them, but may become constrained in the number of individual specifications we can add.

4. How This Advances Organizational and Social Science

Long-form documents such as congressional hearings, regulatory filings, and corporate disclosures record how organizations and governments deliberate, yet they have been difficult to use: established text methods work best on short, information-dense text, and end-to-end LLM use relaxes this constraint only by introducing opacity. Our approach relaxes this constraint while alleviating the opacity of end-to-end use. If successful, it advances organizational research in three ways.

First, it provides a pipeline that turns long, noisy documents into measures whose construction can be inspected stage by stage. LLM-based measures thus become auditable research objects rather than outputs taken on trust, and the pipeline offers a template for reporting them, including intermediate outputs, stage-level validation, and stage-specific sensitivity analysis.

Second, it provides a public research dataset: summaries of more than 2,300 congressional hearings, a panel of legislators' stances by topic, and firm-level measures of exposure to policy debate. Because intermediate outputs are released alongside the final measures, other researchers can build on any stage, for example by re-aggregating stances by member or relating firm exposure to new outcomes.

Third, the framework enables a new form of replication. Because the pipeline is shared as a modular repository, researchers can direct coding agents to rebuild or adapt it at low cost. And because each stage produces outputs that can be compared with ours, a replication need not succeed or fail as a whole: discrepancies can be located at the stage where they arise. Replication thus shifts from an all-or-nothing comparison of final results to a stage-by-stage check.

Together, these contributions allow researchers both to do existing work better and to do new work. Existing work improves because the risks identified above become testable: when each stage is validated, systematic error can be detected and located before it biases a finding, and when a replication can localize discrepancies, disagreements over results can be traced to specific choices rather than left unresolved. New work becomes possible because researchers no longer face a choice between avoiding long-form documents and relying on measures that cannot be checked. Hearings, regulatory proceedings, and corporate disclosures, which record how organizations and governments deliberate, can support credible measures at scale; and because outputs are retained within documents, researchers can ask not only what a collective position is but who shapes it. The aim is not more research from the same materials, but better research from materials previously out of reach.

References

- Asirvatham H, Mokski E, Shleifer A (2026) GPT as a measurement tool. NBER Working Paper, National Bureau of Economic Research, Cambridge, MA.
- Benoit K, De Marchi S, Laver C, Laver M, Ma J (2026) Using large language models to analyze political texts through natural language understanding. *American Journal of Political Science* 70(4):1589–1605.
- Carlson NA, Burbano V (2026) The use of LLMs to annotate data in management research: Foundational guidelines and warnings. *Strategic Management Journal* 47(3):699–725.
- Csaszar FA, Ketkar H, Kim H (2024) Artificial intelligence and strategic decision-making: Evidence from entrepreneurs and investors. *Strategy Science* 9(4):322–345.
- de Kok T (2025) ChatGPT for textual analysis? How to use generative LLMs in accounting research. *Management Science* 71(9):7888–7906.
- Dell'Acqua F, McFowland E, Mollick ER, Lifshitz-Assaf H, Kellogg K, Rajendran S, Krayer L, Candelon F, Lakhani KR (2026) Navigating the jagged technological frontier: Field experimental evidence of the effects of artificial intelligence on knowledge worker productivity and quality. *Organization Science* 37(2):403–423.
- Dell M (2025) Deep learning for economists. *Journal of Economic Literature* 63(1):5–58.
- Dell M, Rambachan A (2026) The measurement revolution? Credible measurement and inference in the age of AI. NBER Working Paper, National Bureau of Economic Research, Cambridge, MA.

- Doshi AR, Bell JJ, Mirzayev E, Vanneste BS (2025) Generative artificial intelligence and evaluating strategic decisions. *Strategic Management Journal* 46(3):583–610.
- Gilardi F, Alizadeh M, Kubli M (2023) ChatGPT outperforms crowd workers for text-annotation tasks. *Proceedings of the National Academy of Sciences* 120(30):e2305016120.
- Grimmer J, Stewart BM (2013) Text as data: The promise and pitfalls of automatic content analysis methods for political texts. *Political Analysis* 21(3):267–297.
- Hannigan TR, Haans RF, Vakili K, Tchalian H, Glaser VL, Wang MS, Kaplan S, Jennings PD (2019) Topic modeling in management research: Rendering new theory from textual data. *Academy of Management Annals* 13(2):586–632.
- Jha M, Qian J, Weber M, Yang B (2024) ChatGPT and corporate policies. NBER Working Paper, National Bureau of Economic Research, Cambridge, MA.
- Kim AG, Muhn M, Nikolaev VV (2023) Bloated disclosures: Can ChatGPT help investors process information? Chicago Booth Research Paper 23-07, University of Chicago, Booth School of Business, Chicago.
- Kogan L, Papanikolaou D, Seru A, Stoffman N (2017) Technological innovation, resource allocation, and growth. *Quarterly Journal of Economics* 132(2):665–712.
- Rathje S, Mirea DM, Sucholutsky I, Marjieh R, Robertson CE, Van Bavel JJ (2024) GPT is an effective tool for multilingual psychological text analysis. *Proceedings of the National Academy of Sciences* 121(34):e2308950121.