



ANAPLAN 1.0 USER MANUAL

Author: Hasan Can Beydili

ABOUT ANAPLAN:

Anaplan is a machine learning library written in Python for professionals, incorporating advanced, unique, new, and modern techniques. Its most important component is the PLAN (Potentiation Learning Artificial Neural Network).

Both the PLAN algorithm and the Anaplan library were created by Author, and all rights are reserved by Author.

Anaplan is free to use for commercial business and individual users.

As of 08/21/2024, the library includes only the PLAN module, but other machine learning modules are expected to be added in the future.

The PLAN algorithm will not be explained in this document. This document focuses on how professionals can integrate and use Pyeural Jetwork in their systems. However, briefly, the PLAN algorithm can be described as a classification algorithm. PLAN algorithm achieves this task with an incredibly energy-efficient, fast, and hyperparameter-free user-friendly approach. For more detailed information, you can check out 'PLAN.pdf' file.

HOW DO I IMPORT IT TO MY PROJECT?

Anaconda users can access the 'Anaconda Prompt' terminal from the Start menu and add the necessary library modules to the Python module search queue by typing `"pip install anaplan"` and pressing enter. If you are not using Anaconda, you can simply open the 'cmd' Windows command terminal from the Start menu and type `"pip install anaplan"`. (Visual Studio Code recommended) After installation, it's important to periodically open the terminal of the environment you are using and stay up to date by using the command `"pip install anaplan --upgrade"`. The latest version was `"1.0.3"` at the time this document was written

After installing the module using `"pip"` you can now call the library module in your project environment. Use: `"from anaplan import plan"`. Now, you can call the necessary functions from the plan module.

MAIN FUNCTIONS:

- 1. fit (2Args - 8Args)**
- 2. evaluate (5Args -6Args)**
- 3. save_model (8Args - 9Args)**
- 4. load_model (2Args)**
- 5. predict_model_ssd (3Args)**
- 6. predict_model_ram (3Args - 4Args)**
- 7. auto_balancer (2Args)**
- 8. synthetic_augmentation (2Args)**
- 9. get_weights ()**
- 10. get_scaler ()**
- 11. get_preds ()**
- 12. get_acc ()**
- 13. get_pot ()**
- 14. encode_one_hot (2Args)**
- 15. split (4Args)**
- 16. metrics (3Args)**
- 17. decode_one_hot (1Args)**
- 18. roc_curve (2Args)**
- 19. confusion_matrix (3Args)**
- 20. plot_decision_space (2Args)**
- 21. standard_scaler(1Args - 3Args)**
- 22. manuel_balancer(3Args)**
- 23. weight_normalization (2Args)**
- 24. activation_optimizer (2Args - 12Args)**
- 25. activations_list ()**

The functions of the Anaplan modules, uses snake_case written style.

Yellow labeled parameters is **not necessary**.

Like this labeled functions highly recommended to use.

Green labeled parameters **necessary**.

1. fit (x_train, y_train, show_training, val, val_count, x_val, y_val, activation_potentiation)

The purpose of this function, as the name suggests, is to train the model.

```
a. x_train (list[num]): List or numarray of input data.
b.     y_train (list[num]): List or numarray of target labels. (one hot
    encoded)
c.     val (None or True): validation in training process ? None or
    True default: None (optional)
d.     val_count (None or int): After how many examples learned will an
    accuracy test be performed? default: 10=(%10) it means every
    approximately 10 step (optional)
e.     activation_potentiation (list): For deeper PLAN networks,
    activation function parameters. For more information please look this
    functions doc: plan.activations_list() default: [None] (optional)
f.     x_val (list[num]): List of validation data. (optional) Default:
    %10 of x_train (auto_balanced) it means every %1 of train progress
    starts validation default: x_train (optional)
g.     y_val (list[num]): (list[num]): List of target labels. (one hot
    encoded) (optional) Default: %10 of y_train (auto_balanced) it means
    every %1 of train progress starts validation default: y_train (optional)
h.     show_training (bool, str): True or None default: None (optional)
i.     visible_layer: For the future [DISABLED]
j.     LTD (int): Long Term Depression Hyperparameter for train PLAN
    neural network default: 0 (optional)
k.     interval (float, int): frame delay (milisecond) parameter for
    Training Report (show_training=True) This parameter effects to your
```

```
Training Report performance. Lower value is more difficult for Low end PC's (33.33 = 30 FPS, 16.67 = 60 FPS) default: 100 (optional)
1.      loading_voice(bool): Loading speak may effects training time (True or False) (optional) default: False
```

The output of this function Weight matrix of model.

2. evaluate (x_test, y_test, show_metrics, loading_bar_status, acc_bar_status, W, activation_potentiation)

This function calculates the test accuracy of the model using the inputs and labels set aside for testing, along with the weight matrices and other model parameters obtained as output from the training function.

```
a. x_test (list[num]): Test input data.
b. y_test (list[num]): Test labels.
c. W (list[num]): Weight matrix list of the neural network.
d. activation_potentiation (list): For deeper PLAN networks, activation function parameters. For more information please run this code: help(plan.activation_functions_list) default: [None]
e. loading_bar_status: Evaluate progress have a loading bar ? (True or False) Default: True.
f. acc_bar_status: Evaluate progress have accuracy bar ? (True or False) Default: True.
g. show_metrics (bool): (True or None) (optional) Default: None
```

The outputs of this function are, in order: weights of test process, a list of test predictions, and test accuracy rate.

3. `save_model(model_name, model_type, test_acc, weights_type, weights_format, model_path, scaler_params, W, activation_potentiation)`

This function creates log files in the form of a pandas DataFrame containing all the parameters and information of the trained and tested model, and saves them to the specified location along with the weight matrices.

```
a. model_name (str): Name of the model.
b.
c. model_type (str): Type of the model.(options: PLAN)
d.
e. test_acc (float): Test accuracy of the model.
f.
g. weights_type (str): Type of weights to save (options: 'txt', 'numpy',
  'mat'). RECCOMENDED: 'txt'
h.
i. WeightFormat (str): Format of the weights (options: 'd', 'f', 'raw').
  RECCOMENDED: 'raw'
j.
k. model_path (str): Path where the model will be saved. For example:
  C:/Users/beydili/Desktop/denemePLAN/
l.
m. scaler_params (list[num, num]): standard scaler params list: mean,std.
  If not used standard scaler then be: None.
n.
o. W: Weights of the model.
p.
q. activation_potentiation (list): For deeper PLAN networks, activation
  function parameters. For more information please run this code:
  help(plan.activation_functions_list) default: [None]
r.
```

This function returns messages such as 'saved' or 'could not be saved' as output.

4. `load_model(model_name, model_path)`

This function retrieves everything about the model into the Python environment from the saved log file and the model name.

```
a. model_name (str): Name of the model.  
b. model_path (str): Path where the model is saved.
```

This function returns the following outputs in order: W, `activation_potentiation`, df (Data frame of model).

5. `predict_model_ssd(Input, model_name, model_path)`

This function loads the model directly from its saved location, predicts a requested input, and returns the output. (It can be integrated into application systems and the output can be converted to .json format and used in web applications.)

```
a. Input (list or ndarray): Input data for the model (single  
vector or single matrix).  
b. model_name (str): Name of the model.
```

This function returns the last output layer of the model as the output of the given input.

6. `predict_model_ram` (Input, scaler_params, W, activation_potentiation)

This function predicts and returns the output for a requested input using a model that has already been loaded into the program (located in the computer's RAM). (It can be integrated into application systems and the output can be converted to .json format and used in web applications.) (Other parameters are information about the model and are defined as described and listed above.)

- a. `Input` (list or ndarray): Input data for the model (single vector or single matrix).
- b. `W` (list of ndarrays): Weights of the model.
- c. `scaler_params` (list): standard scaler params list: mean,std. (optional) Default: None.
- d. `activation_potentiation` (list): ac list for deep PLAN. default: [None] ('linear') (optional)

This function returns the last output layer of the model as the output of the given input.

7. `auto_balancer` (x_train, y_train)

This function aims to balance all training data according to class distribution before training the model. All data is reduced to the number of data points of the class with the least number of examples.

- a. `x_train` (list): Input data for training.
- b. `y_train` (list): Labels corresponding to the input data.

This function returns the following outputs in order: a list containing the balanced training data and a list containing the balanced training labels.

8 .synthetic_augmentation (x_train, y_train)

This function creates synthetic data samples with given data samples for balance data distribution.

```
a.      x -- Input dataset (examples) - array format
b.      y -- Class labels (one-hot encoded) - array format
```

This function returns the following outputs in order: a list containing the balanced training data and a list containing the balanced training labels. or testing labels.

9. get_weights()

This function returns wight matrices list of the selected model. For exp:

```
test_model = plan.evaluate(x_test, y_test)
```

```
W = test_model[plan.get_weights()]
```

10. get_scaler ()

Returns scaler_params of the selected model For exp:

```
model = plan.load_model(model_name="example", model_path="")
```

```
scaler_params = model[plan.get_scaler()]
```

11. get_preds()

Returns predictions list of the selected model

12. `get_acc()`

Returns accuracy of the selected model

13. `get_pot()`

Returns activation potential of the selected model.

14. `encode_one_hot(y_train, y_test)`

```
a.      y_train (numpy.ndarray): Labeled train data.  
b.      y_test (numpy.ndarray): Labeled test data.
```

Returns one hot encoded labels.

15. `split(X, y, test_size, random_state)`

This function splits all data for train and test

```
a.      X (numpy.ndarray): Features data.  
b.      y (numpy.ndarray): Labels data.  
c.      test_size (float or int): Proportion or number of samples for  
      the test subset.  
d.      random_state (int or None): Seed for random state.
```

Returns: x_train, x_test, y_train, y_test

16. metrics (y_test, y_preds, average)

This function calculates precision, recall and f1 score of model.

```
a.      y_ts (list or numpy.ndarray): True labels.  
b.      test_preds (list or numpy.ndarray): Predicted labels.  
c.      average (str): Type of averaging ('micro', 'macro', 'weighted').
```

Returns: precision, recall, f1.

17. decode_one_hot (y_test)

```
a. encoded_data (numpy.ndarray): One-hot encoded data with shape  
   (n_samples, n_classes).
```

Returns: decoded y_test given input

18. roc_curve (y_test, y_preds)

```
a.      y_true : array, shape = [n_samples]  
b.      True binary labels in range {0, 1} or {-1, 1}.  
c.      y_score : array, shape = [n_samples]  
d.      Target scores, can either be probability estimates of the  
   positive class,  
e.      confidence values, or non-thresholded measure of decisions  
   (as returned  
f.      by decision_function on some classifiers).
```

Returns: fpr, tpr, thresholds

19. confusion_matrix (y_test, y_preds, class_count)

```
a.      y_true (numpy.ndarray): True class labels (1D array).  
b.      y_pred (numpy.ndarray): Predicted class labels (1D array).  
c.      num_classes (int): Number of classes.
```

Returns: confusion matrix

20. plot_decision_space (x, y)

Plots decision boundary like data distribution.

21. standard_scaler (x_train, x_test, scaler_params)

```
a. train_data: numpy.ndarray  
b. test_data: numpy.ndarray (optional)  
c. scaler_params (optional for using model)
```

Returns: If x_test given then returns: standard scaled parameters, standard scaled x_train, standard scaled y_test. If x_test is not given then returns: standard scaled parameters, standard scaled x_train.

22. manuel_balancer (x_train, y_train target_samples_per_class)

Same operation of `auto_balacner`, but this function gives the limit of sample addition to user.

```
a.    x_train -- Input dataset (examples) - NumPy array format
b.    y_train -- Class labels (one-hot encoded) - NumPy array format
c.    target_samples_per_class -- Desired number of samples per class
```

Returns: `x_train`, `y_train`

23. `weight_normalization (W, class_count)`

Some cases need to normalize neurons. This function does this operation. Mostly in unbalanced training cases.

```
a.    W (list(num)): Trained weight matrix list.
b.    class_count (int): Class count of model.
```

Returns: `W`

24. `activation_optimizer (x_train, y_train, x_val, y_val, depth, early_stop, show_history, interval, target_acc, decision_boundary_status, except_this, only_this)`

```
a.    x_train (array-like): Training input data.
b.    y_train (array-like): Labels for training data.
c.    x_val (array-like): Validation input data.
d.    y_val (array-like): Labels for validation data.
e.    depth (int, optional): The depth of the neural network.
    Default is max length of activation functions list.
f.    early_stop (bool, optional): If True, implements early
    stopping during training. Default is False.
g.    show_history (bool, optional): If True, displays the training
    history after optimization. Default is False.
h.    interval (int, optional): The interval at which evaluations
    are conducted during training. Default is 100.
```

```
i.      target_acc (float, optional): The target accuracy to stop
training early when achieved. Default is None.
j.      decision_boundary_status (bool, optional): If True,
visualizes the decision boundary after optimization. Default is True.
k.      except_this (list, optional): A list of activations to
exclude from optimization. Default is None.
l.      only_this (list, optional): A list of activations to focus on
during optimization. Default is None.
```

25. activations_list()

This function includes all available activations list in the module

Returns: all available activations

ERROR MESSAGES:

100 Type Errors: Value Errors.

200 Type Errors: Variable type errors.

300 Type Errors: List length errors.

LAST PART:

Despite being in its early stages of development, Anaplan has already demonstrated its potential to deliver valuable services and solutions in the field of machine learning. Notably, it stands as the first library dedicated to PLAN (Potentiation Learning Artificial Neural Network), embracing innovation and welcoming new ideas from its users with open arms. Recognizing the value of diverse perspectives and fresh ideas, I, Hasan Can Beydili, the creator of Anaplan, am committed to fostering an open and collaborative environment where users can freely share their thoughts and suggestions. The most promising contributions will be carefully considered and potentially integrated into the Anaplan library. For your suggestions, lists and feedback, my e-mail address is: tchasancan@gmail.com

And finally, trust the PLAN...