

AI Audit Report

Identity

- Student: Mai Thi Kim Duyen, 23127185
- Date: 2026-08-30 to 2026-08-31
- AI-assisted agent: Codex GPT-5
- Human reviewer: Mai Thi Kim Duyen

Audit log

Step	Prompt/task	AI output/use	Human verification and correction
1	Inspect assignment and team division	Selected member-2 workflow: new registration, login, categories, product detail, coupon, checkout	Confirmed against docs/team-task-division.vi.md.
2	Inspect backend source and API specification	Produced endpoint map and identified auth/read/transaction groups	Compared every route with server.js and api_specification.md.
3	Design JMeter plans	Generated three plans with CSV, assertions, different listener names and workload values	XML was validated; corrected invalid ResultCollector XML and CSV header handling.
4	Run draft Load plan	JMeter produced 90 samples with assertion failures because protected calls had 401	Kept raw JTL; traced cause to token extractor placement. Did not present this as a clean pass.
5	Implement reusable Agent Skill runner	Generated real API calls, unique test users, JTL output and metrics parser	Fixed a harness bug where GET requests sent a null body. Re-ran smoke and obtained 0 transport errors.
6	Run Load/Stress/Spike	JMeter produced 90/90/90 samples, 0 errors; runner runs also completed with 0 errors	Checked raw JTL labels and error fields.
7	Run Soak	599,935 ms, 278,460 samples, 0 errors	Verified duration and counts from the latest runner output and raw JTL.
8	Interpret coupon/auth behavior	Identified implementation defects in source	Reproduced relevant response paths through workflow and documented them separately from performance metrics.

AI misinterpretation hunt

1. The initial JMeter artifact looked structurally complete but was not functionally correlated. AI-generated configuration must be checked in GUI/CLI with a protected request, not judged by XML existence.
2. A clean runner result does not prove production scalability because all calls use localhost, SQLite and one Node process.
3. Zero errors in the runner does not mean the SUT meets all functional requirements; it only means this positive path returned successfully.
4. The apparent low latency is expected for loopback and must not be used as an Internet-facing SLA.

AI usage boundary

AI created scaffolding, commands, parsing and draft prose. It did not fabricate raw logs, screenshots, hardware values, video or GitHub issues. Human execution and review remain necessary for screenshots, resource monitoring, video narration, final defect confirmation and submission approval.