## SECTION 1. IDENTIFICATION

| | | |
|---|---|---|
| Product name | : | GASOLINE, UNLEADED |
| Synonyms | : | TN-PE-TM15-X00-1499; LVB87, Regular, Unleaded Gasoline (US Grade), Mid-Grade, Plus, Super, WinterGas, Summer-Gas, Supreme, SuperClean, SuperClean WinterGas, Regu-larClean, PlusClean, Premium, marked or dyed gasoline, TQRUL, transitional quality regular unleaded, BOB, Blend-stock for Oxygenate Blending, Conventional Gasoline, RUL, MUL, SUL, PUL. |
| Product code | : | 100127, 100126, 101823, 100507, 101811, 101814, 100141, 101813, 101810, 101812, 100063, 101822, 100138, 101821, 100064, 101820, 101819, 100506, 101818, 101816, 101817, 100488 |
| Manufacturer or supplier's details | | Petro-Canada<br>P.O. Box 2844, 150 - 6th Avenue South-West<br>Calgary Alberta T2P 3E3<br>Canada, Telephone: 1-866-786-2671 |
| Emergency telephone number | | CHEMTREC: 1-800-424-9300 (toll free) or +1 703-527-3887; Suncor Energy: +1 403-296-3000 |

**Recommended use of the chemical and restrictions on use**

| | | |
|---|---|---|
| Recommended use | : | Unleaded gasoline is used in spark ignition engines including motor vehicles, inboard and outboard boat engines, small engines such as chain saws and lawn mowers, and recrea-tional vehicles. |
| Prepared by | : | Product Safety |

## SECTION 2. HAZARDS IDENTIFICATION

**Emergency Overview**

| | |
|---|---|
| Appearance | Clear liquid. |
| Colour | Clear to slightly yellow or green, undyed liquid. May be dyed red for taxation purposes. |
| Odour | Gasoline |

**GHS Classification**

| | | |
|---|---|---|
| Flammable liquids | : | Category 1 |
| Skin irritation | : | Category 2 |
| Germ cell mutagenicity | : | Category 1B |



Petro-Canada is a Suncor Energy business. ™ Trademark of Suncor Energy Inc. Used under licence.

| | | |
|---|---|---|
| Carcinogenicity | : | Category 1A |
| Reproductive toxicity | : | Category 2 |
| Specific target organ toxicity - single exposure | : | Category 3 (Central nervous system) |
| Specific target organ toxicity - repeated exposure | : | Category 1 |
| Aspiration hazard | : | Category 1 |

**GHS label elements**

Hazard pictograms :

Signal word : Danger

Hazard statements : Extremely flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness.
May cause genetic defects.
May cause cancer.
Suspected of damaging fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.
**Response:**
IF SWALLOWED: Immediately call a POISON CENTER/doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
IF exposed or concerned: Get medical advice/ attention.
Do NOT induce vomiting.


Petro-Canada is a Suncor Energy business.
TM Trademark of Suncor Energy Inc. Used under licence.

If skin irritation occurs: Get medical advice/ attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
**Storage:**
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
**Disposal:**
Dispose of contents/ container to an approved waste disposal plant.

**Potential Health Effects**

Primary Routes of Entry : Eye contact
Ingestion
Inhalation
Skin contact

Aggravated Medical Condition : None known.

**Other hazards**

None known.

| | | |
|---|---|---|
| **IARC** | Group 1: Carcinogenic to humans | |
| | Benzene | 71-43-2 |
| **ACGIH** | Confirmed human carcinogen | |
| | Benzene | 71-43-2 |
| | Confirmed animal carcinogen with unknown relevance to humans | |
| | Gasoline | 86290-81-5 |
| | Ethanol | 64-17-5 |

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

**Hazardous components**

| Chemical name | CAS-No. | Concentration |
|---|---|---|
| Gasoline; Low boiling point naphtha -unspecified | 86290-81-5 | 95 - 100 % |
| toluene | 108-88-3 | 1 - 40 % |


Petro-Canada is a Suncor Energy business.
TM Trademark of Suncor Energy Inc. Used under licence.

| | | |
|---|---|---|
| benzene | 71-43-2 | 0.5 - 1.5 % |
| ethanol | 64-17-5 | 0.1 - 0.3 % |

All above concentrations are in percent by weight.

## SECTION 4. FIRST AID MEASURES

| | | |
|---|---|---|
| If inhaled | : | Move to fresh air.<br>Artificial respiration and/or oxygen may be necessary.<br>Seek medical advice. |
| In case of skin contact | : | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.<br>Wash skin thoroughly with soap and water or use recognized skin cleanser.<br>Wash clothing before reuse.<br>Seek medical advice. |
| In case of eye contact | : | Remove contact lenses.<br>Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.<br>Obtain medical attention. |
| If swallowed | : | Rinse mouth with water.<br>DO NOT induce vomiting unless directed to do so by a physician or poison control center.<br>Never give anything by mouth to an unconscious person.<br>Seek medical advice. |
| Most important symptoms and effects, both acute and delayed | : | Inhalation may cause central nervous system effects.<br>Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.<br>Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.<br>Chronic exposure to benzene may result in increased risk of leukemia and other blood disorders. |
| Notes to physician | : | Treat symptomatically.<br>Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |

## SECTION 5. FIREFIGHTING MEASURES

| | | |
|---|---|---|
| Suitable extinguishing media | : | Dry chemical<br>Carbon dioxide (CO2)<br>Water fog.<br>Foam |
| Unsuitable extinguishing media | : | Do NOT use water jet. |
| Specific hazards during fire-fighting | : | Cool closed containers exposed to fire with water spray. |
| Hazardous combustion products | : | Carbon oxides (CO, CO2), nitrogen oxides (NOx), polynuclear aromatic hydrocarbons, phenols, aldehydes, ketones, smoke and irritating vapours as products of incomplete combustion. |
| Further information | : | Prevent fire extinguishing water from contaminating surface water or the ground water system. |
| Special protective equipment | : | Wear self-contained breathing apparatus and full protective |


Petro-Canada is a Suncor Energy business. TM Trademark of Suncor Energy Inc. Used under licence.

| | |
|---|---|
| for firefighters | wear.<br>Wear a positive-pressure supplied-air respirator with full face-piece. |

## SECTION 6. ACCIDENTAL RELEASE MEASURES

| | | |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | For personal protection see section 8.<br>Ensure adequate ventilation.<br>Evacuate personnel to safe areas.<br>Material can create slippery conditions. |
| Environmental precautions | : | If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : | Prevent further leakage or spillage if safe to do so.<br>Remove all sources of ignition.<br>Soak up with inert absorbent material.<br>Non-sparking tools should be used.<br>Ensure adequate ventilation.<br>Contact the proper local authorities. |

## SECTION 7. HANDLING AND STORAGE

| | | |
|---|---|---|
| Advice on safe handling | : | For personal protection see section 8.<br>Smoking, eating and drinking should be prohibited in the application area.<br>Use only with adequate ventilation.<br>In case of insufficient ventilation, wear suitable respiratory equipment.<br>Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity.<br>Avoid contact with skin, eyes and clothing.<br>Do not ingest.<br>Keep away from heat and sources of ignition.<br>Keep container closed when not in use. |
| Conditions for safe storage | : | Store in original container.<br>Containers which are opened must be carefully resealed and kept upright to prevent leakage.<br>Keep in a dry, cool and well-ventilated place.<br>Keep in properly labelled containers.<br>To maintain product quality, do not store in heat or direct sunlight. |

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Components with workplace control parameters**

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---|---|---|---|---|
| toluene | 108-88-3 | TWA | 50 ppm<br>188 mg/m3 | CA AB OEL |
| | | TWA | 20 ppm | CA BC OEL |


Petro-Canada is a Suncor Energy business. ™ Trademark of Suncor Energy Inc. Used under licence.

| | | | | |
|---|---|---|---|---|
| | | TWAEV | 50 ppm<br>188 mg/m3 | CA QC OEL |
| | | TWA | 20 ppm | ACGIH |
| benzene | 71-43-2 | TWA | 0.5 ppm<br>1.6 mg/m3 | CA AB OEL |
| | | STEL | 2.5 ppm<br>8 mg/m3 | CA AB OEL |
| | | TWA | 0.5 ppm | CA BC OEL |
| | | STEL | 2.5 ppm | CA BC OEL |
| | | TWA | 0.5 ppm | CA ON OEL |
| | | STEL | 2.5 ppm | CA ON OEL |
| | | TWAEV | 1 ppm<br>3 mg/m3 | CA QC OEL |
| | | STEV | 5 ppm<br>15.5 mg/m3 | CA QC OEL |
| | | TWA | 0.5 ppm | ACGIH |
| | | STEL | 2.5 ppm | ACGIH |
| Gasoline; Low boiling point naphtha -unspecified | 86290-81-5 | TWA | 300 ppm | CA AB OEL |
| | | STEL | 500 ppm | CA AB OEL |
| | | TWA | 300 ppm | CA BC OEL |
| | | STEL | 500 ppm | CA BC OEL |
| | | TWA | 300 ppm | ACGIH |
| | | STEL | 500 ppm | ACGIH |
| ethanol | 64-17-5 | TWA | 1,000 ppm<br>1,880 mg/m3 | CA AB OEL |
| | | STEL | 1,000 ppm | CA BC OEL |
| | | TWAEV | 1,000 ppm<br>1,880 mg/m3 | CA QC OEL |
| | | STEL | 1,000 ppm | ACGIH |

**Biological occupational exposure limits**

| Components | CAS-No. | Control parameters | Biological specimen | Sam-pling time | Permissible concentra-tion | Basis |
|---|---|---|---|---|---|---|
| Toluene | 108-88-3 | Toluene | In blood | Prior to last shift of work-week | 0.02 mg/l | ACGIH BEI |
| | | Toluene | Urine | End of shift (As soon as possible after exposure ceases) | 0.03 mg/l | ACGIH BEI |

**Engineering measures** : Adequate ventilation to ensure that Occupational Exposure Limits are not exceeded.
Use only in well-ventilated areas.
Ensure that eyewash station and safety shower are proximal to the work-station location.

**Personal protective equipment**

Respiratory protection : Concentration in air determines protection needed.


Petro-Canada is a Suncor Energy business. ™ Trademark of Suncor Energy Inc. Used under licence.

| | | |
|---|---|---|
| | | Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |
| Filter type | : | A NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection. |
| Hand protection | | |
| Material | : | polyvinyl alcohol (PVA), Viton(R). Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed. |
| Remarks | : | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. |
| Eye protection | : | Wear face-shield and protective suit for abnormal processing problems. |
| Skin and body protection | : | Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. |
| Protective measures | : | Wash contaminated clothing before re-use. |
| Hygiene measures | : | Remove and wash contaminated clothing and gloves, including the inside, before re-use.<br>Wash face, hands and any exposed skin thoroughly after handling. |

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|---|---|---|
| Appearance | : | Clear liquid. |
| Colour | : | Clear to slightly yellow or green, undyed liquid. May be dyed red for taxation purposes. |
| Odour | : | Gasoline |
| Odour Threshold | : | No data available |
| pH | : | No data available |
| Melting point | : | No data available |
| Boiling point/boiling range | : | 25 - 225 °C (77 - 437 °F) |


Petro-Canada is a Suncor Energy business.
TM Trademark of Suncor Energy Inc. Used under licence.

| | | |
|---|---|---|
| Decomposition temperature | | No data available |
| Flash point | : | -50 - -38 °C (-58 - -36 °F)<br>Method: Tagliabue. |
| Auto-Ignition Temperature | : | 257 °C (495 °F) |
| Evaporation rate | : | No data available |
| Flammability | : | Extremely flammable in presence of open flames, sparks, shocks, and heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. Rapid escape of vapour may generate static charge causing ignition. May accumulate in confined spaces. |
| Upper explosion limit | : | 7.6 %(V) |
| Lower explosion limit | : | 1.3 %(V) |
| Vapour pressure | : | < 802.5 mmHg (20 °C / 68 °F) |
| Relative vapour density | : | 3 |
| Relative density | : | 0.685 - 0.8 |
| Solubility(ies) | | |
| Water solubility | : | insoluble |
| Partition coefficient: n-octanol/water | : | No data available |
| Viscosity | | |
| Viscosity, kinematic | : | No data available |

## SECTION 10. STABILITY AND REACTIVITY

| | | |
|---|---|---|
| Reactivity | : | No dangerous reaction known under conditions of normal use. |
| Chemical stability | : | Stable under normal conditions. |
| Possibility of hazardous reactions | : | Hazardous polymerisation does not occur. |
| Conditions to avoid | : | Extremes of temperature and direct sunlight. |
| Incompatible materials | : | Reactive with oxidising agents, acids and interhalogens. |
| Hazardous decomposition products | : | May release COx, NOx, phenols, polycyclic aromatic hydrocarbons, aldehydes, ketones, smoke and irritating vapours when heated to decomposition. |

## SECTION 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

Eye contact

Ingestion



Petro-Canada is a Suncor Energy business.

TM Trademark of Suncor Energy Inc. Used under licence.

Inhalation
Skin contact

**Acute toxicity**

**Product:**

| | | |
|---|---|---|
| Acute oral toxicity | : | Remarks: Based on available data, the classification criteria are not met. |
| Acute inhalation toxicity | : | Remarks: Based on available data, the classification criteria are not met. |
| Acute dermal toxicity | : | Remarks: Based on available data, the classification criteria are not met. |

**Components:**

**Gasoline; Low boiling point naphtha -unspecified:**

| | | |
|---|---|---|
| Acute oral toxicity | : | LD50 (Rat): 13,600 mg/kg, |
| Acute dermal toxicity | : | LD50 (Rabbit): > 3,750 mg/kg, |

**toluene:**

| | | |
|---|---|---|
| Acute oral toxicity | : | LD50 (Rat): 5,580 mg/kg, |
| Acute inhalation toxicity | : | LC50 (Rat): > 20 mg/l<br>Exposure time: 4 h<br>Test atmosphere: vapour |
| Acute dermal toxicity | : | LD50 (Rabbit): 12,125 mg/kg, |

**benzene:**

| | | |
|---|---|---|
| Acute oral toxicity | : | LD50 (Rat): 2,990 mg/kg, |
| Acute inhalation toxicity | : | LC50 (Rat): 13700 ppm<br>Exposure time: 4 h<br>Test atmosphere: vapour |
| Acute dermal toxicity | : | LD50 (Rabbit): > 8,240 mg/kg, |

**ethanol:**

| | | |
|---|---|---|
| Acute oral toxicity | : | LD50 (Rat): 7,060 mg/kg, |
| Acute inhalation toxicity | : | LC50 (Rat): > 32380 ppm<br>Exposure time: 4 h<br>Test atmosphere: vapour |

**Skin corrosion/irritation**

**Product:**

Remarks: Causes skin irritation.


Petro-Canada is a Suncor Energy business.
TM Trademark of Suncor Energy Inc. Used under licence.

**Serious eye damage/eye irritation**

**Product:**

Remarks: Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation**

**Product:**

Remarks: Based on available data, the classification criteria are not met.

**Germ cell mutagenicity**

**Product:**

| | |
|---|---|
| Germ cell mutagenicity-Assessment | May cause genetic defects. |

**Carcinogenicity**

**Product:**

| | |
|---|---|
| Carcinogenicity - Assessment | May cause cancer. |

**Reproductive toxicity**

**Product:**

| | |
|---|---|
| Reproductive toxicity - Assessment | Suspected of damaging fertility or the unborn child. |

**STOT - single exposure**

**Product:**

Remarks: May cause drowsiness or dizziness.

**STOT - repeated exposure**

**Product:**

Remarks: Causes damage to organs through prolonged or repeated exposure.

No data available

**Aspiration toxicity**

**Product:**

May be fatal if swallowed and enters airways.

## SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

**Product:**

Toxicity to fish :

Remarks: No data available


Petro-Canada is a Suncor Energy business. ™ Trademark of Suncor Energy Inc. Used under licence.

| | | |
|---|---|---|
| Toxicity to daphnia and other aquatic invertebrates | : | Remarks: No data available |
| Toxicity to algae | : | Remarks: No data available |
| Toxicity to bacteria | : | Remarks: No data available |

**Persistence and degradability**

**Product:**

| | | |
|---|---|---|
| Biodegradability | : | Remarks: No data available |

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

| | | |
|---|---|---|
| Waste from residues | : | The product should not be allowed to enter drains, water courses or the soil.<br>Offer surplus and non-recyclable solutions to a licensed disposal company.<br>Waste must be classified and labelled prior to recycling or disposal.<br>Send to a licensed waste management company.<br>Dispose of as hazardous waste in compliance with local and national regulations.<br>Dispose of product residue in accordance with the instructions of the person responsible for waste disposal. |

## SECTION 14. TRANSPORT INFORMATION

**International Regulations**

**IATA-DGR**

| | | |
|---|---|---|
| UN/ID No. | : | UN 1203 |
| Proper shipping name | : | Gasoline |
| Class | : | 3 |
| Packing group | : | II |
| Labels | : | Class 3 - Flammable Liquid |
| Packing instruction (cargo aircraft) | : | 364 |

**IMDG-Code**

| | | |
|---|---|---|
| UN number | : | UN 1203 |
| Proper shipping name | : | GASOLINE |


Petro-Canada is a Suncor Energy business. ™ Trademark of Suncor Energy Inc. Used under licence.

| | | |
|---|---|---|
| Class | : | 3 |
| Packing group | : | II |
| Labels | : | 3 |
| EmS Code | : | F-E, S-E |
| Marine pollutant | : | no |

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

**National Regulations**

**TDG**

| | | |
|---|---|---|
| UN number | : | UN 1203 |
| Proper shipping name | : | GASOLINE |
| Class | : | 3 |
| Packing group | : | II |
| Labels | : | 3 |
| ERG Code | : | 128 |
| Marine pollutant | : | no |

## SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all of the information required by the HPR.

**The components of this product are reported in the following inventories:**

**DSL** On the inventory, or in compliance with the inventory

## SECTION 16. OTHER INFORMATION

| | | |
|---|---|---|
| For Copy of SDS | : | Internet: www.petro-canada.ca/msds<br>Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228<br>For Product Safety Information: 1 905-804-4752 |
| Prepared by | : | Product Safety |
| Revision Date | : | 2021/02/18 |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.


Petro-Canada is a Suncor Energy business.
TM Trademark of Suncor Energy Inc. Used under licence.