HIT-HY 200-A V3

Safety information for 2-Component-products

Issue date: 13/04/2023 Revision date: 13/04/2023 Supersedes: 09/07/2021 Version: 1.1

SECTION 1: Kit identification

1.1 Product identifier

Product name HIT-HY 200-A V3



Product code BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti, Inc.
Legacy Tower, Suite 1000
7250 Dallas Parkway
TX 75024 Plano - USA
T +1 9724035800
1-800-879-8000 toll free - F +1 918 254 0522

SECTION 2: General information

Storage Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3: Kit contents

Classification of the Product

GHS-US classification

Eye Irrit. 2 H319 - Causes serious eye irritation.
Skin Sens. 1 H317 - May cause an allergic skin reaction.

Label elements

GHS US labelling

Hazard pictograms (GHS US)



GHS07

Signal word (GHS US) Warning

Hazardous ingredients methacrylates, dibenzoyl peroxide


Hazard statements (GHS US) May cause an allergic skin reaction.
Causes serious eye irritation.

Precautionary statements (GHS US) Wear eye protection, protective clothing, protective gloves.
Do not get in eyes, on skin, or on clothing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If on skin: Wash with plenty of water.

Additional information

2-Component-foilpack, contains:
Component A: Urethane methacrylate resin, inorganic filler
Component B: Dibenzoyl peroxide, phlegmatized



Name	General description	Quantity	Unit	GHS-US classification
HIT-HY 200-A V3, B		1	pcs (pieces)	Eye Irrit. 2, H319 Skin Sens. 1, H317
HIT-HY 200-A V3, A		1	pcs (pieces)	Skin Sens. 1, H317

SECTION 4: General advice

General advice — For professional users only

SECTION 5: Safe handling advice

General measures — Spilled material may present a slipping hazard

Environmental precautions — Prevent entry to sewers and public waters
Notify authorities if liquid enters sewers or public waters

Storage conditions — Keep cool. Protect from sunlight.

Precautions for safe handling — Wear personal protective equipment
Avoid contact with skin and eyes
Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work
Provide good ventilation in process area to prevent formation of vapour

Methods for cleaning up — This material and its container must be disposed of in a safe way, and as per local legislation
Mechanically recover the product
Store away from other materials.

For containment — Collect spillage.

Incompatible materials — Sources of ignition
Direct sunlight

Incompatible products — Strong bases
Strong acids

SECTION 6: First aid measures

First-aid measures after eye contact — Rinse immediately with plenty of water
Remove contact lenses, if present and easy to do. Continue rinsing.
Obtain medical attention if pain, blinking or redness persists

First-aid measures after ingestion	Rinse mouth Get medical advice/attention. Do not induce vomiting Obtain emergency medical attention
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air Allow the victim to rest
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/… If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects after eye contact	Causes serious eye irritation.
Symptoms/effects after skin contact	May cause an allergic skin reaction.

SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available

HIT-HY 200-A V3, A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 4/13/2023 Issue date: 4/13/2023 Supersedes: 7/9/2021Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form	Mixture
Product name	HIT-HY 200-A V3, A
Product code	BU Anchor

1.2. Recommended use and restrictions on use

Use of the substance/mixture	Composite mortar component for fasteners in the construction industry
Recommended use	For professional use only

1.3. Supplier

Supplier
Hilti, Inc.
Legacy Tower, Suite 1000
7250 Dallas Parkway
Plano, TX 75024
USA
T +1 9724035800
1-800-879-8000 toll free - F +1 918 254 0522

Department issuing data specification sheet
Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
Kaufering, 86916
Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number

Chem-Trec
Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada)
Tel.: 703 527 3887 (Other countries)
+1 918 8723000
1-800-879-8000 toll free

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)



Signal word (GHS US) Warning

Hazard statements (GHS US)
H317 - May cause an allergic skin reaction.

Precautionary statements (GHS US)
P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P302+P352 - If on skin: Wash with plenty of water.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Quartz (SiO2)	CAS-No.: 14808-60-7	40 – 60	Carc. 1A, H350
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester	CAS-No.: 2082-81-7	10 – 25	Skin Sens. 1B, H317
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	CAS-No.: 27813-02-1	5 - 8	Eye Irrit. 2A, H319 Skin Sens. 1, H317
1,1'-(p-tolylimino)dipropan-2-ol	CAS-No.: 38668-48-3	0.1 – 1	Acute Tox. 2 (Oral), H300 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general: Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact: Wash contaminated clothing before reuse. Wash with plenty of water/…. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion: Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential adverse human health effects and symptoms: No additional information available.

Symptoms/effects after skin contact: May cause an allergic skin reaction.

Symptoms/effects after eye contact: May cause severe irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.

6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 – 25 °C

Heat and ignition sources	Keep away from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HIT-HY 200-A V3, A	
USA - OSHA - Occupational Exposure Limits	
Local name	Quartz (Total Dust) (Silica: Crystalline)
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts

Quartz (SiO2) (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Silica crystaline - quartz
ACGIH OEL TWA	0.025 mg/m³ (Respirable fraction)
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, crystalline quartz, respirable dust
Remark (OSHA)	(3) See Table Z-3.

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)
No additional information available

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)
No additional information available

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)
No additional information available

Additional information	The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Appropriate engineering controls

Appropriate engineering controls	Ensure adequate ventilation.
Environmental exposure controls	Not applicable.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Materials for protective clothing:
Long sleeved protective clothing

Hand protection:				
Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.				
Type	**Material**	**Permeation**	**Thickness (mm)**	**Penetration**
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	

Eye protection:		
Wear security glasses which protect from splashes		
Type	**Field of application**	**Characteristics**
Safety glasses	Droplet	clear

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Blue
Odour	characteristic
Odour threshold	Not determined
pH	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	240 °C
Flash point	> 109 °C DIN EN ISO 1523
Relative evaporation rate (butylacetate=1)	No data available
Flammability (solid, gas)	Flammable.
Vapour pressure	No data available
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	1.8 g/ml AW 4.3.23
Solubility	Water: % Not miscible
Partition coefficient n-octanol/water (Log Pow)	No data available
Auto-ignition temperature	Not self-igniting
Decomposition temperature	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	35 – 65 Pa·s (HN-0333)
Explosive limits	No data available
Explosive properties	Product is not explosive.
Oxidising properties	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
LD50 oral rat	25 mg/kg
LD50 dermal rat	> 2000 mg/kg

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LD50 oral rat	10066 mg/kg
LD50 dermal rat	> 3000 mg/kg

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >=2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	≥ 5000 mg/kg bodyweight (Rabbit; Experimental value)

Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Not classified
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified

Quartz (SiO2) (14808-60-7)	
IARC group	1 - Carcinogenic to humans

Quartz (SiO2) (14808-60-7)	
National Toxicology Program (NTP) Status	Known Human Carcinogens

Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Viscosity, kinematic	No data available
Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

SECTION 12: Ecological information

12.1. Toxicity

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
LC50 - Fish [1]	≈ 17 mg/l
LC50 - Other aquatic organisms [1]	245 mg/l
EC50 - Crustacea [1]	28.8 mg/l
NOEC (acute)	57.8 mg/l

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LC50 - Other aquatic organisms [1]	9.79 mg/l
NOEC (acute)	7.51 mg/l
NOEC (chronic)	20 mg/l

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LC50 - Fish [1]	493 mg/l (48 h; Leuciscus idus; GLP)
EC50 - Crustacea [1]	> 143 mg/l (48 h; Daphnia magna; GLP)
ErC50 algae	97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
Threshold limit - Algae [1]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)
Threshold limit - Algae [2]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)

12.2. Persistence and degradability

HIT-HY 200-A V3, A	
Persistence and degradability	Not established.

Quartz (SiO2) (14808-60-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)

Quartz (SiO2) (14808-60-7)	
ThOD	Not applicable (inorganic)

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Not rapidly degradable	
Biodegradation	84 %

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

HIT-HY 200-A V3, A	
Bioaccumulative potential	Not established.

Quartz (SiO2) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
Partition coefficient n-octanol/water (Log Kow)	2.1

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Partition coefficient n-octanol/water (Log Pow)	3.1

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
BCF - Fish [1]	≤ 100
BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).

12.4. Mobility in soil

Quartz (SiO2) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.9 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Other information: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

Quartz (SiO2) (14808-60-7)
Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

WARNING: This product can expose you to 1,2-dihydroxybenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date 04/13/2023

Other information None.

Full text of H-statements	
H300	Fatal if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H350	May cause cancer.


Abbreviations and acronyms	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose

Abbreviations and acronyms	
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

NFPA health hazard — 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard — 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity — 0 - Material that in themselves are normally stable, even under fire conditions.



Indication of changes:			
Section	**Changed item**	**Change**	**Comments**
9	Physical and chemical properties	Modified	

SDS_US_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-HY 200-A V3, B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 4/13/2023 Issue date: 4/13/2023 Supersedes: 7/9/2021Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form	Mixture
Product name	HIT-HY 200-A V3, B
Product code	BU Anchor

1.2. Recommended use and restrictions on use

Use of the substance/mixture	Composite mortar component for fasteners in the construction industry
Recommended use	For professional use only

1.3. Supplier

Supplier
Hilti, Inc.
Legacy Tower, Suite 1000
7250 Dallas Parkway
Plano, TX 75024
USA
T +1 9724035800
1-800-879-8000 toll free - F +1 918 254 0522

Department issuing data specification sheet
Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
Kaufering, 86916
Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Chem-Trec Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada) Tel.: 703 527 3887 (Other countries) +1 918 8723000 1-800-879-8000 toll free

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)



Signal word (GHS US)	Warning
Hazard statements (GHS US)	H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.
Precautionary statements (GHS US)	P280 - Wear eye protection, protective clothing, protective gloves. P262 - Do not get in eyes, on skin, or on clothing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P302+P352 - If on skin: Wash with plenty of water.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Quartz (SiO2)	CAS-No.: 14808-60-7	40 – 60	Carc. 1A, H350
dibenzoyl peroxide	CAS-No.: 94-36-0	10 - 15	Org. Perox. B, H241 Eye Irrit. 2A, H319 Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general: Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact: Wash contaminated clothing before reuse. Wash with plenty of water/…. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion: Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact: May cause an allergic skin reaction.

Symptoms/effects after eye contact: May cause severe irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Water spray. Carbon dioxide. Dry powder. Foam. Sand.

Unsuitable extinguishing media: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.

6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 – 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HIT-HY 200-A V3, B	
USA - ACGIH - Occupational Exposure Limits	
Local name	Benzoyl peroxide
ACGIH OEL TWA	5 mg/m³
Remark (ACGIH)	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OSHA PEL TWA [1]	5 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Quartz (SiO2) (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Silica crystaline - quartz
ACGIH OEL TWA	0.025 mg/m³ (Respirable fraction)
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, crystalline quartz, respirable dust
Remark (OSHA)	(3) See Table Z-3.

dibenzoyl peroxide (94-36-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Benzoyl peroxide
ACGIH OEL TWA	5 mg/m³
Remark (ACGIH)	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OSHA PEL TWA [1]	5 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Additional information	The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Appropriate engineering controls

Appropriate engineering controls	Ensure adequate ventilation.
Environmental exposure controls	Not applicable.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Materials for protective clothing:
Long sleeved protective clothing

Hand protection:				
Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.				
Type	**Material**	**Permeation**	**Thickness (mm)**	**Penetration**
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	

Eye protection:		
Wear security glasses which protect from splashes		
Type	**Field of application**	**Characteristics**
Safety glasses	Droplet	clear

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	white
Odour	characteristic
Odour threshold	Not determined
pH	6 – 7
Melting point	No data available
Freezing point	No data available
Boiling point	100 °C
Flash point	No data available
Relative evaporation rate (butylacetate=1)	No data available
Flammability (solid, gas)	Flammable.
Vapour pressure	23 hPa
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	1.9 g/cm³
Solubility	Water: % Miscible with water
Partition coefficient n-octanol/water (Log Pow)	No data available
Auto-ignition temperature	Not self-igniting

Decomposition temperature	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	25 – 55 Pa·s HN-0333
Explosive limits	No data available
Explosive properties	Product is not explosive.
Oxidising properties	No data available

9.2. Other information

SADT	65 °C dibenzoyl peroxide

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified
Skin corrosion/irritation	Not classified pH: 6 – 7
Serious eye damage/irritation	Causes serious eye irritation. pH: 6 – 7
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified

Quartz (SiO2) (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens

dibenzoyl peroxide (94-36-0)	
IARC group	3 - Not classifiable

Reproductive toxicity	Not classified
STOT-single exposure	Not classified

STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Viscosity, kinematic	No data available
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

SECTION 12: Ecological information

12.1. Toxicity

dibenzoyl peroxide (94-36-0)	
EC50 - Crustacea [1]	0.11 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
LC50 - Fish [2]	0.0602 mg/l (96h; Oncorhynchus mykiss; ECHA)
ErC50 algae	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC (acute)	0.0316 mg/l (96h; Oncorhynchus mykiss; ECHA)
NOEC chronic fish	0.001 mg/l

12.2. Persistence and degradability

HIT-HY 200-A V3, B	
Persistence and degradability	Not established.

Quartz (SiO2) (14808-60-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

dibenzoyl peroxide (94-36-0)	
Persistence and degradability	Readily biodegradable in water. Not established. May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

HIT-HY 200-A V3, B	
Bioaccumulative potential	Not established.

Quartz (SiO2) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.

dibenzoyl peroxide (94-36-0)	
Partition coefficient n-octanol/water (Log Pow)	3.71
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

12.4. Mobility in soil

Quartz (SiO2) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.

dibenzoyl peroxide (94-36-0)	
Surface tension	No data available (test not performed)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.

12.5. Other adverse effects

Other information: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste): Disposal must be done according to official regulations.



Product/Packaging disposal recommendations: After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials: Avoid release to the environment.

SECTION 14: Transport information


In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
Special provision(s) applied : 375	Special provision(s) applied : 969	Special provision(s) applied : A197	Special provision(s) applied : 375
These substances when carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.			
14.1. UN number or ID number			
UN 3077	UN 3077	UN 3077	UN 3077
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)	Environmentally hazardous substance, solid, n.o.s. (dibenzoyl peroxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)
Transport document description			
UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III, (-)	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III	UN 3077 Environmentally hazardous substance, solid, n.o.s. (dibenzoyl peroxide), 9, III	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III

ADR	IMDG	IATA	RID
14.3. Transport hazard class(es)			
9	9	9	9
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
Environmentally hazardous substances derogation applies (quantity of liquids ≤ 5 litres or net mass of solids ≤ 5 kg). The environmentally hazardous substance mark is therefore not required, as stated in the ADR regulation, section 5.2.1.8.1.			
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	M7
Special provisions (ADR)	274, 335, 375, 601
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3
Orange plates	
Tunnel restriction code (ADR)	-

Transport by sea

Special provisions (IMDG)	274, 335, 966, 967, 969
Limited quantities (IMDG)	5 kg
Packing instructions (IMDG)	LP02, P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-F
Stowage category (IMDG)	A
Stowage and handling (IMDG)	SW23
MFAG-No	171

Air transport

PCA packing instructions (IATA)	956
PCA max net quantity (IATA)	400kg
CAO packing instructions (IATA)	956
Special provisions (IATA)	A97, A158, A179, A197, A215

Rail transport

Special provisions (RID)	274, 335, 375, 601
Limited quantities (RID)	5kg
Packing instructions (RID)	P002, IBC08, LP02, R001

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

dibenzoyl peroxide	CAS-No. 94-36-0	10 - 15%

15.2. International regulations

Quartz (SiO2) (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


Revision date	04/13/2023
Other information	None.

Full text of H-statements	
H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H350	May cause cancer.

Abbreviations and acronyms	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

Abbreviations and acronyms	
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

NFPA health hazard	1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard	1 - Materials that must be preheated before ignition can occur.
NFPA reactivity	0 - Material that in themselves are normally stable, even under fire conditions.



SDS_US_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.