

Folder engine

31 printable files

engine/ChessEngine.java
engine/board/ChessBoard.java
engine/board/ChessBoardController.java
engine/board/ChessBoardInitializer.java
engine/board/ChessBoardReader.java
engine/board/ChessBoardWriter.java
engine/generator/Direction.java
engine/generator/DirectionalGenerator.java
engine/generator/DistanceGenerator.java
engine/generator/KnightGenerator.java
engine/generator/MoveGenerator.java
engine/generator/PawnDistanceGenerator.java
engine/move/Capture.java
engine/move/Castling.java
engine/move/ChessMove.java
engine/move/EnPassant.java
engine/move/LongCastling.java
engine/move/Moves.java
engine/move/Promotion.java
engine/move/PromotionWithCapture.java
engine/move/ShortCastling.java
engine/move/StandardMove.java
engine/piece/Bishop.java
engine/piece/ChessPiece.java
engine/piece/King.java
engine/piece/Knight.java
engine/piece/Pawn.java
engine/piece/Position.java
engine/piece/PromotableChessPiece.java
engine/piece/Queen.java
engine/piece/Rook.java

engine/ChessEngine.java

```
package engine;

import chess.ChessController;
import chess.ChessView;
import chess.PlayerColor;
import engine.board.ChessBoard;
import engine.board.ChessBoardController;
import engine.board.ChessBoardInitializer;
import engine.move.ChessMove;
import engine.move.Moves;
import engine.piece.Position;

/**
 * Main engine class responsible for managing the chess game logic, turns, and
 * interactions with the view.
 * Implements the {@link ChessController} interface.
 *
 * @author Leonard Cseres
```

```

* @author Aladin Iseni
*/
public final class ChessEngine implements ChessController {
    private ChessBoardController controller;
    private PlayerColor turnColor;

    /**
     * Starts the chess game, initializes the board, and starts the view.
     *
     * @param view the {@link ChessView} used for displaying the game
     */
    @Override
    public void start(ChessView view) {
        controller = new ChessBoardController(view);
        newGame();
    }

    /**
     * Resets the game state to start a new game.
     *
     * @throws IllegalStateException if the ChessEngine was not initialized properly
     */
    @Override
    public void newGame() {
        turnColor = PlayerColor.WHITE;
        if (controller == null) {
            throw new IllegalStateException("Call ChessEngine.start() before starting a new game");
        }
        ChessBoardInitializer.initializeBoard(controller);
    }

    /**
     * Attempts to make a move on the chessboard from the given coordinates.
     *
     * @param fromX the starting X-coordinate
     * @param fromY the starting Y-coordinate
     * @param toX the destination X-coordinate
     * @param toY the destination Y-coordinate
     * @return true if the move is successful, false otherwise
     */
    @Override
    public boolean move(int fromX, int fromY, int toX, int toY) {
        Position from = new Position(fromX, fromY);
        Position to = new Position(toX, toY);
        assert from.isValid() : "From position is invalid";
        assert to.isValid() : "To position is invalid";
        assert controller.getBoard().containsKey(from) : "From position is invalid";

        ChessBoard board = controller.getBoard();
        Moves moves = board.get(from).getPossibleMoves(board, from);
        ChessMove move = moves.getMove(to);
        if (!board.isValidMove(move, turnColor)) {
            return false;
        }
        move.execute(controller);
        nextTurn();
        updateState();
        return true;
    }

    /**
     * Switches to the next player's turn.
     */
    private void nextTurn() {
        turnColor = getOpponentPlayer();
    }

```

```

    }

    /**
     * Determines the color of the opposing player.
     *
     * @return the color of the opposing player
     */
    private PlayerColor getOpponentPlayer() {
        return turnColor == PlayerColor.WHITE ? PlayerColor.BLACK : PlayerColor.WHITE;
    }

    /**
     * Displays a message to the view if an event occurred
     */
    private void updateState() {
        ChessBoard board = controller.getBoard();
        String event;
        if (board.isCheckmate(turnColor)) {
            event = "Checkmate! " + getOpponentPlayer() + " won!";
        } else if (board.isStalemate(turnColor)) {
            event = "Stalemate... It's a draw";
        } else if (board.isDraw()) {
            event = "Draw! Impossible to checkmate";
        } else if (board.isKingInCheck(turnColor)) {
            event = "Check!";
        } else {
            event = null;
        }

        if (event != null) {
            controller.getView().displayMessage(event);
        }
    }
}

```

engine/board/ChessBoard.java

```

package engine.board;

import chess.PieceType;
import chess.PlayerColor;
import engine.move.ChessMove;
import engine.move.Moves;
import engine.piece.ChessPiece;
import engine.piece.Position;
import engine.piece.Queen;

import java.util.Collections;
import java.util.HashMap;
import java.util.Map;

/**
 * Represents the chessboard, managing the state of the game, including pieces,
 * positions, and special rules like pawn promotion and check.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class ChessBoard implements ChessBoardReader, ChessBoardWriter, Cloneable {
    private Map<Position, ChessPiece> pieces = new HashMap<>();
    private Map<PlayerColor, Position> kings = new HashMap<>();
    private ChessMove lastMove = null;
}

```

```

/**
 * Retrieves the chess piece at the specified position.
 *
 * @param pos the position on the chessboard
 * @return the {@link ChessPiece} at the specified position, or null if empty
 */
@Override
public ChessPiece get(Position pos) {
    return pieces.get(pos);
}

/**
 * Checks if a given position contains a chess piece.
 *
 * @param pos the position to check
 * @return true if a piece exists at the given position, false otherwise
 */
@Override
public boolean containsKey(Position pos) {
    return pieces.containsKey(pos);
}

/**
 * Get all the chessboard pieces
 *
 * @return a map of the positions its piece
 */
@Override
public Map<Position, ChessPiece> getPieces() {
    return Collections.unmodifiableMap(pieces);
}

/**
 * Retrieves the last move that was made on the chessboard.
 *
 * @return the last move that was made on the chessboard
 */
@Override
public ChessMove getLastMove() {
    return lastMove;
}

/**
 * Sets the last move that was made on the chessboard.
 *
 * @param chessMove the last move that was made
 */
@Override
public void setLastMove(ChessMove chessMove) {
    lastMove = chessMove;
}

/**
 * Places a chess piece at the specified position on the board.
 * Updates the view and tracks the position of kings.
 *
 * @param pos the position to place the piece
 * @param piece the {@link ChessPiece} to place
 */
@Override
public void put(Position pos, ChessPiece piece) {
    pieces.put(pos, piece);
    if (piece.getType() == PieceType.KING) {
        kings.put(piece.getColor(), pos);
    }
}

```

```

}

/**
 * Removes a chess piece from the specified position.
 *
 * @param pos the position to remove the piece from
 * @throws IllegalStateException if no piece exists at the position
 */
@Override
public void remove(Position pos) {
    if (pieces.get(pos) == null) {
        throw new IllegalStateException("No piece exists at " + pos);
    }
    pieces.remove(pos);
}

/**
 * Clears all pieces from the chessboard.
 */
@Override
public void clear() {
    pieces.clear();
}

/**
 * Handles pawn promotion at the given position.
 * Defaults to a queen.
 *
 * @param pos the position of the pawn being promoted
 */
@Override
public void handlePawnPromotion(Position pos) {
    put(pos, new Queen(get(pos).getColor()));
}

/**
 * Checks if the king of the given color is in check.
 *
 * @param kingColor the color of the king to check
 * @return true if the king is in check, false otherwise
 */
@Override
public boolean isKingInCheck(PlayerColor kingColor) {
    Position kingPosition = kings.get(kingColor);
    return isSquareAttacked(kingPosition, kingColor, null);
}

/**
 * Checks if the square at the given position is attacked by any piece of the
 * given color.
 *
 * @param position the position to check
 * @param color the color of the attacking pieces
 * @param ignore the piece type to ignore, can be set to null to check all
 * piece types
 * @return true if the square is attacked, false otherwise
 */
@Override
public boolean isSquareAttacked(Position position, PlayerColor color, PieceType ignore) {
    for (Map.Entry<Position, ChessPiece> entry : pieces.entrySet()) {
        ChessPiece piece = entry.getValue();
        if (piece.getColor() != color && (ignore == null || ignore != piece.getType())) {
            Moves possibleMoves = piece.getPossibleMoves(this, entry.getKey());
            if (possibleMoves.getMove(position) != null) {
                return true;
            }
        }
    }
}

```

```

    }
}

return false;
}

/**
 * Checks if the player of the given color is in checkmate.
 *
 * @param color the color of the player to check
 * @return true if the player is in checkmate, false otherwise
 */
public boolean isCheckmate(PlayerColor color) {
    return isKingInCheck(color) && hasNoLegalMoves(color);
}

/**
 * Checks if the player of the given color is in stalemate.
 *
 * @param color the color of the player to check
 * @return true if the player is in stalemate, false otherwise
 */
public boolean isStalemate(PlayerColor color) {
    return !isKingInCheck(color) && hasNoLegalMoves(color);
}

/**
 * Checks if the game is a draw based on insufficient material.
 * Handles scenarios: K vs K, K+B vs K, K+N vs K, and K+B vs K+B (same colored
 * squares)
 *
 * @return true if the game is a draw due to insufficient material
 */
public boolean isDraw() {
    // Count pieces and track bishops for each player
    int whitePieces = 0;
    int blackPieces = 0;
    Position whiteBishopPos = null;
    Position blackBishopPos = null;

    for (Map.Entry<Position, ChessPiece> entry : pieces.entrySet()) {
        ChessPiece piece = entry.getValue();
        if (piece.getColor() == PlayerColor.WHITE) {
            whitePieces++;
            if (piece.getType() == PieceType.BISHOP) {
                whiteBishopPos = entry.getKey();
            }
        } else {
            blackPieces++;
            if (piece.getType() == PieceType.BISHOP) {
                blackBishopPos = entry.getKey();
            }
        }
    }

    // King vs King
    if (whitePieces == 1 && blackPieces == 1) {
        return true;
    }

    // Cases with 2 pieces vs 1 piece
    if ((whitePieces == 2 && blackPieces == 1) || (whitePieces == 1 && blackPieces == 2)) {
        PlayerColor morePieces = whitePieces == 2 ? PlayerColor.WHITE : PlayerColor.BLACK;
        // Find the extra piece
        for (Map.Entry<Position, ChessPiece> entry : pieces.entrySet()) {
            ChessPiece piece = entry.getValue();
            if (piece.getColor() == morePieces && piece.getType() != PieceType.KING) {

```

```

        // King + Bishop vs King or King + Knight vs King
        return piece.getType() == PieceType.BISHOP ||
            piece.getType() == PieceType.KNIGHT;
    }
}

// King + Bishop vs King + Bishop (same colored squares)
if (whitePieces == 2 && blackPieces == 2 && whiteBishopPos != null && blackBishopPos != null) {
    return whiteBishopPos.getColor() == blackBishopPos.getColor();
}

return false;
}

public boolean isValidMove(ChessMove move, PlayerColor turnColor) {
    if (move == null || move.getFromPiece().getColor() != turnColor) {
        return false;
    }
    ChessBoard clonedBoard = this.clone();
    move.execute(clonedBoard);

    return !clonedBoard.isKingInCheck(turnColor);
}

/**
 * Determines if the player of the given color has any legal moves left.
 *
 * @param color the color of the player to check
 * @return true if the player has no legal moves, false otherwise
 */
private boolean hasNoLegalMoves(PlayerColor color) {
    for (Map.Entry<Position, ChessPiece> entry : pieces.entrySet()) {
        ChessPiece piece = entry.getValue();
        if (piece.getColor() == color) {
            Position pos = entry.getKey();
            Moves possibleMoves = piece.getPossibleMoves(this, pos);

            // Check each possible move
            for (ChessMove move : possibleMoves.getAllMoves()) {
                // Create a clone to test the move
                ChessBoard testBoard = this.clone();
                ChessPiece movingPiece = testBoard.get(pos);

                // Make the move on the test board
                testBoard.remove(pos);
                testBoard.put(move.getTo(), movingPiece);

                // If this move doesn't leave/put the king in check, it's a legal move
                if (!testBoard.isKingInCheck(color)) {
                    return false;
                }
            }
        }
    }

    return true;
}

/**
 * Creates a deep clone of this chessboard, including all pieces.
 *
 * @return a new {@link ChessBoard} instance identical to this one
 * @throws AssertionError if the clone failed. We assert it won't happen
 */
@Override
public ChessBoard clone() {
    try {

```

```

        ChessBoard clonedBoard = (ChessBoard) super.clone();

        // Deep copy the pieces map
        clonedBoard.pieces = new HashMap<>();
        for (Map.Entry<Position, ChessPiece> entry : pieces.entrySet()) {
            clonedBoard.pieces.put(entry.getKey(), entry.getValue().clone());
        }
        // Deep copy the kings map
        clonedBoard.kings = new HashMap<>(kings);
        return clonedBoard;
    } catch (CloneNotSupportedException e) {
        throw new AssertionError("Cloning failed", e);
    }
}
}

```

engine/board/ChessBoardController.java

```

package engine.board;

import chess.ChessView;
import chess.PlayerColor;
import engine.move.ChessMove;
import engine.piece.Bishop;
import engine.piece.ChessPiece;
import engine.piece.Knight;
import engine.piece.Position;
import engine.piece.PromotableChessPiece;
import engine.piece.Queen;
import engine.piece.Rook;

/**
 * Wraps the ChessBoard, implementing the ChessBoardWrite interface such that
 * it can interact with the ChessView in conjunction with the ChessBoard.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class ChessBoardController implements ChessBoardWriter {
    private final ChessBoard board = new ChessBoard();
    private final ChessView view;

    /**
     * Instantiates the ChessBoardController.
     *
     * @param view the ChessView
     */
    public ChessBoardController(ChessView view) {
        this.view = view;
        this.view.startView();
    }

    /**
     * Gets the associated ChessView.
     *
     * @return the ChessView
     */
    public ChessView getView() {
        return view;
    }
}

```



```

    * Gets the associated ChessBoard.
    *
    * @return the ChessBoard
    */
    public ChessBoard getBoard() {
        return board;
    }

    /**
     * Places a chess piece at the specified position on the board.
     * Updates the view and tracks the position of kings.
     *
     * @param pos the position to place the piece
     * @param piece the {@link ChessPiece} to place
     */
    @Override
    public void put(Position pos, ChessPiece piece) {
        board.put(pos, piece);
        view.putPiece(piece.getType(), piece.getColor(), pos.x(), pos.y());
    }

    /**
     * Removes a chess piece from the specified position.
     *
     * @param pos the position to remove the piece from
     * @throws IllegalStateException if no piece exist at the position
     */
    @Override
    public void remove(Position pos) {
        board.remove(pos);
        view.removePiece(pos.x(), pos.y());
    }

    /**
     * Clears all pieces from the chessboard.
     */
    @Override
    public void clear() {
        for (Position pos : board.getPieces().keySet()) {
            view.removePiece(pos.x(), pos.y());
        }
        board.clear();
    }

    /**
     * Sets the last move that was made on the chessboard.
     *
     * @param chessMove the last move that was made
     */
    @Override
    public void setLastMove(ChessMove chessMove) {
        board.setLastMove(chessMove);
    }

    /**
     * Handles pawn promotion at the given position.
     * Prompts the user through the ChessView.
     *
     * @param pos the position of the pawn being promoted
     */
    @Override
    public void handlePawnPromotion(Position pos) {
        PlayerColor color = board.get(pos).getColor();
        PromotableChessPiece chosen = view.askUser(
            "Promotion",

```

```

        "Choose piece for promotion:",
        new Queen(color), new Rook(color), new Bishop(color), new Knight(color));
    put(pos, chosen);
}
}

```

engine/board/ChessBoardInitializer.java

```

package engine.board;

import chess.PlayerColor;
import engine.piece.*;

/**
 * Utility class for initializing a chessboard with the standard starting piece
 * configuration.
 * This class is not meant to be instantiated.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public abstract class ChessBoardInitializer {
    /**
     * Initializes the chessboard by placing all pieces in their standard starting
     * positions.
     *
     * @param board the {@link ChessBoard} to initialize
     */
    public static void initializeBoard(ChessBoardWriter board) {
        board.clear();
        placePawns(board);
        placeRooks(board);
        placeKnights(board);
        placeBishops(board);
        placeKings(board);
        placeQueens(board);
    }

    /**
     * Places all pawns on the chessboard in their starting positions.
     *
     * @param board the {@link ChessBoardWriter} to populate with pawns
     */
    private static void placePawns(ChessBoardWriter board) {
        for (int i = 0; i < 8; i++) {
            board.put(new Position(i, 1), new Pawn(PlayerColor.WHITE));
            board.put(new Position(i, 6), new Pawn(PlayerColor.BLACK));
        }
    }

    /**
     * Places all rooks on the chessboard in their starting positions.
     *
     * @param board the {@link ChessBoardWriter} to populate with rooks
     */
    private static void placeRooks(ChessBoardWriter board) {
        board.put(new Position(0, 0), new Rook(PlayerColor.WHITE));
        board.put(new Position(7, 0), new Rook(PlayerColor.WHITE));
        board.put(new Position(0, 7), new Rook(PlayerColor.BLACK));
        board.put(new Position(7, 7), new Rook(PlayerColor.BLACK));
    }
}

```

```

/**
 * Places all knights on the chessboard in their starting positions.
 *
 * @param board the {@link ChessBoardWriter} to populate with knights
 */
private static void placeKnights(ChessBoardWriter board) {
    board.put(new Position(1, 0), new Knight(PlayerColor.WHITE));
    board.put(new Position(6, 0), new Knight(PlayerColor.WHITE));
    board.put(new Position(1, 7), new Knight(PlayerColor.BLACK));
    board.put(new Position(6, 7), new Knight(PlayerColor.BLACK));
}

/**
 * Places all bishops on the chessboard in their starting positions.
 *
 * @param board the {@link ChessBoardWriter} to populate with bishops
 */
private static void placeBishops(ChessBoardWriter board) {
    board.put(new Position(2, 0), new Bishop(PlayerColor.WHITE));
    board.put(new Position(5, 0), new Bishop(PlayerColor.WHITE));
    board.put(new Position(2, 7), new Bishop(PlayerColor.BLACK));
    board.put(new Position(5, 7), new Bishop(PlayerColor.BLACK));
}

/**
 * Places the kings on the chessboard in their starting positions.
 *
 * @param board the {@link ChessBoardWriter} to populate with kings
 */
private static void placeKings(ChessBoardWriter board) {
    board.put(new Position(4, 0), new King(PlayerColor.WHITE));
    board.put(new Position(4, 7), new King(PlayerColor.BLACK));
}

/**
 * Places the queens on the chessboard in their starting positions.
 *
 * @param board the {@link ChessBoardWriter} to populate with queens
 */
private static void placeQueens(ChessBoardWriter board) {
    board.put(new Position(3, 0), new Queen(PlayerColor.WHITE));
    board.put(new Position(3, 7), new Queen(PlayerColor.BLACK));
}
}

```

engine/board/ChessBoardReader.java

```

package engine.board;

import chess.PieceType;
import chess.PlayerColor;
import engine.move.ChessMove;
import engine.piece.ChessPiece;
import engine.piece.Position;

import java.util.Map;

/**
 * Read-only interface for the ChessBoard.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */

```

```

public interface ChessBoardReader {
    /**
     * Retrieves the chess piece located at the specified position.
     *
     * @param pos the position on the chessboard
     * @return the {@link ChessPiece} at the given position, or null if no piece is
     *         present
     */
    ChessPiece get(Position pos);

    /**
     * Checks if the specified position contains a chess piece.
     *
     * @param pos the position on the chessboard
     * @return true if a piece is present at the given position, false otherwise
     */
    boolean containsKey(Position pos);

    /**
     * Get all the chessboard pieces
     *
     * @return a map of the positions its piece
     */
    Map<Position, ChessPiece> getPieces();

    /**
     * Retrieves the last move that was made on the chessboard.
     *
     * @return the last move that was made on the chessboard
     */
    ChessMove getLastMove();

    /**
     * Determines if the king of the specified color is currently in check.
     *
     * @param color the color of the king to check
     * @return true if the king of the specified color is in check, false otherwise
     */
    boolean isKingInCheck(PlayerColor color);

    /**
     * Checks if the square at the given position is attacked by any piece of the
     * given color.
     *
     * @param position the position to check
     * @param color the color of the attacking pieces
     * @param ignore the piece type to ignore, can be set to null to check all
     *              piece types
     * @return true if the square is attacked, false otherwise
     */
    boolean isSquareAttacked(Position position, PlayerColor color, PieceType ignore);
}

```

engine/board/ChessBoardWriter.java

```

package engine.board;

import engine.move.ChessMove;
import engine.piece.ChessPiece;
import engine.piece.Position;

/**
 * Write-only interface for the ChessBoard.

```

```

*
* @author Leonard Cseres
* @author Aladin Iseni
*/
public interface ChessBoardWriter {
    /**
     * Places a chess piece at the specified position on the board.
     * Updates the view and tracks the position of kings.
     *
     * @param pos the position to place the piece
     * @param piece the {@link ChessPiece} to place
     */
    void put(Position pos, ChessPiece piece);

    /**
     * Removes a chess piece from the specified position.
     *
     * @param pos the position to remove the piece from
     * @throws IllegalStateException if no piece exist at the position
     */
    void remove(Position pos);

    /**
     * Clears all pieces from the chessboard.
     */
    void clear();

    /**
     * Sets the last move that was made on the chessboard.
     *
     * @param chessMove the last move that was made
     */
    void setLastMove(ChessMove chessMove);

    /**
     * Handles pawn promotion at the given position.
     *
     * @param pos the position of the pawn being promoted
     */
    void handlePawnPromotion(Position pos);
}

```

engine/generator/Direction.java

```

package engine.generator;

import chess.PlayerColor;
import engine.piece.Position;

import java.util.List;

/**
 * Enum representing the possible directions a chess piece can move on the
 * board.
 * Each direction is represented by a pair of x and y changes (dx, dy).
 * The directions include vertical, horizontal, and diagonal movements.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public enum Direction {
    FORWARDS(0, 1),
    BACKWARDS(0, -1),

```

```

LEFT(-1, 0),
RIGHT(1, 0),
FORWARDS_LEFT(-1, 1),
FORWARDS_RIGHT(1, 1),
BACKWARDS_LEFT(-1, -1),
BACKWARDS_RIGHT(1, -1);

public static final List<Direction> ALL = List.of(Direction.FORWARDS, Direction.BACKWARDS, Direction.LEFT,
    Direction.RIGHT, Direction.FORWARDS_LEFT, Direction.FORWARDS_RIGHT, Direction.BACKWARDS_LEFT,
    Direction.BACKWARDS_RIGHT);
public static final List<Direction> STRAIGHT = List.of(Direction.FORWARDS, Direction.BACKWARDS, Direction.Lf
    Direction.RIGHT);
public static final List<Direction> DIAGONAL = List.of(Direction.FORWARDS_LEFT, Direction.FORWARDS_RIGHT,
    Direction.BACKWARDS_LEFT, Direction.BACKWARDS_RIGHT);

private final int dx;
private final int dy;

/**
 * Constructor for the Direction enum, defining the change in position (dx, dy).
 *
 * @param dx the change in x-coordinate (horizontal movement)
 * @param dy the change in y-coordinate (vertical movement)
 * @throws IllegalArgumentException if the provided arguments are invalid
 */
Direction(int dx, int dy) {
    if (dx < -1 || dx > 1) {
        throw new IllegalArgumentException("dx must be between -1 and 1");
    }
    if (dy < -1 || dy > 1) {
        throw new IllegalArgumentException("dy must be between -1 and 1");
    }
    this.dx = dx;
    this.dy = dy;
}

/**
 * Adjusts the vertical movement (dy) based on the player's color.
 *
 * @param color the color of the player (used to determine direction)
 * @return the adjusted vertical movement (dy) based on the color
 */
private int getDy(PlayerColor color) {
    return color == PlayerColor.WHITE ? dy : -dy;
}

/**
 * Calculates a new position by applying this direction to the given position,
 * taking the piece color into account.
 *
 * @param position the current position of the piece
 * @param color the color of the piece (used to adjust direction)
 * @return the new position after applying the direction
 */
public Position add(Position position, PlayerColor color) {
    return position.add(new Position(dx, getDy(color)));
}

/**
 * Returns a string representation of the direction, including the dx and dy
 * values.
 *
 * @return a string representation of the direction
 */
@Override

```

```

    public String toString() {
        return getClass().getSimpleName() + " (" + dx + ", " + dy + ")";
    }
}

```

engine/generator/DirectionalGenerator.java

```

package engine.generator;

import engine.board.ChessBoardReader;
import engine.move.Capture;
import engine.move.Moves;
import engine.move.StandardMove;
import engine.piece.ChessPiece;
import engine.piece.Position;

import java.util.List;

/**
 * Generates possible moves for pieces that move in specific directions.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public class DirectionalGenerator extends MoveGenerator {
    private final List<Direction> dirs;

    /**
     * Constructs a DirectionalGenerator with specified directions
     * capability.
     *
     * @param dirs the directions the piece can move in
     */
    public DirectionalGenerator(Direction... dirs) {
        this(List.of(dirs));
    }

    /**
     * Constructs a DirectionalGenerator with specified directions
     * capability.
     *
     * @param dirs the directions the piece can move in
     */
    public DirectionalGenerator(List<Direction> dirs) {
        this.dirs = dirs;
    }

    /**
     * Generates all possible moves at a specified position at given directions
     *
     * @param board the current state of the chessboard
     * @param from the position of the piece on the board
     * @return a collection of possible moves
     */
    @Override
    public Moves generate(ChessBoardReader board, Position from) {
        Moves possibleMoves = new Moves();
        ChessPiece piece = board.get(from);

        for (Direction dir : dirs) {
            Position current = from;

            while (true) {

```

```

        current = dir.add(current, piece.getColor());

        if (!current.isValid()) {
            break;
        }

        if (board.containsKey(current)) {
            // If there's a piece at the current position
            ChessPiece otherPiece = board.get(current);
            if (otherPiece.isOpponent(piece)) {
                possibleMoves.addMove(new Capture(from, current, piece));
            }
            break; // Stop further exploration the piece cannot jump
        } else {
            // Add the move if the square is empty
            possibleMoves.addMove(new StandardMove(from, current, piece));
        }
    }
}

return possibleMoves;
}
}

```

engine/generator/DistanceGenerator.java

```

package engine.generator;

import engine.board.ChessBoardReader;
import engine.move.ChessMove;
import engine.move.Moves;
import engine.piece.Position;

import java.util.List;

/**
 * Generates possible moves for pieces that have a maximum distance they can
 * move.
 * Supports a collection of DirectionalGenerators to generate moves in multiple
 * directions.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public class DistanceGenerator extends MoveGenerator {
    private int maxDistance;
    private final List<DirectionalGenerator> directionalGenerators;

    /**
     * Constructs a DistanceGenerator with the specified maximum distance and
     * directional generators.
     *
     * @param maxDistance the maximum distance the piece can move
     * @param directionalGenerators the generators that handle the piece's movement
     * in different directions
     */
    public DistanceGenerator(int maxDistance, DirectionalGenerator... directionalGenerators) {
        this.maxDistance = maxDistance;
        this.directionalGenerators = List.of(directionalGenerators);
    }

    /**
     * Gets the maximum distance the piece can move.
     */
}

```



```

    *
    * @return the maximum distance
    */
    public int getMaxDistance() {
        return maxDistance;
    }

    /**
     * Sets the maximum distance the piece can move.
     *
     * @param maxDistance the maximum distance
     */
    public void setMaxDistance(int maxDistance) {
        this.maxDistance = maxDistance;
    }

    /**
     * Generates all possible moves at a specified position given a max distance and
     * directions
     *
     * @param board the current state of the chessboard
     * @param from the position of the piece on the board
     * @return a collection of possible moves
     */
    @Override
    public Moves generate(CheessBoardReader board, Position from) {
        Moves possibleMoves = new Moves();

        // Generate moves using all directional generators
        for (DirectionalGenerator gen : directionalGenerators) {
            Moves generatedMoves = gen.generate(board, from);

            // Filter moves that exceed the maximum distance
            for (ChessMove move : generatedMoves.getAllMoves()) {
                if (from.dist(move.getTo()) <= maxDistance) {
                    possibleMoves.addMove(move);
                }
            }
        }

        return possibleMoves;
    }

    /**
     * Creates a deep clone of the move generator
     *
     * @return a cloned instance of the move generator
     * @throws CloneNotSupportedException if the cloning process fails
     */
    @Override
    public DistanceGenerator clone() throws CloneNotSupportedException {
        DistanceGenerator dg = (DistanceGenerator) super.clone();
        dg.maxDistance = maxDistance;
        return dg;
    }
}

```

engine/generator/KnightGenerator.java

```

package engine.generator;

import engine.board.CheessBoardReader;
import engine.move.Capture;

```

```

import engine.move.Moves;
import engine.move.StandardMove;
import engine.piece.ChessPiece;
import engine.piece.Position;

/**
 * Generates possible moves for a knight piece on the chessboard.
 * The knight moves in an "L" shape: two squares in one direction and one square
 * perpendicular to that.
 * It can jump over other pieces.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class KnightGenerator extends MoveGenerator {
    // Possible moves for a knight (8 directions)
    private static final int[][] KNIGHT_MOVES = {
        {2, 1}, {2, -1}, {-2, 1}, {-2, -1},
        {1, 2}, {1, -2}, {-1, 2}, {-1, -2}
    };

    /**
     * Generates all possible moves the knight at a specified position
     *
     * @param board the current state of the chessboard
     * @param from the position of the piece on the board
     * @return a collection of possible moves
     */
    @Override
    public Moves generate(ChessBoardReader board, Position from) {
        Moves moves = new Moves();
        ChessPiece piece = board.get(from);

        // Evaluate each possible knight move
        for (int[] move : KNIGHT_MOVES) {
            Position to = from.add(new Position(move[0], move[1]));

            // If the move is valid and the destination is either empty or occupied by an
            // opponent
            if (to.isValid()) {
                if (!board.containsKey(to)) {
                    moves.addMove(new StandardMove(from, to, piece));
                } else if (board.get(to).isOpponent(piece)) {
                    moves.addMove(new Capture(from, to, piece));
                }
            }
        }

        return moves;
    }
}

```

engine/generator/MoveGenerator.java

```

package engine.generator;

import engine.board.ChessBoardReader;
import engine.move.Moves;
import engine.piece.Position;

/**
 * Abstract class for generating possible moves for a chess piece.
 * Implementations of this class will define how to generate moves

```

```

* for specific types of chess pieces.
*
* @author Leonard Cseres
* @author Aladin Iseni
*/
public abstract class MoveGenerator implements Cloneable {
    /**
     * Generates all possible moves for a given piece from a specific position.
     *
     * @param board the current state of the chessboard
     * @param from the position of the piece on the board
     * @return a collection of possible moves
     */
    public abstract Moves generate(ChessBoardReader board, Position from);

    /**
     * Creates a deep clone of the move generator
     *
     * @return a cloned instance of the move generator
     * @throws CloneNotSupportedException if the cloning process fails
     */
    @Override
    public MoveGenerator clone() throws CloneNotSupportedException {
        return (MoveGenerator) super.clone();
    }
}

```

engine/generator/PawnDistanceGenerator.java

```

package engine.generator;

import engine.board.ChessBoardReader;
import engine.move.Moves;
import engine.piece.ChessPiece;
import engine.piece.Position;

/**
 * Generates possible moves for a pawn piece on the chessboard.
 * The pawn can move one or two squares forward on its first move, and one
 * square forward thereafter.
 * It does not consider diagonal captures, which are handled in the
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class PawnDistanceGenerator extends DistanceGenerator {

    public PawnDistanceGenerator() {
        super(2, new DirectionalGenerator(Direction.FORWARDS));
    }

    @Override
    public Moves generate(ChessBoardReader board, Position from) {
        ChessPiece piece = board.get(from);
        // If the pawn has moved, restrict its maximum distance to 1
        if (piece.hasMoved() && getMaxDistance() == 2) {
            setMaxDistance(1);
        }
        return super.generate(board, from);
    }
}

```

engine/move/Capture.java

```
package engine.move;

import engine.board.ChessBoardWriter;
import engine.piece.ChessPiece;
import engine.piece.Position;

/**
 * Represents a capture move in chess, where a piece moves to a position
 * occupied by an opponent's piece.
 * The opponent's piece is removed from the board, and the moving piece replaces
 * it.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public class Capture extends ChessMove {

    /**
     * Constructs a Capture move with the specified starting and destination
     * positions.
     *
     * @param from      the starting position of the move
     * @param to        the destination position of the move (where the opponent's piece
     *                  will be captured)
     * @param fromPiece the starting position chess piece
     */
    public Capture(Position from, Position to, ChessPiece fromPiece) {
        super(from, to, fromPiece);
    }

    /**
     * Executes the capture move on the provided chess board.
     * The piece is moved from the starting position to the destination position,
     * and the opponent's piece at the destination is removed from the board.
     *
     * @param board the chessboard on which the move is executed
     */
    @Override
    public void execute(ChessBoardWriter board) {
        super.execute(board);
        board.remove(from);
        fromPiece.markMoved();
        board.remove(to);
        board.put(to, fromPiece);
    }
}
```

engine/move/Castling.java

```
package engine.move;

import engine.board.ChessBoardWriter;
import engine.piece.ChessPiece;
import engine.piece.Position;

/**
 * Abstract base class representing a castling move in chess.
 * Provides common functionality for both long (queenside) and short (kingside)
 * castling.
 *

```

```

* @author Leonard Cseres
* @author Aladin Iseni
*/
abstract class Castling extends ChessMove {
    private final Position fromRook;
    private final Position toRook;
    private final ChessPiece rook;

    /**
     * Constructs a Castling move with the specified starting and destination
     * positions for the king.
     *
     * @param from      the starting position of the king
     * @param to        the destination position of the king
     * @param king      the starting position king
     * @param fromRook  the starting position of the rook
     * @param toRook    the destination position of the rook
     * @param rook      the starting position rook
     */
    protected Castling(Position from, Position to, ChessPiece king, Position fromRook, Position toRook,
        ChessPiece rook) {
        super(from, to, king);
        this.fromRook = fromRook;
        this.toRook = toRook;
        this.rook = rook.clone();
    }

    /**
     * Executes the castling move on the provided chessboard.
     *
     * @param board the chessboard on which the move is executed
     */
    @Override
    public void execute(ChessBoardWriter board) {
        super.execute(board);
        ChessPiece king = fromPiece;

        board.remove(from);
        board.remove(fromRook);

        king.markMoved();
        rook.markMoved();

        board.put(to, king);
        board.put(toRook, rook);
    }
}

```

engine/move/ChessMove.java

```

package engine.move;

import engine.board.ChessBoardWriter;
import engine.piece.ChessPiece;
import engine.piece.Position;

/**
 * Represents a chess move from one position to another.
 * This is an abstract class that can be extended for specific move types such
 * as regular moves, captures, etc.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni

```

```

*/
public abstract class ChessMove {
    protected final Position from;
    protected final Position to;
    protected final ChessPiece fromPiece;

    /**
     * Constructs a ChessMove with the specified starting and ending positions.
     *
     * @param from      the starting position of the move
     * @param to        the destination position of the move
     * @param fromPiece the starting position chess piece
     */
    public ChessMove(Position from, Position to, ChessPiece fromPiece) {
        this.from = from;
        this.to = to;
        this.fromPiece = fromPiece.clone();
    }

    /**
     * Gets the starting position of the move.
     *
     * @return the starting position
     */
    public Position getFrom() {
        return from;
    }

    /**
     * Gets the destination position of the move.
     *
     * @return the destination position
     */
    public Position getTo() {
        return to;
    }

    /**
     * Gets the starting position chess piece.
     *
     * @return the starting position chess piece
     */
    public ChessPiece getFromPiece() {
        return fromPiece;
    }

    /**
     * Executes the move on the given chess board.
     * This method must be overridden by subclasses to define the specific behavior
     * of the move.
     *
     * @param board the chessboard on which the move is executed
     */
    public void execute(ChessBoardWriter board) {
        board.setLastMove(this);
    }

    /**
     * Returns a string representation of the move, including the class name and the
     * positions involved.
     *
     * @return a string representation of the move
     */
    @Override
    public String toString() {

```

```

        return getClass().getSimpleName() + " (" + from + " -> " + to + ")";
    }
}

```

engine/move/EnPassant.java

```

package engine.move;

import engine.board.ChessBoardWriter;
import engine.piece.ChessPiece;
import engine.piece.Position;

/**
 * Represents an En Passant move in chess, a special pawn capture that occurs
 * when a pawn moves two squares forward from its starting position, and an
 * opposing pawn on an adjacent file captures it as if it had only moved one
 * square.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class EnPassant extends StandardMove {
    private final Position capturePawnPosition;

    /**
     * Constructs an En Passant move with the specified starting and destination
     * positions.
     *
     * @param from           the starting position of the capturing pawn
     * @param to             the destination position where the capturing pawn
     *                       moves to
     * @param fromPiece      the starting position chess piece
     * @param capturePawnPosition the position of the captured pawn
     */
    public EnPassant(Position from, Position to, ChessPiece fromPiece, Position capturePawnPosition) {
        super(from, to, fromPiece);
        this.capturePawnPosition = capturePawnPosition;
    }

    /**
     * Executes the En Passant move on the provided chessboard. The capturing pawn
     * is moved to the destination square, and the captured pawn (which is bypassed
     * in the move) is removed from the board.
     *
     * @param board the chessboard on which the move is executed
     */
    @Override
    public void execute(ChessBoardWriter board) {
        super.execute(board);
        board.remove(capturePawnPosition);
    }
}

```

engine/move/LongCastling.java

```

package engine.move;

import engine.piece.ChessPiece;
import engine.piece.Position;

```

```

/**
 * Represents a long (queenside) castling move in chess.
 * In this move, the king moves two squares towards the queenside rook,
 * and the rook moves three squares towards the center.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class LongCastling extends Castling {
    /**
     * Constructs a long castling move.
     *
     * @param from      the starting position of the king
     * @param to        the destination position of the king
     * @param king       the starting position king
     * @param fromRook   the starting position of the rook
     * @param rook       the starting position rook
     */
    public LongCastling(Position from, Position to, ChessPiece king, Position fromRook, ChessPiece rook) {
        super(from, to, king, fromRook, fromRook.add(new Position(3, 0)), rook);
    }
}

```

engine/move/Moves.java

```

package engine.move;

import engine.piece.Position;

import java.util.Collection;
import java.util.HashMap;
import java.util.Map;

/**
 * Represents a collection of chess moves, storing them in a map with the
 * destination position as the key.
 * Provides methods for adding, extending, and retrieving moves.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class Moves {
    private final Map<Position, ChessMove> movesMap;

    /**
     * Constructs an empty Moves object to hold chess moves.
     */
    public Moves() {
        movesMap = new HashMap<>();
    }

    /**
     * Adds a move to the collection of moves.
     *
     * @param move the chess move to be added
     */
    public void addMove(ChessMove move) {
        movesMap.put(move.getTo(), move);
    }

    /**
     * Extends the current collection of moves by adding all moves from another
     * Moves object.
     */
}

```



```

*
* @param moves the Moves object whose moves should be added
*/
public void extendMoves(Moves moves) {
    for (ChessMove move : moves.getAllMoves()) {
        this.addMove(move);
    }
}

/**
 * Retrieves a move based on its destination position.
 *
 * @param to the destination position of the move
 * @return the chess move associated with the destination position, or null if
 * no such move exists
 */
public ChessMove getMove(Position to) {
    return movesMap.get(to);
}

/**
 * Retrieves all moves in the collection.
 *
 * @return a collection of all chess moves
 */
public Collection<ChessMove> getAllMoves() {
    return movesMap.values();
}

/**
 * Returns a string representation of all moves in the collection.
 *
 * @return a string representing all moves
 */
@Override
public String toString() {
    return movesMap.values().toString();
}
}

```

engine/move/Promotion.java

```

package engine.move;

import engine.board.ChessBoardWriter;
import engine.piece.ChessPiece;
import engine.piece.Position;

/**
 * Represents a promotion move in chess, where a pawn reaches the last rank and
 * is promoted
 * to a more powerful piece (Queen, Rook, Bishop, or Knight).
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class Promotion extends StandardMove {

    /**
     * Constructs a Promotion move with the specified starting and destination
     * positions.
     *
     * @param from the starting position of the pawn

```

```

    * @param to    the destination position where the pawn will be promoted
    * @param pawn  the starting position pawn
    */
    public Promotion(Position from, Position to, ChessPiece pawn) {
        super(from, to, pawn);
    }

    /**
     * Executes the promotion move on the provided chess board. The pawn is moved
     * from its starting position
     * to the destination, and the pawn is promoted to a new piece (Queen, Rook,
     * Bishop, or Knight).
     *
     * @param board the chessboard on which the move is executed
     */
    @Override
    public void execute(ChessBoardWriter board) {
        super.execute(board);
        board.handlePawnPromotion(to);
    }
}

```

engine/move/PromotionWithCapture.java

```

package engine.move;

import engine.board.ChessBoardWriter;
import engine.piece.ChessPiece;
import engine.piece.Position;

/**
 * Represents a promotion move with capture in chess, where a pawn captures an
 * opponent's piece
 * and is promoted to a more powerful piece (Queen, Rook, Bishop, or Knight).
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class PromotionWithCapture extends Capture {

    /**
     * Constructs a PromotionWithCapture move with the specified starting and
     * destination positions.
     *
     * @param from the starting position of the pawn
     * @param to   the destination position where the pawn will capture and be
     *             promoted
     * @param pawn the starting position pawn
     */
    public PromotionWithCapture(Position from, Position to, ChessPiece pawn) {
        super(from, to, pawn);
    }

    /**
     * Executes the promotion with capture move on the provided chess board. The
     * pawn captures an opponent's
     * piece at the destination position, and then the pawn is promoted to a new
     * piece (Queen, Rook, Bishop, or Knight).
     *
     * @param board the chessboard on which the move is executed
     */
    @Override
    public void execute(ChessBoardWriter board) {

```

```

        super.execute(board);
        board.handlePawnPromotion(to);
    }
}

```

engine/move/ShortCastling.java

```

package engine.move;

import engine.piece.ChessPiece;
import engine.piece.Position;

/**
 * Represents a short (kingside) castling move in chess.
 * In this move, the king moves two squares towards the kingside rook,
 * and the rook moves two squares towards the center.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class ShortCastling extends Castling {
    /**
     * Constructs a short castling move.
     *
     * @param from      the starting position of the king
     * @param to         the destination position of the king
     * @param king       the starting position king
     * @param fromRook   the starting position of the rook
     * @param rook       the starting position rook
     */
    public ShortCastling(Position from, Position to, ChessPiece king, Position fromRook, ChessPiece rook) {
        super(from, to, king, fromRook, fromRook.sub(new Position(2, 0)), rook);
    }
}

```

engine/move/StandardMove.java

```

package engine.move;

import engine.board.ChessBoardWriter;
import engine.piece.ChessPiece;
import engine.piece.Position;

/**
 * Represents a standard move in chess, where a piece is moved from one position
 * to another.
 * The piece is removed from the starting position and placed at the destination
 * position.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public class StandardMove extends ChessMove {
    /**
     * Constructs a StandardMove with the specified starting and ending positions.
     *
     * @param from      the starting position of the move
     * @param to         the destination position of the move
     * @param fromPiece the starting position chess piece
     */
}

```

```

    */
    public StandardMove(Position from, Position to, ChessPiece fromPiece) {
        super(from, to, fromPiece);
    }

    /**
     * Executes the move on the provided chess board.
     * The piece is moved from the starting position to the destination position,
     * and it is marked as moved.
     *
     * @param board the chessboard on which the move is executed
     */
    @Override
    public void execute(ChessBoardWriter board) {
        super.execute(board);
        board.remove(from);
        fromPiece.markMoved();
        board.put(to, fromPiece);
    }
}

```

engine/piece/Bishop.java

```

package engine.piece;

import chess.PieceType;
import chess.PlayerColor;
import engine.generator.Direction;
import engine.generator.DirectionGenerator;

/**
 * Represents the Bishop chess piece.
 * The Bishop can move diagonally any number of squares in any diagonal
 * direction.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class Bishop extends PromotableChessPiece {

    /**
     * Constructs a Bishop chess piece with the specified color.
     * Uses a {@link DirectionGenerator} limited to diagonal movements.
     *
     * @param color the color of the Bishop
     */
    public Bishop(PlayerColor color) {
        super(PieceType.BISHOP, color, new DirectionGenerator(Direction.DIAGONAL));
    }
}

```

engine/piece/ChessPiece.java

```

package engine.piece;

import chess.PieceType;
import chess.PlayerColor;
import engine.board.ChessBoardReader;
import engine.generator.MoveGenerator;
import engine.move.Moves;

```

```

import java.util.ArrayList;
import java.util.List;

/**
 * Represents a chess piece with associated type, color, and movement
 * generators.
 * Provides functionality to track movement and generate possible moves.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public abstract class ChessPiece implements Cloneable {
    protected final PieceType type;
    protected final PlayerColor color;
    private List<MoveGenerator> generators;
    private boolean hasMoved = false;

    /**
     * Constructs a chess piece with specified type, color, and movement generators.
     *
     * @param type the type of the chess piece
     * @param color the color of the chess piece
     * @param generators the movement generators defining how the piece moves
     */
    public ChessPiece(PieceType type, PlayerColor color, MoveGenerator... generators) {
        this.type = type;
        this.color = color;
        this.generators = List.of(generators);
    }

    /**
     * Gets the type of the chess piece.
     *
     * @return the {@link PieceType} of the chess piece
     */
    public PieceType getType() {
        return type;
    }

    /**
     * Gets the color of the chess piece.
     *
     * @return the {@link PlayerColor} of the chess piece
     */
    public PlayerColor getColor() {
        return color;
    }

    /**
     * Determines if another chess piece is an opponent.
     *
     * @param other the other chess piece
     * @return true if the other piece is an opponent, false otherwise
     */
    public boolean isOpponent(ChessPiece other) {
        return color != other.color;
    }

    /**
     * Marks the piece has moved.
     */
    public void markMoved() {
        this.hasMoved = true;
    }
}

```

```

/**
 * Checks if the piece has moved at least once.
 *
 * @return true if the piece has moved, false otherwise
 */
public boolean hasMoved() {
    return hasMoved;
}

/**
 * Generates all possible moves for the chess piece from a given position on the
 * board.
 *
 * @param board the current state of the chessboard
 * @param from the position of the piece on the chessboard
 * @return a {@link Moves} object containing all possible moves
 */
public Moves getPossibleMoves(CheessBoardReader board, Position from) {
    Moves moves = new Moves();
    for (MoveGenerator gen : generators) {
        moves.extendMoves(gen.generate(board, from));
    }
    return moves;
}

/**
 * Creates a deep clone of the chess piece, preserving its movement state.
 *
 * @return a cloned instance of the chess piece
 * @throws AssertionError if the clone failed. We assert it won't happen
 */
@Override
public ChessPiece clone() {
    try {
        ChessPiece clonedPiece = (ChessPiece) super.clone();
        clonedPiece.hasMoved = this.hasMoved;

        List<MoveGenerator> clonedGenerators = new ArrayList<>();
        for (MoveGenerator generator : this.generators) {
            clonedGenerators.add(generator.clone());
        }
        clonedPiece.generators = clonedGenerators;

        return clonedPiece;
    } catch (CloneNotSupportedException e) {
        throw new AssertionError("Cloning failed", e);
    }
}
}

```

engine/piece/King.java

```

package engine.piece;

import chess.PieceType;
import chess.PlayerColor;
import engine.board.CheessBoardReader;
import engine.generator.Direction;
import engine.generator.DirectionGenerator;
import engine.generator.DistanceGenerator;
import engine.move.LongCastling;
import engine.move.Moves;

```

```

import engine.move.ShortCastling;

/**
 * Represents the King chess piece.
 * The King can move one square in any direction, as defined by the movement
 * rules.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class King extends ChessPiece {

    /**
     * Constructs a King chess piece with the specified color.
     * Uses a {@link DistanceGenerator} limited to one square and all directions.
     *
     * @param color the color of the King
     */
    public King(PlayerColor color) {
        super(PieceType.KING, color, new DistanceGenerator(1, new DirectionalGenerator(Direction.ALL)));
    }

    /**
     * Gets all possible moves for the King from the given position.
     * Handles regular moves and castling moves.
     *
     * @param board the chess board
     * @param from the starting position of the King
     * @return a {@link Moves} object containing all valid moves for the King
     */
    @Override
    public Moves getPossibleMoves(ChessBoardReader board, Position from) {
        Moves moves = super.getPossibleMoves(board, from);
        moves.extendMoves(getCastlingMoves(board, from));

        return moves;
    }

    /**
     * Calculates the possible castling moves for the king from the given position.
     *
     * @param board the chessboard used to evaluate castling conditions
     * @param from the current position of the king
     * @return a Moves object containing valid castling moves, or empty if
     *         no castling is possible
     */
    private Moves getCastlingMoves(ChessBoardReader board, Position from) {
        Moves castlingMoves = new Moves();

        Position shortCastlingPosition = new Position(from.x() + 2, from.y());
        if (canCastle(board, from, shortCastlingPosition)) {
            Position rookPosition = getRookPosition(from, Direction.RIGHT);
            ChessPiece rook = board.get(rookPosition);
            castlingMoves.addMove(new ShortCastling(from, shortCastlingPosition, this, rookPosition, rook));
        }

        Position longCastlingPosition = new Position(from.x() - 2, from.y());
        if (canCastle(board, from, longCastlingPosition)) {
            Position rookPosition = getRookPosition(from, Direction.LEFT);
            ChessPiece rook = board.get(rookPosition);
            castlingMoves.addMove(new LongCastling(from, longCastlingPosition, this, rookPosition, rook));
        }

        return castlingMoves;
    }
}

```

```

/**
 * Determines if the King can castle with the Rook at the given positions.
 * The King and Rook must not have moved, the squares between them must be
 * empty and not attacked, and the King must not currently be in check.
 *
 * @param board the chess board
 * @param from the position of the King
 * @param to the target position for the King (castling destination)
 * @return true if the King can castle, false otherwise
 */
private boolean canCastle(CheessBoardReader board, Position from, Position to) {
    if (hasMoved()) {
        return false;
    }

    Direction direction = to.x() > from.x() ? Direction.RIGHT : Direction.LEFT;
    Position rookPosition = getRookPosition(from, direction);
    ChessPiece rook = board.get(rookPosition);

    return isValidRook(rook) &&
        areSquaresBetweenEmptyAndSafe(board, from, rookPosition, direction) &&
        !board.isKingInCheck(color);
}

/**
 * Calculates the position of the Rook based on the King's position and the
 * castling direction.
 *
 * @param from the starting position of the King
 * @param direction the direction of castling (RIGHT or LEFT)
 * @return the position of the Rook involved in castling
 */
private Position getRookPosition(Position from, Direction direction) {
    return direction == Direction.RIGHT
        ? new Position(Position.MAX_X, from.y())
        : new Position(0, from.y());
}

/**
 * Checks if the Rook at the given position is valid for castling.
 * The Rook must exist, must not have moved, and must be of type ROOK.
 *
 * @param rook the chess piece at the Rook's position
 * @return true if the Rook is valid for castling, false otherwise
 */
private boolean isValidRook(ChessPiece rook) {
    return rook != null && !rook.hasMoved() && rook.getType() == PieceType.ROOK;
}

/**
 * Checks if the squares between the King and the Rook are both empty and not
 * attacked.
 *
 * @param board the chess board
 * @param from the position of the King
 * @param rookPos the position of the Rook
 * @param direction the direction of castling (RIGHT or LEFT)
 * @return true if the squares between are empty and safe, false otherwise
 */
private boolean areSquaresBetweenEmptyAndSafe(CheessBoardReader board, Position from, Position rookPos,
    Direction direction) {
    Position current = direction.add(from, color);
    while (!current.equals(rookPos)) {
        if (board.containsKey(current) || board.isSquareAttacked(current, color, PieceType.KING)) {
            return false;
        }
    }
}

```



```

        }
        current = direction.add(current, color);
    }
    return true;
}
}

```

engine/piece/Knight.java

```

package engine.piece;

import chess.PieceType;
import chess.PlayerColor;
import engine.generator.KnightGenerator;

/**
 * Represents the Knight chess piece.
 * The Knight moves in an "L" shape: two squares in one direction and then one
 * square perpendicular, or vice versa.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class Knight extends PromotableChessPiece {

    /**
     * Constructs a Knight chess piece with the specified color.
     * Uses a {@link KnightGenerator} to define its movement pattern.
     *
     * @param color the color of the Knight
     */
    public Knight(PlayerColor color) {
        super(PieceType.KNIGHT, color, new KnightGenerator());
    }
}

```

engine/piece/Pawn.java

```

package engine.piece;

import chess.PieceType;
import chess.PlayerColor;
import engine.board.ChessBoardReader;
import engine.generator.Direction;
import engine.generator.DirectionGenerator;
import engine.generator.DistanceGenerator;
import engine.generator.PawnDistanceGenerator;
import engine.move.Capture;
import engine.move.ChessMove;
import engine.move.EnPassant;
import engine.move.Moves;
import engine.move.Promotion;
import engine.move.PromotionWithCapture;
import engine.move.StandardMove;

/**
 * Represents the Pawn chess piece.
 * The Pawn can move one or two squares forward, but captures diagonally.
 * It also has the option to promote upon reaching the opposite end of the
 * board.

```

```

*
* @author Leonard Cseres
* @author Aladin Iseni
*/
public final class Pawn extends ChessPiece {

    /**
     * Constructs a Pawn chess piece with the specified color.
     * Uses a {@link PawnDistanceGenerator} for forward movement and a
     * {@link DirectionalGenerator}
     * for diagonal captures.
     *
     * @param color the color of the Pawn
     */
    public Pawn(PlayerColor color) {
        super(PieceType.PAWN, color, new PawnDistanceGenerator(), new DistanceGenerator(1,
            new DirectionalGenerator(Direction.FORWARDS_LEFT, Direction.FORWARDS_RIGHT)));
    }

    /**
     * Gets all possible moves for the Pawn from the given position.
     * Handles regular moves, captures, and promotions (including promotion with
     * capture).
     *
     * @param board the chess board
     * @param from the starting position of the Pawn
     * @return a {@link Moves} object containing all valid moves for the Pawn
     */
    @Override
    public Moves getPossibleMoves(ChessBoardReader board, Position from) {
        Moves candidateMoves = super.getPossibleMoves(board, from);
        Moves validMoves = new Moves();

        for (ChessMove move : candidateMoves.getAllMoves()) {
            Position to = move.getTo();
            if (isValidMove(board, from, to)) {
                validMoves.addMove(createAppropriateMove(from, to));
            }
        }

        addEnPassantMoves(board, from, validMoves);
        return validMoves;
    }

    /**
     * Validates whether a move is legal according to pawn movement rules.
     * Checks both forward moves and diagonal captures.
     *
     * @param board The current state of the chess board
     * @param from The starting position of the pawn
     * @param to The target position for the move
     * @return true if the move is legal, false otherwise
     */
    private boolean isValidMove(ChessBoardReader board, Position from, Position to) {
        if (isDiagonalMove(from, to)) {
            // Capture
            return board.containsKey(to) && board.get(to).isOpponent(this);
        }
        return !board.containsKey(to); // Forward moves require empty square
    }

    /**
     * Creates the appropriate type of move based on the movement type and position.
     * Handles standard moves, captures, and promotions.
     *
     */

```

```

    * @param from The starting position of the pawn
    * @param to   The target position for the move
    * @return The appropriate ChessMove object for the given move
    */
private ChessMove createAppropriateMove(Position from, Position to) {
    if (isDiagonalMove(from, to)) {
        return createCaptureMove(from, to);
    }
    return createForwardMove(from, to);
}

/**
 * Creates a capture move, either as a regular capture or a promotion with
 * capture.
 *
 * *
 * @param from The starting position of the pawn
 * @param to   The target position for the capture
 * @return A Capture or PromotionWithCapture move
 */
private ChessMove createCaptureMove(Position from, Position to) {
    return isAtPromotionRank(to)
        ? new PromotionWithCapture(from, to, this)
        : new Capture(from, to, this);
}

/**
 * Creates a forward move, either as a standard move or a promotion.
 *
 * *
 * @param from The starting position of the pawn
 * @param to   The target position for the move
 * @return A StandardMove or Promotion move
 */
private ChessMove createForwardMove(Position from, Position to) {
    return isAtPromotionRank(to)
        ? new Promotion(from, to, this)
        : new StandardMove(from, to, this);
}

/**
 * Adds any possible en passant captures to the list of valid moves.
 * Checks adjacent squares for opponent pawns that have just moved two squares.
 *
 * *
 * @param board The current state of the chess board
 * @param from   The current position of the pawn
 * @param moves The collection of moves to add to
 */
private void addEnPassantMoves(ChessBoardReader board, Position from, Moves moves) {
    Position[] adjacentPositions = {
        Direction.LEFT.add(from, color),
        Direction.RIGHT.add(from, color)
    };
    for (Position adjacent : adjacentPositions) {
        if (isValidEnPassantPosition(board, adjacent)) {
            Position captureSquare = Direction.FORWARDS.add(adjacent, color);
            moves.addMove(new EnPassant(from, captureSquare, this, adjacent));
        }
    }
}

/**
 * Checks if an en passant capture is valid from the given position.
 * Validates that there is an opponent's pawn in the correct position
 * and that it just moved two squares forward.
 *
 * *
 * @param board The current state of the chess board

```

```

    * @param adjacent The position adjacent to the pawn
    * @return true if an en passant capture is possible, false otherwise
    */
private boolean isValidEnPassantPosition(ChessBoardReader board, Position adjacent) {
    if (!isPawnAtPosition(board, adjacent))
        return false;
    ChessMove lastMove = board.getLastMove();
    return lastMove != null &&
        wasDoublePawnAdvance(lastMove) &&
        adjacent.equals(lastMove.getTo()) &&
        board.get(adjacent).isOpponent(this);
}

/**
 * Determines if a move is a diagonal based on the positions.
 *
 * @param from The starting position
 * @param to The target position
 * @return true if the move is diagonal, false otherwise
 */
private boolean isDiagonalMove(Position from, Position to) {
    Position delta = from.sub(to).abs();
    return delta.x() == delta.y();
}

/**
 * Checks if there is a pawn at the given position.
 *
 * @param board The current state of the chess board
 * @param pos The position to check
 * @return true if there is a pawn at the position, false otherwise
 */
private boolean isPawnAtPosition(ChessBoardReader board, Position pos) {
    return board.containsKey(pos) && board.get(pos).getType() == PieceType.PAWN;
}

/**
 * Determines if a move was a double square pawn advance.
 *
 * @param move The move to check
 * @return true if the move was a double square advance, false otherwise
 */
private boolean wasDoublePawnAdvance(ChessMove move) {
    return Math.abs(move.getFrom().y() - move.getTo().y()) == 2;
}

/**
 * Checks if a position is on the promotion rank for this pawn's color.
 * White pawns promote on rank 8 (MAX_Y), black pawns promote on rank 1 (0).
 *
 * @param pos The position to check
 * @return true if the position is on the promotion rank, false otherwise
 */
private boolean isAtPromotionRank(Position pos) {
    return color == PlayerColor.WHITE
        ? pos.y() == Position.MAX_Y
        : pos.y() == 0;
}
}

```

engine/piece/Position.java

```
package engine.piece;
```

```

import chess.PlayerColor;

/**
 * Represents a position on the chessboard with x and y coordinates.
 * Provides utility methods for position validation and arithmetic operations.
 *
 * @param x the x-coordinate (column) of the position
 * @param y the y-coordinate (row) of the position
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public record Position(int x, int y) {
    public static final int MAX_X = 7;
    public static final int MAX_Y = 7;

    /**
     * Checks if the position is within the bounds of the chessboard.
     *
     * @return true if the position is valid, false otherwise
     */
    public boolean isValid() {
        return x >= 0 && y >= 0 && x <= MAX_X && y <= MAX_Y;
    }

    /**
     * Calculates the chessboard-compatible distance to another position.
     * The distance is defined as the maximum of the horizontal or vertical steps.
     *
     * @param other the other position to calculate the distance to
     * @return the maximum of horizontal or vertical steps to the other position
     */
    public int dist(Position other) {
        int dx = Math.abs(x - other.x);
        int dy = Math.abs(y - other.y);
        return Math.max(dx, dy);
    }

    /**
     * Adds the coordinates of another position to this position.
     *
     * @param other the position to add
     * @return a new {@link Position} representing the sum
     */
    public Position add(Position other) {
        return new Position(x + other.x, y + other.y);
    }

    /**
     * Subtracts the coordinates of another position from this position.
     *
     * @param other the position to subtract
     * @return a new {@link Position} representing the difference
     */
    public Position sub(Position other) {
        return new Position(x - other.x, y - other.y);
    }

    /**
     * Converts the position's coordinates to their absolute values.
     *
     * @return a new {@link Position} with absolute x and y coordinates
     */
    public Position abs() {
        return new Position(Math.abs(x), Math.abs(y));
    }
}

```

```

    }

    /**
     * Gets the position color
     *
     * @return WHITE if the position is on a white square, BLACK otherwise
     */
    public PlayerColor getColor() {
        return (x + y) % 2 == 0 ? PlayerColor.BLACK : PlayerColor.WHITE;
    }

    /**
     * Provides a string representation of the position in the format "(x, y)".
     *
     * @return a string representation of the position
     */
    @Override
    public String toString() {
        return "(" + x + ", " + y + ")";
    }
}

```

engine/piece/PromotableChessPiece.java

```

package engine.piece;

import chess.ChessView;
import chess.PieceType;
import chess.PlayerColor;
import engine.generator.MoveGenerator;

/**
 * Represents a promotable chess piece (e.g., pawn promotion) that can be chosen
 * by the user during gameplay.
 * Extends {@link ChessPiece} and implements {@link ChessView.UserChoice}.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public abstract class PromotableChessPiece extends ChessPiece implements ChessView.UserChoice {
    /**
     * Constructs a promotable chess piece with a specified type, color, and move
     * generators.
     *
     * @param type          the type of the promotable chess piece
     * @param color          the color of the chess piece
     * @param validationList the move generators for the piece
     */
    public PromotableChessPiece(PieceType type, PlayerColor color, MoveGenerator... validationList) {
        super(type, color, validationList);
    }

    /**
     * Provides a string representation of the piece's type for display purposes.
     *
     * @return the string value of the piece's {@link PieceType}
     */
    @Override
    public String textValue() {
        return type.toString();
    }
}

```

engine/piece/Queen.java

```
package engine.piece;

import chess.PieceType;
import chess.PlayerColor;
import engine.generator.Direction;
import engine.generator.DirectionGenerator;

/**
 * Represents the Queen chess piece.
 * The Queen can move any number of squares in any direction: horizontally,
 * vertically, or diagonally.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class Queen extends PromotableChessPiece {

    /**
     * Constructs a Queen chess piece with the specified color.
     * The Queen moves in all directions (horizontal, vertical, and diagonal) with
     * no restrictions
     * on the number of squares.
     *
     * @param color the color of the Queen
     */
    public Queen(PlayerColor color) {
        super(PieceType.QUEEN, color, new DirectionGenerator(Direction.ALL));
    }
}
```

engine/piece/Rook.java

```
package engine.piece;

import chess.PieceType;
import chess.PlayerColor;
import engine.generator.Direction;
import engine.generator.DirectionGenerator;

/**
 * Represents the Rook chess piece.
 * The Rook can move any number of squares horizontally or vertically.
 *
 * @author Leonard Cseres
 * @author Aladin Iseni
 */
public final class Rook extends PromotableChessPiece {

    /**
     * Constructs a Rook chess piece with the specified color.
     * The Rook moves in straight lines either horizontally or vertically with no
     * restrictions
     * on the number of squares.
     *
     * @param color the color of the Rook
     */
    public Rook(PlayerColor color) {
        super(PieceType.ROOK, color, new DirectionGenerator(Direction.STRAIGHT));
    }
}
```

