

1           DENGUEWATCH: A SYSTEM FOR REAL-TIME  
2   DENGUE MONITORING AND FORECASTING IN ILOILO  
3           PROVINCE

4           A Special Problem  
5           Presented to  
6       the Faculty of the Division of Physical Sciences and Mathematics  
7           College of Arts and Sciences  
8       University of the Philippines Visayas  
9           Miag-ao, Iloilo

10           In Partial Fulfillment  
11           of the Requirements for the Degree of  
12       Bachelor of Science in Computer Science by

13           AMODIA, Kurt Matthew A.  
14           BULAONG, Glen Andrew C.  
15           ELIPAN, Carl Benedict L.

16           Francis DIMZON, Ph.D.  
17           Adviser

18           June 2025

19

## Approval Sheet

20

The Division of Physical Sciences and Mathematics, College of Arts and  
Sciences, University of the Philippines Visayas

22

certifies that this is the approved version of the following special problem:

23

### DENGUEWATCH: A SYSTEM FOR REAL-TIME DENGUE MONITORING AND FORECASTING IN ILOILO PROVINCE

25

26

#### Approved by:

Name

Signature

Date

Francis D. Dimzon, Ph.D. \_\_\_\_\_  
(Adviser)

27

Ara Abigail E. Ambita \_\_\_\_\_  
(Panel Member)

Kent Christian A. Castor \_\_\_\_\_  
(Division Chair)

28                          Division of Physical Sciences and Mathematics  
29                          College of Arts and Sciences  
30                          University of the Philippines Visayas

31                          **Declaration**

32        We, Kurt Matthew A. Amodia, Glen Andrew C. Bulaong, and Carl Benedict  
33        L. Elipan, hereby certify that this Special Problem has been written by us and  
34        is the record of work carried out by us. Any significant borrowings have been  
35        properly acknowledged and referred.

Name	Signature	Date
Kurt Matthew A. Amodia (Student)	_____	_____
Glen Andrew C. Bulaong (Student)	_____	_____
Carl Benedict L. Elipan (Student)	_____	_____

## Dedication

38        We dedicate this special problem to all the teachers who have guided us  
39    throughout our academic journey. Your knowledge and mentorship have laid the  
40    foundation for this research, and for that, we are truly grateful.

41        To our families, friends, and classmates, thank you for your unwavering sup-  
42    port, encouragement, and belief in us. Your presence has been a constant source  
43    of strength.

44        Most especially, we dedicate this work to the health offices and frontline per-  
45    sonnel who continue to battle dengue cases with courage and dedication. Your  
46    tireless efforts and sacrifices are an inspiration. We hope that this research, in its  
47    own small way, can contribute to your work and make a meaningful difference in  
48    your fight against this disease.

49

## Acknowledgment

50 This research would not have been possible without the support and guidance  
51 of several individuals and institutions.

52 First and foremost, we express our deepest gratitude to our adviser, Dr. Francis  
53 Dimzon, for his invaluable insights, unwavering support, and commitment to  
54 our project. His guidance was instrumental in shaping the direction of our re-  
55 search.

56 We also extend our sincere thanks to the Iloilo Provincial Health Office and  
57 the Iloilo Epidemiological Unit, for accomodating our inquiries and sharing vital  
58 data and insights. Their cooperation played a crucial role in the success of the  
59 research.

60 Our appreciation also goes to the UPV Health Services Unit, especially the  
61 doctors and nurses who participated in our user testing. Your thoughtful feedback  
62 provided essential perspectives that greatly contributed to the relevance of our  
63 research.

64 Finally, we are greatly thankful to God Almighty, for granting us the strength,  
65 perseverance, and determination to complete this research.

## Abstract

67        Dengue fever remains a significant public health concern in the Philippines, with  
68        cases rising dramatically in recent years. Iloilo City experienced a surge in cases, with  
69        4,585 reported cases and 10 deaths as of August 10, 2023, a 319% increase from the  
70        previous year's 1,095 cases and one death. This rise overwhelmed local healthcare facil-  
71        ities, with over 76% of non-COVID-19 hospital beds occupied by dengue patients. The  
72        lack of a reliable monitoring and forecasting system delayed interventions, worsening  
73        the public health burden. To address this, the study developed a centralized system to  
74        modernize data management and monitoring of dengue cases in public health institu-  
75        tions. Using data from the Iloilo Provincial Health Office and online sources, several  
76        deep learning models were trained to forecast dengue cases on weather variables and  
77        historical data. Models tested included LSTM, ARIMA, Seasonal ARIMA, Kalman Fil-  
78        ter (KF), and a hybrid KF-LSTM, evaluated with time series cross-validation and error  
79        metrics like MSE, RMSE, and MAE. The LSTM model performed best, achieving the  
80        lowest RMSE of 20.15, followed by the hybrid KF-LSTM with 25.56. The LSTM model  
81        was integrated into the system, providing forecasting capabilities to support proactive  
82        interventions and better resource planning in health institutions.

83        **Keywords:** Dengue, Deep Learning, Monitoring, Prediction

# <sup>84</sup> **Contents**

<sup>85</sup>	<b>1</b>	<b>Introduction</b>	<b>1</b>
<sup>86</sup>		1.1 Overview of the Current State of Technology . . . . .	1
<sup>87</sup>		1.2 Problem Statement . . . . .	3
<sup>88</sup>		1.3 Research Objectives . . . . .	4
<sup>89</sup>		1.3.1 General Objective . . . . .	4
<sup>90</sup>		1.3.2 Specific Objectives . . . . .	4
<sup>91</sup>		1.4 Scope and Limitations of the Research . . . . .	5
<sup>92</sup>		1.5 Significance of the Research . . . . .	6
<sup>93</sup>	<b>2</b>	<b>Review of Related Literature</b>	<b>9</b>
<sup>94</sup>		2.1 Dengue . . . . .	9
<sup>95</sup>		2.2 Outbreak Definition . . . . .	10

96	2.3 Existing System: RabDash DC . . . . .	10
97	2.4 Deep Learning . . . . .	11
98	2.5 Kalman Filter . . . . .	12
99	2.6 Weather Data . . . . .	13
100	2.7 Chapter Summary . . . . .	14
101	<b>3 Research Methodology</b>	<b>15</b>
102	3.1 Research Activities . . . . .	16
103	3.1.1 Dengue and Climate Data Collection . . . . .	16
104	3.1.2 Develop and Evaluate Deep Learning Models for Dengue	
105	Case Forecasting . . . . .	19
106	3.1.3 Integrate the Predictive Model into a Web-Based Data An-	
107	alytics Dashboard . . . . .	25
108	3.1.4 System Development Framework . . . . .	26
109	3.2 Development Tools . . . . .	28
110	3.2.1 Software . . . . .	28
111	3.2.2 Hardware . . . . .	30
112	3.2.3 Packages . . . . .	30
113	3.3 Application Requirements . . . . .	33

## CONTENTS ix

114	3.3.1 Backend Requirements . . . . .	33
115	3.3.2 User Interface Requirements . . . . .	34
116	3.3.3 Security and Validation Requirements . . . . .	37
117	<b>4 Results and Discussion</b>	<b>39</b>
118	4.1 Data Gathering . . . . .	39
119	4.2 Exploratory Data Analysis . . . . .	40
120	4.3 Outbreak Detection . . . . .	45
121	4.4 Model Training Results . . . . .	45
122	4.4.1 LSTM Model . . . . .	47
123	4.4.2 ARIMA Model . . . . .	49
124	4.4.3 Seasonal ARIMA (SARIMA) Model . . . . .	50
125	4.4.4 Kalman Filter Model . . . . .	52
126	4.5 Model Simulation . . . . .	54
127	4.6 System Prototype . . . . .	56
128	4.6.1 Home Page . . . . .	56
129	4.6.2 User Registration, Login, and Authentication . . . . .	57
130	4.6.3 Encoder Interface . . . . .	59

131	4.6.4 Admin Interface . . . . .	68
132	4.7 User Testing . . . . .	74
133	<b>5 Conclusion</b>	<b>77</b>
134	<b>6 References</b>	<b>79</b>
135	<b>A Data Collection Snippets</b>	<b>83</b>

## <sup>136</sup> List of Figures

137	3.1 Workflow for forecasting the number of weekly dengue cases . . . . .	16
138	3.2 Testing Process for DengueWatch . . . . .	27
139	3.3 Entity-Relationship Database Schema Hybrid Diagram for DengueDash Database Structure . . . . .	33
140		
141	3.4 Use Case Diagram for Admins . . . . .	34
142	3.5 Use Case Diagram for Encoder . . . . .	36
143		
144	4.1 Trend of Dengue Cases . . . . .	42
145	4.2 Rainfall and Dengue Cases Over Time . . . . .	42
146	4.3 Kernel Density Estimate Plots of Meteorological Features . . . . .	44
147	4.4 Training Folds - Window Size 5 . . . . .	48
148	4.5 Testing Folds - Window Size 5 . . . . .	49
149	4.6 ARIMA Prediction Results for Test Set . . . . .	50

149	4.7 Seasonal ARIMA Prediction Results for Test Set . . . . .	51
150	4.8 Kalman Filter Prediction Results for Test Set . . . . .	53
151	4.9 Predicted vs Actual Dengue Cases 2025 . . . . .	55
152	4.10 Home Page . . . . .	56
153	4.11 Personal Information Tab of Sign Up Page . . . . .	57
154	4.12 Verification Tab of Sign Up Page . . . . .	58
155	4.13 Login Page . . . . .	58
156	4.14 First Part of Case Report Form . . . . .	60
157	4.15 Second Part of Case Report Form . . . . .	60
158	4.16 Bulk Upload of Cases using CSV . . . . .	61
159	4.17 Dengue Reports . . . . .	62
160	4.18 Detailed Case Report . . . . .	63
161	4.19 Update Report Dialog . . . . .	64
162	4.20 Delete Report Alert Dialog . . . . .	65
163	4.21 Forecasting Page . . . . .	67
164	4.22 Retraining Configurations . . . . .	68
165	4.23 Start Retraining . . . . .	69

*LIST OF FIGURES*

xiii

166	4.24 Retraining Results . . . . .	69
167	4.25 List of Verified Accounts . . . . .	70
168	4.26 List of Pending Accounts . . . . .	71
169	4.27 Account Details . . . . .	71
170	4.28 List of Blacklisted Accounts . . . . .	72
171	4.29 Disease Reporting Unit Registration . . . . .	73
172	4.30 List of Disease Reporting Units . . . . .	73
173	4.31 Disease Reporting Unit details . . . . .	74
174	A.1 Snippet of Consolidated Data . . . . .	83
175	A.2 Snippet of Weather Data Collection . . . . .	84
176	A.3 Letter of Approval for User Testing in UPV HSU . . . . .	85
177	A.4 System Usability Score Questionnaire . . . . .	86



# **List of Tables**

178	3.1 Hyperparameter Tuning: Search Space and Tuner Configuration . . . . .	20
180	4.1 Snippet of the combined dataset . . . . .	40
181	4.2 Data Schema: Column Names, Non-Null Counts, and Data Types . . . . .	41
182	4.3 Descriptive Statistics of the Combined Dataset . . . . .	41
183	4.4 Comparison of different models for dengue prediction . . . . .	46
184	4.5 Comparison of Window Sizes . . . . .	47
185	4.6 Time-Series Cross Validation Results: Comparison of Window Sizes . . . . .	48
186	4.7 Comparison of SARIMA performance for each fold . . . . .	52
187	4.8 Comparison of KF-LSTM performance for each fold . . . . .	54
188	4.9 Computed System Usability Scores per Participant . . . . .	75

<sup>189</sup> **Chapter 1**

<sup>190</sup> **Introduction**

<sup>191</sup> **1.1 Overview of the Current State of Technology**

<sup>192</sup> Dengue cases surged globally in 2023 and continued to rise in 2025, with over  
<sup>193</sup> five million cases and more than 5,000 deaths across 80 countries (Bosano, 2023).

<sup>194</sup> The World Health Organization reported a ten-fold increase in cases from 2000  
<sup>195</sup> to 2019, peaking in 2019 with the disease affecting 129 countries (WHO, 2024).

<sup>196</sup> In the Philippines, dengue remains endemic, leading to prolonged and widespread  
<sup>197</sup> outbreaks.

<sup>198</sup> In Iloilo, dengue cases escalated dramatically. By August 2023, the provincial  
<sup>199</sup> health office reported 4,585 cases and 10 deaths, marking a 319% increase from  
<sup>200</sup> the previous year (Perla, 2024). Iloilo has reached the outbreak threshold, and  
<sup>201</sup> local authorities are on blue alert. In Iloilo City, 649 cases were recorded in 2024,  
<sup>202</sup> with two deaths. Hospital capacity is strained, with non-COVID-19 hospital bed

203 occupancy exceeding 76%. This highlights the increasing pressure on healthcare  
204 resources in the region.

205 In recent years, technology has played a growing role in improving disease  
206 surveillance across the globe. Internationally, a study published in *Frontiers*  
207 in Physics utilized the Kalman filter to predict COVID-19 deaths in Ceará,  
208 Brazil(Ahmadi et al., 2021). A study also suggests that weather-based fore-  
209 casting models using variables like mean temperature and cumulative rainfall can  
210 provide early warnings of dengue outbreaks with high sensitivity and specificity,  
211 enabling predictions up to 16 weeks in advance (Hii, Zhu, Ng, Ng, & Rocklöv,  
212 2012). Locally, in Davao City, Ligue (2022) found that deep learning models can  
213 accurately predict dengue outbreaks by capturing complex, time-dependent pat-  
214 terns in environmental data. The study of Carvajal et. al. uses machine learning  
215 methods to reveal the temporal pattern of dengue cases in Metropolitan Manila  
216 and emphasizes the significance of relative humidity as a key meteorological fac-  
217 tor, alongside rainfall and temperature, in influencing this pattern (Carvajal et  
218 al., 2018).

219 Most studies remain theoretical or academic, with limited translation into  
220 practical tools that communities and local health authorities can use for early  
221 warning and response. An example of such application is RabDash, developed by  
222 the University of the Philippines Mindanao. RabdashDC (2024) is a web-based  
223 dashboard for rabies data analytics. However, while RabDash demonstrates the  
224 potential of applying advanced analytics in public health, similar systems are  
225 lacking in the context of dengue.

<sup>226</sup> **1.2 Problem Statement**

<sup>227</sup> Dengue remains a critical public health challenge worldwide, with cases increasing  
<sup>228</sup> due to the easing of COVID-19 restrictions and heightened global mobility. While  
<sup>229</sup> a temporary decline in cases was observed during the pandemic (2020–2022) due  
<sup>230</sup> to reduced surveillance efforts, 2023 marked a resurgence, with over five million  
<sup>231</sup> cases and more than 5,000 deaths reported across 80 countries (Bosano, 2023).  
<sup>232</sup> In Iloilo City and Province, dengue cases rose by 319% as of August 2023, over-  
<sup>233</sup> whelming local healthcare systems. This surge strained resources, with over 76%  
<sup>234</sup> of non-COVID-19 hospital beds occupied by dengue patients (Perla, 2024), high-  
<sup>235</sup> lighting the urgent need for effective monitoring and predictive tools. Despite  
<sup>236</sup> all these studies, there remains a significant gap in the development of publicly  
<sup>237</sup> accessible systems that apply these predictive models in real-world settings. Most  
<sup>238</sup> existing studies remain confined to academic or theoretical contexts, with little  
<sup>239</sup> translation into practical tools for local communities and public health authorities.  
<sup>240</sup> In particular, there is a lack of research focused specifically on dengue prediction  
<sup>241</sup> and surveillance in Iloilo. While deep learning models have shown high accuracy  
<sup>242</sup> in other regions, their application in the local context of Iloilo is minimal. The  
<sup>243</sup> lack of a reliable system to monitor and forecast dengue outbreaks contributes to  
<sup>244</sup> delayed interventions, exacerbating public health risks and healthcare burdens in  
<sup>245</sup> the region.

<sup>246</sup> **1.3 Research Objectives**

<sup>247</sup> **1.3.1 General Objective**

<sup>248</sup> This study aims to develop a centralized monitoring and analytics system for  
<sup>249</sup> dengue cases in Iloilo City and Province with data management and forecasting  
<sup>250</sup> capabilities. The researchers will train and compare multiple deep learning models  
<sup>251</sup> to predict dengue case trends based on climate data and historical dengue cases  
<sup>252</sup> to help public health officials in dengue surveillance.

<sup>253</sup> **1.3.2 Specific Objectives**

<sup>254</sup> Specifically, this study aims to:

- <sup>255</sup> 1. gather dengue data from the Iloilo Provincial Health Office and climate data  
<sup>256</sup> (including temperature, rainfall, wind, and humidity) from online sources,  
<sup>257</sup> and combine and aggregate these into a unified dataset to facilitate compre-  
<sup>258</sup> hensive dengue case forecasting;
- <sup>259</sup> 2. train and evaluate deep learning models for predicting dengue cases using  
<sup>260</sup> metrics such as Mean Absolute Error (MAE), Root Mean Squared Error  
<sup>261</sup> (RMSE), and Mean Squared Error (MSE), and determine the most accurate  
<sup>262</sup> forecasting approach; and
- <sup>263</sup> 3. develop a web-based analytics dashboard that integrates the predictive model,  
<sup>264</sup> provides a data management system for dengue cases in Iloilo City and the

265 Province, and assess its usability and effectiveness through structured feed-  
266 back from health professionals and policymakers.

## 267 1.4 Scope and Limitations of the Research

268 This study aims to gather dengue data from the Iloilo Provincial Health Office  
269 and climate data from online sources such as PAGASA or weatherandclimate.com.  
270 These data will be preprocessed, cleaned, and combined into a unified dataset to  
271 facilitate comprehensive dengue case forecasting. However, the study is limited by  
272 the availability and completeness of historical data. Inconsistent or missing data  
273 points may introduce biases and reduce the quality of predictions. Furthermore,  
274 the granularity of the data will be in a weekly format.

275 To evaluate deep learning models for predicting dengue cases, the study will  
276 train and compare the performance of various models, using metrics like Mean  
277 Absolute Error (MAE) and Root Mean Square Error (RMSE). While these models  
278 aim to provide accurate forecasts, their performance is heavily influenced by the  
279 quality and size of the dataset. Limited or low-quality data may lead to suboptimal  
280 predictions. Additionally, the models cannot fully account for external factors  
281 such as public health interventions or socio-economic conditions which may impact  
282 dengue transmission dynamics.

283 The study also involves developing a web-based analytics dashboard that in-  
284 tegrates predictive models and provides a data management system for dengue  
285 cases in Iloilo City and the Province. This dashboard will offer public health  
286 officials an interactive interface to visualize dengue trends, input new data, and

287 identify risk areas. However, its usability depends on feedback from stakeholders,  
288 which may vary based on their familiarity with analytics tools. Moreover, exter-  
289 nal factors such as limited internet connectivity or device availability in remote  
290 areas may affect the system's adoption and effectiveness. While the dashboard  
291 provides valuable insights, it cannot incorporate all factors influencing dengue  
292 transmission, emphasizing the need for ongoing validation and refinement.

## 293 1.5 Significance of the Research

294 This study's development of an AI-based dengue forecasting and monitoring sys-  
295 tem has wide-reaching significance for various stakeholders in Iloilo City:

- 296 • Public Health Agencies: Organizations like the Department of Health (DOH)  
297 and local health units in Iloilo City and Province stand to benefit greatly  
298 from the system. With dengue predictions, we can help these agencies opti-  
299 mize their response strategies and implement targeted prevention measures  
300 in high-risk areas before cases escalate.
- 301 • Local Government Units (LGUs): LGUs can use the system to support  
302 their disaster management and health initiatives by proactively addressing  
303 dengue outbreaks. The predictive insights allow for more efficient planning  
304 and resource deployment in barangays and communities most vulnerable to  
305 outbreaks, improving overall public health outcomes.
- 306 • Healthcare Facilities: Hospitals and clinics, which currently face high bed  
307 occupancy rates during dengue season will benefit from early outbreak fore-

## *1.5. SIGNIFICANCE OF THE RESEARCH*

7

308        casts that can help in managing patient inflow and ensuring adequate hos-  
309        pital capacity.

310        • Researchers and Policymakers: This AI-driven approach contributes valua-  
311        ble insights for researchers studying infectious disease patterns and policy-  
312        makers focused on strengthening the national AI Roadmap. The system's  
313        data can support broader initiatives for sustainable health infrastructure  
314        and inform policy decisions on resource allocation for dengue control.

315        • Community Members: By reducing the frequency and severity of outbreaks,  
316        this study ultimately benefits the community at large. This allows for timely  
317        awareness campaigns and community engagement initiatives, empowering  
318        residents with knowledge and preventative measures to protect themselves  
319        and reduce the spread of dengue.



# <sup>320</sup> Chapter 2

## <sup>321</sup> Review of Related Literature

### <sup>322</sup> 2.1 Dengue

<sup>323</sup> Dengue disease is a tropical and subtropical mosquito-borne viral illness and is a  
<sup>324</sup> major health concern in the Philippines (Bravo, Roque, Brett, Dizon, & L'Azou,  
<sup>325</sup> 2014). The majority of individuals with dengue experience no symptoms. Fever is  
<sup>326</sup> the most common symptom, typically 4 to 7 days after being bitten by an infected  
<sup>327</sup> mosquito (Zhou & Malani, 2024). In recent years, the trend of dengue cases in  
<sup>328</sup> the Philippines has shown notable fluctuations, with periodic outbreaks occur-  
<sup>329</sup> ring every 3 to 5 years, often influenced by climatic and environmental changes.  
<sup>330</sup> According to the Department of Health (DOH), the number of reported cases  
<sup>331</sup> has steadily increased over the past decades, attributed to urbanization, popula-  
<sup>332</sup> tion growth, and inadequate vector control measures (World Health Organization  
<sup>333</sup> (WHO), 2018). Moreover, studies suggest that El Niño and La Niña events have  
<sup>334</sup> significant effects on dengue incidence, with warmer temperatures and increased

<sup>335</sup> rainfall providing favorable breeding conditions for mosquitoes (Watts, David M  
<sup>336</sup> and Burke, Donald S and Harrison, Bruce A and Whitmire, Ralph E and Nisalak,  
<sup>337</sup> Ananda, 2020). The study of Carvajal et. al. highlights the temporal pattern of  
<sup>338</sup> dengue cases in Metropolitan Manila and emphasizes the significance of relative  
<sup>339</sup> humidity as a key meteorological factor, alongside rainfall and temperature, in  
<sup>340</sup> influencing this pattern (Carvajal et al., 2018).

## <sup>341</sup> 2.2 Outbreak Definition

<sup>342</sup> The definition of an outbreak is a critical factor in disease surveillance, as it  
<sup>343</sup> determines the threshold at which an unusual increase in cases is considered a  
<sup>344</sup> public health concern. Studies suggest that outbreak thresholds should be context-  
<sup>345</sup> specific, given the variability in transmission dynamics across different locations  
<sup>346</sup> (Runge-Ranzinger et al., 2016). Outbreak definitions defined using the Endemic  
<sup>347</sup> Channel often base thresholds on 2 standard deviations (SD) above the mean  
<sup>348</sup> number of historic dengue cases. Other studies (Hemisphere, 2015) also used an  
<sup>349</sup> alert threshold of a 5-year mean plus 2 standard deviations. A study by (Brady,  
<sup>350</sup> Smith, Scott, & Hay, 2015) discussed that definitions of dengue outbreaks differ  
<sup>351</sup> significantly across regions and time, making them inconsistent and incomparable.

## <sup>352</sup> 2.3 Existing System: RabDash DC

<sup>353</sup> RabDash, developed by the University of the Philippines Mindanao, is a web-  
<sup>354</sup> based dashboard for rabies data analytics. It combines predictive modeling with

355 genomic data, enabling local health authorities to optimize interventions and al-  
356 locate resources more effectively. RabDash's modules include trend visualization,  
357 geographic hotspot mapping, and predictive forecasting, utilizing Long Short-  
358 Term Memory (LSTM) models for time-series forecasting (RabDashDC, 2024).

359 For DengueWatch, RabDash serves as a strong inspiration, particularly in  
360 its monitoring, historical trend visualization, and forecasting capabilities. These  
361 features align well with the needs of dengue control efforts, providing real-time  
362 insights into outbreak trends and enabling more effective, data-driven decision-  
363 making. RabDash's architecture is relevant to the DengueDash, as dengue out-  
364 breaks similarly require time-series forecasting models. By using LSTM, RabDash  
365 effectively models trends in outbreak data, which provides a framework for adapt-  
366 ing LSTM to dengue forecasting. Research indicates that LSTM models outper-  
367 form traditional methods, such as ARIMA and MLP, in handling the complexities  
368 of time-dependent epidemiological data (Ligue & Ligue, 2022).

## 369 2.4 Deep Learning

370 The study of (Ligue & Ligue, 2022) highlights how data-driven models can help  
371 predict dengue outbreaks. The authors compared traditional statistical meth-  
372 ods, such as non-seasonal and seasonal autoregressive integrated moving average  
373 (ARIMA), and traditional feed-forward network approach using a multilayer per-  
374 ceptron (MLP) model with a deep learning approach using the long short-term  
375 memory (LSTM) architecture in their prediction model. They found that the  
376 LSTM model performs better in terms of accuracy. The LSTM model achieved a

<sup>377</sup> much lower root mean square error (RMSE) compared to both MLP and ARIMA  
<sup>378</sup> models, proving its ability to capture complex patterns in time-series data (Ligue  
<sup>379</sup> & Ligue, 2022). This superior performance is attributed to LSTM's capacity  
<sup>380</sup> to capture complex, time-dependent relationships within the data, such as those  
<sup>381</sup> between temperature, rainfall, humidity, and mosquito populations, all of which  
<sup>382</sup> contribute to dengue incidence (Ligue & Ligue, 2022).

## <sup>383</sup> 2.5 Kalman Filter

<sup>384</sup> The Kalman Filter is another powerful tool for time-series forecasting that can be  
<sup>385</sup> integrated into our analysis. It provides a recursive solution to estimating the state  
<sup>386</sup> of a linear dynamic system from a series of noisy measurements. Its application  
<sup>387</sup> in epidemiological modeling can enhance prediction accuracy by accounting for  
<sup>388</sup> uncertainties in the data(Li et al., 2022). Studies have shown that Kalman filters  
<sup>389</sup> are effective in predicting infectious disease outbreaks by refining estimates based  
<sup>390</sup> on observed data. A study published in Frontiers in Physics utilized the Kalman  
<sup>391</sup> filter to predict COVID-19 deaths in Ceará, Brazil. They found that the Kalman  
<sup>392</sup> filter effectively tracked the progression of deaths and cases, providing critical in-  
<sup>393</sup> sights for public health decision-making (Ahmadini et al., 2021). Another research  
<sup>394</sup> article in PLOS ONE focused on tracking the effective reproduction number ( $R_t$ )  
<sup>395</sup> of COVID-19 using a Kalman filter. This method estimated the growth rate of  
<sup>396</sup> new infections from noisy data, demonstrating that the Kalman filter could main-  
<sup>397</sup> tain accurate estimates even when case reporting was inconsistent(Arroyo-Marioli,  
<sup>398</sup> Bullano, Kucinskas, & Rondón-Moreno, 2021).

399 This study compares ARIMA, seasonal ARIMA, Kalman Filter, and LSTM  
400 models using collected dengue case data along with weather data to identify the  
401 most effective model for real-time forecasting.

## 402 2.6 Weather Data

403 The relationship between weather patterns and mosquito-borne diseases is inher-  
404 ently nonlinear, meaning that fluctuations in disease cases do not respond propor-  
405 tionally to changes in climate variables(Colón-González, Fezzi, Lake, & Hunter,  
406 2013) Weather data, such as minimum temperature and accumulated rainfall, are  
407 strongly linked to dengue case fluctuations, with effects observed after several  
408 weeks due to mosquito breeding and virus incubation cycles. Integrating these  
409 lagged weather effects into predictive models can improve early warning systems  
410 for dengue control(Cheong, Burkart, Leitão, & Lakes, 2013). A study also sug-  
411 gests that weather-based forecasting models using variables like mean temperature  
412 and cumulative rainfall can provide early warnings of dengue outbreaks with high  
413 sensitivity and specificity, enabling predictions up to 16 weeks in advance(Hii et  
414 al., 2012).

415 This study utilizes weather data, including variables such as temperature,  
416 rainfall, and humidity, as inputs for our dengue forecasting model. Given the  
417 strong, nonlinear relationship between climate patterns and dengue incidence,  
418 these weather variables, along with their lagged effects, are essential for enhancing  
419 prediction accuracy and providing timely early warnings for dengue outbreaks.

**420 2.7 Chapter Summary**

421 This chapter reviewed key literature relevant to our study, focusing on existing  
422 systems, predictive modeling techniques and the role of weather data in forecast-  
423 ing dengue outbreaks. We examined systems like RabDash DC, which integrates  
424 predictive modeling with real-time data to inform public health decisions, provid-  
425 ing a foundational structure for our Dengue Watch System. Additionally, deep  
426 learning approaches, particularly Long Short-Term Memory (LSTM) networks,  
427 were highlighted for their effectiveness in time-series forecasting, while alternative  
428 methods such as ARIMA and Kalman Filters were considered for their ability to  
429 model complex temporal patterns and handle noisy data.

430 The literature further underscores the significance of weather variables—such  
431 as temperature and rainfall—in forecasting dengue cases. Studies demonstrate  
432 that these variables contribute to accurate outbreak prediction models. Lever-  
433 aging these insights, our study will incorporate both weather data and historical  
434 dengue case counts to build a reliable forecasting model.

# <sup>435</sup> Chapter 3

## <sup>436</sup> Research Methodology

<sup>437</sup> This chapter lists and discusses the specific steps and activities that were per-  
<sup>438</sup> formed to accomplish the project. The discussion covers the activities from pre-  
<sup>439</sup> proposal to Final SP Writing.

<sup>440</sup> Figure 3.1 summarizes the workflow for forecasting the number of weekly  
<sup>441</sup> dengue cases. This workflow focuses on using statistical, deep learning, and prob-  
<sup>442</sup> abilistic models to forecast the number of reported dengue cases. The approach  
<sup>443</sup> involves deploying several models for prediction, including ARIMA and Seasonal  
<sup>444</sup> ARIMA as statistical approaches, LSTM as a deep learning approach, and the  
<sup>445</sup> Kalman Filter as a probabilistic approach. These methods are compared with  
<sup>446</sup> each other to determine the most accurate model.




Figure 3.1: Workflow for forecasting the number of weekly dengue cases

### <sup>447</sup> 3.1 Research Activities

#### <sup>448</sup> 3.1.1 Dengue and Climate Data Collection

##### <sup>449</sup> Acquisition of Dengue Case Data

<sup>450</sup> The historical dengue case dataset used in this study was obtained from the Hu-  
<sup>451</sup> manitarian Data Exchange and the Western Visayas Center for Health Develop-  
<sup>452</sup> ment (WVCHD) via Freedom of Information (FOI) requests. The decision to use  
<sup>453</sup> weekly intervals was driven by the need for precision and timeliness in captur-  
<sup>454</sup> ing fluctuations in dengue cases and weather conditions. Dengue transmission is  
<sup>455</sup> influenced by short-term changes in weather variables such as rainfall and temper-  
<sup>456</sup> ature, which impact mosquito breeding and virus transmission cycles. A weekly  
<sup>457</sup> granularity allowed the model to better capture these short-term trends, enabling  
<sup>458</sup> more accurate predictions and responsive public health interventions.

459 Moreover, using a weekly interval provided more data points for training the  
460 models compared to a monthly format. This is particularly critical in time series  
461 modeling, where larger datasets help improve the robustness of the model and its  
462 ability to generalize to new data. Also, the collection of weather data was done  
463 by utilizing web scraping techniques to extract weekly weather data (e.g., rainfall,  
464 temperature, and humidity) from Weather Underground ([wunderground.com](http://wunderground.com)).

465

466 **Data Fields**

- 467 • **Time.** Represents the specific year and week corresponding to each entry  
468 in the dataset.
- 469 • **Rainfall.** Denotes the observed average rainfall, measured in millimeters,  
470 for a specific week.
- 471 • **Humidity.** Refers to the observed average relative humidity, expressed as  
472 a percentage, for a specific week.
- 473 • **Max Temperature.** Represents the observed maximum temperature, mea-  
474 sured in degrees Celsius, for a specific week.
- 475 • **Average Temperature.** Represents the observed average temperature,  
476 measured in degrees Celsius, for a specific week.
- 477 • **Min Temperature.** Represents the observed minimum temperature, mea-  
478 sured in degrees Celsius, for a specific week.
- 479 • **Wind.** Represents the observed wind speed, measured in miles per hour  
480 (mph), for a specific week.

- 481 • **Cases.** Refers to the number of reported dengue cases during a specific  
482 week.

483 **Data Integration and Preprocessing**

484 The dengue case data was integrated with the weather data to create a com  
485 prehensive dataset, aligning the data based on corresponding timeframes. The  
486 dataset undergoed a cleaning process to address any missing values, outliers, and  
487 inconsistencies to ensure its accuracy and reliability. To ensure that all features  
488 and the target variable were on the same scale, a MinMaxScaler was applied to  
489 normalize both the input features (climate data) and the target variable (dengue  
490 cases).

491 **Exploratory Data Analysis (EDA)**

492 Trends, seasonality, and correlations between reported dengue cases and weather  
493 factors were thoroughly analyzed to identify potential relationships in the dataset.  
494 To support and illustrate these findings, a series of visualizations, including time-  
495 series plots and scatterplots, were developed, to highlight key patterns and rela-  
496 tionships within the dataset.

497 **Outbreak Detection**

498 To detect outbreaks, we computed the outbreak threshold value of dengue cases  
499 using the formula,

$$\text{Outbreak Threshold Value} = \mu + 2\sigma \quad (3.1)$$

500 where  $\mu$  is the historical mean and  $\sigma$  is the standard deviation.

501 It is important to take note that definitions of dengue outbreaks differ signifi-  
502 cantly across regions and time. This computation is subject to changes depending  
503 on how the surveillance units detect outbreaks themselves.

### 504 **3.1.2 Develop and Evaluate Deep Learning Models for** 505 **Dengue Case Forecasting**

506 The deep learning models were developed and trained to forecast weekly dengue  
507 cases using historical weather data (rainfall, temperature, wind, and humidity)  
508 and dengue case counts. The dataset was normalized and divided into training and  
509 testing sets, ensuring temporal continuity to avoid data leakage. The methodology  
510 for preparing and training the model are outlined below.

#### 511 **Data Preprocessing**

512 The raw dataset included weekly aggregated weather variables (rainfall, tempera-  
513 ture, wind, humidity) and dengue case counts. The "Time" column was converted  
514 to a datetime format to ensure proper temporal indexing. To standardize the data  
515 for training, MinMaxScaler was employed, normalizing the feature values and tar-  
516 get variable to a range of 0 to 1. This step ensured that the models could efficiently  
517 process the data without being biased by feature scaling differences.

<sup>518</sup> **LSTM Model**

<sup>519</sup> The dataset was split into training and test sets to evaluate the model's performance and generalizability:

<sup>521</sup> • **Training Set:** 80% of the data (572 sequences) was used for model training,  
<sup>522</sup> enabling the LSTM to learn underlying patterns in historical dengue case  
<sup>523</sup> trends and their relationship with weather variables.

<sup>524</sup> • **Test Set:** The remaining 20% of the data (148 sequences) was reserved for  
<sup>525</sup> testing

<sup>526</sup> To prepare the data for LSTM, a sliding window approach was utilized. Sequences of weeks of normalized features were constructed as input, while the <sup>527</sup> dengue case count for the subsequent week was set as the target variable. This <sup>528</sup> approach ensured that the model leveraged temporal dependencies in the data for <sup>529</sup> forecasting. To enhance the performance of the LSTM model in predicting dengue <sup>530</sup> cases, Bayesian Optimization was employed using the Keras Tuner library. The <sup>531</sup> tuning process aimed to minimize the validation loss (mean squared error) by <sup>532</sup> adjusting key model hyper-parameters. Table 3.1 summarizes the search space <sup>533</sup> below:

Search Space	LSTM Units	Learning Rate
Min Value	32	0.0001
Max Value	128	0.01
Step	16	None
Sampling	Linear	Log
<b>Tuner Configuration</b>		
Max Trials	10	
Executions per Trial	3	
Validation Split	0.2	

Table 3.1: Hyperparameter Tuning: Search Space and Tuner Configuration

535        The hyperparameter tuning was conducted for three different window sizes of  
536        data: 5, 10, and 20. This allows the model to have the optimal hyperparameters  
537        used for each window size. Training was conducted over 100 epochs with early  
538        stopping to prevent overfitting while maintaining computational efficiency. A  
539        batch size of 1 was used, enabling the model to process individual sequences,  
540        which is suitable for smaller datasets but results in longer training times. The  
541        Adam optimizer, known for its adaptive learning capabilities and stability was  
542        employed.

543        To validate the effectiveness of the model, cross-validation was implemented.  
544        However, standard k-fold cross-validation randomly shuffles the data, which isn't  
545        suitable for time series since the order of observations is important. To address  
546        this, a time series-specific cross-validation strategy was used with TimeSeriesS-  
547        plit from the scikit-learn library. This method creates multiple train-test splits  
548        where each training set expands over time and each test set follows sequentially.  
549        This approach preserves the temporal structure of the data while helping reduce  
550        overfitting by validating the model across different time segments.

551        After training, predictions on both the training and test datasets were rescaled  
552        to their original scale using the inverse transformation of MinMaxScaler. Model  
553        performance was evaluated using the mean squared error (MSE), root mean  
554        squared error (RMSE) and mean absolute error (MAE).

## 555        ARIMA

556        The ARIMA model was utilized to forecast weekly dengue cases, leveraging histor-  
557        ical weather data—including rainfall, maximum temperature, and humidity—as

558 exogenous variables alongside historical dengue case counts as the primary dependent  
559 variable. The dataset was partitioned into training (80%) and testing (20%)  
560 sets while maintaining temporal consistency.

561 To identify the optimal ARIMA configuration, a comprehensive grid search  
562 was performed across the following parameter ranges:

- 563 • Autoregressive order (p): 0 to 3  
564 • Differencing order (d): 0 to 2  
565 • Moving average order (q): 0 to 3

566 Each combination of (p,d,q) was used to fit an ARIMA model, and performance  
567 was evaluated based on the mean squared error (MSE) between the predicted  
568 and actual dengue cases on the test set. The parameter set that achieved  
569 the lowest MSE was selected as the final model configuration.

570 Following model selection, the best-fit ARIMA model was retrained on the  
571 training set and subsequently used to forecast dengue cases for the test period.  
572 The predictions were assigned to the **PredictedCases** column in the test dataset.  
573 Model performance was further assessed using key evaluation metrics, including  
574 MSE, root mean squared error (RMSE), and mean absolute error (MAE). Visual  
575 comparisons between actual and predicted dengue cases were produced through  
576 line plots to better illustrate the model's forecasting accuracy.

**577 Seasonal ARIMA (SARIMA)**

578 The SARIMA modeling process began with data preprocessing, which included  
579 handling missing values through interpolation or imputation, and standardizing  
580 features to ensure stable model training. The dataset was then split into training  
581 and testing sets in an 80:20 ratio, preserving the temporal order of observations.  
582 Seasonality analysis was conducted using time series decomposition and autocor-  
583 relation plots, which revealed a periodicity of 52 weeks—justifying the adoption  
584 of a seasonal model. To fine-tune the model, a grid search was performed over a  
585 range of SARIMA parameters  $(p,d,q)(P,D,Q)[S]$ , while stationarity was validated  
586 using the Augmented Dickey-Fuller (ADF) test. The model was then trained  
587 on the dataset using rainfall, temperature, and humidity as exogenous variables,  
588 with convergence ensured by setting a maximum number of iterations. Residual  
589 diagnostics were used to confirm that residuals were uncorrelated, indicating a  
590 good model fit. For evaluation, forecasts were compared against actual values,  
591 and results were visualized with line plots. Finally, to validate the model's gener-  
592 alizability across different time periods, Time Series Cross-Validation with three  
593 folds was applied. This allowed assessment of the model's performance on multi-  
594 ple time segments, providing insights into its robustness in real-world forecasting  
595 scenarios.

**596 Kalman Filter:**

- 597 • Input Variables: The target variable (Cases) was modeled using three re-  
598 gressors: rainfall, max temperature, and humidity.
- 599 • Training and Testing Split: The dataset was split into 80% training and

600        20% testing to evaluate model performance.

601        • Observation Matrix: The Kalman Filter requires an observation matrix,  
602           which was constructed by adding an intercept (column of ones) to the re-  
603           gressors.

604        The Kalman Filter's Expectation-Maximization (EM) method was employed  
605        for training, iteratively estimating model parameters over 10 iterations. After  
606        training, the smoothing method was used to compute the refined state estimates  
607        across the training data. Observation matrices for the test data were constructed  
608        in the same manner as for the training set, ensuring compatibility with the learned  
609        model parameters. On the test data, the Kalman Filter applied these parameters  
610        to predict and correct the estimated dengue cases, providing more stable and  
611        accurate forecasts compared to direct regression models. Additionally, a hybrid  
612        Kalman Filter-LSTM (KF-LSTM) model was developed to combine the strengths  
613        of both approaches. In this setup, the LSTM model was first used to predict  
614        dengue cases based on historical data and weather features. The Kalman Filter  
615        was then applied as a post-processing step to the LSTM predictions, smoothing  
616        out noise and correcting potential errors.

617        **Model Simulation:**

618        After identifying the best-performing model among all the trained deep learning  
619        models, a simulation was conducted. Using the same parameters from the initial  
620        training, the selected model was retrained with the original dataset along with  
621        new data up to January 2025. The retrained model was then used to forecast

622 dengue cases for the period from February 2025 to May 2025. Listing 3.1 shows  
 623 a code snippet of the model training.

Listing 3.1: Code Snippet for Model Training

```

624     # Fit on train set
625
626     history = model.fit(
627         X_train, y_train,
628         epochs=100,
629         batch_size=1,
630         validation_split=0.2,
631         callbacks=[early_stop],
632         verbose=1
633     )
634
635     # Predict on 2025
636
637     y_pred_test = model.predict(X_test, verbose=0)

```

### 636 3.1.3 Integrate the Predictive Model into a Web-Based 637 Data Analytics Dashboard

#### 638 Dashboard Design and Development

- 639 • Design an intuitive, user-friendly web-based dashboard incorporating:
  - 640 – Interactive visualizations of yearly dengue case trends.
  - 641 – Data input and update forms for dengue and weather data.
  - 642 – Map display of dengue cases in each district in Iloilo City

**643 Model Integration and Deployment**

- 644 • Deploy the best-performing model within the dashboard as a backend service  
645 to enable real-time or periodic forecasting.

**646 3.1.4 System Development Framework**

647 The Agile Model is the birthchild of both iterative and incremental approaches  
648 in Software Engineering. It aims to be flexible and effective at the same time by  
649 being adaptable to change. It's also important to note that small teams looking  
650 to construct and develop projects quickly can benefit from this kind of method-  
651 ology. As the Agile Method focuses on continuous testing, quality assurance is a  
652 guarantee since bugs and errors are quickly identified and patched.

**653 Design and Development**

654 After brainstorming and researching the most appropriate type of application to  
655 accommodate both the prospected users and the proposed solutions, the team  
656 has decided to proceed with a web application. Given the time constraints and  
657 available resources, it has been decided that the said means is the most pragmatic  
658 and practical move. The next step is to select modern and stable frameworks  
659 that align with the fundamental ideas learned by the researchers in the university.  
660 The template obtained from WVCHD and Iloilo Provincial Epidemiology and  
661 Surveillance Unit was meticulously analyzed to create use cases and develop a  
662 preliminary well-structured database that adheres to the requirements needed  
663 to produce a quality application. The said use cases serve as the basis of general

664 features. Part by part, these are converted into code, and with the help of selected  
665 libraries and packages, it resulted in the desired outcome that may still modified  
666 and extended to achieve scalability.

667 **Testing and Integration**




Figure 3.2: Testing Process for DengueWatch

668 Implementing testing is important to validate the system's performance and ef-  
669 ficacy. Thus a series of tests were conducted to identify and resolve bugs during  
670 the developmental phase. Each feature was rigorously tested to ensure quality as-  
671 surance, with particular emphasis on prerequisite features, as development cannot  
672 progress properly if these fail. Because of this, integration between each feature

673 serves as a pillar for a cohesive user experience. Since dengue reports include  
674 confidential information, anonymized historical dengue reports were used to train  
675 the model and create the foundational architecture of the system. By using func-  
676 tional tests, data validation and visualization can be ensured for further continual  
677 improvements. Security testing is also important as it is needed to safeguard  
678 confidential information when the system is deployed. It includes proper authen-  
679 tication, permission views, and mitigating common injection attacks. Finally, a  
680 user acceptance test from the prospected users, in this case, doctors, nurses, and  
681 other health workers is crucial to assess its performance and user experience. It  
682 enables the developers to confirm if the system meets the needs of the problem.

## 683 **3.2 Development Tools**

### 684 **3.2.1 Software**

#### 685 **Github**

686 GitHub is a cloud-based platform that tracks file changes using Git, an open-  
687 source version control system (*About GitHub and Git - GitHub Docs*, n.d.). It is  
688 used in the project to store the application's source code, manage the system's  
689 source version control, and serve as a repository for the Latex files used in the  
690 actual research.

**691 Visual Studio Code**

692 Visual Studio Code is a free, lightweight, and cross-platform source code editor  
693 developed by Microsoft (*Why Visual Studio Code?*, 2021). As VS Code supports  
694 this project's programming and scripting languages, it was chosen as the primary  
695 source code editor.

**696 Django**

697 Django is a free and open-sourced Python-based web framework that offers an  
698 abstraction to develop and maintain a secure web application. As this research  
699 aims to create a well-developed and maintainable application, it is in the best  
700 interest to follow an architectural pattern that developers and contributors in the  
701 future can understand. Since Django adheres to Model-View-Template (MVT)  
702 that promotes a clean codebase by separating data models, business logic, and  
703 presentation layers, it became the primary candidate for the application's back-  
704 bone.

**705 Next.js**

706 A report by Statista (2024) claims that React is the most popular front-end frame-  
707 work among web developers. However, React has limitations that can be a nui-  
708 sance in rapid software development, which includes routing and performance op-  
709 timizations. This is where Next.js comes in—a framework built on top of React.  
710 It offers solutions for React's deficiency, making it a rising star in the framework  
711 race.

**712 Postman**

713 As the application heavily relies on the Application Programming Interface (API)  
714 being thrown by the backend, it is a must to use a development tool that facilitates  
715 the development and testing of the API. Postman is a freemium API platform  
716 that offers a user-friendly interface to create and manage API requests (*What is*  
717 *Postman? Postman API Platform*, n.d.).

**718 3.2.2 Hardware**

719 The web application was developed on laptop computers with minimum specifica-  
720 tions of an 11th-generation Intel i5 CPU and 16 gigabytes of RAM. Furthermore,  
721 an RTX 3060 mobile GPU was also utilized to retrain the integrated model locally.

**722 3.2.3 Packages****723 Django REST Framework**

724 Django Rest Framework (DRF) is a third-party package for Django that provides a  
725 comprehensive suite of features to simplify the development of robust and scalable  
726 Web APIs (Christie, n.d.). These services include Serialization, Authentication  
727 and Permissions, Viewsets and Routers, and a Browsable API .

**728 Leaflet**

729 One of the features of the web application is the ability to map the number  
730 of cases using a Choropleth Map. Leaflet is the only free, open-sourced, and  
731 most importantly, stable JavaScript package that can do the job. With its ultra-  
732 lightweight size, it offers a comprehensive set of features that does not trade  
733 off performance and usability (*Leaflet — an open-source JavaScript library for*  
734 *interactive maps*, n.d.).

**735 Chart.js**

736 Another feature of the application is to provide users with informative, approach-  
737 able data storytelling that is easy for everyone to understand. The transformation  
738 of pure data points and statistics into figures such as charts is a big factor. Thus,  
739 there is a need for a package that can handle this feature without compromising  
740 the performance of the application. Chart.js is a free and open-source JavaScript  
741 package that is made to meet this criteria as it supports various types of charts  
742 (*Chart.js*, n.d.).

**743 Tailwind CSS**

744 Using plain CSS in production-quality applications can be counterproductive.  
745 Therefore, CSS frameworks were developed to promote consistency and accelerate  
746 the rapid development of web applications (Joel, 2021). One of these is Tailwind,  
747 which offers low-level utility classes that can be applied directly to each HTML  
748 element to create a custom design (*Tailwind CSS - Rapidly build modern web-*

<sup>749</sup> *sites without ever leaving your HTML.*, n.d.). Given the limited timeline for this  
<sup>750</sup> project, using this framework is a wise choice due to its stability and popularity  
<sup>751</sup> among developers.

<sup>752</sup> **Shadcn**

<sup>753</sup> Shadcn offers a collection of open-source UI boilerplate components that can be  
<sup>754</sup> directly copied and pasted into one's project. With the flexibility of the provided  
<sup>755</sup> components, Shadcn allows developers to have full control over customization and  
<sup>756</sup> styling. Since this is built on top of Tailwind CSS and Radix UI, it is supported  
<sup>757</sup> by most modern frontend frameworks, including Next.js (Shadcn, n.d.).

<sup>758</sup> **Zod**

<sup>759</sup> Data validation is integral in this web application since it will handle crucial data  
<sup>760</sup> that will be used for analytical inferences and observations. Since Zod is primarily  
<sup>761</sup> used for validating and parsing data, it ensures proper communication between  
<sup>762</sup> the client and the server (Zod, n.d.).

<sup>763</sup> **3.3 Application Requirements**

<sup>764</sup> **3.3.1 Backend Requirements**

<sup>765</sup> **Database Structure Design**

<sup>766</sup> Determining how data flows and how it would be structured is crucial in creating  
<sup>767</sup> the system as it defines how extendible and flexible it would be for future features  
<sup>768</sup> and updates. Thus, creating a comprehensive map of data ensures proper nor-  
<sup>769</sup> malization that eliminates data redundancy and improves data integrity. Figure  
<sup>770</sup> 3.3 depicts the designed database schema that showcases the relationship between  
<sup>771</sup> the application's entities.




Figure 3.3: Entity-Relationship Database Schema Hybrid Diagram for DengueDash Database Structure

### <sup>772</sup> 3.3.2 User Interface Requirements

#### <sup>773</sup> Admin Interface




Figure 3.4: Use Case Diagram for Admins

774 Figure 3.4 shows the actions of an admin for a specific Disease Reporting Unit  
775 (DRU) and an admin for a specific Surveillance Unit can take in the application.  
776 Both of them include the management of accounts, browsing records, and fore-  
777 casting and retraining all the consolidated data under their supervision. Most  
778 importantly, these users must verify the encoders who register under their ju-  
779 risdiction before allowing their account to access the application in the name of  
780 safeguarding the integrity of the data. The only advantage of the latter type of ad-  
781 ministrator is that it has a one-step higher authorization as it manages the DRUs.  
782 In addition, only the authorized surveillance unit administrator can register and  
783 create a DRU to uphold transparency and accountability.

<sup>784</sup> **Encoder Interface**




Figure 3.5: Use Case Diagram for Encoder

<sup>785</sup> Figure 3.5, on the other hand, illustrates the use cases for the system's primary  
<sup>786</sup> users. These users can register but must wait for further verification to access the  
<sup>787</sup> application. Similar to the previous interfaces, encoders can browse and manage  
<sup>788</sup> records, as well as forecast the consolidated cases under a specific surveillance or  
<sup>789</sup> disease reporting unit, but they are not allowed to retrain the model. Lastly, they  
<sup>790</sup> are the only type of user that can file and create dengue cases by filling out a form  
<sup>791</sup> with the required details.

**792 3.3.3 Security and Validation Requirements****793 Password Encryption**

794 Storing passwords as plain text in the database is a disgrace and a mortal sin in  
795 production. It is important to implement precautionary methods such as hashing  
796 and salting, followed by encryption with a strong algorithm, to prevent bad actors  
797 from using the accounts for malicious transactions. By default, Django generates  
798 a unique random salt for each password and encrypts it with Password-Based Key  
799 Derivation Function 2 (PBKDF2) with a SHA256 hash function. Utilizing these  
800 techniques ensures that in the event of a data breach, cracking these passwords  
801 would be time-consuming and useless for the attackers.

**802 Authentication**

803 DengueWatch utilizes JSON Web Tokens (JWT) to authenticate the user. Since  
804 the mechanism operates in a stateless manner, tokens are served only after a  
805 successful login, eliminating the need for the server to keep a record of the token,  
806 which is vulnerable to session hijacking. In addition, these tokens are signed with  
807 a secret key, ensuring they have not been tampered with.

**808 Data Validation**

809 Both the backend and frontend should validate the input from the user to preserve  
810 data integrity. Thus, Zod is implemented in the latter to help catch invalid inputs  
811 from the user. By doing this, the user can only send proper requests to the server

which streamlines the total workflow. On the other hand, Django has also a built-in validator that checks the data type and ensures that the input matches the expected format on the server side. These validation processes ensure that only valid and properly formatted data is accepted, which reduces the risk of errors and ensures consistency across the web application.

<sup>817</sup> **Chapter 4**

<sup>818</sup> **Results and Discussion**

<sup>819</sup> **4.1 Data Gathering**

<sup>820</sup> The data for dengue case prediction was gathered from a variety of reliable sources,  
<sup>821</sup> enabling a comprehensive dataset spanning from January 2011 to October 2024.  
<sup>822</sup> This dataset includes 720 rows of data, each containing weekly records of dengue  
<sup>823</sup> cases along with corresponding meteorological variables, such as rainfall, temper-  
<sup>824</sup> ature, and humidity.

<sup>825</sup> 1. Dengue Case Data: The primary source of historical dengue cases came  
<sup>826</sup> from the Humanitarian Data Exchange and the Western Visayas Center for  
<sup>827</sup> Health Development (WVCHD). The dataset, accessed through Freedom of  
<sup>828</sup> Information (FOI) requests, provided robust case numbers for the Western  
<sup>829</sup> Visayas region. The systematic collection of these data points was essential  
<sup>830</sup> for establishing a reliable baseline for model training and evaluation.

831     2. Weather Data: Weekly weather data was obtained by web scraping from  
 832       Weather Underground, allowing access to rainfall, temperature, wind, and  
 833       humidity levels that correlate with dengue prevalence.

Time	Rainfall	MaxTemperature	AverageTemperature	MinTemperature	Wind	Humidity	Cases
2011-01-03	9.938571	29.444400	25.888890	23.888900	11.39	86.242857	5
2011-01-10	8.587143	30.000000	26.705556	24.444444	7.32	88.028571	4
2011-01-17	5.338571	30.000000	26.616667	25.000000	7.55	84.028571	2
2011-01-24	5.410000	30.555556	26.483333	20.555556	10.67	80.971429	7
2011-01-31	2.914286	28.333333	25.283333	18.650000	11.01	74.885714	2

Table 4.1: Snippet of the combined dataset

## 834   4.2 Exploratory Data Analysis

835   From Table 4.2, the dataset consists of 720 weekly records with 8 columns:

- 836     • **Time.** Weekly timestamps (e.g. “2011-w1”)
- 837     • **Rainfall.** Weekly average rainfall (mm)
- 838     • **MaxTemperature, AverageTemperature, MinTemperature.** Weekly  
 839       temperature data ( $^{\circ}\text{C}$ )
- 840     • **Wind.** Wind speed (m/s)
- 841     • **Humidity.** Weekly average humidity (%)
- 842     • **Cases.** Reported dengue cases

843   From the statistics in Table 4.3, the number of cases ranges from 0 to 319.

844   The average number of dengue cases per week is 23.74, with a median of 12 cases  
 845   and a standard deviation of 37.14. The distribution is highly skewed, with some

#	Column	Non-Null Count	Data Type
0	Time	720 non-null	datetime64[ns]
1	Rainfall	720 non-null	float64
2	MaxTemperature	720 non-null	float64
3	AverageTemperature	720 non-null	float64
4	MinTemperature	720 non-null	float64
5	Wind	720 non-null	float64
6	Humidity	720 non-null	float64
7	Cases	720 non-null	int64

Table 4.2: Data Schema: Column Names, Non-Null Counts, and Data Types

846 weeks experiencing significant number of cases (up to 319 cases). Rainfall shows  
 847 a wide variation (0 to 445mm), while temperature remains relatively stable, with  
 848 an average of 28.1 degree celsius. Humidity levels ranges from 73% to 89% with  
 849 a mean of 81.6%.

Statistic	Time	Rainfall	MaxTemperature	AverageTemperature	MinTemperature	Wind	Humidity	Cases
Count	720	720.000000	720.000000	720.000000	720.000000	720.000000	720.000000	720.000000
Mean	2017-12-02 11:22:00	13.957499	32.191142	28.110319	25.038472	6.172417	81.609442	23.744444
Min	2011-01-03 00:00:00	0.000000	-14.600000	24.494444	12.222222	1.910000	73.185714	0.000000
25%	2014-06-21 06:00:00	1.270000	31.666667	27.504167	25.000000	4.117500	79.885713	5.000000
50% (Median)	2017-12-07 12:00:00	4.318000	32.222222	28.161111	25.000000	5.725000	81.771429	12.000000
75%	2021-05-11 18:00:00	10.414000	32.777778	28.751389	25.555556	7.860000	83.503571	26.000000
Max	2024-10-28 00:00:00	445.008000	58.333333	30.916667	32.222222	19.200000	89.571429	319.000000
Std Dev	N/A	35.448846	2.616379	0.999800	1.291659	2.446703	2.831674	37.144813

Table 4.3: Descriptive Statistics of the Combined Dataset

850 Figure 4.1 illustrates the trend of weekly dengue cases over time. The data  
 851 reveals periodic spikes in the number of cases, suggesting a seasonal pattern in  
 852 dengue cases. Notably, peak cases are observed during certain periods approx-  
 853 imately 3 years, potentially aligning with specific climatic conditions such as  
 854 increased rainfall or temperature changes. This underscores the importance of  
 855 incorporating climate variables into the forecasting model.

856 Figure 4.2 presents a time series subplot that combines rainfall and dengue  
 857 cases to highlight potential non-linear associations between the two variables. In  
 858 this figure, raw rainfall data is represented by blue scatter points (aligned with




Figure 4.1: Trend of Dengue Cases

the left y-axis), while a blue solid line traces its 4-week rolling average to reveal underlying trends. Simultaneously, the red dashed line illustrates the smoothed trajectory of dengue cases (aligned with the right y-axis), also using a 4-week rolling average to reduce short-term fluctuations and emphasize longer-term patterns.

Notably, the plot suggests a recurring pattern. Periods of increased rainfall often precede or coincide with spikes in dengue cases. This observed relationship supports existing literature which proposes that higher rainfall contributes to the proliferation of mosquito breeding sites, particularly in stagnant water, thereby elevating the risk of dengue transmission.




Figure 4.2: Rainfall and Dengue Cases Over Time

The KDE plots in Figure 4.3 illustrate the distributions of meteorological vari-

ables during outbreak and normal dengue weeks. The x-axes represent the actual values of each feature, while the y-axes show density, indicating how frequently values occur within each category. The graphs reveal that outbreak weeks tend to have moderately higher rainfall than weeks with no outbreak. This is evident in the way the curve for outbreak weeks is positioned slightly to the right of the curve for normal weeks. In terms of temperature, the distributions for both normal and outbreak weeks appear very similar; however, upon closer inspection, the curve for maximum temperature shows a slightly higher density at higher values during outbreak weeks. The same is true for humidity, with outbreak weeks showing greater density at higher humidity levels. These patterns suggest that dengue outbreaks are more likely to occur during warm, humid periods with relatively high rainfall. Based on these observations, rainfall, maximum temperature, and humidity were selected as the meteorological features for training the predictive models.




Figure 4.3: Kernel Density Estimate Plots of Meteorological Features

**884 4.3 Outbreak Detection**

885 To identify outbreaks, the researchers calculated the outbreak threshold value  
886 using the historical mean as the endemic channel. The threshold is determined  
887 using the formula:

$$\text{Outbreak Threshold Value} = \mu + 2\sigma \quad (4.1)$$

$$= 23.744444 + 2(37.144813) \quad (4.2)$$

$$= 23.744444 + 74.289626 \quad (4.3)$$

$$= 98.03407 \quad (4.4)$$

888 where  $\mu$  is the historical mean and  $\sigma$  is the standard deviation.

889 This result indicates that dengue cases exceeding 98 in Iloilo City can be  
890 considered an outbreak. However, it is important to note that this threshold  
891 serves only as a baseline.

**892 4.4 Model Training Results**

893 The models were evaluated using three commonly used regression metrics: Mean  
894 Squared Error (MSE), Root Mean Squared Error (RMSE), and Mean Absolute  
895 Error (MAE). These metrics help assess how accurately each model forecasts  
896 dengue cases based on historical data. Table 4.4 presents a comparative analysis

897 of the models using these metrics.

- 898 • **MSE** represents the average of the squared differences between predicted
- 899 and actual values. It penalizes larger errors more heavily.
- 900 • **RMSE**, the square root of MSE, provides a more interpretable value in the
- 901 same units as the target (i.e., number of dengue cases).
- 902 • **MAE** calculates the average magnitude of the errors without considering
- 903 their direction, giving a more straightforward understanding of the average
- 904 prediction error.

905 In simpler terms, lower values in these metrics indicate that the model is  
906 making more accurate predictions.

Method	LSTM	Seasonal ARIMA	ARIMA	Kalman Filter	KF-LSTM
Testing MSE	406.03	1261.20	1521.48	1474.82	785.35
Testing RMSE	20.15	34.45	39.00	38.40	25.56
Testing MAE	12.61	18.73	25.80	22.33	14.55
Best Parameters	Window Size: 5 Learning Rate: 0.01 Units: 64	(2,0,2)(0,1,1)	(1,2,2)	Observation Covariance: 10.0 Transition Covariance: 0.1 × Identity	Same as LSTM

Table 4.4: Comparison of different models for dengue prediction

907 As shown in Table 4.4, the LSTM model consistently achieved the lowest MSE  
908 (406.03), RMSE (20.15), and MAE (12.61) among all evaluated models. This  
909 suggests that, on average, the LSTM’s predictions were about 12 to 20 cases away  
910 from the actual values, which is a strong indication of reliability for practical use  
911 in public health decision-making.

912 In contrast, traditional time series models like Seasonal ARIMA and ARIMA  
913 showed higher errors, indicating less accurate predictions. For example, the Sea-  
914 sonal ARIMA model had an RMSE of 34.45, which implies that its forecasts devi-

915 ated from actual dengue case counts by around 34 cases on average, a significant  
 916 discrepancy for health officials planning resource allocation.

917 The Kalman Filter and hybrid KF-LSTM models showed moderate perfor-  
 918 mance. Although they did not outperform LSTM, the hybrid model (KF-LSTM)  
 919 still reduced errors compared to the standalone Kalman Filter.

920 These results highlight the potential of LSTM-based models to provide timely  
 921 and accurate forecasts that can support early intervention, resource planning, and  
 922 policy formulation to combat dengue outbreaks in Iloilo City.

#### 923 4.4.1 LSTM Model

924 The LSTM model was tuned for the following parameters: learning rate and units.  
 925 The hyperparameter tuning was conducted for each window size, finding the best  
 926 parameters for each window size. Further evaluating which window size is most  
 927 suitable for the prediction model, Table 4.5 shows the evaluation metrics for each  
 window size used in the LSTM model training.

Window Size	MSE	RMSE	MAE	R <sup>2</sup>
5	406.03	20.15	12.61	0.76
10	1037.77	32.21	26.79	0.39
20	427.39	20.67	13.61	0.75

Table 4.5: Comparison of Window Sizes

928

929 The results indicate that a window size of 5 weeks provides the most accurate  
 930 predictions, as evidenced by the lowest MSE and RMSE values. Furthermore, the  
 931 R<sup>2</sup> score of 0.76 indicates that 76% of the variability in the target variable (cases)  
 932 is explained by the independent variables (the inputs) in the model, making it a

933 reliable configuration overall.

934 As shown in Table 4.6, the results from time series cross-validation indicate  
 935 consistent performance trends, with a window size of 5 yielding the highest average  
 936 RMSE across all folds compared to the other window sizes.

Window Size	Average RMSE	Average MAE	Average R <sup>2</sup>
<b>5</b>	<b>16.69</b>	<b>9.06</b>	<b>0.79</b>
<b>10</b>	<b>17.08</b>	<b>10.40</b>	<b>0.75</b>
<b>20</b>	<b>16.93</b>	<b>8.75</b>	<b>0.81</b>

Table 4.6: Time-Series Cross Validation Results: Comparison of Window Sizes

937 Figure 4.4 illustrates the model's performance in predicting dengue cases for  
 938 each fold using a window size of 5. As shown in the plot, the training set pro-  
 939 gressively increases with each fold, mimicking a real-world scenario where more  
 940 data becomes available over time for dengue prediction. Figure 4.5 demonstrates  
 941 that the predicted cases closely follow the trend of the actual cases, indicating  
 942 that the LSTM model successfully captures the underlying patterns in the data.  
 943 It is also evident that as the fold number increases and the training set grows, the  
 944 accuracy of the predictions on the test set improves. Despite the test data being  
 945 unseen, the model exhibits a strong ability to generalize, suggesting it effectively  
 946 leverages past observations to predict future trends.




Figure 4.4: Training Folds - Window Size 5




Figure 4.5: Testing Folds - Window Size 5

#### 947 4.4.2 ARIMA Model

948 The ARIMA model was developed to capture non-seasonal trends in the data.  
 949 To determine the best model configuration, grid search was used to explore vari-  
 950 ous combinations of ARIMA parameters, ultimately selecting **ARIMA(1, 2, 2)**.  
 951 The model was iteratively refined over **400 iterations** to ensure convergence to  
 952 an optimal solution. Figure 4.6 illustrates the comparison between actual and  
 953 predicted dengue cases in the test set. As shown in the plot, the ARIMA model  
 954 struggled to capture the non-linear characteristics and abrupt spikes in the data.  
 955 Consequently, it failed to accurately reflect the fluctuations and outbreak patterns  
 956 seen in the actual case counts.




Figure 4.6: ARIMA Prediction Results for Test Set

957        The model's performance was assessed using regression metrics to evaluate its  
 958        forecasting capability. The ARIMA model yielded the following error metrics:

- 959        • **MSE (Mean Squared Error):** 1521.48
- 960        • **RMSE (Root Mean Squared Error):** 39.01
- 961        • **MAE (Mean Absolute Error):** 25.80

#### 962        4.4.3 Seasonal ARIMA (SARIMA) Model

963        To address the limitations of the ARIMA model, a Seasonal ARIMA (SARIMA)  
 964        model was developed to capture both non-seasonal and seasonal variations in the

965 data.

966 This model incorporates seasonal parameters, which were tuned using grid  
 967 search to find the best configuration: **SARIMA(2, 0, 2)(0, 1, 1)[52]**. As with  
 968 ARIMA, **400 iterations** were applied to ensure a robust fit. As shown in Figure  
 969 4.7, the SARIMA model demonstrates a notable improvement in performance.  
 970 Unlike its non-seasonal counterpart, it effectively captures the general trend and  
 971 aligns more closely with the peaks observed in the actual dengue cases, indicating  
 972 its ability to model seasonal dynamics.




Figure 4.7: Seasonal ARIMA Prediction Results for Test Set

973 The model's performance was assessed using regression metrics to evaluate its  
 974 forecasting capability. The SARIMA model yielded the following error metrics:

975        • **MSE:** 1109.69

976        • **RMSE:** 33.31

977        • **MAE:** 18.09

978        The lower error values, when compared to the ARIMA model, highlight the  
 979        SARIMA model's superior capability in forecasting dengue cases. Its effective-  
 980        ness in capturing seasonal patterns contributed to a more accurate representation  
 981        of the actual cases.

982        After training the model, the SARIMA model was validated using the same  
 983        Time Series Cross-Validation strategy employed in the LSTM model. Table 4.7  
 984        presents the performance metrics for each fold, as well as the average metrics  
 985        across all folds. The average RMSE and MAE values were close to those obtained  
 986        during the initial training phase, indicating that the SARIMA model performed  
 987        consistently across different time segments.

Fold	MSE	RMSE	MAE
1	659.68	25.68	16.00
2	2127.49	46.12	21.30
3	996.43	31.56	18.89
<b>Average</b>	<b>1261.20</b>	<b>34.45</b>	<b>18.73</b>

Table 4.7: Comparison of SARIMA performance for each fold

#### 988 4.4.4 Kalman Filter Model

989        Figure 4.8 shows the comparison between the actual dengue cases and the pre-  
 990        dicted values on the test set. As illustrated in the plot, the Kalman Filter model  
 991        demonstrates a moderate ability to follow the general trend of the actual data.

992 While it effectively captures some rising and falling patterns, it still struggles to  
 993 accurately replicate the sharp peaks and extreme values found in the real case  
 994 counts. This limitation is particularly noticeable during the large spikes in 2022  
 995 and 2024. The model's performance was evaluated using standard regression met-  
 996 rics. The results are as follows:

$$\text{MSE} = 1474.82, \quad \text{RMSE} = 38.40, \quad \text{MAE} = 22.34$$




Figure 4.8: Kalman Filter Prediction Results for Test Set

997 The Kalman Filter was then combined with the LSTM model in order to see  
 998 improvements in its predictions. Table 4.8 shows the metrics across three folds  
 999 using the same Time Series Cross Validation Strategy employed in the previous  
 1000 models to see how it performed on different time segments.

Fold	MSE	RMSE	MAE
1	113.59	10.66	6.42
2	752.51	27.43	12.11
3	1489.95	38.60	25.13
<b>Average</b>	<b>785.35</b>	<b>25.56</b>	<b>14.55</b>

Table 4.8: Comparison of KF-LSTM performance for each fold

1001 As can be seen in the table above, the performance of the hybrid model demon-  
 1002 strated improvements in all metrics as compared to just using the Kalman Filter  
 1003 alone.

## 1004 4.5 Model Simulation

1005 To evaluate the LSTM model’s real-world forecasting ability, a simulation was  
 1006 conducted to predict dengue cases for the year 2025. The model was retrained  
 1007 exclusively, using the parameters found from the initial training, on data from 2011  
 1008 to January 2025, using both dengue cases and weather variables. Importantly, the  
 1009 actual dengue case values for 2025 were never included during training. Instead,  
 1010 only the weather variables collected for 2025 were input into the model to generate  
 1011 predictions for that year. After prediction, the forecasted dengue cases for 2025  
 1012 were compared against the true observed cases to assess the model’s accuracy.  
 1013 Figure 4.9 shows that the predicted values closely follow the trend, although it  
 1014 may overestimate the dengue cases in some weeks.




Figure 4.9: Predicted vs Actual Dengue Cases 2025

1015 Retraining the model is essential to ensure it remains accurate and responsive  
 1016 to the evolving trends of dengue case patterns over time. Ideally, the model should  
 1017 be updated whenever new data becomes available to capture recent dynamics.  
 1018 However, given the computational cost associated with retraining, a more practical  
 1019 approach is to update the model on a monthly basis. This allows the incorporation  
 1020 of approximately four weeks' worth of new data, providing a meaningful update  
 1021 to the model's predictive capabilities without excessive resource consumption.  
 1022 Furthermore, this schedule aligns with the typical data release cycle of provincial  
 1023 health offices, which, based on the researchers' experience, usually occurs monthly.  
 1024 This balance between accuracy and efficiency ensures that the model remains both  
 1025 up-to-date and manageable in real-world deployment.

<sup>1026</sup> **4.6 System Prototype**

<sup>1027</sup> **4.6.1 Home Page**

<sup>1028</sup> The Home Page is intended for all visitors to the web application. The Analytics  
<sup>1029</sup> Dashboard, which displays relevant statistics for dengue cases at a certain time  
<sup>1030</sup> and location, is the primary component highlighted, as seen in Figure 4.10. This  
<sup>1031</sup> component includes a combo chart that graphs the number of dengue cases and  
<sup>1032</sup> deaths per week in a specific year, a choropleth map that tracks the number of  
<sup>1033</sup> dengue cases per barangay in a location, and various bar charts that indicate the  
<sup>1034</sup> top constituent places affected by dengue.





Figure 4.10: Home Page

1035 **4.6.2 User Registration, Login, and Authentication**

1036 The registration page, as shown in 4.11 and 4.12, serves as a gateway to access  
 1037 the authenticated pages of the web application. Only prospective encoders can  
 1038 register an account, as administrator accounts are created by existing administra-  
 1039 tor accounts to protect the integrity of the data in production. After registering,  
 1040 the "encoder account" cannot access the authorized pages yet as it needs to be  
 1041 verified first by an administrator managing the unit the user entered. Because  
 1042 of this, proper identification (user's picture and employee identification card) is  
 1043 mandatory to help the admins verify the identity of the registrant. Once verified,  
 1044 the user can log in to the system through the page shown in Figure 4.13. Af-  
 1045 ter entering the correct credentials, which consist of an email and password, the  
 1046 system uses HTTP-only cookies containing JSON Web Tokens (JWT) to prevent  
 1047 vulnerability to Cross-site Scripting (XSS) attacks. It will then proceed to the  
 1048 appropriate page for the type of user it belongs to. Logging out, on the other  
 1049 hand, will remove both the access and refresh tokens from the browser and will  
 1050 blacklist the latter token to make it unusable for security purposes.



The screenshot shows the 'Sign Up' page for the DengueDash application. At the top, there is a dark header bar with the DengueDash logo on the left and 'Dashboard' and 'Login' links on the right. Below the header, the main title 'Sign Up' is centered above a sub-instruction 'Create your account to get started'. The form is divided into two tabs: 'Personal Information' (which is active, indicated by a blue border) and 'Verification' (indicated by a grey border). The 'Personal Information' tab contains fields for First Name ('John'), Middle Name ('David'), Last Name ('Doe'), Sex ('Male'), Email ('testereee@example.gov.ph'), Region ('Region VI (Western Visayas)'), Surveillance Unit ('Iloilo CESU'), DRU ('Saint Paul's Hospital'), Password (a masked string), and Confirm Password (a masked string). A note at the bottom of the form states 'Must be at least 8 characters long'. At the bottom of the form is a large black 'Next →' button. Below the button, a small link says 'Already have an account? [Sign in](#)'.

Figure 4.11: Personal Information Tab of Sign Up Page




Figure 4.12: Verification Tab of Sign Up Page




Figure 4.13: Login Page

**1051 4.6.3 Encoder Interface****1052 Case Report Form**

1053 Figures 4.14 and 4.15 show the digitized counterpart of the form obtained from the  
1054 Iloilo Provincial Epidemiology and Surveillance Unit. As the system aims to sup-  
1055 port expandability for future features, some fields were modified to accommodate  
1056 more detailed input. It is worth noting that all of the included fields adhere to the  
1057 latest Philippine Integrated Disease and Surveillance Response (PIDS) Dengue  
1058 Forms, which the referenced form was based on. By doing this, if implemented  
1059 on a national scale, the transition between targeted users will be easier. More-  
1060 over, the case form includes the patient's basic information, dengue vaccination  
1061 status, consultation details, laboratory results, and the outcome. On the other  
1062 hand, encoders can also create case records using a "bulk upload" feature that  
1063 makes use of a formatted CSV file template. As shown in Figure 4.16, an encoder  
1064 can download the template using the "Download Template" button, and insert  
1065 multiple records inside the file, then upload it by clicking the "Click to upload"  
1066 button. The web application automatically checks the file for data inconsis-  
1067 tencies and validation.

## CHAPTER 4. RESULTS AND DISCUSSION

**DengueDash**

Modules

- Analytics
- Forms
  - Case Report Form
- Data Tables

Forms > Case Report Form

### Case Report Form

**Personal Information**

**Clinical Status**

**Personal Detail**

First Name	Middle Name
Last Name	Suffix
Sex	Civil Status
Select Sex	Select Civil Status

Date of Birth

Pick a date

**Address**

Region	Province
Select Region	Select Province
City	Borough
Select City/Municipality	Select Borough
Street	House No.

**Vaccination**

Date of First Vaccination	Date of Last Vaccination
Pick a date	Pick a date

**Next**

Figure 4.14: First Part of Case Report Form

**DengueDash**

Modules

- Analytics
- Forms
  - Case Report Form
- Data Tables

Forms > Case Report Form

### Case Report Form

**Personal Information**

**Clinical Status**

**Consultation**

Date Admitted/Consulted/Seen	Is Admitted?
Pick a date	Select
Date Onset of illness	Clinical Classification
Pick a date	Select

**Laboratory Results**

NS1	Date done (NS1)
Pending Result	Pick a date
IgG ELISA	Date done (IgG ELISA)
Pending Result	Pick a date
IgM ELISA	Date done (IgM ELISA)
Pending Result	Pick a date
PCR	Date done (PCR)
Pending Result	Pick a date

**Outcome**

Case Classification	Outcome
Select	Select

Date of Death

Pick a date

**Previous**

**Submit**

Figure 4.15: Second Part of Case Report Form




Figure 4.16: Bulk Upload of Cases using CSV

### 1068 Browsing, Update, and Deletion of Records

1069 Once the data generated from the case report form or the bulk upload is vali-  
 1070 dated, it will be assigned as a new case and can be accessed through the Dengue  
 1071 Reports page, as shown in Figure 4.17. The said page displays basic information  
 1072 about the patient related to a specific case, including their name, address, date  
 1073 of consultation, and clinical and case classifications. It is also worth noting that  
 1074 it only shows cases that the user is permitted to view. For example, in a local  
 1075 Disease Reporting Unit (DRU) setting, the user can only access records that be-  
 1076 long to the same DRU. Additionally, users can search for cases by name, location,  
 1077 date of consultation, or classifications associated with the specific query, making

it easier to find pertinent information quickly and efficiently. On the other hand, in a consolidated surveillance unit such as a regional, provincial, or city quarter, its users can view all the records from all the DRUs that report to them. Moving forward, Figure 4.18 shows the detailed case report of the patient on a particular consultation date.

Case ID	Name	Barangay	City	Date Consulted	Clinical Classification	Case Classification	Action
25017062	Corey, Cassie Jonathan	Magsaysay	ILOILO CITY (Capital)	2024-12-28	With warning signs	Confirmed	<button>Open</button>
25017082	Kirk, Dominique Jacqueline	Rizal Palapala II	ILOILO CITY (Capital)	2024-12-28	Severe dengue	Confirmed	<button>Open</button>
25017067	Henderson, Joel Lindsey	Santa Rosa	ILOILO CITY (Capital)	2024-12-27	Severe dengue	Confirmed	<button>Open</button>
25017077	H Flynn, Christina Shannon	Tabuc Suba (Jaro)	ILOILO CITY (Capital)	2024-12-27	Severe dengue	Confirmed	<button>Open</button>
25017070	Green, Monique Mark	West Habog-habog	ILOILO CITY (Capital)	2024-12-26	With warning signs	Confirmed	<button>Open</button>
25017061	Thomas, Lisa Jared	San Pedro (Molo)	ILOILO CITY (Capital)	2024-12-24	With warning signs	Confirmed	<button>Open</button>
25017079	Esparza, Nicole Stephanie	Tabucan	ILOILO CITY (Capital)	2024-12-24	Severe dengue	Confirmed	<button>Open</button>
25017069	James, Emily Sara	Libertad, Santa Isabel	ILOILO CITY (Capital)	2024-12-23	With warning signs	Confirmed	<button>Open</button>

Figure 4.17: Dengue Reports

The screenshot shows the DengueDash application interface. On the left is a sidebar with 'DengueDash' logo and navigation links: Modules (Analytics, Forms, Data Tables, Dengue Reports), and a user profile for Charles Larson Griffin (CN: Charles Larson Griffin, Email: bakerwendy@example.com). The main content area is titled 'Data Tables > Dengue Reports'. It displays a detailed case record for Case Record #25016448.

**Personal Information:**

- Full Name: Doe, John David
- Date of Birth: April 29, 2025
- Sex: Male
- Civil Status: Married
- Full Address: 1231 Ice Ice Baby, Bulak Sur, BATAD, ILOILO

**Vaccination Status:**

- First Dose: May 7, 2025
- Last Dose: May 13, 2025

**Case Record #25016448:**

- Date of Consultation: April 30, 2025
- Patient Admitted?: No
- Date Onset of Illness: April 29, 2025
- Clinical Classification: With warning signs

**Laboratory Results:**

Test	Status	Date Done
NS1	Pending Result	N/A
IgG Elisa	Pending Result	N/A
IgM Elisa	Pending Result	N/A
PCR	Pending Result	N/A

**Outcome:**

- Case Classification: Probable
- Outcome: Dead
- Date of Death: May 13, 2025

**Interviewer:**

- Interviewer: Griffin, Charles Larson
- DRU: Saint Paul's Hospital

Figure 4.18: Detailed Case Report

1083 To update the case, the user can click the "Update Case" button, where a  
 1084 dialog will appear, and the updateable fields will be shown. It is worth noting  
 1085 that in this case, only fields under Laboratory Results and Outcome are included  
 1086 since they are the only ones that are time-based, where the result may change  
 1087 in the future. After updating, a prompt will show confirming the user's action.  
 1088 Moving forward, to delete a case record, the user must click the "Delete Case"  
 1089 button, and a prompt verifying the action will appear. After confirming, the case

1090 will be deleted permanently.

The screenshot shows the DengueDash application interface. On the left, there's a sidebar with 'Modules' listed: Analytics, Forms, Data Tables, and the currently selected 'Dengue Reports'. The main area displays 'Personal Information' for a patient named Doe, John David, born on May 15, 2025, female, from ILOCOS NORTE. Below this is a 'Case Record' section with consultation and onset dates both set to May 15, 2025. A 'Laboratory Results' section is open, showing pending results for NS1, IgG Elisa, IgM Elisa, and PCR. An 'Outcome' section indicates the patient is alive. An 'Interviewer' section lists Griffin, Charles Larson. A central modal dialog titled 'Update Case #25016548' contains fields for 'NS1' (Pending Result, Date Done N/A), 'IgG Elisa' (Pending Result, Date Done N/A), 'IgM Elisa' (Pending Result, Date Done N/A), and 'PCR' (Pending Result, Date Done N/A). It also has an 'Outcome' dropdown set to 'Alive' and a 'Save Changes' button. At the bottom of the dialog, it says 'N/A'.

Figure 4.19: Update Report Dialog




Figure 4.20: Delete Report Alert Dialog

## 1091 Forecasting

1092 The pièce de résistance of the web application's features is the Forecasting Page.  
 1093 This is where users can forecast dengue cases for the next few weeks. To predict,  
 1094 the application utilizes the exported LSTM model in a Keras format derived from  
 1095 training the consolidated data from the database. The said file stores the model's  
 1096 architecture and the learned parameters, which include the weights and biases  
 1097 to predict cases without training the data again. Furthermore, it requires the

recent weekly dengue cases and weather variable data (temperature, humidity, and rainfall) to form a sequence based on the window size, and the forecasted weather data via OpenWeatherAPI. Due to the limitations posed to the current subscribed student plan in the said API, only two weeks of forecasted weather data can be fetched. As a result, the web application can predict dengue cases for the next two following weeks. Moving forward, the Forecasting page, as shown in Figure 4.21, introduces a user-friendly interface that shows the current cases for the week and the predictions for the next two weeks with a range of 90 percent to 110 percent confidence interval that is presented in a simple but organized manner. There is also a line chart that shows the number of cases from the last 5 weeks plus the forecasted weekly cases. In addition, the current weather data for a specific week is also shown, as well as the forecasted weather data fetched from the said API. Lastly, locations where dengue cases have been reported for the current week are listed in the Location Risk Assessment component.




Figure 4.21: Forecasting Page

#### 1112 4.6.4 Admin Interface

##### 1113 Retraining

1114 With LSTM being the best-performing model among the models used in forecast-  
1115 ing dengue cases, it is the model chosen to power the prediction and retraining  
1116 of the consolidated data within the web application. Since the retraining process  
1117 consumes a lot of processing power and requires a more advanced understanding  
1118 of how it works, it was decided that the said feature should only be available to  
1119 admin users of surveillance units. Furthermore, the retraining component in the  
1120 Forecasting page includes three additional components that include the configura-  
1121 tion of LSTM parameters (Figure 4.22), the actual retraining of the consolidated  
1122 data from the database (Figure 4.23), and the results of the retraining that shows  
1123 the current and previous model metrics depending on the parameters entered  
1124 (Figure 4.24). It is also worth noting that when training, the model used a seeded  
1125 number to promote reproducibility.




Figure 4.22: Retraining Configurations

## 4.6. SYSTEM PROTOTYPE

69




Figure 4.23: Start Retraining




Figure 4.24: Retraining Results

1126 **Managing Accounts**

1127 Proper management of accounts is important to protect the integrity and confi-  
1128 dentiality of data. Thus, it is crucial for administrators to track their users and  
1129 control the flow of information. As discussed in the user registration of encoders,  
1130 admin users from a specific DRU or surveillance unit have the power to grant  
1131 them access to the web application. Figure 4.26 illustrates the interface for this  
1132 scenario, as the admins can approve or reject their applications. Once approved,  
1133 these users can access the features given to encoders and may be promoted to  
1134 have administrative access, as shown in Figure 4.27. Both Figure 4.26 and 4.27  
1135 also show the expanded details of the user, which include personal information,  
1136 proof of identification, and brief activity details within the system. When deleting  
1137 an account, the user’s email will be blacklisted and illegible to use when creating  
1138 another account, and all the cases reported by this user will be soft-deleted. How-  
1139 ever, the blacklist status can be reverted by clicking the ”Unban” button, which  
1140 would make the user of the email able to register to the web application again as  
1141 shown in Figure 4.28.

Name	Email	Role	Sex	Actions
Daniel Santiago Brandt	brandon02@example.org	Encoder	Female	<button>Open</button>

Figure 4.25: List of Verified Accounts

#### 4.6. SYSTEM PROTOTYPE

71

DengueDash

Modules

Accounts > Manage

User Approval

View and manage pending accounts

John David Doe

Encoder

SEX

Male

HOSPITAL ((DRU))

Saint Paul's Hospital

CREATED AT

June 1 2025 at 17:28:48

UPDATED AT

June 1 2025 at 17:28:48

LAST LOGIN

N/A

ID CARD

Pennsylvania IDENTIFICATION CARD  
NOT FOR REAL ID PURPOSES  
000-000-0000-0000-0000-0000-0000-0000  
01/07/1973 00  
ANDREW JASON  
RAPPORTEUR, PA 17181-0000  
1234567890  
01/07/2022  
18-000000000000000000  
5'11"  
SAMPLE  
Andrew Sample  
ID  
ORGAN DONOR

Approve

Delete

Figure 4.26: User Approval Page

Figure 4.27: Account Management

Email	Date Added	Actions
testereee@example.gov.ph	2025-05-15	<button>Unban</button>

Figure 4.28: List of Blacklisted Accounts

## 1142 Managing DRUs

1143 Unlike the registration of encoder accounts, the creation of Disease Reporting  
 1144 Units can only be done within the web application, and the user performing the  
 1145 creation must be an administrator of a surveillance unit. Figure 4.29 presents the  
 1146 fields the admin user must fill out, and once completed, the new entry will show  
 1147 as being managed by that unit, as shown in Figure 4.30. Figure 4.31, on the other  
 1148 hand, shows the details provided in the registration form as well as its creation  
 1149 details. There is also an option to delete the DRU, and when invoked, all the  
 1150 accounts being managed by it, and the cases reported under those accounts will  
 1151 be soft-deleted.

**DengueDash**

Modules

- Accounts
- DRU
  - Manage DRU
  - Add DRU
- Analytics
- Data Tables

CN iloilo City Epidemiol... [ilolocesu@gmail.com](#)

**Register Disease Reporting Unit**

Add a new Disease Reporting Unit to the surveillance system.

**Name**  
Enter DRU name  
The official name of the Disease Reporting Unit.

**Address Information**

Region	Province
Select Region	Select Province
City/Municipality	Barangay
Select City/Municipality	Select Barangay

**Street Address**  
House/Building No., Street Name

**Email**  
example@health.gov

**Contact Number**  
+63 912 345 6789

**DRU Type**  
Select DRU type  
The category that best describes this reporting unit.

**Register DRU**

Figure 4.29: Disease Reporting Unit Registration

**DengueDash**

Modules

- Accounts
- DRU
  - Manage DRU
  - Add DRU
- Analytics
- Data Tables

CN iloilo City Epidemiol... [ilolocesu@gmail.com](#)

**Manage Disease Reporting Units**

View and manage Disease Reporting Units

DRU Name	Email	Action
Molo District Health Center	molodistricthealth@gmail.com	<a href="#">Open</a>
Jaro Health Center	jarohealth@gmail.com	<a href="#">Open</a>
Saint Paul's Hospital	saintpaul@gmail.com	<a href="#">Open</a>

Figure 4.30: List of Disease Reporting Units

The screenshot shows the DengueDash application interface. On the left is a sidebar with navigation links: Accounts, DRU (selected), Analytics, and Data Tables. The main content area is titled "Disease Reporting Unit Profile" and shows the following details:

Name of DRU	Molo District Health Center	Email	moldistrictthealth@gmail.com
Address	M.H. Del Pilar Street, Molo, Molo, ILOILO CITY (Capital), ILOILO	Contact Number	09123456782
Region	Region VI (Western Visayas)	Surveillance Unit	Iloilo CESU
DRU Type	CHO/MHO/PHO		
Created At	May 5 2025 at 04:47:11	Updated At	May 5 2025 at 04:47:11

At the bottom right of the main content area is a red button labeled "Delete DRU".

Figure 4.31: Disease Reporting Unit details

## 1152 4.7 User Testing

1153 To evaluate the usability of the system, the System Usability Scale (SUS) was  
 1154 utilized. SUS is a Likert-scale-based questionnaire comprising 10 items that are  
 1155 critical to assessing system usability. A total of five participants completed the sur-  
 1156vey. Their responses were processed following the step-by-step calculation method  
 1157 adopted from (Babich, n.d.). The resulting usability scores for each participant  
 1158 are shown in Table 4.9.

1159 The average System Usability Scale (SUS) score across systems is typically  
 1160 68 (Babich, n.d.). In this testing, the system achieved an average SUS score  
 1161 of 88.5, indicating a highly positive user experience. This score suggests that  
 1162 participants found the system not only enjoyable to use but also intuitive enough

Participant	Usability Score
1	95.0
2	90.0
3	85.0
4	87.5
5	85.0
<b>Average</b>	<b>88.5</b>

Table 4.9: Computed System Usability Scores per Participant

<sub>1163</sub> to recommend to others. Furthermore, it demonstrates that the system is suitable  
<sub>1164</sub> for real-world applications without presenting significant complexity for first-time  
<sub>1165</sub> users.



<sup>1166</sup> **Chapter 5**

<sup>1167</sup> **Conclusion**

<sup>1168</sup> The development of DengueWatch marks a transformative leap forward in public  
<sup>1169</sup> health technology, providing Iloilo City with a centralized system to combat one  
<sup>1170</sup> of the most persistent mosquito-borne diseases. Previously, data was recorded  
<sup>1171</sup> manually on paper, making tracking and analysis slow and error-prone. Dengue-  
<sup>1172</sup> Watch digitizes this process, enabling faster, more accurate monitoring. More  
<sup>1173</sup> than an academic project, DengueWatch serves as a practical solution aimed at  
<sup>1174</sup> shifting the approach from reactive outbreak response to proactive prevention. By  
<sup>1175</sup> combining deep learning models with real-time climate data integration, the sys-  
<sup>1176</sup> tem achieves a level of accuracy and usability that makes it viable for real-world  
<sup>1177</sup> deployment.

<sup>1178</sup> At the heart of DengueWatch is a Long Short-Term Memory (LSTM) neural  
<sup>1179</sup> network, which outperformed traditional forecasting models such as ARIMA and  
<sup>1180</sup> Kalman Filter. The LSTM model achieved a Root Mean Square Error (RMSE) of  
<sup>1181</sup> 20.15, followed by the hybrid KF-LSTM model with an RMSE of 25.56, demon-

strating a substantial improvement in predictive capability. Consequently, the LSTM model was selected for integration into the DengueWatch system. Re-training the model monthly strikes a balance between maintaining accuracy and managing computational costs. It allows the model to incorporate new trends from the latest four weeks of data and aligns with the typical monthly data release schedule of provincial health offices.

Usability testing further underscored DengueWatch's readiness for real-world deployment. The system achieved an average System Usability Scale (SUS) score of 88.5, significantly above the industry benchmark of 68. This indicates that users found the system intuitive, efficient, and suitable for operational use in public health contexts. Key features such as a user-friendly dashboard and a two-week forecasting window ensure that the system supports timely, effective responses.

Beyond its immediate application in Iloilo City, the framework behind DengueWatch holds the potential for broader impact. With minor adaptations, it can be scaled nationally through integration with Department of Health surveillance systems.

<sub>1199</sub> **Chapter 6**

<sub>1200</sub> **References**

- <sub>1201</sub> About GitHub and Git - GitHub Docs. (n.d.). Retrieved from  
<sub>1202</sub> [https://docs.github.com/en/get-started/start-your-journey/  
about-github-and-git](https://docs.github.com/en/get-started/start-your-journey/about-github-and-git)
- <sub>1203</sub> Ahmadini, A. A. H., Naeem, M., Aamir, M., Dewan, R., Alshqaq, S. S. A., &  
Mashwani, W. K. (2021). Analysis and Forecast of the Number of Deaths,  
Recovered Cases, and Confirmed Cases from COVID-19 for the Top Four  
Affected Countries Using Kalman Filter. *Frontiers in Physics*, *9*, 629320.
- <sub>1207</sub> Arroyo-Marioli, F., Bullano, F., Kucinskas, S., & Rondón-Moreno, C. (2021).  
Tracking R of COVID-19: A New Real-Time Estimation Using the Kalman  
Filter. *PLOS ONE*, *16*(1), e0244474.
- <sub>1211</sub> Babich, N. (n.d.). *How to Use the System Usability Scale (SUS) to Evaluate the Usability of Your Website, year=2015*. Usability Geek. Retrieved  
from [https://usabilitygeek.com/how-to-use-the-system-usability  
-scale-sus-to-evaluate-the-usability-of-your-website/](https://usabilitygeek.com/how-to-use-the-system-usability-scale-sus-to-evaluate-the-usability-of-your-website/) (Accessed: 2025-04-26)

- 1216 Bobbitt, Z. (2021, November 17). *The Five Assumptions for Pearson Correla-  
1217 tion*. Retrieved from [https://www.statology.org/pearson-correlation-  
assumptions/](https://www.statology.org/pearson-correlation-<br/>1218 assumptions/) (Statology)
- 1219 Bosano, R. (2023). *WHO: PH Most Affected by Dengue in Western Pacific.*  
1220 Retrieved Use the date of access, from [https://news.abs-cbn.com/  
spotlight/12/22/23/who-ph-most-affected-by-dengue-in-western  
-pacific](https://news.abs-cbn.com/<br/>1221 spotlight/12/22/23/who-ph-most-affected-by-dengue-in-western<br/>1222 -pacific)
- 1223 Brady, O. J., Smith, D. L., Scott, T. W., & Hay, S. I. (2015). Dengue Disease  
1224 Outbreak Definitions Are Implicitly Variable. *Epidemics*, 11, 92–102.
- 1225 Bravo, L., Roque, V. G., Brett, J., Dizon, R., & L’Azou, M. (2014). Epidemiology  
1226 of Dengue Disease in the Philippines (2000–2011): A Systematic Literature  
1227 Review. *PLOS Neglected Tropical Diseases*, 8(11), e3027.
- 1228 Carvajal, T. M., Viacrucis, K. M., Hernandez, L. F. T., Ho, H. T., Amalin, D. M.,  
1229 & Watanabe, K. (2018). Machine Learning Methods Reveal the Temporal  
1230 Pattern of Dengue Incidence Using Meteorological Factors in Metropolitan  
1231 Manila, Philippines. *BMC Infectious Diseases*, 18, 1–15.
- 1232 Chart.js. (n.d.). Retrieved from <https://www.chartjs.org/>
- 1233 Cheong, Y. L., Burkart, K., Leitão, P. J., & Lakes, T. (2013). Assessing Weather  
1234 Effects on Dengue Disease in Malaysia. *International Journal of Environ-  
1235 mental Research and Public Health*, 10(12), 6319–6334.
- 1236 Christie, T. (n.d.). *Home - Django REST framework*. Retrieved from [https://www.djangoproject-rest-framework.org/](https://<br/>1237 www.djangoproject-rest-framework.org/)
- 1238 Colón-González, F. J., Fezzi, C., Lake, I. R., & Hunter, P. R. (2013). The  
1239 Effects of Weather and Climate Change on Dengue. *PLOS Neglected Tropical  
1240 Diseases*, 7(11), e2503.
- 1241 Hemisphere, N. (2015). Update on the Dengue Situation in the Western Pacific

- 1242           Region. *Update*.
- 1243   Hii, Y. L., Zhu, H., Ng, N., Ng, L. C., & Rocklöv, J. (2012). Forecast of Dengue  
 1244           Incidence Using Temperature and Rainfall. *PLOS Neglected Tropical Diseases*, 6(11), e1908.
- 1245
- 1246   Htoon, K. S. (2021, December 13). *Log Transformation: Purpose and In-*  
 1247           terpretation. [https://medium.com/@kyawsawtoon/log-transformation](https://medium.com/@kyawsawtoon/log-transformation-purpose-and-interpretation-9444b4b049c9)  
 1248           -purpose-and-interpretation-9444b4b049c9. (Medium)
- 1249   Joel, C. (2021, 10). *6 reasons to use Tailwind over traditional CSS*. Re-  
 1250           trieved from [https://dev.to/charliejoel/6-reasons-to-use-tailwind](https://dev.to/charliejoel/6-reasons-to-use-tailwind-over-traditional-css-1nc3)  
 1251           -over-traditional-css-1nc3
- 1252   Leaflet — an open-source JavaScript library for interactive maps. (n.d.). Retrieved  
 1253           from <https://leafletjs.com/>
- 1254   Li, X., Feng, S., Hou, N., Li, H., Zhang, S., Jian, Z., & Zi, Q. (2022). Applications  
 1255           of Kalman Filtering in Time Series Prediction. In *International conference*  
 1256           on *intelligent robotics and applications* (pp. 520–531).
- 1257   Ligue, K. D. B., & Ligue, K. J. B. (2022). Deep Learning Approach to Forecast-  
 1258           ing Dengue Cases in Davao City Using Long Short-Term Memory (LSTM).  
 1259           *Philippine Journal of Science*, 151(3).
- 1260   Perla. (2024). *Iloilo Beef Up Efforts Amid Hike in Dengue Cases*. Retrieved Use  
 1261           the date of access, from <https://www.pna.gov.ph/articles/1231208>
- 1262   RabDashDC. (2024). *RabDash DC*. Retrieved Use the date of access, from  
 1263           <https://rabdash.com>
- 1264   Runge-Ranzinger, S., Kroeger, A., Olliaro, P., McCall, P. J., Sánchez Tejeda, G.,  
 1265           Lloyd, L. S., . . . Coelho, G. (2016). Dengue Contingency Planning: From  
 1266           Research to Policy and Practice. *PLOS Neglected Tropical Diseases*, 10(9),  
 1267           e0004916.

- 1268 Shadcn. (n.d.). *Introduction*. Retrieved from <https://ui.shadcn.com/docs>
- 1269 *Tailwind CSS - Rapidly build modern websites without ever leaving your HTML*.
- 1270 (n.d.). Retrieved from <https://tailwindcss.com/>
- 1271 Watts, David M and Burke, Donald S and Harrison, Bruce A and Whitmire, Ralph
- 1272 E and Nisalak, Ananda. (2020). Effect of temperature on the transmission
- 1273 of dengue virus by *\*aedes aegypti\**. *The American Journal of Tropical*
- 1274 *Medicine and Hygiene*, 36(1), 143–152.
- 1275 *What is Postman? Postman API Platform*. (n.d.). Retrieved from <https://www.postman.com/product/what-is-postman/>
- 1276
- 1277 *Why Visual Studio Code?* (2021, 11). Retrieved from <https://code.visualstudio.com/docs/editor/whyvscode>
- 1278
- 1279 World Health Organization (WHO). (2018). Dengue and severe dengue in the
- 1280 philippines. *WHO Dengue Factsheet*. (Available at: <https://www.who.int>)
- 1281
- 1282 Zhou, S., & Malani, P. (2024). What Is Dengue? *JAMA*, 332(10), 850–850.
- 1283 Zod. (n.d.). *TypeScript-First Schema Validation with Static Type Inference*. Re-
- 1284 trieved from <https://zod.dev/?id=introduction> (Accessed: 2025-04-
- 1285 26)

<sup>1286</sup> **Appendix A**

<sup>1287</sup> **Data Collection Snippets**

Time	Rainfall	MaxTemperature	AverageTemperature	MinTemperature	Wind	Humidity	Cases
2011-w1	9.938571429	29.4444	25.88889	23.8889	11.39	86.24285714	5
2011-w2	8.587142857	30	26.70555556	24.44444444	7.32	88.02857143	4
2011-w3	5.338571429	30	26.61666667	25	7.55	84.02857143	2
2011-w4	5.41	30.55555556	26.48333333	20.55555556	10.67	80.97142857	7
2011-w5	2.914285714	28.33333333	25.28333333	18.65	11.01	74.88571429	2
2011-w6	3.44	31.11111111	27.53333333	25	3.69	85.27142857	5
2011-w7	1.444285714	30	27.06111111	25	6.69	82.1	6
2011-w8	0.7685714286	30.55555556	27.03333333	25	7.82	76.18571429	2
2011-w9	4.064285714	30.55555556	26.75	24.44444444	6.64	84.1	5
2011-w10	1.252857143	31.11111111	27.7	25.55555556	7.92	80.18571429	4
2011-w11	7.068571429	28.33333333	26.03888889	23.88888889	10.35	85.7	2
2011-w12	3.567142857	30.55555556	26.4	24.44444444	9.57	87.74285714	3
2011-w13	2.745714286	30	26.61666667	25	10.05	86.25714286	2
2011-w14	0.09285714286	30	27.44444444	25	8.25	76.32857143	4
2011-w15	1.008571429	31.11111111	26.89444444	22.77777778	7.93	80.64285714	5
2011-w16	0.8771428571	31.66666667	28.43333333	24.44444444	4.76	80.35714286	3
2011-w17	2.15	32.77777778	28.87222222	25.55555556	5.54	81.77142857	5
2011-w18	3.062857143	32.77777778	28.62777778	25	5.15	81.9	4
2011-w19	9.828571429	32.77777778	27.97222222	25	4.18	85.77142857	5
2011-w20	2.848571429	33.33333333	29.71111111	25.55555556	3.77	79.65714286	3
2011-w21	11.74142857	32.77777778	28.51111111	25	4.28	81.81428571	3
2011-w22	14.52857143	32.77777778	28.47222222	25.55555556	4.04	82.45714286	4
2011-w23	11.51714286	32.22222222	28.26111111	24.44444444	3.91	84.24285714	9
2011-w24	8.784285714	32.22222222	27.71111111	24.44444444	3.87	84.7	3
2011-w25	10.43714286	32.77777778	27.47777778	24.44444444	4.46	86.52857143	13
2011-w26	6.702857143	32.22222222	28.39444444	25	3.94	81.87142857	7
2011-w27	14.48	32.22222222	27.66666667	25	4.19	85.42857143	13
2011-w28	3.32	32.22222222	27.49444444	19.68333333	6.69	80.78571429	9
2011-w29	17.33714286	32.77777778	27.95555556	25	3.57	80.05714286	10
2011-w30	22.77	31.66666667	26.63888889	24.44444444	5.13	88.01428571	16
2011-w31	9.875714286	32.77777778	27.81111111	25	4.66	83.11428571	13

Figure A.1: Snippet of Consolidated Data




Figure A.2: Snippet of Weather Data Collection




Figure A.3: Letter of Approval for User Testing in UPV HSU

Please enter your participant number: 2

**System Usability Scale (SUS)**

This is a standard questionnaire that measures the overall usability of a system. Please select the answer that best expresses how you feel about each statement after using the system today.

	Strongly Disagree	Somewhat Disagree	Neutral	Somewhat Agree	Strongly Agree
1. I think I would like to use DengueWatch frequently to monitor and forecast dengue cases.	<input type="checkbox"/>				
2. I found DengueWatch unnecessarily complex when entering or analyzing data.	<input type="checkbox"/>				
3. I thought DengueWatch was easy to use, even for someone unfamiliar with AI forecasting tools.	<input type="checkbox"/>				
4. I think I would need the support of an IT or technical person to use all the features of DengueWatch.	<input type="checkbox"/>				
5. I found the visualizations (charts, maps, graphs) in DengueWatch to be well-integrated and informative.	<input type="checkbox"/>				
6. I thought there was too much inconsistency in how different parts of the DengueWatch system behaved.	<input type="checkbox"/>				
7. I believe most public health workers would learn to use DengueWatch very quickly.	<input type="checkbox"/>				
8. I found DengueWatch very cumbersome to use when entering weekly case reports or viewing forecasts.	<input type="checkbox"/>				
9. I felt confident in using DengueWatch to get the information I needed for decision-making.	<input type="checkbox"/>				
10. I needed to learn a lot of things before I could get going with DengueWatch.	<input type="checkbox"/>				

How likely are you to recommend this website to others? (please circle your answer)

Not at all likely 0    1    2    3    4    5    6    7    8    9    10 Extremely likely

Please provide important comments about the website:

Figure A.4: System Usability Score Questionnaire