TD3
Adli BOUZGUENDA

git branch / git status

```
@adli-bouzguenda ➜ /workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $ git branch --show-current
Adli_BOUZGUENDA
@adli-bouzguenda ➜ /workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $ git status
On branch Adli_BOUZGUENDA
Your branch is up to date with 'origin/Adli_BOUZGUENDA'.

nothing to commit, working tree clean
@adli-bouzguenda ➜ /workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $
```

Code src/main.py

```
from pathlib import Path
import csv
import json


DATA_DIR = Path("data/sample")

# These starter values mirror config/settings.yml.
# settings.yml is a human-readable configuration contract in the CORE.
# Parsing YAML is optional and is not required by the 18-hour lab sequence.
LOOKBACK_LABEL = "1 month"
INTERVAL_LABEL = "Daily"


def load_instruments():
    with open(DATA_DIR / "instruments.json", encoding="utf-8") as file:
        return json.load(file)


def load_prices():
    with open(DATA_DIR / "prices.csv", encoding="utf-8") as file:
        return list(csv.DictReader(file))


def filter_prices(prices, ticker):
    return [row for row in prices if row["ticker"] == ticker]


def get_first_close(prices):
    return float(prices[0]["close"])


def get_last_close(prices):
    return float(prices[-1]["close"])


def display_market_summary(asset, prices, show_currency=True):
    currency = f" {asset['currency']}" if show_currency else ""

    print(f"{asset['ticker']} - {asset['name']}")
    print(f"Observations : {len(prices)}")
    print(f"First close  : {get_first_close(prices):.2f}{currency}")
    print(f"Last close   : {get_last_close(prices):.2f}{currency}")


def main():
    instruments = load_instruments()
    prices = load_prices()

    instrument = instruments["instrument"]
    benchmark = instruments["benchmark"]

    instrument_prices = filter_prices(prices, instrument["ticker"])
    benchmark_prices = filter_prices(prices, benchmark["ticker"])

    print("=== MarketPulse ===")
    print()
    print("Market configuration")
    print(f"Period   : {LOOKBACK_LABEL}")
    print(f"Interval : {INTERVAL_LABEL}")
    print()
    print("Instrument")
    display_market_summary(instrument, instrument_prices)
    print()
    print("Benchmark")
    display_market_summary(benchmark, benchmark_prices, show_currency=False)


if __name__ == "__main__":
    main()
```

python src/main.py

```
@adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $ python src/main.py
=== MarketPulse ===

Market configuration
Period   : 1 month
Interval : Daily

Instrument
AAPL - Apple Inc.
Observations : 21
First close  : 250.00 USD
Last close   : 266.20 USD

Benchmark
SP500 - S&P 500
Observations : 21
First close  : 6600.00
Last close   : 6742.00
@adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $
```

git config

```
@adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $ git config user.name
Adli Bouzguenda
@adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $ git config user.email
adlib1805@gmail.com
@adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $
```

git status

```
@adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $ git status
On branch Adli_BOUZGUENDA
Your branch is up to date with 'origin/Adli_BOUZGUENDA'.

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   src/main.py

no changes added to commit (use "git add" and/or "git commit -a")
@adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $
```

git diff

```
$ git --no-pager diff
diff --git a/src/main.py b/src/main.py
index 884b045..9083283 100644
--- a/src/main.py
+++ b/src/main.py
@@ -26,6 +26,23 @@ def filter_prices(prices, ticker):
     return [row for row in prices if row["ticker"] == ticker]


+def get_first_close(prices):
+    return float(prices[0]["close"])
+
+
+def get_last_close(prices):
+    return float(prices[-1]["close"])
+
+
+def display_market_summary(asset, prices, show_currency=True):
+    currency = f" {asset['currency']}" if show_currency else ""
+
+    print(f"{asset['ticker']} - {asset['name']}")
+    print(f"Observations : {len(prices)}")
+    print(f"First close  : {get_first_close(prices):.2f}{currency}")
+    print(f"Last close   : {get_last_close(prices):.2f}{currency}")
+
+
 def main():
     instruments = load_instruments()
     prices = load_prices()
@@ -36,26 +53,18 @@ def main():
     instrument_prices = filter_prices(prices, instrument["ticker"])
     benchmark_prices = filter_prices(prices, benchmark["ticker"])

-    instrument_latest = instrument_prices[-1]
-    benchmark_latest = benchmark_prices[-1]
-
     print("=== MarketPulse ===")
     print()
+    print("Market configuration")
+    print(f"Period   : {LOOKBACK_LABEL}")
+    print(f"Interval : {INTERVAL_LABEL}")
+    print()
     print("Instrument")
-    print(f"{instrument['ticker']} - {instrument['name']}")
-    print(f"Last price: {instrument_latest['close']} {instrument['currency']}")
+    display_market_summary(instrument, instrument_prices)
     print()
     print("Benchmark")
-    print(f"{benchmark['ticker']} - {benchmark['name']}")
-    print(f"Last level: {benchmark_latest['close']}")
-    print()
-    print(f"Period: {LOOKBACK_LABEL}")
-    print(f"Interval: {INTERVAL_LABEL}")
-    print()
-    print("Observations")
-    print(f"{instrument['ticker']}: {len(instrument_prices)}")
-    print(f"{benchmark['ticker']}: {len(benchmark_prices)}")
+    display_market_summary(benchmark, benchmark_prices, show_currency=False)


 if __name__ == "__main__":
-    main()
+    main()
\ No newline at end of file
```

git add + git diff --staged

```
$ git add src/main.py
$ git --no-pager diff --staged
diff --git a/src/main.py b/src/main.py
index 884b045..9083283 100644
--- a/src/main.py
+++ b/src/main.py
@@ -26,6 +26,23 @@ def filter_prices(prices, ticker):
     return [row for row in prices if row["ticker"] == ticker]


+def get_first_close(prices):
+    return float(prices[0]["close"])
+
+
+def get_last_close(prices):
+    return float(prices[-1]["close"])
+
+
+def display_market_summary(asset, prices, show_currency=True):
+    currency = f" {asset['currency']}" if show_currency else ""
+
+    print(f"{asset['ticker']} - {asset['name']}")
+    print(f"Observations : {len(prices)}")
+    print(f"First close  : {get_first_close(prices):.2f}{currency}")
+    print(f"Last close   : {get_last_close(prices):.2f}{currency}")
+
+
 def main():
     instruments = load_instruments()
     prices = load_prices()
@@ -36,26 +53,18 @@ def main():
     instrument_prices = filter_prices(prices, instrument["ticker"])
     benchmark_prices = filter_prices(prices, benchmark["ticker"])

-    instrument_latest = instrument_prices[-1]
-    benchmark_latest = benchmark_prices[-1]
-
     print("=== MarketPulse ===")
     print()
+    print("Market configuration")
+    print(f"Period   : {LOOKBACK_LABEL}")
+    print(f"Interval : {INTERVAL_LABEL}")
+    print()
     print("Instrument")
-    print(f"{instrument['ticker']} - {instrument['name']}")
-    print(f"Last price: {instrument_latest['close']} {instrument['currency']}")
+    display_market_summary(instrument, instrument_prices)
     print()
     print("Benchmark")
-    print(f"{benchmark['ticker']} - {benchmark['name']}")
-    print(f"Last level: {benchmark_latest['close']}")
-    print()
-    print(f"Period: {LOOKBACK_LABEL}")
-    print(f"Interval: {INTERVAL_LABEL}")
-    print()
-    print("Observations")
-    print(f"{instrument['ticker']}: {len(instrument_prices)}")
-    print(f"{benchmark['ticker']}: {len(benchmark_prices)}")
+    display_market_summary(benchmark, benchmark_prices, show_currency=False)


 if __name__ == "__main__":
-    main()
+    main()
\ No newline at end of file
```

git status apres git add

```
● @adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $ git status
  On branch Adli_BOUZGUENDA
  Your branch is up to date with 'origin/Adli_BOUZGUENDA'.

  Changes to be committed:
    (use "git restore --staged <file>..." to unstage)
          modified:   src/main.py

○ @adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $
```

git commit

```
● @adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $ git commit -m "refactor: reuse market summary display"
  [Adli_BOUZGUENDA 7c87c8e] refactor: reuse market summary display
   1 file changed, 24 insertions(+), 15 deletions(-)
○ @adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $
```

git log

```
● @adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $ git --no-pager log --oneline
  7c87c8e (HEAD -> Adli_BOUZGUENDA) refactor: reuse market summary display
  a41d3b8 (origin/Adli_BOUZGUENDA) Add files via upload
  b584340 Add files via upload
  5207db8 first td session
  ba5c9f4 Update Readme
  9fd6c8a Update Readme
  bfb94a6 init projecttemplate
○ @adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $
```

git show HEAD

```
$ git --no-pager show HEAD
commit 7c87c8e5bf81a61bb12e1c077b6bdb75c1ac532e (HEAD -> Adli_BOUZGUENDA)
Author: Adli Bouzguenda <adlib1805@gmail.com>
Date:   Fri Nov 13 13:57:58 2026 +0000

    refactor: reuse market summary display

diff --git a/src/main.py b/src/main.py
index 884b045..9083283 100644
--- a/src/main.py
+++ b/src/main.py
@@ -26,6 +26,23 @@ def filter_prices(prices, ticker):
     return [row for row in prices if row["ticker"] == ticker]


+def get_first_close(prices):
+    return float(prices[0]["close"])
+
+
+def get_last_close(prices):
+    return float(prices[-1]["close"])
+
+
+def display_market_summary(asset, prices, show_currency=True):
+    currency = f" {asset['currency']}" if show_currency else ""
+
+    print(f"{asset['ticker']} - {asset['name']}")
+    print(f"Observations : {len(prices)}")
+    print(f"First close  : {get_first_close(prices):.2f}{currency}")
+    print(f"Last close   : {get_last_close(prices):.2f}{currency}")
+
+
 def main():
     instruments = load_instruments()
     prices = load_prices()
@@ -36,26 +53,18 @@ def main():
     instrument_prices = filter_prices(prices, instrument["ticker"])
     benchmark_prices = filter_prices(prices, benchmark["ticker"])

-    instrument_latest = instrument_prices[-1]
-    benchmark_latest = benchmark_prices[-1]
-
     print("=== MarketPulse ===")
     print()
+    print("Market configuration")
+    print(f"Period   : {LOOKBACK_LABEL}")
+    print(f"Interval : {INTERVAL_LABEL}")
+    print()
     print("Instrument")
-    print(f"{instrument['ticker']} - {instrument['name']}")
-    print(f"Last price: {instrument_latest['close']} {instrument['currency']}")
+    display_market_summary(instrument, instrument_prices)
     print()
     print("Benchmark")
-    print(f"{benchmark['ticker']} - {benchmark['name']}")
-    print(f"Last level: {benchmark_latest['close']}")
-    print()
-    print(f"Period: {LOOKBACK_LABEL}")
-    print(f"Interval: {INTERVAL_LABEL}")
-    print()
-    print("Observations")
-    print(f"{instrument['ticker']}: {len(instrument_prices)}")
-    print(f"{benchmark['ticker']}: {len(benchmark_prices)}")
+    display_market_summary(benchmark, benchmark_prices, show_currency=False)


 if __name__ == "__main__":
-    main()
+    main()
\ No newline at end of file
```

git push

```
● @adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $ git push origin Adli_BOUZGUENDA
  Enumerating objects: 7, done.
  Counting objects: 100% (7/7), done.
  Delta compression using up to 2 threads
  Compressing objects: 100% (3/3), done.
  Writing objects: 100% (4/4), 685 bytes | 685.00 KiB/s, done.
  Total 4 (delta 2), reused 0 (delta 0), pack-reused 0 (from 0)
  remote: Resolving deltas: 100% (2/2), completed with 2 local objects.
  To https://github.com/HENRIDVX/esilv-marketpulse-g01-HANEteam
     a41d3b8..7c87c8e  Adli_BOUZGUENDA -> Adli_BOUZGUENDA
○ @adli-bouzguenda ➜/workspaces/esilv-marketpulse-g01-HANEteam (Adli_BOUZGUENDA) $
```