Basics of MapReduce


NOT REQUIRED FOR THE EXAM

Overview over this video

This video discusses the basics of the MapReduce framework

C


Relational Databases are Powerful



Allow us to store, manage, and analyse large datasets

Some data analysis applications go beyond what such systems can handle...

Importance of Web Pages



Graph with all relevant HTML pages on the web

Task: rank pages by "importance"

Basis of Google Search

Problem: millions to billions of web pages

 \circ \approx an iterated matrix product (number of rows = number of pages)

"Big Data"

Finding Patterns in Large Datasets

Predictive maintenance, e.g.

- Which parts of a system are likely to fail or cause certain effects?
- Learn from sensor data, infrastructure data, etc.

Detect interesting patterns, e.g.

- Interesting phenomena in space, on earth, under water, in stock markets, etc.
- Recognise plants with certain diseases
- Estimate the likelihood of archeological artifacts at a certain site based on archeological data, geological parameters, etc.

Understand the structure/dynamics of large networks, e.g.


- Train networks
- Social networks

In these applications, the data is potentially huge.

Divide and Conquer

Often such problems can be solved as follows:

- Divide data into smaller chunks
- Perform computations on smaller chunks
- Combine results



MapReduce

Programming framework

Provides simple means to create programs that can scale to terabytes of data

Users only implement two methods

- Map: the computation on the smaller chunks of data
- **Reduce**: how the results are combined to the final result
- MapReduces manages the rest!

Implementations:

- MapReduce: Google's original implementation
- Apache Hadoop: open-source

Counting Words in Documents or: Hello World!

The Task

Given: a collection of "not too large" text files

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis noste exercitation

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostratione describitione de la consecuencia de l

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrati exercitation Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostar exercitation Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostratione exercitation Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostra exercitation

•••

file1.txt

file2.txt

file3.txt

file4.txt

file5.txt


file6.txt

•••

Task: for each word **w**, count how often **w** occurs in these files

How To Do This In MapReduce?

The MapReduce computation:



To implement this computation, we have to write two functions: Map & Reduce


The Map Function

The Map function is applied to a single key/value pair and produces a list of zero or more key/value pairs

Map(String filepath, String contents):
for each word w in contents:
output pair (w, "1")

Example:


("file1.txt", "Hello World! Hello UK! Hello Liverpool!")



("Hello", "1"), ("World!", "1"), ("Hello", "1"), ("UK!", "1"), ("Hello", "1"), ("Liverpool!", "1")

Grouping

After the Map functions have been applied, we group all values by key



The list of values for a key is the input to Reduce

The Reduce Function


The Reduce function takes a key and a list of values as input and outputs a list of key/value pairs

```
Reduce(String word, Iterator<String> values):
  int count = 0
  for each v in values:
     count = count + parseInt(v)
  output pair (word, toString(count))
```

Example:

Reduce("Hello", ("1","1","1")) outputs ("Hello", "3")

Putting Things Together



The Beauty of It...

We only had to implement these two functions...

MapReduce takes care of everything else:

- Parallel execution, including allocation of Map/Reduce to machines
- Failure

Summary

MapReduce (or Hadoop) is a powerful tool to deal with divide and conquer style problems