

Faculty of Natural and Mathematical Sciences

January 2021



Dr Sophia Tsoka

Department of Informatics

4CCS1DBS – Database Systems

Week 2 – Data Modelling Using the Entity-Relationship Model

Topic: Conceptual Modelling for Database Systems

Overview of Week 2 Topics

2

- Overview of Database Design Process
- Recapping data models
- Entity-Relationship (ER) Model Concepts
 - Entities, Entity Types, Attributes
 - Relationships and Relationship Types
 - Weak Entity Types
 - Constraints and Attributes in Relationship Types
- ER Diagrams - Notation
- ER Diagram for COMPANY Schema

In this Recording

3


- Overview of Database Design Process
- Recapping data models
- Entity-Relationship (ER) Model Concepts
 - Entities, Entity Types, Attributes
 - Relationships and Relationship Types
 - Weak Entity Types
 - Constraints and Attributes in Relationship Types
- ER Diagrams - Notation
- ER Diagram for COMPANY Schema

Overview of Database Design Process

4

- Two main activities:
 - Database design
 - Applications design
- Focus on database design here
 - To design the *conceptual schema* for a database application
- Applications design focuses on the *programs* and *interfaces* that access the database
 - Generally considered part of software engineering

5



Recap: Data Models

6

■ Data Model:

- A set of concepts to describe the **structure** of a database, the **data types, relationships** and certain **constraints** that apply to the data. May include basic operations for retrievals or updates.

■ Data Model Structure and Constraints:


- Constructs are used to define the database structure
- Constructs typically include **elements** (and their **data types**) as well as groups of elements (e.g. **entity, record, table**), and **relationships** among such groups
- Constraints specify some restrictions on valid data; these constraints must be enforced at all times

■ Data Model Operations:

- Database retrievals and updates by referring to the constructs of the data model (basic model operations or user-defined operations)


Recap: Categories of Data Models

- **Conceptual (high-level, semantic) data models:**
 - Provide concepts that are close to the way many users perceive data.
 - (Also called *entity-based* or *object-based* data models.)
- **Physical (low-level, internal) data models:**
 - Provide concepts that describe details of how data is stored in the computer. These are usually specified in an ad-hoc manner through DBMS design and administration manuals
- **Implementation (representational) data models:**
 - Provide concepts that fall between the above two, used by many commercial DBMS implementations (e.g. relational data models used in many commercial systems).



Overview of the Database Design Process

8



Example COMPANY Database

9

- We need to create a database schema design based on the following (simplified) **requirements** of the COMPANY Database:
 - The company is organised into DEPARTMENTS. Each department has a name, number and an employee who *manages* the department. We keep track of the start date of the department manager. A department may have several locations.
 - Each department *controls* a number of PROJECTs. Each project has a unique name, unique number and is located at a single location.


Example COMPANY Database (Contd.)

10

- We store each EMPLOYEE's social security number, address, salary, gender and birthdate.
 - Each employee *works for* one department but may *work on* several projects.
 - We keep track of the number of hours per week that an employee currently works on each project.
 - We also keep track of the *direct supervisor* of each employee.
- Each employee may *have* a number of DEPENDENTS.
 - For each dependent, we keep track of their name, sex, birthdate, and relationship to the employee.

An Entity-Relationship Diagram

11



Faculty of Natural and Mathematical Sciences

January 2021



Dr Sophia Tsoka

Department of Informatics

4CCS1DBS – Database Systems

Week 2 – Data Modelling Using the Entity-Relationship Model

Topic: Entities and Attributes


In this Recording

13

- Overview of Database Design Process
- Recapping data models
- Entity-Relationship (ER) Model Concepts
 - Entities, Entity Types, Attributes
 - Relationships and Relationship Types
 - Weak Entity Types
 - Constraints and Attributes in Relationship Types
- ER Diagrams - Notation
- ER Diagram for COMPANY Schema

An Entity-Relationship Diagram for the COMPANY Database

14



The COMPANY Database

15

- The company is organised into **DEPARTMENTS**. Each department has a name, number and an employee who manages the department. We keep track of the start date of the department manager. A department may have several locations.
- Each department controls a number of **PROJECTS**. Each project has a unique name, unique number and is located at a single location.
- We store each **EMPLOYEE's** social security number, address, salary, gender and birthdate.
- Each employee works for one department but may work on several projects.
- We keep track of the number of hours per week that an employee currently works on each project.
- We also keep track of the direct supervisor of each employee.
- Each employee may have a number of **DEPENDENTS**.
- For each dependent, we keep track of their name, sex, birthdate, and relationship to the employee.

Entity-Relationship (ER) Model Concepts

16

- Based on the previous specification of a mini-world, we define the conceptual model based on Entity-Relationship principles
- An Entity-Relationship model has three main concepts:
 - Entities (and their entity types and entity sets)
 - Attributes (simple, composite, single-valued, multi-valued)
 - Relationships (and their relationship types and relationship sets)

ER Model Concepts – Entities

17

- Entities are specific *objects* or *things* in the mini-world that are represented in the database
- For example:
 - the EMPLOYEE John Smith,
 - the Research DEPARTMENT,
 - the ProductX PROJECT
- Entities may be either physical (employees) or non-physical objects (projects)

ER Model Concepts – Attributes

18

- Attributes are properties used to describe an entity
 - For example an EMPLOYEE entity may have the attributes Name, SSN, Address, BirthDate etc.
- A specific entity will have a value for each of its attributes
 - For example a specific employee entity may have Name='John Smith', SSN='123456789', Address ='731, Fondren, Houston, TX', Sex='M', BirthDate='09-JAN-55'
- Each attribute has a *value set* (or *data type*) associated with it – e.g. integer, string, date, etc.

Types of Attributes (1)


19

- Simple attribute
 - Each entity has an atomic (non-divisible) value for this attribute
 - For example: Employee Social Security Number (SSN)

- Composite
 - The attribute may be composed of several components
 - For example:
 - Address(Apt#, House#, Street, City, State, ZipCode, Country), or
 - Name(FirstName, MiddleName, LastName).
 - Composition may form a hierarchy where some components are themselves composite.

Example of a Composite Attribute

20



Types of Attributes (2)

21

- Single-valued
 - Each entity can have a single value for this attribute
 - For example: the 'Age' attribute for each EMPLOYEE entity

- Multi-valued
 - An entity may have multiple values for that attribute.
 - For example: Colour of a CAR Entity or PreviousDegrees of a STUDENT.
 - Denoted as {Colour} or {PreviousDegrees}.

Types of Attributes (3)

22

- An attribute can be both composite and multi-valued
- For example, PreviousDegrees of a STUDENT is a composite and multi-valued attribute
 - denoted by {PreviousDegrees (College, Year, Degree, Field)}
 - Multiple PreviousDegrees values can exist
 - Each degree has four subcomponent attributes:
 - College, Year, Degree, Field

Entity Types and Key Attributes (1)


23

- Entities with the same basic attributes are grouped or typed into an **entity type**.
 - For example, the entity type EMPLOYEE and PROJECT.
- An attribute of an entity type for which each entity must always have a unique value is called a **key attribute** of the entity type.
 - For example, SSN of EMPLOYEE.

Entity Types and Key Attributes (2)

24


- A key attribute may be *composite*.
 - Example (from US car ids):
 - VehicleTagNumber is a key of the CAR entity type with components (Number, State).
- An entity type may have more than one key attribute.
 - The CAR entity type may have two keys:
 - VehicleIdentificationNumber (popularly called VIN)
 - VehicleTagNumber (Number, State) or license plate number.
- Each key attribute is underlined in the ER diagram



Displaying an Entity type

25


- In ER diagrams, an entity type is displayed in a rectangular box
- Attributes are displayed in ovals
 - Each attribute is connected to its entity type
 - Components of a composite attribute are connected to the oval representing the composite attribute
 - Each key attribute is underlined
 - Multivalued attributes displayed in double ovals



Entity Type CAR with Two Keys and a Corresponding Entity Set

26

■ Entity type



CAR
Registration (Number, State), Vehicle_id, Make, Model, Year, {Color}

■ Entity set

CAR₁
((ABC 123, TEXAS), TK629, Ford Mustang, convertible, 2004 {red, black})

CAR₂
((ABC 123, NEW YORK), WP9872, Nissan Maxima, 4-door, 2005, {blue})

CAR₃
((VSY 720, TEXAS), TD729, Chrysler LeBaron, 4-door, 2002, {white, blue})

⋮

Entity Set

27

- Each entity type will have a collection of entities stored in the database
 - Called the entity set
- Three CAR entity instances in the entity set for CAR are shown
- Same name (CAR) used to refer to both the entity type and the entity set
- Entity set is the current *state* of the entities of that type that are stored in the database

CAR₁
((ABC 123, TEXAS), TK629, Ford Mustang, convertible, 2004 {red, black})

CAR₂
((ABC 123, NEW YORK), WP9872, Nissan Maxima, 4-door, 2005, {blue})

CAR₃
((VSY 720, TEXAS), TD729, Chrysler LeBaron, 4-door, 2002, {white, blue})

⋮

The COMPANY Database

28

- The company is organised into **DEPARTMENTS**. Each department has a name, number and an employee who manages the department. We keep track of the start date of the department manager. A department may have several locations.
- Each department controls a number of **PROJECTS**. Each project has a unique name, unique number and is located at a single location.
- We store each **EMPLOYEE's** social security number, address, salary, gender and birthdate.
- Each employee works for one department but may work on several projects.
- We keep track of the number of hours per week that an employee currently works on each project.
- We also keep track of the direct supervisor of each employee.
- Each employee may have a number of **DEPENDENTS**.
- For each dependent, we keep track of their name, sex, birthdate, and relationship to the employee.





Initial Design of Entity Types for the COMPANY Database Schema

29

- Based on the requirements, we can identify four initial entity types in the COMPANY database:
 - DEPARTMENT
 - PROJECT
 - EMPLOYEE
 - DEPENDENT
- Their initial design is shown on the following slide
- The initial attributes shown are derived from the requirements description

Initial Design of Entity Types: EMPLOYEE, DEPARTMENT, PROJECT, DEPENDENT

30



Faculty of Natural and Mathematical Sciences

January 2021



Dr Sophia Tsoka

Department of Informatics

4CCS1DBS – Database Systems

Week 2 – Data Modelling Using the Entity-Relationship Model

Topic: Relationships

In this Recoding

32

- Overview of Database Design Process
- Recapping data models
- Entity-Relationship (ER) Model Concepts
 - Entities, Entity Types, Attributes
 - Relationships and Relationship Types
 - Weak Entity Types
 - Constraints and Attributes in Relationship Types
- ER Diagrams - Notation
- ER Diagram for COMPANY Schema

The COMPANY Database

33

- The company is organised into DEPARTMENTS. Each department has a name, number and an employee who manages the department. We keep track of the start date of the department manager. A department may have several locations.
- Each department controls a number of PROJECTs. Each project has a unique name, unique number and is located at a single location.
- We store each EMPLOYEE's social security number, address, salary, gender and birthdate.
- Each employee works for one department but may work on several projects.
- We keep track of the number of hours per week that an employee currently works on each project.
- We also keep track of the direct supervisor of each employee.
- Each employee may have a number of DEPENDENTS.
- For each dependent, we keep track of their name, sex, birthdate, and relationship to the employee.





Initial Design of Entity Types for the COMPANY Database Schema

34

- Based on the requirements, we can identify four initial entity types in the COMPANY database:
 - DEPARTMENT
 - PROJECT
 - EMPLOYEE
 - DEPENDENT
- Their initial design is shown on the following slide
- The initial attributes shown are derived from the requirements description

Initial Design of Entity Types: EMPLOYEE, DEPARTMENT, PROJECT, DEPENDENT

35



Refining the Initial Design by Introducing Relationships

36

- The initial design is typically not complete
- Some aspects in the requirements will be represented as **relationships**
- ER model has three main concepts:
 - Entities (and their entity types and entity sets)
 - Attributes (simple, composite, single-valued, multi-valued)
 - Relationships (and their relationship types and relationship sets)

Relationships and Relationship Types (1)

37

- A **relationship** relates two or more distinct entities with a specific meaning
 - For example:
 - EMPLOYEE John Smith ***works on*** the ProductX PROJECT
 - EMPLOYEE Franklin Wong ***manages*** the Research DEPARTMENT
- Relationships of the same type are grouped or typed into a **relationship type**
 - For example:
 - the WORKS_ON relationship type in which EMPLOYEES and PROJECTs participate
 - or the MANAGES relationship type in which EMPLOYEES and DEPARTMENTS participate
- The degree of a relationship type is the number of participating entity types
 - Both MANAGES and WORKS_ON are *binary* relationships

Relationship Type vs. Relationship Set


38

- Relationship Type:
 - A set of associations among entities
 - The schema description of a relationship
 - Identifies the relationship name and the participating entity types
 - Also identifies certain relationship constraints
- Relationship Set:
 - The current set of relationship instances represented in the database
 - The current *state* of a relationship type

Relationship Type vs. Relationship Set (contd.)

39

- In ER diagrams, we represent the *relationship type* as follows:
 - Diamond-shaped box is used to display a relationship type
 - Connected to the participating entity types via straight lines



COMPANY Database Requirements

40

- The company is organised into DEPARTMENTS. Each department has a name, number and an employee who manages the department. We keep track of the start date of the department manager. A department may have several locations.
- Each department controls a number of PROJECTS. Each project has a unique name, unique number and is located at a single location.
- Each employee works for one department but may work on several projects. We keep track of the number of hours per week that an employee currently works on each project, and the direct supervisor of each employee.
- Each employee may have a number of DEPENDENTS. For each dependent, we keep track of their name, sex, birthdate, and relationship to the employee.

COMPANY Database Requirements

41

- The company is organised into DEPARTMENTS. Each department has a name, number and an employee who **manages** the department. We keep track of the start date of the department manager. A department may have several locations.
- Each department **controls** a number of PROJECTS. Each project has a unique name, unique number and is located at a single location.
- Each employee **works for** one department but may **work on** several projects. We keep track of the number of hours per week that an employee currently works on each project, and the *direct* **supervisor** of each employee.
- Each employee may **have** a number of DEPENDENTS. For each dependent, we keep track of their name, sex, birthdate, and relationship to the employee.

Refining the COMPANY Database Schema by Introducing Relationships


42

- By examining the requirements, six relationship types are identified
- Listed below with their participating entity types:
 - WORKS_FOR (between EMPLOYEE, DEPARTMENT)
 - MANAGES (also between EMPLOYEE, DEPARTMENT)
 - CONTROLS (between DEPARTMENT, PROJECT)
 - WORKS_ON (between EMPLOYEE, PROJECT)
 - SUPERVISION (between EMPLOYEE (as subordinate), EMPLOYEE (as supervisor))
 - DEPENDENTS_OF (between EMPLOYEE, DEPENDENT)
- Most are *binary* relationships (degree of 2), apart from SUPERVISION that is *unary* (degree of 1)

ER DIAGRAM – Relationship Types -

WORKS_FOR, MANAGES, WORKS_ON, CONTROLS, SUPERVISION, DEPENDENTS_OF



43



Discussion on Relationship Types

44


- In the refined design, some *attributes* from the initial entity types are refined into *relationships*:
 - Manager of DEPARTMENT → MANAGES
 - Works_on of EMPLOYEE → WORKS_ON
 - Department of EMPLOYEE → WORKS_FOR



Discussion on Relationship Types (cont'd)

45


- In general, more than one relationship type can exist between the same participating entity types
 - MANAGES and WORKS_FOR are distinct relationship types between EMPLOYEE and DEPARTMENT
 - Different meanings and different relationship instances.



Recursive Relationship Type

46


- A relationship type with the same participating entity type in distinct roles
- Example: the SUPERVISION relationship
- EMPLOYEE participates twice in two distinct roles:
 - supervisor (or boss) role
 - supervisee (or subordinate) role
- Each relationship instance relates two distinct EMPLOYEE entities:
 - One employee in *supervisor* role
 - One employee in *supervisee* role




Displaying a Recursive Relationship

47

- In a recursive relationship type:
 - Both participations are same entity type in different roles
 - For example: SUPERVISION relationships between EMPLOYEE in role of *supervisor* or *boss* and another EMPLOYEE in role of *subordinate* or *worker*
- In figure, first role participation labeled with 'Supervisor' and second role participation labeled with 'Supervisee'
- In ER diagram, need to display role names to distinguish participations




Recursive Relationship Type is: SUPERVISION (participation role names are shown)




Weak Entity Types

49

- An entity that does not have a key attribute
- A weak entity must participate in an identifying relationship type with an *owner* or *identifying* entity type
- Entities are identified by the combination of:
 - The particular entity they are related to in the identifying entity type
 - A partial key: an attribute that can uniquely identify weak entities *that are related to the same owner entity*
- **Example:**
 - DEPENDENT is a *weak entity type*
 - A DEPENDENT entity is identified by the dependent's first name, *and* the specific EMPLOYEE with whom the dependent is related
 - EMPLOYEE is its *identifying entity type* via the identifying relationship type DEPENDENT_OF
 - Name of DEPENDENT is the *partial key*



Recursive Relationship Type is: SUPERVISION (participation role names are shown)



Faculty of Natural and Mathematical Sciences

January 2021



Dr Sophia Tsoka

Department of Informatics

4CCS1DBS – Database Systems

Week 2 – Data Modelling Using the Entity-Relationship Model

Topic: Structural Constraints of Relationships

Week 2 Overview

52

- Overview of Database Design Process
- Recapping data models
- Entity-Relationship (ER) Model Concepts
 - Entities, Entity Types, Attributes
 - Relationships and Relationship Types
 - Weak Entity Types
 - Constraints and Attributes in Relationship Types
- ER Diagrams - Notation
- ER Diagram for COMPANY Schema


The COMPANY Database

53

- The company is organised into **DEPARTMENTS**. Each department has a name, number and an employee who manages the department. We keep track of the start date of the department manager. A department may have several locations.
- Each department controls a number of **PROJECTS**. Each project has a unique name, unique number and is located at a single location.
- Each **EMPLOYEE** works for one department but may work on several projects. We keep track of the number of hours per week that an employee currently works on each project, and the *direct* supervisor of each employee.
- Each employee may have a number of **DEPENDENTS**. For each dependent, we keep track of their name, sex, birthdate, and relationship to the employee.

The COMPANY Database – ER diagram

54



Constraints on Relationships


55

- Structural Constraints on Relationship Types
 - Also known as *ratio constraints*.
 - Cardinality Ratio: specifies *maximum* number of relationship instances that an entity can participate in.
 - One-to-one (1:1)
 - One-to-many (1:N) or Many-to-one (N:1)
 - Many-to-many (M:N)
 - Existence Dependency Constraint: specifies *minimum* participation of an entity in a relationship, i.e. if existence of an entity depends on it being related to another entity via relationship type (also called participation constraint)
 - zero (optional participation, not existence-dependent)
 - one or more (mandatory participation, existence-dependent)

Notation for Constraints on Relationships

56


- Cardinality ratio (of a binary relationship): 1:1, 1:N, N:1, or M:N
 - Shown by placing appropriate numbers on the relationship edges
- Participation constraint (on each participating entity type)
 - **total (called *existence dependency*)**
 - shown by double line
 - **partial**
 - shown by single line



Relationship Instances of the WORKS_FOR Relationship Between EMPLOYEE and DEPARTMENT (N:1)

57


Each *instance of a relationship set* relates *individual participating entities*, one from each participating entity type



Many-to-one (N:1) Relationship

Relationship Instances of the WORKS_ON Relationship Between EMPLOYEE and PROJECT (M:N)

58




Many-to-many (M:N) Relationship

The COMPANY Database – Cardinality Ratios

59

Cardinality Ratio: specifies *maximum* number of relationship instances that an entity can participate in.

- One-to-one (1:1)
- One-to-many (1:N) or Many-to-one (N:1)
- Many-to-many (M:N)




The COMPANY Database – Existence Dependency Constraints

60

Existence Dependency Constraint:
specifies *minimum* participation of an entity type

- Indicates if existence of an entity depends on it being related to another entity via relationship type
 - Zero: optional participation, not existence-dependent
 - One or more: mandatory participation, existence-dependent



Alternative (min, max) Notation for Relationship (1)

61

- Structural Constraints:
 - Specified on each participation of an entity type E in a relationship type R
 - Specifies that each entity e in E participates in at least *min* and at most *max* relationship instances in R
 - Default(no constraint): $\text{min}=0$, $\text{max}=n$ (signifying no limit)
 - Must have $\text{min} \leq \text{max}$, $\text{min} \geq 0$, $\text{max} \geq 1$
 - Derived from the knowledge of mini-world constraints

Alternative (min, max) Notation for Relationship (2)

62

- Examples:
 - A department has exactly one manager and an employee can manage at most one department.
 - Specify (0,1) for participation of EMPLOYEE in MANAGES
 - Specify (1,1) for participation of DEPARTMENT in MANAGES



The (min,max) Notation for Relationship Constraints


63

- Examples:
 - An employee can work for exactly one department but a department can have any number of employees.
 - Specify (1,1) for participation of EMPLOYEE in WORKS_FOR
 - Specify (1,N) for participation of DEPARTMENT in WORKS_FOR



COMPANY ER Schema Diagram using (min, max) notation


64



Displaying a Recursive Relationship

65

- In a recursive relationship type:
 - Both participations are same entity type in different roles.
 - For example: SUPERVISION relationships between EMPLOYEE in role of *supervisor* or *boss* and another EMPLOYEE in role of *subordinate* or *worker*.
- In figure, first role participation labeled with 1 and second role participation labeled with 2.
- In ER diagram, need to display role names to distinguish participations.




1: supervisor role
2: supervisee role

Attributes of Relationship Types

Example: Hours of Relationship WORKS_ON













66

- A relationship type can have attributes:
 - For example, HoursPerWeek of WORKS_ON
 - Its value for each relationship instance describes the number of hours per week that an EMPLOYEE works on a PROJECT.
 - A value of HoursPerWeek depends on a particular (employee, project) combination
 - Most relationship attributes are used with M:N relationships
 - In 1:N relationships, they can be transferred to the entity type on the N-side of the relationship



Summary of Notation for ER Diagrams

67

Symbol	Meaning
	Entity
	Weak Entity
	Relationship
	Identifying Relationship
	Attribute
	Key Attribute
	Multivalued Attribute
	Composite Attribute
	Derived Attribute
	Total Participation of E_2 in R
	Cardinality Ratio 1: N for $E_1:E_2$ in R
	Structural Constraint (min, max) on Participation of E in R

Relationships of Higher Degree

68

- Relationship types of degree 2 are called binary
- Relationship types of degree 3 are called ternary and of degree n are called n -ary
- In general, an n -ary relationship is not equivalent to n binary relationships
- Constraints are harder to specify for higher-degree relationships ($n > 2$) than for binary relationships

Alternative Diagrammatic Notation

69

- ER diagrams is a popular means for displaying database schemas
- Many other notations exist in the literature and in various database design and modeling tools
- UML class diagrams is representative of another way of displaying ER concepts that is used in several commercial design tools
- Please note that this module will only focus on ER diagrams


UML Class Diagrams

70

- Represent *classes* (similar to entity types) as large boxes with three sections:
 - Top section includes entity type (class) name
 - Second section includes attributes
 - Third section includes class operations (operations are not in basic ER model)
- Relationships (called *associations*) represented as lines connecting the classes
 - Other UML terminology also differs from ER terminology
- Used in database design and object-oriented software design
- UML has many other types of diagrams for software design

UML Class Diagram for COMPANY Database Schema

71



Summary of Week 2 Topics

72

- Overview of Database Design Process
- Recapping data models
- Entity-Relationship (ER) Model Concepts
 - Entities, Entity Types, Attributes
 - Relationships and Relationship Types
 - Weak Entity Types
 - Constraints and Attributes in Relationship Types
- ER Diagrams - Notation
- ER Diagram for COMPANY Schema

