

Week 3

FIT5202 Big Data Processing



Week 3 Agenda

- Week 2 Review
- Assignment 1 Briefing
- Join Strategies in Spark
- Joins used in Spark
- Understanding Query Execution Plan and DAG in Spark UI (Demo)



Week 2 Review

- Understanding SparkSession and SparkContext
- Data Partitioning in RDDs
- Parallel Search and RDDs with multiple conditions
- RDDs vs DataFrames
- Partitioning in DataFrames
- Searching and Filtering in DataFrames
- Using SparkSQL With DataFrames.



Solution – Week 2

```
from pyspark.sql.functions import col
bank df = df round
## The functions to filter in dataframes are similar to the functions in RDD. Thus, the steps are:
# 1. Search the records with balance between 1000 and 2000
bank df = bank df.filter(col("balance")>1000)\
            .filter(col("balance")<2000)</pre>
# TODO:
# 2. Also in the same dataframe, search the records with primary or secondary education and age less than 30
# bank df =
#### SOLUTION:
bank df = bank df.where(col("education").isin(["primary", "secondary"])).filter(col("age")<30)</pre>
# TODO:
# 3. Also filter with those who are married
# bank df =
#### SOLUTION:
bank_df = bank_df.filter(bank_df["marital"]=='married')
# TODO:
# 4. Display the previous attributes plus the information of day, month and deposit
# bank df =
#### SOLUTION:
bank df = bank df.select("age", "education", "balance", "day", "month", "deposit")
# 5. Display the records
bank df.show()
```




Joining Strategies By Spark

Why do we need different join strategy?


- 1. Shuffle Sort Merge Join (default)
- Broadcast Hash Join
- 3. Shuffle Hash Join


https://towardsdatascience.com/strategies-of-spark-join-c0e7b4572bcf












Sort-Merge Join

- Data from both tables are shuffled (when no bucketing was done)
- Data are then sorted based on the key and perform sort-merge join on each executer

Most Scalable joining strategy in Spark




https://databricks.com/session_eu19/spark-sql-bucketing-at-facebook



Broadcast Hash

- Smallest table is broadcasted to each node (using broadcast variable)
- 2. Joining then takes place
- 3. Eliminates the shuffling process for bigger dataset.
- Threshold can be Configured using "spark.sql.autoBroadcastJoinThreshold"
- 5. Default is 10 MB




https://henning.kropponline.de/2016/12/11/broadcast-join-with-spark/



Shuffle Hash

1. When both data frames are partitioned using same partitioner. So join keys will fall into the same partition.



https://databricks.com/session/optimizing-apache-spark-sql-joins



When to use which?

- 1. When both datasets are too big: Sort-merge join/ Shuffle-hash join
- 2. When one table is big and another is small: Broadcast Hash Join



Other Core Joins

- INNER
- OUTER
- LEFT
- RIGHT
- LEFT SEMI
- LEFT ANTI



Query Exectuion Plan and DAG Demo



Thank You!

See you next week.