

COMP9120

Week 6: Database Integrity

Semester 1, 2022

Professor Athman Bouguettaya
School of Computer Science



THE UNIVERSITY OF
SYDNEY



Acknowledgement of Country

I would like to acknowledge the Traditional Owners of Australia and recognise their continuing connection to land, water and culture. I am currently on the land of the Darug people and pay my respects to their Elders, past, present and emerging.

I further acknowledge the Traditional Owners of the country on which you are on and pay respects to their Elders, past, present and future.



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of the University of Sydney pursuant to Part VB of the Copyright Act 1968 (**the Act**).

The material in this communication may be subject to copyright under the Act. Any further copying or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.



› Overview of Integrity Constraints

› Static Integrity Constraints

- Domain Constraints
- Key / Referential Constraints
- Semantic Integrity Constraints
- Assertions

› Dynamic Integrity Constraints

- Triggers

› Integrity Constraint (IC):

a condition that must hold true for every instance of a database

- ICs are an integral part of the initial database schema design (through the **create table** command) to ensure the integrity and consistency of the database.
- ICs can be added/updated later (through **alter table *table-name* add constraint** command).
 - When such a command is executed, the system first ensures that the relation satisfies the specified constraint. If it does, the constraint is added to the relation; if not, the command is rejected.
- A **legal** instance of a relation is one that (*eventually*) satisfies all specified ICs.
 - Not *necessarily at all times*.

› Example integrity constraints

- Each student ID must be unique.
- No two lecturers can have the same ID.
- Every school name in the *unit* relation must have a matching school name in the *school* relation.
- For every student, a name must be given.
- The only possible grades are either 'F', 'P', 'C', 'D', or 'H'.
- Valid lecturer titles are 'Associate Lecturer', 'Lecturer', 'Senior Lecturer', 'Associate Professor', or 'Professor'.
- Students can only enrol in the units of study that are currently on offer.
- The sum of all marks in a course cannot be higher than 100.

- › Why do we need to capture integrity constraints:
 - Data consistency (e.g., deleting an employee from the **Employee** table should also result in all corresponding tuples from the **Works-on** relation to be deleted).
 - Stored data is more faithful to the real-world meaning (semantics) of the domain application
 - Avoid data entry errors (e.g., inserting a *grade* into the **Student** table which does not exist).
 - Easier application development and better maintainability because ICs are centrally managed by the DBMS.
 - We do not have to worry about “**how**” integrity constraints are enforced/implemented.

- › ICs are specified as part of the database schema design
 - The database designer is responsible for ensuring that the integrity constraints are not contradicting each other!
 - Could be automated but may introduce unacceptable overhead.
- › ICs are checked when the related parts of the database are modified
 - Can specify when ICs should be checked: after a SQL statement, or at the end of a 'transaction'
 - Transaction: a **group of statements** to be executed atomically
(will later look at "ACID" properties of transactions later in the semester)
- › Possible *reactions* if an IC is violated:
 - Reject database operation
 - Abort of the 'transaction' – rollback operations part of current 'transaction'
 - Execution of "maintenance" operations to make DB legal again

An Informal Introduction to Transaction

- › A group of statements to be executed **atomically**

BEGIN;

A group of SQL statements;

COMMIT;

- › A SQL statement usually starts with the following keywords and ends with a semicolon

- **SELECT** - extracts data from a database
- **UPDATE** - updates data in a database
- **DELETE** - deletes data from a database
- **INSERT INTO** - inserts new data into a database
- **CREATE TABLE** - creates a new table
- **ALTER TABLE** - modifies a table
- **DROP TABLE** - deletes a table

- › Consider an empty table

R(id: integer, name: varchar(8))

- What will be the result of the following transaction?

BEGIN;

INSERT INTO R VALUES(1, 'Adam');

INSERT INTO R VALUES(1, 'Smith');

COMMIT;

› **Static Integrity Constraints**

describe conditions that every *legal instance* of a database must satisfy

- Inserts / deletes / updates that violate ICs are disallowed
- Four kinds:
 - *Domain Constraints*
 - *Key Constraints & Referential Integrity*
 - *Semantic Integrity Constraints*
 - *Assertions*

› **Dynamic Integrity Constraints**

are predicates on database state changes

- *Triggers*

› Overview of Integrity Constraints

› Static Integrity Constraints

- Domain Constraints
- Key / Referential Constraints
- Semantic Integrity Constraints
- Assertions

› Dynamic Integrity Constraints

- Triggers

- › Fields must be of the right data domain
 - always enforced for values inserted in the database
 - Also: queries are tested to ensure that the comparisons make sense.
- › Most simply, each attribute needs to have a *data type*
- › SQL DDL allows domains of attributes to be further restricted in the **CREATE TABLE** statement with the following clauses:
 - **DEFAULT** *default-value*
default value for an attribute if its value is omitted in an insert statement.
 - **NOT NULL**
attribute is not allowed to become NULL
 - **NULL**
the values for an attribute may be NULL (which is the default)

Example of Domain Constraints

CREATE TABLE Student

```
(  
    sid      INTEGER      NOT NULL,  
    name     VARCHAR(20) NOT NULL,  
    semester INTEGER      DEFAULT 1,  
    birthday DATE         NULL,  
    country  VARCHAR(20)  
);
```

Example:

INSERT INTO Student(sid,name) **VALUES** (123,'Peter');

Student				
sid	name	semester	birthday	country
123	Peter	1	null	null

- › Limit the allowed values for an attribute by specifying extra conditions with an in-line check constraint

att-name sql-data-type **CHECK**(*condition*)

- › Examples:

- Gender can be 'male' or 'female'

gender **VARCHAR**(6) **CHECK**(gender **IN** ('male', 'female'))

- Age must be positive

age **INTEGER CHECK**(age ≥ 0)

- › New domains can be created from existing data domains, with their own defaults and restrictions

CREATE DOMAIN domain-name sql-data-type ...

- Example:


```
CREATE DOMAIN Grade CHAR DEFAULT 'P' CHECK(VALUE IN
('F','P','C','D','H'))
```

equivalent to:

```
CREATE TABLE Student (  
  sid      INTEGER      NOT NULL,  
  name     VARCHAR(20) NOT NULL,  
  grade    Grade,  
  birthday DATE  
);
```

```
CREATE TABLE Student (  
  sid      INTEGER      NOT NULL,  
  name     VARCHAR(20) NOT NULL,  
  grade    CHAR DEFAULT 'P' CHECK(grade IN ('F','P','C','D','H')),  
  birthday DATE );
```


- › In SQL, we specify key constraints using the **PRIMARY KEY** and **UNIQUE** clauses:



```
CREATE TABLE Student
(  
  sid    INTEGER PRIMARY KEY,  
  name VARCHAR(20)  
);
```

- › A primary key is automatically **UNIQUE** and **NOT NULL**
 - A relation can have multiple candidate (unique) keys, but only one primary key

- › Composite keys: a key consisting of multiple attributes
 - Must be specified in a separate clause



```
CREATE TABLE Boat
(
  name VARCHAR(20),
  colour VARCHAR(20),
  PRIMARY KEY (name, colour)
);
```

```
CREATE TABLE Boat
(
  name VARCHAR(20) PRIMARY KEY,
  colour VARCHAR(20) PRIMARY KEY
);
```

(The above SQL statement is crossed out with a large red X, indicating it is incorrect.)

- › **Foreign key:** set of attributes in a relation that is used to `refer' to a tuple in a parent/referred relation.
 - Must refer to a **candidate key** of the parent (i.e., referred) relation

- › **Referential Integrity:** for each tuple in the referring relation whose foreign key value is α , there must be a tuple in the referred relation **whose value of the referred attribute** is also α
 - e.g. Enrolled(*sid*: integer, ucode: string, semester: string)
sid is a foreign key referring to Student:
 - If all foreign key constraints are enforced, referential integrity is achieved, i.e., no dangling references

- › Only students listed in the Students relation should be allowed to enrol in Units of study.

```
CREATE TABLE Enrolled
( sid CHAR(5), uos CHAR(8), grade VARCHAR(2),
  PRIMARY KEY (sid,uos),
  FOREIGN KEY (sid) REFERENCES Student,
  FOREIGN KEY (uos) REFERENCES Unitofstudy
);
```

Student

<u>sid</u>	name	age	country
53666	Jones	19	AUS
53650	Smith	21	AUS
54541	Ha Tschi	20	CHN
54672	Loman	20	AUS

Enrolled

<u>sid</u>	<u>uos</u>	grade
53666	COMP5138	CR
53666	INFO4990	CR
53650	COMP5138	P
53666	SOFT4200	D
54221	INFO4990	F

??? Dangling reference

Enforcing Referential Integrity in SQL

- › SQL-92 and SQL-1999 support all 4 options on deletes and updates.
 - Default is **NO ACTION** (delete/update is rejected)
 - **CASCADE** (also delete/update all tuples that refer to deleted/updated tuple)
 - **SET NULL / SET DEFAULT** (sets foreign key value of referencing tuple)

CREATE TABLE Enrolled

```
(  
  -- the sid field default  
  value is 12345  
  sid CHAR(5) DEFAULT 12345,  
  uos CHAR(8),  
  grade VARCHAR(2),
```

PRIMARY KEY (sid,uos),

FOREIGN KEY (sid) **REFERENCES** Student

```
-- the on delete cascade conveys  
  that an enrolled row should be  
  deleted when the student with sid  
  that it refers to is deleted
```

ON DELETE CASCADE

```
-- the on update set default  
  will attempt to update the  
  value of sid to a default value  
  that is specified as the default  
  in this Enrolled schema definition
```

ON UPDATE SET DEFAULT

```
);
```

Short 5 mn break:

please stand up, stretch, and move around



THE UNIVERSITY OF
SYDNEY

Semantic Integrity Constraints (Table Constraints)

› Examples:

- “Total marks are between 0 and 100”
- “Only lecturers of a course can give marks for that course.”

› Use SQL **CHECK** constraints, in-line like before, or as separate named constraints:

CHECK (semantic-condition)

Example of Semantic Integrity Constraints

CREATE TABLE Assessment

```
(  
    sid    INTEGER    REFERENCES Student,  
    uos    VARCHAR(8) REFERENCES UnitOfStudy,  
    mark   INTEGER,  
    CHECK (mark BETWEEN 0 AND 100)  
);
```

› The **CONSTRAINT** clause can be used to name all kinds of integrity constraints

› Example:

```
CREATE TABLE Enrolled
(
  sid    INTEGER,
  uos    VARCHAR(8),
  grade  VARCHAR(2),
  CONSTRAINT FK_sid_enrolled FOREIGN KEY (sid)
                        REFERENCES Student
                        ON DELETE CASCADE,
  CONSTRAINT FK_cid_enrolled FOREIGN KEY (uos)
                        REFERENCES UnitOfStudy
                        ON DELETE CASCADE,
  CONSTRAINT CK_grade_enrolled CHECK(grade IN ('F',...)),
  CONSTRAINT PK_enrolled      PRIMARY KEY (sid,uos)
);
```


› Any constraint - domain, key, foreign-key, semantic - may be declared:

- **NOT DEFERRABLE**

The default. It means that every time a database modification occurs to tuples that a DBMS sees as being related, the constraint is checked immediately afterwards.

- **DEFERRABLE**

Gives the option to wait until a transaction is complete before checking the constraint.

- **INITIALLY DEFERRED** wait until transaction end,
 but allow to dynamically change later by

SET CONSTRAINT name **IMMEDIATE**

- **INITIALLY IMMEDIATE** check immediate,
 but allow to dynamically change later by

SET CONSTRAINT name **DEFERRED**

Example of Deferring Constraint Checking

```
CREATE TABLE UnitOfStudy
```

```
(
```

```
  uos_code    VARCHAR(8),
```

```
  title       VARCHAR(20),
```

```
  lecturer    INTEGER,
```

```
  credit_points INTEGER,
```

```
  CONSTRAINT UoS_PK PRIMARY KEY (uos_code),
```

```
  CONSTRAINT UoS_FK FOREIGN KEY (lecturer)
```

```
    REFERENCES Lecturer DEFERRABLE INITIALLY DEFERRED
```

```
);
```

- › Allows us to insert a new course referencing a lecturer that is not present at the time, but who will be added later *in the same transaction*.
- › Behaviour can be dynamically changed within a transaction with the SQL statement

```
SET CONSTRAINT UoS_FK IMMEDIATE;
```

Add/Modify/Remove Integrity Constraints

- › Integrity constraints can be added, modified (only domain constraints), and removed from an existing schema using **ALTER TABLE** statement

ALTER TABLE table-name constraint-modification

- › where constraint-modification is one of:

ADD CONSTRAINT constraint-name new-constraint

DROP CONSTRAINT constraint-name

RENAME CONSTRAINT old-name **TO** new-name

ALTER COLUMN attribute-name domain-constraint

- › Example (PostgreSQL syntax):

ALTER TABLE Enrolled **ALTER COLUMN** grade **TYPE VARCHAR(3)**,
ALTER COLUMN mark **SET NOT NULL**;

- › What happens if the existing data in a table does not fulfil a newly added constraint?

Then constraint doesn't get created!

e.g. "SQL Error: ORA-02296: cannot enable (USER.) - null values found"

- › The integrity constraints seen so far are associated with a single table
- › Need for more general integrity constraints
 - E.g. integrity constraints over several tables
- › **Assertion**: a predicate expressing a condition that we wish the database to always satisfy.
- › SQL-92 syntax:
CREATE ASSERTION assertion-name **CHECK** (condition)
- › When an assertion is made, the system tests it for validity, and tests it again on every update that may violate it
 - This testing may introduce a significant amount of overhead; hence assertions should be used with great care.

- › The number of boats plus the number of sailors should be less than 100.

```
CREATE TABLE Sailors (  
    sid INTEGER,  
    sname CHAR(10),  
    rating INTEGER,  
    PRIMARY KEY (sid),  
    CHECK (rating >=1 AND rating <=10),  
    CHECK ((SELECT COUNT(s.sid) FROM Sailors s)  
        + (SELECT COUNT(b.bid) FROM Boats b) < 100))  
);
```

```
CREATE ASSERTION smallclub CHECK  
(  
    (SELECT COUNT(s.sid) FROM Sailors s)  
    + (SELECT COUNT(b.bid) FROM Boats b) < 100) );
```

*PostgreSQL does not support ASSERTION

<https://www.postgresql.org/docs/9.2/unsupported-features-sql-standard.html>

*PostgreSQL does not support subquery in CHECK

<https://www.postgresql.org/docs/9.1/sql-createtable.html>



› Overview of Integrity Constraints

› Static Integrity Constraints

- Domain Constraints
- Key / Referential Constraints
- Semantic Integrity Constraints
- Assertions

› Dynamic Integrity Constraints

- Triggers

- › A **trigger** is a section of code that is executed automatically if some specified modifications occur to the database AND a certain condition holds true.

- › A trigger specification consists of three parts:
 ON *event* **IF** *condition* **THEN** *action*
 - *Event* (what activates the trigger)
 - *Condition* (test the condition's truth to determine whether to execute an action)
 - *Action* (what happens if the condition is true)

› Constraint maintenance

- Triggers can be used to maintain foreign-key and semantic constraints; commonly used with ON DELETE and ON UPDATE

› Business rules

- Some dynamic business rules can be encoded as triggers

› Monitoring

- E.g. to react on the insertion of some sensor reading into db



Trigger Example (SQL:1999)

```
CREATE TRIGGER gradeUpgrade
AFTER INSERT OR UPDATE ON Assessment
BEGIN
  UPDATE Enrolled E
    SET grade='P'
  WHERE ( SELECT SUM(mark)
    FROM Assessment A
    WHERE A.sid=E.sid AND
      A.uos=E.uosCode ) >= 50;
END;
```

- › Triggering event can be **INSERT**, **DELETE** or **UPDATE**
- › Triggers on update can be restricted to specific attributes

CREATE TRIGGER overdraft-trigger **AFTER UPDATE OF** balance
ON Account

- › Values of attributes before and after an update can be referenced
 - **REFERENCING OLD ROW AS** name: for deletes and updates
 - **REFERENCING NEW ROW AS** name: for inserts and updates
 - In PostgreSQL: separate **OLD** and **NEW** variable automatically generated with a trigger function (PL/pgsql).

› Granularity

- *Row-level trigger*: A row-level trigger is fired for each row that needs to be updated.
 - *Statement-level trigger*: A statement-level trigger is fired for each SQL statement which may involve a set of rows that need to be updated.
-
- › Statement-level trigger can be more efficient when dealing with SQL statements that update many rows...

- › Example: Assume the following schema
Employee(name, salary)

with *1000 tuples* and a **AFTER INSERT** *trigger* on salary...

- › Now let us give employees a pay raise of 2.5%:

Create Trigger Pay_raise

AFTER INSERT OF salary **ON** Employee

For Each Row

UPDATE Employee **SET** salary = salary*1.025

› Update Costs:

- How many rows are updated?
- How often is a ***row-level*** trigger executed?
- How often is a ***statement-level*** trigger executed?

- › Instead of executing a separate action for each affected row, a single action can be executed for all rows affected by a statement
 - Use **FOR EACH STATEMENT** instead of **FOR EACH ROW**
(actually, the default)
- › Statement-level triggers can be more efficient when dealing with SQL statements that update many rows...



After Trigger Example (statement-level triggers)

*Keep track of salary
averages in the log*

```
CREATE FUNCTION Salary_Average() RETURNS trigger AS $emp_stamp$  
BEGIN  
.....  
END;
```

```
CREATE TRIGGER RecordNewAverage  
AFTER UPDATE OF Salary ON Employee  
FOR EACH STATEMENT  
BEGIN  
    EXECUTE PROCEDURE Salary_Average()  
END;
```

```
CREATE [OR REPLACE] TRIGGER trigger-name
```

```
    ( BEFORE  
      AFTER  
    INSTEAD OF ) ( INSERT  
                  DELETE  
                  UPDATE OF attr ) ON table-name
```

```
    REFERENCEING ( OLD  
                  NEW ) TABLE AS variable-name -- optional
```

```
    FOR EACH ROW
```

```
    WHEN (condition)
```

```
    DECLARE
```

```
        <local variable declarations>
```

```
    BEGIN
```

```
        <PL/SQL block>
```

```
    END;
```

-- optional; otherwise, a statement trigger
-- optional

In PostgreSQL, this
is replaced by a
trigger procedure

- › Use BEFORE triggers
 - Usually for checking integrity constraints
- › Use AFTER triggers
 - Usually for integrity maintenance and update propagation
- › Good overviews:
 - Ramakrishnan – Brief overview Section 5.8, 5.9
 - Kifer/Bernstein/Lewis: “Database Systems - An Application-oriented Approach”, 2nd edition, Chapter 7.
 - Michael v. Mannino: “Database - Design, Application Development and Administration”

- › Capture Integrity Constraints in an SQL Schema
 - Including key constraints, referential integrity, domain constraints and semantic constraints
- › Formulate complex semantic constraints using Assertions
- › Know when to use Assertions, and CHECK constraints
- › Know the semantic of deferring integrity constraints
- › Be able to formulate simple triggers
 - Know the difference between row-level & statement-level triggers

- › Ramakrishnan/Gehrke (3rd edition - the 'Cow' book)
 - **Sections 3.2-3.3 and Sections 5.7-5.9**
 - *Integrity constraints are covered in different parts of the SQL discussion; only brief on triggers*
- › Kifer/Bernstein/Lewis (2nd edition)
 - Sections 3.2.2-3.3 and Chapter 7
 - *Integrity constraints are covered as part of the relational model, but a good dedicated chapter (Chap 7) on triggers*
- › Ullman/Widom (3rd edition)
 - Chapter 7
 - *Has a complete chapter dedicated to both integrity constraints&triggers. Good.*
- › Michael v.Mannino: "Database - Design, Application Development and Administration"
 - *Include a good introduction to triggers.*

› Transaction Management

- Transaction Concept
- Serializability

› Readings:

- **Ramakrishnan/Gehrke (Cow book), Chapter 16**
- Kifer/Bernstein/Lewis book, Chapter 18
- Ullman/Widom, Chapter 6.6 onwards



See you next week!



THE UNIVERSITY OF
SYDNEY