

---

# **decisionengine**

***Release 2.0.1.dev18+gb5e56ab8***

**Fermilab**

**Jul 07, 2022**



## CONTENTS

<b>1</b>	<b>Release Notes</b>	<b>3</b>
<b>2</b>	<b>Install Decision Engine</b>	<b>31</b>
<b>3</b>	<b>Developer Documentation</b>	<b>37</b>
<b>4</b>	<b>Jenkins CI pipeline</b>	<b>39</b>
<b>5</b>	<b>Source code</b>	<b>45</b>
<b>6</b>	<b>Indices and tables</b>	<b>115</b>
	<b>Python Module Index</b>	<b>117</b>
	<b>Index</b>	<b>121</b>



The Decision Engine is a critical component of the HEP Cloud Facility. It provides the functionality of resource scheduling for disparate resource providers, including those which may have a cost or restricted allocation of cycles. This package, `decisionengine`, provides the framework and base classes, the `decisionengine_modules` package contains provider specific implementations of the base classes.



## **RELEASE NOTES**

### **1.1 Release Notes**

HEPCloud's Decision Engine release notes.

The latest release is the designated production release. Decision Engine will support also N-1. New feature development will happen in the development branch and go in the next (N+1) release.

#### **1.1.1 Release 2.0.0**

This release series follows 1.7. A lot started to happen in 1.7.0 and has happened since, so we felt it was proper to change the major version number. We are proud to introduce Decision Engine 2.0.0 to outside users: it provides a friendlier installation procedure and configuration samples to test it on all resources supported by the GlideinWMS Factory, like OSG, some HPC resources and commercial cloud providers.

- New architecture with redesigned source system using Kombu message passing with a Redis backend.
- Token support via DE modules: support for SciToken, WlcgToken (for CE authentication) and HTCCondor Idtokens (for Glideins and Factory communication)
- Separation from the GlideinWMS Frontend. Decision Engine still shares some libraries with GlideinWMS but you don't need any more to install and configure the Frontend.
- Structured logging. Improved python logging and adoption of structured logs format that will increase the semantic content of the messages and ease the export of information for dashboards and Elastic Search.
- Monitoring via Prometheus.
- SQLAlchemy object-relational mapper to increase the testability of DB interactions and to allow different database backends.
- Packaging via setuptools for both decisionengine and decisionengine\_modules: Dependencies are not yet fully listed in the RPMs.
- Added support of CentOS8 (RHEL7 is still out main platform)
- Configuration example using HTC resources via GlideinWMS Factory
- Decision Engine is distributed under the Apache 2.0 license
- We increased our CI tests including also code auto-formatting and license compliance. We introduced integration tests and we are proud of our over 95% unit test coverage.

---

**Note:** SQLAlchemy is required and is now the only datasource backend supported. Upgrading from a different datasource backend (1.6 or earlier were using direct PostgreSQL, 1.7 was supporting both) is a one-way change with

a migration tool. We suggest dropping all objects if you wish to reuse the tablespace. You can preserve a copy of the old database to query historical information.

---

**Note:** Added requirement on the Kombu library and a Redis server. We suggest to [install Redis using a container](#).

---

**Note:** Added requirement on prometheus-client. Prometheus is be used as optional monitoring component.

---

## Issues fixed in this release

- 528: Update license and add copyright notices
- 207: Under certain circumstances the fetch of the “consumes” information fails but the channel does not go offline operations
- 547: Update DE client libs to pgsql-12
- 459: Setuptools issues in decisionengine rpm
- 546: Request CentOS8 Stream support for Decision Engine
- 453: Struct Logging Self test errors with pytest-xdist
- 418: Add auto-formatting of the code
- 134: Yum update on decisionengine rpm doesn’t restart the service
- 480: Request: Make postgresql migration script to migrate from old postgresql schema to new sqlalchemy schema

## Full list of commits since version 1.7.0

685a3a8e: Added changelog file for developers curated list of changes

044f4463: Updated 1.7 and 2.0 release notes, ready for 2.0.0 RC4

19994fb5: Convert timeout program options to floats.

e2055f92: Address Marco’s review comments.

abdf35ad: Restore multiple queues but purge source queue after each publish.

52936cb5: Improve error-handling.

aad20744: Change to multiprocessing.Lock for protecting channel/source workers.

24bbee41: Adjust launching of source workers in attempt to avoid deadlock.

6d13a392: Remove unnecessary (and perhaps harmful) external updating of channel states.

5456f32f: Improve test coverage.

1afabb70: Use service\_actions to disable sources whenever client channels fail.

7f67a172: Various naming and logging adjustments

e6e49184: Adjust de-client –status and add –product-dependencies program option.

a7c1f351: Apply block-while timeout to all channels, not each channel.

3d739ec7: Update ci workflow to include workflow\_dispatch mechanism and to customize artifact file name



c5a05650: Archive unit test logs in case of unit test failure and make them available as artifacts

e94c2abb: Update Python 3.6-compatible pre-commit hooks.

aeb6b974: Update Countdown docstrings.

525eb3a8: Add Countdown class to address global timeout problem.

4c458e0c: Updated release notes for 2.0.0 RC3 (1.7.99.post3)

137b574a: Add a minimal container image more suited to production usage

9d7f6875: Provide de-client `--queue-status` program option.

a7dcc30d: Ensure that channels and sources shared the same queues.

49a316e0: Restore pyupgrade to v2.30, which works on Python 3.6

2ce5ccb6: [pre-commit.ci] pre-commit autoupdate

7bd41851: Print number of pickled bytes of source-produced data.

97aed846: Protect tests from Redis DB/routing-key collisions.

4d3abab7: Flush the Redis DB once the DE server stops.

e36c2150: Remove unnecessary `@pytest.mark.usefixtures(...)` decorations.

30d68610: More unit testing

7850995d: We should have one path where we test without `-v`.

a81a52cc: A simple test to ensure the metrics can run

7547720c: Logger tests are a bit unstable at high parallelization.

56516df7: Add missing test to ensure we can change the channel level twice

abde7d0f: Add missing tests for inherited functions

6522ed37: Note lines we are not testing

de7829a4: Remove the unit test log directory if it got created

28fbd599: pin jsonnet 0.17.0

9c5c827e: Metrics seems to want the channels setup to complete

b8829997: Pin pytest version

b348d6f7: Fix deadlock starting cherrypy metrics server

7697e6c1: Log invocation of random port

9e7e4813: Clarify note on xdist, run more workers

0b495fbf: Leave note to remember to cleanup temp files

ca5ddf6f: Ensure we are calling the cherrypy shutdown methods

e60efe78: Move metrics fixtures to the fixtures file

9c717cc5: Log finished with DB init

55965f9e: Prep the server fixture to permit the metrics webserver

732ff99b: Add a 'ping' method

6117cc95: [pre-commit.ci] pre-commit autoupdate

b5af73ca: More logging about cherrypy state

dfe4278f: Added unlinked release notes for DE 2.0.0  
7d6484ad: Test source shared between two channels.  
ae29d9d1: Test same source types, separate channels  
6095d33f: Test LatestMessages utility.  
dfbf3e06: Separate sources from channels.  
2c10391e: Remove source proxy  
afcc7cff: Add some more logging to try and trace startup state  
dbd49a66: Explicitly pass .coveragerc to pytest.  
e6b03216: Set max retry timeout for sqlite in unit tests.  
51bed3d6: Updated documentation for 1.7.1 release  
3829151f: Allow duplicate keys if their values are the same.  
1ea288e0: [pre-commit.ci] pre-commit autoupdate  
6b6611e5: Use pre-commit.ci rather than local actions  
dedbe4bd: Use local time for structlog timestamp  
461c506e: Make sure de\_std.libsonnet is provided when packaged.  
f93b5963: Update pre-commit hook versions and accommodate python-debian issue.  
bba51609: Reduce number of fixtures.  
a4510cb1: Segment the update for setuptools so it gets cached correctly  
40098f35: Merge pull request #584 from jcpunk/user-pip  
4e1b79a1: Merge pull request #583 from jcpunk/drop-dbutils  
72c8db4a: Recommend using the site user pip dir instead.  
ff604495: Drop unneeded module  
b203e2c4: remove extraneous 'import gc'  
ee2278e7: replace needed import  
4b7dedf2: add licensing info  
e5a56816: add licensing info  
a114abba: add licensing info  
c2d511cd: adding queue logging to de\_logger  
77dd8d5a: Also run checks on backports to 1.7  
7c029578: Updated developers instructions w/ license maintenance via REUSE information  
e66b985d: Fix faulty tests.  
d1a86c57: Set Apache 2.0 license and added REUSE compliance  
e488030e: Ensure that redis is running.  
6c982c11: Report PID for source process.  
3f844ca4: Further flesh out the documentation  
1d750001: Simplifications and rearrangements.

b85dca45: Set state to error for exceptions caught before the thread start.

c4727acb: Changed summaries to histograms in DecisionEngine and TaskManager modules

6fa0bf4d: Added install document and updated the index and development instructions accordingly

e4de391e: Do the build of the wheel as not-root per our requirements

24ba5272: Add a redis server to the CI testing containers

c939a6ed: Address Pat's comments.

1925a7b0: First implementation using Kombu/redis to communicate data from sources to cycles.

82faa271: Don't try to package obsolete sql file

9cbffe94: Drop redundant tests.

ab0de9a5: Drop obsolete raw postgresql interface

164b36d3: Removed unnecessary comment

91f7a76f: Fixed rebase errors

e475fbd5: Added import statement to fix MultiProcessCollector

a409f126: Add no-webserver setting to all DE Test Workers

39cca32e: Moved multiprocess import to metrics to clean up imports.

73762e90: Added --no-webserver to invocations of DEServer

303ee4be: Added \_\_all\_\_ global to control what is exported.

5170224b: Allow for metrics disabling from systemd unit file

2cacef4f: Added check for proper metrics environment and associated unit tests

a637a088: Make webserver operation configurable

b3d6445a: Changed set\_to\_function calls to set() calls for metrics

5dccc7fa: Changed metric names to match prometheus convention

7371c2e8: Added cherrypy requirement

2c511cea: Added metrics to record time to run Modules and DecisionEngine rpc calls

c24d33bc: Renamed prometheus.py to metrics.py

2335134d: Moved TaskManager metrics to util/prometheus.py to avoid duplicates

3c1b790c: Added metrics endpoint to RPC server, changed prometheus to multiprocess mode, and added CherryPy webserver for prometheus metrics

d8972de0: Added unit tests for metrics API

7b0f641b: Add instructions for running the Redis container.

8d0c4919: Block pytest-postgresql 4

d988f1a0: Lower timeout for actions.

4f920dcc: Simplifications in preparation for Kombu.

eb9f4292: Make TaskManager not executable

00c8f6e6: Remove unused files.

dd990d2c: Adding de-logparser, a tool to help parsing Decision Engine semi-structured logs

1da0d61e: Added a comment to help developers with incomplete installation

1cbc7334: Drop testing/support for PyPy

3ba3e8e6: Ignoring E203, whitespace after `:`, since black is adding the whitespace

814669d5: Disable PyPy test that fails for PG\_DE\_DB\_WITH\_SCHEMA fixture value.

8d68c287: Fix debug message

33db6425: Test composite workflows using source proxies and configuration combination.

30951a5b: EL7 doesn't ship with a new enough golang for jsonnetfmt

e72eb3fd: Forbid inheritance from SourceProxy.

e95071fd: Automatically format jsonnet files with jsonnetfmt

355ccd45: Correct tests for python 3.10

64119161: Start testing python 3.10

c1cb8258: add dummy source and test

31b0f30b: Check for duplicate keys after source proxies have been removed.

140a4c47: Fix configuration-combination function signature.

d4a05299: Remove now unnecessary blocking.

1e78a889: Don't run setup.py as root

a71d5b0a: Add error for running server as root

cd345701: Increase coverage in LogicEngine

6c132924: Fix out of sync devel requirements

8bfab003: Start running tests with xdist

aebe7d49: Remove unnecessary conversion to Pandas dataframe.

28919b16: Allow channels to boot in parallel.

c4fc5997: Improve parameter and variable names.

e021419b: Encourage use of automatic nag hook

cc4e469a: Update hooks to latest via *pre-commit autoupgrade*

cef30b69: Further simplify some cases

590bea3f: Add channel-combination facilities.

a4a7938c: Various simplifications recommended by flake8-simple

d5157416: Possible simplification to logging.

81e3d1ee: Fix pylint error on *create\_runner* and *ProcessingState*

2a328c25: Added missing init file to make managers a package

d7f44015: Rework tests for #454

9521d3ce: Add debug statement when default logic-engine configuration is used.

c6dc778c: Unconditionally execute publishers with default configured logic engine.

a48dd7d8: Remove now-unnecessary Python-to-Jsonnet conversion.

a6a81ce7: Run autoformatters

49dac1ec: Setup pre-commit hooks for autoformatters

3800cc2a: Run the code style/standards checks early.

1d42eb0d: TaskManager now inherits from ComponentManager. Also added SourceManager, ChannelManager, and SourceSubscriptionManager files for future integration.

85a16f3b: Python optimised byte code removes assert under some conditions

bed2f5d9: Support latest setuptools\_scm release

## 1.1.2 Release 1.7.2

Same as 1.7.1 release. Done to maintain the same version number as decisionengine\_modules.

## 1.1.3 Release 1.7.1

Patch level (bug fix) release.

### Issues fixed in this release

Bugs fixed

- [DE 522](#): Decision engine log files get split between several different processes with several different versions open: ([fd1e99ce](#))

Enhancements:

- Added dummy sources ([de1536fa](#))

### Full list of commits since version 1.7.0

[606e1e9f](#): Merge pull request #585 from vitodb/fix/1.7/vito\_port\_PR527

[538cf940](#): Merge pull request #586 from HEPCloud/goodenou-patch-remove-gc

[67febfd0](#): remove unnecessary 'import gc'

[9da797d3](#): Improve parameter and variable names.

[55a5b547](#): porting #PR515 into 1.7 (simplifications to logging in Modules) cherry-picked from commit d515741

[fd1e99ce](#): porting #PR563 into 1.7 (adding queue logging into de\_logger)

[c75deef4](#): Also run tests on PRs for backports to 1.7

[de1536fa](#): add dummy source and test

### 1.1.4 Release 1.7.0

This release features:

- New produces-consumes structure using decorators. This will improve the code quality, improving static checks and reducing the lines of code by removing repetitive boilerplates, especially in the modules.
- Added structured logging. Improved python logging and adoption of structured logs format that will increase the semantic content of the messages and ease the export of information for dashboards and Elastic Search.
- Added SQLAlchemy object-relational mapper to increase the testability of DB interactions and to allow different database backends. Switching between datasource backends requires dropping all objects if you wish to reuse the tablespace.
- Packaging via setuptools for both decisionengine and decisionengine\_modules: Dependencies are not yet fully listed in the RPMs.
- A new, optional, configuration parameter called “channel\_name” is available. “channel\_name” is one of the keys in the output dictionary of the structured logging and will be used in the upcoming monitoring. If the variable is not defined in the configuration file, then it is taken from the name of the file, e.g. the job\_classification.jsonnet config file gives a default “channel\_name” value of “job\_classification”.

---

**Note:** Added requirement on SQLAlchemy (for new datasource backend). Non-SQLAlchemy users should ensure the indexes from [13c2f283](#) are in their database.

---

---

**Note:** Added requirement on prometheus-client. Prometheus will be used as optional monitoring component.

---

---

**Note:** The “channel\_name” key in the Source Proxy config dictionaries needs to be changed to “source\_channel”. “channel\_name” is now being used to describe the name of the channel itself, not the name of the channel the Source Proxy is getting information from.

---

### Issues fixed in this release

- [481](#): Channel name should be available to all worker types in TaskManager
- [456](#): Logic engine messages show in the main DE log (1.6.99 post4) prj\_testing
- [458](#): Exception in new SQLAlchemy data source 1.6.99post4
- [455](#): New postgresql exception in 1.6.99post4 (aka Fixed database inconsistency silently ignored in v1.6)
- [456](#): Logic engine messages show in the main DE log (1.6.99 post4)
- [451](#): Transforms executed in wrong order in 1.6.99.post3
- [367](#): Test race conditions bug
- [406](#): Taskmanager doesn't use/honor global log level
- [379](#): Add postgresql.sql to distributed decisionengine rpm
- [329](#): Docker container is missing pylint
- [293](#): Drop requirements.txt setup mode
- [285](#): Unify ProcessingState with Reaper state management code

- 253: Decision engine can sometimes start up at boot time before network name resolution is working ([ae04db5](#))

### Full list of commits since version 1.6.0

f42558df: Updated documentation for 1.7.0 release  
029d118a: Updated release notes for 1.7.0 RC4 (1.6.99.post8)  
0e19c754: fix SP  
810994af: Update release\_notes\_1.7.rst  
fbee95e7: Update release\_notes\_1.7.rst  
68b955b0: Make sure product is a string  
ef7a8b96: Automatically adjust PYTHONPATH for tests  
e292d388: Updated release notes for 1.7.0 RC3 (1.6.99.post7)  
d60b6e4e: new changes for logging with common logger name “channel”  
8cdeb67e: Simplify return expression  
8fb128d3: Ensure file is “flushed” so name is fully established  
7806aa00: Add github CodeQL analysis  
9f09bca9: removed modules/LogicEngine.py and corresponding test  
b9d28fbf: Cleaner check for *Any*  
cc91aa24: Switch to fstring formatting  
7bb5b64f: Just return created value rather than store then return  
f4847fbe: Combine nested *with* blocks  
4ba38bcd: Drop redundant brackets  
bdcfe8c9: By convention, pandas is usually imported as *pd*  
1dd904ff: Use more traditional expression order  
cccd31bc: Unused loop vars should start with *\_*  
c055a5cd: Drop *\_keys* in favor of DB backed *keys*  
e8c689b4: Moved prometheus-client requirement to proper place in list  
5391500d: Added metrics API module  
c2d7835c: Drop unnecessary timeout  
c167fc50: Add tests for de-query-tool entry point  
efabfeb3: Updated release notes for 1.7.0 RC2 (1.6.99.post6)  
b2739c14: moved logging of LogicEngine from decisionengine logger to channel loggers  
0c0532f3: Add locks to help ensure data changes are “atomic”  
ae63c6ee: Use DB generated known keys so it always matches DB state  
b2259e9e: Use public *.keys()* rather than internal implementation  
85b6c3ba: Real world data shows the defaults are fine  
95fb3fdf: Further constrain tablespace

3ebe8619: Finish implementation of get\_datablock  
edbb3568: Add entry point for de-query-tool  
fed95c62: adding logging of importlib imports of modules  
53e62f03: Sometimes pypy times out on the cleanup.  
a44d4bc4: Don't test sqlite on pypy it isn't necessary  
b13aa8a9: Some corrections  
94c14110: Fix missing defines  
5f102095: More detailed testing of datablock  
b6c99021: Make sure our sqlite tests have ForeignKeyConditional support  
6b76ba7c: Fix typo  
6694369d: Ensure dbutils uses transactions  
1df400ae: Fix spaces  
5278fd99: Raise timeout for numpy on pypy  
6d0a1a74: Release notes ready for v1.7.0  
084f74e1: Initial SQLAlchemy Datasource  
3353aa00: Make sure our jsonnet is json syntax valid  
402b1c26: Fix transform-ordering problem.  
49297573: Fix incorrect packaging of tests at top level  
fbfae499: The test\_channel loads data once per second.  
33f9ade1: Rename taskmanager test nodb  
308343e9: Initial modifications for addition of structured logging  
6f337b75: Add missing error message  
23a4b770: Call fixtures in a cleaner manner for xdist  
1f2fe8c4: Add self.config so I can introspect the fixtures later  
689c0020: Add missing *config* attrib test  
d2732816: Best practices are for fixtures to *yield* vs *return*  
acce50a: Seed SQLAlchemy fixtures for later activation  
31002bc5: Help define the fixture interlocking  
0f5fb129: The pandas 1.3.0 doesn't build against PyPy any longer  
a7d18a41: Correctly test datablock construction paths  
9af4c144: the *mock* package was a backport for python2.  
5dda8f8f: Add another constructor test  
9ae9ad13: Make sure if the client says to stop we don't override it  
a581cd2b: run pyupgrade against codebase for python3.6  
09e4e79c: Handle reaper duplicate shutdowns more cleanly  
64d29dc5: Drop pointless cache restore



1c6b2588: Update PyPy to 3.7 for testing  
2bae173e: Increase wait for overloaded test workers, update log messages  
b67c185c: When aborting CI builds cleanup all processes  
6c5d6306: Trim pytest fast functions, add required plugin  
8c63ca6b: note why we're ignoring this line  
2bd4ecbc: Add a syntax check for the toml files  
e2dca404: Sometimes these get stuck  
6d012fab: Add in Jenkinsfile pipeline configuration a timeout at stage level  
baf07973: Add timeout option to block-while/until  
970faf92: Make pre-commit happy  
0cea2285: Fix alignment issue  
5620c65b: List why we aren't checking  
88611d90: Ensure fixtures are cleaned up between invocations  
0ba135d2: Setup blank DB for SQLAlchemy tests and prep fixtures  
3793e674: Setup pre-commit  
9e6d1317: Migrate test\_Reaper to pytest fixtures  
51df43bf: Cleanup a bunch of pointless whitespace  
96e5d069: Fix typo  
9f96f418: Setup datablock to use our paramaterized fixture  
36ebc66c: Add config for LGTM  
c6032e5f: Use topologically sorted transforms to remove some multi-threading.  
e063f82a: Drop pointless comma  
bfd6689e: Begin prepwork for PEP517  
72c5725f: Stub out null source rather than more complex mocking  
3b65e5e2: Push Singleton into its own space  
fb5b177e: Put fixtures in central location  
5ab3cbaa: Add more details to channel startup logs  
afe7f7d7: Add log about what DB we are hitting  
38034b2c: Let the datasource handle the connections internally  
5e03b6fe: Since we are opening an IPv4 socket, just use 127.0.0.1 to check  
cac2bef3: Fix missing version requirements  
3be8f84f: Add line lenght for autoformater  
90e2baad: Protect against inappropriate wait under error condition.  
943a17a7: Fix de-client typo and adjust tests accordingly.  
3b104eba: Set the logs to DEBUG for testing  
4c5564d4: Add another sync method to try and make tests less spotty

66bd81f2: Make sure to encourage updates to tools  
d16f04cc: Put postgresql datasource schema into RPM  
62b97e79: Fix \_\_str\_\_ so it includes all the data  
611ef1f8: Drop pointless lines  
5b9e2fb6: Drop unreachable excepts  
6991f65f: Restore product-name translation required for some source-proxy cases.  
f6258c09: Fixed formatting and updated content  
104a0446: Update index.rst  
2ed61289: Update index.rst  
cb687150: Create release\_notes.rst  
3b57d4a2: Note new requirement  
871af08b: Added 1.7.0 release notes  
ce42b802: improved 1.6 release note  
583c10fb: fixed rst error  
96d4dc1e: Added 1.6.2 release notes, from branch 1.6  
13c2f283: Add some helpful indexes to our default schema  
29c32571: Log as workers are started  
619021c2: One of these tests seems to be spotty, break them out to find which one  
29a2c72d: Run the test in a way that gives us colors  
4e36bfd2: Drop unused table create logic  
5511f69e: Stronger notify state for when we've a lot of watchers.  
b6cc7a46: Test the dataspace abstractions  
e3b1f594: Better messages about our state  
2d2feab9: Drop duplicate tests, leave specifics  
8e737329: Add parameter based datasource api tests  
5c023aa5: Don't do debug logs for flake8, they aren't helpful  
f5d1a12f: Setup list of public exports for dataspace.py  
7158b422: Merge pull request #365 from jcpunk/bad-update-is-error  
cd98cc4a: Update should error out if you try to do it wrongly  
eb7907fe: Add option to set taskmanager datestamp and sample usage  
e124532c: Make sure the fixture uses the production flow  
a8241b6e: Make sure RPM also owns the .egg-info so we don't confuse the namespaces  
da87376e: Ensure the DE server is fully started before running query  
622bfac: Simplify use of our PG fixtures  
df98ecdf: Fixed flake8 issue  
061ff6cf: decisionengine/framework: stop\_channel runs Publisher shutdown methods

3727b80b: Fixup comment to avoid assuming this test uses the DB  
d45aaf6b: Fix script path typo  
a25a4a30: Fix ABC to match our actual usage  
1510b2d1: Address minor linting issues  
945e4b16: Fix missing attribute insert  
5eace9d5: Add note for how to get modules in place  
50a8e268: Add list of packages in the CI env to output  
b9cb197d: Sanity check the home directory  
cd17223c: Have client provide a hint when you ask for no behavior  
95b02365: Fix de-query-tool to support produce/consume model  
e660ca72: Update required versions for bugfixes  
6863cb81: Fix path error  
bb52e8b1: Merge pull request #340 from jcpunk/service-stop  
6d7aba95: Drop obsolete files  
168ae7aa: Name the tests better  
0f60c4e3: Support new produces/consumes/configuration-description infrastructure.  
81912469: Add de-query-tool  
2a26c944: ExecStopPre is not supported on all systemd instances  
67a54d5c: Merge pull request #338 from jcpunk/fix-pytest-postgres  
70ab133f: Fixup use of pytest\_postgresql for version 3.0.0  
f8f4255e: Merge pull request #337 from jcpunk/thread-names  
5f49a4f6: Set names for the various parallel code  
64da77c6: Merge pull request #327 from jcpunk/datablock-expire  
de33a60a: Merge pull request #336 from knoepfel/use-toposort  
31a8a905: Merge pull request #328 from knoepfel/de-class-inference  
410e383d: Merge pull request #331 from jcpunk/reaper-interval-tests  
719ff0c8: Test datablock expire funtions  
e14c49d8: The 'name' parameter is optional.  
7846c9f3: Enable DE class inference based on configuration.  
32ab7e44: Use third-party topological sort.  
01aa8ae6: Merge pull request #325 from jcpunk/channel-tests  
52b48479: Merge pull request #326 from jcpunk/valid-config-tests  
8c4749e7: Merge pull request #330 from jcpunk/pylint-actions  
a37770c9: Ensure validation testing is tested  
d8ab5eb6: Add missing test to ensure the run interval is actually used  
0cd9c42b: Also run pylint for extra sanity checks

c5cf1fff: Ensure our errors error out  
baf01700: Merge pull request #324 from jcpunk/cleanup-trivial-tests  
2a0133aa: Try to cleanup trivial missing coverage  
44e0ad6f: Merge pull request #323 from jcpunk/about-coverage  
d811f617: Merge pull request #322 from knoepfel/fix-fail-on-error  
cb426262: Merge pull request #312 from jcpunk/finish-setuptools  
8f6d407d: Merge pull request #316 from jcpunk/abc-coverage  
4d0676bb: Merge pull request #317 from vitodb/pylint  
d7c43b96: Use regular expression to support fail\_on\_error feature.  
ada66925: add support to run pylint tests  
efb1e57b: Finish migration to pure setuptools  
bc4720cf: We aren't testing 'unversioned' releases  
e4dc35e3: Merge pull request #314 from jcpunk/jsonnet\_syntax  
87e32c22: Merge pull request #294 from jcpunk/move-reaper  
dec85d5e: Merge pull request #319 from jcpunk/task-loop  
4108472a: Merge pull request #320 from jcpunk/container-swig  
920af1c9: Merge pull request #321 from knoepfel/include-init-files  
650dfa7: Don't forget \_\_init\_\_.py files.  
1b412e03: The latest m2crypto seems to need swig now  
a6e3ab1c: Merge pull request #313 from jcpunk/conf-test  
1205636a: Simplify run loop  
30e59dc9: fix test\_client\_with\_no\_server\_verbose unit test for Jenkins CI (#315)  
10384a8c: Move reaper into its own place and reuse state logic  
940584e4: No real way to test abstract base classes  
250c14b1: The *\_validate* function doesn't permit missing 'PRODUCES'  
5ae1ce9f: Make sure syntax error in config names the problem  
b899fa23: Add SourceProxy module test. (#307)  
7b3df14c: Increase coverage of utils (#304)  
ddba2a31: Fix duplicate entry warning (#311)  
915673fa: Test modules minimally (#298)  
bc0c21a9: Some repos may error out, don't let them kill the build (#297)  
924a7047: doc: add 1.6.1 release notes  
b1ab4d31: doc: fix typo  
85e5d714: postgresql: do not print stack trace for low level library (#309)  
255c6415: Setuptools uses entry return value as an error msg (#303)  
2fd8db45: Fix name to match expectations (#305)

9cddb70a: updated release notes

7fe0358e: Error in more clean methods (#300)

84aa506c: Fix a bug in setup.py parsing of requirements. (#301)

a58b61bb: fix typo in release notes

## 1.1.5 Release 1.6.2

Patch level (bug fix) release.

### Issues fixed in this release

Bugs fixed

- DEM 200 (part of it): Invoke correctly channels shutdown: (75eaa90)
- no issue: Use regular expression to support fail\_on\_error feature (1386d20)

Enhancements:

- Improved CI support (e.g. added pylint tests)
- 217: Add option to de-client --print-product to only print the column names in a data block and-or to print one or more records in key/value format. (c4c7681)

### Full list of commits since version 1.6.1

c4c7681: Updated de-query-tool w/ cherry pick of fixes from latest version of PR#332

f964d4b: Fixup use of pytest\_postgresql for version 3.0.0

635ffd1: Also run pylint for extra sanity checks

11676ff: Fixed function w/ the same name

b8278f6: Add de-query-tool

75eaa90: Merge pull request #335 from shreyb/publisher\_shutdown\_from\_1.6

77e3d79: Added set\_to\_shutdown method to TaskManager and accompanying test

1386d20: Merge branch 'knoepfel-fix-fail-on-error' into 1.6

73a18b1: Merge branch 'fix-fail-on-error' of <https://github.com/knoepfel/decisionengine> into knoepfel-fix-fail-on-error

4f49fb7: Merge branch 'jcpunk-finish-setuptools' into 1.6

a5e5d39: Merge branch 'finish-setuptools' of <https://github.com/jcpunk/decisionengine> into jcpunk-finish-setuptools

a1ed252: Merge branch 'vitodb-pylint' into 1.6

c8eddda: Merge branch 'pylint' of <https://github.com/vitodb/decisionengine> into vitodb-pylint Meerging PR#317 to release branch 1.6

d7c43b9: Use regular expression to support fail\_on\_error feature.

ada6692: add support to run pylint tests

efb1e57: Finish migration to pure setuptools

e4dc35e: Merge pull request #314 from jcpunk/jsonnet\_syntax

87e32c2: Merge pull request #294 from jcpunk/move-reaper  
dec85d5: Merge pull request #319 from jcpunk/task-loop  
4108472: Merge pull request #320 from jcpunk/container-swig  
920af1c: Merge pull request #321 from knoepfel/include-init-files  
650dffa: Don't forget \_\_init\_\_.py files.  
1b412e0: The latest m2crypto seems to need swig now  
a6e3ab1: Merge pull request #313 from jcpunk/conf-test  
1205636: Simplify run loop  
de553a7: fix test\_client\_with\_no\_server\_verbose unit test for Jenkins CI (#315)  
30e59dc: fix test\_client\_with\_no\_server\_verbose unit test for Jenkins CI (#315)  
10384a8: Move reaper into its own place and reuse state logic  
250c14b: The `_validate` function doesn't permit missing 'PRODUCES'  
5ae1ce9: Make sure syntax error in config names the problem  
b899fa2: Add SourceProxy module test. (#307)  
7b3df14: Increase coverage of utils (#304)  
ddba2a3: Fix duplicate entry warning (#311)  
915673f: Test modules minimally (#298)  
bc0c21a: Some repos may error out, don't let them kill the build (#297)  
924a704: doc: add 1.6.1 release notes  
b1ab4d3: doc: fix typo  
85e5d71: postgresql: do not print stack trace for low level library (#309)  
255c641: Setuptools uses entry return value as an error msg (#303)  
2fd8db4: Fix name to match expectations (#305)  
9cddb70: updated release notes  
7fe0358: Error in more clean methods (#300)  
84aa506: Fix a bug in setup.py parsing of requirements. (#301)  
a58b61b: fix typo in release notes  
33660bf: fixed a typo[locuser@fermicloud462 decisionengine]

## **1.1.6 Release 1.6.1**

Patch level (bug fix) release.

### Issues fixed in this release

- [306](#) : /etc/decisionengine/decision\_engine.conf as shipped in RPM is wrong format ([de0aef3](#))
- [275](#) : Running de-client --stop-channel <channel> results in KeyError ([59fb44e](#))

### Full list of commits since version 1.6.0

[d7ccd8a](#) : doc: fix typo

[ac48e50](#) : updated release notes

[de0aef3](#) : Fix name to match expectations (#305)

[59fb44e](#) : postgresql: do not print stack trace for low level library (#309) (#310)

[2162bbe](#) : Setuptools uses entry return value as an error msg (#308)

[b0fd9fb](#) : 1.6.0 package backports (#302)

## 1.1.7 Release 1.6.0

In this release:

- The logic engine has been rewritten in pure python. This removes the last C++ dependency the decision engine had. The build system has been updated accordingly.
- Migrated to setuptools package development library. This build system is the standard vanilla python build system provided with the python distribution. Build configurations have been updated and rpm packaging remains the primary distribution method.
- Completed logging implementation.
- Improvements in error handling and code coverage.
- Improvements in Jenkins and GitHub actions CI/CD pipelines.

### Issues fixed in this release

- [44](#) : Logic Engine doesn't handle missing values gracefully ([743effc](#))
- [253](#) : Decision engine can sometimes start up at boot time before network name resolution is working ([ae04db5](#))

### Full list of commits since version 1.5.0

[2551e07](#) : More coverage for de-client (#296)

[dde3945](#) : Make sure actions either complete in time or die (#295)

[381861c](#) : Update Jenkins pipeline configuration (#292)

[eb771f4](#) : Try to cleanup Dockerfile PATH issue (#291)

[780cb56](#) : fix unittest doc

[8680942](#) : update unittest documentation

[8154b24](#) : Fixup sphinx doc (#290)

[5f7e13a](#) : enhancements in logging and error handling in dataspace dir (#283)

3d92725 : Add missing runtime requirement (#286)  
743effc : Allow conversion from errors to false values in logic-engine expressions. (#284)  
124dcab : Inherit version from setuptools\_scm if possible (#287)  
3669803 : added missing "" as line continuation  
761f1d9 : Drop invalid **init.py**  
dc0e71b : migrate to setuptools (#264)  
3b6f1bf : Make reaper reset state when starting from stopped proc (#280)  
b2f9061 : added ISO-8601 format to time in logging. changed name of function for better clarity. (#279)  
0a74fe1 : Improved DE client usage (#281)  
ebf53e3 : Added shutdown method to Publisher class (#278)  
f95ab6d : Address some flake8/black reports (#274)  
1c383b7 : Automatically pull in our settings from about.py (#273)  
e71f186 : logging and error handling enhancements to taskmanager directory (#277)  
7de9ab9 : Increase Reaper log verbosity (#267)  
019d245 : Update actions to follow new best practices (#272)  
b84e847 : Avoid possible sync issues in reaper startup (#271)  
891975f : Remove vestigial C++ files. (#270)  
42e5e1f : enhancements in logging and exception handling in newly added logicengine files (#265)  
38effe6 : Ensure the scheduler has started the thread before returning (#269)  
db54fa1 : Start testing on PyPy with pycpg2cffi (#223)  
cc44058 : Squashed commit of the following: (#263)  
d6548e9 : Enhanced logging in the logicengine directory files (#261)  
c341bf7 : Better match our workflow with codecov (#260)  
1fbe44d : Use 'new' syntax for forward compat (#259)  
2294b0b : Do a limited pin on version requirements (#256)  
bcd470 : Python implementation of logic engine (#246)  
c6721b4 : address comment on RB  
ae04db5 : Add Wants and After (network-online.target) dependency  
1a96b14 : Fix action repodata  
a70cee8 : Move to CodeCov.io  
7b16b4e : Add Wants and Requires dependencies (#258)  
76c3670 : Move to CodeCov.io (#254)  
e7ba013 : Fix action repodata (#255)  
d7e72f2 : revert 3.9 test  
b04154b : added 1.5.0 release notes  
a03da29 : remove 3.9 to see if documentatoin gets generated



### 1.1.8 Release 1.5.0

In this release:

- Introduce data product query interface
- Cleanup of Ligic Engine code
- Improvements in error handling
- Improvements in testing and CI

#### Issues fixed in this release

- [217](#) , [218](#) : Add option to de-client –print-product to only print the column names in a data block and-or to print one or more records in key/value format ([fe7abcf](#))
- [240](#) : Logic Engine call leads to immediate taskmanager segfault exit ([d855aa0](#))
- [239](#) : implement data product browsing interface ([fe9faa9](#))

#### Full list of commits since version 1.4.1

[d66c54b](#) : Add PEP-0396 metadata (#243)

[bfc91a6](#) : More compat between psycpg2/psycpg2cffi (#248)

[f5d31a6](#) : Cleanup Fixture FIXME (#249)

[0dfaf3c](#) : Adding docker documentation (#251)

[4b166a2](#) : Since we are python3 only now, drop python-six compat layer (#252)

[fe7abcf](#) : Add format support to de-client (#217) (#241)

[df5a3d7](#) : Add wheel support for easier testing (#247)

[7de970d](#) : Add place to inject env if need be (#242)

[84e2930](#) : Fix race in test case (#250)

[d855aa0](#) : Fix fact-lookup to support duplicate names in separate rules. (#245)

[51370fb](#) : Resolve fixture ‘quickstart’ issue (#238)

[3ea9129](#) : Move from TravisCI to raw actions (#235)

[fe9faa9](#) : implement data product browsing interface (#239)

[cf0f3c0](#) : Add support to use custom base docker container to run tests (#234)

[d91722f](#) : Compat with psycpg2cffi (#233)

[7d15a8c](#) : Test failing source proxy. (#232)

[b9a4bbb](#) : Add debug logs for which threads are created #176 (#231)

[6e6f4c9](#) : Updated Jenkins configuration documentation (#229)

[2d9fd7b](#) : Log if config passed validation #117 (#230)

[60c46d3](#) : Self-test needs a real namespace to ‘import numpy’ in new python eval (#228)

[a120077](#) : Test that the doc actually builds during CI (#227)

[4b6240a](#) : Extend timeout for coverage combine (#226)

b059696 : Update workflow per changes at github (#225)  
7a71cac : Use newer compilers/runtimes (#224)  
15ffd93 : Add header for strict includes (#222)  
71b141a : Add special PyPy only requirement (#221)  
9dbb932 : Move Python C extension to versioned .so file (#220)  
ea7ade5 : Migrate from boost-python to pybind11 (#215)  
e6b2eae : Add python 3.9 to testing matrix (#219)  
04c8f9c : Add the option to print columns types on de-client (#216)  
8815dc6 : Logic-engine cleanups (#211)  
086d0d5 : fix missing back tick  
54cc084 : modified release notes  
24744cf : Synchronize access to the task managers (#214)  
87a7fda : replde dash with underscore  
743d0fd : try sphinx\_rtd\_theme  
18c7909 : added 1.4.0 release notes  
ff3d491 : force docker pull when building the docker container to make sure to use an updated base layer (#210)

## **1.1.9 Release 1.4.1**

In this release:

- Bug fixes to 1.4.0 release

### **Issues fixed in this release**

- 213 : de-client hangs under certain circumstances in version 1.4 and greater (race condition) ([84ecfe2](#))

### **Full list of commits since version 1.4.0**

9799b9a : update release version to 1.4.1  
84ecfe2 : Synchronize access to the task managers (#214)  
751b6b8 : Address data races; remove need to sleep in unit tests (#205)

## **1.1.10 Release 1.4.0**

In this release:

- Improvements in error handling and client/server interactions
- Added log rotation by time
- Improvements in code coverage

## Issues fixed in this release

- 153 : Have de-client --print-product return different error message if product does not exist (18a950c)
- 171 : yum update on decision engine rpm from python2 to python3 doesn't undo the symlinks (eb85c97)
- 188 : Channel debug info now leaks into startup.log (99d20a5)
- 208 : Error when trying to run reaper in version 1.4.0 (84eccf3)

## Full list of commits since version 1.3

84eccf3 : Fix typo in reaper script. (#209)  
d836abf : next RC  
926944a : Fix coveralls reporting (#198)  
b95c323 : Updating base Dockerfile (#199)  
d302e31 : Help jsonnet, which doesn't understand PosixPath objects. (#204)  
2d791a7 : Test configuration policies. (#197)  
236e27a : Ensure items are returned in a stable order (#202)  
e974f5f : add pylint and pycodestyle (#203)  
fbe7616 : Test task manager (#196)  
686ca80 : require more recent version of pytest-postgresql (#195)  
99d20a5 : Fix double-logging problem. (#192)  
4ce3d17 : A set of fixtures to simplify unit tests (#183)  
65f8052 : Fix typo (#190)  
f3a4be8 : Protect against None workers (#187)  
ec310fb : remove py3 from package name  
7006489 : bump version to 1.4.0rc  
158d835 : decisionengine/framework/modules: Fix SourceProxy retries (#184)  
1356bf1 : Add support to test any branch in Jenkins (#182)  
692fa8e : Add timeout support for unit test on Jenkins (#181)  
e3d6e6a : Updated Jenkins documentation to take into account unit tests timeout parametr (#180)  
2586a3e : Configuration redesign (#168)  
fac984d : Fix error with DBUtils import. Looks like names of modules changed (#175)  
7d661ee : Move postgres-specific implementation to postgres source. (#174)  
eb85c97 : Rpm (#173)  
10fe843 : Adding log rotation by time (#170)  
a8d239b : Various improvements. (#167)  
d9b92ee : Ignore vim's \*.swp files (#166)  
d9f72ef : Fix call to shutdown\_timeout (and add sample entry to config) (#165)  
3161795 : Add drops for items using tables being dropped (#164)

77d186d : Show output of test runtimes in travis (#163)  
81820a4 : Allow server to start with no channels. (#161)  
49879a6 : DE server and client usability improvements (#160)  
de91c4f : Add tests to default and override config (#158)  
14df1f6 : Use python fallback for options (#159)  
ac64a92 : Drop python 2.7 integration tests since we are python3 only (#157)  
d963301 : Update Jenkins pipeline to properly test closing PR (#156)  
64248cb : Merge 'runtime' tests into running channel tests (#150)  
065ad77 : Adding Jenkins pipeline documentation (#155)  
18a950c : fix print-product to report non-existing product as such (#154)  
6493735 : Fix invalid attribute name (#152)  
d953c6a : Remove unnecessary set\_start\_method call (#149)  
c8c9b65 : guarantee that process is killed so test never hang (#147)  
f1542b6 : Channel test (#146)  
7f349a8 : Fix faulty TaskManager state type (#145)  
d50f1c4 : fix logging regression introduced in f5e299969e0611e3480e9fa2782052df... (#142)  
becfa26 : Pass the correct type. (#144)  
1a60daf : DecisionEngine: fix typo (#143)  
9e7b867 : Updating Jenkins pipeline configuration (#140)  
e3a6703 : fix regression introduced in f5e299969e0611e3480e9fa2782052df86d7c4ed (#141)  
4900bc6 : Restore runtime test. (#139)  
0823f3d : Consolidate DE server/client tests into one file. (#138)  
4f84435 : A few more access fixes.  
160cfd1 : Fix task manager state access.  
c00d819 : A few more cleanups.  
ec087e2 : Various cleanups  
a309ffe : Improvements to DE client CLI.

### **1.1.11 Release 1.3.0**

In this release:

- Introduced Jsonnet based configuration system
- Improved logging
- Improved coverage of datasource

## Full list of commits since version 1.2

239e82c : postgresql: improve SQL query (#133)  
668eb1f : Update to make the code compatible with both python and JSON based config files (#129)  
afd8837 : Configuration-manager fixes (#128)  
571e2be : Remove pip installed system python packages  
407d9ed : Update Dockerfile  
1fefc69 : Implement unit tests for datablock.py (#122)  
43c8d7a : Adjust global configuration to include program-option values. (#126)  
2840813 : Switch to Jsonnet configuration system (#125)  
5c4ae0e : logging changes: added config file and command line interface (#124)  
6697f22 : Further config-manager testing and factorizations. (#123)  
fa89fd0 : Insulate multiprocessing test from parent environment. (#120)  
139a537 : Allow empty base directory for log file. (#119)  
f14d40c : Factorize configuration-loading steps. (#118)  
e00afee : Enhance testing and error reporting of ConfigManager (#117)  
c3d1be3 : Python 3 upgrades. (#116)  
e7399af : Header fix (#114)  
0456abf : Adding editor config file, see <https://editorconfig.org/> (#115)  
82112d1 : Dockerfile: fetch osg 3.5 repo rpm (#113)  
97c21b1 : osg version 3.5 (#112)  
33f28a8 : Introduce jsonnet dependency (#110)  
3f8b55e : improve server error handling (#108)  
f15588e : added 1.2.0 release notes  
b433325 : Remove unnecessary 'main' functionality. (#107)

## 1.1.12 Release 1.2.0

In this release:

- Switched to python3
- Improved coverage
- Database data retention : added reaper to remove data older than configurable number of days
- Improved logging

## **decisionengine**

3dfe167 : Jenkins pipeline improvements (#106)  
22a7073 : pull request for review request 137 (#105)  
cafffb2 : Make it possible to run code directly (for tests), and (#100)  
802e98b : replace psycog2 witt psycopg2-binary (#101)  
573ce8f : Jenkins pipeline improvements (#99)  
9d08835 : Run coveralls even under failed state (#97)  
bc1df4b : Add tests for PostgreSQL datasource (#71)  
c1ac391 : Fix missing py-modules.html (#96)  
8dbfdee : Setup gh-pages doc workflow (#94)  
cd4a01a : Doc (#93)  
673080d : set version to 1.2.0 (for now). Supply conf file that corresponds to (#91)  
f912225 : Db (#92)  
dc8b68a : Add reaper to the RPC (#83) (#90)  
29ade91 : adding .Jenkinsfile with Jenkins pipeline configuration (#86)  
c1dfe5c : Don't exclude E1004 from pylint, do exclude line breaks (#89)  
440f949 : Fix varname (#88)  
313d135 : Compress (#87)  
6b8dc4b : Revert "Add reaper to the RPC (#83)"  
dbea8e5 : Update utils.sh so pytest will complete.  
e848316 : Update to postgresql11  
7f4b805 : Add reaper to the RPC (#83)  
0ba2c51 : remove astpp module and dependencies it pulls in (#81)  
6b8eab9 : don't track test coverage of tests (#80)  
0da18ec : made reaper.py executable  
aca24a3 : make reaper.py executable, make symbolic link to it from /usr/bin (#72)  
0202acf : Implementation of data reaper (#70)  
16b6be1 : Simple changes for Python 3 deployment (#69)  
fd2418c : Fix warnings caught by PEP-8 Speaks.  
d16359b : Python 3 (and other) simplifications.  
3c7b6b7 : Only run Github Actions for python3.6 (#68)  
453cbba : Update README.md  
b27ed53 : remove unnecessary (and atually harmful) python shebang (#66)

## decisionengine\_modules

30d928b : clone version 1.2.0 of decisionengine  
ae7c5a6 : Jenkins pipeline improvements (#236)  
310befd : T198 (#235)  
a65886d : Fix import as reported in : <https://github.com/HEPCloud/decisionengin...> (#232)  
93711cc : Run coveralls even if tests fail (#229)  
03d763a : Jenkins pipeline improvements (#230)  
f48d30f : Fix/223 (#228)  
c8aa262 : github ticket 199 (#222)  
0323bda : Address : [https://github.com/HEPCloud/decisionengine\\_modules/issues/224](https://github.com/HEPCloud/decisionengine_modules/issues/224) (#226)  
62e4df6 : Add support to run CI on Jenkins (#221)  
5ab1541 : bump master version to 1.2.0 (for now) (#219)  
bc19c65 : decisionengine\_modules/NERSC: Added retry loop for NERSC API Calls (#220)  
41a50de : Sync up pep8speaks and run\_pylint.sh with decisionengine settings (#218)  
db4634f : silence pylint error (#217)  
1b95141 : Fix whitespace around operator error  
746ea38 : ignore W503  
8a8b5f4 : remove unused variable  
a6668bf : fix PEP8 warnings  
13773ee : address pep8 warnings  
6bea4ca : silence pylint error  
f589895 : Pass sort=True parameter to fix future warning (#215)  
a1d0507 : fixing pep8 warning  
a10bd17 : debugging one import error  
ec501ad : make coveralls.io links work  
deab1a7 : T201 (#204)  
69f2645 : Add coveragerc  
6d8a5f5 : decisionengine\_modules/NERSC: Make Nersc API call backward-compatible with old config (#196)  
a7e0af9 : Only run Github Actions for python3.6 (#24)

### 1.1.13 Release 1.1.0

In this release:

- Fixed. [https://github.com/HEPCloud/decisionengine\\_modules/issues/108](https://github.com/HEPCloud/decisionengine_modules/issues/108) “Supply Postgres script to delete fields in main database before a certain date”
- significant code cleanup and pep8 compliance
- unit test work
- CI (GitHub actions and Travis) is introduced

commits

f894b1d : Skip unittest (#77)

632e64b : Add ipython

f681a79 : Make python 2.7 tests run on 1.1 branch

d6a32c0 : implementation of data reaper (#75)

2ad8614 : Use sparse checkout for first checkout to get .github/actions (#65)

812f032 : Cat output of pytest log Exit pylint entrypoint with the line count of pep8 and pylint logs Deal with (detach from ...) Only tar up (S)RPMS dirs for rpm build.

6b05ec7 : Fix errors reported by run\_pylint (#62)

d9f5b66 : Setup pep8speaks

c3b8ac2 : Run github actions as non-root uid. Install packages in virtualenv and remove system rpms.

ae01f9e : Support Python 3 for Boost Python

579761c : Support Python 3 for Boost Python

044b979 : Remove unnecessary using declarations.

00f6d00 : Add extra header dependency due to Boost Python omission.

24e0795 : Apply clang-format

17c17f9 : Remove JSON dependency.

faa0b22 : Massive cleanup.

07b555f : Updates to Github Actions to allow building with python3.6

fef6c11 : Fix errors when running pylint.sh multiple times

da6f077 : Autopep8 -i fixes

39fe5b3 : TaskManager: fix calling log\_exception with correct number of arguments and minor format changes to reduce PEP8 warnings

17396da : logicengine: get rid of compiler warnings

01dc3d1 : Only track what we need

b609d73 : Configure coveralls (and some minor cleanup)

bd9ed5e : Many C++ cleanups

2a61876 : Add Badges

c864f27 : Do not call pytest fixtures directly.

307db5f : white space fix



882b58f : fix unit tests

1da687c : Replace Boost facilities with C++ STL ones.

5a6e6b1 : Run tests on push

8404245 : Add missing Boost regex library dependency.

ceb5fe7 : Apply clang-format to files that were missed earlier.

3de9940 : Apply clang-format to C++ code.

8a8f560 : Cache venv directory instead

ad017ce : Build private boost for testing

928c64a : Test pip cache

358939a : Adjust CMakeLists.txt files to use correct Python versions

9f0ddb3 : Add pylint github action.

5e6ce4a : Remove more unused C++ files.

63717fe : Setup travis to use new cmake var

74fab2a : Use cmake argument -DPYVER=3.6 to build python3 library <https://fermicloud140.fnal.gov/reviews/r/31/>

843f30c : Minor cleanups per travis-lint

a538cac : Remove unused C++ files.

4c9d125 : Update repo where action is taken from

87fb2d9 : Update rpms installed in docker image. Update entrypoint.sh to use cmake3.

199ee87 : Find python3 libraries using cmake3 from epel rpm Also need to install python3-devel

4c79d2c : Remove unused GNUmakefiles.

94342ee : Add unit test as a Github Action

1a0e102 : more advanced travis.yml

0be413f : Add helper file for pip

7794327 : Make recursive import happy

7005c78 : Add simple target

de8b0fa : python3 compliance: replace string.join() where appropriate, handle UserDict

2662e6c : note required packages

3b87119 : Add missing header includes.

3e79b84 : Remove defunct code and its tests

b1dbe1a : Ensure attribs are defined at **init**

c4ad78a : Correct logger arguments do avoid duplicate string parse

a8dcc67 : Remove unused imports (per pylint)

d3502b5 : Remove obsolete CVS directories.

d744111 : add six module to the list of required modules

0a9b1e8 : Fix class declaration

b83157e : Handle metaclasses

549f33b : Add config for Travis CI

ee71044 : Drop trailing white space

3f82af6 : Python3 forward compatible syntax

28bf291 : Add safe (for python 2.7) python3 compatible syntax

1d1d76f : prepare for python3

## INSTALL DECISION ENGINE

Here are instructions for operators and developers to install the Decision Engine using the distributed RPM packages.

### 2.1 Installing and running HEPCloud's Decision Engine

Decision engine uses a PostgreSQL database back-end and Redis as message broker and cache.

You need to install first PostgreSQL, Redis, and then the Decision engine framework (decisionengine) and install and add the standard channels (decisionengine\_modules).

The following instructions assume a system installation, performed as root. decisionengine will run as the decisionengine user.

#### 2.1.1 Install PostgreSQL

The default postgresql installed on RH7 is 9.2 which is outdated. Suggest to remove it and install 12 instead :

1. Remove old postgresql

```
yum erase -y postgresql*
```

2. Install postgresql 12

```
yum install -y https://download.postgresql.org/pub/repos/yum/reporepms/EL-7-x86_64/  
↳pgdg-redhat-repo-latest.noarch.rpm  
yum install -y postgresql12 postgresql12-server  
# optional, also: postgresql11-devel
```

3. Enable postgresql

```
systemctl enable postgresql-12
```

4. Init the database

```
/usr/pgsql-12/bin/postgresql-12-setup initdb
```

5. edit /var/lib/pgsql/12/data/pg\_hba.conf like the following:

```
[root@fermicloud371 ~]# diff /var/lib/pgsql/12/data/pg_hba.conf~ /var/lib/pgsql/12/  
↳data/pg_hba.conf  
80c80
```

(continues on next page)

(continued from previous page)

```

< local  all          all          peer
---
> local  all          all          trust
82c82
< host   all          all          127.0.0.1/32  ident
---
> host   all          all          127.0.0.1/32  trust
84c84
< host   all          all          ::1/128      ident
---
> host   all          all          ::1/128      trust

```

This is setting the authentication method to *trust*

6. start the database

```
systemctl start postgresql-12
```

7. create decisionengine

```
createdb -U postgres decisionengine
```

The schema and the connection will be created and configured during the Decision engine framework installation.

To use the database you have to add it to the environment:

```
export PG_VERSION=12
export PATH="/usr/pgsql-${PG_VERSION}/bin:~/.local/bin:$PATH"
```

## 2.1.2 Install Redis

Install and start the message broker (Redis) as explained in the redis document

## 2.1.3 Install Decision Engine and the standard modules

1. Prerequisites setup. Make sure that the required yum repositories and some required packages (python3, gcc, ...) are installed and up to date.

```

yum install -y http://ftp.scientificlinux.org/linux/scientific/7x/repos/x86_64/yum-
↳ conf-softwarecollections-2.0-1.el7.noarch.rpm
yum install -y https://dl.fedoraproject.org/pub/epel/epel-release-latest-7.noarch.
↳ rpm
# gcc, swig and make are needed for dependencies (jsonnet)
yum -y install python3 python3-pip python3-setuptools python3-wheel \
    gcc gcc-c++ make \
    python3-devel swig openssl-devel git rpm-build
python3 -m pip install --upgrade --user pip
python3 -m pip install --upgrade --user setuptools wheel setuptools-scm[toml]

# To install the modules you will also need GlideinWMS Frontend, which is in the
↳ OSG repository.
# Assuming the use of OSG 3.5 that supports both GSI and tokens, here is a brief
↳ summary of the setup:

```

(continues on next page)

(continued from previous page)

```

yum install -y yum-priorities
yum install -y https://repo.opensciencegrid.org/osg/3.5/osg-3.5-el7-release-latest.
↳rpm
# HTCondor 8.9.x or 9.x, required by GlideinWMS, is in the osg-upcoming repository.↳
↳It should be enabled to find the dependency
# GlideinWMS 3.9.x is in osg-contrib. The repository should be enabled to find the↳
↳dependency
# In both the following files set: enabled=1
vi /etc/yum.repos.d/osg-upcoming.repo
vi /etc/yum.repos.d/osg-contrib.repo
# Change the Epel repository priority to make sure that comes after the OSG↳
↳repositories, which are 98. Make sure that epel has:
priority=99
vi /etc/yum.repos.d/epel.repo

```

The complete version of the GlideinWMS installation instructions is available here<<https://opensciencegrid.org/docs/other/install-gwms-frontend/>>

## 2. Setup the decision engine yum repositories

```

wget -O /etc/yum.repos.d/ssi-hepcloud.repo http://ssi-rpm.fnal.gov/hep/ssi-hepcloud.
↳repo
wget -O /etc/yum.repos.d/ssi-hepcloud-dev.repo http://ssi-rpm.fnal.gov/hep/ssi-
↳hepcloud-dev.repo

```

## 3. Install the decision engine (add --enablerepo=ssi-hepcloud-dev for the latest development version)

```

yum install decisionengine
yum install decisionengine_modules
# The modules RPM was renamed. For versions <1.7 use instead
yum install decisionengine-standard-library

```

## 4. Not all packages are available as RPM. It is necessary to install directly some Python dependencies. To avoid to pollute the system Python we will install them for the decisionengine user, the user the service is running as. Install the required Python packages (these are taken from setup.py)

```

su decisionengine -s /bin/bash
python3 -m pip install --upgrade pip setuptools wheel --user
python3 /path/to/decisionengine/setup.py develop --user
python3 /path/to/decisionengine/setup.py develop --user --uninstall
python3 /path/to/decisionengine_modules/setup.py develop --user
python3 /path/to/decisionengine_modules/setup.py develop --user --uninstall
exit

```

The commands above should be sufficient. Anyway, here is an explicit list you can use in alternative:

```

su decisionengine -s /bin/bash
# from decisionengine setup.py
python3 -m pip install --user jsonnet tabulate toposort structlog
python3 -m pip install --user wheel DBUtils sqlalchemy
python3 -m pip install --user pandas==1.1.5 numpy==1.19.5
python3 -m pip install --user "psycopg2-binary >= 2.8.6; platform_python_
↳implementation == 'CPython'"

```

(continues on next page)

(continued from previous page)

```
python3 -m pip install --user "psycpg2cffi >= 2.9.0; platform_python_
↳implementation == 'PyPy'"
# from decisionengine_modules setup.py
python3 -m pip install --user boto3 google_auth google-api-python-client
python3 -m pip install --user gcs-oauth2-boto-plugin
# Condor should be already there from the RPM, if not add: python3 -m pip install_
↳htcondor
# bill-calculator-hep is only for versions >= 1.7
python3 -m pip install --user bill-calculator-hep

# The following are additional requirements for v1.6 and earlier
python3 -m pip install --user boto packaging
# This is not in pypi
python3 -m pip install --user https://test-files.pythonhosted.org/packages/f4/a5/
↳17a14b4ef85bc412a0ddb771771de3f562430328b0d83da6091a4131bb26/bill_calculator_hep_
↳mapsacosta-0.0.10-py3-none-any.whl

exit
```

Now you can type `decisionengine --help` to print the help message. To do more you need first to configure Decision Engine.

## 2.1.4 Configure Decision Engine

The default configuration file lives in `/etc/decisionengine/decision_engine.jsonnet`.

A number of defaults are set for you.

### Selecting your datasource

You need a datasource to store in the database the channel's data (datablocks). Each datasource has its own unique schema and cannot be used with a different datasource.

#### The SQLAlchemy Data Source

SQLAlchemy is the default Data Source after v1.7 and is setup with a configuration like:

```
"datasource": {
  "module": "decisionengine.framework.dataspace.datasources.sqlalchemy_ds",
  "name": "SQLAlchemyDS",
  "config": {
    "url": "postgresql://{db_user}:{db_password}@{db_host}:{db_port}/{db_dbname}",
  }
}
```

Any extra keywords you can pass to the `sqlalchemy.engine.Engine` constructor may be set under `config`.

SQLAlchemy will create any tablespace objects it requires automatically.

#### The PostgreSQL Data Source

The postgresql Data Source is the only one supported pre v1.7 and is setup with a config like:

```
"datasource": {
  "module": "decisionengine.framework.dataspace.datasources.postgresql",
  "name": "Postgresql",
  "config": {
    "user": "postgres",
    "blocking": true,
    "host": "localhost",
    "port": 5432,
    "database": "decisionengine",
    "maxconnections": 100,
    "maxcached": 10
  }
}
```

If you use this datasource you must also load the database schema by hand. To load the database schema run:

```
psql -U postgres decisionengine -f /usr/share/doc/decisionengine/datasources/postgresql.
↪sql
```

## 2.1.5 Start decision engine

Start the service

```
systemctl start decisionengine
```

## 2.1.6 Add channels to decision engine

Decision engine decision cycles happen in channels. You can add channels by adding configuration files in `/etc/decisionengine/config.d/` and restarting the decision engine.

Here is a simple test channel configuration. This test channel is using some NOP classes currently defined in the unit tests and not distributed. First, copy these classes from the Git repository:

```
cd YOUR_decisionengine_REPO
# OR download the files from GitHub
mkdir /tmp/derepo
cd /tmp/derepo
wget https://github.com/HEPCloud/decisionengine/archive/refs/heads/master.zip
unzip master.zip
cd decisionengine-master
# Now copy the files
cp -r src/decisionengine/framework/tests /lib/python3.6/site-packages/decisionengine/
↪framework/
```

Then, add the channel by placing this in `/etc/decisionengine/config.d/test_channel.jsonnet`:

```
{
  sources: {
    source1: {
      module: "decisionengine.framework.tests.SourceNOP",
      parameters: {},
    }
  }
}
```

(continues on next page)

(continued from previous page)

```
    schedule: 1,
  },
},
transforms: {
  transform1: {
    module: "decisionengine.framework.tests.TransformNOP",
    parameters: {},
    schedule: 1
  }
},
logicengines: {
  le1: {
    module: "decisionengine.framework.logicengine.LogicEngine",
    parameters: {
      facts: {
        pass_all: "True"
      },
      rules: {
        r1: {
          expression: 'pass_all',
          actions: ['publisher1']
        }
      }
    }
  }
},
publishers: {
  publisher1: {
    module: "decisionengine.framework.tests.PublisherNOP",
    parameters: {}
  }
}
}
```

Finally, restart decision engine to start the new channel:

```
systemctl restart decisionengine
```

de-client --status should show the active test channel



## DEVELOPER DOCUMENTATION

The developer documentation is in the [GitHub Wiki](#)

Instructions to build the package, or to run unit tests and other CI tests, and to install decisionengine are in the [GitHub Wiki](#) as well.



## JENKINS CI PIPELINE

### 4.1 Decisionengine CI with Jenkins pipeline

Jenkins dashboard with Decisionengine framework CI results is available [here](#).

A CI build is triggered any time a PR is created/closed or a commit is made to an existing PR. There are also *nightly CI builds* to test a list of predefined branches.

The Jenkins pipeline runs *pylint* and *unit\_tests* test suites alongside the *rpmbuild* stage.

The Jenkins dashboard looks like this:

Jenkins > CI > decisionengine\_pipeline >

[Back to Dashboard](#)  
[Status](#)  
[Changes](#)  
[Build with Parameters](#)  
[Delete Pipeline](#)  
[Configure](#)  
[Full Stage View](#)  
[GitHub](#)  
[Job Config History](#)  
[Rename](#)  
[GitHub PR](#)  
[Pipeline Syntax](#)  
[GitHub PR Polling Log](#)  
[Set Next Build Number](#)

## Pipeline decisionengine\_pipeline

DE pipeline

**Last Successful Artifacts**

mail.results	2.04 KB	<a href="#">view</a>
pep8.merge150.log	0 B	<a href="#">view</a>
pylint.merge150.log	0 B	<a href="#">view</a>
pytest.log	7.89 KB	<a href="#">view</a>
results.merge150.log	5.16 KB	<a href="#">view</a>
rpmbuild.tar	1.37 MB	<a href="#">view</a>

**Recent Changes**

### Stage View

Average stage times:  
(Average full run time: ~27min 25s)

	Declarative: Checkout SCM	DE tests	pylint	unit_tests	rpmbuild
	1s	51ms	15min 17s	13min 24s	9min 44s
319#PR#150 Sep 02 17:00 No Changes	602ms	49ms	12min 45s	13min 49s failed	6min 20s
318#PR#150 Sep 02 16:36 No Changes	617ms	49ms	27min 5s	23min 43s	19min 15s
317#PR#150 Sep 02 16:25 No Changes	1s	54ms	21min 14s	20min 1s	15min 5s
316#PR#150 Sep 02 16:23 No Changes	1s	54ms	21min 4s	18min 41s	14min 36s
315#PR#150 Sep 02 16:16 No Changes	2s	57ms	22min 32s	19min 24s	14min 31s
314#PR#150 Sep 02 16:10 No Changes	921ms	55ms	16min 43s	14min 16s	7min 23s
313#PR#150 Sep 02 16:08 4 commits	789ms	42ms	16min 56s	14min 11s	8min 17s

**Build History** [trend](#)


find


- 319#PR#150 Sep 2, 2020 5:00 PM [#150](#)
- 318#PR#150 Sep 2, 2020 4:36 PM [#150](#)
- 317#PR#150 Sep 2, 2020 4:25 PM [#150](#)
- 316#PR#150 Sep 2, 2020 4:23 PM [#150](#)
- 315#PR#150 Sep 2, 2020 4:16 PM [#150](#)
- 314#PR#150 Sep 2, 2020 4:10 PM [#150](#)
- 313#PR#150 Sep 2, 2020 4:08 PM [#150](#)
- 312#PR#149 Sep 2, 2020 3:38 PM [#149](#)
- 311#PR#149 Sep 2, 2020 3:31 PM [#149](#)
- 310#PR#149 Sep 2, 2020 3:23 PM [#149](#)
- 309#PR#147 Sep 2, 2020 12:42 PM [#147](#)


On the bottom left side there is the list of recent CI builds that are named after the PR or the branch tested.

On the bottom right side the dashboard shows for each CI build detailed status for each test suite.

Hovering the mouse over the *status box* for each CI build stage, a tool-tip with a button to access log details shows up.

Next to the build number the symbol  gives access to a menu with the list of artifacts stored for that build. Those artifacts include logs and the tarball with RPMs.

From the panel on the left side it is possible to access the PR on GitHub by clicking on the PR icon that looks like this  [#142](#).

On occasion it could be useful to trigger a manual CI build to test a branch on the official DE GitHub repository or on the user fork. For this purpose, on the top left panel the user can click on the  **Build with Parameters** button, and this panel shows up

# Pipeline decisionengine\_pipeline

This build requires parameters:

DOCKER_IMAGE	<input type="text" value="vitodb/decision-engine-ci:jenkins"/>
	Docker image name to use. Default is: vitodb/decision-engine-ci:jenkins
DE_REPO	<input type="text" value="https://github.com/HEPCloud/decisionengine/"/>
	Decisionengine repo. Default is: https://github.com/HEPCloud/decisionengine/
BRANCH	<input type="text" value="master"/>
	Branch to test. Default is: master
PYTEST_TIMEOUT	<input type="text" value="300"/>
	Timeout in seconds for unit_tests (it applies to individual unit test) Default is: 300

Build

the user can modify these parameters to customize what code to test with the CI build.

The *DE\_REPO* parameter can point to the user fork or to the main repository.

The *BRANCH* parameter can point to the desired branch to test.

The *PYTEST\_TIMEOUT* parameter is the timeout in seconds for *unit\_tests*.

When ready, by clicking on the *Build* button, the CI build will start.

The [pipeline configuration](#) is part of the decisionengine repo.

### 4.1.1 Nightly CI build configuration

The nightly CI build for Decisionengine framework uses this [Jenkins project](#) that triggers a CI build using the Jenkins pipeline described above to test a list of predefined branches.

**Jenkins** ▸ **CI** ▸ **decisionengine\_ci** ▸

Back to Dashboard

Status

Changes

Workspace

Build Now

Configure

Delete Multi-configuration project

Rebuild Last

Job Config History

Rename

Set Next Build Number

## Project decisionengine\_ci

Decision Engine CI running inside dedicated docker container

## Configurations

BRANCH=master BRANCH=1.4

## Subprojects

### Static

- decisionengine\_modules\_pipeline(non-blocking)
- decisionengine\_pipeline(non-blocking)

## Permalinks


- Last build (#295), 7 hr 6 min ago
- Last stable build (#295), 7 hr 6 min ago
- Last successful build (#295), 7 hr 6 min ago
- Last completed build (#295), 7 hr 6 min ago

**Build History** [trend](#)

find

<a href="#">#295</a>	<a href="#">Nov 19, 2020 2:23 AM</a>
<a href="#">#294</a>	<a href="#">Nov 18, 2020 2:23 AM</a>
<a href="#">#293</a>	<a href="#">Nov 17, 2020 2:23 AM</a>

Branches to test are defined using the project matrix as shown in the picture below. Each branch in the list (here *master* and *1.4*) spawns an independent CI build.




The screenshot shows the Jenkins Configuration Matrix tab. The 'User-defined Axis' section is expanded, showing a 'Name' field with the value 'BRANCH' and a 'Values' field with the value 'master 1.4'. There is a red 'X' icon in the top right corner of the axis section and a blue question mark icon in the bottom right corner of the values field.

In the *Build* section of the configuration it is set the list of Jenkins subprojects to be triggered, in this case we have *decisionengine\_pipeline* and *decisionengine\_modules\_pipeline*.

The *Parameters* text box is used to override parameters of each Jenkins subproject with a custom value.

In total this Jenkins project triggers 4 CI builds, i.e. 2 branches X 2 Jenkins subprojects.



The screenshot shows the Jenkins Build tab. The 'Trigger/call builds on other projects' section is expanded, showing 'Projects to build' as 'decisionengine\_pipeline,decisionengine\_modules\_pipeline' and a checkbox for 'Block until the triggered projects finish their builds'. Below this, the 'Predefined parameters' section is expanded, showing 'Parameters' as 'BRANCH=\${BRANCH}'. There are red 'X' icons in the top right corner of the 'Trigger/call builds on other projects' section and the 'Predefined parameters' section, and blue question mark icons in the bottom right corner of the 'Projects to build' and 'Parameters' fields.

Finally the *Build Triggers* section is used to setup the schedule for the periodic build, in this case it is scheduled to run at about 2 AM.

Jenkins will choose the actual time depending on the actual load on the system.

General

Advanced Project Options

Source Code Management

Build Triggers

Configuration Matrix

Build Environment

Build

Post-build Actions

Build Triggers

☐ Trigger builds remotely (e.g., from scripts)

☐ Build after other projects are built

☒ Build periodically

Schedule

H 2 \* \* \*

Would last have run at Wednesday, November 4, 2020 2:23:53 AM CST;  
would next run at Thursday, November 5, 2020 2:23:53 AM CST.

?

?

?

?



## SOURCE CODE

### 5.1 Welcome to decisionengine's documentation!

#### 5.1.1 decisionengine package

##### Subpackages

`decisionengine.framework` package

##### Subpackages

`decisionengine.framework.config` package

##### Subpackages

`decisionengine.framework.config.tests` package

##### Submodules

`decisionengine.framework.config.tests.test_config` module

`decisionengine.framework.config.tests.test_config._channel_config_dir`(*relative\_dir*)

`decisionengine.framework.config.tests.test_config._global_config_file`(*relative\_filename*)

`decisionengine.framework.config.tests.test_config.load`()

`decisionengine.framework.config.tests.test_config.test_channel_empty_config`(*load*, *caplog*)

`decisionengine.framework.config.tests.test_config.test_channel_empty_dictionary`(*load*,  
*caplog*)

`decisionengine.framework.config.tests.test_config.test_channel_invalid_modules_list`(*load*,  
*caplog*)

`decisionengine.framework.config.tests.test_config.test_channel_invalid_modules_no_keys`(*load*,  
*caplog*)

```
decisionengine.framework.config.tests.test_config.test_channel_invalid_modules_string(load,
                                                                                       caplog)
decisionengine.framework.config.tests.test_config.test_channel_loading(caplog)
decisionengine.framework.config.tests.test_config.test_channel_module_missing_all(load,
                                                                                   caplog)
decisionengine.framework.config.tests.test_config.test_channel_module_missing_module(load,
                                                                                   caplog)
decisionengine.framework.config.tests.test_config.test_channel_module_missing_parameters(load,
                                                                                       caplog)
decisionengine.framework.config.tests.test_config.test_channel_names(load)
decisionengine.framework.config.tests.test_config.test_channel_no_config_files(load)
decisionengine.framework.config.tests.test_config.test_channel_no_modules(load)
decisionengine.framework.config.tests.test_config.test_empty_config(load)
decisionengine.framework.config.tests.test_config.test_minimal_jsonnet_right_extension(load,
                                                                                       cap-
                                                                                       sys)
decisionengine.framework.config.tests.test_config.test_minimal_jsonnet_wrong_extension(load,
                                                                                       cap-
                                                                                       sys)
decisionengine.framework.config.tests.test_config.test_syntax_error_in_config_names_bad_file(load)
decisionengine.framework.config.tests.test_config.test_valid_but_empty_config(load)
```

#### **decisionengine.framework.config.tests.test\_de\_std module**

```
decisionengine.framework.config.tests.test_de_std.config(basename, jpathdirs=None)
decisionengine.framework.config.tests.test_de_std.test_allow_duplicate_keys_same_values()
decisionengine.framework.config.tests.test_de_std.test_allow_duplicate_source_proxy_keys()
decisionengine.framework.config.tests.test_de_std.test_combine_one_level()
decisionengine.framework.config.tests.test_de_std.test_combine_one_level_skip_proxies()
decisionengine.framework.config.tests.test_de_std.test_error_on_duplicate_keys()
decisionengine.framework.config.tests.test_de_std.test_jpath()
```

## decisionengine.framework.config.tests.test\_policies module

decisionengine.framework.config.tests.test\_policies.**test\_channel\_config\_dir**(*tmp\_path*,  
*monkeypatch*)

decisionengine.framework.config.tests.test\_policies.**test\_global\_config\_dir**(*tmp\_path*,  
*monkeypatch*)

decisionengine.framework.config.tests.test\_policies.**test\_global\_config\_file**(*tmp\_path*,  
*monkeypatch*)

decisionengine.framework.config.tests.test\_policies.**test\_valid\_dir**(*tmp\_path*)

## Module contents

### Submodules

## decisionengine.framework.config.ChannelConfigHandler module

Manager of channel configurations.

The ChannelConfigHandler manages only channel configurations and not the global decision-engine configuration. It is responsible for loading channel configuration files and validating that the channels have the correct configuration artifacts.

**class** decisionengine.framework.config.ChannelConfigHandler.**ChannelConfigHandler**(*global\_config*,  
*chan-*  
*nel\_config\_dir*)

Bases: object

**\_load\_channel**(*channel\_name*, *path*)

**get\_channels**()

**load\_all\_channels**()

Load all channel configurations inside the stored channel-configuration directory.

Any cached configurations will be dropped prior to reloading.

**load\_channel**(*channel\_name*)

Load a single configuration for a channel with the supplied name.

The behavior is to read a configuration file whose path is:

<cached channel config. dir>/{channel\_name}.jsonnet

where the cached channel-configuration directory was stored whenever the ChannelConfigHandler object was created, and {channel\_name} is the value of the supplied method argument.

**print\_channel\_config**(*channel*)

decisionengine.framework.config.ChannelConfigHandler.**\_check\_keys**(*channel\_conf\_dict*)

check that channel config has mandatory keys :type data: dict

decisionengine.framework.config.ChannelConfigHandler.**\_make\_de\_logger**(*global\_config*)

## decisionengine.framework.config.ValidConfig module

ValidConfig represents a valid JSON document.

The decision engine requires each of its configuration files to be valid JSON. This is achieved by either supplying a valid Jsonnet or JSON document upfront.

Vetting of a file for JSON validity happens upon construction of a ‘ValidConfig’ object. A fully constructed ‘ValidConfig’ object thus corresponds to a valid JSON document.

**class** decisionengine.framework.config.ValidConfig.ValidConfig(filename, jpathdirs=None)

Bases: UserDict

ValidConfig represents a valid JSON configuration in the form of a dictionary.

In addition to the normal dictionary operations, users may call ‘dump()’ to print out in a string form the JSON configuration.

**\_abc\_impl** = <\_abc.\_abc\_data object>

**dump()**

Print dictionary data to a valid JSON string.

decisionengine.framework.config.ValidConfig.\_config\_from\_file(config\_file, jpaths=None)

## decisionengine.framework.config.policies module

Decision-engine default configuration policies.

For the decision-engine process, the configuration policies are:

- The global configuration file must be named ‘decision\_engine.jsonnet’ and it must reside in (a) a directory that can be accessed through the ‘CONFIG\_PATH’ environment variable, or (b) the /etc/decisionengine directory.
- All channel configurations must reside in (a) a directory accessible through the ‘CHANNEL\_CONFIG\_PATH’ environment variable, or (b) a ‘config.d’ subdirectory of the /etc/decisionengine directory.

The utilities provided in this module provide simple means of accessing the configuration artifacts according to the policies listed above. Please consult the documentation for each function below for more detailed information.

decisionengine.framework.config.policies.channel\_config\_dir(parent\_dir=None)

Retrieve the channel configuration directory as a pathlib.Path object.

This function returns a path object according to the following precedence rules:

1. If the ‘parent\_dir’ argument is provided, the returned path object will correspond to ‘{parent\_dir}/config.d’.
2. If the ‘CHANNEL\_CONFIG\_PATH’ environment variable has been set, the returned path object will correspond to ‘{CHANNEL\_CONFIG\_PATH}’.
3. If neither 1 or 2 apply, the returned path object corresponds to ‘{global\_config\_dir()}/config.d’ (see documentation for ‘global\_config\_dir()’).

Regardless of the precedence rule used, the returned path object must be a valid directory or an exception will be raised—i.e. if the ‘parent\_dir’ argument is supplied, and the resulting path object is not a valid directory, the function will exit with an exception and not attempt rule 2 or 3.

`decisionengine.framework.config.policies.global_config_dir()`

Retrieve global configuration dir as `pathlib.Path` object.

This is the directory that houses the ‘decision\_engine.jsonnet’ global configuration file.

This function checks that the ‘CONFIG\_PATH’ variable has been set or will use /etc/decisionengine otherwise. If the path exists as a directory, then the directory path is returned as a string; otherwise an exception is raised.

`decisionengine.framework.config.policies.global_config_file(parent_dir=None)`

Return the `pathlib.Path` object corresponding to the global configuration.

If supplied, the ‘parent\_dir’ is assumed to be the full path corresponding to a directory containing the ‘decision\_engine.jsonnet’ file. If not provided, the global configuration directory is determined based on the behavior of the ‘global\_config\_dir()’ function.

An exception is raised if no ‘decision\_engine.jsonnet’ file is found.

`decisionengine.framework.config.policies.valid_dir(path, scope)`

Throws if the supplied path object is not a directory, otherwise returns the path object.

## Module contents

### decisionengine.framework.dataspace package

#### Subpackages

#### decisionengine.framework.dataspace.datasources package

#### Subpackages

#### decisionengine.framework.dataspace.datasources.sqlalchemy\_ds package

#### Submodules

#### decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.datasource\_api module

The datasource layer for our abstraction

**class** `decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource_api.SQLAlchemyDS(config_dict)`

Bases: `DataSource`

A DecisionEngine data source via the SQL Alchemy ORM

```
{
    "dataspace": {
        "datasource": {
            "module": "decisionengine.framework.dataspace.datasources.sqlalchemy_ds",    "name":
            "SQLAlchemyDS", "params": {
                "pool_size": 5, "max_overflow": 10, "timeout": 30,
                # url is mandatory, but any engine keyword is accepted here.    "url": "di-
                alect[+driver]://user:password@host/dbname"
```

```
    }  
  }  
}
```

Exceptions should be caught and logged by the caller.

**\_abc\_impl** = <\_abc.\_abc\_data object>

**close()**

Close all connections to the database

**Returns**

None

**connect()**

Create a pool of database connections

**Returns**

None

**create\_tables()**

Create database tables

**Returns**

None

**delete\_data\_older\_than(days)**

Delete data older than interval

**Parameters**

**days** (*int*) – remove data older than this many days

**Returns**

None

**duplicate\_datablock(taskmanager\_id, generation\_id, new\_generation\_id)**

For the given taskmanager\_id, make a copy of the datablock with given generation\_id, set the generation\_id for the datablock copy

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to clone
- **new\_generation\_id** (*int*) – generation id to create

**Returns**

None

**get\_datablock(taskmanager\_id, generation\_id)**

Return the entire datablock from the dataproduct table for the given taskmanager\_id, generation\_id

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to locate

**Returns**

with all set keys and their associated values

**Return type**

dict

**get\_dataproduct**(*taskmanager\_id*, *generation\_id*, *key*)

Return the data from the dataproduct table for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to locate
- **key** (*str*) – key for the value

**Returns**

The possibly binary value stored earlier

**Return type**

obj

**get\_dataproducts**(*taskmanager\_id*, *key=None*)

Return list of all data products associated with with taskmanager\_id

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **key** (*str*) – key for the value

**Returns**

each element is the matching row as a dict()

**Return type**

tuple

**get\_header**(*taskmanager\_id*, *generation\_id*, *key*)

Return the header from the header table for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to locate
- **key** (*str*) – key for the value

**Returns****fields in order are:**

taskmanager.taskmanager\_id, header.taskmanager\_id, header.generation\_id,  
header.key, header.create\_time, header.expiration\_time, header.scheduled\_create\_time,  
header.creator, header.schema\_id

**Return type**

tuple

**get\_last\_generation\_id**(*taskmanager\_name*, *taskmanager\_id=None*)

Return last generation id for current task manager or taskmanager w/ task\_manager\_id.

**Parameters**

- **taskmanager\_name** (*str*) – name of taskmanager to retrieve
- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve

**Returns**

the largest generation stored within the database

**Return type**

int

**get\_metadata**(*taskmanager\_id*, *generation\_id*, *key*)

Return the metadata from the metadata table for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to locate
- **key** (*str*) – key for the value

**Returns****fields in order are:**

taskmanager.taskmanager\_id, metadata.taskmanager\_id, metadata.generation\_id, metadata.key, metadata.state, metadata.generation\_time, metadata.missed\_update\_count

**Return type**

tuple

**get\_schema**(*table=None*)

Given the table name return it's schema

**get\_taskmanager**(*taskmanager\_name*, *taskmanager\_id=None*)

Find the task manager by name/uuid in the database get back the primary key.

If multiples match, find highest primary key.

**Parameters**

- **taskmanager\_name** (*str*) – name of taskmanager to retrieve
- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve

**Returns**

the matching row, column names as keys

**Return type**

dict

**get\_taskmanagers**(*taskmanager\_name=None*, *start\_time=None*, *end\_time=None*)

Find taskmanagers that meet our search

**Parameters**

- **taskmanager\_name** (*str*) – name of taskmanager to retrieve
- **start\_time** (*datetime*) – Datetime to confine against
- **end\_time** (*datetime*) – Datetime to confine against

**Returns**

each element is a dict() matching row, column names as keys

**Return type**

list



**insert**(*taskmanager\_id, generation\_id, key, value, header, metadata*)

Insert data into respective tables for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to create
- **key** (*str*) – key for the value
- **value** (*obj*) – Value can be an object or dict or a binary
- **header** ([datablock.Header](#)) – Header for the value
- **metadata** ([datablock.Metadata](#)) – Metadata for the value

**Returns**

None

**reset\_connections**()

Reset the connection to the database. So long as self.engine isn't undef, the engine can still make new connections if new db actions happen. It just wont have any open at this time.

**Returns**

None

**store\_taskmanager**(*name, taskmanager\_id, timestamp=None*)

Store TaskManager in database

**Parameters**

- **name** (*str*) – name of taskmanager to retrieve
- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **timestamp** (*datetime*) – datetime of created object, defaults to 'now'

**Returns**

the primary key of the row in the database

**Return type**

int

**update**(*taskmanager\_id, generation\_id, key, value, header, metadata*)

Update the data in respective tables for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to update
- **key** (*str*) – key for the value
- **value** (*obj*) – Value can be an object or dict or a binary
- **header** ([datablock.Header](#)) – Header for the value
- **metadata** ([datablock.Metadata](#)) – Metadata for the value

**Returns**

None

**decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema module**

The table layout and utilities for our SQLAlchemy ORM

```
class decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Base(**kwargs)
```

Bases: object

The base class of the class hierarchy.

When called, it accepts no arguments and returns a new featureless instance that has no instance attributes and cannot be given any.

```
_sa_registry = <sqlalchemy.orm.decl_api.registry object>
```

```
metadata = MetaData()
```

```
registry = <sqlalchemy.orm.decl_api.registry object>
```

```
class decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Dataproduct(**kwargs)
```

Bases: *Base*

The PRIMARY KEY on this table isn't used....

Existing code appears to depend on column order.

```
_sa_class_manager = {'generation_id':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'id':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'key':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'taskmanager':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'taskmanager_id':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'value':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>}
```

generation\_id

id

key

taskmanager

taskmanager\_id

value

```
class decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Header(**kwargs)
```

Bases: *Base*

The PRIMARY KEY on this table isn't used....

The existing code has a hard expectation on the time columns being BIGINT rather than datetime objects buried within the classes.

**Looks like there was an initial goal of a relationship**  
with the Schema table, but it may not be in use

Existing code appears to depend on column order.

```

_sa_class_manager = {'create_time':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'creator':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'expiration_time':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'generation_id':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'id':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'key':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'scheduled_create_time':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'schema_id':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'taskmanager':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'taskmanager_id':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>}

```

create\_time

creator

expiration\_time

generation\_id

id

key

scheduled\_create\_time

schema\_id

taskmanager

taskmanager\_id

**class** decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.**Metadata**(\*\*kwargs)

Bases: [Base](#)

The PRIMARY KEY on this table isn't used...

The existing code has a hard expectation on the state field as a 'text' element.

The existing code has a hard expectation on the time columns being BIGINT rather than datetime objects burried within the classes.

Existing code appears to depend on column order.

```

_sa_class_manager = {'generation_id':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'generation_time':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'id':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'key':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'missed_update_count':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'state':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'taskmanager':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'taskmanager_id':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>}

```

generation\_id

generation\_time

id

key

missed\_update\_count

state

taskmanager

taskmanager\_id

```
class decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Schema(**kwargs)
```

Bases: [Base](#)

This table may not be in use

**Has a one-to-many relationship with:**

Header - may not be in use

```
_sa_class_manager = {'schema': <sqlalchemy.orm.attributes.InstrumentedAttribute
object>, 'schema_id': <sqlalchemy.orm.attributes.InstrumentedAttribute object>}
```

schema

schema\_id

```
class decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Taskmanager(**kwargs)
```

Bases: [Base](#)

**Has a one-to-many relationship with:**

Header Metadata Dataproduct

**changes cascade on:**

Header Metadata Dataproduct

Existing code appears to depend on column order.

```
_sa_class_manager = {'datestamp': <sqlalchemy.orm.attributes.InstrumentedAttribute
object>, 'name': <sqlalchemy.orm.attributes.InstrumentedAttribute object>,
'sequence_id': <sqlalchemy.orm.attributes.InstrumentedAttribute object>,
'task_dataproduct': <sqlalchemy.orm.attributes.InstrumentedAttribute object>,
'task_header': <sqlalchemy.orm.attributes.InstrumentedAttribute object>,
'task_metadata': <sqlalchemy.orm.attributes.InstrumentedAttribute object>,
'taskmanager_id': <sqlalchemy.orm.attributes.InstrumentedAttribute object>}
```

datestamp

name

sequence\_id

task\_dataproduct

task\_header

task\_metadata

taskmanager\_id

**decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.utils module**

Code not written by us

`decisionengine.framework.dataspace.datasources.sqlalchemy_ds.utils.add_engine_pidguard(engine)`

Based on <https://stackoverflow.com/questions/62920507/using-sqlalchemy-connection-pooling-queues-with-python-multiprocessing>

`decisionengine.framework.dataspace.datasources.sqlalchemy_ds.utils.clone_model(model, **kwargs)`

Based on <https://stackoverflow.com/a/55991358>

`decisionengine.framework.dataspace.datasources.sqlalchemy_ds.utils.orm_as_dict(obj)`

Based on : <https://stackoverflow.com/a/37350445>

**Module contents**

Top level import so we can rationally segment items of the ORM

**class** `decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS(config_dict)`

Bases: `DataSource`

A DecisionEngine data source via the SQL Alchemy ORM

```
{
    "dataspace": {
        "datasource": {
            "module": "decisionengine.framework.dataspace.datasources.sqlalchemy_ds",    "name":
            "SQLAlchemyDS", "params": {
                "pool_size": 5, "max_overflow": 10, "timeout": 30,
                # url is mandatory, but any engine keyword is accepted here.    "url": "di-
                alect[+driver]://user:password@host/dbname"
            }
        }
    }
}
```

Exceptions should be caught and logged by the caller.

`_abc_impl = <_abc._abc_data object>`

**close()**

Close all connections to the database

**Returns**

None

**connect()**

Create a pool of database connections

**Returns**

None

**create\_tables()**

Create database tables

**Returns**

None

**delete\_data\_older\_than(days)**

Delete data older than interval

**Parameters**

**days** (*int*) – remove data older than this many days

**Returns**

None

**duplicate\_datablock(taskmanager\_id, generation\_id, new\_generation\_id)**

For the given taskmanager\_id, make a copy of the datablock with given generation\_id, set the generation\_id for the datablock copy

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to clone
- **new\_generation\_id** (*int*) – generation id to create

**Returns**

None

**get\_datablock(taskmanager\_id, generation\_id)**

Return the entire datablock from the dataproduct table for the given taskmanager\_id, generation\_id

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to locate

**Returns**

with all set keys and their associated values

**Return type**

dict

**get\_dataproduct(taskmanager\_id, generation\_id, key)**

Return the data from the dataproduct table for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to locate
- **key** (*str*) – key for the value

**Returns**

The possibly binary value stored earlier

**Return type**

obj

**get\_dataproducts**(*taskmanager\_id*, *key=None*)

Return list of all data products associated with with *taskmanager\_id*

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **key** (*str*) – key for the value

**Returns**

each element is the matching row as a dict()

**Return type**

tuple

**get\_header**(*taskmanager\_id*, *generation\_id*, *key*)

Return the header from the header table for the given *taskmanager\_id*, *generation\_id*, *key*

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to locate
- **key** (*str*) – key for the value

**Returns**

**fields in order are:**

*taskmanager.taskmanager\_id*, *header.taskmanager\_id*, *header.generation\_id*,  
*header.key*, *header.create\_time*, *header.expiration\_time*, *header.scheduled\_create\_time*,  
*header.creator*, *header.schema\_id*

**Return type**

tuple

**get\_last\_generation\_id**(*taskmanager\_name*, *taskmanager\_id=None*)

Return last generation id for current task manager or taskmanager w/ *task\_manager\_id*.

**Parameters**

- **taskmanager\_name** (*str*) – name of taskmanager to retrieve
- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve

**Returns**

the largest generation stored within the database

**Return type**

int

**get\_metadata**(*taskmanager\_id*, *generation\_id*, *key*)

Return the metadata from the metadata table for the given *taskmanager\_id*, *generation\_id*, *key*

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to locate
- **key** (*str*) – key for the value

**Returns**

**fields in order are:**

taskmanager.taskmanager\_id, metadata.taskmanager\_id, metadata.generation\_id, metadata.key, metadata.state, metadata.generation\_time, metadata.missed\_update\_count

**Return type**

tuple

**get\_schema**(*table=None*)

Given the table name return it's schema

**get\_taskmanager**(*taskmanager\_name, taskmanager\_id=None*)

Find the task manager by name/uuid in the database get back the primary key.

If multiples match, find highest primary key.

**Parameters**

- **taskmanager\_name** (*str*) – name of taskmanager to retrieve
- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve

**Returns**

the matching row, column names as keys

**Return type**

dict

**get\_taskmanagers**(*taskmanager\_name=None, start\_time=None, end\_time=None*)

Find taskmanagers that meet our search

**Parameters**

- **taskmanager\_name** (*str*) – name of taskmanager to retrieve
- **start\_time** (*datetime*) – Datetime to confine against
- **end\_time** (*datetime*) – Datetime to confine against

**Returns**

each element is a dict() matching row, column names as keys

**Return type**

list

**insert**(*taskmanager\_id, generation\_id, key, value, header, metadata*)

Insert data into respective tables for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to create
- **key** (*str*) – key for the value
- **value** (*obj*) – Value can be an object or dict or a binary
- **header** ([datablock.Header](#)) – Header for the value
- **metadata** ([datablock.Metadata](#)) – Metadata for the value

**Returns**

None



**reset\_connections()**

Reset the connection to the database. So long as self.engine isn't undef, the engine can still make new connections if new db actions happen. It just wont have any open at this time.

**Returns**

None

**store\_taskmanager**(*name, taskmanager\_id, datestamp=None*)

Store TaskManager in database

**Parameters**

- **name** (*str*) – name of taskmanager to retrieve
- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **datestamp** (*datetime*) – datetime of created object, defaults to 'now'

**Returns**

the primary key of the row in the database

**Return type**

int

**update**(*taskmanager\_id, generation\_id, key, value, header, metadata*)

Update the data in respective tables for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation\_id** (*int*) – generation id to update
- **key** (*str*) – key for the value
- **value** (*obj*) – Value can be an object or dict or a binary
- **header** (*datablock.Header*) – Header for the value
- **metadata** (*datablock.Metadata*) – Metadata for the value

**Returns**

None

**decisionengine.framework.dataspace.datasources.tests package****Submodules****decisionengine.framework.dataspace.datasources.tests.fixtures module**

pytest fixtures/constants

decisionengine.framework.dataspace.datasources.tests.fixtures.PG\_DE\_DB\_WITHOUT\_SCHEMA(*request: FixtureRequest*)  
 → connection

Fixture factory for PostgreSQL.

**Parameters**

**request** – fixture request object

**Returns**

postgresql client

```
decisionengine.framework.dataspace.datasources.tests.fixtures.PG_PROG(request: FixtureRequest,
                                                                    tmp_path_factory:
                                                                    TempPathFactory) →
                                                                    Iterator[PostgreSQLExecutor]
```

Process fixture for PostgreSQL.

**Parameters**

- **request** – fixture request object
- **tmp\_path\_factory** – temporary path object (fixture)

**Returns**

tcp executor

```
decisionengine.framework.dataspace.datasources.tests.fixtures.SQLALCHEMY_PG_WITH_SCHEMA(PG_DE_DB_WITH_SCHEMA)
```

Get a blank database from `pytest_postgresql`. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

```
decisionengine.framework.dataspace.datasources.tests.fixtures.SQLALCHEMY_TEMPFILE_SQLITE(tmp_path)
```

Setup an SQLite database with the `pytest tmp_path` fixture. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

```
decisionengine.framework.dataspace.datasources.tests.fixtures.datasource(request)
```

This parameterized fixture will setup up various datasources.

Add datasource objects to `DATASOURCES_TO_TEST` once they've got our basic schema loaded. And adjust our *if* statements here until we are SQLAlchemy only.

Pytest should take it from there and automatically run it through all the tests using this fixture.

```
decisionengine.framework.dataspace.datasources.tests.fixtures.mock_data_block()
```

This fixture replaces the standard datablock implementation.

The current DataBlock implementation does not own any data products but forwards them immediately to a backend datasource. The only implemented datasource requires Postgres, which is overkill when needing to test simple data-product communication between modules.

This mock datablock class directly owns the data products, thus avoiding the need for a datasource backend. It is anticipated that a future design of the DataBlock will own the data products, thus making this mock class unnecessary.

## decisionengine.framework.dataspace.datasources.tests.test\_datasource\_api module

This test plan covers a generic dataspace object via pytest parameters.

```
decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_create_tables(datasource)
```

`create_tables()` should be safe to call multiple times

```
decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_delete_data_older_than_age
```

Can we delete old entries

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_duplicate_datablock(datasource)`  
Can we duplicate taskmanager1 and all its entries

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_datablock(datasource)`

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_dataproduct(datasource)`  
Can we get the dataproduct by uuid with key

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_dataproduct_not_exist(datasource)`  
Does it error out if we ask for bogus information?

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_dataproducts(datasource)`  
Can we get the dataproducts by uuid and uuid with key

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_dataproducts_not_exist(datasource)`  
Does it error out if we ask for bogus information?

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_header(datasource)`  
Can we fetch a header?

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_header_not_exist(datasource)`  
Does it error out if we ask for a bogus header?

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_last_generation_id(datasource)`  
Can we get the last generation id by name or name and uuid

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_last_generation_id_not_exist(datasource)`  
Does it error out if we ask for a bogus taskmanager?

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_metadata(datasource)`  
Can we fetch a metadata element?

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_metadata_not_exist(datasource)`  
Does it error out if we ask for a bogus metadata element?

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_taskmanager_exists(datasource)`  
Can I get a taskmanager by name or name and uuid

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_taskmanager_not_exist(datasource)`  
This should error out

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_taskmanagers(datasource)`  
Can I get multiple task managers

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_taskmanagers_not_exist(datasource)`  
Do I error out when asking for garbage

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_has_config(datasource)`  
This should have a *config* dict we can pass to jsonnet

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_insert(datasource)`  
Can we insert new elements

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_reset_connections(datasource)`  
`reset_connections()` should be safe to call any time

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_store_taskmanager(datasource)`  
Can we make new entries

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_update(datasource)`

Do updates work as expected

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_update_bad(datasource)`

Do updates fail to work on bogus taskmanager as expected

## Module contents

### Submodules

#### decisionengine.framework.dataspace.datasources.null module

**class** `decisionengine.framework.dataspace.datasources.null.NullDataSource(config_dict)`

Bases: *DataSource*

Implementation of data source ABC that does nothing

**\_abc\_impl** = `<_abc._abc_data object>`

**close()**

Close all connections to the database

**connect()**

Create a pool of database connections

**create\_tables()**

Create database tables

**delete\_data\_older\_than(*days*)**

Delete data older than interval :type days: long :arg days: remove data older than interval

**duplicate\_datablock(*taskmanager\_id*, *generation\_id*, *new\_generation\_id*)**

For the given taskmanager\_id, make a copy of the datablock with given generation\_id, set the generation\_id for the datablock copy

#### Parameters

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data
- **new\_generation\_id** (int) – generation\_id of the new datablock created

**get\_datablock(*taskmanager\_id*, *generation\_id*)**

Return the entire datablock from the dataproduct table for the given taskmanager\_id, generation\_id

#### Parameters

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data

**get\_dataproduct(*taskmanager\_id*, *generation\_id*, *key*)**

Return the data from the dataproduct table for the given taskmanager\_id, generation\_id, key

#### Parameters

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data

- **key** (string) – key for the value

**get\_dataproducts**(*taskmanager\_id*, *key=None*)

Return list of all data products associated with with taskmanager\_id

**Parameters**

- **key** (string) – data product key

**get\_header**(*taskmanager\_id*, *generation\_id*, *key*)

Return the header from the header table for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data
- **key** (string) – key for the value

**get\_last\_generation\_id**(*taskmanager\_name*, *taskmanager\_id=None*)

Return last generation id for current task manager or taskmanager w/ task\_manager\_id.

**Parameters**

- **taskmanager\_name** (string) – task manager name
- **taskmanager\_id** (string) – task manager id

**get\_metadata**(*taskmanager\_id*, *generation\_id*, *key*)

Return the metadata from the metadata table for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data
- **key** (string) – key for the value

**get\_schema**(*table=None*)

Given the table name return it's schema

**Parameters**

- **table** (string) – Name of the table

**get\_taskmanager**(*taskmanager\_name*, *taskmanager\_id=None*)

Retrieve TaskManager :type taskmanager\_name: **string** :arg taskmanager\_name: name of taskmanager to retrieve :type taskmanager\_id: **string** :arg taskmanager\_id: id of taskmanager to retrieve

**get\_taskmanagers**(*taskmanager\_name=None*, *start\_time=None*, *end\_time=None*)

Retrieve TaskManagers :type taskmanager\_name: **string** :arg taskmanager\_name: name of taskmanager to retrieve :type taskmanager\_id: **string** :arg taskmanager\_id: id of taskmanager to retrieve

**insert**(*taskmanager\_id*, *generation\_id*, *key*, *value*, *header*, *metadata*)

Insert data into respective tables for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data
- **key** (string) – key for the value
- **value** (object) – Value can be an object or dict

- **header** (Header) – Header for the value
- **header** – Metadata for the value

**reset\_connections()**

Drop any cached connections and reconnect to the database

**store\_taskmanager**(*name, taskmanager\_id, datestamp=None*)

Store TaskManager :type taskmanager\_name: **string** :arg taskmanager\_name: name of taskmanager to retrieve :type taskmanager\_id: **string** :arg taskmanager\_id: id of taskmanager to retrieve :type datestamp: **datetime** :arg datestamp: datetime of created object, defaults to 'now'

**update**(*taskmanager\_id, generation\_id, key, value, header, metadata*)

Update the data in respective tables for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data
- **key** (string) – key for the value
- **value** (object) – Value can be an object or dict
- **header** (Header) – Header for the value
- **header** – Metadata for the value

## Module contents

### decisionengine.framework.dataspace.tests package

#### Submodules

#### decisionengine.framework.dataspace.tests.fixtures module

decisionengine.framework.dataspace.tests.fixtures.**PG\_DE\_DB\_WITHOUT\_SCHEMA**(*request: FixtureRequest*) → connection

Fixture factory for PostgreSQL.

**Parameters**

**request** – fixture request object

**Returns**

postgresql client

decisionengine.framework.dataspace.tests.fixtures.**PG\_PROG**(*request: FixtureRequest, tmp\_path\_factory: TempPathFactory*) → Iterator[PostgreSQLExecutor]

Process fixture for PostgreSQL.

**Parameters**

- **request** – fixture request object
- **tmp\_path\_factory** – temporary path object (fixture)

**Returns**

tcp executor

`decisionengine.framework.dataspace.tests.fixtures.SQLALCHEMY_PG_WITH_SCHEMA(PG_DE_DB_WITHOUT_SCHEMA)`

Get a blank database from `pytest_postgresql`. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

`decisionengine.framework.dataspace.tests.fixtures.SQLALCHEMY_TEMPFILE_SQLITE(tmp_path)`

Setup an SQLite database with the `pytest tmp_path` fixture. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

`decisionengine.framework.dataspace.tests.fixtures.datasources(request)`

This parameterized fixture will setup up various datasources.

Add datasource objects to `DATASOURCES_TO_TEST` once they've got our basic schema loaded. And adjust our *if* statements here until we are SQLAlchemy only.

Pytest should take it from there and automatically run it through all the tests using this fixture.

`decisionengine.framework.dataspace.tests.fixtures.dataspace(request)`

This parameterized fixture will setup up various datasources. Add datasource objects to `DATASOURCES_TO_TEST` once they've got our basic schema loaded. And adjust our *if* statements here until we are SQLAlchemy only.

Pytest should take it from there and automatically run it through all the tests using this fixture.

`decisionengine.framework.dataspace.tests.fixtures.load_sample_data_into_datasource(schema_only_db)`

load our sample test data into a dataspace This is a function not a fixture so you can run it on any datasource providing the right API.

**decisionengine.framework.dataspace.tests.test\_Reaper module**`decisionengine.framework.dataspace.tests.test_Reaper.config()``decisionengine.framework.dataspace.tests.test_Reaper.reaper(request)``decisionengine.framework.dataspace.tests.test_Reaper.test_fail_bad_config(reaper, config)``decisionengine.framework.dataspace.tests.test_Reaper.test_fail_missing_config(reaper, config)``decisionengine.framework.dataspace.tests.test_Reaper.test_fail_missing_config_key(reaper, config)``decisionengine.framework.dataspace.tests.test_Reaper.test_fail_small_retain(reaper)``decisionengine.framework.dataspace.tests.test_Reaper.test_fail_small_run_interval(reaper)``decisionengine.framework.dataspace.tests.test_Reaper.test_fail_start_two_reapers(reaper)``decisionengine.framework.dataspace.tests.test_Reaper.test_fail_wrong_config_key(reaper, config)``decisionengine.framework.dataspace.tests.test_Reaper.test_just_stop_no_error(reaper)``decisionengine.framework.dataspace.tests.test_Reaper.test_loop_of_start_stop_in_clumps(reaper)``decisionengine.framework.dataspace.tests.test_Reaper.test_reap_default_state(reaper)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_reaper_can_reap(reaper)`  
`decisionengine.framework.dataspace.tests.test_Reaper.test_source_fail_can_be_fixed(reaper)`  
`decisionengine.framework.dataspace.tests.test_Reaper.test_start_delay(reaper)`  
`decisionengine.framework.dataspace.tests.test_Reaper.test_start_stop(reaper)`  
`decisionengine.framework.dataspace.tests.test_Reaper.test_start_stop_stop(reaper)`  
`decisionengine.framework.dataspace.tests.test_Reaper.test_state_can_be_active(reaper)`  
`decisionengine.framework.dataspace.tests.test_Reaper.test_state_sets_timer_and_uses_it(reaper)`

### **decisionengine.framework.dataspace.tests.test\_datablock module**

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_constructor(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_duplicate(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_get_dataproducts(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_get_header(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_get_metadata(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_get_taskmanager(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_is_expired(dataspace)`  
    This test just validates the method/function exists. The stub within our default code should be replaced by a class inheriting from it. That class should have more rational return types.  
`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_is_expired_with_key(dataspace)`  
    This test just validates the method/function exists. The stub within our default code should be replaced by a class inheriting from it. That class should have more rational return types.  
`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_key_management(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_key_management_change_name(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_mark_expired(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_no_key_by_name(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_to_str(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_Header_constructor(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_Header_is_valid(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_Metadata_constructor(dataspace)`  
`decisionengine.framework.dataspace.tests.test_datablock.test_Metadata_set_state(dataspace)`



**decisionengine.framework.dataspace.tests.test\_datablock\_zlib module**

`decisionengine.framework.dataspace.tests.test_datablock_zlib.test_compress()`

`decisionengine.framework.dataspace.tests.test_datablock_zlib.test_zdumps()`

`decisionengine.framework.dataspace.tests.test_datablock_zlib.test_zloads()`

**decisionengine.framework.dataspace.tests.test\_datasource module**

`decisionengine.framework.dataspace.tests.test_datasource.test_has_methods_we_expect()`

**decisionengine.framework.dataspace.tests.test\_dataspace module**

`decisionengine.framework.dataspace.tests.test_dataspace.test_dataspace_config_finds_bad()`

`decisionengine.framework.dataspace.tests.test_dataspace.test_delete(dataspace)`

`decisionengine.framework.dataspace.tests.test_dataspace.test_duplicate_datablock(dataspace)`

Can we duplicate taskmanager1 and all its entries

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_datablock(dataspace)`

Can we get the datablock content

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_dataproduct(dataspace)`

Can we get the dataproduct by uuid with key

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_dataproduct_not_exist(dataspace)`

Does it error out if we ask for bogus information?

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_dataproducts(dataspace)`

Can we get the dataproducts by uuid and uuid with key

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_dataproducts_not_exist(dataspace)`

Does it error out if we ask for bogus information?

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_header(dataspace)`

Can we fetch a header?

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_header_not_exist(dataspace)`

Does it error out if we ask for a bogus header?

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_last_generation_id(dataspace)`

Can we get the last generation id by name or name and uuid

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_last_generation_id_not_exist(dataspace)`

Does it error out if we ask for a bogus taskmanager?

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_metadata(dataspace)`

Can we fetch a metadata element?

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_metadata_not_exist(dataspace)`

Does it error out if we ask for a bogus metadata element?

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_taskmanager_exists(dataspace)`  
Can I get a taskmanager by name or name and uuid

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_taskmanager_not_exists(dataspace)`  
This should error out

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_taskmanagers(dataspace)`  
Can I get multiple task managers

`decisionengine.framework.dataspace.tests.test_dataspace.test_get_taskmanagers_not_exist(dataspace)`  
Do I error out when asking for garbage

`decisionengine.framework.dataspace.tests.test_dataspace.test_has_config(dataspace)`  
verify our config entry exists

`decisionengine.framework.dataspace.tests.test_dataspace.test_insert(dataspace)`  
Can we insert new elements

`decisionengine.framework.dataspace.tests.test_dataspace.test_mark_expired(dataspace)`

`decisionengine.framework.dataspace.tests.test_dataspace.test_store_taskmanager(dataspace)`  
Can we make new entries

`decisionengine.framework.dataspace.tests.test_dataspace.test_update(dataspace)`  
Do updates work as expected

`decisionengine.framework.dataspace.tests.test_dataspace.test_update_bad(dataspace)`  
Do updates fail to work on bogus taskmanager as expected

## Module contents

### Submodules

#### decisionengine.framework.dataspace.datablock module

`class decisionengine.framework.dataspace.datablock.DataBlock(dataspace, name, taskmanager_id=None, generation_id=None, sequence_id=None)`

Bases: object

`__insert(key, value, header, metadata)`

Insert a new product into database with header and metadata

`__update(key, value, header, metadata)`

Update an existing product in the database with header and metadata

`_setitem(key, value, header, metadata=None)`

put a product in the database with header and metadata

**duplicate()**

Duplicate the datablock and return this new DataBlock. The intent is that at the point the duplication occurs there is only information from the sources in the DataBlock. This also increments the generation\_id of this DataBlock.

TODO: Also update the header and the metadata information TODO: Make this threadsafe

**Return type**

*DataBlock*

**get(key, default=None)**

Return the value associated with the key in the database

**Return type**

dict

**get\_dataproducts(key=None)****get\_header(key)**

Return the Header associated with the key in the database

**Return type**

*Header*

**get\_metadata(key)**

Return the metadata associated with the key in the database

**Return type**

*Metadata*

**get\_taskmanager(taskmanager\_name, taskmanager\_id=None)**

Retrieve TaskManager :type taskmanager\_name: `string` :arg taskmanager\_name: name of taskmanager to retrieve :type taskmanager\_id: `string` :arg taskmanager\_id: id of taskmanager to retrieve :rtype: :obj: dict

The dictionary returned looks like : { 'datestamp': datetime.datetime(2017, 12, 20, 17, 37, 17, 503210,

tzinfo=psycopg2.tz.FixedOffsetTimezone(offset=-360, name=None)),

'sequence\_id': 135L, 'name': 'AWS\_Calculations', 'taskmanager\_id': '77B16EB5-C79E-45B0-B1B1-37E846692E1D' }

**is\_expired(key=None)**

Check if the dataproduct for a given key or any key is expired

**keys()****mark\_expired(expiration\_time)**

Set the expiration\_time for the current generation of the dataproduct and mark it as expired if expiration\_time <= current time

**put(key, value, header, metadata=None)**

Put data into the DataBlock

**store\_taskmanager(taskmanager\_name, taskmanager\_id)**

Persist TaskManager, returns sequence number :type taskmanager\_name: `string` :type taskmanager\_id: :obj: `string` :rtype: `int`

```
class decisionengine.framework.dataspace.datablock.Header(taskmanager_id, create_time=None,
                                                         expiration_time=None,
                                                         scheduled_create_time=None,
                                                         creator='module', schema_id=None)
```

Bases: UserDict

```
_abc_impl = <_abc._abc_data object>
```

```
default_data_lifetime = 1800
```

```
is_valid()
```

Check if the Header has minimum required information

```
required_keys = {'create_time', 'creator', 'expiration_time',
                 'scheduled_create_time', 'schema_id', 'taskmanager_id'}
```

```
exception decisionengine.framework.dataspace.datablock.InvalidMetadataError
```

Bases: Exception

Errors due to invalid Metadata

```
class decisionengine.framework.dataspace.datablock.Metadata(taskmanager_id, state='NEW',
                                                            generation_id=None,
                                                            generation_time=None,
                                                            missed_update_count=0)
```

Bases: UserDict

```
_abc_impl = <_abc._abc_data object>
```

```
required_keys = {'generation_id', 'generation_time', 'missed_update_count', 'state',
                 'taskmanager_id'}
```

```
set_state(state)
```

Set the state for the Metadata

```
valid_states = {'END_CYCLE', 'METADATA_UPDATE', 'NEW', 'START_BACKUP'}
```

```
class decisionengine.framework.dataspace.datablock.ProductRetriever(product_name,
                                                                    product_type,
                                                                    product_source)
```

Bases: object

```
decisionengine.framework.dataspace.datablock.compress(obj)
```

Compress python object :param obj: python object :return: compressed object

```
decisionengine.framework.dataspace.datablock.decompress(zbytes)
```

Decompress zipped byte stream, convert to string. :param zbytes: byte stream :return: uncompressed string

```
decisionengine.framework.dataspace.datablock.zdumps(obj)
```

Pickle and compress :param obj: a python object :return: compressed string

```
decisionengine.framework.dataspace.datablock.zloads(zbytes)
```

Decompress and unpickle If input is not compressed attempts to just unpickle it

#### Parameters

**zbytes** – compressed bytes

**Returns**

returns python object

**decisionengine.framework.dataspace.datasource module****class** decisionengine.framework.dataspace.datasource.DataSource(*config*)

Bases: object

**\_abc\_impl** = <\_abc.\_abc\_data object>**abstract close()**

Close all connections to the database

**abstract connect()**

Create a pool of database connections

**abstract create\_tables()**

Create database tables

**dataprodukt\_table** = 'dataprodukt'

Name of the dataprodukt table

**abstract delete\_data\_older\_than(days)**

Delete data older than interval :type days: long :arg days: remove data older than interval

**abstract duplicate\_datablock(taskmanager\_id, generation\_id, new\_generation\_id)**

For the given taskmanager\_id, make a copy of the datablock with given generation\_id, set the generation\_id for the datablock copy

**Parameters**

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data
- **new\_generation\_id** (int) – generation\_id of the new datablock created

**abstract get\_datablock(taskmanager\_id, generation\_id)**

Return the entire datablock from the dataprodukt table for the given taskmanager\_id, generation\_id

**Parameters**

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data

**abstract get\_dataproduct(taskmanager\_id, generation\_id, key)**

Return the data from the dataprodukt table for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data
- **key** (string) – key for the value

**abstract get\_dataproducts(taskmanager\_id, key)**

Return list of all data products associated with taskmanager\_id

**Parameters****key** (string) – data product key

**abstract get\_header**(*taskmanager\_id, generation\_id, key*)

Return the header from the header table for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data
- **key** (string) – key for the value

**abstract get\_last\_generation\_id**(*taskmanager\_name, taskmanager\_id=None*)

Return last generation id for current task manager or taskmanager w/ task\_manager\_id.

**Parameters**

- **taskmanager\_name** (string) – task manager name
- **taskmanager\_id** (string) – task manager id

**abstract get\_metadata**(*taskmanager\_id, generation\_id, key*)

Return the metadata from the metadata table for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data
- **key** (string) – key for the value

**abstract get\_schema**(*table=None*)

Given the table name return it's schema

**Parameters**

**table** (string) – Name of the table

**abstract get\_taskmanager**(*taskmanager\_name, taskmanager\_id*)

Retrieve TaskManager :type taskmanager\_name: string :arg taskmanager\_name: name of taskmanager to retrieve :type taskmanager\_id: string :arg taskmanager\_id: id of taskmanager to retrieve

**abstract get\_taskmanagers**(*taskmanager\_name=None, start\_time=None, end\_time=None*)

Retrieve TaskManagers :type taskmanager\_name: string :arg taskmanager\_name: name of taskmanager to retrieve :type taskmanager\_id: string :arg taskmanager\_id: id of taskmanager to retrieve

**header\_table = 'header'**

Name of the header table

**abstract insert**(*taskmanager\_id, generation\_id, key, value, header, metadata*)

Insert data into respective tables for the given taskmanager\_id, generation\_id, key

**Parameters**

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data
- **key** (string) – key for the value
- **value** (object) – Value can be an object or dict
- **header** (Header) – Header for the value
- **header** – Metadata for the value

**metadata\_table = 'metadata'**

Name of the metadata table

**abstract reset\_connections()**

Drop any cached connections and reconnect to the database

**abstract store\_taskmanager**(*taskmanager\_name, taskmanager\_id, datestamp=None*)

Store TaskManager :type taskmanager\_name: **string** :arg taskmanager\_name: name of taskmanager to retrieve :type taskmanager\_id: **string** :arg taskmanager\_id: id of taskmanager to retrieve :type datestamp: **datetime** :arg datestamp: datetime of created object, defaults to 'now'

**taskmanager\_table = 'taskmanager'**

Name of the taskmanager table

**abstract update**(*taskmanager\_id, generation\_id, key, value, header, metadata*)

Update the data in respective tables for the given taskmanager\_id, generation\_id, key

#### Parameters

- **taskmanager\_id** (string) – taskmanager\_id for generation to be retrieved
- **generation\_id** (int) – generation\_id of the data
- **key** (string) – key for the value
- **value** (object) – Value can be an object or dict
- **header** (Header) – Header for the value
- **header** – Metadata for the value

## decisionengine.framework.dataspace.dataspace module

**class** decisionengine.framework.dataspace.dataspace.**DataSpace**(*config*)

Bases: object

DataSpace class is collection of datablocks and provides interface to the database used to store the actual data

**close()**

**delete**(*taskmanager\_id, all\_generations=False*)

**duplicate\_datablock**(*taskmanager\_id, generation\_id, new\_generation\_id*)

**get\_datablock**(*taskmanager\_id, generation\_id*)

**get\_dataproduct**(*taskmanager\_id, generation\_id, key*)

**get\_dataproducts**(*taskmanager\_id, key=None*)

**get\_header**(*taskmanager\_id, generation\_id, key*)

**get\_last\_generation\_id**(*taskmanager\_name, taskmanager\_id=None*)

**get\_metadata**(*taskmanager\_id, generation\_id, key*)

**get\_taskmanager**(*taskmanager\_name, taskmanager\_id=None*)

**get\_taskmanagers**(*taskmanager\_name=None, start\_time=None, end\_time=None*)

**insert**(*taskmanager\_id, generation\_id, key, value, header, metadata*)

**mark\_demented**(*taskmanager\_id, keys, generation\_id=None*)

**mark\_expired**(*taskmanager\_id, generation\_id, key, expiry\_time*)

**store\_taskmanager**(*name, taskmanager\_id, datestamp=None*)

**update**(*taskmanager\_id, generation\_id, key, value, header, metadata*)

**exception** decisionengine.framework.dataspace.dataspace.DataSpaceConfigurationError

Bases: Exception

Errors related to database access

**exception** decisionengine.framework.dataspace.dataspace.DataSpaceConnectionError

Bases: Exception

Errors related to database access

**exception** decisionengine.framework.dataspace.dataspace.DataSpaceError

Bases: Exception

Errors related to database access

**exception** decisionengine.framework.dataspace.dataspace.DataSpaceExistsError

Bases: Exception

Errors related to database access

## decisionengine.framework.dataspace.maintain module

**class** decisionengine.framework.dataspace.maintain.Reaper(*config*)

Bases: object

Reaper provides functionality of periodic deletion of data older than retention\_interval in days

The class attributes indicate a rational set of defaults that shouldn't be altered by user configuration.

**MIN\_RETENTION\_INTERVAL\_DAYS** = 7

**MIN\_SECONDS\_BETWEEN\_RUNS** = 7080

**\_reaper\_loop**(*delay*)

The thread actually runs this.

**reap**()

Actually spawn the query to delete the old records. Lock the state as this task doesn't have a cancel option.

**property** retention\_interval

We have data constraints, so use a property to track

**property** seconds\_between\_runs

We have data constraints, so use a property to track

**start**(*delay=0*)

Start thread with an optional delay to start the thread in X seconds

**stop**()

Try to stop the reaper, will block if the reaper cannot be interrupted.



## Module contents

### decisionengine.framework.engine package

### Subpackages

### decisionengine.framework.engine.tests package

### Submodules

### decisionengine.framework.engine.tests.fixtures module

pytest defaults

decisionengine.framework.engine.tests.fixtures.**DEServer**(*conf\_path=None, conf\_override=None, channel\_conf\_path=None, channel\_conf\_override=None, host='127.0.0.1', port=None, make\_conf\_dirs\_if\_missing=False, block\_until\_startup\_complete=True*)

A DE Server using a private database

decisionengine.framework.engine.tests.fixtures.**PG\_DE\_DB\_WITHOUT\_SCHEMA**(*request: FixtureRequest*) → connection

Fixture factory for PostgreSQL.

#### Parameters

**request** – fixture request object

#### Returns

postgresql client

decisionengine.framework.engine.tests.fixtures.**PG\_PROG**(*request: FixtureRequest, tmp\_path\_factory: TempPathFactory*) → Iterator[PostgreSQLExecutor]

Process fixture for PostgreSQL.

#### Parameters

- **request** – fixture request object
- **tmp\_path\_factory** – temporary path object (fixture)

#### Returns

tcp executor

decisionengine.framework.engine.tests.fixtures.**SQLALCHEMY\_PG\_WITH\_SCHEMA**(*PG\_DE\_DB\_WITHOUT\_SCHEMA*)

Get a blank database from pytest\_postgresql. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

decisionengine.framework.engine.tests.fixtures.**SQLALCHEMY\_TEMPFILE\_SQLITE**(*tmp\_path*)

Setup an SQLite database with the pytest tmp\_path fixture. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

**decisionengine.framework.engine.tests.test\_ChannelWorkers module**

```
class decisionengine.framework.engine.tests.test_ChannelWorkers.TaskManager
```

```
    Bases: object
```

```
    name = 'test_channel'
```

```
    set_loglevel_value(value)
```

```
decisionengine.framework.engine.tests.test_ChannelWorkers.global_config(dataspace)
```

```
decisionengine.framework.engine.tests.test_ChannelWorkers.test_worker_logger_sized_rotation(global_config)
```

```
decisionengine.framework.engine.tests.test_ChannelWorkers.test_worker_logger_timed_rotation(global_config)
```

```
decisionengine.framework.engine.tests.test_ChannelWorkers.test_worker_name(global_config)
```

**decisionengine.framework.engine.tests.test\_SourceWorkers module**

```
decisionengine.framework.engine.tests.test_SourceWorkers.global_config(dataspace)
```

```
decisionengine.framework.engine.tests.test_SourceWorkers.source_config(channel_name,  
                                                                           source_name)
```

```
decisionengine.framework.engine.tests.test_SourceWorkers.source_worker_for(src_config,  
                                                                              global_config)
```

```
decisionengine.framework.engine.tests.test_SourceWorkers.test_worker_logger_sized_rotation(global_config)
```

```
decisionengine.framework.engine.tests.test_SourceWorkers.test_worker_logger_timed_rotation(global_config)
```

```
decisionengine.framework.engine.tests.test_SourceWorkers.test_worker_logger_wrong_rotation_method(global_config)
```

```
decisionengine.framework.engine.tests.test_SourceWorkers.test_worker_name(global_config)
```

**decisionengine.framework.engine.tests.test\_client\_only module**

```
decisionengine.framework.engine.tests.test_client_only.test_client_err_returned_as_rc()
```

```
    no de server is running, so --status should error
```

```
decisionengine.framework.engine.tests.test_client_only.test_client_err_returned_verbose_as_rc()
```

```
    no de server is running, so --status should error
```

```
decisionengine.framework.engine.tests.test_client_only.test_client_help(capfd)
```

```
decisionengine.framework.engine.tests.test_client_only.test_client_with_no_command_says_use_help()
```

```
decisionengine.framework.engine.tests.test_client_only.test_client_with_no_server()
```

```
decisionengine.framework.engine.tests.test_client_only.test_client_with_no_server_verbose()
```

```
decisionengine.framework.engine.tests.test_client_only.test_exclusive_options()
```

### **decisionengine.framework.engine.tests.test\_query\_tool\_only module**

`decisionengine.framework.engine.tests.test_query_tool_only.test_client_err_returned_as_rc()`  
no de server is running, so `-status` should error

`decisionengine.framework.engine.tests.test_query_tool_only.test_client_err_returned_verbose_as_rc()`  
no de server is running, so `-status` should error

`decisionengine.framework.engine.tests.test_query_tool_only.test_query_tool_help()`

`decisionengine.framework.engine.tests.test_query_tool_only.test_query_tool_with_no_server()`

`decisionengine.framework.engine.tests.test_query_tool_only.test_query_tool_with_no_server_verbose()`

### **decisionengine.framework.engine.tests.test\_startup module**

`decisionengine.framework.engine.tests.test_startup._check_override(arguments)`

`decisionengine.framework.engine.tests.test_startup.metrics_env_setup(tmp_path, monkeypatch)`  
Make sure we have a directory set for `PROMETHEUS_MULTIPROC_DIR` so that metric instantiation gives us multiprocess metrics

`decisionengine.framework.engine.tests.test_startup.test_change_port()`

`decisionengine.framework.engine.tests.test_startup.test_check_metrics_env_no_webserver()`

`decisionengine.framework.engine.tests.test_startup.test_check_metrics_env_var_set()`

`decisionengine.framework.engine.tests.test_startup.test_check_metrics_env_var_unset()`

`decisionengine.framework.engine.tests.test_startup.test_default_config()`

### **decisionengine.framework.engine.tests.test\_verify\_redis\_server module**

`decisionengine.framework.engine.tests.test_verify_redis_server.test_verify_bad_broker()`

`decisionengine.framework.engine.tests.test_verify_redis_server.test_verify_bad_redis_server()`

`decisionengine.framework.engine.tests.test_verify_redis_server.test_verify_bad_url()`

`decisionengine.framework.engine.tests.test_verify_redis_server.test_verify_redis_server()`

`decisionengine.framework.engine.tests.test_verify_redis_server.test_verify_redis_url()`

## **Module contents**

### **Submodules**

#### **decisionengine.framework.engine.ChannelWorkers module**

```
class decisionengine.framework.engine.ChannelWorkers.ChannelWorker(task_manager,  
                                                                logger_config)
```

Bases: Process

Class that encapsulates a channel's task manager as a separate process.

This class' run function is called whenever the process is started. If the process is abruptly terminated—e.g. the run method is pre-empted by a signal or an `os._exit(n)` call—the `ChannelWorker` object will still exist even if the operating-system process no longer does.

To determine the exit code of this process, use the `ChannelWorker.exitcode` value, provided by the multiprocessing.Process base class.

**get\_consumes()**

**get\_produces()**

**get\_state\_name()**

**run()**

Method to be run in sub-process; can be overridden in sub-class

**setup\_logger()**

**wait\_while**(*state*, *timeout=None*)

```
class decisionengine.framework.engine.ChannelWorkers.ChannelWorkers
```

Bases: object

This class manages and provides access to the task-manager workers.

The intention is that the decision engine never directly interacts with the workers but refers to them via a context manager:

**with workers.access() as ws:**

# Access to ws now protected `ws['new_channel'] = ChannelWorker(...)`

In cases where the decision engine's `block_while` method must be called (e.g. during tests), one should use unguarded access:

`ws = workers.get_unguarded() # Access to ws is unprotected ws['new_channel'].wait_while(...)`

Calling a blocking method while using the protected context manager (i.e. `workers.access()`) will likely result in a deadlock.

```
class Access(workers, lock)
```

Bases: object

**access()**

**accessed\_by\_another\_thread()**

**get\_unguarded()**

**decisionengine.framework.engine.ClientMessageReceiver module**

```
class decisionengine.framework.engine.ClientMessageReceiver.ClientMessageReceiver(exchange_name,
                                                                              ex-
                                                                              change_type,
                                                                              bro-
                                                                              ker_url,
                                                                              rout-
                                                                              ing_key_suffix,
                                                                              log-
                                                                              ger_name)
```

Bases: object

**\_receive**(*body, message*)

**execute**(*func, \*args*)

**decisionengine.framework.engine.DecisionEngine module**

Main loop for Decision Engine. The following environment variable points to decision engine configuration file: DECISION\_ENGINE\_CONFIG\_FILE if this environment variable is not defined the DE-Config.py file from the ``./tests/etc/`` directory will be used.

```
class decisionengine.framework.engine.DecisionEngine.DecisionEngine(global_config,
                                                                    channel_config_loader,
                                                                    server_address)
```

Bases: ThreadingMixIn, SimpleXMLRPCServer

**\_dataframe\_to\_column\_names**(*df*)

**\_dataframe\_to\_csv**(*df*)

**\_dataframe\_to\_json**(*df*)

**\_dataframe\_to\_table**(*df*)

**\_dataframe\_to\_vertical\_tables**(*df*)

**\_dispatch**(*method, params*)

Dispatches the XML-RPC method.

XML-RPC calls are forwarded to a registered function that matches the called XML-RPC method name. If no such function exists then the call is forwarded to the registered instance, if available.

If the registered instance has a `_dispatch` method then that method will be called with the name of the XML-RPC method and its parameters as a tuple e.g. `instance._dispatch('add',(2,3))`

If the registered instance does not have a `_dispatch` method then the instance will be searched to find a matching method and, if found, will be called.

Methods beginning with an `'_'` are considered private and will not be called.

**block\_while**(*state, timeout=None*)

**create\_channel**(*channel\_name, channel\_config*)

**get\_logger**()

**metrics()**

**reaper\_start**(*delay*)

**reaper\_status()**

**reaper\_stop()**

**rm\_channel**(*channel, maybe\_timeout*)

**rpc\_block\_while**(*client\_queue, state\_str, timeout=None*)

**rpc\_get\_channel\_log\_level**(*client\_queue, channel*)

**rpc\_get\_log\_level**(*client\_queue*)

**rpc\_get\_source\_log\_level**(*client\_queue, source*)

**rpc\_kill\_channel**(*client\_queue, channel, timeout=None*)

**rpc\_metrics**(*client\_queue*)  
Display collected metrics

**rpc\_ping**(*client\_queue*)

**rpc\_print\_product**(*client\_queue, product, columns=None, query=None, types=False, format=None*)

**rpc\_print\_products**(*client\_queue*)

**rpc\_product\_dependencies**(*client\_queue*)

**rpc\_query\_tool**(*client\_queue, product, format=None, start\_time=None*)

**rpc\_queue\_status**(*client\_queue*)

**rpc\_reaper\_start**(*client\_queue, delay=0*)  
Start the reaper process after ‘delay’ seconds. Default 0 seconds delay. :type delay: int

**rpc\_reaper\_status**(*client\_queue*)

**rpc\_reaper\_stop**(*client\_queue*)

**rpc\_rm\_channel**(*client\_queue, channel, maybe\_timeout*)

**rpc\_set\_channel\_log\_level**(*client\_queue, channel, log\_level*)  
Assumes log\_level is a string corresponding to the supported logging-module levels.

**rpc\_set\_source\_log\_level**(*client\_queue, source, log\_level*)  
Assumes log\_level is a string corresponding to the supported logging-module levels.

**rpc\_show\_config**(*client\_queue, channel*)  
Show the configuration for a channel.

**rpc\_show\_de\_config**(*client\_queue*)

**rpc\_start\_channel**(*client\_queue, channel\_name*)

**rpc\_start\_channels**(*client\_queue*)

```

rpc_status(client_queue)

rpc_stop(client_queue=None)

rpc_stop_channel(client_queue, channel)

rpc_stop_channels(client_queue)

service_actions()
    Called by the serve_forever() loop.
    May be overridden by a subclass / Mixin to implement any code that needs to be run during the loop.

start_channel(channel_name, src_workers)

start_channels()

start_webserver()
    Start CherryPy webserver using configured port. If port is not configured use default webserver port.

stop_channels()

stop_worker(worker, timeout)

class decisionengine.framework.engine.DecisionEngine.RequestHandler(request, client_address,
                                                                    server)

    Bases: SimpleXMLRPCRequestHandler

    rpc_paths = ('/RPC2',)

class decisionengine.framework.engine.DecisionEngine.StopState(value)
    Bases: Enum

    An enumeration.

    Clean = 2

    NotFound = 1

    Terminated = 3

decisionengine.framework.engine.DecisionEngine._channel_preamble(name)

decisionengine.framework.engine.DecisionEngine._check_metrics_env(options)

decisionengine.framework.engine.DecisionEngine._create_de_server(global_config,
                                                                channel_config_loader)

    Create the DE server with the passed global configuration and config manager

decisionengine.framework.engine.DecisionEngine._get_de_conf_manager(global_config_dir,
                                                                channel_config_dir,
                                                                options)

decisionengine.framework.engine.DecisionEngine._get_global_config(config_file, options)

decisionengine.framework.engine.DecisionEngine._initial_start_channels(server)

decisionengine.framework.engine.DecisionEngine._queue_name_and_type(redis_obj, redis_member)

decisionengine.framework.engine.DecisionEngine._requests_in_flight(redis_obj, exchange_name)

```

`decisionengine.framework.engine.DecisionEngine._start_de_server(server)`

Start the DE server and listen forever

`decisionengine.framework.engine.DecisionEngine._verify_redis_server(broker_url)`

`decisionengine.framework.engine.DecisionEngine._verify_redis_url(broker_url)`

`decisionengine.framework.engine.DecisionEngine.main(args=None)`

If args is None, sys.argv will be used instead If args is a list, it will be used instead of sys.argv (for unit testing)

`decisionengine.framework.engine.DecisionEngine.parse_program_options(args=None)`

If args is a list, it will be used instead of sys.argv

## decisionengine.framework.engine.SourceWorkers module

**class** `decisionengine.framework.engine.SourceWorkers.SourceWorker(key, config, logger_config, channel_name, exchange, broker_url)`

Bases: `Process`

Provides interface to loadable modules an events to synchronize execution

**get\_loglevel()**

**run()**

Get the data from source

**set\_loglevel\_value(log\_level)**

Assumes log\_level is a string corresponding to the supported logging-module levels.

**setup\_logger()**

**take\_offline()**

**class** `decisionengine.framework.engine.SourceWorkers.SourceWorkers(exchange, broker_url, logger=<BoundLoggerLazyProxy(logger=None, wrapper_class=None, processors=None, context_class=None, initial_values={}, logger_factory_args=('decisionengine',))>)`

Bases: `object`

This class manages and provides access to the Source workers.

The intention is that the decision engine never directly interacts with the workers but refers to them via a context manager:

**with workers.access() as ws:**

# Access to ws now protected ws['new\_source'] = SourceWorker(...)

In cases where the decision engine's block\_while method must be called (e.g. during tests), one should use unguarded access:

ws = workers.get\_unguarded() # Access to ws is unprotected ws['new\_source'].wait\_while(...)

Calling a blocking method while using the protected context manager (i.e. workers.access()) will likely result in a deadlock.



```
class Access(workers, lock)
    Bases: object
access()
detach(channel_name, source_names)
get_unguarded()
prune(channel_name, source_names)
remove_all(timeout)
update(channel_name, source_configs, logger_config)
```

### decisionengine.framework.engine.de\_client module

```
decisionengine.framework.engine.de_client.command_for_args(argsparsed, de_socket)
    argsparsed should be from create_parser in this file
decisionengine.framework.engine.de_client.console_scripts_main(args_to_parse=None)
    This is the entry point for the setuptools auto generated scripts. Setuptools thinks a return from this function is
    an error message.
decisionengine.framework.engine.de_client.create_parser()
decisionengine.framework.engine.de_client.main(args_to_parse=None, logger_name='de_client')
    If you pass a list of args, they will be used instead of sys.argv
```

### decisionengine.framework.engine.de\_query\_tool module

```
decisionengine.framework.engine.de_query_tool.command_for_args(argsparsed, de_socket)
    Calls the proper function for the arguments passed to de_query_tool.
```

#### Parameters

- **argsparsed** (*Namespace*) – Should be from create\_parser in this file.
- **de\_socket** (*ServerProxy*) – RPC Server Proxy.

#### Returns

Output of the command.

#### Return type

str

```
decisionengine.framework.engine.de_query_tool.console_scripts_main(args_to_parse=None)
    This is the entry point for the setuptools auto generated scripts. Setuptools thinks a return from this function is
    an error message.
decisionengine.framework.engine.de_query_tool.create_parser()
decisionengine.framework.engine.de_query_tool.main(args_to_parse=None,
                                                    logger_name='de_query_tool')
    Main function for de_query_tool
```

**Parameters**

**args\_to\_parse** (*list, optional*) – If you pass a list of args, they will be used instead of `sys.argv`. Defaults to `None`.

**Returns**

Query result

**Return type**

str

**Module contents**

**decisionengine.framework.logicengine package**

**Subpackages**

**decisionengine.framework.logicengine.tests package**

**Submodules**

**decisionengine.framework.logicengine.tests.test\_bool\_function\_name module**

`decisionengine.framework.logicengine.tests.test_bool_function_name.test_error_conditions()`

**decisionengine.framework.logicengine.tests.test\_cascaded\_rules module**

`decisionengine.framework.logicengine.tests.test_cascaded_rules.myengine()`

`decisionengine.framework.logicengine.tests.test_cascaded_rules.test_rule_that_does_not_fire(myengine)`

`decisionengine.framework.logicengine.tests.test_cascaded_rules.test_rule_that_fires(myengine)`

**decisionengine.framework.logicengine.tests.test\_construction module**

`decisionengine.framework.logicengine.tests.test_construction.test_configuration_with_fact_using_function`

`decisionengine.framework.logicengine.tests.test_construction.test_configuration_with_numpy_facts()`

`decisionengine.framework.logicengine.tests.test_construction.test_default_construction()`

LogicEngine is not default constructible.

`decisionengine.framework.logicengine.tests.test_construction.test_trivial_configuration()`

Logic engine constructed with trivial rules and facts.

`decisionengine.framework.logicengine.tests.test_construction.test_wrong_configuration()`

LogicEngine construction requires rules and facts; if we don't supply them it is an error.

**decisionengine.framework.logicengine.tests.test\_duplicate\_fact\_names module**

decisionengine.framework.logicengine.tests.test\_duplicate\_fact\_names.test\_duplicate\_fact\_names()

**decisionengine.framework.logicengine.tests.test\_facts module**

decisionengine.framework.logicengine.tests.test\_facts.make\_db(*maximum*)

decisionengine.framework.logicengine.tests.test\_facts.test\_compound\_fact\_with\_spaces()

decisionengine.framework.logicengine.tests.test\_facts.test\_fact\_using\_numpy\_array()

decisionengine.framework.logicengine.tests.test\_facts.test\_fact\_using\_numpy\_function()

decisionengine.framework.logicengine.tests.test\_facts.test\_fact\_with\_fail\_on\_error()

decisionengine.framework.logicengine.tests.test\_facts.test\_fact\_with\_nested\_names()

decisionengine.framework.logicengine.tests.test\_facts.test\_simple\_fact()

decisionengine.framework.logicengine.tests.test\_facts.test\_syntax\_error(*caplog*)

**decisionengine.framework.logicengine.tests.test\_fail\_on\_error module**

decisionengine.framework.logicengine.tests.test\_fail\_on\_error.logic\_engine\_with\_fact(*fact*)

decisionengine.framework.logicengine.tests.test\_fail\_on\_error.test\_conditional\_fact()

decisionengine.framework.logicengine.tests.test\_fail\_on\_error.test\_fact\_with\_misspecified\_attribute()

decisionengine.framework.logicengine.tests.test\_fail\_on\_error.test\_fail\_on\_error(*caplog*)

decisionengine.framework.logicengine.tests.test\_fail\_on\_error.test\_false\_fact\_with\_spaces()

decisionengine.framework.logicengine.tests.test\_fail\_on\_error.test\_false\_literal\_fact()

decisionengine.framework.logicengine.tests.test\_fail\_on\_error.test\_index\_error()

decisionengine.framework.logicengine.tests.test\_fail\_on\_error.test\_misspecified\_fact()

decisionengine.framework.logicengine.tests.test\_fail\_on\_error.test\_true\_fact()

decisionengine.framework.logicengine.tests.test\_fail\_on\_error.test\_true\_literal\_fact()

**decisionengine.framework.logicengine.tests.test\_pandas\_fact module**

decisionengine.framework.logicengine.tests.test\_pandas\_fact.mydata(*y*)

Return a 'datablock' surrogate carrying a Pandas DataFrame, and a parameter named 'y' with value y.

decisionengine.framework.logicengine.tests.test\_pandas\_fact.myengine()

decisionengine.framework.logicengine.tests.test\_pandas\_fact.test\_rule\_that\_does\_not\_fire(*myengine*)

Rules that do not fire do not create entries in the returned actions and newfacts.

decisionengine.framework.logicengine.tests.test\_pandas\_fact.test\_rule\_that\_fires(*myengine*)

### decisionengine.framework.logicengine.tests.test\_rule\_with\_negated\_fact module

decisionengine.framework.logicengine.tests.test\_rule\_with\_negated\_fact.**myengine**()

decisionengine.framework.logicengine.tests.test\_rule\_with\_negated\_fact.**test\_rule\_that\_does\_not\_fire**(myengine)

Rules that do not fire do not create entries in the returned actions and newfacts.

decisionengine.framework.logicengine.tests.test\_rule\_with\_negated\_fact.**test\_rule\_that\_fires**(myengine)

### decisionengine.framework.logicengine.tests.test\_simple\_configuration module

decisionengine.framework.logicengine.tests.test\_simple\_configuration.**myengine**()

decisionengine.framework.logicengine.tests.test\_simple\_configuration.**test\_error\_on\_bad\_names**(myengine)

decisionengine.framework.logicengine.tests.test\_simple\_configuration.**test\_rule\_that\_does\_not\_fire**(myengine)

Rules that do not fire do not create entries in the returned actions and newfacts.

decisionengine.framework.logicengine.tests.test\_simple\_configuration.**test\_rule\_that\_fires**(myengine)

## Module contents

### Submodules

### decisionengine.framework.logicengine.BooleanExpression module

**class** decisionengine.framework.logicengine.BooleanExpression.**BooleanExpression**(expr)

Bases: object

**evaluate**(d)

Return the evaluated Boolean value of this expression in the context of the given data 'd'.

**exception** decisionengine.framework.logicengine.BooleanExpression.**LogicError**

Bases: TypeError

decisionengine.framework.logicengine.BooleanExpression.**function\_name\_from\_call**(callnode)

decisionengine.framework.logicengine.BooleanExpression.**maybe\_fail\_on\_error**(expr)

### decisionengine.framework.logicengine.FactLookup module

**class** decisionengine.framework.logicengine.FactLookup.**FactLookup**(fact\_names, rules\_cfg)

Bases: object

Establishes a policy for looking up a fact based on the given name.

To wit, the first fact with a given name is the one that is used in the evaluation of all subsequent facts.

As an example, consider the following configuration:

```
facts: {
    should_publish: "(True)",
}, rules: {
```

```

publish_1: {
    expression: "should_publish", facts: ["should_publish"]
}, publish_2: {
    expression: "should_publish", actions: ["go_to_press"] facts: ["should_publish"]
} retract: {
    expression: "not should_publish", facts: ["should_retract"]
}

```

In the above, the first fact to be evaluated will always be the top-level facts (i.e. those not encapsulated by the 'rules' table). The rules labeled 'publish\_1' and 'publish\_2' both rely on the 'should\_publish' fact in their expressions, and they in turn create their own facts with the same name. FactLookup ensures that 'publish\_1' and 'publish\_2' will both use the evaluated fact from the top-level 'facts' table.

#### **rule\_for**(*fact\_name*)

Selects rule required to evaluate fact with the supplied name.

##### **Parameters**

**fact\_name** (*str*) – Name of fact for which rule will be selected.

##### **Return type**

str

##### **Returns**

Rule name

#### **sorted\_rules**(*rules\_cfg*)

Rules sorted according to rule dependencies.

##### **Parameters**

**rules\_cfg** (*dict*) – rules as specified in logic-engine configuration

##### **Return type**

list

##### **Returns**

Rules to be evaluated by the rule engine.

## **decisionengine.framework.logicengine.LogicEngine module**

**class** decisionengine.framework.logicengine.LogicEngine.LogicEngine(*cfg*)

Bases: [Module](#)

**\_create\_facts\_dataframe**(*newfacts*)

Convert newfacts dict in format below to dataframe with columns ['rule\_name', 'fact\_name', 'fact\_value']

facts dict format: 'newfacts': {

```

    'publish_glidein_requests': {
        'allow_hpc_new': True, 'allow_foo': True
    }, 'dummy_rule': {
        'dummy_new_fact': True
    }
}

```

**consumes()**

Return the names of all the items that must be in the DataBlock for the rules to be evaluated.

**evaluate(*db*)**

Evaluate our facts and rules, in the context of the given data. *db* can be any mappable, in particular a DataBlock or dictionary.

**Parameters**

**db** (DataBlock) – Products used to evaluate facts.

**evaluate\_facts(*db*)****Parameters**

**db** (DataBlock) – Products used to evaluate facts.

**Return type**

dict

**Returns**

Evaluated fact values (e.g. True or False) for each fact name.

**produces()**

`decisionengine.framework.logicengine.LogicEngine.passthrough_configuration(publisher_names)`

Assembles logic-engine configuration to unconditionally execute all publishers.

**decisionengine.framework.logicengine.Rule module**

**class** `decisionengine.framework.logicengine.Rule.Rule(rule_name, rule_cfg)`

Bases: object

In-memory representation of logic-engine rule, relying on parsing utilities in BooleanExpression.

**evaluate(*evaluated\_facts*)**

Evaluates a compiled expression given the supplied facts.

**Parameters**

**evaluated\_facts** (*dict*) – Initial fact values (e.g. True or False) for each fact name.

**Return type**

bool

**decisionengine.framework.logicengine.RuleEngine module**

**class** `decisionengine.framework.logicengine.RuleEngine.RuleEngine(fact_names, rules_cfg)`

Bases: object

Engine responsible for evaluating logic-engine rules.

This class is responsible for (a) forming a sorted set of rules that supports dependencies between them, and (b) evaluating the rules according to a specified fact-lookup policy.

**execute(*evaluated\_facts*)**

Evaluates all rules given the supplied facts.

**Parameters**

**evaluated\_facts** (*dict*) – Initial fact values (e.g. True or False) for each fact name.

**Return type**

tuple

**Returns**

Actions to be taken based on rule evaluation; new facts produced during that evaluation.

**Module contents****decisionengine.framework.modules package****Subpackages****decisionengine.framework.modules.tests package****Submodules****decisionengine.framework.modules.tests.test\_EmptySource module**`decisionengine.framework.modules.tests.test_EmptySource.test_empty_source_structure()``decisionengine.framework.modules.tests.test_EmptySource.test_missing_data_product_name_not_supported()`**decisionengine.framework.modules.tests.test\_Module module**`decisionengine.framework.modules.tests.test_Module.test_module_structure()`

The module.Module itself is a bit of a skeleton...

**decisionengine.framework.modules.tests.test\_Publisher module**`decisionengine.framework.modules.tests.test_Publisher.test_publisher_structure()`

The module.publisher itself is a bit of a skeleton...

**decisionengine.framework.modules.tests.test\_QueueLogger module**`decisionengine.framework.modules.tests.test_QueueLogger.handler_setup()``decisionengine.framework.modules.tests.test_QueueLogger.log_setup()``decisionengine.framework.modules.tests.test_QueueLogger.queue_logger_setup()``decisionengine.framework.modules.tests.test_QueueLogger.setup_queue_logging(queue_logger_setup,  
log_setup,  
handler_setup)``decisionengine.framework.modules.tests.test_QueueLogger.test_setup_queue_logging(queue_logger_setup,  
log_setup,  
han-  
dler_setup)`

```
decisionengine.framework.modules.tests.test_QueueLogger.test_start_queue_logger(queue_logger_setup,  
                                                                                  log_setup,  
                                                                                  han-  
                                                                                  dler_setup)
```

```
decisionengine.framework.modules.tests.test_QueueLogger.test_stop_queue_logger(queue_logger_setup,  
                                                                                  log_setup,  
                                                                                  han-  
                                                                                  dler_setup)
```

### **decisionengine.framework.modules.tests.test\_Source module**

```
decisionengine.framework.modules.tests.test_Source.test_source_structure()
```

The module.Source itself is a bit of a skeleton...

### **decisionengine.framework.modules.tests.test\_Transform module**

```
decisionengine.framework.modules.tests.test_Transform.test_transform_structure()
```

The module.Transform itself is a bit of a skeleton...

### **decisionengine.framework.modules.tests.test\_de\_logger module**

```
decisionengine.framework.modules.tests.test_de_logger.log_setup()
```

```
decisionengine.framework.modules.tests.test_de_logger.test_by_nonsense_is_err(log_setup)
```

```
decisionengine.framework.modules.tests.test_de_logger.test_by_size(log_setup)
```

```
decisionengine.framework.modules.tests.test_de_logger.test_by_time(log_setup)
```

### **decisionengine.framework.modules.tests.test\_module\_decorators module**

```
decisionengine.framework.modules.tests.test_module_decorators.test_multiple_consumes_declarations()
```

```
decisionengine.framework.modules.tests.test_module_decorators.test_multiple_produces_declarations()
```

```
decisionengine.framework.modules.tests.test_module_decorators.test_supports_config()
```

```
decisionengine.framework.modules.tests.test_module_decorators.test_wrong_product_names()
```

```
decisionengine.framework.modules.tests.test_module_decorators.test_wrong_product_types()
```



### decisionengine.framework.modules.tests.test\_translate\_product\_name module

```
decisionengine.framework.modules.tests.test_translate_product_name.test_translate_all()
decisionengine.framework.modules.tests.test_translate_product_name.test_translate_illegal_characters()
decisionengine.framework.modules.tests.test_translate_product_name.test_translate_none()
decisionengine.framework.modules.tests.test_translate_product_name.test_translate_simple()
decisionengine.framework.modules.tests.test_translate_product_name.test_translate_with_underscores()
```

### Module contents

#### Submodules

### decisionengine.framework.modules.EmptySource module

This dummy source takes the name of a source datablock from config file as parameter “data\_product\_name” and produces an empty pandas DataFrame as a datablock with that name

```
class decisionengine.framework.modules.EmptySource.EmptySource(config)
    Bases: Source
    _supported_config = {'data_product_name': (<class 'str'>, '', None)}
    acquire()
```

### decisionengine.framework.modules.Module module

```
class decisionengine.framework.modules.Module.Module(set_of_parameters)
    Bases: object
    A skeleton of a module
    get_data_block()
    get_parameters()
    set_data_block(data_block)

decisionengine.framework.modules.Module.consumes(**kwargs)
decisionengine.framework.modules.Module.produces(**kwargs)
decisionengine.framework.modules.Module.verify_products(producer, data)
```

**decisionengine.framework.modules.Publisher module**

```
class decisionengine.framework.modules.Publisher.Parameter(name, type=None, default=None,
                                                         comment=None)
```

Bases: object

```
class decisionengine.framework.modules.Publisher.Publisher(set_of_parameters)
```

Bases: *Module*

```
_consumes = {}
```

```
publish(data_block=None)
```

```
shutdown()
```

```
decisionengine.framework.modules.Publisher.consumes(**kwargs)
```

```
decisionengine.framework.modules.Publisher.describe(cls, program_options=<class 'decisionengine.framework.modules.describe.ModuleProgramOptions'>)
```

```
decisionengine.framework.modules.Publisher.supports_config(*args)
```

**decisionengine.framework.modules.QueueLogger module**

```
class decisionengine.framework.modules.QueueLogger.QueueLogger
```

Bases: object

```
configure_listener(handlers)
```

```
format_logger(logger)
```

```
initialize_q()
```

```
setup_queue_logging(logger, handlers)
```

```
start()
```

```
stop()
```

**decisionengine.framework.modules.Source module**

```
class decisionengine.framework.modules.Source.Parameter(name, type=None, default=None,
                                                         comment=None)
```

Bases: object

```
class decisionengine.framework.modules.Source.Source(set_of_parameters)
```

Bases: *Module*

```
_produces = {}
```

```
acquire()
```

```
decisionengine.framework.modules.Source.describe(cls, sample_config=None)
```

```
decisionengine.framework.modules.Source.produces(**kwargs)
```

```
decisionengine.framework.modules.Source.supports_config(*args)
```

**decisionengine.framework.modules.Transform module**

**class** decisionengine.framework.modules.Transform.**Parameter**(*name*, *type=None*, *default=None*, *comment=None*)

Bases: object

**class** decisionengine.framework.modules.Transform.**Transform**(*set\_of\_parameters*)

Bases: *Module*

**\_consumes** = {}

**\_produces** = {}

**transform**()

decisionengine.framework.modules.Transform.**consumes**(\*\**kwargs*)

decisionengine.framework.modules.Transform.**describe**(*cls*, *program\_options=<class 'decisionengine.framework.modules.describe.ModuleProgramOptions'>*)

decisionengine.framework.modules.Transform.**produces**(\*\**kwargs*)

decisionengine.framework.modules.Transform.**supports\_config**(\**args*)

**decisionengine.framework.modules.de\_logger module**

Logger to use in all modules

decisionengine.framework.modules.de\_logger.**configure\_logging**(*log\_level='DEBUG'*,  
*file\_rotate\_by='size'*,  
*rotation\_time\_unit='D'*,  
*rotation\_interval=1*,  
*max\_backup\_count=6*,  
*max\_file\_size=200000000*,  
*log\_file\_name='/tmp/decision\_engine\_logs/decisioneng*  
*start\_q\_logger='True'*)

**Parameters**

- **log\_level** (str) – log level
- **file\_rotate\_by** – files rotation by size or by time
- **rotation\_time\_unit** (str) – unit of time for file rotation
- **rotation\_interval** (int) – time in rotation\_time\_units between file rotations
- **log\_file\_name** (str) – log file name
- **max\_file\_size** (int) – maximal size of log file. If reached save and start new log.
- **max\_backup\_count** (int) – start rotaion after this number is reached

**Return type**

None

decisionengine.framework.modules.de\_logger.**get\_logger**()

get default logger - “decisionengine” :rtype: logging.Logger - rotating file logger

```
decisionengine.framework.modules.de_logger.get_queue_logger()
    get QueueLogger which owns the logging queues and listeners :rtype: decisionengine.framework.
    modules.QueueLogger`
decisionengine.framework.modules.de_logger.stop_queue_logger()
```

### **decisionengine.framework.modules.describe module**

```
class decisionengine.framework.modules.describe.ModuleProgramOptions(module_spec, cls)
    Bases: object
    process_args()
```

```
class decisionengine.framework.modules.describe.Parameter(name, type=None, default=None,
    comment=None)
```

Bases: object

```
decisionengine.framework.modules.describe._par_default(par_type, default_value)
```

```
decisionengine.framework.modules.describe._par_type(par_type, default_value)
```

```
decisionengine.framework.modules.describe.main_wrapper(cls, program_options=<class 'decision-
    engine.framework.modules.describe.ModuleProgramOptions'>)
```

```
decisionengine.framework.modules.describe.supports_config(*args)
```

### **decisionengine.framework.modules.logging\_configDict module**

Global Logger config dictionary used by all loggers (in their own subkeys)

### **decisionengine.framework.modules.print\_description module**

```
decisionengine.framework.modules.print_description._print_comment(comment)
```

```
decisionengine.framework.modules.print_description._print_type(type_or_value)
```

```
decisionengine.framework.modules.print_description._print_value(v)
```

```
decisionengine.framework.modules.print_description._spec_from_file_name(filename)
```

```
decisionengine.framework.modules.print_description.print_consumes(cls)
```

```
decisionengine.framework.modules.print_description.print_produces(cls)
```

```
decisionengine.framework.modules.print_description.print_supported_config(module_spec, cls)
```

```
decisionengine.framework.modules.print_description.spec_if_main(cls)
```

## decisionengine.framework.modules.translate\_product\_name module

decisionengine.framework.modules.translate\_product\_name.**translate**(*spec*)

Break apart the string 'old -> new' into a tuple ('old', 'new')

decisionengine.framework.modules.translate\_product\_name.**translate\_all**(*specs*)

## Module contents

### decisionengine.framework.taskmanager package

#### Submodules

#### decisionengine.framework.taskmanager.LatestMessages module

The LatestMessages class listens for messages from a set of queues and retains only the last unconsumed message from each queue.

The latest messages are consumed by calling the consume() instance method, which returns a dictionary whose key is the message routing key and whose value is the full message. If no messages are available, consume() returns an empty dictionary.

The LatestMessages class is intended to be used as a context manager (e.g.):

```
with LatestMessages(queues, broker_url) as messages:
```

```
    while some_predicate():
```

```
        msgs = messages.consume() if not msgs:
```

```
            continue
```

```
        for routing_key, msg in msgs.items():
```

```
            ...
```

Upon exiting the the context, a LatestMessage object will no longer listen for any messages.

```
class decisionengine.framework.taskmanager.LatestMessages.LatestMessages(queues, broker_url)
```

```
    Bases: object
```

```
    _listen()
```

```
    consume()
```

```
        Return dictionary of latest messages, keyed by message routing key.
```

#### decisionengine.framework.taskmanager.ProcessingState module

The ProcessingState class can represent any of the following task-manager states:

BOOT IDLE ACTIVE STEADY OFFLINE SHUTTINGDOWN SHUTDOWN ERROR

In addition, the class supports 'wait\_until(state)' and 'wait\_while(state)' methods, which, when called from a different process, block until the state has been entered or exited, respectively.

The 'RUNNING\_CONDITIONS' list is a list of states that a thread may have if it is started/starting. The 'STOPPING\_CONDITIONS' list is a list of states that a thread may have if it is stopped/stopping. The 'INACTIVE\_CONDITIONS' list is a list of states that a thread may have when it is not active

**class** decisionengine.framework.taskmanager.ProcessingState.**ProcessingState**(*state=State.BOOT*)

Bases: object

This object tracks the state of a process.

A number of convenience wrappers are provided.

Additionally you may use the *.lock* attribute for *with* block to lock the state during specific operations.

**get()**

This function is a minimally locking check to fetch the state.

**get\_state\_value()**

**has\_value**(*state*)

**inactive()**

**property lock**

**probably\_running()**

**set**(*state*)

This function will lock (and possibly block) to ensure a consistent change to the state value.

This function can be blocked using the *.lock* to force state sync between threads if need be.

**should\_stop()**

**wait\_until**(*state, timeout=None*)

**wait\_while**(*state, timeout=None*)

**class** decisionengine.framework.taskmanager.ProcessingState.**State**(*value*)

Bases: Enum

An enumeration.

**ACTIVE** = 2

**BOOT** = 0

**ERROR** = 7

**IDLE** = 1

**OFFLINE** = 6

**SHUTDOWN** = 5

**SHUTTINGDOWN** = 4

**STEADY** = 3

**decisionengine.framework.taskmanager.SourceProductCache module**

**class** decisionengine.framework.taskmanager.SourceProductCache.**SourceProductCache**(*expected\_products*,  
*logger*)

Bases: object

**update**(*new\_data*)

**decisionengine.framework.taskmanager.TaskManager module**

Task manager

**class** decisionengine.framework.taskmanager.TaskManager.**TaskManager**(*name*, *workers*, *dataspace*,  
*expected\_products*,  
*exchange*, *broker\_url*,  
*routing\_keys*)

Bases: object

Task manager

**data\_block\_put**(*data*, *header*, *data\_block*)

Put data into data block

**Parameters**

- **data** (dict) – key, value pairs
- **header** (Header) – data header
- **data\_block** (DataBlock) – data block

**decision\_cycle**()

Decision cycle to be run periodically (by trigger)

**get\_consumes**()

**get\_loglevel**()

**get\_produces**()

**get\_state**()

**get\_state\_name**()

**get\_state\_value**()

**run\_cycle**(*messages*)

**run\_cycles**()

Task manager main loop

**run\_logic\_engine**(*data\_block*)

Run Logic Engine.

**Parameters**

**data\_block** (DataBlock) – data block

**run\_publishers**(*actions, data\_block*)

Run Publishers in main process.

**Parameters**

**data\_block** (DataBlock) – data block

**run\_transform**(*worker, data\_block*)

Run a transform

**Parameters**

- **worker** (Worker) – Transform worker
- **data\_block** (DataBlock) – data block

**run\_transforms**(*data\_block=None*)

Run transforms. So far in main process.

**Parameters**

**data\_block** (DataBlock) – data block

**set\_loglevel\_value**(*log\_level*)

Assumes log\_level is a string corresponding to the supported logging-module levels.

**take\_offline**()

Adjust status to stop the decision cycles and bring the task manager offline

## decisionengine.framework.taskmanager.module\_graph module

Ensure no circularities in produces and consumes.

**class** decisionengine.framework.taskmanager.module\_graph.**Worker**(*key, conf\_dict, base\_class, channel\_name*)

Bases: object

Provides interface to loadable modules and events to synchronise execution

decisionengine.framework.taskmanager.module\_graph.**\_consumed\_products**(\**worker\_lists*)

decisionengine.framework.taskmanager.module\_graph.**\_create\_module\_instance**(*config\_dict, base\_class, channel\_name*)

Create instance of dynamically loaded module

decisionengine.framework.taskmanager.module\_graph.**\_find\_only\_one\_subclass**(*module, base\_class*)

Search through module looking for only one subclass of the supplied base\_class

decisionengine.framework.taskmanager.module\_graph.**\_make\_workers\_for**(*configs, base\_class, channel\_name*)

decisionengine.framework.taskmanager.module\_graph.**\_produced\_products**(\**worker\_lists*)

decisionengine.framework.taskmanager.module\_graph.**channel\_workers**(*channel\_name, channel\_config, logger*)



`decisionengine.framework.taskmanager.module_graph.ensure_no_circularities`(*sources, transforms, publishers*)

Ensures no circularities among data products.

`decisionengine.framework.taskmanager.module_graph.source_products`(*source\_workers*)

`decisionengine.framework.taskmanager.module_graph.validated_workflow`(*channel\_name, sources, channel\_config, logger=<BoundLoggerLazyProxy(logger=None, wrapper\_class=None, processors=None, context\_class=None, initial\_values={}, logger\_factory\_args=())>*)

## Module contents

### decisionengine.framework.tests package

#### Submodules

#### decisionengine.framework.tests.ABTransform module

`class decisionengine.framework.tests.ABTransform.ABTransform`(*module\_parameters, \*args, \*\*kwargs*)

Bases: *Transform*

`_consumes` = {'B': None}

`_produces` = {'A': None}

#### decisionengine.framework.tests.BATransform module

`class decisionengine.framework.tests.BATransform.BATransform`(*module\_parameters, \*args, \*\*kwargs*)

Bases: *Transform*

`_consumes` = {'A': None}

`_produces` = {'B': None}

#### decisionengine.framework.tests.DynamicPublisher module

`class decisionengine.framework.tests.DynamicPublisher.DynamicPublisher`(*config*)

Bases: *Publisher*

`_supported_config` = {'consumes': (<class 'list'>, None, None), 'expects': (<class 'int'>, None, None)}

`publisher`(*data\_block*)

**decisionengine.framework.tests.DynamicSource module**

```
class decisionengine.framework.tests.DynamicSource.DynamicSource(config)
    Bases: Source
    _supported_config = {'data_product_name': (<class 'str'>, None, None)}
    acquire()
```

**decisionengine.framework.tests.DynamicTransform module**

```
class decisionengine.framework.tests.DynamicTransform.DynamicTransform(config)
    Bases: Transform
    _supported_config = {'consumes': (<class 'list'>, None, None), 'data_product_name':
    (<class 'str'>, None, None)}
    transform(data_block)
```

**decisionengine.framework.tests.ErrorOnAcquire module**

```
class decisionengine.framework.tests.ErrorOnAcquire.ErrorOnAcquire(config)
    Bases: Source
    _produces = {'_placeholder': None}
    acquire()
```

**decisionengine.framework.tests.FailingPublisher module**

```
class decisionengine.framework.tests.FailingPublisher.FailingPublisher(module_parameters,
                                                                    *args, **kwargs)
    Bases: Publisher
    _consumes = {'bar': None}
    publish(data_block)
```

**decisionengine.framework.tests.FailingSourceNOP module**

```
class decisionengine.framework.tests.FailingSourceNOP.SourceWithMissingProduces(set_of_parameters)
    Bases: Source
```

**decisionengine.framework.tests.IntSource module**

```

class decisionengine.framework.tests.IntSource.IntSource(config)
    Bases: Source
    _produces = {'int_value': <class 'int'>}
    _supported_config = {'int_value': (<class 'int'>, None, None)}
    acquire()

```

**decisionengine.framework.tests.ModuleProgramOptions module**

```

class decisionengine.framework.tests.ModuleProgramOptions.AcquireWithConfig(name)
    Bases: object
    test(byte_str, expected_stderr='')

class decisionengine.framework.tests.ModuleProgramOptions.AcquireWithSampleConfig(name)
    Bases: object
    test()

class decisionengine.framework.tests.ModuleProgramOptions.ConfigTemplate(name)
    Bases: object
    test(has_comments=False)

class decisionengine.framework.tests.ModuleProgramOptions.Describe(name)
    Bases: object
    test(consumes=None, produces=None)

class decisionengine.framework.tests.ModuleProgramOptions.DescribeAlias(alias, original)
    Bases: object
    test()

class decisionengine.framework.tests.ModuleProgramOptions.Help(name)
    Bases: object
    test(has_sample_config=False)

decisionengine.framework.tests.ModuleProgramOptions._expected_acquire_result(name, con-
                                                                              fig_file=None,
                                                                              multiplier=1,
                                                                              chan-
                                                                              nel_name='test1')

decisionengine.framework.tests.ModuleProgramOptions._expected_config_template(name)

decisionengine.framework.tests.ModuleProgramOptions._expected_config_template_with_comments(name)

decisionengine.framework.tests.ModuleProgramOptions._expected_help(name)

decisionengine.framework.tests.ModuleProgramOptions._expected_source_help(name,
                                                                              has_sample_config=False)

```

```
decisionengine.framework.tests.ModuleProgramOptions._normalize(string)
```

```
decisionengine.framework.tests.ModuleProgramOptions._run_as_main(name, *program_options)
```

### decisionengine.framework.tests.PublisherNOP module

```
class decisionengine.framework.tests.PublisherNOP.PublisherNOP(module_parameters, *args,
                                                                **kwargs)
```

Bases: *Publisher*

```
_consumes = {'bar': <class 'pandas.core.frame.DataFrame'>}
```

```
publish(data_block)
```

### decisionengine.framework.tests.PublisherWithMissingConsumes module

```
class decisionengine.framework.tests.PublisherWithMissingConsumes.PublisherWithMissingConsumes(set_of_parameters)
```

Bases: *Publisher*

### decisionengine.framework.tests.SourceAlias module

### decisionengine.framework.tests.SourceNOP module

```
class decisionengine.framework.tests.SourceNOP.SourceNOP(config)
```

Bases: *Source*

```
_produces = {'foo': <class 'pandas.core.frame.DataFrame'>}
```

```
acquire()
```

### decisionengine.framework.tests.SourceWithSampleConfigNOP module

```
class decisionengine.framework.tests.SourceWithSampleConfigNOP.SourceWithSampleConfigNOP(config)
```

Bases: *Source*

```
_produces = {'foo': <class 'pandas.core.frame.DataFrame'>}
```

```
_supported_config = {'channel_name': (<class 'str'>, None, None), 'multiplier':  
(<class 'int'>, None, None)}
```

```
acquire()
```

### decisionengine.framework.tests.SupportsConfigPublisher module

```
class decisionengine.framework.tests.SupportsConfigPublisher.SupportsConfig(set_of_parameters)
    Bases: Publisher
    _supported_config = {'comment': (<class 'str'>, None, 'Single-line comment'),
        'comment_with_nl': (<class 'str'>, None, 'Comment with newline\n'), 'convert_to':
        (<class 'int'>, 3, None), 'default_only': (<class 'float'>, 2.5, None), 'no_type':
        (None, None, None), 'only_type': (<class 'int'>, None, None)}
```

### decisionengine.framework.tests.TransformNOP module

```
class decisionengine.framework.tests.TransformNOP.TransformNOP(module_parameters, *args,
                                                                **kwargs)
    Bases: Transform
    _consumes = {'foo': <class 'pandas.core.frame.DataFrame'>}
    _produces = {'bar': <class 'pandas.core.frame.DataFrame'>}
    transform(data_block)
```

### decisionengine.framework.tests.TransformWithMissingProducesConsumes module

```
class decisionengine.framework.tests.TransformWithMissingProducesConsumes.TransformWithMissingProducesConsumesC
    Bases: Transform
    transform(data_block)
```

### decisionengine.framework.tests.WriteToDisk module

Special publisher used to register publish calls with an external file.

It is difficult to interact with individual publishers while testing a workflow. The WriteToDisk publisher therefore writes to an external file that can be read by a test. Ideally, we would implement a system so that the test and any instance of the WriteToDisk class are passed the same file-name string. Unfortunately, this is non-trivial to achieve without adjusting the behavior of the decision-engine server itself. We therefore choose the following abstruse logic:

- WriteToDisk creates a temporary file and broadcasts its name to STDOUT. Note that this temporary file must be uniquely named as multiple tests can use WriteToDisk in parallel.
- Capture STDOUT in the DETestWorker class.
- Pass STDOUT to the 'wait\_for\_n\_writes' which will wait until the number 'n' appears in the file.

```
class decisionengine.framework.tests.WriteToDisk.WriteToDisk(config)
    Bases: Publisher
    _supported_config = {'consumes': (<class 'list'>, None, None), 'filename': (<class
    'str'>, None, None)}
    publish(data_block)
```

```
decisionengine.framework.tests.WriteToDisk.wait_for_n_writes(stdout, n)
```

## decisionengine.framework.tests.fixtures module

defaults for pytest

`decisionengine.framework.tests.fixtures.DEServer`(*conf\_path=None, conf\_override=None, channel\_conf\_path=None, channel\_conf\_override=None, host='127.0.0.1', port=None, make\_conf\_dirs\_if\_missing=False, block\_until\_startup\_complete=True*)

A DE Server using a private database

`decisionengine.framework.tests.fixtures.PG_DE_DB_WITHOUT_SCHEMA`(*request: FixtureRequest*) → connection

Fixture factory for PostgreSQL.

### Parameters

**request** – fixture request object

### Returns

postgresql client

`decisionengine.framework.tests.fixtures.PG_PROG`(*request: FixtureRequest, tmp\_path\_factory: TempPathFactory*) → Iterator[PostgreSQLExecutor]

Process fixture for PostgreSQL.

### Parameters

- **request** – fixture request object
- **tmp\_path\_factory** – temporary path object (fixture)

### Returns

tcp executor

`decisionengine.framework.tests.fixtures.SQLALCHEMY_PG_WITH_SCHEMA`(*PG\_DE\_DB\_WITHOUT\_SCHEMA*)

Get a blank database from `pytest_postgresql`. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

`decisionengine.framework.tests.fixtures.SQLALCHEMY_TEMPFILE_SQLITE`(*tmp\_path*)

Setup an SQLite database with the `pytest tmp_path` fixture. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

## decisionengine.framework.tests.test\_client\_errors module

Fixture based DE Server tests of the sample config

`decisionengine.framework.tests.test_client_errors.test_client_cannot_wait_on_bad_state`(*deserver*)

Verify wait is for a valid state

### **decisionengine.framework.tests.test\_client\_server module**

Fixture based DE Server for the de-client tests

```
decisionengine.framework.tests.test_client_server.test_client_get_loglevel(deserver)
```

```
decisionengine.framework.tests.test_client_server.test_client_print_product(deserver)
```

```
decisionengine.framework.tests.test_client_server.test_client_set_loglevel(deserver)
```

```
decisionengine.framework.tests.test_client_server.test_client_status_msg_to_logger(deserver,  
                                                                                    caplog)
```

Make sure the actual client console call goes to a logging destination

### **decisionengine.framework.tests.test\_combined\_channels module**

```
decisionengine.framework.tests.test_combined_channels.test_combined_channels(deserver)
```

```
decisionengine.framework.tests.test_combined_channels.test_combined_channels_3g(deserver_combined)
```

### **decisionengine.framework.tests.test\_defaults module**

Fixture based DE Server tests of the sample config

```
decisionengine.framework.tests.test_defaults.test_defaults(deserver)
```

### **decisionengine.framework.tests.test\_dynamic\_test\_modules module**

```
decisionengine.framework.tests.test_dynamic_test_modules.test_dynamic_publisher()
```

```
decisionengine.framework.tests.test_dynamic_test_modules.test_dynamic_source()
```

```
decisionengine.framework.tests.test_dynamic_test_modules.test_dynamic_transform()
```

### **decisionengine.framework.tests.test\_empty\_config module**

Fixture based DE Server tests of adding a channel later on

```
decisionengine.framework.tests.test_empty_config.test_client_can_start_one_channel_added_after_startup()
```

Verify client can start a single channel

### **decisionengine.framework.tests.test\_error\_on\_acquire module**

```
decisionengine.framework.tests.test_error_on_acquire.test_error_on_acquire(deserver)
```

### **decisionengine.framework.tests.test\_module\_program\_options module**

```
decisionengine.framework.tests.test_module_program_options.test_acquire_for_sources()
decisionengine.framework.tests.test_module_program_options.test_config_templates()
decisionengine.framework.tests.test_module_program_options.test_descriptions()
decisionengine.framework.tests.test_module_program_options.test_help()
decisionengine.framework.tests.test_module_program_options.test_module_alias()
```

### **decisionengine.framework.tests.test\_query\_tool\_server module**

Fixture based DE Server for the de-query-tool tests

```
decisionengine.framework.tests.test_query_tool_server.test_query_tool(deserver)
```

### **decisionengine.framework.tests.test\_reaper module**

Fixture based DE Server for the reaper tests

```
decisionengine.framework.tests.test_reaper.test_client_can_get_de_server_reaper_status(deserver)
    Verify reaper status
```

### **decisionengine.framework.tests.test\_same\_source\_types module**

```
decisionengine.framework.tests.test_same_source_types.test_same_source_types_separate_channels(deserver)
```

### **decisionengine.framework.tests.test\_sample\_config module**

Fixture based DE Server tests of the defaults

```
decisionengine.framework.tests.test_sample_config.stopped_channel_opts(timeout=1)
decisionengine.framework.tests.test_sample_config.test_client_can_get_de_server_status(deserver)
decisionengine.framework.tests.test_sample_config.test_client_can_kill_one_channel(deserver)
decisionengine.framework.tests.test_sample_config.test_client_can_restart_all_channels(deserver)
    Verify client can get channel products even when none are run
decisionengine.framework.tests.test_sample_config.test_client_can_restart_one_channel(deserver)
    Verify client can restart a single channel
decisionengine.framework.tests.test_sample_config.test_client_logger_level(deserver)
decisionengine.framework.tests.test_sample_config.test_client_non_real_channel(deserver)
```



### decisionengine.framework.tests.test\_shared\_sources module

decisionengine.framework.tests.test\_shared\_sources.**record\_that\_matches**(*substring, records*)

decisionengine.framework.tests.test\_shared\_sources.**test\_conflicting\_source\_configurations**(*deserver\_conflict, caplog*)

decisionengine.framework.tests.test\_shared\_sources.**test\_shared\_source**(*deserver\_shared, caplog*)

### decisionengine.framework.tests.test\_start\_with\_bad\_channels module

Fixture based DE Server tests of invalid channel configs

decisionengine.framework.tests.test\_start\_with\_bad\_channels.**\_consumes\_not\_subset**(*test\_str*)

decisionengine.framework.tests.test\_start\_with\_bad\_channels.**\_expected\_circularity**(*test\_str*)

decisionengine.framework.tests.test\_start\_with\_bad\_channels.**\_missing\_consumes**(*name*)

decisionengine.framework.tests.test\_start\_with\_bad\_channels.**\_missing\_produces**(*name*)

decisionengine.framework.tests.test\_start\_with\_bad\_channels.**test\_client\_can\_get\_products\_no\_channels**(*deserver\_no\_channels, caplog*)

Verify client can get channel products even when none are run

### decisionengine.framework.tests.test\_status\_during\_startup module

decisionengine.framework.tests.test\_status\_during\_startup.**test\_status\_during\_startup**(*deserver\_no\_wait*)

## Module contents

### decisionengine.framework.util package

#### Submodules

### decisionengine.framework.util.countdown module

**class** decisionengine.framework.util.countdown.**Countdown**(*wait\_up\_to*)

Bases: object

Countdown is a context manager that keeps track of elapsed time.

It is designed to be used for cases where a sequence of operations should not take longer than a specified period of time. This is done by occasionally querying the 'time\_left' attribute (e.g.):

countdown = Countdown(wait\_up\_to=10) for p in processes:

**with** countdown:

        rc = p.join(countdown.time\_left) if rc is None:

            p.terminate()

In the above example, the time it takes to shutdown all processes should not exceed 10 seconds. Upon entering the countdown context, a timer starts. Once that context is exited, the timer stops and the elapsed time is subtracted from the initial 'wait\_up\_to' value. If it takes 10 seconds for the first process to join, then the 'time\_left' value will be 0 when joining all subsequent processes. In this way, the entire sequence of operations is constrained to occur in roughly 10 seconds.

### **decisionengine.framework.util.fs module**

`decisionengine.framework.util.fs.files_with_extensions(dir_path, *extensions)`

Return all files in `dir_path` that match the provided extensions.

If no extensions are given, then all files in `dir_path` are returned.

Results are sorted by channel name to ensure stable output.

### **decisionengine.framework.util.logparser module**

`decisionengine.framework.util.logparser.console_scripts_main(args_to_parse=None)`

This is the entry point for the setuptools auto generated scripts. Setuptools thinks a return from this function is an error message.

`decisionengine.framework.util.logparser.create_parser()`

`decisionengine.framework.util.logparser.execute_command_from_args(argsparsed, logfile=None, constraint=None)`

Parse the log file as requested.

#### **Parameters**

- **argsparsed** (*Namespace*) – Parsed arguments from `create_parser` in this file.
- **logfile** (*path*) – Log file path.
- **constraint** (*dict*) – Combined constraints dictionary

#### **Returns**

Output of the command.

#### **Return type**

str

`decisionengine.framework.util.logparser.main(args_to_parse=None)`

Main function for logparser

#### **Parameters**

- **args\_to\_parse** (*list, optional*) – If you pass a list of args, they will be used instead of `sys.argv`.
- **None.** (*Defaults to*) –

#### **Returns**

Parsing result

#### **Return type**

str

`decisionengine.framework.util.logparser.matches_constraint`(*constraint*, *linelist*, *linedict*)

Return True if all constraints are marched

**Parameters**

- **constraint** (*dict* / *None*) – combined constraints
- **linelist** (*list*) – List of line fields
- **linedict** (*dict*) – Dictionary with structured elements

**Returns**

True is all constraints are matched, False otherwise

**Return type**

bool

`decisionengine.framework.util.logparser.parse_constraints`(*constraints*, *loglevel*=*None*)

Parse and combine the constraints

**Parameters**

- **constraints** (*list* / *None*) – List of constraints
- **loglevel** (*str*) – Logging level, e.g. DEBUG, INFO, ...

**Returns**

combined constraint dictionary

**Return type**

dict

## decisionengine.framework.util.metrics module

```
class decisionengine.framework.util.metrics.Counter(name: str, documentation: str, labelnames:
    ~typing.Iterable[str] = (), namespace: str = "",
    subsystem: str = "", unit: str = "", registry: ~typing.
    Optional[~prometheus_client.registry.CollectorRegistry]
    = <prometheus_client.registry.CollectorRegistry
    object>, _labelvalues:
    ~typing.Optional[~typing.Sequence[str]] =
    None)
```

Bases: Counter

`_abc_impl = <_abc._abc_data object>`

```
class decisionengine.framework.util.metrics.Gauge(*args, **kwargs)
```

Bases: Gauge

Override prometheus client Gauge so that multiprocessing\_mode 'liveall' is the default as opposed to 'all'

`_DEFAULT_MULTIPROC_MODE = 'liveall'`

`__determine_multiprocess_mode_existence(*args, **kwargs)`

`_abc_impl = <_abc._abc_data object>`

```
class decisionengine.framework.util.metrics.Histogram(name: str, documentation: str, labelnames:
    ~typing.Iterable[str] = (), namespace: str = "",
    subsystem: str = "", unit: str = "", registry: ~typing.Optional[~prometheus_client.registry.CollectorRegistry]
    =
    <prometheus_client.registry.CollectorRegistry
    object>, _labelvalues:
    ~typing.Optional[~typing.Sequence[str]] =
    None, buckets:
    ~typing.Sequence[~typing.Union[float, str]] =
    (0.005, 0.01, 0.025, 0.05, 0.075, 0.1, 0.25, 0.5,
    0.75, 1.0, 2.5, 5.0, 7.5, 10.0, inf))
```

Bases: Histogram

```
_abc_impl = <_abc._abc_data object>
```

```
class decisionengine.framework.util.metrics.Summary(name: str, documentation: str, labelnames:
    ~typing.Iterable[str] = (), namespace: str = "",
    subsystem: str = "", unit: str = "", registry: ~typing.Optional[~prometheus_client.registry.CollectorRegistry]
    = <prometheus_client.registry.CollectorRegistry
    object>, _labelvalues:
    ~typing.Optional[~typing.Sequence[str]] =
    None)
```

Bases: Summary

```
_abc_impl = <_abc._abc_data object>
```

```
decisionengine.framework.util.metrics.display_metrics()
```

## decisionengine.framework.util.reaper module

A stand-alone script purges data in database older than specified in configuration. Configuration file has to have this bit added:

```
{
    "dataspace"
    [{ "retention_interval_in_days"[365,]
        "datasource": { ... }
    }
}
```

Can be used in a cron job.

```
decisionengine.framework.util.reaper.main()
```

## decisionengine.framework.util.redis\_stats module

decisionengine.framework.util.redis\_stats.**redis\_stats**(*broker\_url, exchange*)

## decisionengine.framework.util.singleton module

**class** decisionengine.framework.util.singleton.ScopedSingleton

Bases: [Singleton](#)

Singleton pattern using Metaclass with weak refs

**\_instances** = <WeakValueDictionary>

**class** decisionengine.framework.util.singleton.ScopedSingletonABC(*name, bases, namespace, \*\*kwargs*)

Bases: ABCMeta, [ScopedSingleton](#)

**class** decisionengine.framework.util.singleton.Singleton

Bases: type

Singleton pattern using Metaclass with strong refs

**\_instances** = {}

**class** decisionengine.framework.util.singleton.SingletonABC(*name, bases, namespace, \*\*kwargs*)

Bases: ABCMeta, [Singleton](#)

## decisionengine.framework.util.sockets module

decisionengine.framework.util.sockets.**get\_random\_port**()

## decisionengine.framework.util.subclasses module

decisionengine.framework.util.subclasses.**\_derived\_class**(*cls, base\_class*)

Only matches subclasses that are not equal to the base class.

decisionengine.framework.util.subclasses.**all\_subclasses**(*module, base\_class*)

Return all of a module's subclasses of the given base class.

## Module contents

### Submodules

## decisionengine.framework.about module

PEP-0396 provides instructions for providing module versions While we are at it, add a few other useful bits

**decisionengine.framework.version module**

**Module contents**

**decisionengine.tests package**

**Submodules**

**decisionengine.tests.test\_framework\_package module**

Make sure decisionengine.framework is a valid python package

`decisionengine.tests.test_framework_package.test_can_import()`

**Module contents**

**Module contents**

## 5.2 Indices and tables

- [genindex](#)
- [modindex](#)
- [search](#)

## INDICES AND TABLES

- `genindex`
- `modindex`
- `search`





## PYTHON MODULE INDEX

### d

[decisionengine](#), 114  
[decisionengine.framework](#), 114  
[decisionengine.framework.about](#), 113  
[decisionengine.framework.config](#), 49  
[decisionengine.framework.config.ChannelConfigHandler](#), 47  
[decisionengine.framework.config.policies](#), 48  
[decisionengine.framework.config.tests](#), 47  
[decisionengine.framework.config.tests.test\\_config](#), 45  
[decisionengine.framework.config.tests.test\\_de\\_std](#), 46  
[decisionengine.framework.config.tests.test\\_policies](#), 47  
[decisionengine.framework.config.ValidConfig](#), 48  
[decisionengine.framework.dataspace](#), 77  
[decisionengine.framework.dataspace.datablock](#), 70  
[decisionengine.framework.dataspace.datasource](#), 73  
[decisionengine.framework.dataspace.datasources](#), 66  
[decisionengine.framework.dataspace.datasources.null](#), 64  
[decisionengine.framework.dataspace.datasources.sqlalchemy\\_ds](#), 57  
[decisionengine.framework.dataspace.datasources.sqlalchemy\\_ds.datasource\\_api](#), 49  
[decisionengine.framework.dataspace.datasources.sqlalchemy\\_ds.db\\_schema](#), 54  
[decisionengine.framework.dataspace.datasources.sqlalchemy\\_ds.utils](#), 57  
[decisionengine.framework.dataspace.datasources.tests](#), 64  
[decisionengine.framework.dataspace.datasources.tests.fixtures](#), 61  
[decisionengine.framework.dataspace.datasources.tests.test\\_datasource\\_api](#), 62  
[decisionengine.framework.dataspace.dataspace](#), 75  
[decisionengine.framework.dataspace.maintain](#), 76  
[decisionengine.framework.dataspace.tests](#), 70  
[decisionengine.framework.dataspace.tests.fixtures](#), 66  
[decisionengine.framework.dataspace.tests.test\\_datablock](#), 68  
[decisionengine.framework.dataspace.tests.test\\_datablock\\_zl](#), 69  
[decisionengine.framework.dataspace.tests.test\\_datasource](#), 69  
[decisionengine.framework.dataspace.tests.test\\_dataspace](#), 69  
[decisionengine.framework.dataspace.tests.test\\_Reaper](#), 67  
[decisionengine.framework.engine](#), 86  
[decisionengine.framework.engine.ChannelWorkers](#), 79  
[decisionengine.framework.engine.ClientMessageReceiver](#), 81  
[decisionengine.framework.engine.de\\_client](#), 85  
[decisionengine.framework.engine.de\\_query\\_tool](#), 85  
[decisionengine.framework.engine.DecisionEngine](#), 81  
[decisionengine.framework.engine.SourceWorkers](#), 84  
[decisionengine.framework.engine.tests](#), 79  
[decisionengine.framework.engine.tests.fixtures](#), 77  
[decisionengine.framework.engine.tests.test\\_ChannelWorkers](#), 78  
[decisionengine.framework.engine.tests.test\\_client\\_only](#), 78  
[decisionengine.framework.engine.tests.test\\_query\\_tool\\_only](#), 79  
[decisionengine.framework.engine.tests.test\\_SourceWorkers](#), 78  
[decisionengine.framework.engine.tests.test\\_startup](#), 79  
[decisionengine.framework.engine.tests.test\\_verify\\_redis\\_se](#), 79

decisionengine.framework.logicengine, 91  
decisionengine.framework.logicengine.BooleanExpression, 88  
decisionengine.framework.logicengine.FactLookup, 88  
decisionengine.framework.logicengine.LogicEngine, 89  
decisionengine.framework.logicengine.Rule, 90  
decisionengine.framework.logicengine.RuleEngine, 90  
decisionengine.framework.logicengine.tests, 88  
decisionengine.framework.logicengine.tests.test\_bool\_function\_name, 86  
decisionengine.framework.logicengine.tests.test\_cascaded\_rules, 86  
decisionengine.framework.logicengine.tests.test\_decisionengine, 86  
decisionengine.framework.logicengine.tests.test\_dispatcher\_framework, 87  
decisionengine.framework.logicengine.tests.test\_factengine, 87  
decisionengine.framework.logicengine.tests.test\_factengine, 87  
decisionengine.framework.logicengine.tests.test\_parser\_fact, 87  
decisionengine.framework.logicengine.tests.test\_ruleengine, 88  
decisionengine.framework.logicengine.tests.test\_simple\_configuration, 88  
decisionengine.framework.modules, 97  
decisionengine.framework.modules.de\_logger, 95  
decisionengine.framework.modules.describe, 96  
decisionengine.framework.modules.EmptySource, 93  
decisionengine.framework.modules.logging\_configDict, 96  
decisionengine.framework.modules.Module, 93  
decisionengine.framework.modules.print\_descriptions, 96  
decisionengine.framework.modules.Publisher, 94  
decisionengine.framework.modules.QueueLogger, 94  
decisionengine.framework.modules.Source, 94  
decisionengine.framework.modules.tests, 93  
decisionengine.framework.modules.tests.test\_decisionengine, 92  
decisionengine.framework.modules.tests.test\_EmptySource, 91  
decisionengine.framework.modules.tests.test\_Modules, 91  
decisionengine.framework.modules.tests.test\_modules, 91  
decisionengine.framework.modules.tests.test\_Publisher, 92  
decisionengine.framework.modules.tests.test\_QueueLogger, 91  
decisionengine.framework.modules.tests.test\_Source, 92  
decisionengine.framework.modules.tests.test\_Transform, 92  
decisionengine.framework.modules.tests.test\_translate\_product\_name, 93  
decisionengine.framework.modules.Transform, 95  
decisionengine.framework.modules.translate\_product\_name, 97  
decisionengine.framework.taskmanager, 101  
decisionengine.framework.taskmanager.LatestMessages, 97  
decisionengine.framework.taskmanager.module\_graph, 100  
decisionengine.framework.taskmanager.ProcessingState, 97  
decisionengine.framework.taskmanager.SourceProductCache, 99  
decisionengine.framework.taskmanager.TaskManager, 99  
decisionengine.framework.tests, 109  
decisionengine.framework.tests.ABTransform, 100  
decisionengine.framework.tests.BATransform, 101  
decisionengine.framework.tests.DynamicPublisher, 101  
decisionengine.framework.tests.DynamicSource, 102  
decisionengine.framework.tests.DynamicTransform, 102  
decisionengine.framework.tests.ErrorOnAcquire, 102  
decisionengine.framework.tests.FailingPublisher, 102  
decisionengine.framework.tests.FailingSourceNOP, 102  
decisionengine.framework.tests.fixtures, 106  
decisionengine.framework.tests.IntSource, 103  
decisionengine.framework.tests.ModuleProgramOptions, 103  
decisionengine.framework.tests.PublisherNOP, 104  
decisionengine.framework.tests.PublisherWithMissingConsumer, 104  
decisionengine.framework.tests.SourceAlias, 104  
decisionengine.framework.tests.SourceNOP, 104

decisionengine.framework.tests.SourceWithSampleConfigNOP, 104  
decisionengine.framework.tests.SupportsConfigPublisher, 105  
decisionengine.framework.tests.test\_client\_errors, 106  
decisionengine.framework.tests.test\_client\_server, 107  
decisionengine.framework.tests.test\_combined\_channels, 107  
decisionengine.framework.tests.test\_defaults, 107  
decisionengine.framework.tests.test\_dynamic\_test\_modules, 107  
decisionengine.framework.tests.test\_empty\_config, 107  
decisionengine.framework.tests.test\_error\_on\_acquire, 107  
decisionengine.framework.tests.test\_module\_program\_options, 108  
decisionengine.framework.tests.test\_query\_tool\_server, 108  
decisionengine.framework.tests.test\_reaper, 108  
decisionengine.framework.tests.test\_same\_source\_types, 108  
decisionengine.framework.tests.test\_sample\_config, 108  
decisionengine.framework.tests.test\_shared\_sources, 109  
decisionengine.framework.tests.test\_start\_with\_bad\_channels, 109  
decisionengine.framework.tests.test\_status\_during\_startup, 109  
decisionengine.framework.tests.TransformNOP, 105  
decisionengine.framework.tests.TransformWithMissingProducesConsumes, 105  
decisionengine.framework.tests.WriteToDisk, 105  
decisionengine.framework.util, 113  
decisionengine.framework.util.countdown, 109  
decisionengine.framework.util.fs, 110  
decisionengine.framework.util.logparser, 110  
decisionengine.framework.util.metrics, 111  
decisionengine.framework.util.reaper, 112  
decisionengine.framework.util.redis\_stats, 113  
decisionengine.framework.util.singleton, 113  
decisionengine.framework.util.sockets, 113  
decisionengine.framework.util.subclasses, 113  
decisionengine.framework.version, 114  
decisionengine.tests, 114  
decisionengine.tests.test\_framework\_package,



## INDEX

### Symbols

<code>_DEFAULT_MULTIPROC_MODE</code> (decisionengine.framework.util.metrics.Gauge attribute), 111	<code>_check_metrics_env()</code> (in module decisionengine.framework.engine.DecisionEngine), 83
<code>__determine_multiprocess_mode_existence()</code> (decisionengine.framework.util.metrics.Gauge method), 111	<code>_check_override()</code> (in module decisionengine.framework.engine.tests.test_startup), 79
<code>__insert()</code> (decisionengine.framework.dataspace.datablock.DataBlock method), 70	<code>_config_from_file()</code> (in module decisionengine.framework.config.ValidConfig), 48
<code>__update()</code> (decisionengine.framework.dataspace.datablock.DataBlock method), 70	<code>consumed_products()</code> (in module decisionengine.framework.taskmanager.module_graph), 100
<code>_abc_impl</code> (decisionengine.framework.config.ValidConfig.ValidConfig attribute), 48	<code>_consumes</code> (decisionengine.framework.modules.Publisher.Publisher attribute), 94
<code>_abc_impl</code> (decisionengine.framework.dataspace.datablock.Header attribute), 72	<code>_consumes</code> (decisionengine.framework.modules.Transform.Transform attribute), 95
<code>_abc_impl</code> (decisionengine.framework.dataspace.datablock.Metadata attribute), 72	<code>_consumes</code> (decisionengine.framework.tests.ABTransform.ABTransform attribute), 101
<code>_abc_impl</code> (decisionengine.framework.dataspace.datasource.DataSource attribute), 73	<code>_consumes</code> (decisionengine.framework.tests.BATransform.BATransform attribute), 101
<code>_abc_impl</code> (decisionengine.framework.dataspace.datasources.null.NullDataSource attribute), 64	<code>_consumes</code> (decisionengine.framework.tests.FailingPublisher.FailingPublisher attribute), 102
<code>_abc_impl</code> (decisionengine.framework.dataspace.datasources.sqlalchemy_us.SQLAlchemyDS attribute), 57	<code>_consumes</code> (decisionengine.framework.tests.PublisherNOP.PublisherNOP attribute), 104
<code>_abc_impl</code> (decisionengine.framework.dataspace.datasources.sqlalchemy_us.datasource_api.SQLAlchemyDS attribute), 50	<code>_consumes</code> (decisionengine.framework.tests.TransformNOP.TransformNOP attribute), 105
<code>_abc_impl</code> (decisionengine.framework.util.metrics.Counter attribute), 111	<code>_consumes_not_subset()</code> (in module decisionengine.framework.tests.test_start_with_bad_channels), 109
<code>_abc_impl</code> (decisionengine.framework.util.metrics.Gauge attribute), 111	<code>create_de_server()</code> (in module decisionengine.framework.engine.DecisionEngine), 83
<code>_abc_impl</code> (decisionengine.framework.util.metrics.Histogram attribute), 112	<code>_create_facts_dataframe()</code> (decisionengine.framework.logicengine.LogicEngine.LogicEngine method), 89
<code>_abc_impl</code> (decisionengine.framework.util.metrics.Summary attribute), 112	<code>_create_module_instance()</code> (in module decisionengine.framework.taskmanager.module_graph), 100
<code>_channel_config_dir()</code> (in module decisionengine.framework.config.tests.test_config), 45	<code>_dataframe_to_column_names()</code> (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 81
<code>_channel_preamble()</code> (in module decisionengine.framework.engine.DecisionEngine), 83	<code>_dataframe_to_csv()</code> (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 81
<code>_check_keys()</code> (in module decisionengine.framework.config.ChannelConfigHandler), 47	

`nengine.framework.engine.DecisionEngine.DecisionEngine()` (`decisionengine.framework.taskmanager.LatestMessages.LatestMessages` attribute), 81  
`_dataframe_to_json()` (`decisionengine.framework.engine.DecisionEngine.DecisionEngine` method), 81  
`_dataframe_to_table()` (`decisionengine.framework.engine.DecisionEngine.DecisionEngine` method), 81  
`_dataframe_to_vertical_tables()` (`decisionengine.framework.engine.DecisionEngine.DecisionEngine` method), 81  
`_derived_class()` (`in module decisionengine.framework.util.subclasses`), 113  
`_dispatch()` (`decisionengine.framework.engine.DecisionEngine.DecisionEngine` method), 81  
`_expected_acquire_result()` (`in module decisionengine.framework.tests.ModuleProgramOptions`), 103  
`_expected_circularity()` (`in module decisionengine.framework.tests.test_start_with_bad_channels`), 109  
`_expected_config_template()` (`in module decisionengine.framework.tests.ModuleProgramOptions`), 103  
`_expected_config_template_with_comments()` (`in module decisionengine.framework.tests.ModuleProgramOptions`), 103  
`_expected_help()` (`in module decisionengine.framework.tests.ModuleProgramOptions`), 103  
`_expected_source_help()` (`in module decisionengine.framework.tests.ModuleProgramOptions`), 103  
`_find_only_one_subclass()` (`in module decisionengine.framework.taskmanager.module_graph`), 100  
`_get_de_conf_manager()` (`in module decisionengine.framework.engine.DecisionEngine`), 83  
`_get_global_config()` (`in module decisionengine.framework.engine.DecisionEngine`), 83  
`_global_config_file()` (`in module decisionengine.framework.config.tests.test_config`), 45  
`_initial_start_channels()` (`in module decisionengine.framework.engine.DecisionEngine`), 83  
`_instances` (`decisionengine.framework.util.singleton.ScopeSingleton` attribute), 113  
`_instances` (`decisionengine.framework.util.singleton.Singleton` attribute), 113  
`_load_channel()` (`decisionengine.framework.config.ChannelConfigHandler.ChannelConfigHandler` method), 47  
`_make_de_logger()` (`in module decisionengine.framework.config.ChannelConfigHandler`), 47  
`_make_workers_for()` (`in module decisionengine.framework.taskmanager.module_graph`), 100  
`_missing_consumes()` (`in module decisionengine.framework.tests.test_start_with_bad_channels`), 109  
`_missing_produces()` (`in module decisionengine.framework.tests.test_start_with_bad_channels`), 109  
`_normalize()` (`in module decisionengine.framework.tests.ModuleProgramOptions`), 103  
`_par.default()` (`in module decisionengine.framework.modules.describe`), 96  
`_par_type()` (`in module decisionengine.framework.modules.describe`), 96  
`_print_comment()` (`in module decisionengine.framework.modules.print_description`), 96  
`_print_type()` (`in module decisionengine.framework.modules.print_description`), 96  
`_produced_products()` (`in module decisionengine.framework.taskmanager.module_graph`), 100  
`_produces` (`decisionengine.framework.modules.Source.Source` attribute), 94  
`_produces` (`decisionengine.framework.modules.Transform.Transform` attribute), 95  
`_produces` (`decisionengine.framework.tests.ABTransform.ABTransform` attribute), 101  
`_produces` (`decisionengine.framework.tests.BATransform.BATransform` attribute), 101  
`_produces` (`decisionengine.framework.tests.ErrorOnAcquire.ErrorOnAcquire` attribute), 102  
`_produces` (`decisionengine.framework.tests.IntSource.IntSource` attribute), 103  
`_produces` (`decisionengine.framework.tests.SourceNOP.SourceNOP` attribute), 104  
`_produces` (`decisionengine.framework.tests.SourceWithSampleConfigNOP.SourceWithSampleConfigNOP` attribute), 104  
`_produces` (`decisionengine.framework.tests.TransformNOP.TransformNOP` attribute), 105

[\\_queue\\_name\\_and\\_type\(\)](#) (in module `decisionengine.framework.engine.DecisionEngine`), 83  
[\\_reaper\\_loop\(\)](#) (decisionengine.framework.dataspace.maintain.Reaper method), 76  
[\\_receive\(\)](#) (decisionengine.framework.engine.ClientMessageReceiver and ClientMessageReceiver method), 81  
[\\_requests\\_in\\_flight\(\)](#) (in module `decisionengine.framework.engine.DecisionEngine`), 83  
[\\_run\\_as\\_main\(\)](#) (in module `decisionengine.framework.tests.ModuleProgramOptions`), 104  
[\\_sa\\_class\\_manager](#) (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db4schema.Dataprodut attribute), 54  
[\\_sa\\_class\\_manager](#) (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db4schema.Dataprodut attribute), 54  
[\\_sa\\_class\\_manager](#) (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db4schema.Dataprodut attribute), 55  
[\\_sa\\_class\\_manager](#) (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db4schema.Dataprodut attribute), 56  
[\\_sa\\_class\\_manager](#) (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db4schema.Dataprodut attribute), 56  
[\\_sa\\_registry](#) (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db4schema.Dataprodut attribute), 54  
[\\_setitem\(\)](#) (decisionengine.framework.dataspace.datablock.DataBlock method), 70  
[\\_spec\\_from\\_file\\_name\(\)](#) (in module `decisionengine.framework.modules.print_description`), 96  
[\\_start\\_de\\_server\(\)](#) (in module `decisionengine.framework.engine.DecisionEngine`), 83  
[\\_supported\\_config](#) (decisionengine.framework.modules.EmptySource.EmptySource attribute), 93  
[\\_supported\\_config](#) (decisionengine.framework.tests.DynamicPublisher.DynamicPublisher attribute), 101  
[\\_supported\\_config](#) (decisionengine.framework.tests.DynamicSource.DynamicSource attribute), 102  
[\\_supported\\_config](#) (decisionengine.framework.tests.DynamicTransform.DynamicTransform attribute), 102  
[\\_supported\\_config](#) (decisionengine.framework.tests.IntSource.IntSource attribute), 103  
[\\_supported\\_config](#) (decisionengine.framework.tests.SourceWithSampleConfigNOP.SourceWithSampleConfigNOP attribute), 104  
[\\_supported\\_config](#) (decisionengine.framework.tests.SupportsConfigPublisher.SupportsConfigPublisher attribute), 104  
[\\_supported\\_config](#) (decisionengine.framework.tests.WriteToDisk.WriteToDisk attribute), 105  
[\\_verify\\_redis\\_server\(\)](#) (in module `decisionengine.framework.engine.DecisionEngine`), 84  
[\\_verify\\_redis\\_url\(\)](#) (in module `decisionengine.framework.engine.DecisionEngine`), 84

## A

[ABTransform](#) (class in `decisionengine.framework.tests.ABTransform`), 101  
[access\(\)](#) (decisionengine.framework.engine.ChannelWorkers.ChannelWorkers method), 85  
[access\(\)](#) (decisionengine.framework.engine.SourceWorkers.SourceWorkers method), 85  
[accessed\\_by\\_another\\_thread\(\)](#) (decisionengine.framework.engine.ChannelWorkers.ChannelWorkers method), 80  
[acquired\\_schema\\_taskmanager](#) (decisionengine.framework.modules.EmptySource.EmptySource attribute), 93  
[acquire\(\)](#) (decisionengine.framework.modules.Source.Source method), 102  
[acquire\(\)](#) (decisionengine.framework.tests.DynamicSource.DynamicSource method), 102  
[acquire\(\)](#) (decisionengine.framework.tests.ErrorOnAcquire.ErrorOnAcquire method), 102  
[acquire\(\)](#) (decisionengine.framework.tests.IntSource.IntSource method), 103  
[acquire\(\)](#) (decisionengine.framework.tests.SourceNOP.SourceNOP method), 104  
[acquire\(\)](#) (decisionengine.framework.tests.SourceWithSampleConfigNOP.SourceWithSampleConfigNOP method), 104  
[acquire\\_with\\_config](#) (class in `decisionengine.framework.tests.ModuleProgramOptions`), 103  
[acquire\\_with\\_sample\\_config](#) (class in `decisionengine.framework.tests.ModuleProgramOptions`), 103  
[ACTIVE](#) (decisionengine.framework.taskmanager.ProcessingState.State attribute), 98  
[add\\_engine\\_pidguard\(\)](#) (in module `decisionengine.framework.dataspace.datasources.sqlalchemy_ds.utils`), 57  
[all\\_subclasses\(\)](#) (in module `decisionengine.framework.util.subclasses`), 113



## B

Base (class in decisionengine.framework.engine.de\_query\_tool),  
 nengine.framework.dataspace.datasources.sqlalchemy\_db5schema),  
 compress() (in module decisionengine.framework.dataspace.datablock),  
 BATransform (class in decisionengine.framework.tests.BATransform), 101  
 block\_while() (decisionengine.framework.engine.DecisionEngine.config(),  
 method), 81  
 BooleanExpression (class in decisionengine.framework.logicengine.BooleanExpression),  
 config() (in module decisionengine.framework.dataspace.tests.test\_Reaper),  
 88  
 BOOT (decisionengine.framework.taskmanager.ProcessingState.State  
 attribute), 98  
 ConfigTemplate (class in decisionengine.framework.tests.ModuleProgramOptions),  
 103

## C

channel\_config\_dir() (in module decisionengine.framework.config.policies), 48  
 channel\_workers() (in module decisionengine.framework.taskmanager.module\_graph),  
 100  
 ChannelConfigHandler (class in decisionengine.framework.config.ChannelConfigHandler),  
 47  
 ChannelWorker (class in decisionengine.framework.engine.ChannelWorkers),  
 79  
 ChannelWorkers (class in decisionengine.framework.engine.ChannelWorkers),  
 80  
 ChannelWorkers.Access (class in decisionengine.framework.engine.ChannelWorkers),  
 80  
 Clean (decisionengine.framework.engine.DecisionEngine.StopState  
 attribute), 83  
 ClientMessageReceiver (class in decisionengine.framework.engine.ClientMessageReceiver),  
 81  
 clone\_model() (in module decisionengine.framework.dataspace.datasources.sqlalchemy\_db5utils),  
 57  
 close() (decisionengine.framework.dataspace.datasource.DataSource  
 method), 73  
 close() (decisionengine.framework.dataspace.datasources.null.NullDataSource  
 method), 64  
 close() (decisionengine.framework.dataspace.datasources.sqlalchemy\_db5DataSource  
 method), 50  
 close() (decisionengine.framework.dataspace.datasources.sqlalchemy\_db5SQLAlchemyDS  
 method), 57  
 close() (decisionengine.framework.dataspace.dataspace.DataSource  
 method), 75  
 command\_for\_args() (in module decisionengine.framework.engine.de\_client), 85  
 command\_for\_args() (in module decisionengine.framework.engine.de\_query\_tool),  
 nengine.framework.engine.de\_query\_tool),  
 config() (in module decisionengine.framework.config.tests.test\_de\_std),  
 46  
 config() (in module decisionengine.framework.dataspace.tests.test\_Reaper),  
 67  
 configure\_listener() (decisionengine.framework.modules.QueueLogger.QueueLogger  
 method), 94  
 configure\_logging() (in module decisionengine.framework.modules.de\_logger),  
 95  
 connect() (decisionengine.framework.dataspace.datasource.DataSource  
 method), 73  
 connect() (decisionengine.framework.dataspace.datasources.null.NullDataSource  
 method), 64  
 connect() (decisionengine.framework.dataspace.datasources.sqlalchemy\_db5DataSource  
 method), 50  
 connect() (decisionengine.framework.dataspace.datasources.sqlalchemy\_db5DataSource  
 method), 57  
 console\_scripts\_main() (in module decisionengine.framework.engine.de\_client), 85  
 console\_scripts\_main() (in module decisionengine.framework.engine.de\_query\_tool),  
 85  
 console\_scripts\_main() (in module decisionengine.framework.util.logparser), 110  
 consume() (decisionengine.framework.taskmanager.LatestMessages.LatestMessages  
 method), 97  
 consumes() (decisionengine.framework.logicengine.LogicEngine.LogicEngine  
 method), 89  
 consumes() (in module decisionengine.framework.modules.Module), 93  
 consumes() (in module decisionengine.framework.modules.Publisher),  
 94  
 consumes() (in module decisionengine.framework.modules.Transform),  
 95  
 Countdown (class in decisionengine.framework.util.countdown), 109  
 Counter (class in decisionengine.framework.util.metrics), 111  
 create\_channel() (decisionengine.framework.engine.DecisionEngine.DecisionEngine



method), 81

create\_parser() (in module decisionengine.framework.engine.de\_client), 85

create\_parser() (in module decisionengine.framework.engine.de\_query\_tool), 85

create\_parser() (in module decisionengine.framework.util.logparser), 110

create\_tables() (decisionengine.framework.dataspace.datasource.DataSource method), 73

create\_tables() (decisionengine.framework.dataspace.datasources.null.NullDataSource method), 64

create\_tables() (decisionengine.framework.dataspace.datasources.sqlalchemy.DataSource method), 50

create\_tables() (decisionengine.framework.dataspace.datasources.sqlalchemy.DataSource method), 57

create\_time (decisionengine.framework.dataspace.datasources.sqlalchemy.DataSource attribute), 55

creator (decisionengine.framework.dataspace.datasources.sqlalchemy.DataSource attribute), 55

## D

data\_block\_put() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 99

DataBlock (class in decisionengine.framework.dataspace.datablock), 70

Dataproduct (class in decisionengine.framework.dataspace.datasources.sqlalchemy.DataSource), 54

dataproduct\_table (decisionengine.framework.dataspace.datasource.DataSource attribute), 73

DataSource (class in decisionengine.framework.dataspace.datasource), 73

datasource() (in module decisionengine.framework.dataspace.datasources.tests.fixtures), 62

datasource() (in module decisionengine.framework.dataspace.tests.fixtures), 67

DataSpace (class in decisionengine.framework.dataspace.dataspace), 75

dataspace() (in module decisionengine.framework.dataspace.tests.fixtures), 67

DataSpaceConfigurationError, 76

DataSpaceConnectionError, 76

DataSpaceError, 76

DataSpaceExistsError, 76

datestamp (decisionengine.framework.dataspace.datasources.sqlalchemy.DataSource attribute), 56

decision\_cycle() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 99

decisionengine module, 114

DecisionEngine (class in decisionengine.framework.engine.DecisionEngine), 81

decisionengine.framework module, 114

decisionengine.framework.api.SQLAlchemyDS module, 113

decisionengine.framework.config module, 49

decisionengine.framework.config.ChannelConfigHandler module, 47

decisionengine.framework.config.schema.Header module, 48

decisionengine.framework.config.policies module, 48

decisionengine.framework.config.tests module, 47

decisionengine.framework.config.tests.test\_config module, 45

decisionengine.framework.config.tests.test\_de\_std module, 46

decisionengine.framework.config.tests.test\_policies module, 47

decisionengine.framework.config.ValidConfig module, 48

decisionengine.framework.dataspace module, 77

decisionengine.framework.dataspace.datablock module, 70

decisionengine.framework.dataspace.datasource module, 73

decisionengine.framework.dataspace.datasources module, 66

decisionengine.framework.dataspace.datasources.null module, 64

decisionengine.framework.dataspace.datasources.sqlalchemy module, 57

decisionengine.framework.dataspace.datasources.sqlalchemy module, 49

decisionengine.framework.dataspace.datasources.sqlalchemy module, 54

decisionengine.framework.dataspace.datasources.sqlalchemy module, 57

decisionengine.framework.dataspace.datasources.tests module, 64

decisionengine.framework.dataspace.datasourcesdecisionengine.framework.dataspace	decisionengine.framework.logicengine.BooleanExpression
module, 61	module, 88
decisionengine.framework.dataspace.datasourcesdecisionengine.framework.datasources	decisionengine.framework.logicengine.FactLookup
module, 62	module, 88
decisionengine.framework.dataspace.dataspace	decisionengine.framework.logicengine.LogicEngine
module, 75	module, 89
decisionengine.framework.dataspace.maintain	decisionengine.framework.logicengine.Rule
module, 76	module, 90
decisionengine.framework.dataspace.tests	decisionengine.framework.logicengine.RuleEngine
module, 70	module, 90
decisionengine.framework.dataspace.tests.fixture	decisionengine.framework.logicengine.tests
module, 66	module, 88
decisionengine.framework.dataspace.tests.test_decisionengine	decisionengine.framework.logicengine.tests.test_bool_func
module, 68	module, 86
decisionengine.framework.dataspace.tests.test_decisionengine	decisionengine.framework.logicengine.tests.test_cascaded_r
module, 69	module, 86
decisionengine.framework.dataspace.tests.test_decisionengine	decisionengine.framework.logicengine.tests.test_constructi
module, 69	module, 86
decisionengine.framework.dataspace.tests.test_decisionengine	decisionengine.framework.logicengine.tests.test_duplicate
module, 69	module, 87
decisionengine.framework.dataspace.tests.test_decisionengine	decisionengine.framework.logicengine.tests.test_facts
module, 67	module, 87
decisionengine.framework.engine	decisionengine.framework.logicengine.tests.test_fail_on_er
module, 86	module, 87
decisionengine.framework.engine.ChannelWorkers	decisionengine.framework.logicengine.tests.test_pandas_fac
module, 79	module, 87
decisionengine.framework.engine.ClientMessageReceiver	decisionengine.framework.logicengine.tests.test_rule_with
module, 81	module, 88
decisionengine.framework.engine.de_client	decisionengine.framework.logicengine.tests.test_simple_cor
module, 85	module, 88
decisionengine.framework.engine.de_query_tool	decisionengine.framework.modules
module, 85	module, 97
decisionengine.framework.engine.DecisionEngine	decisionengine.framework.modules.de_logger
module, 81	module, 95
decisionengine.framework.engine.SourceWorkers	decisionengine.framework.modules.describe
module, 84	module, 96
decisionengine.framework.engine.tests	decisionengine.framework.modules.EmptySource
module, 79	module, 93
decisionengine.framework.engine.tests.fixture	decisionengine.framework.modules.logging_configDict
module, 77	module, 96
decisionengine.framework.engine.tests.test_ChannelWorkers	decisionengine.framework.modules.Module
module, 78	module, 93
decisionengine.framework.engine.tests.test_client_side	decisionengine.framework.modules.print_description
module, 78	module, 96
decisionengine.framework.engine.tests.test_query_tool	decisionengine.framework.modules.Publisher
module, 79	module, 94
decisionengine.framework.engine.tests.test_SourceWorkers	decisionengine.framework.modules.QueueLogger
module, 78	module, 94
decisionengine.framework.engine.tests.test_startup	decisionengine.framework.modules.Source
module, 79	module, 94
decisionengine.framework.engine.tests.test_verification	decisionengine.framework.modules.tests
module, 79	module, 93
decisionengine.framework.logicengine	decisionengine.framework.modules.tests.test_de_logger
module, 91	module, 92

decisionengine.framework.modules.tests.test_EmptySource	decisionengine.framework.tests.ModuleProgramOptions
module, 91	module, 103
decisionengine.framework.modules.tests.test_ModuleSource	decisionengine.framework.tests.PublisherNOP
module, 91	module, 104
decisionengine.framework.modules.tests.test_ModuleSink	decisionengine.framework.tests.PublisherWithMissingConsumer
module, 92	module, 104
decisionengine.framework.modules.tests.test_Publisher	decisionengine.framework.tests.SourceAlias
module, 91	module, 104
decisionengine.framework.modules.tests.test_QuerySink	decisionengine.framework.tests.SourceNOP
module, 91	module, 104
decisionengine.framework.modules.tests.test_Source	decisionengine.framework.tests.SourceWithSampleConfigNOP
module, 92	module, 104
decisionengine.framework.modules.tests.test_Transformer	decisionengine.framework.tests.SupportsConfigPublisher
module, 92	module, 105
decisionengine.framework.modules.tests.test_transformer_framework	decisionengine.framework.tests.test_client_errors
module, 93	module, 106
decisionengine.framework.modules.Transform	decisionengine.framework.tests.test_client_server
module, 95	module, 107
decisionengine.framework.modules.translate_producer_name	decisionengine.framework.tests.test_combined_channels
module, 97	module, 107
decisionengine.framework.taskmanager	decisionengine.framework.tests.test_defaults
module, 101	module, 107
decisionengine.framework.taskmanager.LatestMessages	decisionengine.framework.tests.test_dynamic_test_modules
module, 97	module, 107
decisionengine.framework.taskmanager.module_graph	decisionengine.framework.tests.test_empty_config
module, 100	module, 107
decisionengine.framework.taskmanager.ProcessingStatus	decisionengine.framework.tests.test_error_on_acquire
module, 97	module, 107
decisionengine.framework.taskmanager.SourceProducer	decisionengine.framework.tests.test_module_program_options
module, 99	module, 108
decisionengine.framework.taskmanager.TaskManager	decisionengine.framework.tests.test_query_tool_server
module, 99	module, 108
decisionengine.framework.tests	decisionengine.framework.tests.test_reaper
module, 109	module, 108
decisionengine.framework.tests.ABTransform	decisionengine.framework.tests.test_same_source_types
module, 101	module, 108
decisionengine.framework.tests.BATTransform	decisionengine.framework.tests.test_sample_config
module, 101	module, 108
decisionengine.framework.tests.DynamicPublisher	decisionengine.framework.tests.test_shared_sources
module, 101	module, 109
decisionengine.framework.tests.DynamicSource	decisionengine.framework.tests.test_start_with_bad_channel
module, 102	module, 109
decisionengine.framework.tests.DynamicTransformer	decisionengine.framework.tests.test_status_during_startup
module, 102	module, 109
decisionengine.framework.tests.ErrorOnAcquire	decisionengine.framework.tests.TransformNOP
module, 102	module, 105
decisionengine.framework.tests.FailingPublisher	decisionengine.framework.tests.TransformWithMissingProducer
module, 102	module, 105
decisionengine.framework.tests.FailingSourceNOP	decisionengine.framework.tests.WriteToDisk
module, 102	module, 105
decisionengine.framework.tests.fixtures	decisionengine.framework.util
module, 106	module, 113
decisionengine.framework.tests.IntSource	decisionengine.framework.util.countdown
module, 103	module, 109

decisionengine.framework.util.fs  
     module, 110  
 decisionengine.framework.util.logparser  
     module, 110  
 decisionengine.framework.util.metrics  
     module, 111  
 decisionengine.framework.util.reaper  
     module, 112  
 decisionengine.framework.util.redis\_stats  
     module, 113  
 decisionengine.framework.util.singleton  
     module, 113  
 decisionengine.framework.util.sockets  
     module, 113  
 decisionengine.framework.util.subclasses  
     module, 113  
 decisionengine.framework.version  
     module, 114  
 decisionengine.tests  
     module, 114  
 decisionengine.tests.test\_framework\_package  
     module, 114  
 decompress() (in module decision-  
     engine.framework.dataspace.datablock),  
     72  
 default\_data\_lifetime (decision-  
     engine.framework.dataspace.datablock.Header  
     attribute), 72  
 delete() (decisionengine.framework.dataspace.dataspace.  
     method), 75  
 delete\_data\_older\_than() (decision-  
     engine.framework.dataspace.datasource.DataSource  
     method), 73  
 delete\_data\_older\_than() (decision-  
     engine.framework.dataspace.datasources.null.NullDataSource  
     method), 64  
 delete\_data\_older\_than() (decision-  
     engine.framework.dataspace.datasources.sqlalchemy.SQLAlchemyDataSource  
     method), 50  
 delete\_data\_older\_than() (decision-  
     engine.framework.dataspace.datasources.sqlalchemy\_ds.SQLAlchemyDS  
     method), 58  
 Describe (class in decision-  
     engine.framework.tests.ModuleProgramOptions),  
     103  
 describe() (in module decision-  
     engine.framework.modules.Publisher),  
     94  
 describe() (in module decision-  
     engine.framework.modules.Source), 94  
 describe() (in module decision-  
     engine.framework.modules.Transform),  
     95  
 DescribeAlias (class in decision-  
     engine.framework.tests.ModuleProgramOptions),  
     103  
 DEServer() (in module decision-  
     engine.framework.engine.tests.fixtures),  
     77  
 DEServer() (in module decision-  
     engine.framework.tests.fixtures), 106  
 detach() (decisionengine.framework.engine.SourceWorkers.SourceWorker  
     method), 85  
 display\_metrics() (in module decision-  
     engine.framework.util.metrics), 112  
 dump() (decisionengine.framework.config.ValidConfig.ValidConfig  
     method), 48  
 duplicate() (decision-  
     engine.framework.dataspace.datablock.DataBlock  
     method), 70  
 duplicate\_datablock() (decision-  
     engine.framework.dataspace.datasource.DataSource  
     method), 73  
 duplicate\_datablock() (decision-  
     engine.framework.dataspace.datasources.null.NullDataSource  
     method), 64  
 duplicate\_datablock() (decision-  
     engine.framework.dataspace.datasources.sqlalchemy\_ds.datasource  
     method), 50  
 duplicate\_datablock() (decision-  
     engine.framework.dataspace.datasources.sqlalchemy\_ds.SQLAlchemyDS  
     method), 58  
 DuplicateSpace\_datablock() (decision-  
     engine.framework.dataspace.dataspace.DataSpace  
     method), 75  
 DynamicPublisher (class in decision-  
     engine.framework.tests.DynamicPublisher),  
     101  
 DynamicSource (class in decision-  
     engine.framework.tests.DynamicSource),  
     102  
 DynamicTransform (class in decision-  
     engine.framework.tests.DynamicTransform),  
     102  
**E**  
 EmptySource (class in decision-  
     engine.framework.modules.EmptySource),  
     93  
 ensure\_no\_circularities() (in module decision-  
     engine.framework.taskmanager.module\_graph),  
     100  
 ERROR (decisionengine.framework.taskmanager.ProcessingState.State  
     attribute), 98  
 ErrorOnAcquire (class in decision-  
     engine.framework.tests.ErrorOnAcquire),  
     102  
 evaluate() (decisionengine.framework.logicengine.BooleanExpression.B

method), 88  
 evaluate() (decisionengine.framework.logicengine.LogicEngine.LogicEngineFramework.config.ChannelConfigHandler.ChannelConfigHandler method), 90  
 evaluate() (decisionengine.framework.logicengine.RuleEngine.RuleEngineFramework.config.ChannelConfigHandler.ChannelConfigHandler method), 90  
 evaluate\_facts() (decisionengine.framework.logicengine.LogicEngine.LogicEngineFramework.config.ChannelConfigHandler.ChannelConfigHandler method), 90  
 execute() (decisionengine.framework.engine.ClientMessageReceiver.ClientMessageReceiver method), 81  
 execute() (decisionengine.framework.logicengine.RuleEngine.RuleEngineFramework.config.ChannelConfigHandler.ChannelConfigHandler method), 90  
 execute\_command\_from\_args() (in module decisionengine.framework.util.logparser), 110  
 expiration\_time (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Header attribute), 55

## F

FactLookup (class in decisionengine.framework.logicengine.FactLookup), 88  
 FailingPublisher (class in decisionengine.framework.tests.FailingPublisher), 102  
 files\_with\_extensions() (in module decisionengine.framework.util.fs), 110  
 format\_logger() (decisionengine.framework.modules.QueueLogger.QueueLogger method), 94  
 function\_name\_from\_call() (in module decisionengine.framework.logicengine.BooleanExpression), 88

## G

Gauge (class in decisionengine.framework.util.metrics), 111  
 generation\_id (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Dataprod attribute), 54  
 generation\_id (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Header attribute), 55  
 generation\_id (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Metadata attribute), 55  
 generation\_time (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Metadata attribute), 55  
 get() (decisionengine.framework.dataspace.datablock.DataBlock method), 71  
 get() (decisionengine.framework.taskmanager.ProcessingState.ProcessingState method), 98  
 get\_channels() (decisionengine.framework.config.ChannelConfigHandler.ChannelConfigHandler method), 47  
 get\_consumes() (decisionengine.framework.engine.ChannelWorkers.ChannelWorker method), 80  
 get\_consumes() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 90  
 get\_data\_block() (decisionengine.framework.modules.Module.Module method), 93  
 get\_datablock() (decisionengine.framework.dataspace.datasource.DataSource method), 73  
 get\_data\_block() (decisionengine.framework.dataspace.datasources.null.NullDataSource method), 64  
 get\_datablock() (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.datasource method), 50  
 get\_datablock() (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.SQLAlchemy method), 58  
 get\_datablock() (decisionengine.framework.dataspace.dataspace.DataSpace method), 75  
 get\_dataproduct() (decisionengine.framework.dataspace.datasource.DataSource method), 73  
 get\_dataproduct() (decisionengine.framework.dataspace.datasources.null.NullDataSource method), 64  
 get\_dataproduct() (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.datasource method), 51  
 get\_dataproduct() (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.SQLAlchemy method), 58  
 get\_dataproduct() (decisionengine.framework.dataspace.dataspace.DataSpace method), 75  
 get\_dataproducts() (decisionengine.framework.dataspace.datablock.DataBlock method), 71  
 get\_dataproducts() (decisionengine.framework.dataspace.datasource.DataSource method), 73  
 get\_dataproducts() (decisionengine.framework.dataspace.datasources.null.NullDataSource method), 65  
 get\_dataproducts() (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.datasource method), 51



get_dataproducts()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS method), 58	get_metadata()	(decisionengine.framework.dataspace.datasource.DataSource method), 74
get_dataproducts()	(decisionengine.framework.dataspace.DataSpace method), 75	get_metadata()	(decisionengine.framework.dataspace.datasources.null.NullDataSource method), 65
get_header()	(decisionengine.framework.dataspace.datablock.DataBlock method), 71	get_metadata()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource method), 52
get_header()	(decisionengine.framework.dataspace.datasource.DataSource method), 74	get_metadata()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS method), 59
get_header()	(decisionengine.framework.dataspace.datasources.null.NullDataSource method), 65	get_metadata()	(decisionengine.framework.dataspace.DataSpace method), 75
get_header()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource method), 51	get_parameters()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource method), 93
get_header()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource method), 59	get_produces()	(decisionengine.framework.engine.ChannelWorkers.ChannelWorker method), 80
get_header()	(decisionengine.framework.dataspace.DataSpace method), 75	get_produces()	(decisionengine.framework.taskmanager.TaskManager.TaskManager method), 99
get_last_generation_id()	(decisionengine.framework.dataspace.datasource.DataSource method), 74	get_queue_logger()	(in module decisionengine.framework.modules.de_logger), 95
get_last_generation_id()	(decisionengine.framework.dataspace.datasources.null.NullDataSource method), 65	get_random_port()	(in module decisionengine.framework.util.sockets), 113
get_last_generation_id()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource method), 51	get_schema()	(decisionengine.framework.dataspace.datasource.DataSource method), 74
get_last_generation_id()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource method), 59	get_schema()	(decisionengine.framework.dataspace.datasources.null.NullDataSource method), 65
get_last_generation_id()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource method), 59	get_schema()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource method), 52
get_last_generation_id()	(decisionengine.framework.dataspace.DataSpace method), 75	get_schema()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource method), 52
get_logger()	(decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 81	get_state()	(decisionengine.framework.taskmanager.TaskManager.TaskManager method), 99
get_logger()	(in module decisionengine.framework.modules.de_logger), 95	get_state_name()	(decisionengine.framework.engine.ChannelWorkers.ChannelWorker method), 80
get_loglevel()	(decisionengine.framework.engine.SourceWorkers.SourceWorker method), 84	get_state_name()	(decisionengine.framework.taskmanager.TaskManager.TaskManager method), 99
get_loglevel()	(decisionengine.framework.taskmanager.TaskManager.TaskManager method), 99	get_state_value()	(decisionengine.framework.taskmanager.ProcessingState.ProcessingState method), 98
get_metadata()	(decisionengine.framework.dataspace.datablock.DataBlock method), 71	get_state_value()	(decisionengine.framework.taskmanager.ProcessingState.ProcessingState method), 98

nengine.framework.taskmanager.TaskManager.TaskManager(nengine.framework.modules.tests.test\_QueueLogger),  
 method), 99 91  
 get\_taskmanager() (decision- has\_value() (decision-  
 nengine.framework.dataspace.datablock.DataBlock nengine.framework.taskmanager.ProcessingState.ProcessingState  
 method), 71 method), 98  
 get\_taskmanager() (decision- Header (class in decisio-  
 nengine.framework.dataspace.datasource.DataSource nengine.framework.dataspace.datablock),  
 method), 74 71  
 get\_taskmanager() (decision- Header (class in decisio-  
 nengine.framework.dataspace.datasources.null.NullDataSource nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_sch  
 method), 65 54  
 get\_taskmanager() (decision- header\_table (decision-  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.api.SQLAlchemyDS nengine.framework.dataspace.datasource.DataSource  
 method), 52 attribute), 74  
 get\_taskmanager() (decision- Help (class in decisio-  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.api.SQLAlchemyDS nengine.framework.tests.ModuleProgramOptions),  
 method), 60 103  
 get\_taskmanager() (decision- Histogram (class in decisio-  
 nengine.framework.dataspace.dataspace.DataSpace nengine.framework.util.metrics), 111  
 method), 75  
 get\_taskmanagers() (decision- |  
 nengine.framework.dataspace.datasource.DataSource (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_sch  
 method), 74 attribute), 54  
 get\_taskmanagers() (decision- id (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_sch  
 nengine.framework.dataspace.datasources.null.NullDataSource attribute), 55  
 method), 65 id (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_sch  
 get\_taskmanagers() (decision- attribute), 55  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.datasource.api.SQLAlchemyDS  
 method), 52 FILE (decisionengine.framework.taskmanager.ProcessingState.State  
 attribute), 98  
 get\_taskmanagers() (decision- inactive() (decisionengine.framework.taskmanager.ProcessingState.Proc  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.api.SQLAlchemyDS  
 method), 60 method), 98  
 get\_taskmanagers() (decision- initialize\_q() (decision-  
 nengine.framework.dataspace.dataspace.DataSpace nengine.framework.modules.QueueLogger.QueueLogger  
 method), 75 method), 94  
 get\_unguarded() (decision- insert() (decisionengine.framework.dataspace.datasource.DataSource  
 nengine.framework.engine.ChannelWorkers.ChannelWorkers insert() (decisionengine.framework.dataspace.datasources.null.NullData  
 method), 80 method), 65  
 get\_unguarded() (decision- insert() (decisionengine.framework.dataspace.datasources.sqlalchemy\_a  
 nengine.framework.engine.SourceWorkers.SourceWorkers method), 52  
 method), 85 insert() (decisionengine.framework.dataspace.datasources.sqlalchemy\_a  
 global\_config() (in module decisio- method), 60  
 nengine.framework.engine.tests.test\_ChannelWorkers insert() (decisionengine.framework.dataspace.dataspace.DataSpace  
 78 method), 75  
 global\_config() (in module decisio- IntSource (class in decisio-  
 nengine.framework.engine.tests.test\_SourceWorkers), nengine.framework.tests.IntSource), 103  
 78 InvalidMetadataError, 72  
 global\_config\_dir() (in module decisio-  
 nengine.framework.config.policies), 48 is\_expired() (decision-  
 global\_config\_file() (in module decisio- nengine.framework.dataspace.datablock.DataBlock  
 nengine.framework.config.policies), 49 method), 71  
 is\_valid() (decisionengine.framework.dataspace.datablock.Header  
 method), 72  
**H**  
 handler\_setup() (in module decisio-

## K

key (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.DataBlock attribute), 54

key (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Header attribute), 55

key (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Metadata attribute), 55

keys() (decisionengine.framework.dataspace.datablock.DataBlock method), 71

main() (in module decisionengine.framework.util.reaper), 112

main\_wrapper() (in module decisionengine.framework.modules.describe), 96

make\_db() (in module decisionengine.framework.logicengine.tests.test\_facts), 87

mark\_demented() (decisionengine.framework.dataspace.dataspace.DataSpace method), 76

## L

LatestMessages (class in decisionengine.framework.taskmanager.LatestMessages), 97

load() (in module decisionengine.framework.config.tests.test\_config), 45

load\_all\_channels() (decisionengine.framework.config.ChannelConfigHandler.ChannelConfigHandler method), 47

load\_channel() (decisionengine.framework.config.ChannelConfigHandler.ChannelConfigHandler method), 47

load\_sample\_data\_into\_datasource() (in module decisionengine.framework.dataspace.tests.fixtures), 67

lock (decisionengine.framework.taskmanager.ProcessingState.ProcessingState property), 98

log\_setup() (in module decisionengine.framework.modules.tests.test\_de\_logger), 92

log\_setup() (in module decisionengine.framework.modules.tests.test\_QueueLogger), 91

logic\_engine\_with\_fact() (in module decisionengine.framework.logicengine.tests.test\_fail\_on\_error), 87

LogicEngine (class in decisionengine.framework.logicengine.LogicEngine), 89

LogicError, 88

mark\_expired() (decisionengine.framework.dataspace.datablock.DataBlock method), 71

mark\_expired() (decisionengine.framework.dataspace.dataspace.DataSpace method), 76

matches\_constraint() (in module decisionengine.framework.util.logparser), 110

maybe\_fail\_on\_error() (in module decisionengine.framework.logicengine.BooleanExpression), 88

Metadata (class in decisionengine.framework.config.ChannelConfigHandler.ChannelConfigHandler), 72

Metadata (class in decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema), 55

metadata (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema attribute), 54

metadata\_table (decisionengine.framework.dataspace.datasource.DataSource attribute), 74

metrics() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 81

metrics\_env\_setup() (in module decisionengine.framework.engine.tests.test\_startup), 79

MIN\_RETENTION\_INTERVAL\_DAYS (decisionengine.framework.dataspace.maintain.Reaper attribute), 76

MIN\_SECONDS\_BETWEEN\_RUNS (decisionengine.framework.dataspace.maintain.Reaper attribute), 76

missed\_update\_count (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema attribute), 56

## M

main() (in module decisionengine.framework.engine.de\_client), 85

main() (in module decisionengine.framework.engine.de\_query\_tool), 85

main() (in module decisionengine.framework.engine.DecisionEngine), 84

main() (in module decisionengine.framework.util.logparser), 110

mock\_data\_block() (in module decisionengine.framework.dataspace.datasources.tests.fixtures), 62

module

- decisionengine, 114
- decisionengine.framework, 114
- decisionengine.framework.about, 113
- decisionengine.framework.config, 49



[decisionengine.framework.config.ChannelConfigHandler](#), [decisionengine.framework.engine](#), 86  
[47](#) [decisionengine.framework.engine.ChannelWorkers](#),  
[decisionengine.framework.config.policies](#), [79](#)  
[48](#) [decisionengine.framework.engine.ClientMessageReceiver](#),  
[decisionengine.framework.config.tests](#), [47](#) [81](#)  
[decisionengine.framework.config.tests.test\\_config](#), [decisionengine.framework.engine.de\\_client](#),  
[45](#) [85](#)  
[decisionengine.framework.config.tests.test\\_de\\_cli](#), [decisionengine.framework.engine.de\\_query\\_tool](#),  
[46](#) [85](#)  
[decisionengine.framework.config.tests.test\\_policy](#), [decisionengine.framework.engine.DecisionEngine](#),  
[47](#) [81](#)  
[decisionengine.framework.config.ValidConfig](#), [decisionengine.framework.engine.SourceWorkers](#),  
[48](#) [84](#)  
[decisionengine.framework.dataspace](#), [77](#) [decisionengine.framework.engine.tests](#), [79](#)  
[decisionengine.framework.dataspace.datablock](#), [decisionengine.framework.engine.tests.fixtures](#),  
[70](#) [77](#)  
[decisionengine.framework.dataspace.datasource](#), [decisionengine.framework.engine.tests.test\\_ChannelWork](#)  
[73](#) [78](#)  
[decisionengine.framework.dataspace.datasources](#), [decisionengine.framework.engine.tests.test\\_client\\_only](#)  
[66](#) [78](#)  
[decisionengine.framework.dataspace.datasources.de\\_cli](#), [decisionengine.framework.engine.tests.test\\_query\\_tool](#)  
[64](#) [79](#)  
[decisionengine.framework.dataspace.datasources.de\\_cli\\_schema](#), [decisionengine.framework.engine.tests.test\\_SourceWork](#)  
[57](#) [78](#)  
[decisionengine.framework.dataspace.datasources.de\\_cli\\_schema](#), [decisionengine.framework.engine.tests.test\\_startup](#),  
[49](#) [79](#)  
[decisionengine.framework.dataspace.datasources.de\\_cli\\_schema](#), [decisionengine.framework.engine.tests.test\\_verify\\_redi](#)  
[54](#) [79](#)  
[decisionengine.framework.dataspace.datasources.de\\_cli\\_schema](#), [decisionengine.framework.logicengine](#), [91](#)  
[57](#) [decisionengine.framework.logicengine.BooleanExpression](#)  
[decisionengine.framework.dataspace.datasources.tests](#), [88](#)  
[64](#) [decisionengine.framework.logicengine.FactLookup](#),  
[decisionengine.framework.dataspace.datasources.tests.fixtures](#), [88](#)  
[61](#) [decisionengine.framework.logicengine.LogicEngine](#),  
[decisionengine.framework.dataspace.datasources.tests.test\\_datasource\\_api](#), [89](#)  
[62](#) [decisionengine.framework.logicengine.Rule](#),  
[decisionengine.framework.dataspace.dataspace](#), [90](#)  
[75](#) [decisionengine.framework.logicengine.RuleEngine](#),  
[decisionengine.framework.dataspace.maintain](#), [90](#)  
[76](#) [decisionengine.framework.logicengine.tests](#),  
[decisionengine.framework.dataspace.tests](#), [88](#)  
[70](#) [decisionengine.framework.logicengine.tests.test\\_bool\\_f](#)  
[decisionengine.framework.dataspace.tests.fixtures](#), [86](#)  
[66](#) [decisionengine.framework.logicengine.tests.test\\_cascad](#)  
[decisionengine.framework.dataspace.tests.test\\_datablock](#), [86](#)  
[68](#) [decisionengine.framework.logicengine.tests.test\\_constr](#)  
[decisionengine.framework.dataspace.tests.test\\_datablock\\_zlib](#), [86](#)  
[69](#) [decisionengine.framework.logicengine.tests.test\\_duplic](#)  
[decisionengine.framework.dataspace.tests.test\\_datasource](#), [85](#)  
[69](#) [decisionengine.framework.logicengine.tests.test\\_facts](#),  
[decisionengine.framework.dataspace.tests.test\\_dataspace](#), [85](#)  
[69](#) [decisionengine.framework.logicengine.tests.test\\_fail\\_o](#)  
[decisionengine.framework.dataspace.tests.test\\_Reaper](#), [86](#)  
[67](#) [decisionengine.framework.logicengine.tests.test\\_pandas](#)

87	97
decisionengine.framework.logicengine.tests.test_decisionengineframework,	taskmanager.SourceProductCache,
88	99
decisionengine.framework.logicengine.tests.test_decisionengineframework,	taskmanager.TaskManager,
88	99
decisionengine.framework.modules, 97	decisionengine.framework.tests, 109
decisionengine.framework.modules.de_logger,	decisionengine.framework.tests.ABTransform,
95	101
decisionengine.framework.modules.describe,	decisionengine.framework.tests.BATransform,
96	101
decisionengine.framework.modules.EmptySource,	decisionengine.framework.tests.DynamicPublisher,
93	101
decisionengine.framework.modules.logging_config,	decisionengine.framework.tests.DynamicSource,
96	102
decisionengine.framework.modules.Module,	decisionengine.framework.tests.DynamicTransform,
93	102
decisionengine.framework.modules.print_description,	decisionengine.framework.tests.ErrorOnAcquire,
96	102
decisionengine.framework.modules.Publisher,	decisionengine.framework.tests.FailingPublisher,
94	102
decisionengine.framework.modules.QueueLogger,	decisionengine.framework.tests.FailingSourceNOP,
94	102
decisionengine.framework.modules.Source,	decisionengine.framework.tests.fixtures,
94	106
decisionengine.framework.modules.tests,	decisionengine.framework.tests.IntSource,
93	103
decisionengine.framework.modules.tests.test_decisionengine,	decisionengine.framework.tests.ModuleProgramOptions,
92	103
decisionengine.framework.modules.tests.test_EmptySource,	decisionengine.framework.tests.PublisherNOP,
91	104
decisionengine.framework.modules.tests.test_ModuleIsDecisionengine,	decisionengine.framework.tests.PublisherWithMissingConn,
91	104
decisionengine.framework.modules.tests.test_moduleIsDecisionengine,	decisionengine.framework.tests.SourceAlias,
92	104
decisionengine.framework.modules.tests.test_PublisherIsDecisionengine,	decisionengine.framework.tests.SourceNOP,
91	104
decisionengine.framework.modules.tests.test_QueueLogger,	decisionengine.framework.tests.SourceWithSampleConfig,
91	104
decisionengine.framework.modules.tests.test_Sources,	decisionengine.framework.tests.SupportsConfigPublisher,
92	105
decisionengine.framework.modules.tests.test_Transform,	decisionengine.framework.tests.test_client_errors,
92	106
decisionengine.framework.modules.tests.test_transform,	decisionengine.framework.tests.test_client_server,
93	107
decisionengine.framework.modules.Transform,	decisionengine.framework.tests.test_combined_channels,
95	107
decisionengine.framework.modules.translate_product_name,	decisionengine.framework.tests.test_defaults,
97	107
decisionengine.framework.taskmanager, 101	decisionengine.framework.tests.test_dynamic_test_module,
decisionengine.framework.taskmanager.LatestMessages,	97
97	decisionengine.framework.tests.test_empty_config,
decisionengine.framework.taskmanager.module_graph,	107
100	decisionengine.framework.tests.test_error_on_acquire,
decisionengine.framework.taskmanager.ProcessingState,	107

decisionengine.framework.tests.test\_module\_program\_options, 87  
 108  
 decisionengine.framework.tests.test\_query\_type\_engine\_per, (in module decisio-  
 108 engine.framework.logicengine.tests.test\_rule\_with\_negated\_fact  
 decisionengine.framework.tests.test\_reaper, 88  
 108 myengine() (in module decisio-  
 decisionengine.framework.tests.test\_same\_source\_types, engine.framework.logicengine.tests.test\_simple\_configuration),  
 108 88  
 decisionengine.framework.tests.test\_sample\_config, N  
 108  
 decisionengine.framework.tests.test\_shared\_sources, decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_  
 109 name(attribute), 56  
 decisionengine.framework.tests.test\_start\_with\_channels, decisionengine.framework.engine.tests.test\_ChannelWorkers.TaskMa  
 109 attribute), 78  
 decisionengine.framework.tests.test\_status\_not\_running\_starting, decisionengine.framework.engine.DecisionEngine.StopState  
 109 attribute), 83  
 decisionengine.framework.tests.TransformNullDataSource (class in decisio-  
 105 engine.framework.dataspace.datasources.null),  
 decisionengine.framework.tests.TransformWithMissingProducesConsumes,  
 105  
 decisionengine.framework.tests.WriteToDisk, O  
 105 OFFLINE (decisionengine.framework.taskmanager.ProcessingState.State  
 decisionengine.framework.util, 113 attribute), 98  
 decisionengine.framework.util.countdown, orm\_as\_dict() (in module decisio-  
 109 engine.framework.dataspace.datasources.sqlalchemy\_ds.utils),  
 decisionengine.framework.util.fs, 110 57  
 decisionengine.framework.util.logparser, P  
 110  
 decisionengine.framework.util.metrics, Parameter (class in decisio-  
 111 engine.framework.modules.describe), 96  
 decisionengine.framework.util.reaper, 112 Parameter (class in decisio-  
 decisionengine.framework.util.redis\_stats, engine.framework.modules.Publisher),  
 113 94  
 decisionengine.framework.util.singleton, Parameter (class in decisio-  
 113 engine.framework.modules.Source), 94  
 decisionengine.framework.util.sockets, Parameter (class in decisio-  
 113 engine.framework.modules.Transform),  
 decisionengine.framework.util.subclasses, 95  
 113  
 decisionengine.framework.version, 114 parse\_constraints() (in module decisio-  
 decisionengine.tests, 114 engine.framework.util.logparser), 111  
 decisionengine.tests.test\_framework\_package, parse\_program\_options() (in module decisio-  
 114 engine.framework.engine.DecisionEngine),  
 84  
 Module (class in decisio- passthrough\_configuration() (in module decisio-  
 engine.framework.modules.Module), 93 engine.framework.logicengine.LogicEngine),  
 90  
 ModuleProgramOptions (class in decisio- PG\_DE\_DB\_WITHOUT\_SCHEMA() (in module decisio-  
 engine.framework.modules.describe), 96 engine.framework.dataspace.datasources.tests.fixtures),  
 mydata() (in module decisio- 61  
 engine.framework.logicengine.tests.test\_pandas\_fact), 87  
 myengine() (in module decisio- PG\_DE\_DB\_WITHOUT\_SCHEMA() (in module decisio-  
 engine.framework.logicengine.tests.test\_cascaded\_rules), 66  
 86  
 myengine() (in module decisio- PG\_DE\_DB\_WITHOUT\_SCHEMA() (in module decisio-  
 engine.framework.engine.tests.fixtures), 77

PG\_DE\_DB\_WITHOUT\_SCHEMA() (in module decisionengine.framework.tests.fixtures), 106

PG\_PROG() (in module decisionengine.framework.dataspace.datasources.tests.fixtures), 62

PG\_PROG() (in module decisionengine.framework.dataspace.tests.fixtures), 66

PG\_PROG() (in module decisionengine.framework.engine.tests.fixtures), 77

PG\_PROG() (in module decisionengine.framework.tests.fixtures), 106

print\_channel\_config() (decisionengine.framework.config.ChannelConfigHandler.ChannelConfigHandler method), 47

print\_consumes() (in module decisionengine.framework.modules.print\_description), 96

print\_produces() (in module decisionengine.framework.modules.print\_description), 96

print\_supported\_config() (in module decisionengine.framework.modules.print\_description), 96

probably\_running() (decisionengine.framework.taskmanager.ProcessingState.ProcessingState method), 98

process\_args() (decisionengine.framework.modules.describe.ModuleProgramOptions.ModuleProgramOptions method), 96

ProcessingState (class in decisionengine.framework.taskmanager.ProcessingState), 97

produces() (decisionengine.framework.logicengine.LogicEngine.LogicEngine method), 90

produces() (in module decisionengine.framework.modules.Module), 93

produces() (in module decisionengine.framework.modules.Source), 94

produces() (in module decisionengine.framework.modules.Transform), 95

ProductRetriever (class in decisionengine.framework.dataspace.datablock), 72

prune() (decisionengine.framework.engine.SourceWorkers.SourceWorkers method), 85

publish() (decisionengine.framework.modules.Publisher.Publisher method), 94

publish() (decisionengine.framework.tests.FailingPublisher.FailingPublisher method), 102

publish() (decisionengine.framework.tests.PublisherNOP.PublisherNOP method), 104

publish() (decisionengine.framework.tests.WriteToDisk.WriteToDisk method), 105

Publisher (class in decisionengine.framework.modules.Publisher), 94

publisher() (decisionengine.framework.tests.DynamicPublisher.DynamicPublisher method), 101

PublisherNOP (class in decisionengine.framework.tests.PublisherNOP), 104

PublisherWithMissingConsumes (class in decisionengine.framework.tests.PublisherWithMissingConsumes), 104

put() (decisionengine.framework.dataspace.datablock.DataBlock.DataBlock method), 71

## Q

queue\_logger\_setup() (in module decisionengine.framework.modules.tests.test\_QueueLogger), 91

QueueLogger (class in decisionengine.framework.modules.QueueLogger), 94

## R

reaper() (decisionengine.framework.dataspace.maintain.Reaper.Reaper method), 76

Reaper (class in decisionengine.framework.dataspace.maintain), 76

reaper() (in module decisionengine.framework.dataspace.tests.test\_Reaper), 67

reaper\_start() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 82

reaper\_status() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 82

reaper\_stop() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 82

record\_that\_matches() (in module decisionengine.framework.tests.test\_shared\_sources), 109

redis\_stats() (in module decisionengine.framework.util.redis\_stats), 113

registry (decisionengine.framework.dataspace.datasources.sqlalchemy attribute), 54

remove\_all() (decisionengine.framework.engine.SourceWorkers.SourceWorkers method), 85

RequestHandler (class in decisionengine.framework.engine.DecisionEngine), 82  
 83  
 required\_keys (decisionengine.framework.dataspace.datablock.Header attribute), 72  
 required\_keys (decisionengine.framework.dataspace.datablock.Metadata attribute), 72  
 reset\_connections() (decisionengine.framework.dataspace.datasource.DataSource method), 75  
 reset\_connections() (decisionengine.framework.dataspace.sources.null.NullDataSource method), 66  
 reset\_connections() (decisionengine.framework.dataspace.sources.sqlalchemy.DataSource method), 53  
 reset\_connections() (decisionengine.framework.dataspace.sources.sqlalchemy.DataSource method), 60  
 retention\_interval (decisionengine.framework.dataspace.maintain.Reaper property), 76  
 rm\_channel() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_block\_while() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_get\_channel\_log\_level() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_get\_log\_level() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_get\_source\_log\_level() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_kill\_channel() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_metrics() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_paths (decisionengine.framework.engine.DecisionEngine attribute), 83  
 rpc\_ping() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_print\_product() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_print\_products() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_product\_dependencies() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_query\_tool() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_queue\_status() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_reaper\_start() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_reaper\_status() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_reaper\_stop() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_rm\_channel() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_set\_channel\_log\_level() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_set\_source\_log\_level() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_show\_config() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_show\_de\_config() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_start\_channel() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_start\_channels() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_status() (decisionengine.framework.engine.DecisionEngine method), 82  
 rpc\_stop() (decisionengine.framework.engine.DecisionEngine method), 83  
 rpc\_stop\_channel() (decisionengine.framework.engine.DecisionEngine method), 83  
 rpc\_stop\_channels() (decisionengine.framework.engine.DecisionEngine method), 83  
 Rule (class in decisionengine.framework.logicengine.Rule), 90  
 rule\_for() (decisionengine.framework.logicengine.FactLookup.FactLookup method), 90



method), 89  
 RuleEngine (class in decisionengine.framework.logicengine.RuleEngine), 90  
 run() (decisionengine.framework.engine.ChannelWorkers.ChannelWorker method), 80  
 run() (decisionengine.framework.engine.SourceWorkers.SourceWorker method), 84  
 run\_cycle() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 99  
 run\_cycles() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 99  
 run\_logic\_engine() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 99  
 run\_publishers() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 99  
 run\_transform() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 100  
 run\_transforms() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 100  
 S  
 scheduled\_create\_time (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Header attribute), 55  
 Schema (class in decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema), 56  
 schema (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Schema attribute), 56  
 schema\_id (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Header attribute), 55  
 schema\_id (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Schema attribute), 56  
 ScopedSingleton (class in decisionengine.framework.util.singleton), 113  
 ScopedSingletonABC (class in decisionengine.framework.util.singleton), 113  
 seconds\_between\_runs (decisionengine.framework.dataspace.maintain.Reaper property), 76  
 sequence\_id (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.TaskManager attribute), 56  
 service\_actions() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 83  
 set() (decisionengine.framework.taskmanager.ProcessingState.ProcessingState method), 98  
 set\_data\_block() (decisionengine.framework.modules.Module.Module method), 93  
 set\_loglevel\_value() (decisionengine.framework.engine.SourceWorkers.SourceWorker method), 84  
 set\_loglevel\_value() (decisionengine.framework.engine.tests.test\_ChannelWorkers.TaskManager method), 78  
 set\_loglevel\_value() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 100  
 set\_state() (decisionengine.framework.dataspace.datablock.Metadata method), 72  
 setup\_logger() (decisionengine.framework.engine.ChannelWorkers.ChannelWorker method), 80  
 setup\_logger() (decisionengine.framework.engine.SourceWorkers.SourceWorker method), 84  
 setup\_queue\_logging() (decisionengine.framework.modules.QueueLogger.QueueLogger method), 94  
 setup\_queue\_logging() (in module decisionengine.framework.modules.tests.test\_QueueLogger), 91  
 should\_stop() (decisionengine.framework.taskmanager.ProcessingState.ProcessingState method), 98  
 SHUTDOWN (decisionengine.framework.taskmanager.ProcessingState.State attribute), 98  
 shutdown() (decisionengine.framework.modules.Publisher.Publisher method), 94  
 SHUTTINGDOWN (decisionengine.framework.taskmanager.ProcessingState.State attribute), 98  
 Singleton (class in decisionengine.framework.util.singleton), 113  
 SingletonABC (class in decisionengine.framework.util.singleton), 113  
 sorted\_rules() (decisionengine.framework.logicengine.FactLookup.FactLookup method), 89  
 Source (class in decisionengine.framework.modules.Source), 94  
 source\_config() (in module decisionengine.framework.engine.tests.test\_SourceWorkers), 78  
 source\_products() (in module decisionengine.framework.taskmanager.module\_graph), 101

source\_worker\_for() (in module decisionengine.framework.engine.tests.test\_SourceWorkers), 78  
 SourceNOP (class in decisionengine.framework.tests.SourceNOP), 104  
 SourceProductCache (class in decisionengine.framework.taskmanager.SourceProductCache), 99  
 SourceWithMissingProduces (class in decisionengine.framework.tests.FailingSourceNOP), 102  
 SourceWithSampleConfigNOP (class in decisionengine.framework.tests.SourceWithSampleConfigNOP), 104  
 SourceWorker (class in decisionengine.framework.engine.SourceWorkers), 84  
 SourceWorkers (class in decisionengine.framework.engine.SourceWorkers), 84  
 SourceWorkers.Access (class in decisionengine.framework.engine.SourceWorkers), 84  
 spec\_if\_main() (in module decisionengine.framework.modules.print\_description), 96  
 SQLALCHEMY\_PG\_WITH\_SCHEMA() (in module decisionengine.framework.dataspace.datasources.tests.fixtures), 62  
 SQLALCHEMY\_PG\_WITH\_SCHEMA() (in module decisionengine.framework.dataspace.tests.fixtures), 67  
 SQLALCHEMY\_PG\_WITH\_SCHEMA() (in module decisionengine.framework.engine.tests.fixtures), 77  
 SQLALCHEMY\_PG\_WITH\_SCHEMA() (in module decisionengine.framework.tests.fixtures), 106  
 SQLALCHEMY\_TEMPFILE\_SQLITE() (in module decisionengine.framework.dataspace.datasources.tests.fixtures), 62  
 SQLALCHEMY\_TEMPFILE\_SQLITE() (in module decisionengine.framework.dataspace.tests.fixtures), 67  
 SQLALCHEMY\_TEMPFILE\_SQLITE() (in module decisionengine.framework.engine.tests.fixtures), 77  
 SQLALCHEMY\_TEMPFILE\_SQLITE() (in module decisionengine.framework.tests.fixtures), 106  
 SQLAlchemyDS (class in decisionengine.framework.dataspace.datasources.sqlalchemy\_ds), 57  
 SQLAlchemyDS (class in decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.SQLAlchemyDS), 49  
 start() (decisionengine.framework.dataspace.maintain.Reaper method), 76  
 start() (decisionengine.framework.modules.QueueLogger.QueueLogger method), 94  
 start\_channel() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 83  
 start\_channels() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 83  
 start\_webserver() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 83  
 State (class in decisionengine.framework.taskmanager.ProcessingState), 98  
 State (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db attribute), 56  
 STEADY (decisionengine.framework.taskmanager.ProcessingState.State attribute), 98  
 stop() (decisionengine.framework.dataspace.maintain.Reaper method), 76  
 stop() (decisionengine.framework.modules.QueueLogger.QueueLogger method), 94  
 stop\_channels() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 83  
 stop\_queue\_logger() (in module decisionengine.framework.modules.de\_logger), 96  
 stop\_worker() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 83  
 stopped\_channel\_opts() (in module decisionengine.framework.tests.test\_sample\_config), 108  
 StopState (class in decisionengine.framework.engine.DecisionEngine), 83  
 store\_taskmanager() (decisionengine.framework.dataspace.datablock.DataBlock method), 71  
 store\_taskmanager() (decisionengine.framework.dataspace.datasource.DataSource method), 75  
 store\_taskmanager() (decisionengine.framework.dataspace.datasources.null.NullDataSource method), 66  
 store\_taskmanager() (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.datasource method), 53  
 store\_taskmanager() (decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.SQLAlchemyDS method), 61  
 store\_taskmanager() (decisionengine.framework.dataspace.dataspace.DataSpace method), 76  
 Summary (class in decisionengine.framework.engine.DecisionEngine), 83

nengine.framework.util.metrics), 112  
 supports\_config() (in module decisio-  
 nengine.framework.modules.describe), 96  
 supports\_config() (in module decisio-  
 nengine.framework.modules.Publisher),  
 94  
 supports\_config() (in module decisio-  
 nengine.framework.modules.Source), 94  
 supports\_config() (in module decisio-  
 nengine.framework.modules.Transform),  
 95  
 SupportsConfig (class in decisio-  
 nengine.framework.tests.SupportsConfigPublisher),  
 105

## T

take\_offline() (decision-  
 nengine.framework.engine.SourceWorkers.SourceWorker  
 method), 84  
 take\_offline() (decision-  
 nengine.framework.taskmanager.TaskManager.TaskManager  
 method), 100  
 task\_dataproduct (decision-  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Taskmanager  
 attribute), 56  
 task\_header (decision-  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Taskmanager  
 attribute), 56  
 task\_metadata (decision-  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Taskmanager  
 attribute), 56  
 Taskmanager (class in decisio-  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema),  
 56  
 TaskManager (class in decisio-  
 nengine.framework.engine.tests.test\_ChannelWorker),  
 78  
 TaskManager (class in decisio-  
 nengine.framework.taskmanager.TaskManager),  
 99  
 taskmanager (decision-  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Taskmanager  
 attribute), 54  
 taskmanager (decision-  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Taskmanager  
 attribute), 55  
 taskmanager (decision-  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Taskmanager  
 attribute), 56  
 taskmanager\_id (decision-  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Taskmanager  
 attribute), 54  
 taskmanager\_id (decision-  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Taskmanager  
 attribute), 55  
 taskmanager\_id (decision-  
 nengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Taskmanager  
 attribute), 56  
 taskmanager\_table (decision-  
 nengine.framework.dataspace.datasource.DataSource  
 attribute), 75  
 Terminated (decisionengine.framework.engine.DecisionEngine.StopState  
 attribute), 83  
 test() (decisionengine.framework.tests.ModuleProgramOptions.AcquireW  
 method), 103  
 test() (decisionengine.framework.tests.ModuleProgramOptions.AcquireW  
 method), 103  
 test() (decisionengine.framework.tests.ModuleProgramOptions.ConfigTer  
 method), 103  
 test() (decisionengine.framework.tests.ModuleProgramOptions.Describe  
 method), 103  
 test() (decisionengine.framework.tests.ModuleProgramOptions.Describe  
 method), 103  
 test() (decisionengine.framework.tests.ModuleProgramOptions.Help  
 method), 103  
 test\_acquire\_for\_sources() (in module decisio-  
 nengine.framework.tests.test\_module\_program\_options),  
 108  
 test\_allow\_duplicate\_keys\_same\_values() (in module decisio-  
 nengine.framework.config.tests.test\_de\_std),  
 46  
 test\_allow\_duplicate\_source\_proxy\_keys() (in module decisio-  
 nengine.framework.config.tests.test\_de\_std),  
 46  
 test\_by\_nonsense\_is\_err() (in module decisio-  
 nengine.framework.modules.tests.test\_de\_logger),  
 92  
 test\_by\_size() (in module decisio-  
 nengine.framework.modules.tests.test\_de\_logger),  
 92  
 test\_byt\_is\_err() (in module decisio-  
 nengine.framework.modules.tests.test\_de\_logger),  
 92  
 test\_data\_import\_header (in module decisio-  
 nengine.tests.test\_framework\_package), 114  
 test\_change\_port() (in module decisio-  
 nengine.framework.engine.tests.test\_startup),  
 79  
 test\_channel\_config\_dir() (in module decisio-  
 nengine.framework.config.tests.test\_policies),  
 47  
 test\_channel\_empty\_config() (in module decisio-  
 nengine.framework.config.tests.test\_config), 45



test_channel_empty_dictionary() (in module <i>decisionengine.framework.config.tests.test_config</i> ), 45	test_client_can_get_de_server_status() (in module <i>decisionengine.framework.tests.test_sample_config</i> ), 108
test_channel_invalid_modules_list() (in module <i>decisionengine.framework.config.tests.test_config</i> ), 45	test_client_can_get_products_no_channels() (in module <i>decisionengine.framework.tests.test_start_with_bad_channels</i> ), 109
test_channel_invalid_modules_no_keys() (in module <i>decisionengine.framework.config.tests.test_config</i> ), 45	test_client_can_kill_one_channel() (in module <i>decisionengine.framework.tests.test_sample_config</i> ), 108
test_channel_invalid_modules_string() (in module <i>decisionengine.framework.config.tests.test_config</i> ), 45	test_client_can_restart_all_channels() (in module <i>decisionengine.framework.tests.test_sample_config</i> ), 108
test_channel_loading() (in module <i>decisionengine.framework.config.tests.test_config</i> ), 46	test_client_can_restart_one_channel() (in module <i>decisionengine.framework.tests.test_sample_config</i> ), 108
test_channel_module_missing_all() (in module <i>decisionengine.framework.config.tests.test_config</i> ), 46	test_client_can_start_one_channel_added_after_startup() (in module <i>decisionengine.framework.tests.test_empty_config</i> ), 107
test_channel_module_missing_module() (in module <i>decisionengine.framework.config.tests.test_config</i> ), 46	test_client_cannot_wait_on_bad_state() (in module <i>decisionengine.framework.tests.test_client_errors</i> ), 106
test_channel_module_missing_parameters() (in module <i>decisionengine.framework.config.tests.test_config</i> ), 46	test_client_err_returned_as_rc() (in module <i>decisionengine.framework.engine.tests.test_client_only</i> ), 78
test_channel_names() (in module <i>decisionengine.framework.config.tests.test_config</i> ), 46	test_client_err_returned_as_rc() (in module <i>decisionengine.framework.engine.tests.test_query_tool_only</i> ), 79
test_channel_no_config_files() (in module <i>decisionengine.framework.config.tests.test_config</i> ), 46	test_client_err_returned_verbose_as_rc() (in module <i>decisionengine.framework.engine.tests.test_client_only</i> ), 78
test_channel_no_modules() (in module <i>decisionengine.framework.config.tests.test_config</i> ), 46	test_client_err_returned_verbose_as_rc() (in module <i>decisionengine.framework.engine.tests.test_query_tool_only</i> ), 79
test_check_metrics_env_no_webserver() (in module <i>decisionengine.framework.engine.tests.test_startup</i> ), 79	test_client_get_loglevel() (in module <i>decisionengine.framework.tests.test_client_server</i> ), 107
test_check_metrics_env_var_set() (in module <i>decisionengine.framework.engine.tests.test_startup</i> ), 79	test_client_help() (in module <i>decisionengine.framework.engine.tests.test_client_only</i> ), 78
test_check_metrics_env_var_unset() (in module <i>decisionengine.framework.engine.tests.test_startup</i> ), 79	test_client_logger_level() (in module <i>decisionengine.framework.tests.test_sample_config</i> ), 108
test_client_can_get_de_server_reaper_status() (in module <i>decisionengine.framework.tests.test_reaper</i> ), 108	test_client_non_real_channel()

<i>(in module decisionengine.framework.tests.test_sample_config),</i> 108	<i>test_configuration_with_numpy_facts()</i> <i>(in module decisionengine.framework.logicengine.tests.test_construction),</i> 86
<i>test_client_print_product()</i> <i>(in module decisionengine.framework.tests.test_client_server),</i> 107	<i>test_conflicting_source_configurations()</i> <i>(in module decisionengine.framework.tests.test_shared_sources),</i> 109
<i>test_client_set_loglevel()</i> <i>(in module decisionengine.framework.tests.test_client_server),</i> 107	<i>test_create_tables()</i> <i>(in module decisionengine.framework.dataspace.datasources.tests.test_datasource_</i> 62
<i>test_client_status_msg_to_logger()</i> <i>(in module decisionengine.framework.tests.test_client_server),</i> 107	<i>test_DataBlock_constructor()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock),</i> 68
<i>test_client_with_no_command_says_use_help()</i> <i>(in module decisionengine.framework.engine.tests.test_client_only),</i> 78	<i>test_DataBlock_duplicate()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock),</i> 68
<i>test_client_with_no_server()</i> <i>(in module decisionengine.framework.engine.tests.test_client_only),</i> 78	<i>test_DataBlock_get_dataproducts()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock),</i> 68
<i>test_client_with_no_server_verbose()</i> <i>(in module decisionengine.framework.engine.tests.test_client_only),</i> 78	<i>test_DataBlock_get_header()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock),</i> 68
<i>test_combine_one_level()</i> <i>(in module decisionengine.framework.config.tests.test_de_std),</i> 46	<i>test_DataBlock_get_metadata()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock),</i> 68
<i>test_combine_one_level_skip_proxies()</i> <i>(in module decisionengine.framework.config.tests.test_de_std),</i> 46	<i>test_DataBlock_get_taskmanager()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock),</i> 68
<i>test_combined_channels()</i> <i>(in module decisionengine.framework.tests.test_combined_channels),</i> 107	<i>test_DataBlock_is_expired()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock),</i> 68
<i>test_combined_channels_3g()</i> <i>(in module decisionengine.framework.tests.test_combined_channels),</i> 107	<i>test_DataBlock_is_expired_with_key()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock),</i> 68
<i>test_compound_fact_with_spaces()</i> <i>(in module decisionengine.framework.logicengine.tests.test_facts),</i> 87	<i>test_DataBlock_key_management()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock),</i> 68
<i>test_compress()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock_test),</i> 69	<i>test_DataBlock_key_management_change_name()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock),</i> 68
<i>test_conditional_fact()</i> <i>(in module decisionengine.framework.logicengine.tests.test_fail_on_error),</i> 87	<i>test_DataBlock_mark_expired()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock),</i> 68
<i>test_config_templates()</i> <i>(in module decisionengine.framework.tests.test_module_program_options),</i> 108	<i>test_DataBlock_no_key_by_name()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock),</i> 68
<i>test_configuration_with_fact_using_function()</i> <i>(in module decisionengine.framework.logicengine.tests.test_construction),</i> 86	<i>test_DataBlock_to_str()</i> <i>(in module decisionengine.framework.dataspace.tests.test_datablock),</i> 68

<code>nengine.framework.dataspace.tests.test_datablock()</code>	<code>test_error_on_bad_names()</code> (in module <code>decisionengine.framework.logicengine.tests.test_simple_configuration</code> ),
68	88
<code>test_dataspace_config_finds_bad()</code>	<code>test_error_on_duplicate_keys()</code> (in module <code>decisionengine.framework.config.tests.test_defaults</code> ),
(in module <code>decisionengine.framework.dataspace.tests.test_dataspace</code> ),	46
69	
<code>test_default_config()</code> (in module <code>decisionengine.framework.engine.tests.test_startup</code> ),	<code>test_exclusive_options()</code> (in module <code>decisionengine.framework.engine.tests.test_client_only</code> ),
79	78
<code>test_default_construction()</code> (in module <code>decisionengine.framework.logicengine.tests.test_construction</code> ),	<code>test_fact_using_numpy_array()</code> (in module <code>decisionengine.framework.logicengine.tests.test_facts</code> ),
86	87
<code>test_defaults()</code> (in module <code>decisionengine.framework.tests.test_defaults</code> ),	<code>test_fact_using_numpy_function()</code>
107	(in module <code>decisionengine.framework.logicengine.tests.test_facts</code> ),
<code>test_delete()</code> (in module <code>decisionengine.framework.dataspace.tests.test_dataspace</code> ),	87
69	<code>test_fact_with_fail_on_error()</code>
<code>test_delete_data_older_than_arg()</code>	(in module <code>decisionengine.framework.logicengine.tests.test_facts</code> ),
(in module <code>decisionengine.framework.dataspace.datasources.tests.test_datasource_api</code> ),	87
62	<code>test_fact_with_misspecified_attribute()</code>
<code>test_descriptions()</code> (in module <code>decisionengine.framework.tests.test_module_program_options</code> ),	(in module <code>decisionengine.framework.logicengine.tests.test_fail_on_error</code> ),
108	87
<code>test_duplicate_datablock()</code> (in module <code>decisionengine.framework.dataspace.datasources.tests.test_datasource_api</code> ),	<code>test_fact_with_nested_names()</code> (in module <code>decisionengine.framework.logicengine.tests.test_facts</code> ),
62	87
<code>test_duplicate_datablock()</code> (in module <code>decisionengine.framework.dataspace.tests.test_dataspace</code> ),	<code>test_fail_bad_config()</code> (in module <code>decisionengine.framework.dataspace.tests.test_Reaper</code> ),
69	67
<code>test_duplicate_fact_names()</code> (in module <code>decisionengine.framework.logicengine.tests.test_duplicate_fact_names</code> ),	<code>test_fail_missing_config()</code> (in module <code>decisionengine.framework.dataspace.tests.test_Reaper</code> ),
87	67
<code>test_dynamic_publisher()</code> (in module <code>decisionengine.framework.tests.test_dynamic_test_modules</code> ),	<code>test_fail_missing_config_key()</code>
107	(in module <code>decisionengine.framework.dataspace.tests.test_Reaper</code> ),
<code>test_dynamic_source()</code> (in module <code>decisionengine.framework.tests.test_dynamic_test_modules</code> ),	67
107	<code>test_fail_on_error()</code> (in module <code>decisionengine.framework.logicengine.tests.test_fail_on_error</code> ),
<code>test_dynamic_transform()</code> (in module <code>decisionengine.framework.tests.test_dynamic_test_modules</code> ),	87
107	<code>test_fail_small_retain()</code> (in module <code>decisionengine.framework.dataspace.tests.test_Reaper</code> ),
<code>test_empty_config()</code> (in module <code>decisionengine.framework.config.tests.test_config</code> ),	67
46	<code>test_fail_small_run_interval()</code>
<code>test_empty_source_structure()</code> (in module <code>decisionengine.framework.modules.tests.test_EmptySource</code> ),	(in module <code>decisionengine.framework.dataspace.tests.test_Reaper</code> ),
91	67
<code>test_error_conditions()</code> (in module <code>decisionengine.framework.logicengine.tests.test_bool_function_name</code> ),	<code>test_fail_start_two_reapers()</code> (in module <code>decisionengine.framework.dataspace.tests.test_Reaper</code> ),
86	67
<code>test_error_on_acquire()</code> (in module <code>decisionengine.framework.tests.test_error_on_acquire</code> ),	<code>test_fail_wrong_config_key()</code> (in module <code>decisionengine.framework.dataspace.tests.test_Reaper</code> ),
107	67
	<code>test_false_fact_with_spaces()</code> (in module <code>decisionengine.framework.logicengine.tests.test_facts</code> ),

```

nengine.framework.logicengine.tests.test_fail_on_test) get_last_generation_id() (in module decisio-
87 nengine.framework.dataspace.tests.test_dataspace),
test_false_literal_fact() (in module decisio- 69
nengine.framework.logicengine.tests.test_fail_on_test) get_last_generation_id_not_exist()
87 (in module decisio-
test_get_datablock() (in module decisio- nengine.framework.dataspace.datasources.tests.test_datasource_
nengine.framework.dataspace.datasources.tests.test_datasource_63ce_api),
63 test_get_last_generation_id_not_exist()
test_get_datablock() (in module decisio- (in module decisio-
nengine.framework.dataspace.tests.test_dataspace), nengine.framework.dataspace.tests.test_dataspace),
69 69
test_get_dataproduct() (in module decisio- test_get_metadata() (in module decisio-
nengine.framework.dataspace.datasources.tests.test_datasource_63ce_api), nengine.framework.dataspace.datasources.tests.test_datasource_
63 63
test_get_dataproduct() (in module decisio- test_get_metadata() (in module decisio-
nengine.framework.dataspace.tests.test_dataspace), nengine.framework.dataspace.tests.test_dataspace),
69 69
test_get_dataproduct_not_exist() test_get_metadata_not_exist() (in module decisio-
(in module decisio- nengine.framework.dataspace.datasources.tests.test_datasource_
nengine.framework.dataspace.datasources.tests.test_datasource_63ce_api),
63 test_get_metadata_not_exist() (in module decisio-
test_get_dataproduct_not_exist() nengine.framework.dataspace.tests.test_dataspace),
(in module decisio- 69
nengine.framework.dataspace.tests.test_dataspace) test_get_taskmanager_exists() (in module decisio-
69 nengine.framework.dataspace.datasources.tests.test_datasource_
test_get_dataproducts() (in module decisio- 63
nengine.framework.dataspace.datasources.tests.test_datasource_63ce_api),
63 test_get_taskmanager_exists() (in module decisio-
nengine.framework.dataspace.tests.test_dataspace),
test_get_dataproducts() (in module decisio- 69
nengine.framework.dataspace.tests.test_dataspace) test_get_taskmanager_not_exists()
69 (in module decisio-
test_get_dataproducts_not_exist() nengine.framework.dataspace.datasources.tests.test_datasource_
(in module decisio- 63
nengine.framework.dataspace.datasources.tests.test_datasource_63ce_api),
63 test_get_taskmanager_not_exists()
test_get_dataproducts_not_exist() (in module decisio-
(in module decisio- nengine.framework.dataspace.tests.test_dataspace),
nengine.framework.dataspace.tests.test_dataspace) test_get_taskmanagers() (in module decisio-
69 nengine.framework.dataspace.datasources.tests.test_datasource_
test_get_header() (in module decisio- 63
nengine.framework.dataspace.datasources.tests.test_datasource_63ce_api),
63 test_get_taskmanagers() (in module decisio-
nengine.framework.dataspace.tests.test_dataspace),
test_get_header() (in module decisio- 70
nengine.framework.dataspace.tests.test_dataspace) test_get_taskmanagers_not_exist()
69 (in module decisio-
test_get_header_not_exist() (in module decisio- nengine.framework.dataspace.datasources.tests.test_datasource_
nengine.framework.dataspace.datasources.tests.test_datasource_63ce_api),
63 test_get_taskmanagers_not_exist()
test_get_header_not_exist() (in module decisio- (in module decisio-
nengine.framework.dataspace.tests.test_dataspace), nengine.framework.dataspace.tests.test_dataspace),
69 70
test_get_last_generation_id() (in module decisio- test_global_config_dir() (in module decisio-
nengine.framework.dataspace.datasources.tests.test_datasource_63ce_api), nengine.framework.config.tests.test_policies),
63 47

```

test_global_config_file() (in module decisio- engine.framework.config.tests.test_policies), 47	(in module decisio- engine.framework.config.tests.test_config), 46
test_has_config() (in module decisio- engine.framework.dataspace.datasources.tests.test_datasource_api), 63	test_missing_data_product_name_not_supported() (in module decisio- engine.framework.modules.tests.test_EmptySource), 91
test_has_config() (in module decisio- engine.framework.dataspace.tests.test_dataspace), 70	test_misspecified_fact() (in module decisio- engine.framework.logicengine.tests.test_fail_on_error), 87
test_has_methods_we_expect() (in module decisio- engine.framework.dataspace.tests.test_datasource), 69	test_module_alias() (in module decisio- engine.framework.tests.test_module_program_options), 108
test_Header_constructor() (in module decisio- engine.framework.dataspace.tests.test_datablock), 68	test_module_structure() (in module decisio- engine.framework.modules.tests.test_Module), 91
test_Header_is_valid() (in module decisio- engine.framework.dataspace.tests.test_datablock), 68	test_multiple_consumes_declarations() (in module decisio- engine.framework.modules.tests.test_module_decorators), 92
test_help() (in module decisio- engine.framework.tests.test_module_program_options), 108	test_multiple_produces_declarations() (in module decisio- engine.framework.modules.tests.test_module_decorators), 92
test_index_error() (in module decisio- engine.framework.logicengine.tests.test_fail_on_error), 87	test_publisher_structure() (in module decisio- engine.framework.modules.tests.test_Publisher), 91
test_insert() (in module decisio- engine.framework.dataspace.datasources.tests.test_datasource_api), 63	test_query_tool() (in module decisio- engine.framework.tests.test_query_tool_server), 108
test_insert() (in module decisio- engine.framework.dataspace.tests.test_dataspace), 70	test_query_tool_help() (in module decisio- engine.framework.engine.tests.test_query_tool_only), 79
test_jpath() (in module decisio- engine.framework.config.tests.test_de_std), 46	test_query_tool_with_no_server() (in module decisio- engine.framework.engine.tests.test_query_tool_only), 79
test_just_stop_no_error() (in module decisio- engine.framework.dataspace.tests.test_Reaper), 67	test_query_tool_with_no_server_verbose() (in module decisio- engine.framework.engine.tests.test_query_tool_only), 79
test_loop_of_start_stop_in_clumps() (in module decisio- engine.framework.dataspace.tests.test_Reaper), 67	test_reap_default_state() (in module decisio- engine.framework.dataspace.tests.test_Reaper), 67
test_mark_expired() (in module decisio- engine.framework.dataspace.tests.test_dataspace), 70	test_reaper_can_reap() (in module decisio- engine.framework.dataspace.tests.test_Reaper), 67
test_Metadata_constructor() (in module decisio- engine.framework.dataspace.tests.test_datablock), 68	test_reset_connections() (in module decisio- engine.framework.dataspace.datasources.tests.test_datasource_api), 63
test_Metadata_set_state() (in module decisio- engine.framework.dataspace.tests.test_datablock), 68	test_rule_that_does_not_fire() (in module decisio- engine.framework.logicengine.tests.test_cascaded_rules), 86
test_minimal_jsonnet_right_extension() (in module decisio- engine.framework.config.tests.test_config), 46	
test_minimal_jsonnet_wrong_extension()	



```

test_rule_that_does_not_fire()                                nengine.framework.dataspace.tests.test_Reaper),
    (in module decision-                                     68
nengine.framework.logicengine.tests.test_pandas_fact),
87 nengine.framework.dataspace.tests.test_Reaper),
test_rule_that_does_not_fire()                                68
    (in module decision- test_state_sets_timer_and_uses_it()
nengine.framework.logicengine.tests.test_rule_with_negated_ifact), module decision-
88 nengine.framework.dataspace.tests.test_Reaper),
test_rule_that_does_not_fire()                                68
    (in module decision- test_status_during_startup() (in module decisio-
nengine.framework.logicengine.tests.test_simple_configuration), nengine.framework.tests.test_status_during_startup),
88 109
test_rule_that_fires() (in module decision- test_stop_queue_logger() (in module decisio-
nengine.framework.logicengine.tests.test_cascaded_rules), nengine.framework.modules.tests.test_QueueLogger),
86 92
test_rule_that_fires() (in module decision- test_store_taskmanager() (in module decisio-
nengine.framework.logicengine.tests.test_pandas_fact), nengine.framework.dataspace.datasources.tests.test_datasource_
87 63
test_rule_that_fires() (in module decision- test_store_taskmanager() (in module decisio-
nengine.framework.logicengine.tests.test_rule_with_negated_ifact), nengine.framework.dataspace.tests.test_dataspace),
88 70
test_rule_that_fires() (in module decision- test_supports_config() (in module decisio-
nengine.framework.logicengine.tests.test_simple_configuration), nengine.framework.modules.tests.test_module_decorators),
88 92
test_same_source_types_separate_channels() test_syntax_error() (in module decisio-
    (in module decision- nengine.framework.logicengine.tests.test_facts),
nengine.framework.tests.test_same_source_types), 87
108
test_setup_queue_logging() (in module decisio- test_syntax_error_in_config_names_bad_file()
nengine.framework.modules.tests.test_QueueLogger), (in module decision-
91 nengine.framework.config.tests.test_config),
46
test_shared_source() (in module decisio- test_transform_structure() (in module decisio-
nengine.framework.tests.test_shared_sources), nengine.framework.modules.tests.test_Transform),
109 92
test_simple_fact() (in module decisio- test_translate_all() (in module decisio-
nengine.framework.logicengine.tests.test_facts), nengine.framework.modules.tests.test_translate_product_name),
87 93
test_source_fail_can_be_fixed() test_translate_illegal_characters()
    (in module decision- (in module decision-
nengine.framework.dataspace.tests.test_Reaper), nengine.framework.modules.tests.test_translate_product_name),
68 93
test_source_structure() (in module decisio- test_translate_none() (in module decisio-
nengine.framework.modules.tests.test_Source), nengine.framework.modules.tests.test_translate_product_name),
92 93
test_start_delay() (in module decisio- test_translate_simple() (in module decisio-
nengine.framework.dataspace.tests.test_Reaper), nengine.framework.modules.tests.test_translate_product_name),
68 93
test_start_queue_logger() (in module decisio- test_translate_with_underscores()
nengine.framework.modules.tests.test_QueueLogger), (in module decision-
91 nengine.framework.modules.tests.test_translate_product_name),
93
test_start_stop() (in module decisio- test_trivial_configuration() (in module decisio-
nengine.framework.dataspace.tests.test_Reaper), nengine.framework.logicengine.tests.test_construction),
68
test_start_stop_stop() (in module decisio- 86

```



## U

`update()` (*decisionengine.framework.dataspace.datasource.DataSource* `zloads()` (in module *decisionengine.framework.dataspace.datablock*), method), 75

`update()` (*decisionengine.framework.dataspace.datasources.null.NullDataSource* `DataSource` method), 66

`update()` (*decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.datasource\_api.SQLAlchemyDS* `SQLAlchemyDS` method), 53

`update()` (*decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.SQLAlchemyDS* `SQLAlchemyDS` method), 61

`update()` (*decisionengine.framework.dataspace.dataspace.DataSpace* `DataSpace` method), 76

`update()` (*decisionengine.framework.engine.SourceWorkers.SourceWorkers* `SourceWorkers` method), 85

`update()` (*decisionengine.framework.taskmanager.SourceProductCache.SourceProductCache* `SourceProductCache` method), 99

## V

`valid_dir()` (in module *decisionengine.framework.config.policies*), 49

`valid_states` (*decisionengine.framework.dataspace.datablock.Metadata* `Metadata` attribute), 72

`validated_workflow()` (in module *decisionengine.framework.taskmanager.module\_graph*), 101

`ValidConfig` (class in *decisionengine.framework.config* `ValidConfig`), 48

`value` (*decisionengine.framework.dataspace.datasources.sqlalchemy\_ds.db\_schema.Dataprodut* `Dataprodut` attribute), 54

`verify_products()` (in module *decisionengine.framework.modules.Module*), 93

## W

`wait_for_n_writes()` (in module *decisionengine.framework.tests.WriteToDisk*), 105

`wait_until()` (*decisionengine.framework.taskmanager.ProcessingState.ProcessingState* `ProcessingState` method), 98

`wait_while()` (*decisionengine.framework.engine.ChannelWorkers.ChannelWorker* `ChannelWorker` method), 80

`wait_while()` (*decisionengine.framework.taskmanager.ProcessingState.ProcessingState* `ProcessingState` method), 98

`Worker` (class in *decisionengine.framework.taskmanager.module\_graph*), 100

`WriteToDisk` (class in *decisionengine.framework.tests* `WriteToDisk`), 105

## Z

`z.dumps()` (in module *decisionengine.framework.dataspace.datablock*),