
decisionengine

Release 1.6.99.post6.post17+g8cdeb67e

Fermilab

Aug 25, 2021

CONTENTS

1	Release Notes	3
2	Developer Documentation	17
3	Jenkins CI pipeline	19
4	Source code	25
5	Indices and tables	87
	Python Module Index	89
	Index	93

The Decision Engine is a critical component of the HEP Cloud Facility. It provides the functionality of resource scheduling for disparate resource providers, including those which may have a cost or a restricted allocation of cycles

RELEASE NOTES

1.1 Release Notes

HEPCloud's Decision Engine release notes.

The latest release is the designated production release. Decision Engine will support also N-1. New feature development will happen in the development branch and go in the next (N+1) release.

1.1.1 Release 1.6.2

Patch level (bug fix) release.

Issues fixed in this release

Bugs fixed

- [DEM 200](#) (part of it): Invoke correctly channels shutdown: ([75eaa90](#))
- no issue: Use regular expression to support fail_on_error feature ([1386d20](#))

Enhancements:

- Improved CI support (e.g. added pylint tests)
- [217](#): Add option to de-client `-print-product` to only print the column names in a data block and-or to print one or more records in key/value format. ([c4c7681](#))

Full list of commits since version 1.6.1

[c4c7681](#): Updated de-query-tool w/ cherry pick of fixes from latest version of PR#332

[f964d4b](#): Fixup use of `pytest_postgresql` for version 3.0.0

[635ffd1](#): Also run pylint for extra sanity checks

[11676ff](#): Fixed function w/ the same name

[b8278f6](#): Add de-query-tool

[75eaa90](#): Merge pull request #335 from shreyb/publisher_shutdown_from_1.6

[77e3d79](#): Added `set_to_shutdown` method to TaskManager and accompanying test

[1386d20](#): Merge branch 'knoepfel-fix-fail-on-error' into 1.6

73a18b1: Merge branch 'fix-fail-on-error' of <https://github.com/knoepfel/decisionengine> into knoepfel-fix-fail-on-error

4f49fb7: Merge branch 'jcpunk-finish-setuptools' into 1.6

a5e5d39: Merge branch 'finish-setuptools' of <https://github.com/jcpunk/decisionengine> into jcpunk-finish-setuptools

a1ed252: Merge branch 'vitodb-pylint' into 1.6

c8eddda: Merge branch 'pylint' of <https://github.com/vitodb/decisionengine> into vitodb-pylint Meerging PR#317 to release branch 1.6

d7c43b9: Use regular expression to support fail_on_error feature.

ada6692: add support to run pylint tests

efb1e57: Finish migration to pure setuptools

e4dc35e: Merge pull request #314 from jcpunk/jsonnet_syntax

87e32c2: Merge pull request #294 from jcpunk/move-reaper

dec85d5: Merge pull request #319 from jcpunk/task-loop

4108472: Merge pull request #320 from jcpunk/container-swig

920af1c: Merge pull request #321 from knoepfel/include-init-files

650dfa: Don't forget __init__.py files.

1b412e0: The latest m2crypto seems to need swig now

a6e3ab1: Merge pull request #313 from jcpunk/conf-test

1205636: Simplify run loop

de553a7: fix test_client_with_no_server_verbose unit test for Jenkins CI (#315)

30e59dc: fix test_client_with_no_server_verbose unit test for Jenkins CI (#315)

10384a8: Move reaper into its own place and reuse state logic

250c14b: The _validate function doesn't permit missing 'PRODUCES'

5ae1ce9: Make sure syntax error in config names the problem

b899fa2: Add SourceProxy module test. (#307)

7b3df14: Increase coverage of utils (#304)

ddba2a3: Fix duplicate entry warning (#311)

915673f: Test modules minimally (#298)

bc0c21a: Some repos may error out, don't let them kill the build (#297)

924a704: doc: add 1.6.1 release notes

b1ab4d3: doc: fix typo

85e5d71: postgresql: do not print stack trace for low level library (#309)

255c641: Setuptools uses entry return value as an error msg (#303)

2fd8db4: Fix name to match expectations (#305)

9cddb70: updated release notes

7fe0358: Error in more clean methods (#300)

84aa506: Fix a bug in setup.py parsing of requirements. (#301)

a58b61b: fix typo in release notes

33660bf: fixed a typo[locuser@fermicloud462 decisionengine]

1.1.2 Release 1.6.1

Patch level (bug fix) release.

Issues fixed in this release

- 306 : /etc/decisionengine/decision_engine.conf as shipped in RPM is wrong format (de0aef3)
- 275 : Running de-client --stop-channel <channel> results in KeyError (59fb44e)

Full list of commits since version 1.6.0

d7ccd8a : doc: fix typo

ac48e50 : updated release notes

de0aef3 : Fix name to match expectations (#305)

59fb44e : postgresql: do not print stack trace for low level library (#309) (#310)

2162bbe : Setuptools uses entry return value as an error msg (#308)

b0fd9fb : 1.6.0 package backports (#302)

1.1.3 Release 1.6.0

In this release:

- The logic engine has been rewritten in pure python. This removes the last C++ dependency the decision engine had. The build system has been updated accordingly.
- Migrated to setuptools package development library. This build system is the standard vanilla python build system provided with the python distribution. Build configurations have been updated and rpm packaging remains the primary distribution method.
- Completed logging implementation.
- Improvements in error handling and code coverage.
- Improvements in Jenkins and GitHub actions CI/CD pipelines.

Issues fixed in this release

- 44 : Logic Engine doesn't handle missing values gracefully (743effc)
- 253 : Decision engine can sometimes start up at boot time before network name resolution is working (ae04db5)

Full list of commits since version 1.5.0

2551e07 : More coverage for de-client (#296)
dde3945 : Make sure actions either complete in time or die (#295)
381861c : Update Jenkins pipeline configuration (#292)
eb771f4 : Try to cleanup Dockerfile PATH issue (#291)
780cb56 : fix unittest doc
8680942 : update unittest documentation
8154b24 : Fixup sphinx doc (#290)
5f7e13a : enhancements in logging and error handling in dataspace dir (#283)
3d92725 : Add missing runtime requirement (#286)
743effc : Allow conversion from errors to false values in logic-engine expressions. (#284)
124dcab : Inherit version from setuptools_scm if possible (#287)
3669803 : added missing "" as line continuation
761f1d9 : Drop invalid **init.py**
dc0e71b : migrate to setuptools (#264)
3b6f1bf : Make reaper reset state when starting from stopped proc (#280)
b2f9061 : added ISO-8601 format to time in logging. changed name of function for better clarity. (#279)
0a74fe1 : Improved DE client usage (#281)
ebf53e3 : Added shutdown method to Publisher class (#278)
f95ab6d : Address some flake8/black reports (#274)
1c383b7 : Automatically pull in our settings from about.py (#273)
e71f186 : logging and error handling enhancements to taskmanager directory (#277)
7de9ab9 : Increase Reaper log verbosity (#267)
019d245 : Update actions to follow new best practices (#272)
b84e847 : Avoid possible sync issues in reaper startup (#271)
891975f : Remove vestigial C++ files. (#270)
42e5e1f : enhancements in logging and exception handling in newly added logicengine files (#265)
38effe6 : Ensure the scheduler has started the thread before returning (#269)
db54fa1 : Start testing on PyPy with pycpg2cffi (#223)
cc44058 : Squashed commit of the following: (#263)
d6548e9 : Enhanced logging in the logicengine directory files (#261)
c341bf7 : Better match our workflow with codecov (#260)
1fbe44d : Use 'new' syntax for forward compat (#259)
2294b0b : Do a limited pin on version requirements (#256)
bcda470 : Python implementation of logic engine (#246)
c6721b4 : address comment on RB

ae04db5 : Add Wants and After (network-online.target) dependency

1a96b14 : Fix action repodata

a70cee8 : Move to CodeCov.io

7b16b4e : Add Wants and Requires dependencies (#258)

76c3670 : Move to CodeCov.io (#254)

e7ba013 : Fix action repodata (#255)

d7e72f2 : revert 3.9 test

b04154b : added 1.5.0 release notes

a03da29 : remove 3.9 to see if documentatoin gets generated

1.1.4 Release 1.5.0

In this release:

- Introduce data product query interface
- Cleanup of Lagic Engine code
- Improvements in error handling
- Improvements in testing and CI

Issues fixed in this release

- 217 , 218 : Add option to de-client --print-product to only print the column names in a data block and-or to print one or more records in key/value format (fe7abcf)
- 240 : Logic Engine call leads to immediate taskmanager segfault exit (d855aa0)
- 239 : implement data product browsing interface (fe9faa9)

Full list of commits since version 1.4.1

d66c54b : Add PEP-0396 metadata (#243)

bfc91a6 : More compat between psycopg2/psycopg2cffi (#248)

f5d31a6 : Cleanup Fixture FIXME (#249)

0dfaf3c : Adding docker documentation (#251)

4b166a2 : Since we are python3 only now, drop python-six compat layer (#252)

fe7abcf : Add format support to de-client (#217) (#241)

df5a3d7 : Add wheel support for easier testing (#247)

7de970d : Add place to inject env if need be (#242)

84e2930 : Fix race in test case (#250)

d855aa0 : Fix fact-lookup to support duplicate names in separate rules. (#245)

51370fb : Resolve fixture 'quickstart' issue (#238)

3ea9129 : Move from TravisCI to raw actions (#235)

fe9faa9 : implement data product browsing interface (#239)
cf0f3c0 : Add support to use custom base docker container to run tests (#234)
d91722f : Compat with psycpg2cffi (#233)
7d15a8c : Test failing source proxy. (#232)
b9a4bbb : Add debug logs for which threads are created #176 (#231)
6e6f4c9 : Updated Jenkins configuration documentation (#229)
2d9fd7b : Log if config passed validation #117 (#230)
60c46d3 : Self-test needs a real namespace to 'import numpy' in new python eval (#228)
a120077 : Test that the doc actually builds during CI (#227)
4b6240a : Extend timeout for coverage combine (#226)
b059696 : Update workflow per changes at github (#225)
7a71cac : Use newer compilers/runtimes (#224)
15ffd93 : Add header for strict includes (#222)
71b141a : Add special PyPy only requirement (#221)
9dbb932 : Move Python C extension to versioned .so file (#220)
ea7ade5 : Migrate from boost-python to pybind11 (#215)
e6b2eae : Add python 3.9 to testing matrix (#219)
04c8f9c : Add the option to print columns types on de-client (#216)
8815dc6 : Logic-engine cleanups (#211)
086d0d5 : fix missing back tick
54cc084 : modified release notes
24744cf : Synchronize access to the task managers (#214)
87a7fda : replde dash with underscore
743d0fd : try sphinx_rtd_theme
18c7909 : added 1.4.0 release notes
ff3d491 : force docker pull when building the docker container to make sure to use an updated base layer (#210)

1.1.5 Release 1.4.1

In this release:

- Bug fixes to 1.4.0 release

Issues fixed in this release

- [213](#) : de-client hangs under certain circumstances in version 1.4 and greater (race condition) ([84ecfe2](#))

Full list of commits since version 1.4.0

[9799b9a](#) : update release version to 1.4.1

[84ecfe2](#) : Synchronize access to the task managers (#214)

[751b6b8](#) : Address data races; remove need to sleep in unit tests (#205)

1.1.6 Release 1.4.0

In this release:

- Improvements in error handling and client/server interactions
- Added log rotation by time
- Improvements in code coverage

Issues fixed in this release

- [153](#) : Have de-client --print-product return different error message if product does not exist ([18a950c](#))
- [171](#) : yum update on decision engine rpm from python2 to python3 doesn't undo the symlinks ([eb85c97](#))
- [188](#) : Channel debug info now leaks into startup.log ([99d20a5](#))
- [208](#) : Error when trying to run reaper in version 1.4.0 ([84eccf3](#))

Full list of commits since version 1.3

[84eccf3](#) : Fix typo in reaper script. (#209)

[d836abf](#) : next RC

[926944a](#) : Fix coveralls reporting (#198)

[b95c323](#) : Updating base Dockerfile (#199)

[d302e31](#) : Help jsonnet, which doesn't understand PosixPath objects. (#204)

[2d791a7](#) : Test configuration policies. (#197)

[236e27a](#) : Ensure items are returned in a stable order (#202)

[e974f5f](#) : add pylint and pycodestyle (#203)

[fbe7616](#) : Test task manager (#196)

[686ca80](#) : require more recent version of pytest-postgresql (#195)

[99d20a5](#) : Fix double-logging problem. (#192)

[4ce3d17](#) : A set of fixtures to simplify unit tests (#183)

[65f8052](#) : Fix typo (#190)

[f3a4be8](#) : Protect against None workers (#187)

ec310fb : remove py3 from package name
7006489 : bump version to 1.4.0rc
158d835 : decisionengine/framework/modules: Fix SourceProxy retries (#184)
1356bf1 : Add support to test any branch in Jenkins (#182)
692fa8e : Add timeout support for unit test on Jenkins (#181)
e3d6e6a : Updated Jenkins documentation to take into account unit tests timeout parametr (#180)
2586a3e : Configuration redesign (#168)
fac984d : Fix error with DBUtils import. Looks like names of modules changed (#175)
7d661ee : Move postgres-specific implementation to postgres source. (#174)
eb85c97 : Rpm (#173)
10fe843 : Adding log rotation by time (#170)
a8d239b : Various improvements. (#167)
d9b92ee : Ignore vim's *.swp files (#166)
d9f72ef : Fix call to shutdown_timeout (and add sample entry to config) (#165)
3161795 : Add drops for items using tables being dropped (#164)
77d186d : Show output of test runtimes in travis (#163)
81820a4 : Allow server to start with no channels. (#161)
49879a6 : DE server and client usability improvements (#160)
de91c4f : Add tests to default and override config (#158)
14df1f6 : Use python fallback for options (#159)
ac64a92 : Drop python 2.7 integration tests since we are python3 only (#157)
d963301 : Update Jenkins pipeline to properly test closing PR (#156)
64248cb : Merge 'runtime' tests into running channel tests (#150)
065ad77 : Adding Jenkins pipeline documentation (#155)
18a950c : fix print-product to report non-existing product as such (#154)
6493735 : Fix invalid attribute name (#152)
d953c6a : Remove unnecessary set_start_method call (#149)
c8c9b65 : guarantee that process is killed so test never hang (#147)
f1542b6 : Channel test (#146)
7f349a8 : Fix faulty TaskManager state type (#145)
d50f1c4 : fix logging regression introduced in f5e299969e0611e3480e9fa2782052df... (#142)
becfa26 : Pass the correct type. (#144)
1a60daf : DecisionEngine: fix typo (#143)
9e7b867 : Updating Jenkins pipeline configuration (#140)
e3a6703 : fix regression introduced in f5e299969e0611e3480e9fa2782052df86d7c4ed (#141)
4900bc6 : Restore runtime test. (#139)

0823f3d : Consolidate DE server/client tests into one file. (#138)

4f84435 : A few more access fixes.

160cfd1 : Fix task manager state access.

c00d819 : A few more cleanups.

ec087e2 : Various cleanups

a309ffe : Improvements to DE client CLI.

1.1.7 Release 1.3.0

In this release:

- Introduced Jsonnet based configuration system
- Improved logging
- Improved coverage of datasource

Full list of commits since version 1.2

239e82c : postgresql: improve SQL query (#133)

668eb1f : Update to make the code compatible with both python and JSON based config files (#129)

afd8837 : Configuration-manager fixes (#128)

571e2be : Remove pip installed system python packages

407d9ed : Update Dockerfile

1fefc69 : Implement unit tests for datablock.py (#122)

43c8d7a : Adjust global configuration to include program-option values. (#126)

2840813 : Switch to Jsonnet configuration system (#125)

5c4ae0e : logging changes: added config file and command line interface (#124)

6697f22 : Further config-manager testing and factorizations. (#123)

fa89fd0 : Insulate multiprocessing test from parent environment. (#120)

139a537 : Allow empty base directory for log file. (#119)

f14d40c : Factorize configuration-loading steps. (#118)

e00afee : Enhance testing and error reporting of ConfigManager (#117)

c3d1be3 : Python 3 upgrades. (#116)

e7399af : Header fix (#114)

0456abf : Adding editor config file, see <https://editorconfig.org/> (#115)

82112d1 : Dockerfile: fetch osg 3.5 repo rpm (#113)

97c21b1 : osg version 3.5 (#112)

33f28a8 : Introduce jsonnet dependency (#110)

3f8b55e : improve server error handling (#108)

f15588e : added 1.2.0 release notes

b433325 : Remove unnecessary 'main' functionality. (#107)

1.1.8 Release 1.2.0

In this release:

- Switched to python3
- Improved coverage
- Database data retention : added reaper to remove data older than configurable number of days
- Improved logging

decisionengine

3dfe167 : Jenkins pipeline improvements (#106)

22a7073 : pull request for review request 137 (#105)

cafffb2 : Make it possible to run code directly (for tests), and (#100)

802e98b : replace psycog2 with psycog2-binary (#101)

573ce8f : Jenkins pipeline improvements (#99)

9d08835 : Run coveralls even under failed state (#97)

bc1df4b : Add tests for PostgreSQL datasource (#71)

c1ac391 : Fix missing py-modules.html (#96)

8dbfdee : Setup gh-pages doc workflow (#94)

cd4a01a : Doc (#93)

673080d : set version to 1.2.0 (for now). Supply conf file that corresponds to (#91)

f912225 : Db (#92)

dc8b68a : Add reaper to the RPC (#83) (#90)

29ade91 : adding .Jenkinsfile with Jenkins pipeline configuration (#86)

c1dfe5c : Don't exclude E1004 from pylint, do exclude line breaks (#89)

440f949 : Fix varname (#88)

313d135 : Compress (#87)

6b8dc4b : Revert "Add reaper to the RPC (#83)"

dbea8e5 : Update utils.sh so pytest will complete.

e848316 : Update to postgresql11

7f4b805 : Add reaper to the RPC (#83)

0ba2c51 : remove astpp module and dependencies it pulls in (#81)

6b8eab9 : don't track test coverage of tests (#80)

0da18ec : made reaper.py executable

aca24a3 : make reaper.py executable, make symbolic link to it from /usr/bin (#72)

0202acf : Implementation of data reaper (#70)

16b6be1 : Simple changes for Python 3 deployment (#69)
fd2418c : Fix warnings caught by PEP-8 Speaks.
d16359b : Python 3 (and other) simplifications.
3c7b6b7 : Only run Github Actions for python3.6 (#68)
453cbba : Update README.md
b27ed53 : remove unnecessary (and atually harmful) python shebang (#66)

decisionengine_modules

30d928b : clone version 1.2.0 of decisionengine
ae7c5a6 : Jenkins pipeline improvements (#236)
310befd : T198 (#235)
a65886d : Fix import as reported in : <https://github.com/HEPCloud/decisionengin...> (#232)
93711cc : Run coveralls even if tests fail (#229)
03d763a : Jenkins pipeline improvements (#230)
f48d30f : Fix/223 (#228)
c8aa262 : github ticket 199 (#222)
0323bda : Address : https://github.com/HEPCloud/decisionengine_modules/issues/224 (#226)
62e4df6 : Add support to run CI on Jenkins (#221)
5ab1541 : bump master version to 1.2.0 (for now) (#219)
bc19c65 : decisionengine_modules/NERSC: Added retry loop for NERSC API Calls (#220)
41a50de : Sync up pep8speaks and run_pylint.sh with decisionengine settings (#218)
db4634f : silence pylint error (#217)
1b95141 : Fix whitespace around operator error
746ea38 : ignore W503
8a8b5f4 : remove unused variable
a6668bf : fix PEP8 warnings
13773ee : address pep8 warnings
6bea4ca : silence pylint error
f589895 : Pass sort=True parameter to fix future warning (#215)
a1d0507 : fixing pep8 warning
a10bd17 : debugging one import error
ec501ad : make coveralls.io links work
deab1a7 : T201 (#204)
69f2645 : Add coveragerc
6d8a5f5 : decisionengine_modules/NERSC: Make Nersc API call backward-compatible with old config (#196)
a7e0af9 : Only run Github Actions for python3.6 (#24)

1.1.9 Release 1.1.0

In this release:

- Fixed. https://github.com/HEPCloud/decisionengine_modules/issues/108 “Supply Postgres script to delete fields in main database before a certain date”
- significant code cleanup and pep8 compliance
- unit test work
- CI (GitHub actions and Travis) is introduced

commits

f894b1d : Skip unittest (#77)

632e64b : Add ipython

f681a79 : Make python 2.7 tests run on 1.1 branch

d6a32c0 : implementation of data reaper (#75)

2ad8614 : Use sparse checkout for first checkout to get .github/actions (#65)

812f032 : Cat output of pytest log Exit pylint entrypoint with the line count of pep8 and pylint logs Deal with (detach from ...) Only tar up (S)RPMS dirs for rpm build.

6b05ec7 : Fix errors reported by run_pylint (#62)

d9f5b66 : Setup pep8speaks

c3b8ac2 : Run github actions as non-root uid. Install packages in virtualenv and remove system rpms.

ae01f9e : Support Python 3 for Boost Python

579761c : Support Python 3 for Boost Python

044b979 : Remove unnecessary using declarations.

00f6d00 : Add extra header dependency due to Boost Python ommission.

24e0795 : Apply clang-format

17c17f9 : Remove JSON dependency.

faa0b22 : Massive cleanup.

07b555f : Updates to Github Actions to allow building with python3.6

fef6c11 : Fix errors when running pylint.sh multiple times

da6f077 : Autopep8 -i fixes

39fe5b3 : TaskManager: fix calling log_exception with correct number of arguments and minor format changes to reduce PEP8 warnings

17396da : logicengine: get rid of compuler warnings

01dc3d1 : Only track what we need

b609d73 : Configure coveralls (and some minor cleanup)

bd9ed5e : Many C++ cleanups

2a61876 : Add Badges

c864f27 : Do not call pytest fixtures directly.

307db5f : white space fix

882b58f : fix unit tests

1da687c : Replace Boost facilities with C++ STL ones.

5a6e6b1 : Run tests on push

8404245 : Add missing Boost regex library dependency.

ceb5fe7 : Apply clang-format to files that were missed earlier.

3de9940 : Apply clang-format to C++ code.

8a8f560 : Cache venv directory instead

ad017ce : Build private boost for testing

928c64a : Test pip cache

358939a : Adjust CMakeLists.txt files to use correct Python versions

9f0ddb3 : Add pylint github action.

5e6ce4a : Remove more unused C++ files.

63717fe : Setup travis to use new cmake var

74fab2a : Use cmake argument -DPYVER=3.6 to build python3 library <https://fermicloud140.fnal.gov/reviews/r/31/>

843f30c : Minor cleanups per travis-lint

a538cac : Remove unused C++ files.

4c9d125 : Update repo where action is taken from

87fb2d9 : Update rpms installed in docker image. Update entrypoint.sh to use cmake3.

199ee87 : Find python3 libraries using cmake3 from epel rpm Also need to install python3-devel

4c79d2c : Remove unused GNUmakefiles.

94342ee : Add unit test as a Github Action

1a0e102 : more advanced travis.yml

0be413f : Add helper file for pip

7794327 : Make recursive import happy

7005c78 : Add simple target

de8b0fa : python3 compliance: replace string.join() where appropriate, handle UserDict

2662e6c : note required packages

3b87119 : Add missing header includes.

3e79b84 : Remove defunct code and its tests

b1dbe1a : Ensure attribs are defined at **init**

c4ad78a : Correct logger arguments do avoid duplicate string parse

a8dcc67 : Remove unused imports (per pylint)

d3502b5 : Remove obsolete CVS directories.

d744111 : add six module to the list of required modules

0a9b1e8 : Fix class declaration

b83157e : Handle metaclasses

549f33b : Add config for Travis CI

ee71044 : Drop trailing white space

3f82af6 : Python3 forward compatible syntax

28bf291 : Add safe (for python 2.7) python3 compatible syntax

1d1d76f : prepare for python3

DEVELOPER DOCUMENTATION

JENKINS CI PIPELINE

3.1 Decisionengine CI with Jenkins pipeline

Jenkins dashboard with Decisionengine framework CI results is available [here](#).

A CI build is triggered any time a PR is created/closed or a commit is made to an existing PR. There are also *nightly CI builds* to test a list of predefined branches.

The Jenkins pipeline runs *pylint* and *unit_tests* test suites alongside the *rpmbuild* stage.

The Jenkins dashboard looks like this:

Jenkins > CI > decisionengine_pipeline >

[Back to Dashboard](#)
[Status](#)
[Changes](#)
[Build with Parameters](#)
[Delete Pipeline](#)
[Configure](#)
[Full Stage View](#)
[GitHub](#)
[Job Config History](#)
[Rename](#)
[GitHub PR](#)
[Pipeline Syntax](#)
[GitHub PR Polling Log](#)
[Set Next Build Number](#)

Pipeline decisionengine_pipeline

DE pipeline

[Last Successful Artifacts](#)

mail.results	2.04 KB	view
pep8.merge150.log	0 B	view
pylint.merge150.log	0 B	view
pytest.log	7.89 KB	view
results.merge150.log	5.16 KB	view
rpmbuild.tar	1.37 MB	view

[Recent Changes](#)

Stage View

Average stage times:
(Average full run time: ~27min 25s)

	Declarative: Checkout SCM	DE tests	pylint	unit_tests	rpmbuild
	1s	51ms	15min 17s	13min 24s	9min 44s
319#PR#150 Sep 02 17:00 No Changes	602ms	49ms	12min 45s	13min 49s failed	6min 20s
318#PR#150 Sep 02 16:36 No Changes	617ms	49ms	27min 5s	23min 43s	19min 15s
317#PR#150 Sep 02 16:25 No Changes	1s	54ms	21min 14s	20min 1s	15min 5s
316#PR#150 Sep 02 16:23 No Changes	1s	54ms	21min 4s	18min 41s	14min 36s
315#PR#150 Sep 02 16:16 No Changes	2s	57ms	22min 32s	19min 24s	14min 31s
314#PR#150 Sep 02 16:10 No Changes	921ms	55ms	16min 43s	14min 16s	7min 23s
313#PR#150 Sep 02 16:08 4 commits	789ms	42ms	16min 56s	14min 11s	8min 17s

Build History [trend](#)

find

- 319#PR#150 Sep 2, 2020 5:00 PM [#150](#)
- 318#PR#150 Sep 2, 2020 4:36 PM [#150](#)
- 317#PR#150 Sep 2, 2020 4:25 PM [#150](#)
- 316#PR#150 Sep 2, 2020 4:23 PM [#150](#)
- 315#PR#150 Sep 2, 2020 4:16 PM [#150](#)
- 314#PR#150 Sep 2, 2020 4:10 PM [#150](#)
- 313#PR#150 Sep 2, 2020 4:08 PM [#150](#)
- 312#PR#149 Sep 2, 2020 3:38 PM [#149](#)
- 311#PR#149 Sep 2, 2020 3:31 PM [#149](#)
- 310#PR#149 Sep 2, 2020 3:23 PM [#149](#)
- 309#PR#147 Sep 2, 2020 12:42 PM [#147](#)

On the bottom left side there is the list of recent CI builds that are named after the PR or the branch tested.

On the bottom right side the dashboard shows for each CI build detailed status for each test suite.

Hovering the mouse over the *status box* for each CI build stage, a tool-tip with a button to access log details shows up.

Next to the build number the symbol  gives access to a menu with the list of artifacts stored for that build. Those artifacts include logs and the tarball with RPMs.

From the panel on the left side it is possible to access the PR on GitHub by clicking on the PR icon that looks like this  [#142](#).

On occasion it could be useful to trigger a manual CI build to test a branch on the official DE GitHub repository or on the user fork. For this purpose, on the top left panel the user can click on the  **Build with Parameters** button, and this panel shows up

Pipeline decisionengine_pipeline

This build requires parameters:

DOCKER_IMAGE	<input type="text" value="vitodb/decision-engine-ci:jenkins"/>
	Docker image name to use. Default is: vitodb/decision-engine-ci:jenkins
DE_REPO	<input type="text" value="https://github.com/HEPCloud/decisionengine/"/>
	Decisionengine repo. Default is: https://github.com/HEPCloud/decisionengine/
BRANCH	<input type="text" value="master"/>
	Branch to test. Default is: master
PYTEST_TIMEOUT	<input type="text" value="300"/>
	Timeout in seconds for unit_tests (it applies to individual unit test) Default is: 300

Build

the user can modify these parameters to customize what code to test with the CI build.

The *DE_REPO* parameter can point to the user fork or to the main repository.

The *BRANCH* parameter can point to the desired branch to test.

The *PYTEST_TIMEOUT* parameter is the timeout in seconds for *unit_tests*.

When ready, by clicking on the *Build* button, the CI build will start.

The [pipeline configuration](#) is part of the decisionengine repo.

3.1.1 Nightly CI build configuration

The nightly CI build for Decisionengine framework uses this [Jenkins project](#) that triggers a CI build using the Jenkins pipeline described above to test a list of predefined branches.

Jenkins ▸ **CI** ▸ **decisionengine_ci** ▸

Back to Dashboard

Status

Changes

Workspace

Build Now

Configure

Delete Multi-configuration project

Rebuild Last

Job Config History

Rename

Set Next Build Number

Project decisionengine_ci

Decision Engine CI running inside dedicated docker container

Configurations

BRANCH=master BRANCH=1.4

Subprojects

Static

- decisionengine_modules_pipeline(non-blocking)
- decisionengine_pipeline(non-blocking)

Permalinks

- Last build (#295), 7 hr 6 min ago
- Last stable build (#295), 7 hr 6 min ago
- Last successful build (#295), 7 hr 6 min ago
- Last completed build (#295), 7 hr 6 min ago

Build History [trend](#) ^

find

#295	Nov 19, 2020 2:23 AM
#294	Nov 18, 2020 2:23 AM
#293	Nov 17, 2020 2:23 AM

Branches to test are defined using the project matrix as shown in the picture below. Each branch in the list (here *master* and *1.4*) spawns an independent CI build.

The screenshot shows the Jenkins Configuration Matrix configuration page. The 'User-defined Axis' section is expanded, showing a 'Name' field with the value 'BRANCH' and a 'Values' field with the value 'master 1.4'. There is a red 'X' icon in the top right corner of the axis configuration area and a blue question mark icon next to the 'Values' field.

In the *Build* section of the configuration it is set the list of Jenkins subprojects to be triggered, in this case we have *decisionengine_pipeline* and *decisionengine_modules_pipeline*.

The *Parameters* text box is used to override parameters of each Jenkins subproject with a custom value.

In total this Jenkins project triggers 4 CI builds, i.e. 2 branches X 2 Jenkins subprojects.

The screenshot shows the Jenkins Build configuration page. The 'Trigger/call builds on other projects' section is expanded, showing 'Projects to build' as 'decisionengine_pipeline,decisionengine_modules_pipeline' and a checkbox for 'Block until the triggered projects finish their builds'. Below this, the 'Predefined parameters' section is expanded, showing 'Parameters' as 'BRANCH=\${BRANCH}'. There are red 'X' icons in the top right corner of the 'Trigger/call builds on other projects' and 'Predefined parameters' sections, and blue question mark icons next to the 'Projects to build' and 'Parameters' fields.

Finally the *Build Triggers* section is used to setup the schedule for the periodic build, in this case it is scheduled to run at about 2 AM.

Jenkins will choose the actual time depending on the actual load on the system.

GeneralAdvanced Project OptionsSource Code ManagementBuild TriggersConfiguration MatrixBuild Environment

BuildPost-build Actions

Build Triggers

☐ Trigger builds remotely (e.g., from scripts)☐ Build after other projects are built☒ Build periodically

Schedule

H 2 * * *

Would last have run at Wednesday, November 4, 2020 2:23:53 AM CST;
would next run at Thursday, November 5, 2020 2:23:53 AM CST.

SOURCE CODE

4.1 Welcome to decisionengine's documentation!

4.1.1 decisionengine package

Subpackages

decisionengine.framework package

Subpackages

decisionengine.framework.config package

Subpackages

decisionengine.framework.config.tests package

Submodules

decisionengine.framework.config.tests.test_config module

```
decisionengine.framework.config.tests.test_config._channel_config_dir(relative_dir)
decisionengine.framework.config.tests.test_config._global_config_file(relative_filename)
decisionengine.framework.config.tests.test_config.load()
decisionengine.framework.config.tests.test_config.test_channel_empty_config(load, capsys,
                                                                              caplog)
decisionengine.framework.config.tests.test_config.test_channel_empty_dictionary(load,
                                                                                  caplog)
decisionengine.framework.config.tests.test_config.test_channel_invalid_modules_list(load,
                                                                                      caplog)
decisionengine.framework.config.tests.test_config.test_channel_invalid_modules_no_keys(load,
                                                                                       caplog)
decisionengine.framework.config.tests.test_config.test_channel_invalid_modules_string(load,
                                                                                       caplog)
```

```
decisionengine.framework.config.tests.test_config.test_channel_loading(caplog)
decisionengine.framework.config.tests.test_config.test_channel_module_missing_all(load,
                                                                                    caplog)
decisionengine.framework.config.tests.test_config.test_channel_module_missing_module(load,
                                                                                    caplog)
decisionengine.framework.config.tests.test_config.test_channel_module_missing_parameters(load,
                                                                                    caplog)
decisionengine.framework.config.tests.test_config.test_channel_names(load)
decisionengine.framework.config.tests.test_config.test_channel_no_config_files(load)
decisionengine.framework.config.tests.test_config.test_channel_no_modules(load)
decisionengine.framework.config.tests.test_config.test_empty_config(load)
decisionengine.framework.config.tests.test_config.test_empty_dict(load)
decisionengine.framework.config.tests.test_config.test_empty_dict_with_leading_comment(load)
decisionengine.framework.config.tests.test_config.test_minimal_jsonnet_right_extension(load,
                                                                                    cap-
                                                                                    sys)
decisionengine.framework.config.tests.test_config.test_minimal_jsonnet_wrong_extension(load,
                                                                                    cap-
                                                                                    sys)

decisionengine.framework.config.tests.test_config.test_minimal_python(load, capsys)
decisionengine.framework.config.tests.test_config.test_syntax_error_in_config_names_bad_file(load)
decisionengine.framework.config.tests.test_config.test_wrong_type(load)
```

decisionengine.framework.config.tests.test_policies module

```
decisionengine.framework.config.tests.test_policies.test_channel_config_dir(tmp_path,
                                                                              monkeypatch)
decisionengine.framework.config.tests.test_policies.test_global_config_dir(tmp_path,
                                                                              monkeypatch)
decisionengine.framework.config.tests.test_policies.test_global_config_file(tmp_path,
                                                                              monkeypatch)
decisionengine.framework.config.tests.test_policies.test_valid_dir(tmp_path)
```

decisionengine.framework.config.tests.test_validconfig module

```
decisionengine.framework.config.tests.test_validconfig._global_config_file(relative_filename)
decisionengine.framework.config.tests.test_validconfig.test_empty_config()
decisionengine.framework.config.tests.test_validconfig.test_invalid_config()
decisionengine.framework.config.tests.test_validconfig.test_no_such_file()
decisionengine.framework.config.tests.test_validconfig.test_wrong_type_config()
```

Module contents

Submodules

decisionengine.framework.config.ChannelConfigHandler module

Manager of channel configurations.

The ChannelConfigHandler manages only channel configurations and not the global decision-engine configuration. It is responsible for loading channel configuration files and validating that the channels have the correct configuration artifacts and inter-module product dependencies.

```
class decisionengine.framework.config.ChannelConfigHandler.ChannelConfigHandler(global_config,
                                                                              chan-
                                                                              nel_config_dir)
```

Bases: object

_load_channel(*channel_name, path*)

get_channels()

load_all_channels()

Load all channel configurations inside the stored channel-configuration directory.

Any cached configurations will be dropped prior to reloading.

load_channel(*channel_name*)

Load a single configuration for a channel with the supplied name.

The behavior is to read a configuration file whose path is:

<cached channel config. dir>/{channel_name}.jsonnet

where the cached channel-configuration directory was stored whenever the ChannelConfigHandler object was created, and {channel_name} is the value of the supplied method argument.

print_channel_config(*channel*)

decisionengine.framework.config.ChannelConfigHandler.**_check_keys**(*channel_conf_dict*)

check that channel config has mandatory keys :type data: dict

decisionengine.framework.config.ChannelConfigHandler.**_make_de_logger**(*global_config*)

decisionengine.framework.config.ValidConfig module

ValidConfig represents a valid JSON document.

The decision engine requires each of its configuration files to be valid JSON. This is achieved by either supplying a valid Jsonnet or JSON document upfront, or by providing a Python dictionary that can be trivially converted to a JSON document.

Vetting of a file for JSON validity happens upon construction of a 'ValidConfig' object. A fully constructed 'ValidConfig' object thus corresponds to a valid JSON document.

```
class decisionengine.framework.config.ValidConfig.ValidConfig(filename)
```

Bases: collections.UserDict

ValidConfig represents a valid JSON configuration in the form of a dictionary.

In addition to the normal dictionary operations, users may call 'dump()' to print out in a string form the JSON configuration.

```
_abc_impl = <_abc._abc_data object>
```

```
dump()
```

Print dictionary data to a valid JSON string.

```
decisionengine.framework.config.ValidConfig._config_from_file(config_file)
```

```
decisionengine.framework.config.ValidConfig._convert_to_json(config_file)
```

Attempt to convert JSON non-compliant configuration into a compliant one.

This is a temporary facility to aid the migration of Python-based configurations to Jsonnet-based ones. Python dictionaries that are similar in structure to JSON documents are generally trivially convertible.

decisionengine.framework.config.policies module

Decision-engine default configuration policies.

For the decision-engine process, the configuration policies are:

- The global configuration file must be named ‘decision_engine.jsonnet’ and it must reside in (a) a directory that can be accessed through the ‘CONFIG_PATH’ environment variable, or (b) the /etc/decisionengine directory.
- All channel configurations must reside in (a) a directory accessible through the ‘CHANNEL_CONFIG_PATH’ environment variable, or (b) a ‘config.d’ subdirectory of the /etc/decisionengine directory.

The utilities provided in this module provide simple means of accessing the configuration artifacts according to the policies listed above. Please consult the documentation for each function below for more detailed information.

```
decisionengine.framework.config.policies.channel_config_dir(parent_dir=None)
```

Retrieve the channel configuration directory as a pathlib.Path object.

This function returns a path object according to the following precedence rules:

1. If the ‘parent_dir’ argument is provided, the returned path object will correspond to ‘{parent_dir}/config.d’.
2. If the ‘CHANNEL_CONFIG_PATH’ environment variable has been set, the returned path object will correspond to \${CHANNEL_CONFIG_PATH}.
3. If neither 1 or 2 apply, the returned path object corresponds to ‘{global_config_dir()}/config.d’ (see documentation for ‘global_config_dir()’).

Regardless of the precedence rule used, the returned path object must be a valid directory or an exception will be raised—i.e. if the ‘parent_dir’ argument is supplied, and the resulting path object is not a valid directory, the function will exit with an exception and not attempt rule 2 or 3.

```
decisionengine.framework.config.policies.global_config_dir()
```

Retrieve global configuration dir as pathlib.Path object.

This is the directory that houses the ‘decision_engine.jsonnet’ global configuration file.

This function checks that the ‘CONFIG_PATH’ variable has been set or will use /etc/decisionengine otherwise. If the path exists as a directory, then the directory path is returned as a string; otherwise an exception is raised.

```
decisionengine.framework.config.policies.global_config_file(parent_dir=None)
```

Return the pathlib.Path object corresponding to the global configuration.

If supplied, the ‘parent_dir’ is assumed to be the full path corresponding to a directory containing the ‘decision_engine.jsonnet’ file. If not provided, the global configuration directory is determined based on the behavior of the ‘global_config_dir()’ function.

An exception is raised if no ‘decision_engine.jsonnet’ file is found.

`decisionengine.framework.config.policies.valid_dir(path, scope)`

Throws if the supplied path object is not a directory, otherwise returns the path object.

Module contents

decisionengine.framework.dataspace package

Subpackages

decisionengine.framework.dataspace.datasources package

Subpackages

decisionengine.framework.dataspace.datasources.sqlalchemy_ds package

Submodules

decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource_api module

The datasource layer for our abstraction

class `decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource_api.SQLAlchemyDS(config_dict)`

Bases: `decisionengine.framework.dataspace.datasource.DataSource`

A DecisionEngine data source via the SQL Alchemy ORM

```
{
    "dataspace": {
        "datasource": { "module": "decisionengine.framework.dataspace.datasources.sqlalchemy_ds",
                        "name": "SQLAlchemyDS", "params": {
                            "pool_size": 5, "max_overflow": 10, "timeout": 30,
                            # url is mandatory, but any engine keyword is accepted here.
                            "url": "dialect[+driver]://user:password@host/dbname"
                        }
                    }
    }
}
```

Exceptions should be caught and logged by the caller.

_abc_impl = `<_abc._abc_data object>`

close()

Close all connections to the database

Returns None

connect()

Create a pool of database connections

Returns None

create_tables()

Create database tables

Returns None

delete_data_older_than(days)

Delete data older than interval

Parameters **days** (*int*) – remove data older than this many days

Returns None

duplicate_datablock(taskmanager_id, generation_id, new_generation_id)

For the given taskmanager_id, make a copy of the datablock with given generation_id, set the generation_id for the datablock copy

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to clone
- **new_generation_id** (*int*) – generation id to create

Returns None

get_datablock(taskmanager_id, generation_id)

Return the entire datablock from the dataproduct table for the given taskmanager_id, generation_id

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to locate

Returns with all set keys and their associated values

Return type dict

get_dataproduct(taskmanager_id, generation_id, key)

Return the data from the dataproduct table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to locate
- **key** (*str*) – key for the value

Returns The possibly binary value stored earlier

Return type obj

get_dataproducts(taskmanager_id, key=None)

Return list of all data products associated with taskmanager_id

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **key** (*str*) – key for the value

Returns each element is the matching row as a dict()

Return type tuple

get_header(taskmanager_id, generation_id, key)

Return the header from the header table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to locate
- **key** (*str*) – key for the value

Returns

fields in order are: taskmanager.taskmanager_id, header.taskmanager_id,
header.generation_id, header.key, header.create_time, header.expiration_time,
header.scheduled_create_time, header.creator, header.schema_id

Return type tuple

get_last_generation_id(*taskmanager_name, taskmanager_id=None*)

Return last generation id for current task manager or taskmanager w/ task_manager_id.

Parameters

- **taskmanager_name** (*str*) – name of taskmanager to retrieve
- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve

Returns the largest generation stored within the database

Return type int

get_metadata(*taskmanager_id, generation_id, key*)

Return the metadata from the metadata table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to locate
- **key** (*str*) – key for the value

Returns

fields in order are: taskmanager.taskmanager_id, metadata.taskmanager_id, meta-
data.generation_id, metadata.key, metadata.state, metadata.generation_time, meta-
data.missed_update_count

Return type tuple

get_schema(*table=None*)

Given the table name return it's schema

get_taskmanager(*taskmanager_name, taskmanager_id=None*)

Find the task manager by name/uuid in the database get back the primary key.

If multiples match, find highest primary key.

Parameters

- **taskmanager_name** (*str*) – name of taskmanager to retrieve
- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve

Returns the matching row, column names as keys

Return type dict

get_taskmanagers(*taskmanager_name=None, start_time=None, end_time=None*)

Find taskmanagers that meet our search

Parameters

- **taskmanager_name** (*str*) – name of taskmanager to retrieve
- **start_time** (*datetime*) – Datetime to confine against
- **end_time** (*datetime*) – Datetime to confine against

Returns each element is a dict() matching row, column names as keys

Return type list

insert(*taskmanager_id, generation_id, key, value, header, metadata*)

Insert data into respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to create
- **key** (*str*) – key for the value
- **value** (*obj*) – Value can be an object or dict or a binary
- **header** (*datablock.Header*) – Header for the value
- **metadata** (*datablock.Metadata*) – Metadata for the value

Returns None

reset_connections()

Reset the connection to the database. So long as self.engine isn't undef, the engine can still make new connections if new db actions happen. It just won't have any open at this time.

Returns None

store_taskmanager(*name, taskmanager_id, datestamp=None*)

Store TaskManager in database

Parameters

- **name** (*str*) – name of taskmanager to retrieve
- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **datestamp** (*datetime*) – datetime of created object, defaults to 'now'

Returns the primary key of the row in the database

Return type int

update(*taskmanager_id, generation_id, key, value, header, metadata*)

Update the data in respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to update
- **key** (*str*) – key for the value
- **value** (*obj*) – Value can be an object or dict or a binary
- **header** (*datablock.Header*) – Header for the value
- **metadata** (*datablock.Metadata*) – Metadata for the value

Returns None

decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema module

The table layout and utilities for our SQLAlchemy ORM

class decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.**Base**(**kwargs)
 Bases: object

The base class of the class hierarchy.

When called, it accepts no arguments and returns a new featureless instance that has no instance attributes and cannot be given any.

_sa_registry = <sqlalchemy.orm.decl_api.registry object>

metadata = MetaData()

registry = <sqlalchemy.orm.decl_api.registry object>

class decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.**Dataproduct**(**kwargs)
 Bases: [sqlalchemy.orm.decl_api.Base](#)

The PRIMARY KEY on this table isn't used...

Existing code appears to depend on column order.

```
_sa_class_manager = {'generation_id':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'id':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'key':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'taskmanager':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'taskmanager_id':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'value':
<sqlalchemy.orm.attributes.InstrumentedAttribute object>}
```

generation_id

id

key

taskmanager

taskmanager_id

value

class decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.**Header**(**kwargs)
 Bases: [sqlalchemy.orm.decl_api.Base](#)

The PRIMARY KEY on this table isn't used...

The existing code has a hard expectation on the time columns being BIGINT rather than datetime objects burried within the classes.

Looks like there was an inital goal of a relationship with the Schema table, but it may not be in use

Existing code appears to depend on column order.

```
_sa_class_manager = {'create_time':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'creator':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'expiration_time':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'generation_id':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'id':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'key':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'scheduled_create_time':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'schema_id':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'taskmanager':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'taskmanager_id':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>}
```

create_time

creator

expiration_time

generation_id

id

key

scheduled_create_time

schema_id

taskmanager

taskmanager_id

```
class decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Metadata(**kwargs)  
    Bases: sqlalchemy.orm.decl\_api.Base
```

The PRIMARY KEY on this table isn't used....

The existing code has a hard expectation on the state field as a 'text' element.

The existing code has a hard expectation on the time columns being BIGINT rather than datetime objects burried within the classes.

Existing code appears to depend on column order.

```
_sa_class_manager = {'generation_id':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'generation_time':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'id':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'key':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'missed_update_count':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'state':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'taskmanager':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>, 'taskmanager_id':  
<sqlalchemy.orm.attributes.InstrumentedAttribute object>}
```

generation_id

generation_time

id

key

missed_update_count

state

taskmanager

taskmanager_id

```
class decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Schema(**kwargs)
    Bases: sqlalchemy.orm.decl_api.Base
```

This table may not be in use

Has a one-to-many relationship with: Header - may not be in use

```
_sa_class_manager = {'schema': <sqlalchemy.orm.attributes.InstrumentedAttribute
object>, 'schema_id': <sqlalchemy.orm.attributes.InstrumentedAttribute object>}
```

schema

schema_id

```
class decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Taskmanager(**kwargs)
    Bases: sqlalchemy.orm.decl_api.Base
```

Has a one-to-many relationship with: Header Metadata Dataproduct

changes cascade on: Header Metadata Dataproduct

Existing code appears to depend on column order.

```
_sa_class_manager = {'datestamp': <sqlalchemy.orm.attributes.InstrumentedAttribute
object>, 'name': <sqlalchemy.orm.attributes.InstrumentedAttribute object>,
'sequence_id': <sqlalchemy.orm.attributes.InstrumentedAttribute object>,
'task_dataproduct': <sqlalchemy.orm.attributes.InstrumentedAttribute object>,
'task_header': <sqlalchemy.orm.attributes.InstrumentedAttribute object>,
'task_metadata': <sqlalchemy.orm.attributes.InstrumentedAttribute object>,
'taskmanager_id': <sqlalchemy.orm.attributes.InstrumentedAttribute object>}
```

datestamp

name

sequence_id

task_dataproduct

task_header

task_metadata

taskmanager_id

decisionengine.framework.dataspace.datasources.sqlalchemy_ds.utils module

Code not written by us

```
decisionengine.framework.dataspace.datasources.sqlalchemy_ds.utils.add_engine_pidguard(engine)
```

Based on <https://stackoverflow.com/questions/62920507/using-sqlalchemy-connection-pooling-queues-with-python-multiprocessing>

```
decisionengine.framework.dataspace.datasources.sqlalchemy_ds.utils.clone_model(model,
                                                                                **kwargs)
```

Based on <https://stackoverflow.com/a/55991358>

```
decisionengine.framework.dataspace.datasources.sqlalchemy_ds.utils.orm_as_dict(obj)
```

Based on : <https://stackoverflow.com/a/37350445>

Module contents

Top level import so we can rationally segment items of the ORM

class decisionengine.framework.dataspace.datasources.sqlalchemy_ds.**SQLAlchemyDS**(*config_dict*)
Bases: *decisionengine.framework.dataspace.datasource.DataSource*

A DecisionEngine data source via the SQL Alchemy ORM

```
{
    "dataspace": {
        "datasource": { "module": "decisionengine.framework.dataspace.datasources.sqlalchemy_ds",
                        "name": "SQLAlchemyDS", "params": {
                            "pool_size": 5, "max_overflow": 10, "timeout": 30,
                            # url is mandatory, but any engine keyword is accepted here.
                            "url": "dialect[+driver]://user:password@host/dbname"
                        }
                    }
    }
}
```

Exceptions should be caught and logged by the caller.

_abc_impl = <_abc._abc_data object>

close()

Close all connections to the database

Returns None

connect()

Create a pool of database connections

Returns None

create_tables()

Create database tables

Returns None

delete_data_older_than(days)

Delete data older than interval

Parameters **days** (*int*) – remove data older than this many days

Returns None

duplicate_datablock(taskmanager_id, generation_id, new_generation_id)

For the given taskmanager_id, make a copy of the datablock with given generation_id, set the generation_id for the datablock copy

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to clone
- **new_generation_id** (*int*) – generation id to create

Returns None

get_datablock(*taskmanager_id*, *generation_id*)

Return the entire datablock from the dataproduct table for the given taskmanager_id, generation_id

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to locate

Returns with all set keys and their associated values

Return type dict

get_dataproduct(*taskmanager_id*, *generation_id*, *key*)

Return the data from the dataproduct table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to locate
- **key** (*str*) – key for the value

Returns The possibly binary value stored earlier

Return type obj

get_dataproducts(*taskmanager_id*, *key=None*)

Return list of all data products associated with with taskmanager_id

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **key** (*str*) – key for the value

Returns each element is the matching row as a dict()

Return type tuple

get_header(*taskmanager_id*, *generation_id*, *key*)

Return the header from the header table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to locate
- **key** (*str*) – key for the value

Returns

fields in order are: taskmanager.taskmanager_id, header.taskmanager_id,
header.generation_id, header.key, header.create_time, header.expiration_time,
header.scheduled_create_time, header.creator, header.schema_id

Return type tuple

get_last_generation_id(*taskmanager_name*, *taskmanager_id=None*)

Return last generation id for current task manager or taskmanager w/ task_manager_id.

Parameters

- **taskmanager_name** (*str*) – name of taskmanager to retrieve
- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve

Returns the largest generation stored within the database

Return type int

get_metadata(*taskmanager_id*, *generation_id*, *key*)

Return the metadata from the metadata table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to locate
- **key** (*str*) – key for the value

Returns

fields in order are: taskmanager.taskmanager_id, metadata.taskmanager_id, metadata.generation_id, metadata.key, metadata.state, metadata.generation_time, metadata.missed_update_count

Return type tuple

get_schema(*table=None*)

Given the table name return it's schema

get_taskmanager(*taskmanager_name*, *taskmanager_id=None*)

Find the task manager by name/uuid in the database get back the primary key.

If multiples match, find highest primary key.

Parameters

- **taskmanager_name** (*str*) – name of taskmanager to retrieve
- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve

Returns the matching row, column names as keys

Return type dict

get_taskmanagers(*taskmanager_name=None*, *start_time=None*, *end_time=None*)

Find taskmanagers that meet our search

Parameters

- **taskmanager_name** (*str*) – name of taskmanager to retrieve
- **start_time** (*datetime*) – Datetime to confine against
- **end_time** (*datetime*) – Datetime to confine against

Returns each element is a dict() matching row, column names as keys

Return type list

insert(*taskmanager_id*, *generation_id*, *key*, *value*, *header*, *metadata*)

Insert data into respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to create
- **key** (*str*) – key for the value
- **value** (*obj*) – Value can be an object or dict or a binary

- **header** (`datablock.Header`) – Header for the value
- **metadata** (`datablock.Metadata`) – Metadata for the value

Returns None

reset_connections()

Reset the connection to the database. So long as self.engine isn't undef, the engine can still make new connections if new db actions happen. It just wont have any open at this time.

Returns None

store_taskmanager(*name, taskmanager_id, datestamp=None*)

Store TaskManager in database

Parameters

- **name** (*str*) – name of taskmanager to retrieve
- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **datestamp** (*datetime*) – datetime of created object, defaults to 'now'

Returns the primary key of the row in the database

Return type int

update(*taskmanager_id, generation_id, key, value, header, metadata*)

Update the data in respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*str/uuid*) – id of taskmanager to retrieve
- **generation_id** (*int*) – generation id to update
- **key** (*str*) – key for the value
- **value** (*obj*) – Value can be an object or dict or a binary
- **header** (`datablock.Header`) – Header for the value
- **metadata** (`datablock.Metadata`) – Metadata for the value

Returns None

decisionengine.framework.dataspace.datasources.tests package

Submodules

decisionengine.framework.dataspace.datasources.tests.fixtures module

pytest fixtures/constants

decisionengine.framework.dataspace.datasources.tests.fixtures.PG_DE_DB_WITHOUT_SCHEMA(*request:*

_pytest.fixtures.FixtureRequest)
→
psycpg2.extensions.cursor

Fixture factory for PostgreSQL.

Parameters **request** – fixture request object

Returns postgresql client

`decisionengine.framework.dataspace.datasources.tests.fixtures.PG_DE_DB_WITH_SCHEMA(PG_DE_DB_WITHOUT_SCHEMA)`
Load our PG schema into the database via this fixture so pytest knows the limitations on parallel usage of this database scope.

`decisionengine.framework.dataspace.datasources.tests.fixtures.PG_PROG(request: _pytest.fixtures.FixtureRequest, tmpdir_factory: _pytest.tmpdir.TempdirFactory) → Iterator[pytest_postgresql.executor.PostgreSQLExecutor]`

Process fixture for PostgreSQL.

Parameters `request` – fixture request object

Returns tcp executor

`decisionengine.framework.dataspace.datasources.tests.fixtures.SQLALCHEMY_PG_WITH_SCHEMA(PG_DE_DB_WITHOUT_SCHEMA)`
Get a blank database from `pytest_postgresql`. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

`decisionengine.framework.dataspace.datasources.tests.fixtures.SQLALCHEMY_TEMPFILE_SQLITE(tmp_path)`
Setup an SQLite database with the `pytest tmp_path` fixture. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

`decisionengine.framework.dataspace.datasources.tests.fixtures.datasources(request)`
This parameterized fixture will setup up various datasources.

Add datasource objects to `DATASOURCES_TO_TEST` once they've got our basic schema loaded. And adjust our *if* statements here until we are SQLAlchemy only.

Pytest should take it from there and automatically run it through all the tests using this fixture.

`decisionengine.framework.dataspace.datasources.tests.fixtures.mock_data_block()`
This fixture replaces the standard datablock implementation.

The current DataBlock implementation does not own any data products but forwards them immediately to a backend datasource. The only implemented datasource requires Postgres, which is overkill when needing to test simple data-product communication between modules.

This mock datablock class directly owns the data products, thus avoiding the need for a datasource backend. It is anticipated that a future design of the DataBlock will own the data products, thus making this mock class unnecessary.

decisionengine.framework.dataspace.datasources.tests.test_datasource_api module

This test plan covers a generic dataspace object via pytest parameters.

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_create_tables(datasource)`
`create_tables()` should be safe to call multiple times

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_delete_data_older_than_age(datasource)`
Can we delete old entries

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_duplicate_datablock(datasource)`
Can we duplicate taskmanager1 and all its entries

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_datablock(datasource)`

`decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_dataproduct(datasource)`
Can we get the dataproduct by uuid with key

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_dataproduct_not_exist
Does it error out if we ask for bogus information?

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_dataproducts(datasource)
Can we get the dataproducts by uuid and uuid with key

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_dataproducts_not_exist
Does it error out if we ask for bogus information?

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_header(datasource)
Can we fetch a header?

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_header_not_exist(datasource)
Does it error out if we ask for a bogus header?

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_last_generation_id(datasource)
Can we get the last generation id by name or name and uuid

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_last_generation_id_not_exist
Does it error out if we ask for a bogus taskmanager?

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_metadata(datasource)
Can we fetch a metadata element?

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_metadata_not_exist(datasource)
Does it error out if we ask for a bogus metadata element?

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_taskmanager_exists(datasource)
Can I get a taskmanager by name or name and uuid

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_taskmanager_not_exist
This should error out

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_taskmanagers(datasource)
Can I get multiple task managers

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_get_taskmanagers_not_exist
Do I error out when asking for garbage

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_has_config(datasource)
This should have a *config* dict we can pass to jsonnet

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_insert(datasource)
Can we insert new elements

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_reset_connections(datasource)
reset_connections() should be safe to call any time

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_store_taskmanager(datasource)
Can we make new entries

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_update(datasource)
Do updates work as expected

decisionengine.framework.dataspace.datasources.tests.test_datasource_api.test_update_bad(datasource)
Do updates fail to work on bogus taskmanager as expected

decisionengine.framework.dataspace.datasources.tests.test_postgresql module`decisionengine.framework.dataspace.datasources.tests.test_postgresql.test_generate_insert_query()`**Module contents****Submodules****decisionengine.framework.dataspace.datasources.null module****class** `decisionengine.framework.dataspace.datasources.null.NullDataSource(config_dict)`Bases: `decisionengine.framework.dataspace.datasource.DataSource`

Implementation of data source ABC that does nothing

`_abc_impl = <_abc._abc_data object>`**close()**

Close all connections to the database

connect()

Create a pool of database connections

create_tables()

Create database tables

delete_data_older_than(*days*)

Delete data older than interval :type days: long :arg days: remove data older than interval

duplicate_datablock(*taskmanager_id, generation_id, new_generation_id*)

For the given taskmanager_id, make a copy of the datablock with given generation_id, set the generation_id for the datablock copy

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **new_generation_id** (int) – generation_id of the new datablock created

get_datablock(*taskmanager_id, generation_id*)

Return the entire datablock from the dataproduct table for the given taskmanager_id, generation_id

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data

get_dataproduct(*taskmanager_id, generation_id, key*)

Return the data from the dataproduct table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

get_dataproducts(*taskmanager_id*, *key=None*)

Return list of all data products associated with with taskmanager_id

Parameters **key** (string) – data product key

get_header(*taskmanager_id*, *generation_id*, *key*)

Return the header from the header table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

get_last_generation_id(*taskmanager_name*, *taskmanager_id=None*)

Return last generation id for current task manager or taskmanager w/ task_manager_id.

Parameters

- **taskmanager_name** (string) – task manager name
- **taskmanager_id** (string) – task manager id

get_metadata(*taskmanager_id*, *generation_id*, *key*)

Return the metadata from the metadata table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

get_schema(*table=None*)

Given the table name return it's schema

Parameters **table** (string) – Name of the table

get_taskmanager(*taskmanager_name*, *taskmanager_id=None*)

Retrieve TaskManager :type taskmanager_name: **string** :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: **string** :arg taskmanager_id: id of taskmanager to retrieve

get_taskmanagers(*taskmanager_name=None*, *start_time=None*, *end_time=None*)

Retrieve TaskManagers :type taskmanager_name: **string** :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: **string** :arg taskmanager_id: id of taskmanager to retrieve

insert(*taskmanager_id*, *generation_id*, *key*, *value*, *header*, *metadata*)

Insert data into respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value
- **value** (object) – Value can be an object or dict
- **header** (Header) – Header for the value
- **header** – Metadata for the value

reset_connections()

Drop any cached connections and reconnect to the database

store_taskmanager(*name, taskmanager_id, datestamp=None*)

Store TaskManager :type taskmanager_name: **string** :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: **string** :arg taskmanager_id: id of taskmanager to retrieve :type datestamp: **datetime** :arg datestamp: datetime of created object, defaults to 'now'

update(*taskmanager_id, generation_id, key, value, header, metadata*)

Update the data in respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (**string**) – taskmanager_id for generation to be retrieved
- **generation_id** (**int**) – generation_id of the data
- **key** (**string**) – key for the value
- **value** (**object**) – Value can be an object or dict
- **header** (**Header**) – Header for the value
- **header** – Metadata for the value

decisionengine.framework.dataspace.datasources.postgresql module

class decisionengine.framework.dataspace.datasources.postgresql.**Postgresql**(*config_dict*)

Bases: [decisionengine.framework.dataspace.datasource.DataSource](#)

Implementation of postgresql data source

__query(*query_string, values=None, cursor_factory=None*)

_abc_impl = <_abc._abc_data object>

_delete(*sql_query, values=None*)

_insert(*table_name_or_sql_query, record=None*)

_insert_returning_result(*table_name_or_sql_query, record=None*)

_remove(*sql_query, values=None*)

_select(*query_string, values=None, cursor_factory=None*)

_select_dictresult(*sql_query, values=None*)

_select_getresult(*sql_query, values=None*)

_select_tuple(*sql_query, values*)

_update(*query_string, values=None*)

_update_returning_result(*query_string, values=None*)

close()

Close all connections to the database

connect()

Create a pool of database connections

create_tables()

Create database tables

delete_data_older_than(*days*)

Delete data older than days interval :type days: **int** :arg days: remove data older than days interval

duplicate_datablock(*taskmanager_id, generation_id, new_generation_id*)

For the given taskmanager_id, make a copy of the datablock with given generation_id, set the generation_id for the datablock copy

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **new_generation_id** (int) – generation_id of the new datablock created

get_connection()**get_datablock**(*taskmanager_id, generation_id*)

Return the entire datablock from the dataproduct table for the given taskmanager_id, generation_id

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data

get_dataproduct(*taskmanager_id, generation_id, key*)

Return the data from the dataproduct table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

get_dataproducts(*taskmanager_id, key=None*)

Return list of all data products associated with with taskmanager_id

Parameters **key** (string) – data product key

get_header(*taskmanager_id, generation_id, key*)

Return the header from the header table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

get_last_generation_id(*taskmanager_name, taskmanager_id=None*)

Return last generation id for current task manager or taskmanager w/ task_manager_id.

Parameters

- **taskmanager_name** (string) – task manager name
- **taskmanager_id** (string) – task manager id

get_metadata(*taskmanager_id, generation_id, key*)

Return the metadata from the metadata table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

get_schema(*table=None*)

Given the table name return it's schema

Parameters **table** (string) – Name of the table

get_taskmanager(*taskmanager_name, taskmanager_id=None*)

Retrieve TaskManager :type taskmanager_name: string :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: string :arg taskmanager_id: id of taskmanager to retrieve

get_taskmanagers(*taskmanager_name=None, start_time=None, end_time=None*)

Retrieve TaskManagers :type taskmanager_name: string :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: string :arg taskmanager_id: id of taskmanager to retrieve

insert(*taskmanager_id, generation_id, key, value, header, metadata*)

Insert data into respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value
- **value** (object) – Value can be an object or dict
- **header** (Header) – Header for the value
- **header** – Metadata for the value

reset_connections()

Drop any cached connections and reconnect to the database

store_taskmanager(*name, taskmanager_id, datestamp=None*)

Store TaskManager :type taskmanager_name: string :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: string :arg taskmanager_id: id of taskmanager to retrieve :type datestamp: datetime :arg datestamp: datetime of created object, defaults to 'now'

```
tables = {'dataprodukt': ['taskmanager_id TEXT', 'generation_id INT', 'key TEXT',  
'value BLOB'], 'header': ['taskmanager_id TEXT', 'generation_id INT', 'key TEXT',  
'create_time REAL', 'expiration_time REAL', 'scheduled_create_time REAL', 'creator  
TEXT', 'schema_id INT'], 'metadata': ['taskmanager_id TEXT', 'generation_id INT',  
'key TEXT', 'state TEXT', 'generation_time REAL', 'missed_update_count INT'],  
'schema': ['schema_id INT', 'schema BLOB']}
```

update(*taskmanager_id, generation_id, key, value, header, metadata*)

Update the data in respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value
- **value** (object) – Value can be an object or dict
- **header** (Header) – Header for the value
- **header** – Metadata for the value

decisionengine.framework.dataspace.datasources.postgresql.**generate_insert_query**(*table_name, keys*)

Generate insert query given table name and list of fields

Parameters

- **table_name** (str) – Name of the table to insert into
- **keys** – List of column names

Keys list**Return type** str - insert query**Module contents****decisionengine.framework.dataspace.tests package****Submodules****decisionengine.framework.dataspace.tests.fixtures module**

`decisionengine.framework.dataspace.tests.fixtures.PG_DE_DB_WITHOUT_SCHEMA(request: _pytest.fixtures.FixtureRequest) → psycopg2.extensions.connection`

Fixture factory for PostgreSQL.

Parameters **request** – fixture request object**Returns** postgresql client

`decisionengine.framework.dataspace.tests.fixtures.PG_DE_DB_WITH_SCHEMA(PG_DE_DB_WITHOUT_SCHEMA)`
Load our PG schema into the database via this fixture so pytest knows the limitations on parallel usage of this database scope.

`decisionengine.framework.dataspace.tests.fixtures.PG_PROG(request: _pytest.fixtures.FixtureRequest, tmpdir_factory: _pytest.tmpdir.TempdirFactory) → Iterator[pytest_postgresql.executor.PostgreSQLExecutor]`

Process fixture for PostgreSQL.

Parameters **request** – fixture request object**Returns** tcp executor

`decisionengine.framework.dataspace.tests.fixtures.SQLALCHEMY_PG_WITH_SCHEMA(PG_DE_DB_WITHOUT_SCHEMA)`
Get a blank database from `pytest_postgresql`. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

`decisionengine.framework.dataspace.tests.fixtures.SQLALCHEMY_TEMPFILE_SQLITE(tmp_path)`
Setup an SQLite database with the `pytest tmp_path` fixture. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

`decisionengine.framework.dataspace.tests.fixtures.datasources(request)`
This parameterized fixture will setup up various datasources.

Add datasource objects to `DATASOURCES_TO_TEST` once they've got our basic schema loaded. And adjust our *if* statements here until we are SQLAlchemy only.

Pytest should take it from there and automatically run it through all the tests using this fixture.

`decisionengine.framework.dataspace.tests.fixtures.dataspace(request)`

This parameterized fixture will setup up various datasources. Add datasource objects to DATA-SOURCES_TO_TEST once they've got our basic schema loaded. And adjust our *if* statements here until we are SQLAlchemy only.

Pytest should take it from there and automatically run it through all the tests using this fixture.

`decisionengine.framework.dataspace.tests.fixtures.load_sample_data_into_datasource(schema_only_db)`

load our sample test data into a dataspace This is a function not a fixture so you can run it on any datasource providing the right API.

decisionengine.framework.dataspace.tests.test_Reaper module

`decisionengine.framework.dataspace.tests.test_Reaper.config()`

`decisionengine.framework.dataspace.tests.test_Reaper.reaper(request)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_fail_bad_config(reaper, config)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_fail_missing_config(reaper,
config)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_fail_missing_config_key(reaper,
config)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_fail_small_retain(reaper)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_fail_small_run_interval(reaper)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_fail_start_two_reapers(reaper)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_fail_wrong_config_key(reaper,
config)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_just_stop_no_error(reaper)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_loop_of_start_stop_in_clumps(reaper)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_reap_default_state(reaper)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_reaper_can_reap(reaper)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_source_fail_can_be_fixed(reaper)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_start_delay(reaper)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_start_stop(reaper)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_start_stop_stop(reaper)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_state_can_be_active(reaper)`

`decisionengine.framework.dataspace.tests.test_Reaper.test_state_sets_timer_and_uses_it(reaper)`

decisionengine.framework.dataspace.tests.test_datablock module

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_constructor(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_duplicate(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_get_dataproducts(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_get_header(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_get_metadata(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_get_taskmanager(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_is_expired(dataspace)`

This test just validates the method/function exists. The stub within our default code should be replaced by a class inheriting from it. That class should have more rational return types.

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_is_expired_with_key(dataspace)`

This test just validates the method/function exists. The stub within our default code should be replaced by a class inheriting from it. That class should have more rational return types.

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_key_management(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_key_management_change_name(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_mark_expired(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_no_key_by_name(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_DataBlock_to_str(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_Header_constructor(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_Header_is_valid(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_Metadata_constructor(dataspace)`

`decisionengine.framework.dataspace.tests.test_datablock.test_Metadata_set_state(dataspace)`

decisionengine.framework.dataspace.tests.test_datablock_zlib module

`decisionengine.framework.dataspace.tests.test_datablock_zlib.test_compress()`

`decisionengine.framework.dataspace.tests.test_datablock_zlib.test_zdumps()`

`decisionengine.framework.dataspace.tests.test_datablock_zlib.test_zloads()`

decisionengine.framework.dataspace.tests.test_datasource module

`decisionengine.framework.dataspace.tests.test_datasource.test_has_methods_we_expect()`

decisionengine.framework.dataspace.tests.test_dataspace module

decisionengine.framework.dataspace.tests.test_dataspace.test_dataspace_config_finds_bad()

decisionengine.framework.dataspace.tests.test_dataspace.test_duplicate_datablock(dataspace)

Can we duplicate taskmanager1 and all its entries

decisionengine.framework.dataspace.tests.test_dataspace.test_get_datablock(dataspace)

Can we get the datablock content

decisionengine.framework.dataspace.tests.test_dataspace.test_get_dataproduct(dataspace)

Can we get the dataproduct by uuid with key

decisionengine.framework.dataspace.tests.test_dataspace.test_get_dataproduct_not_exist(dataspace)

Does it error out if we ask for bogus information?

decisionengine.framework.dataspace.tests.test_dataspace.test_get_dataproducts(dataspace)

Can we get the dataproducts by uuid and uuid with key

decisionengine.framework.dataspace.tests.test_dataspace.test_get_dataproducts_not_exist(dataspace)

Does it error out if we ask for bogus information?

decisionengine.framework.dataspace.tests.test_dataspace.test_get_header(dataspace)

Can we fetch a header?

decisionengine.framework.dataspace.tests.test_dataspace.test_get_header_not_exist(dataspace)

Does it error out if we ask for a bogus header?

decisionengine.framework.dataspace.tests.test_dataspace.test_get_last_generation_id(dataspace)

Can we get the last generation id by name or name and uuid

decisionengine.framework.dataspace.tests.test_dataspace.test_get_last_generation_id_not_exist(dataspace)

Does it error out if we ask for a bogus taskmanager?

decisionengine.framework.dataspace.tests.test_dataspace.test_get_metadata(dataspace)

Can we fetch a metadata element?

decisionengine.framework.dataspace.tests.test_dataspace.test_get_metadata_not_exist(dataspace)

Does it error out if we ask for a bogus metadata element?

decisionengine.framework.dataspace.tests.test_dataspace.test_get_taskmanager_exists(dataspace)

Can I get a taskmanager by name or name and uuid

decisionengine.framework.dataspace.tests.test_dataspace.test_get_taskmanager_not_exists(dataspace)

This should error out

decisionengine.framework.dataspace.tests.test_dataspace.test_get_taskmanagers(dataspace)

Can I get multiple task managers

decisionengine.framework.dataspace.tests.test_dataspace.test_get_taskmanagers_not_exist(dataspace)

Do I error out when asking for garbage

decisionengine.framework.dataspace.tests.test_dataspace.test_has_config(dataspace)

verify our config entry exists

decisionengine.framework.dataspace.tests.test_dataspace.test_insert(dataspace)

Can we insert new elements

decisionengine.framework.dataspace.tests.test_dataspace.test_store_taskmanager(dataspace)

Can we make new entries

decisionengine.framework.dataspace.tests.test_dataspace.test_update(dataspace)

Do updates work as expected

decisionengine.framework.dataspace.tests.test_dataspace.test_update_bad(dataspace)
Do updates fail to work on bogus taskmanager as expected

Module contents

Submodules

decisionengine.framework.dataspace.datablock module

class decisionengine.framework.dataspace.datablock.**DataBlock**(dataspace, name,
taskmanager_id=None,
generation_id=None,
sequence_id=None)

Bases: object

__insert(key, value, header, metadata)
Insert a new product into database with header and metadata

__update(key, value, header, metadata)
Update an existing product in the database with header and metadata

_setitem(key, value, header, metadata=None)
put a product in the database with header and metadata

duplicate()
Duplicate the datablock and return this new DataBlock. The intent is that at the point the duplication occurs there is only information from the sources in the DataBlock. This also increments the generation_id of this DataBlock.

TODO: Also update the header and the metadata information TODO: Make this threadsafe

Return type *DataBlock*

get(key, default=None)
Return the value associated with the key in the database

Return type dict

get_dataproducts(key=None)

get_header(key)
Return the Header associated with the key in the database

Return type *Header*

get_metadata(key)
Return the metadata associated with the key in the database

Return type *Metadata*

get_taskmanager(taskmanager_name, taskmanager_id=None)
Retrieve TaskManager :type taskmanager_name: string :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: string :arg taskmanager_id: id of taskmanager to retrieve :rtype: :obj: dict

The dictionary returned looks like : { 'datestamp': datetime.datetime(2017, 12, 20, 17, 37, 17, 503210, tzinfo=psycpg2.tz.FixedOffsetTimezone(offset=-360, name=None)),
'sequence_id': 135L, 'name': 'AWS_Calculations', 'taskmanager_id': '77B16EB5-C79E-45B0-B1B1-37E846692E1D' }

is_expired(*key=None*)

Check if the dataproduct for a given key or any key is expired

keys()

mark_expired(*expiration_time*)

Set the expiration_time for the current generation of the dataproduct and mark it as expired if expiration_time <= current time

put(*key, value, header, metadata=None*)

Put data into the DataBlock

store_taskmanager(*taskmanager_name, taskmanager_id*)

Persist TaskManager, returns sequence number :type taskmanager_name: string :type taskmanager_id: :obj: string :rtype: int

```
class decisionengine.framework.dataspace.datablock.Header(taskmanager_id, create_time=None,
                                                         expiration_time=None,
                                                         scheduled_create_time=None,
                                                         creator='module', schema_id=None)
```

Bases: collections.UserDict

_abc_impl = <_abc._abc_data object>

default_data_lifetime = 1800

is_valid()

Check if the Header has minimum required information

required_keys = {'create_time', 'creator', 'expiration_time',
'scheduled_create_time', 'schema_id', 'taskmanager_id'}

```
exception decisionengine.framework.dataspace.datablock.InvalidMetadataError
```

Bases: Exception

Errors due to invalid Metadata

```
class decisionengine.framework.dataspace.datablock.Metadata(taskmanager_id, state='NEW',
                                                            generation_id=None,
                                                            generation_time=None,
                                                            missed_update_count=0)
```

Bases: collections.UserDict

_abc_impl = <_abc._abc_data object>

required_keys = {'generation_id', 'generation_time', 'missed_update_count', 'state',
'taskmanager_id'}

set_state(*state*)

Set the state for the Metadata

valid_states = {'END_CYCLE', 'METADATA_UPDATE', 'NEW', 'START_BACKUP'}


```
class decisionengine.framework.dataspace.datablock.ProductRetriever(product_name,
                                                                    product_type,
                                                                    product_source)
```

Bases: object

```
decisionengine.framework.dataspace.datablock.compress(obj)
```

Compress python object :param obj: python object :return: compressed object

```
decisionengine.framework.dataspace.datablock.decompress(zbytes)
```

Decompress zipped byte stream, convert to string. :param zbytes: byte stream :return: uncompressed string

```
decisionengine.framework.dataspace.datablock.zdumps(obj)
```

Pickle and compress :param obj: a python object :return: compressed string

```
decisionengine.framework.dataspace.datablock.zloads(zbytes)
```

Decompress and unpickle If input is not compressed attempts to just unpickle it

Parameters **zbytes** – compressed bytes

Returns returns python object

decisionengine.framework.dataspace.datasource module

```
class decisionengine.framework.dataspace.datasource.DataSource(config)
```

Bases: object

```
_abc_impl = <_abc._abc_data object>
```

```
abstract close()
```

Close all connections to the database

```
abstract connect()
```

Create a pool of database connections

```
abstract create_tables()
```

Create database tables

```
dataprodut_table = 'dataprodut'
```

Name of the dataprodut table

```
abstract delete_data_older_than(days)
```

Delete data older that interval :type days: long :arg days: remove data older than interval

```
abstract duplicate_datablock(taskmanager_id, generation_id, new_generation_id)
```

For the given taskmanager_id, make a copy of the datablock with given generation_id, set the generation_id for the datablock copy

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **new_generation_id** (int) – generation_id of the new datablock created

```
abstract get_datablock(taskmanager_id, generation_id)
```

Return the entire datablock from the dataprodut table for the given taskmanager_id, generation_id

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data

abstract get_dataproduct(*taskmanager_id, generation_id, key*)

Return the data from the dataproduct table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

abstract get_dataproducts(*taskmanager_id, key*)

Return list of all data products associated with with taskmanager_id

Parameters **key** (string) – data product key

abstract get_header(*taskmanager_id, generation_id, key*)

Return the header from the header table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

abstract get_last_generation_id(*taskmanager_name, taskmanager_id=None*)

Return last generation id for current task manager or taskmanager w/ task_manager_id.

Parameters

- **taskmanager_name** (string) – task manager name
- **taskmanager_id** (string) – task manager id

abstract get_metadata(*taskmanager_id, generation_id, key*)

Return the metadata from the metadata table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

abstract get_schema(*table=None*)

Given the table name return it's schema

Parameters **table** (string) – Name of the table

abstract get_taskmanager(*taskmanager_name, taskmanager_id*)

Retrieve TaskManager :type taskmanager_name: **string** :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: **string** :arg taskmanager_id: id of taskmanager to retrieve

abstract get_taskmanagers(*taskmanager_name=None, start_time=None, end_time=None*)

Retrieve TaskManagers :type taskmanager_name: **string** :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: **string** :arg taskmanager_id: id of taskmanager to retrieve

header_table = 'header'

Name of the header table

abstract insert(*taskmanager_id, generation_id, key, value, header, metadata*)

Insert data into respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value
- **value** (object) – Value can be an object or dict
- **header** (Header) – Header for the value
- **header** – Metadata for the value

metadata_table = 'metadata'

Name of the metadata table

abstract reset_connections()

Drop any cached connections and reconnect to the database

abstract store_taskmanager(*taskmanager_name, taskmanager_id, datestamp=None*)

Store TaskManager :type taskmanager_name: string :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: string :arg taskmanager_id: id of taskmanager to retrieve :type datestamp: datetime :arg datestamp: datetime of created object, defaults to 'now'

taskmanager_table = 'taskmanager'

Name of the taskmanager table

abstract update(*taskmanager_id, generation_id, key, value, header, metadata*)

Update the data in respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value
- **value** (object) – Value can be an object or dict
- **header** (Header) – Header for the value
- **header** – Metadata for the value

decisionengine.framework.dataspace.dataspace module

class decisionengine.framework.dataspace.dataspace.**DataSet**(*config*)

Bases: object

DataSet class is collection of datablocks and provides interface to the database used to store the actual data

close()

delete(*taskmanager_id, all_generations=False*)

duplicate_datablock(*taskmanager_id, generation_id, new_generation_id*)

get_datablock(*taskmanager_id, generation_id*)

get_dataproduct(*taskmanager_id, generation_id, key*)

get_dataproducts(*taskmanager_id, key=None*)

get_header(*taskmanager_id, generation_id, key*)

get_last_generation_id(*taskmanager_name, taskmanager_id=None*)

```
get_metadata(taskmanager_id, generation_id, key)
get_taskmanager(taskmanager_name, taskmanager_id=None)
get_taskmanagers(taskmanager_name=None, start_time=None, end_time=None)
insert(taskmanager_id, generation_id, key, value, header, metadata)
mark_demented(taskmanager_id, keys, generation_id=None)
mark_expired(taskmanager_id, generation_id, key, expiry_time)
store_taskmanager(name, taskmanager_id, timestamp=None)
update(taskmanager_id, generation_id, key, value, header, metadata)
```

exception decisionengine.framework.dataspace.dataspace.DataSpaceConfigurationError

Bases: Exception

Errors related to database access

exception decisionengine.framework.dataspace.dataspace.DataSpaceConnectionError

Bases: Exception

Errors related to database access

exception decisionengine.framework.dataspace.dataspace.DataSpaceError

Bases: Exception

Errors related to database access

exception decisionengine.framework.dataspace.dataspace.DataSpaceExistsError

Bases: Exception

Errors related to database access

decisionengine.framework.dataspace.maintain module

class decisionengine.framework.dataspace.maintain.Reaper(*config*)

Bases: object

Reaper provides functionality of periodic deletion of data older than retention_interval in days

The class attributes indicate a rational set of defaults that shouldn't be altered by user configuration.

MIN_RETENTION_INTERVAL_DAYS = 7

MIN_SECONDS_BETWEEN_RUNS = 7080

_reaper_loop(*delay*)

The thread actually runs this.

reap()

Actually spawn the query to delete the old records. Lock the state as this task doesn't have a cancel option.

property retention_interval

We have data constraints, so use a property to track

property seconds_between_runs

We have data constraints, so use a property to track

start(*delay=0*)

Start thread with an optional delay to start the thread in X seconds

stop()

Try to stop the reaper, will block if the reaper cannot be interrupted.

Module contents

decisionengine.framework.engine package

Subpackages

decisionengine.framework.engine.tests package

Submodules

decisionengine.framework.engine.tests.fixtures module

pytest defaults

decisionengine.framework.engine.tests.fixtures.**DEServer**(*conf_path=None, conf_override=None, channel_conf_path=None, channel_conf_override=None, host='127.0.0.1', port=None*)

A DE Server using a private database

decisionengine.framework.engine.tests.fixtures.**PG_DE_DB_WITHOUT_SCHEMA**(*request: _pytest.fixtures.FixtureRequest*)
→
psycpg2.extensions.connection

Fixture factory for PostgreSQL.

Parameters **request** – fixture request object

Returns postgresql client

decisionengine.framework.engine.tests.fixtures.**PG_DE_DB_WITH_SCHEMA**(*PG_DE_DB_WITHOUT_SCHEMA*)
Load our PG schema into the database via this fixture so pytest knows the limitations on parallel usage of this database scope.

decisionengine.framework.engine.tests.fixtures.**PG_PROG**(*request: _pytest.fixtures.FixtureRequest, tmpdir_factory: _pytest.tmpdir.TempdirFactory*) →
Iterator[pytest_postgresql.executor.PostgreSQLExecutor]

Process fixture for PostgreSQL.

Parameters **request** – fixture request object

Returns tcp executor

decisionengine.framework.engine.tests.fixtures.**SQLALCHEMY_PG_WITH_SCHEMA**(*PG_DE_DB_WITHOUT_SCHEMA*)
Get a blank database from pytest_postgresql. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

decisionengine.framework.engine.tests.fixtures.**SQLALCHEMY_TEMPFILE_SQLITE**(*tmp_path*)
Setup an SQLite database with the pytest tmp_path fixture. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

decisionengine.framework.engine.tests.test_client_only module

```
decisionengine.framework.engine.tests.test_client_only.test_client_err_returned_as_rc()
    no de server is running, so -status should error
decisionengine.framework.engine.tests.test_client_only.test_client_err_returned_verbose_as_rc()
    no de server is running, so -status should error
decisionengine.framework.engine.tests.test_client_only.test_client_help(capfd)
decisionengine.framework.engine.tests.test_client_only.test_client_with_no_command_says_use_help()
decisionengine.framework.engine.tests.test_client_only.test_client_with_no_server()
decisionengine.framework.engine.tests.test_client_only.test_client_with_no_server_verbose()
decisionengine.framework.engine.tests.test_client_only.test_exclusive_options()
```

decisionengine.framework.engine.tests.test_query_tool_only module

```
decisionengine.framework.engine.tests.test_query_tool_only.test_client_err_returned_as_rc()
    no de server is running, so -status should error
decisionengine.framework.engine.tests.test_query_tool_only.test_client_err_returned_verbose_as_rc()
    no de server is running, so -status should error
decisionengine.framework.engine.tests.test_query_tool_only.test_query_tool_help()
decisionengine.framework.engine.tests.test_query_tool_only.test_query_tool_with_no_server()
decisionengine.framework.engine.tests.test_query_tool_only.test_query_tool_with_no_server_verbose()
```

decisionengine.framework.engine.tests.test_startup module

```
decisionengine.framework.engine.tests.test_startup._check_override(arguments)
decisionengine.framework.engine.tests.test_startup.test_change_port()
decisionengine.framework.engine.tests.test_startup.test_default_config()
```

Module contents

Submodules

decisionengine.framework.engine.DecisionEngine module

Main loop for Decision Engine. The following environment variable points to decision engine configuration file: `DECISION_ENGINE_CONFIG_FILE` if this environment variable is not defined the `DE-Config.py` file from the `../tests/etc/` directory will be used.

```
class decisionengine.framework.engine.DecisionEngine.DecisionEngine(global_config,
                                                                    channel_config_loader,
                                                                    server_address)
    Bases: socketserver.ThreadingMixIn, xmlrpc.server.SimpleXMLRPCServer
    _dataframe_to_column_names(df)
```

_dataframe_to_csv(*df*)**_dataframe_to_json**(*df*)**_dataframe_to_table**(*df*)**_dataframe_to_vertical_tables**(*df*)**_dispatch**(*method, params*)

Dispatches the XML-RPC method.

XML-RPC calls are forwarded to a registered function that matches the called XML-RPC method name. If no such function exists then the call is forwarded to the registered instance, if available.

If the registered instance has a `_dispatch` method then that method will be called with the name of the XML-RPC method and its parameters as a tuple e.g. `instance._dispatch('add',(2,3))`

If the registered instance does not have a `_dispatch` method then the instance will be searched to find a matching method and, if found, will be called.

Methods beginning with an `'_'` are considered private and will not be called.

block_until(*state, timeout=None*)**block_while**(*state, timeout=None*)**get_logger**()**handle_sighup**(*signum, frame*)**reaper_start**(*delay*)**reaper_status**()**reaper_stop**()**rm_channel**(*channel, maybe_timeout*)**rpc_block_while**(*state_str, timeout=None*)**rpc_get_channel_log_level**(*channel*)**rpc_get_log_level**()**rpc_kill_channel**(*channel, timeout=None*)**rpc_print_product**(*product, columns=None, query=None, types=False, format=None*)**rpc_print_products**()**rpc_query_tool**(*product, format=None, start_time=None*)**rpc_reaper_start**(*delay=0*)

Start the reaper process after `'delay'` seconds. Default 0 seconds delay. :type delay: int

rpc_reaper_status()**rpc_reaper_stop**()**rpc_rm_channel**(*channel, maybe_timeout*)**rpc_set_channel_log_level**(*channel, log_level*)

Assumes `log_level` is a string corresponding to the supported logging-module levels.

rpc_show_config(*channel*)

Show the configuration for a channel.

```
rpc_show_de_config()
rpc_start_channel(channel_name)
rpc_start_channels()
rpc_status()
rpc_stop()
rpc_stop_channel(channel)
rpc_stop_channels()
start_channel(channel_name, channel_config)
start_channels()
stop_channels()
stop_worker(worker, timeout)

class decisionengine.framework.engine.DecisionEngine.RequestHandler(request, client_address,
                                                                    server)
    Bases: xmlrpc.server.SimpleXMLRPCRequestHandler
    rpc_paths = ('/RPC2',)

class decisionengine.framework.engine.DecisionEngine.StopState(value)
    Bases: enum.Enum
    An enumeration.
    Clean = 2
    NotFound = 1
    Terminated = 3

decisionengine.framework.engine.DecisionEngine._channel_preamble(name)
decisionengine.framework.engine.DecisionEngine._create_de_server(global_config,
                                                                    channel_config_loader)
    Create the DE server with the passed global configuration and config manager
decisionengine.framework.engine.DecisionEngine._get_de_conf_manager(global_config_dir,
                                                                    channel_config_dir,
                                                                    options)

decisionengine.framework.engine.DecisionEngine._get_global_config(config_file, options)
decisionengine.framework.engine.DecisionEngine._start_de_server(server)
    Start the DE server and listen forever

decisionengine.framework.engine.DecisionEngine.main(args=None)
    If args is None, sys.argv will be used instead If args is a list, it will be used instead of sys.argv (for unit testing)
decisionengine.framework.engine.DecisionEngine.parse_program_options(args=None)
    If args is a list, it will be used instead of sys.argv
```


decisionengine.framework.engine.Workers module

class decisionengine.framework.engine.Workers.**Worker**(*task_manager*, *logger_config*)

Bases: multiprocessing.context.Process

Class that encapsulates a channel's task manager as a separate process.

This class' run function is called whenever the process is started. If the process is abruptly terminated—e.g. the run method is pre-empted by a signal or an os._exit(n) call—the Worker object will still exist even if the operating-system process no longer does.

To determine the exit code of this process, use the Worker.exitcode value, provided by the multiprocessing.Process base class.

get_consumes()

get_produces()

get_state_name()

run()

Method to be run in sub-process; can be overridden in sub-class

wait_until(*state*, *timeout=None*)

wait_while(*state*, *timeout=None*)

class decisionengine.framework.engine.Workers.**Workers**

Bases: object

This class manages and provides access to the task-manager workers.

The intention is that the decision engine never directly interacts with the workers but refers to them via a context manager:

```
with workers.access() as ws: # Access to ws now protected ws['new_channel'] = Worker(...)
```

In cases where the decision engine's block_while or block_until methods must be called (e.g. during tests), one should use the unguarded access:

```
with workers.unguarded_access() as ws: # Access to ws is unprotected
    ws['new_channel'].wait_until(...)
```

Calling a blocking method while using the protected context manager (i.e. workers.access()) will likely result in a deadlock.

class Access(*workers*, *lock*)

Bases: object

_update_channel_states()

access()

unguarded_access()

decisionengine.framework.engine.de_client module

`decisionengine.framework.engine.de_client.console_scripts_main(args_to_parse=None)`

This is the entry point for the setuptools auto generated scripts. Setuptools thinks a return from this function is an error message.

`decisionengine.framework.engine.de_client.create_parser()`

`decisionengine.framework.engine.de_client.execute_command_from_args(argsparsed, de_socket)`
argsparsed should be from create_parser in this file

`decisionengine.framework.engine.de_client.main(args_to_parse=None)`

If you pass a list of args, they will be used instead of sys.argv

decisionengine.framework.engine.de_query_tool module

`decisionengine.framework.engine.de_query_tool.console_scripts_main(args_to_parse=None)`

This is the entry point for the setuptools auto generated scripts. Setuptools thinks a return from this function is an error message.

`decisionengine.framework.engine.de_query_tool.create_parser()`

`decisionengine.framework.engine.de_query_tool.execute_command_from_args(argsparsed, de_socket)`

Calls the proper function for the arguments passed to de_query_tool.

Parameters

- **argsparsed** (*Namespace*) – Should be from create_parser in this file.
- **de_socket** (*ServerProxy*) – RPC Server Proxy.

Returns Output of the command.

Return type str

`decisionengine.framework.engine.de_query_tool.main(args_to_parse=None)`

Main function for de_query_tool

Parameters **args_to_parse** (*list, optional*) – If you pass a list of args, they will be used instead of sys.argv. Defaults to None.

Returns Query result

Return type str

Module contents

decisionengine.framework.logicengine package

Subpackages

decisionengine.framework.logicengine.tests package

Submodules

decisionengine.framework.logicengine.tests.test_cascaded_rules module

```
decisionengine.framework.logicengine.tests.test_cascaded_rules.myengine()  
decisionengine.framework.logicengine.tests.test_cascaded_rules.test_rule_that_does_not_fire(myengine)  
decisionengine.framework.logicengine.tests.test_cascaded_rules.test_rule_that_fires(myengine)
```

decisionengine.framework.logicengine.tests.test_construction module

```
decisionengine.framework.logicengine.tests.test_construction.test_configuration_with_fact_using_function()  
decisionengine.framework.logicengine.tests.test_construction.test_configuration_with_numpy_facts()  
decisionengine.framework.logicengine.tests.test_construction.test_default_construction()  
    LogicEngine is not default constructible.  
decisionengine.framework.logicengine.tests.test_construction.test_trivial_configuration()  
    Logic engine constructed with trivial rules and facts.  
decisionengine.framework.logicengine.tests.test_construction.test_wrong_configuration()  
    LogicEngine construction requires rules and facts; if we don't supply them it is an error.
```

decisionengine.framework.logicengine.tests.test_duplicate_fact_names module

```
decisionengine.framework.logicengine.tests.test_duplicate_fact_names.test_duplicate_fact_names()
```

decisionengine.framework.logicengine.tests.test_facts module

```
decisionengine.framework.logicengine.tests.test_facts.make_db(maximum)  
decisionengine.framework.logicengine.tests.test_facts.test_compound_fact_with_spaces()  
decisionengine.framework.logicengine.tests.test_facts.test_fact_using_numpy_array()  
decisionengine.framework.logicengine.tests.test_facts.test_fact_using_numpy_function()  
decisionengine.framework.logicengine.tests.test_facts.test_fact_with_fail_on_error()  
decisionengine.framework.logicengine.tests.test_facts.test_fact_with_nested_names()  
decisionengine.framework.logicengine.tests.test_facts.test_simple_fact()  
decisionengine.framework.logicengine.tests.test_facts.test_syntax_error(caplog)
```

decisionengine.framework.logicengine.tests.test_fail_on_error module

```
decisionengine.framework.logicengine.tests.test_fail_on_error.logic_engine_with_fact(fact)  
decisionengine.framework.logicengine.tests.test_fail_on_error.test_conditional_fact()  
decisionengine.framework.logicengine.tests.test_fail_on_error.test_fact_with_misspecified_attribute()  
decisionengine.framework.logicengine.tests.test_fail_on_error.test_fail_on_error(caplog)  
decisionengine.framework.logicengine.tests.test_fail_on_error.test_false_fact_with_spaces()  
decisionengine.framework.logicengine.tests.test_fail_on_error.test_false_literal_fact()
```

```
decisionengine.framework.logicengine.tests.test_fail_on_error.test_index_error()
decisionengine.framework.logicengine.tests.test_fail_on_error.test_misspecified_fact()
decisionengine.framework.logicengine.tests.test_fail_on_error.test_true_fact()
decisionengine.framework.logicengine.tests.test_fail_on_error.test_true_literal_fact()
```

decisionengine.framework.logicengine.tests.test_pandas_fact module

```
decisionengine.framework.logicengine.tests.test_pandas_fact.mydata(y)
    Return a 'datablock' surrogate carrying a Pandas DataFrame, and a parameter named 'y' with value y.
decisionengine.framework.logicengine.tests.test_pandas_fact.myengine()
decisionengine.framework.logicengine.tests.test_pandas_fact.test_rule_that_does_not_fire(myengine)
    Rules that do not fire do not create entries in the returned actions and newfacts.
decisionengine.framework.logicengine.tests.test_pandas_fact.test_rule_that_fires(myengine)
```

decisionengine.framework.logicengine.tests.test_rule_with_negated_fact module

```
decisionengine.framework.logicengine.tests.test_rule_with_negated_fact.myengine()
decisionengine.framework.logicengine.tests.test_rule_with_negated_fact.test_rule_that_does_not_fire(myengine)
    Rules that do not fire do not create entries in the returned actions and newfacts.
decisionengine.framework.logicengine.tests.test_rule_with_negated_fact.test_rule_that_fires(myengine)
```

decisionengine.framework.logicengine.tests.test_simple_configuration module

```
decisionengine.framework.logicengine.tests.test_simple_configuration.myengine()
decisionengine.framework.logicengine.tests.test_simple_configuration.test_rule_that_does_not_fire(myengine)
    Rules that do not fire do not create entries in the returned actions and newfacts.
decisionengine.framework.logicengine.tests.test_simple_configuration.test_rule_that_fires(myengine)
```

Module contents

Submodules

decisionengine.framework.logicengine.BooleanExpression module

```
class decisionengine.framework.logicengine.BooleanExpression.BooleanExpression(expr)
    Bases: object
    evaluate(d)
        Return the evaluated Boolean value of this expression in the context of the given data 'd'.
exception decisionengine.framework.logicengine.BooleanExpression.LogicError
    Bases: TypeError
decisionengine.framework.logicengine.BooleanExpression.function_name_from_call(callnode)
decisionengine.framework.logicengine.BooleanExpression.maybe_fail_on_error(expr)
```

decisionengine.framework.logicengine.FactLookup module

class `decisionengine.framework.logicengine.FactLookup.FactLookup(fact_names, rules_cfg)`

Bases: `object`

Establishes a policy for looking up a fact based on the given name.

To wit, the first fact with a given name is the one that is used in the evaluation of all subsequent facts.

As an example, consider the following configuration:

```
facts: { should_publish: "(True)",
}, rules: {
  publish_1: { expression: "should_publish", facts: ["should_publish"]
}, publish_2: {
  expression: "should_publish", actions: ["go_to_press"] facts: ["should_publish"]
} retract: {
  expression: "not should_publish", facts: ["should_retract"]
}
```

In the above, the first fact to be evaluated will always be the top-level facts (i.e. those not encapsulated by the 'rules' table). The rules labeled 'publish_1' and 'publish_2' both rely on the 'should_publish' fact in their expressions, and they in turn create their own facts with the same name. FactLookup ensures that 'publish_1' and 'publish_2' will both use the evaluated fact from the top-level 'facts' table.

rule_for(*fact_name*)

Selects rule required to evaluate fact with the supplied name.

Parameters **fact_name** (*str*) – Name of fact for which rule will be selected.

Return type `str`

Returns Rule name

sorted_rules(*rules_cfg*)

Rules sorted according to rule dependencies.

Parameters **rules_cfg** (*dict*) – rules as specified in logic-engine configuration

Return type `list`

Returns Rules to be evaluated by the rule engine.

decisionengine.framework.logicengine.LogicEngine module

class `decisionengine.framework.logicengine.LogicEngine.LogicEngine(cfg, channel_name)`

Bases: `decisionengine.framework.modules.Module.Module`

_create_facts_dataframe(*newfacts*)

Convert newfacts dict in format below to dataframe with columns ['rule_name', 'fact_name', 'fact_value']

facts dict format: 'newfacts': {

```
  'publish_glidein_requests': { 'allow_hpc_new': True, 'allow_foo': True
```

```
  }, 'dummy_rule': {
```

```
    'dummy_new_fact': True
```

```
    }  
  }  
  
  consumes()  
    Return the names of all the items that must be in the DataBlock for the rules to be evaluated.  
  
  evaluate(db)  
    Evaluate our facts and rules, in the context of the given data. db can be any mappable, in particular a  
    DataBlock or dictionary.  
  
    Parameters db (DataBlock) – Products used to evaluate facts.  
  
  evaluate_facts(db)  
  
    Parameters db (DataBlock) – Products used to evaluate facts.  
  
    Return type dict  
  
    Returns Evaluated fact values (e.g. True or False) for each fact name.  
  
  produces()
```

decisionengine.framework.logicengine.Rule module

```
class decisionengine.framework.logicengine.Rule.Rule(rule_name, rule_cfg)  
  Bases: object  
  
  In-memory representation of logic-engine rule, relying on parsing utilities in BooleanExpression.  
  
  evaluate(evaluated_facts)  
    Evaluates a compiled expression given the supplied facts.  
  
    Parameters evaluated_facts (dict) – Initial fact values (e.g. True or False) for each fact  
    name.  
  
    Return type bool
```

decisionengine.framework.logicengine.RuleEngine module

```
class decisionengine.framework.logicengine.RuleEngine.RuleEngine(fact_names, rules_cfg)  
  Bases: object  
  
  Engine responsible for evaluating logic-engine rules.  
  
  This class is responsible for (a) forming a sorted set of rules that supports dependencies between them, and (b)  
  evaluating the rules according to a specified fact-lookup policy.  
  
  execute(evaluated_facts)  
    Evaluates all rules given the supplied facts.  
  
    Parameters evaluated_facts (dict) – Initial fact values (e.g. True or False) for each fact  
    name.  
  
    Return type tuple  
  
    Returns Actions to be taken based on rule evaluation; new facts produced during that evaluation.
```

Module contents

decisionengine.framework.modules package

Subpackages

decisionengine.framework.modules.tests package

Submodules

decisionengine.framework.modules.tests.test_Module module

`decisionengine.framework.modules.tests.test_Module.test_module_structure()`
The module.Module itself is a bit of a skeleton...

decisionengine.framework.modules.tests.test_Publisher module

`decisionengine.framework.modules.tests.test_Publisher.test_publisher_structure()`
The module.publisher itself is a bit of a skeleton...

decisionengine.framework.modules.tests.test_Source module

`decisionengine.framework.modules.tests.test_Source.test_source_structure()`
The module.Source itself is a bit of a skeleton...

decisionengine.framework.modules.tests.test_Transform module

`decisionengine.framework.modules.tests.test_Transform.test_transform_structure()`
The module.Transform itself is a bit of a skeleton...

decisionengine.framework.modules.tests.test_de_logger module

`decisionengine.framework.modules.tests.test_de_logger.log_setup()`
`decisionengine.framework.modules.tests.test_de_logger.test_by_nonsense_is_err(log_setup)`
`decisionengine.framework.modules.tests.test_de_logger.test_by_size(log_setup)`
`decisionengine.framework.modules.tests.test_de_logger.test_by_time(log_setup)`

decisionengine.framework.modules.tests.test_module_decorators module

```
decisionengine.framework.modules.tests.test_module_decorators.test_multiple_consumes_declarations()
decisionengine.framework.modules.tests.test_module_decorators.test_multiple_produces_declarations()
decisionengine.framework.modules.tests.test_module_decorators.test_supports_config()
decisionengine.framework.modules.tests.test_module_decorators.test_wrong_product_names()
decisionengine.framework.modules.tests.test_module_decorators.test_wrong_product_types()
```

decisionengine.framework.modules.tests.test_translate_product_name module

```
decisionengine.framework.modules.tests.test_translate_product_name.test_translate_all()
decisionengine.framework.modules.tests.test_translate_product_name.test_translate_illegal_characters()
decisionengine.framework.modules.tests.test_translate_product_name.test_translate_none()
decisionengine.framework.modules.tests.test_translate_product_name.test_translate_simple()
decisionengine.framework.modules.tests.test_translate_product_name.test_translate_with_underscores()
```

Module contents

Submodules

decisionengine.framework.modules.Module module

```
class decisionengine.framework.modules.Module.Module(set_of_parameters)
    Bases: object
    A skeleton of a module
    get_data_block()
    get_parameters()
    set_data_block(data_block)
decisionengine.framework.modules.Module.consumes(**kwargs)
decisionengine.framework.modules.Module.produces(**kwargs)
decisionengine.framework.modules.Module.verify_products(producer, data)
```

decisionengine.framework.modules.Publisher module

```
class decisionengine.framework.modules.Publisher.Parameter(name, type=None, default=None,
    comment=None)
    Bases: object
class decisionengine.framework.modules.Publisher.Publisher(set_of_parameters)
    Bases: decisionengine.framework.modules.Module.Module
    _consumes = {}
    publish(data_block=None)
```


shutdown()

decisionengine.framework.modules.Publisher.**consumes**(**kwargs)

decisionengine.framework.modules.Publisher.**describe**(cls, program_options=<class 'decisionengine.framework.modules.describe.ModuleProgramOptions'>)

decisionengine.framework.modules.Publisher.**supports_config**(*args)

decisionengine.framework.modules.Source module

class decisionengine.framework.modules.Source.**Parameter**(name, type=None, default=None, comment=None)

Bases: object

class decisionengine.framework.modules.Source.**Source**(set_of_parameters)

Bases: *decisionengine.framework.modules.Module.Module*

_produces = {}

acquire()

post_create(global_config)

decisionengine.framework.modules.Source.**describe**(cls, sample_config=None)

decisionengine.framework.modules.Source.**produces**(**kwargs)

decisionengine.framework.modules.Source.**supports_config**(*args)

decisionengine.framework.modules.SourceProxy module

Fill in data from another channel data block

class decisionengine.framework.modules.SourceProxy.**SourceProxy**(config)

Bases: *decisionengine.framework.modules.Source.Source*

_get_data(data_block, key)

_supported_config = {'Dataproducts': (<class 'list'>, None, 'List of data products to retrieve.'), 'channel_name': (<class 'str'>, None, 'Channel from which to retrieve data products.'), 'retries': (<class 'int'>, 10, 'Number of attempts allowed to fetch products.'), 'retry_timeout': (<class 'int'>, 60, 'Number of seconds to wait between retries.')}

acquire()

Overrides Source class method

post_create(global_config)

decisionengine.framework.modules.Transform module

```
class decisionengine.framework.modules.Transform.Parameter(name, type=None, default=None,
                                                         comment=None)
```

Bases: object

```
class decisionengine.framework.modules.Transform.Transform(set_of_parameters)
```

Bases: *decisionengine.framework.modules.Module.Module*

```
_consumes = {}
```

```
_produces = {}
```

```
transform()
```

```
decisionengine.framework.modules.Transform.consumes(**kwargs)
```

```
decisionengine.framework.modules.Transform.describe(cls, program_options=<class 'decisionengine.framework.modules.describe.ModuleProgramOptions'>)
```

```
decisionengine.framework.modules.Transform.produces(**kwargs)
```

```
decisionengine.framework.modules.Transform.supports_config(*args)
```

decisionengine.framework.modules.de_logger module

Logger to use in all modules

```
decisionengine.framework.modules.de_logger.get_logger()
```

get default logger - "decisionengine" :rtype: logging.Logger - rotating file logger

```
decisionengine.framework.modules.de_logger.set_logging(log_level, file_rotate_by,
                                                         rotation_time_unit='D', rotation_interval=1,
                                                         max_backup_count=6,
                                                         max_file_size=200000000,
                                                         log_file_name='/tmp/decision_engine_logs/decisionengine.log')
```

Parameters

- **log_level** (str) – log level
- **file_rotate_by** – files rotation by size or by time
- **rotation_time_unit** (str) – unit of time for file rotation
- **rotation_interval** (int) – time in rotation_time_units between file rotations
- **log_file_name** (str) – log file name
- **max_file_size** (int) – maximal size of log file. If reached save and start new log.
- **max_backup_count** (int) – start rotaion after this number is reached

Return type None

decisionengine.framework.modules.describe module

```
class decisionengine.framework.modules.describe.ModuleProgramOptions(module_spec, cls)
    Bases: object
```

```
    process_args()
```

```
class decisionengine.framework.modules.describe.Parameter(name, type=None, default=None,
                                                         comment=None)
    Bases: object
```

```
decisionengine.framework.modules.describe._par_default(par_type, default_value)
```

```
decisionengine.framework.modules.describe._par_type(par_type, default_value)
```

```
decisionengine.framework.modules.describe.main_wrapper(cls, program_options=<class 'decisionengine.framework.modules.describe.ModuleProgramOptions'>)
```

```
decisionengine.framework.modules.describe.supports_config(*args)
```

decisionengine.framework.modules.logging_configDict module

Global Logger config dictionary used by all loggers (in their own subkeys)

decisionengine.framework.modules.print_description module

```
decisionengine.framework.modules.print_description._print_comment(comment)
```

```
decisionengine.framework.modules.print_description._print_type(type_or_value)
```

```
decisionengine.framework.modules.print_description._print_value(v)
```

```
decisionengine.framework.modules.print_description._spec_from_file_name(filename)
```

```
decisionengine.framework.modules.print_description.print_consumes(cls)
```

```
decisionengine.framework.modules.print_description.print_produces(cls)
```

```
decisionengine.framework.modules.print_description.print_supported_config(module_spec, cls)
```

```
decisionengine.framework.modules.print_description.spec_if_main(cls)
```

decisionengine.framework.modules.translate_product_name module

```
decisionengine.framework.modules.translate_product_name.translate(spec)
```

Break apart the string 'old -> new' into a tuple ('old', 'new')

```
decisionengine.framework.modules.translate_product_name.translate_all(specs)
```

Module contents

decisionengine.framework.taskmanager package

Submodules

decisionengine.framework.taskmanager.ProcessingState module

The ProcessingState class can represent any of the following task-manager states:

BOOT IDLE ACTIVE STEADY OFFLINE SHUTTINGDOWN SHUTDOWN ERROR

In addition, the class supports 'wait_until(state)' and 'wait_while(state)' methods, which, when called from a different process, block until the state has been entered or exited, respectively.

The 'RUNNING_CONDITIONS' list is a list of states that a thread may have if it is started/starting. The 'STOPPING_CONDITIONS' list is a list of states that a thread may have if it is stopped/stopping. The 'INACTIVE_CONDITIONS' list is a list of states that a thread may have when it is not active

class decisionengine.framework.taskmanager.ProcessingState.**ProcessingState**(state=State.BOOT)

Bases: object

This object tracks the state of a process.

A number of convenience wrappers are provided.

Additionally you may use the .lock attribute for *with* block to lock the state during specific operations.

get()

This function is a minimally locking check to fetch the state.

has_value(state)

inactive()

property lock

probably_running()

set(state)

This function will lock (and possibly block) to ensure a consistent change to the state value.

This function can be blocked using the .lock to force state sync between threads if need be.

should_stop()

wait_until(state, timeout=None)

wait_while(state, timeout=None)

class decisionengine.framework.taskmanager.ProcessingState.**State**(value)

Bases: enum.Enum

An enumeration.

ACTIVE = 2

BOOT = 0

ERROR = 7

IDLE = 1

OFFLINE = 6

```
SHUTDOWN = 5
SHUTTINGDOWN = 4
STEADY = 3
```

decisionengine.framework.taskmanager.TaskManager module

Task Manager

```
class decisionengine.framework.taskmanager.TaskManager.Channel(channel_dict, channel_name)
    Bases: object
```

Decision Channel. Instantiates workers according to channel configuration

```
class decisionengine.framework.taskmanager.TaskManager.TaskManager(name, generation_id,
                                                                    channel_dict, global_config)
```

Bases: object

Task Manager

```
data_block_put(data, header, data_block)
```

Put data into data block

Parameters

- **data** (dict) – key, value pairs
- **header** (Header) – data header
- **data_block** (DataBlock) – data block

```
decision_cycle()
```

Decision cycle to be run periodically (by trigger)

```
do_backup()
```

Duplicate current data block and return its copy

Return type DataBlock

```
get_consumes()
```

```
get_loglevel()
```

```
get_produces()
```

```
get_state()
```

```
get_state_name()
```

```
get_state_value()
```

```
run()
```

Task Manager main loop

```
run_logic_engine(data_block=None)
```

Run Logic Engine.

Parameters **data_block** (DataBlock) – data block

```
run_publishers(actions, facts, data_block=None)
```

Run Publishers in main process.

Parameters **data_block** (DataBlock) – data block

run_source(*src*)

Get the data from source and put it into the data block

Parameters *src* (*Worker*) – source Worker

run_transform(*transform*, *data_block*)

Run a transform

Parameters

- **transform** (*Worker*) – source Worker
- **data_block** (DataBlock) – data block

run_transforms(*data_block=None*)

Run transforms. So far in main process.

Parameters *data_block* (DataBlock) – data block

set_loglevel_value(*log_level*)

Assumes log_level is a string corresponding to the supported logging-module levels.

set_to_shutdown()

start_sources(*data_block=None*)

Start sources, each in a separate thread

Parameters *data_block* (DataBlock) – data block

take_offline(*current_data_block*)

offline and stop task manager

wait_for_all(*events_done*)

Wait for all sources or transforms to finish

Parameters *events_done* (list) – list of events to wait for

wait_for_any(*events_done*)

Wait for any sources to finish

Parameters *events_done* (list) – list of events to wait for

class decisionengine.framework.taskmanager.TaskManager.**Worker**(*conf_dict*, *base_class*,
channel_name)

Bases: object

Provides interface to loadable modules and events to synchronise execution

decisionengine.framework.taskmanager.TaskManager.**_create_module_instance**(*config_dict*,
base_class,
channel_name)

Create instance of dynamically loaded module

decisionengine.framework.taskmanager.TaskManager.**_find_only_one_subclass**(*module*, *base_class*)

Search through module looking for only one subclass of the supplied base_class

decisionengine.framework.taskmanager.TaskManager.**_make_workers_for**(*configs*, *base_class*,
channel_name)

decisionengine.framework.taskmanager.module_graph module

Ensure no circularities in produces and consumes.

`decisionengine.framework.taskmanager.module_graph._consumed_products(*worker_lists)`

`decisionengine.framework.taskmanager.module_graph._produced_products(*worker_lists)`

`decisionengine.framework.taskmanager.module_graph.ensure_no_circularities(sources, transforms, publishers)`

Ensures no circularities among data products.

Module contents

decisionengine.framework.tests package

Submodules

decisionengine.framework.tests.ABTransform module

`class decisionengine.framework.tests.ABTransform.ABTransform(module_parameters, *args, **kwargs)`

Bases: *decisionengine.framework.modules.Transform.Transform*

`_consumes = {'B': None}`

`_produces = {'A': None}`

decisionengine.framework.tests.BATransform module

`class decisionengine.framework.tests.BATransform.BATransform(module_parameters, *args, **kwargs)`

Bases: *decisionengine.framework.modules.Transform.Transform*

`_consumes = {'A': None}`

`_produces = {'B': None}`

decisionengine.framework.tests.ErrorOnAcquire module

`class decisionengine.framework.tests.ErrorOnAcquire.ErrorOnAcquire(config)`

Bases: *decisionengine.framework.modules.Source.Source*

`_produces = {'_placeholder': None}`

`acquire()`

decisionengine.framework.tests.FailingPublisher module

```
class decisionengine.framework.tests.FailingPublisher.FailingPublisher(module_parameters,  
                                                                    *args, **kwargs)  
    Bases: decisionengine.framework.modules.Publisher.Publisher  
    _consumes = {'bar': None}  
    publish(data_block)
```

decisionengine.framework.tests.FailingSourceNOP module

```
class decisionengine.framework.tests.FailingSourceNOP.SourceWithMissingProduces(set_of_parameters)  
    Bases: decisionengine.framework.modules.Source.Source
```

decisionengine.framework.tests.FailingSourceProxy module

```
class decisionengine.framework.tests.FailingSourceProxy.FailingSourceProxy(config)  
    Bases: decisionengine.framework.modules.SourceProxy.SourceProxy  
    acquire()  
        Overrides Source class method
```

decisionengine.framework.tests.ModuleProgramOptions module

```
class decisionengine.framework.tests.ModuleProgramOptions.AcquireWithConfig(name)  
    Bases: object  
    test(byte_str, expected_stderr="")  
class decisionengine.framework.tests.ModuleProgramOptions.AcquireWithSampleConfig(name)  
    Bases: object  
    test()  
class decisionengine.framework.tests.ModuleProgramOptions.ConfigTemplate(name)  
    Bases: object  
    test(has_comments=False)  
class decisionengine.framework.tests.ModuleProgramOptions.Describe(name)  
    Bases: object  
    test(consumes=None, produces=None)  
class decisionengine.framework.tests.ModuleProgramOptions.DescribeAlias(alias, original)  
    Bases: object  
    test()  
class decisionengine.framework.tests.ModuleProgramOptions.Help(name)  
    Bases: object  
    test(has_sample_config=False)  
decisionengine.framework.tests.ModuleProgramOptions._expected_acquire_result(name, con-  
                                                                              fig_file=None,  
                                                                              multiplier=1)
```



```
decisionengine.framework.tests.ModuleProgramOptions._expected_config_template(name)
decisionengine.framework.tests.ModuleProgramOptions._expected_config_template_with_comments(name)
decisionengine.framework.tests.ModuleProgramOptions._expected_help(name)
decisionengine.framework.tests.ModuleProgramOptions._expected_source_help(name,
                                                                    has_sample_config=False)
decisionengine.framework.tests.ModuleProgramOptions._normalize(string)
decisionengine.framework.tests.ModuleProgramOptions._run_as_main(name, *program_options)
```

decisionengine.framework.tests.PublisherNOP module

```
class decisionengine.framework.tests.PublisherNOP.PublisherNOP(module_parameters, *args,
                                                                **kwargs)
    Bases: decisionengine.framework.modules.Publisher.Publisher
    _consumes = {'bar': <class 'pandas.core.frame.DataFrame'>}
    publish(data_block)
```

decisionengine.framework.tests.PublisherWithMissingConsumes module

```
class decisionengine.framework.tests.PublisherWithMissingConsumes.PublisherWithMissingConsumes(set_of_parameters)
    Bases: decisionengine.framework.modules.Publisher.Publisher
```

decisionengine.framework.tests.SourceAlias module

decisionengine.framework.tests.SourceNOP module

```
class decisionengine.framework.tests.SourceNOP.SourceNOP(config)
    Bases: decisionengine.framework.modules.Source.Source
    _produces = {'foo': <class 'pandas.core.frame.DataFrame'>}
    acquire()
```

decisionengine.framework.tests.SourceWithSampleConfigNOP module

```
class decisionengine.framework.tests.SourceWithSampleConfigNOP.SourceWithSampleConfigNOP(config)
    Bases: decisionengine.framework.modules.Source.Source
    _produces = {'foo': <class 'pandas.core.frame.DataFrame'>}
    _supported_config = {'multiplier': (<class 'int'>, None, None)}
    acquire()
```

decisionengine.framework.tests.SupportsConfigPublisher module

```
class decisionengine.framework.tests.SupportsConfigPublisher.SupportsConfig(set_of_parameters)
    Bases: decisionengine.framework.modules.Publisher.Publisher
    _supported_config = {'comment': (<class 'str'>, None, 'Single-line comment'),
        'comment_with_nl': (<class 'str'>, None, 'Comment with newline\n'), 'convert_to':
        (<class 'int'>, 3, None), 'default_only': (<class 'float'>, 2.5, None), 'no_type':
        (None, None, None), 'only_type': (<class 'int'>, None, None)}
```

decisionengine.framework.tests.TransformNOP module

```
class decisionengine.framework.tests.TransformNOP.TransformNOP(module_parameters, *args,
                                                                **kwargs)
    Bases: decisionengine.framework.modules.Transform.Transform
    _consumes = {'foo': <class 'pandas.core.frame.DataFrame'>}
    _produces = {'bar': <class 'pandas.core.frame.DataFrame'>}
    transform(data_block)
```

decisionengine.framework.tests.TransformWithMissingProducesConsumes module

```
class decisionengine.framework.tests.TransformWithMissingProducesConsumes.TransformWithMissingProducesConsumesC
    Bases: decisionengine.framework.modules.Transform.Transform
    transform(data_block)
```

decisionengine.framework.tests.WorkingSourceProxy module

```
class decisionengine.framework.tests.WorkingSourceProxy.WorkingSourceProxy(config)
    Bases: decisionengine.framework.modules.SourceProxy.SourceProxy
    acquire()
        Overrides Source class method
```

decisionengine.framework.tests.fixtures module

defaults for pytest

```
decisionengine.framework.tests.fixtures.DEServer(conf_path=None, conf_override=None,
                                                  channel_conf_path=None,
                                                  channel_conf_override=None, host='127.0.0.1',
                                                  port=None)
```

A DE Server using a private database

```
decisionengine.framework.tests.fixtures.PG_DE_DB_WITHOUT_SCHEMA(request:
                                                                _pytest.fixtures.FixtureRequest)
    →
    psycopg2.extensions.connection
```

Fixture factory for PostgreSQL.

Parameters **request** – fixture request object

Returns postgresql client

`decisionengine.framework.tests.fixtures.PG_DE_DB_WITH_SCHEMA(PG_DE_DB_WITHOUT_SCHEMA)`
Load our PG schema into the database via this fixture so pytest knows the limitations on parallel usage of this database scope.

`decisionengine.framework.tests.fixtures.PG_PROG(request: _pytest.fixtures.FixtureRequest, tmpdir_factory: _pytest.tmpdir.TempdirFactory) → Iterator[pytest_postgresql.executor.PostgreSQLExecutor]`

Process fixture for PostgreSQL.

Parameters **request** – fixture request object

Returns tcp executor

`decisionengine.framework.tests.fixtures.SQLALCHEMY_PG_WITH_SCHEMA(PG_DE_DB_WITHOUT_SCHEMA)`
Get a blank database from `pytest_postgresql`. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

`decisionengine.framework.tests.fixtures.SQLALCHEMY_TEMPFILE_SQLITE(tmp_path)`
Setup an SQLite database with the `pytest tmp_path` fixture. Then setup the SQLAlchemy style URL with that DB. The SQLAlchemyDS will create the schema as needed.

decisionengine.framework.tests.test_client_errors module

Fixture based DE Server tests of the sample config

`decisionengine.framework.tests.test_client_errors.test_client_cannot_wait_on_bad_state(deserver)`
Verify wait is for a valid state

decisionengine.framework.tests.test_client_server module

Fixture based DE Server for the de-client tests

`decisionengine.framework.tests.test_client_server.test_client_print_product(deserver)`
`decisionengine.framework.tests.test_client_server.test_client_print_product_columns(deserver)`
`decisionengine.framework.tests.test_client_server.test_client_print_product_columns_query(deserver)`
`decisionengine.framework.tests.test_client_server.test_client_print_product_json(deserver)`
`decisionengine.framework.tests.test_client_server.test_client_print_product_not_real(deserver)`
`decisionengine.framework.tests.test_client_server.test_client_print_product_query(deserver)`
`decisionengine.framework.tests.test_client_server.test_client_print_product_types(deserver)`
`decisionengine.framework.tests.test_client_server.test_client_print_product_vertical(deserver)`
`decisionengine.framework.tests.test_client_server.test_client_status_msg_to_stdout(deserver)`
Make sure the actual client console call goes to stdout

decisionengine.framework.tests.test_defaults module

Fixture based DE Server tests of the sample config

decisionengine.framework.tests.test_defaults.test_client_can_get_de_server_show_channel_logger_level(*deserver*)
Verify unknown channel has NOTSET

decisionengine.framework.tests.test_defaults.test_client_de_config_is_json(*deserver*)
Verify config can be fetched in json format

decisionengine.framework.tests.test_defaults.test_global_channel_log_level_in_config(*deserver*)
Verify global_channel_log_level setting exists

decisionengine.framework.tests.test_error_on_acquire module

decisionengine.framework.tests.test_error_on_acquire.test_source_only_channel(*deserver*)

decisionengine.framework.tests.test_module_program_options module

decisionengine.framework.tests.test_module_program_options.test_acquire_for_sources()

decisionengine.framework.tests.test_module_program_options.test_config_templates()

decisionengine.framework.tests.test_module_program_options.test_descriptions()

decisionengine.framework.tests.test_module_program_options.test_help()

decisionengine.framework.tests.test_module_program_options.test_module_alias()

decisionengine.framework.tests.test_query_tool_server module

Fixture based DE Server for the de-query-tool tests

decisionengine.framework.tests.test_query_tool_server.test_query_tool_csv(*deserver*)

decisionengine.framework.tests.test_query_tool_server.test_query_tool_default(*deserver*)

decisionengine.framework.tests.test_query_tool_server.test_query_tool_invalid_product(*deserver*)

decisionengine.framework.tests.test_query_tool_server.test_query_tool_json(*deserver*)

decisionengine.framework.tests.test_query_tool_server.test_query_tool_since(*deserver*)

decisionengine.framework.tests.test_reaper module

Fixture based DE Server for the reaper tests

decisionengine.framework.tests.test_reaper.test_client_can_get_de_server_reaper_start_delay(*deserver*)
Verify reaper can start with delay

decisionengine.framework.tests.test_reaper.test_client_can_get_de_server_reaper_status(*deserver*)
Verify reaper status

decisionengine.framework.tests.test_reaper.test_client_can_get_de_server_reaper_stop(*deserver*)
Verify reaper can stop

decisionengine.framework.tests.test_restart_channel module

decisionengine.framework.tests.test_restart_channel.deserver_mock_data_block(*mock_data_block*)

decisionengine.framework.tests.test_restart_channel.test_restart_channel(*deserver_mock_data_block*)

decisionengine.framework.tests.test_sample_config module

Fixture based DE Server tests of the defaults

decisionengine.framework.tests.test_sample_config.test_client_can_double_set_de_server_channel_log_level(*deserver*)

Verify set log level to current level isn't an error

decisionengine.framework.tests.test_sample_config.test_client_can_get_de_server_channel_config(*deserver*)

Verify config has expected items

decisionengine.framework.tests.test_sample_config.test_client_can_get_de_server_channel_log_level(*deserver*)

Verify can fetch log level for a channel

decisionengine.framework.tests.test_sample_config.test_client_can_get_de_server_show_config(*deserver*)

Verify config has expected items

decisionengine.framework.tests.test_sample_config.test_client_can_get_de_server_show_logger_level(*deserver*)

Verify can fetch log level

decisionengine.framework.tests.test_sample_config.test_client_can_get_de_server_status(*deserver*)

Verify channel enters stable state

decisionengine.framework.tests.test_sample_config.test_client_can_get_products(*deserver*)

Verify client can get channel products

decisionengine.framework.tests.test_sample_config.test_client_can_get_products_no_channels(*deserver*)

Verify client can get channel products even when none are run

decisionengine.framework.tests.test_sample_config.test_client_can_kill_one_channel(*deserver*)

Verify client can kill a single channel

decisionengine.framework.tests.test_sample_config.test_client_can_kill_one_channel_force(*deserver*)

Verify client can kill a single channel with force

decisionengine.framework.tests.test_sample_config.test_client_can_kill_one_channel_timeout(*deserver*)

Verify client can kill a single channel with timeout

decisionengine.framework.tests.test_sample_config.test_client_can_set_de_server_channel_log_level(*deserver*)

Verify set log level for a channel

decisionengine.framework.tests.test_sample_config.test_client_can_start_all_channel(*deserver*)

Verify client can start all channel

decisionengine.framework.tests.test_sample_config.test_client_can_start_one_channel(*deserver*)

Verify client can start a single channel

decisionengine.framework.tests.test_sample_config.test_client_can_stop_channels(*deserver*)

Verify client can stop channels

decisionengine.framework.tests.test_sample_config.test_client_can_stop_one_channel(*deserver*)

Verify client can stop a single channel

decisionengine.framework.tests.test_sample_config.test_client_can_stop_server(*deserver*)

Verify de-client can run -stop

`decisionengine.framework.tests.test_sample_config.test_client_cannot_double_start(deserver)`
Verify client cannot double start channels

`decisionengine.framework.tests.test_sample_config.test_client_get_channel_log_fails_cleanly(deserver)`
Verify graceful fail on bogus channel

`decisionengine.framework.tests.test_sample_config.test_client_get_non_real_channel(deserver)`
Verify config for missing channel does what it should

`decisionengine.framework.tests.test_sample_config.test_client_set_channel_log_fails_cleanly(deserver)`
Verify graceful fail on bogus channel

`decisionengine.framework.tests.test_sample_config.test_client_start_non_real_channel(deserver)`
Verify start for missing channel does what it should

`decisionengine.framework.tests.test_sample_config.test_client_stop_non_real_channel(deserver)`
Verify stop for missing channel does what it should

`decisionengine.framework.tests.test_sample_config.test_client_wait_timeout_works(deserver)`
Verify channel enters stable state and timeout works too

decisionengine.framework.tests.test_source_proxy module

Fixture based tests of the SourceProxy module.

`decisionengine.framework.tests.test_source_proxy.test_stop_failing_source_proxy(deserver_fail)`
`decisionengine.framework.tests.test_source_proxy.test_working_source_proxy(deserver)`

decisionengine.framework.tests.test_start_with_bad_channels module

Fixture based DE Server tests of invalid channel configs

`decisionengine.framework.tests.test_start_with_bad_channels._consumes_not_subset(test_str)`
`decisionengine.framework.tests.test_start_with_bad_channels._expected_circularity(test_str)`
`decisionengine.framework.tests.test_start_with_bad_channels._missing_consumes(name)`
`decisionengine.framework.tests.test_start_with_bad_channels._missing_produces(name)`
`decisionengine.framework.tests.test_start_with_bad_channels.test_client_can_get_products_no_channels(deserver_mock_data_block)`
Verify client can get channel products even when none are run

decisionengine.framework.tests.test_start_with_no_channels module

Fixture based DE Server tests of the server without channels, then with them

`decisionengine.framework.tests.test_start_with_no_channels.deserver_mock_data_block(mock_data_block)`
`decisionengine.framework.tests.test_start_with_no_channels.test_start_from_nothing(deserver_mock_data_block)`

Module contents

decisionengine.framework.util package

Submodules

decisionengine.framework.util.fs module

`decisionengine.framework.util.fs.files_with_extensions(dir_path, *extensions)`

Return all files in `dir_path` that match the provided extensions.

If no extensions are given, then all files in `dir_path` are returned.

Results are sorted by channel name to ensure stable output.

decisionengine.framework.util.metrics module

```
class decisionengine.framework.util.metrics.Counter(name, documentation, labelnames=(),
                                                    namespace="", subsystem="", unit="", registry=<prometheus_client.registry.CollectorRegistry
                                                    object>, _labelvalues=None)
```

Bases: `prometheus_client.metrics.Counter`

```
class decisionengine.framework.util.metrics.Gauge(*args, **kwargs)
```

Bases: `prometheus_client.metrics.Gauge`

Override prometheus client Gauge so that `multiprocess_mode` 'liveall' is the default as opposed to 'all'

```
_DEFAULT_MULTIPROC_MODE = 'liveall'
```

```
__determine_multiprocess_mode_existence(*args, **kwargs)
```

```
class decisionengine.framework.util.metrics.Histogram(name, documentation, labelnames=(),
                                                       namespace="", subsystem="", unit="", registry=<prometheus_client.registry.CollectorRegistry
                                                       object>, _labelvalues=None, buckets=(0.005,
                                                       0.01, 0.025, 0.05, 0.075, 0.1, 0.25, 0.5, 0.75,
                                                       1.0, 2.5, 5.0, 7.5, 10.0, inf))
```

Bases: `prometheus_client.metrics.Histogram`

```
class decisionengine.framework.util.metrics.Summary(name, documentation, labelnames=(),
                                                    namespace="", subsystem="", unit="", registry=<prometheus_client.registry.CollectorRegistry
                                                    object>, _labelvalues=None)
```

Bases: `prometheus_client.metrics.Summary`

decisionengine.framework.util.reaper module

A stand-alone script purges data in database older than specified in configuration. Configuration file has to have this bit added:

```
{
    "dataspace" [{ "retention_interval_in_days"[365,]
        "datasource": { ... }
    }
}
```

Can be used in a cron job.

`decisionengine.framework.util.reaper.main()`

decisionengine.framework.util.singleton module

class `decisionengine.framework.util.singleton.ScopedSingleton`

Bases: `decisionengine.framework.util.singleton.Singleton`

Singleton pattern using Metaclass with weak refs

`_instances = <WeakValueDictionary>`

class `decisionengine.framework.util.singleton.ScopedSingletonABC(name, bases, namespace, **kwargs)`

Bases: `abc.ABCMeta`, `decisionengine.framework.util.singleton.ScopedSingleton`

class `decisionengine.framework.util.singleton.Singleton`

Bases: `type`

Singleton pattern using Metaclass with strong refs

`_instances = {}`

class `decisionengine.framework.util.singleton.SingletonABC(name, bases, namespace, **kwargs)`

Bases: `abc.ABCMeta`, `decisionengine.framework.util.singleton.Singleton`

decisionengine.framework.util.sockets module

`decisionengine.framework.util.sockets.get_random_port()`

decisionengine.framework.util.subclasses module

`decisionengine.framework.util.subclasses._derived_class(cls, base_class)`

Only matches subclasses that are not equal to the base class.

`decisionengine.framework.util.subclasses.all_subclasses(module, base_class)`

Return all of a module's subclasses of the given base class.

Module contents

Submodules

decisionengine.framework.about module

PEP-0396 provides instructions for providing module versions While we are at it, add a few other useful bits

decisionengine.framework.version module

Module contents

decisionengine.tests package

Submodules

decisionengine.tests.test_framework_package module

Make sure decisionengine.framework is a valid python package

```
decisionengine.tests.test_framework_package.test_can_import()
```

Module contents

Module contents

4.2 Indices and tables

- [genindex](#)
- [modindex](#)
- [search](#)

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

d

[decisionengine, 85](#)
[decisionengine.framework, 85](#)
[decisionengine.framework.about, 85](#)
[decisionengine.framework.config, 29](#)
[decisionengine.framework.config.ChannelConfigHandler, 27](#)
[decisionengine.framework.config.policies, 28](#)
[decisionengine.framework.config.tests, 27](#)
[decisionengine.framework.config.tests.test_config, 25](#)
[decisionengine.framework.config.tests.test_policies, 26](#)
[decisionengine.framework.config.tests.test_validconfig, 26](#)
[decisionengine.framework.config.ValidConfig, 27](#)
[decisionengine.framework.dataspace, 57](#)
[decisionengine.framework.dataspace.datablock, 51](#)
[decisionengine.framework.dataspace.datasource, 53](#)
[decisionengine.framework.dataspace.datasources, 47](#)
[decisionengine.framework.dataspace.datasources.null, 42](#)
[decisionengine.framework.dataspace.datasources.postgresql, 44](#)
[decisionengine.framework.dataspace.datasources.sqlalchemy_us, 36](#)
[decisionengine.framework.dataspace.datasources.sqlalchemy_us.datasource_api, 29](#)
[decisionengine.framework.dataspace.datasources.sqlalchemy_us.db_schema, 33](#)
[decisionengine.framework.dataspace.datasources.sqlalchemy_us.utils, 35](#)
[decisionengine.framework.dataspace.datasources.tests, 42](#)
[decisionengine.framework.dataspace.datasources.tests.fixtures, 39](#)
[decisionengine.framework.dataspace.datasources.tests.test_datasource_api, 40](#)
[decisionengine.framework.dataspace.datasources.tests.test_datasources, 42](#)
[decisionengine.framework.dataspace.dataspace, 55](#)
[decisionengine.framework.dataspace.maintain, 56](#)
[decisionengine.framework.dataspace.tests, 51](#)
[decisionengine.framework.dataspace.tests.fixtures, 47](#)
[decisionengine.framework.dataspace.tests.test_datablock, 49](#)
[decisionengine.framework.dataspace.tests.test_datablock_zl, 49](#)
[decisionengine.framework.dataspace.tests.test_datasource, 49](#)
[decisionengine.framework.dataspace.tests.test_dataspace, 50](#)
[decisionengine.framework.dataspace.tests.test_Reaper, 48](#)
[decisionengine.framework.engine, 62](#)
[decisionengine.framework.engine.de_client, 62](#)
[decisionengine.framework.engine.de_query_tool, 62](#)
[decisionengine.framework.engine.DecisionEngine, 58](#)
[decisionengine.framework.engine.tests, 58](#)
[decisionengine.framework.engine.tests.fixtures, 57](#)
[decisionengine.framework.engine.tests.test_client_only, 58](#)
[decisionengine.framework.engine.tests.test_query_tool_only, 58](#)
[decisionengine.framework.engine.tests.test_startup, 58](#)
[decisionengine.framework.engine.Workers, 61](#)
[decisionengine.framework.logicengine, 67](#)
[decisionengine.framework.logicengine.BooleanExpression, 64](#)
[decisionengine.framework.logicengine.FactLookup, 65](#)
[decisionengine.framework.logicengine.LogicEngine, 65](#)

decisionengine.framework.logicengine.Rule, 66	decisionengine.framework.taskmanager, 75
decisionengine.framework.logicengine.RuleEngine, 66	decisionengine.framework.taskmanager.module_graph, 75
decisionengine.framework.logicengine.tests, 64	decisionengine.framework.taskmanager.ProcessingState, 72
decisionengine.framework.logicengine.tests.test_casacade, 63	decisionengine.framework.taskmanager.TaskManager, 73
decisionengine.framework.logicengine.tests.test_consistency, 63	decisionengine.framework.tests, 83
decisionengine.framework.logicengine.tests.test_duplicate_fact_names, 63	decisionengine.framework.tests.ABTransform, 75
decisionengine.framework.logicengine.tests.test_facts, 63	decisionengine.framework.tests.BATransform, 75
decisionengine.framework.logicengine.tests.test_fail_on_error, 63	decisionengine.framework.tests.ErrorOnAcquire, 75
decisionengine.framework.logicengine.tests.test_pandasfact, 64	decisionengine.framework.tests.FailingPublisher, 75
decisionengine.framework.logicengine.tests.test_rule_with_negated_fact, 64	decisionengine.framework.tests.FailingSourceNOP, 75
decisionengine.framework.logicengine.tests.test_simple_configuration, 64	decisionengine.framework.tests.FailingSourceProxy, 75
decisionengine.framework.modules, 72	decisionengine.framework.tests.fixtures, 78
decisionengine.framework.modules.de_logger, 70	decisionengine.framework.tests.ModuleProgramOptions, 76
decisionengine.framework.modules.describe, 71	decisionengine.framework.tests.PublisherNOP, 77
decisionengine.framework.modules.logging_configuration, 71	decisionengine.framework.tests.PublisherWithMissingConsumer, 77
decisionengine.framework.modules.Module, 68	decisionengine.framework.tests.SourceAlias, 77
decisionengine.framework.modules.print_description, 71	decisionengine.framework.tests.SourceNOP, 77
decisionengine.framework.modules.Publisher, 68	decisionengine.framework.tests.SourceWithSampleConfigNOP, 77
decisionengine.framework.modules.Source, 69	decisionengine.framework.tests.SupportsConfigPublisher, 78
decisionengine.framework.modules.SourceProxy, 69	decisionengine.framework.tests.test_client_errors, 79
decisionengine.framework.modules.tests, 68	decisionengine.framework.tests.test_client_server, 79
decisionengine.framework.modules.tests.test_decommission, 67	decisionengine.framework.tests.test_defaults, 80
decisionengine.framework.modules.tests.test_Module, 67	decisionengine.framework.tests.test_error_on_acquire, 80
decisionengine.framework.modules.tests.test_module_decommission, 68	decisionengine.framework.tests.test_module_program_options, 80
decisionengine.framework.modules.tests.test_Publisher, 67	decisionengine.framework.tests.test_query_tool_server, 80
decisionengine.framework.modules.tests.test_Source, 67	decisionengine.framework.tests.test_reaper, 80
decisionengine.framework.modules.tests.test_Transform, 67	decisionengine.framework.tests.test_restart_channel, 81
decisionengine.framework.modules.tests.test_transform_frame, 68	decisionengine.framework.tests.test_sample_config, 81
decisionengine.framework.modules.Transform, 70	decisionengine.framework.tests.test_source_proxy, 82
decisionengine.framework.modules.translate_producer_name, 71	

- decisionengine.framework.tests.test_start_with_bad_channels,
82
- decisionengine.framework.tests.test_start_with_no_channels,
82
- decisionengine.framework.tests.TransformNOP,
78
- decisionengine.framework.tests.TransformWithMissingProducesConsumes,
78
- decisionengine.framework.tests.WorkingSourceProxy,
78
- decisionengine.framework.util, 85
- decisionengine.framework.util.fs, 83
- decisionengine.framework.util.metrics, 83
- decisionengine.framework.util.reaper, 84
- decisionengine.framework.util.singleton, 84
- decisionengine.framework.util.sockets, 84
- decisionengine.framework.util.subclasses, 84
- decisionengine.framework.version, 85
- decisionengine.tests, 85
- decisionengine.tests.test_framework_package,
85

INDEX

Symbols

_DEFAULT_MULTIPROC_MODE (decisionengine.framework.util.metrics.Gauge attribute), 83
 __determine_multiprocess_mode_existence() (decisionengine.framework.util.metrics.Gauge method), 83
 __insert() (decisionengine.framework.dataspace.datablock.Datablock method), 51
 __query() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 44
 __update() (decisionengine.framework.dataspace.datablock.Datablock method), 51
 _abc_impl (decisionengine.framework.config.ValidConfig.ValidConfig attribute), 27
 _abc_impl (decisionengine.framework.dataspace.datablock.Datablock.Header attribute), 52
 _abc_impl (decisionengine.framework.dataspace.datablock.Datablock.Metadata attribute), 52
 _abc_impl (decisionengine.framework.dataspace.datasource.DataSource attribute), 53
 _abc_impl (decisionengine.framework.dataspace.datasources.null.NullDataSource attribute), 42
 _abc_impl (decisionengine.framework.dataspace.datasources.postgresql.Postgresql attribute), 44
 _abc_impl (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS attribute), 36
 _abc_impl (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource_api.SQLAlchemyDS attribute), 29
 _channel_config_dir() (in module decisionengine.framework.config.tests.test_config), 25
 _channel_preamble() (in module decisionengine.framework.engine.DecisionEngine), 60
 _check_keys() (in module decisionengine.framework.config.ChannelConfigHandler), 27
 _check_override() (in module decisionengine.framework.engine.tests.test_startup), 58
 _config_from_file() (in module decisionengine.framework.config.ValidConfig), 28
 _consumed_products() (in module decisionengine.framework.taskmanager.module_graph), 75
 _consumes (decisionengine.framework.modules.Publisher.Publisher attribute), 68
 _consumes (decisionengine.framework.modules.Transform.Transform attribute), 70
 _consumes (decisionengine.framework.tests.ABTransform.ABTransform attribute), 75
 _consumes (decisionengine.framework.tests.BATransform.BATransform attribute), 75
 _consumes (decisionengine.framework.tests.FailingPublisher.FailingPublisher attribute), 76
 _consumes (decisionengine.framework.tests.PublisherNOP.PublisherNOP attribute), 77
 _consumes (decisionengine.framework.tests.TransformNOP.TransformNOP attribute), 78
 _consumes_not_subset() (in module decisionengine.framework.tests.test_start_with_bad_channels), 82
 _convert_to_json() (in module decisionengine.framework.config.ValidConfig), 28
 _create_de_server() (in module decisionengine.framework.engine.DecisionEngine), 60
 _create_facts_dataframe() (decisionengine.framework.logicengine.LogicEngine.LogicEngine method), 65
 _create_module_instance() (in module decisionengine.framework.taskmanager.TaskManager), 74
 _dataframe_to_column_names() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 58
 _dataframe_to_csv() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 58
 _dataframe_to_json() (decisionengine.framework.engine.DecisionEngine.DecisionEngine

`method`), 59
`_dataframe_to_table()` (decisionengine.framework.engine.DecisionEngine.DecisionEngine attribute), 44
`_dataframe_to_table()` (decisionengine.framework.engine.DecisionEngine attribute), 59
`_dataframe_to_vertical_tables()` (decisionengine.framework.engine.DecisionEngine attribute), 84
`_delete()` (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 44
`_derived_class()` (in module decisionengine.framework.util.subclasses), 84
`_dispatch()` (decisionengine.framework.engine.DecisionEngine attribute), 59
`_expected_acquire_result()` (in module decisionengine.framework.tests.ModuleProgramOptions), 76
`_expected_circularity()` (in module decisionengine.framework.tests.test_start_with_bad_channels), 82
`_expected_config_template()` (in module decisionengine.framework.tests.ModuleProgramOptions), 76
`_expected_config_template_with_comments()` (in module decisionengine.framework.tests.ModuleProgramOptions), 77
`_expected_help()` (in module decisionengine.framework.tests.ModuleProgramOptions), 77
`_expected_source_help()` (in module decisionengine.framework.tests.ModuleProgramOptions), 77
`_find_only_one_subclass()` (in module decisionengine.framework.taskmanager.TaskManager), 74
`_get_data()` (decisionengine.framework.modules.SourceProxy.SourceProxy method), 69
`_get_de_conf_manager()` (in module decisionengine.framework.engine.DecisionEngine), 60
`_get_global_config()` (in module decisionengine.framework.engine.DecisionEngine), 60
`_global_config_file()` (in module decisionengine.framework.config.tests.test_config), 25
`_global_config_file()` (in module decisionengine.framework.config.tests.test_validconfig), 26
`_insert()` (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 44
`_insert_returning_result()` (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 44
`_instances` (decisionengine.framework.util.singleton.ScopedSingleton attribute), 84
`_instances` (decisionengine.framework.util.singleton.Singleton attribute), 84
`_load_channel()` (decisionengine.framework.config.ChannelConfigHandler.ChannelConfigHandler method), 27
`_make_de_logger()` (in module decisionengine.framework.config.ChannelConfigHandler), 27
`_make_workers_for()` (in module decisionengine.framework.taskmanager.TaskManager), 74
`_missing_consumes()` (in module decisionengine.framework.tests.test_start_with_bad_channels), 82
`_missing_produces()` (in module decisionengine.framework.tests.test_start_with_bad_channels), 82
`_normalize()` (in module decisionengine.framework.tests.ModuleProgramOptions), 77
`_par_default()` (in module decisionengine.framework.modules.describe), 71
`_par_type()` (in module decisionengine.framework.modules.describe), 71
`_print_comment()` (in module decisionengine.framework.modules.print_description), 71
`_print_type()` (in module decisionengine.framework.modules.print_description), 71
`_print_value()` (in module decisionengine.framework.modules.print_description), 71
`_produced_products()` (in module decisionengine.framework.taskmanager.module_graph), 75
`_produces` (decisionengine.framework.modules.Source.Source attribute), 69
`_produces` (decisionengine.framework.modules.Transform.Transform attribute), 70
`_produces` (decisionengine.framework.tests.ABTransform.ABTransform attribute), 75
`_produces` (decisionengine.framework.tests.BATransform.BATransform attribute), 75
`_produces` (decisionengine.framework.tests.ErrorOnAcquire.ErrorOnAcquire attribute), 75
`_produces` (decisionengine.framework.tests.SourceNOP.SourceNOP attribute), 75
`_produces` (decisionengine.framework.tests.SourceWithSampleConfigNOP.SourceWithSampleConfigNOP attribute), 77

_produces (decisionengine.framework.tests.TransformNOP.TransformNOP, framework.tests.SupportsConfigPublisher.SupportsConfigPublisher, attribute), 78
 _reaper_loop() (decisionengine.framework.dataspace.maintain.Reaper.Reaper, method), 56
 _remove() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql, method), 44
 _run_as_main() (in module decisionengine.framework.tests.ModuleProgramOptions), 77
 _sa_class_manager (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Dataproduct, attribute), 33
 _sa_class_manager (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Header, attribute), 33
 _sa_class_manager (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Metadata, attribute), 34
 _sa_class_manager (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Schema, attribute), 35
 _sa_class_manager (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Taskmanager, attribute), 35
 _sa_registry (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Base, attribute), 33
 _select() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql, method), 44
 _select_dictresult() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql, method), 44
 _select_getresult() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql, method), 44
 _select_tuple() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql, method), 44
 _setitem() (decisionengine.framework.dataspace.datablock.DataBlock, method), 51
 _spec_from_file_name() (in module decisionengine.framework.modules.print_description), 71
 _start_de_server() (in module decisionengine.framework.engine.DecisionEngine), 60
 _supported_config (decisionengine.framework.modules.SourceProxy.SourceProxy, attribute), 69
 _supported_config (decisionengine.framework.tests.SourceWithSampleConfigNOP.SourceWithSampleConfigNOP, attribute), 77
 _supported_config (decisionengine.framework.engine.DecisionEngine.DecisionEngine, attribute), 78
 _update() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql, method), 44
 _update_channel_states() (decisionengine.framework.engine.Workers.Workers, method), 61
 _update_returning_result() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql, method), 44
 Any_ds.db_schema.Dataproduct (class in decisionengine.framework.tests.ABTransform), 75
 access() (decisionengine.framework.engine.Workers.Workers, method), 61
 acquire() (decisionengine.framework.modules.Source.Source, method), 61
 acquire() (decisionengine.framework.modules.SourceProxy.SourceProxy, method), 69
 acquire() (decisionengine.framework.tests.ErrorOnAcquire.ErrorOnAcquire, method), 75
 acquire() (decisionengine.framework.tests.FailingSourceProxy.FailingSourceProxy, method), 75
 acquire() (decisionengine.framework.tests.SourceNOP.SourceNOP, method), 77
 acquire() (decisionengine.framework.tests.SourceWithSampleConfigNOP.SourceWithSampleConfigNOP, method), 77
 acquire() (decisionengine.framework.tests.WorkingSourceProxy.WorkingSourceProxy, method), 78
 AcquireWithConfig (class in decisionengine.framework.tests.ModuleProgramOptions), 76
 AcquireWithSampleConfig (class in decisionengine.framework.tests.ModuleProgramOptions), 76
 ACTIVE (decisionengine.framework.taskmanager.ProcessingState.State, attribute), 72
 add_engine_pidguard() (in module decisionengine.framework.dataspace.datasources.sqlalchemy_ds.utils), 35
 all_subclasses() (in module decisionengine.framework.util.subclasses), 84
 B
 Base (class in decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema), 33
 BATransform (class in decisionengine.framework.tests.BATransform), 75
 block_until() (decisionengine.framework.engine.DecisionEngine.DecisionEngine, method), 59

block_while() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 BooleanExpression (class in decisionengine.framework.logicengine.BooleanExpression), 64
 BOOT (decisionengine.framework.taskmanager.ProcessingState.State attribute), 72
C
 Channel (class in decisionengine.framework.taskmanager.TaskManager), 73
 channel_config_dir() (in module decisionengine.framework.config.policies), 28
 ChannelConfigHandler (class in decisionengine.framework.config.ChannelConfigHandler), 27
 Clean (decisionengine.framework.engine.DecisionEngine.StopState attribute), 60
 clone_model() (in module decisionengine.framework.dataspace.datasources.sqlalchemy_ds.utils), 35
 close() (decisionengine.framework.dataspace.datasource.DataSource method), 53
 close() (decisionengine.framework.dataspace.datasources.null.NullDataSource method), 42
 close() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 44
 close() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS method), 29
 close() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS method), 36
 close() (decisionengine.framework.dataspace.dataspace.DataSpace method), 55
 compress() (in module decisionengine.framework.dataspace.datablock), 53
 config() (in module decisionengine.framework.dataspace.tests.test_Reaper), 48
 ConfigTemplate (class in decisionengine.framework.tests.ModuleProgramOptions), 76
 console_scripts_main() (in module decisionengine.framework.engine.de_client), 62
 console_scripts_main() (in module decisionengine.framework.engine.de_query_tool), 62
 consumes() (decisionengine.framework.logicengine.LogicEngine.LogicEngine method), 66
 consumes() (in module decisionengine.framework.modules.Module), 68
 consumes() (in module decisionengine.framework.modules.Publisher), 69
 consumes() (in module decisionengine.framework.modules.Transform), 70
 Counter (class in decisionengine.framework.util.metrics), 83
 create_parser() (in module decisionengine.framework.engine.de_client), 62
 create_parser() (in module decisionengine.framework.engine.de_query_tool), 62
 create_tables() (decisionengine.framework.dataspace.datasource.DataSource method), 53
 create_tables() (decisionengine.framework.dataspace.datasources.null.NullDataSource method), 42
 create_tables() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 44
 create_tables() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS method), 44
 create_tables() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS method), 29
 create_tables() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS method), 36
 create_time (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema attribute), 34
 creator (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema attribute), 34
D
 DataBlockInput (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 73
 DataBlock (class in decisionengine.framework.dataspace.datablock), 51
 DataProduct (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema attribute), 34
 DataSpace (decisionengine.framework.dataspace.DataSpace method), 29
 DataSource (decisionengine.framework.dataspace.datasource.DataSource method), 53
 DataSource (decisionengine.framework.dataspace.datasources.null.NullDataSource method), 42
 DataSource (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 44
 DataSource (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS method), 29
 DataSource (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS method), 36

<code>dataprodukt_table</code>	(<i>decisionengine.framework.dataspace.datasource.DataSource</i> attribute), 53	<code>decisionengine.framework.dataspace.datablock</code> module, 51
<code>DataSource</code>	(class in <i>decisionengine.framework.dataspace.datasource</i>), 53	<code>decisionengine.framework.dataspace.datasource</code> module, 53
<code>datasource()</code>	(in module <i>decisionengine.framework.dataspace.datasources.tests.fixture</i>), 40	<code>decisionengine.framework.dataspace.datasources</code> module, 47
<code>datasource()</code>	(in module <i>decisionengine.framework.dataspace.tests.fixture</i>), 47	<code>decisionengine.framework.dataspace.datasources.null</code> module, 42
<code>DataSpace</code>	(class in <i>decisionengine.framework.dataspace.dataspace</i>), 55	<code>decisionengine.framework.dataspace.datasources.postgresql</code> module, 44
<code>dataspace()</code>	(in module <i>decisionengine.framework.dataspace.tests.fixture</i>), 47	<code>decisionengine.framework.dataspace.datasources.sqlalchemy</code> module, 36
<code>DataSpaceConfigurationError</code> , 56		<code>decisionengine.framework.dataspace.datasources.sqlalchemy</code> module, 29
<code>DataSpaceConnectionError</code> , 56		<code>decisionengine.framework.dataspace.datasources.sqlalchemy</code> module, 33
<code>DataSpaceError</code> , 56		<code>decisionengine.framework.dataspace.datasources.sqlalchemy</code> module, 35
<code>DataSpaceExistsError</code> , 56		<code>decisionengine.framework.dataspace.datasources.tests</code> module, 42
<code>datestamp</code> (<i>decisionengine.framework.dataspace.datasource.DataSource</i> attribute), 35		<code>decisionengine.framework.dataspace.datasources.tests.fixture</code> module, 39
<code>decision_cycle()</code>	(<i>decisionengine.framework.taskmanager.TaskManager.TaskManager</i> method), 73	<code>decisionengine.framework.dataspace.datasources.tests.test_</code> module, 40
<code>decisionengine</code>	module, 85	<code>decisionengine.framework.dataspace.dataspace</code> module, 55
<code>DecisionEngine</code>	(class in <i>decisionengine.framework.engine.DecisionEngine</i>), 58	<code>decisionengine.framework.dataspace.maintain</code> module, 56
<code>decisionengine.framework</code>	module, 85	<code>decisionengine.framework.dataspace.tests</code> module, 51
<code>decisionengine.framework.about</code>	module, 85	<code>decisionengine.framework.dataspace.tests.fixture</code> module, 47
<code>decisionengine.framework.config</code>	module, 29	<code>decisionengine.framework.dataspace.tests.test_datablock</code> module, 49
<code>decisionengine.framework.config.ChannelConfigHandler</code>	module, 27	<code>decisionengine.framework.dataspace.tests.test_datablock_zl</code> module, 49
<code>decisionengine.framework.config.policies</code>	module, 28	<code>decisionengine.framework.dataspace.tests.test_datasource</code> module, 49
<code>decisionengine.framework.config.tests</code>	module, 27	<code>decisionengine.framework.dataspace.tests.test_dataspace</code> module, 50
<code>decisionengine.framework.config.tests.test_config</code>	module, 25	<code>decisionengine.framework.dataspace.tests.test_Reaper</code> module, 48
<code>decisionengine.framework.config.tests.test_policy</code>	module, 26	<code>decisionengine.framework.engine</code> module, 62
<code>decisionengine.framework.config.tests.test_validation</code>	module, 26	<code>decisionengine.framework.engine.de_client</code> module, 62
<code>decisionengine.framework.config.ValidConfig</code>	module, 27	<code>decisionengine.framework.engine.de_query_tool</code> module, 62
<code>decisionengine.framework.dataspace</code>	module, 57	<code>decisionengine.framework.engine.DecisionEngine</code> module, 58
		<code>decisionengine.framework.engine.tests</code> module, 58

decisionengine.framework.engine.tests.fixtures	decisionengine.framework.modules.Source
module, 57	module, 69
decisionengine.framework.engine.tests.test_client_side_engine	decisionengine.framework.modules.SourceProxy
module, 58	module, 69
decisionengine.framework.engine.tests.test_query_side_engine	decisionengine.framework.modules.tests
module, 58	module, 68
decisionengine.framework.engine.tests.test_startup	decisionengine.framework.modules.tests.test_de_logger
module, 58	module, 67
decisionengine.framework.engine.Workers	decisionengine.framework.modules.tests.test_Module
module, 61	module, 67
decisionengine.framework.logicengine	decisionengine.framework.modules.tests.test_module_decorator
module, 67	module, 68
decisionengine.framework.logicengine.BooleanExpression	decisionengine.framework.modules.tests.test_Publisher
module, 64	module, 67
decisionengine.framework.logicengine.FactLookup	decisionengine.framework.modules.tests.test_Source
module, 65	module, 67
decisionengine.framework.logicengine.LogicEngine	decisionengine.framework.modules.tests.test_Transform
module, 65	module, 67
decisionengine.framework.logicengine.Rule	decisionengine.framework.modules.tests.test_translate_product
module, 66	module, 68
decisionengine.framework.logicengine.RuleEngine	decisionengine.framework.modules.Transform
module, 66	module, 70
decisionengine.framework.logicengine.tests	decisionengine.framework.modules.translate_product_name
module, 64	module, 71
decisionengine.framework.logicengine.tests.test_client_side_engine	decisionengine.framework.taskmanager
module, 63	module, 75
decisionengine.framework.logicengine.tests.test_client_side_engine	decisionengine.framework.taskmanager.module_graph
module, 63	module, 75
decisionengine.framework.logicengine.tests.test_dispatcher_framework	decisionengine.framework.taskmanager.ProcessingState
module, 63	module, 72
decisionengine.framework.logicengine.tests.test_dispatcher_framework	decisionengine.framework.taskmanager.TaskManager
module, 63	module, 73
decisionengine.framework.logicengine.tests.test_dispatcher_framework	decisionengine.framework.tests
module, 63	module, 83
decisionengine.framework.logicengine.tests.test_dispatcher_framework	decisionengine.framework.tests.ABTransform
module, 64	module, 75
decisionengine.framework.logicengine.tests.test_dispatcher_framework	decisionengine.framework.tests.BATransform
module, 64	module, 75
decisionengine.framework.logicengine.tests.test_dispatcher_framework	decisionengine.framework.tests.ErrorOnAcquire
module, 64	module, 75
decisionengine.framework.modules	decisionengine.framework.tests.FailingPublisher
module, 72	module, 76
decisionengine.framework.modules.de_logger	decisionengine.framework.tests.FailingSourceNOP
module, 70	module, 76
decisionengine.framework.modules.describe	decisionengine.framework.tests.FailingSourceProxy
module, 71	module, 76
decisionengine.framework.modules.logging_config	decisionengine.framework.tests.fixtures
module, 71	module, 78
decisionengine.framework.modules.Module	decisionengine.framework.tests.ModuleProgramOptions
module, 68	module, 76
decisionengine.framework.modules.print_descriptions	decisionengine.framework.tests.PublisherNOP
module, 71	module, 77
decisionengine.framework.modules.Publisher	decisionengine.framework.tests.PublisherWithMissingConsumer
module, 68	module, 77

decisionengine.framework.tests.SourceAlias	decisionengine.tests
module, 77	module, 85
decisionengine.framework.tests.SourceNOP	decisionengine.tests.test_framework_package
module, 77	module, 85
decisionengine.framework.tests.SourceWithSampleConfigNOP	delete_data_block() (in module decisio-
module, 77	engine.framework.dataspace.datablock),
decisionengine.framework.tests.SupportsConfigPublisher	default_data_lifetime (decisio-
module, 78	engine.framework.dataspace.datablock.Header
decisionengine.framework.tests.test_client_errors	attribute), 52
module, 79	delete() (decisionengine.framework.dataspace.dataspace.DataSpace
decisionengine.framework.tests.test_client_server	method), 55
module, 79	delete_data_older_than() (decisio-
decisionengine.framework.tests.test_defaults	engine.framework.dataspace.datasource.DataSource
module, 80	method), 53
decisionengine.framework.tests.test_error_on_acquire	delete_data_older_than() (decisio-
module, 80	engine.framework.dataspace.datasources.null.NullDataSource
decisionengine.framework.tests.test_module_program_options	method), 42
module, 80	delete_data_older_than() (decisio-
decisionengine.framework.tests.test_query_tool_server	engine.framework.dataspace.datasources.postgresql.Postgresql
module, 80	method), 44
decisionengine.framework.tests.test_reaper	delete_data_older_than() (decisio-
module, 80	engine.framework.dataspace.datasources.sqlalchemy_ds.datasource
decisionengine.framework.tests.test_restart_channel	method), 30
module, 81	delete_data_older_than() (decisio-
decisionengine.framework.tests.test_sample_config	engine.framework.dataspace.datasources.sqlalchemy_ds.SQLAL
module, 81	method), 36
decisionengine.framework.tests.test_source_proxy	Describe (class in decisio-
module, 82	engine.framework.tests.ModuleProgramOptions),
decisionengine.framework.tests.test_start_with_bad_channels	76
module, 82	describe() (in module decisio-
decisionengine.framework.tests.test_start_with_channels	engine.framework.modules.Publisher),
module, 82	69
decisionengine.framework.tests.TransformNOP	describe() (in module decisio-
module, 78	engine.framework.modules.Source), 69
decisionengine.framework.tests.TransformWithMissingProducersConsumers	describe() (in module decisio-
module, 78	engine.framework.modules.Transform),
decisionengine.framework.tests.WorkingSourceProxy	70
module, 78	DescribeAlias (class in decisio-
decisionengine.framework.util	engine.framework.tests.ModuleProgramOptions),
module, 85	76
decisionengine.framework.util.fs	DEServer() (in module decisio-
module, 83	engine.framework.engine.tests.fixtures),
decisionengine.framework.util.metrics	57
module, 83	DEServer() (in module decisio-
decisionengine.framework.util.reaper	engine.framework.tests.fixtures), 78
module, 84	deserver_mock_data_block() (in module decisio-
decisionengine.framework.util.singleton	engine.framework.tests.test_restart_channel),
module, 84	81
decisionengine.framework.util.sockets	deserver_mock_data_block() (in module decisio-
module, 84	engine.framework.tests.test_start_with_no_channels),
decisionengine.framework.util.subclasses	82
module, 84	do_backup() (decisio-
decisionengine.framework.version	engine.framework.taskmanager.TaskManager.TaskManager
module, 85	

method), 73

F

dump() (decisionengine.framework.config.ValidConfig.ValidConfig method), 28

FactLookup (class in decisionengine.framework.logicengine.FactLookup), 65

duplicate() (decisionengine.framework.dataspace.datablock.DataBlock method), 51

FailingPublisher (class in decisionengine.framework.tests.FailingPublisher), 76

duplicate_datablock() (decisionengine.framework.dataspace.datasource.DataSource method), 53

FailingSourceProxy (class in decisionengine.framework.tests.FailingSourceProxy), 76

duplicate_datablock() (decisionengine.framework.dataspace.datasources.null.NullDataSource method), 42

files_with_extensions() (in module decisionengine.framework.util.fs), 83

duplicate_datablock() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 44

function_name_from_call() (in module decisionengine.framework.logicengine.BooleanExpression), 64

duplicate_datablock() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource_api.SQLAlchemyDS method), 30

Gauge (class in decisionengine.framework.util.metrics), 83

duplicate_datablock() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource_api.SQLAlchemyDS method), 36

generate_insert_query() (in module decisionengine.framework.dataspace.datasources.postgresql), 46

duplicate_datablock() (decisionengine.framework.dataspace.dataspace.DataSpace method), 55

generation_id (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema attribute), 33

E

generation_id (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema attribute), 34

ensure_no_circularities() (in module decisionengine.framework.taskmanager.module_graph), 75

generation_id (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema attribute), 34

ERROR (decisionengine.framework.taskmanager.ProcessingState.State attribute), 72

generation_time (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema attribute), 34

ErrorOnAcquire (class in decisionengine.framework.tests.ErrorOnAcquire), 75

generation_time (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema attribute), 34

evaluate() (decisionengine.framework.logicengine.BooleanExpression.BooleanExpression method), 64

get() (decisionengine.framework.dataspace.datablock.DataBlock method), 51

evaluate() (decisionengine.framework.logicengine.LogicEngine.LogicEngine method), 66

get() (decisionengine.framework.taskmanager.ProcessingState.ProcessingState method), 72

evaluate() (decisionengine.framework.logicengine.Rule.Rule method), 66

get_channels() (decisionengine.framework.config.ChannelConfigHandler.ChannelConfigHandler method), 27

evaluate_facts() (decisionengine.framework.logicengine.LogicEngine.LogicEngine method), 66

getConnection() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 45

execute() (decisionengine.framework.logicengine.RuleEngine.RuleEngine method), 66

get_consumes() (decisionengine.framework.engine.Workers.Worker method), 61

execute_command_from_args() (in module decisionengine.framework.engine.de_client), 62

get_consumes() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 73

execute_command_from_args() (in module decisionengine.framework.engine.de_query_tool), 62

get_data_block_header() (decisionengine.framework.modules.Module.Module method), 68

expiration_time (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema attribute), 34

get_datablock()	(decisionengine.framework.dataspace.datasource.DataSource method), 53	get_dataproducts()	(decisionengine.framework.dataspace.dataspace.DataSpace method), 55
get_datablock()	(decisionengine.framework.dataspace.datasources.null.NullDataSource method), 42	get_header()	(decisionengine.framework.dataspace.datablock.DataBlock method), 51
get_datablock()	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 45	get_header()	(decisionengine.framework.dataspace.datasource.DataSource method), 54
get_datablock()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.DataSource method), 30	get_header()	(decisionengine.framework.dataspace.datasources.null.NullDataSource method), 43
get_datablock()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.DataSource method), 36	get_header()	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 45
get_datablock()	(decisionengine.framework.dataspace.dataspace.DataSpace method), 55	get_header()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource method), 30
get_dataproduct()	(decisionengine.framework.dataspace.datasource.DataSource method), 53	get_header()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS method), 37
get_dataproduct()	(decisionengine.framework.dataspace.datasources.null.NullDataSource method), 42	get_header()	(decisionengine.framework.dataspace.dataspace.DataSpace method), 55
get_dataproduct()	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 45	get_last_generation_id()	(decisionengine.framework.dataspace.datasource.DataSource method), 54
get_dataproduct()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.DataSource method), 30	get_last_generation_id()	(decisionengine.framework.dataspace.datasources.null.NullDataSource method), 43
get_dataproduct()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.DataSource method), 37	get_last_generation_id()	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 45
get_dataproduct()	(decisionengine.framework.dataspace.dataspace.DataSpace method), 55	get_last_generation_id()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource method), 31
get_dataproducts()	(decisionengine.framework.dataspace.datablock.DataBlock method), 51	get_last_generation_id()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS method), 37
get_dataproducts()	(decisionengine.framework.dataspace.datasource.DataSource method), 54	get_last_generation_id()	(decisionengine.framework.dataspace.dataspace.DataSpace method), 55
get_dataproducts()	(decisionengine.framework.dataspace.datasources.null.NullDataSource method), 42	get_logger()	(decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
get_dataproducts()	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 45	get_logger()	(in module decisionengine.framework.modules.de_logger), 70
get_dataproducts()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.DataSource method), 30	get_loglevel()	(decisionengine.framework.datasource.TaskManager.TaskManager method), 73
get_dataproducts()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.DataSource method), 37	get_metadata()	(decisionengine.framework.dataspace.datablock.DataBlock method), 51

get_metadata()	(decisionengine.framework.dataspace.datasource.DataSource method), 73	nengine.framework.taskmanager.TaskManager.TaskManager method), 73
get_metadata()	(decisionengine.framework.dataspace.datasources.null.NullDataSource method), 51	get_taskmanager() (decisionengine.framework.dataspace.datablock.DataBlock method), 51
get_metadata()	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 54	get_taskmanager() (decisionengine.framework.dataspace.datasource.DataSource method), 54
get_metadata()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource4api SQLAlchemyDS method), 31	get_taskmanager() (decisionengine.framework.dataspace.datasources.null.NullDataSource method), 43
get_metadata()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource4api SQLAlchemyDS method), 38	get_taskmanager() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 46
get_metadata()	(decisionengine.framework.dataspace.dataspace.DataSpace method), 31	get_taskmanager() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource4api SQLAlchemyDS method), 46
get_parameters()	(decisionengine.framework.modules.Module.Module method), 68	get_taskmanager() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource4api SQLAlchemyDS method), 38
get_produces()	(decisionengine.framework.engine.Workers.Worker method), 61	get_taskmanager() (decisionengine.framework.dataspace.dataspace.DataSpace method), 56
get_produces()	(decisionengine.framework.taskmanager.TaskManager.TaskManager method), 73	get_taskmanagers() (decisionengine.framework.dataspace.datasource.DataSource method), 54
get_random_port()	(in module decisionengine.framework.util.sockets), 84	get_taskmanagers() (decisionengine.framework.dataspace.datasources.null.NullDataSource method), 43
get_schema()	(decisionengine.framework.dataspace.datasource.DataSource method), 54	get_taskmanagers() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 46
get_schema()	(decisionengine.framework.dataspace.datasources.null.NullDataSource method), 43	get_taskmanagers() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource4api SQLAlchemyDS method), 31
get_schema()	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 45	get_taskmanagers() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource4api SQLAlchemyDS method), 38
get_schema()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource4api SQLAlchemyDS method), 31	get_taskmanagers() (decisionengine.framework.dataspace.dataspace.DataSpace method), 56
get_schema()	(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource4api SQLAlchemyDS method), 38	global_config_dir() (in module decisionengine.framework.config.policies), 28
get_state()	(decisionengine.framework.taskmanager.TaskManager.TaskManager method), 73	global_config_file() (in module decisionengine.framework.config.policies), 28
get_state_name()	(decisionengine.framework.engine.Workers.Worker method), 61	
get_state_name()	(decisionengine.framework.taskmanager.TaskManager.TaskManager method), 73	
get_state_value()	(decisionengine.framework.taskmanager.TaskManager.TaskManager method), 72	

H

Header (class in decisionengine.framework.dataspace.datablock), 52

Header (class in decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema), 33

header_table (decisionengine.framework.dataspace.datasource.DataSource attribute), 54

Help (class in decisionengine.framework.tests.ModuleProgramOptions), 76

Histogram (class in decisionengine.framework.util.metrics), 83

I

id (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Dataproduct module decisionengine.framework.modules.tests.test_de_logger), 33

id (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Header attribute), 34

id (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Metadata attribute), 34

IDLE (decisionengine.framework.taskmanager.ProcessingState attribute), 72

inactive() (decisionengine.framework.taskmanager.ProcessingState.ProcessingState method), 72

insert() (decisionengine.framework.dataspace.datasource.DataSource method), 54

insert() (decisionengine.framework.dataspace.datasource.NullDataSource method), 43

insert() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql module decisionengine.framework.engine.de_client), 62

insert() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql module decisionengine.framework.engine.de_query_tool), 46

insert() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource_api.SQLAlchemyDS method), 32

insert() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.SQLAlchemyDS module decisionengine.framework.engine.DecisionEngine), 60

insert() (decisionengine.framework.dataspace.dataspace.DataSpace method), 56

InvalidMetadataError, 52

is_expired() (decisionengine.framework.dataspace.datablock.DataBlock method), 52

is_valid() (decisionengine.framework.dataspace.datablock.Header method), 52

K

key (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Dataproduct (decisionengine.framework.dataspace.datablock.DataBlock attribute), 33

key (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Header attribute), 34

key (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Metadata attribute), 34

keys() (decisionengine.framework.dataspace.datablock.DataBlock method), 52

load() (in module decisionengine.framework.config.tests.test_config), 25

load_all_channels() (decisionengine.framework.config.ChannelConfigHandler.ChannelConfig method), 27

load_channel() (decisionengine.framework.config.ChannelConfigHandler.ChannelConfig method), 27

load_sample_data_into_datasource() (in module decisionengine.framework.dataspace.tests.fixtures), 48

lock (decisionengine.framework.taskmanager.ProcessingState.ProcessingState property), 72

log_setup() (in module decisionengine.framework.modules.tests.test_de_logger), 47

logic_engine_with_fact() (in module decisionengine.framework.tests.test_fail_on_error), 63

LogicEngine (class in decisionengine.framework.logicengine.LogicEngine), 64

LogicError, 64

M

main() (in module decisionengine.framework.engine.de_client), 62

main() (in module decisionengine.framework.engine.de_query_tool), 46

main() (in module decisionengine.framework.engine.DecisionEngine), 60

main_wrapper() (in module decisionengine.framework.modules.describe), 71

make_db() (in module decisionengine.framework.logicengine.tests.test_facts), 63

mark_demented() (decisionengine.framework.dataspace.dataspace.DataSpace method), 56

mark_expired() (decisionengine.framework.dataspace.datablock.DataBlock method), 56

mark_expired() (decisionengine.framework.dataspace.dataspace.DataSpace method), 56

mark_expired() (decisionengine.framework.dataspace.datablock.DataBlock method), 56

mark_expired() (decisionengine.framework.dataspace.dataspace.DataSpace method), 56

mark_fail_on_error() (in module decisionengine.framework.logicengine.BooleanExpression), 63

64	Metadata (class in decisio-	36	decisionengine.framework.dataspace.datasources.sqlalch
	nengine.framework.dataspace.datablock),	29	
52			decisionengine.framework.dataspace.datasources.sqlalch
Metadata (class in decisio-		33	decisionengine.framework.dataspace.datasources.sqlalch
nengine.framework.dataspace.datasources.sqlalchemy		35	decisionengine.framework.dataspace.datasources.sqlalch
34		35	decisionengine.framework.dataspace.datasources.tests,
metadata (decisionengine.framework.dataspace.datasources.sqlalchemy		42	decisionengine.framework.dataspace.datasources.tests.f
attribute), 33		39	decisionengine.framework.dataspace.datasources.tests.t
metadata_table (decisio-		40	decisionengine.framework.dataspace.datasources.tests.t
nengine.framework.dataspace.datasource.DataSource		42	decisionengine.framework.dataspace.dataspace,
attribute), 55		55	decisionengine.framework.dataspace.dataspace,
MIN_RETENTION_INTERVAL_DAYS (decisio-		56	decisionengine.framework.dataspace.dataspace,
nengine.framework.dataspace.maintain.Reaper		51	decisionengine.framework.dataspace.tests,
attribute), 56		47	decisionengine.framework.dataspace.tests.fixtures,
MIN_SECONDS_BETWEEN_RUNS (decisio-		49	decisionengine.framework.dataspace.tests.test_databloc
nengine.framework.dataspace.maintain.Reaper		49	decisionengine.framework.dataspace.tests.test_databloc
attribute), 56		49	decisionengine.framework.dataspace.tests.test_datasour
missed_update_count (decisio-		49	decisionengine.framework.dataspace.tests.test_dataspac
nengine.framework.dataspace.datasources.sqlalchemy		50	decisionengine.framework.dataspace.tests.test_Reaper,
attribute), 34		48	decisionengine.framework.engine, 62
mock_data_block() (in module decisio-		62	decisionengine.framework.engine.de_client,
nengine.framework.dataspace.datasources.tests.fixtures),		62	decisionengine.framework.engine.de_query_tool,
40		58	decisionengine.framework.engine.DecisionEngine,
module		58	decisionengine.framework.engine.tests, 58
decisionengine, 85		57	decisionengine.framework.engine.tests.fixtures,
decisionengine.framework, 85		58	decisionengine.framework.engine.tests.test_client_only
decisionengine.framework.about, 85		58	decisionengine.framework.engine.tests.test_query_tool
decisionengine.framework.config, 29		58	decisionengine.framework.engine.tests.test_startup,
decisionengine.framework.config.ChannelConfigHandler		61	decisionengine.framework.engine.Workers,
27		67	decisionengine.framework.logicengine, 67
decisionengine.framework.config.policies,			decisionengine.framework.logicengine.BooleanExpression
28			decisionengine.framework.logicengine.sqlalchemy_ds,
decisionengine.framework.config.tests, 27			
decisionengine.framework.config.tests.test_conf			
25			
decisionengine.framework.config.tests.test_pold			
26			
decisionengine.framework.config.tests.test_vald			
26			
decisionengine.framework.config.ValidConfig,			
27			
decisionengine.framework.dataspace, 57			
decisionengine.framework.dataspace.datablock,			
51			
decisionengine.framework.dataspace.datasource,			
53			
decisionengine.framework.dataspace.datasources,			
47			
decisionengine.framework.dataspace.datasources,			
42			
decisionengine.framework.dataspace.datasources,			
44			
decisionengine.framework.dataspace.datasources.sqlalchemy_ds,			

decisionengine.framework.logicengine.FactLookup, 67
 65 decisionengine.framework.modules.tests.test_Transform,
 decisionengine.framework.logicengine.LogicEngine, 67
 65 decisionengine.framework.modules.tests.test_translate_
 decisionengine.framework.logicengine.Rule, 68
 66 decisionengine.framework.modules.Transform,
 decisionengine.framework.logicengine.RuleEngine, 70
 66 decisionengine.framework.modules.translate_product_name_
 decisionengine.framework.logicengine.tests, 71
 64 decisionengine.framework.taskmanager, 75
 decisionengine.framework.logicengine.tests.test_casacade_infer, decisionengine.framework.taskmanager.module_graph,
 63 75
 decisionengine.framework.logicengine.tests.test_consistent, decisionengine.framework.taskmanager.ProcessingState,
 63 72
 decisionengine.framework.logicengine.tests.test_duplicate_interfaces, decisionengine.framework.taskmanager.TaskManager,
 63 73
 decisionengine.framework.logicengine.tests.test_facton, decisionengine.framework.tests, 83
 63 decisionengine.framework.tests.ABTransform,
 decisionengine.framework.logicengine.tests.test_fail_on_error, decisionengine.framework.tests.BATransform,
 63
 decisionengine.framework.logicengine.tests.test_pandas_fact, decisionengine.framework.tests.ErrorOnAcquire,
 64
 decisionengine.framework.logicengine.tests.test_rule_with_negated_fact, decisionengine.framework.tests.FailingPublisher,
 64
 decisionengine.framework.logicengine.tests.test_simple_configuration, decisionengine.framework.tests.FailingSourceNOP,
 64
 decisionengine.framework.modules, 72 76
 decisionengine.framework.modules.de_logger, decisionengine.framework.tests.FailingSourceProxy,
 70 76
 decisionengine.framework.modules.describe, decisionengine.framework.tests.fixtures,
 71 78
 decisionengine.framework.modules.logging_configuration, decisionengine.framework.tests.ModuleProgramOptions,
 71 76
 decisionengine.framework.modules.Module, decisionengine.framework.tests.PublisherNOP,
 68 77
 decisionengine.framework.modules.print_descriptions, decisionengine.framework.tests.PublisherWithMissingConnections,
 71 77
 decisionengine.framework.modules.Publisher, decisionengine.framework.tests.SourceAlias,
 68 77
 decisionengine.framework.modules.Source, decisionengine.framework.tests.SourceNOP,
 69 77
 decisionengine.framework.modules.SourceProxy, decisionengine.framework.tests.SourceWithSampleConfiguration,
 69 77
 decisionengine.framework.modules.tests, decisionengine.framework.tests.SupportsConfigPublisher,
 68 78
 decisionengine.framework.modules.tests.test_delegation, decisionengine.framework.tests.test_client_errors,
 67 79
 decisionengine.framework.modules.tests.test_Modules, decisionengine.framework.tests.test_client_server,
 67 79
 decisionengine.framework.modules.tests.test_modules_in_engine, decisionengine.framework.tests.test_defaults,
 68 80
 decisionengine.framework.modules.tests.test_Publisher, decisionengine.framework.tests.test_error_on_acquire,
 67 80
 decisionengine.framework.modules.tests.test_Sources, decisionengine.framework.tests.test_module_program_options

80
 decisionengine.framework.tests.test_query_tool_server
 80
 decisionengine.framework.tests.test_reaper, 35
 80
 decisionengine.framework.tests.test_restart_channel, 60
 81
 decisionengine.framework.tests.test_sample_config, 42
 81
 decisionengine.framework.tests.test_source_proxy,
 82
 decisionengine.framework.tests.test_start_with_bad_channels,
 82
 decisionengine.framework.tests.test_start_with_no_channels,
 82
 decisionengine.framework.tests.TransformNOP, 35
 78
 decisionengine.framework.tests.TransformWithMissingParameter, 71
 78
 decisionengine.framework.tests.WorkingSourceProxyParameter, 71
 78
 decisionengine.framework.util, 85
 decisionengine.framework.util.fs, 83
 decisionengine.framework.util.metrics, 83
 decisionengine.framework.util.reaper, 84
 decisionengine.framework.util.singleton, 84
 decisionengine.framework.util.sockets, 84
 decisionengine.framework.util.subclasses, 84
 decisionengine.framework.version, 85
 decisionengine.tests, 85
 decisionengine.tests.test_framework_package, 85
 Module (class in decisionengine.framework.modules.Module), 68
 ModuleProgramOptions (class in decisionengine.framework.modules.describe), 71
 mydata() (in module decisionengine.framework.logicengine.tests.test_pandas_fact), 64
 myengine() (in module decisionengine.framework.logicengine.tests.test_cascaded_rules), 63
 myengine() (in module decisionengine.framework.logicengine.tests.test_pandas_fact), 64
 myengine() (in module decisionengine.framework.logicengine.tests.test_rule_with_negated_fact), 64
 myengine() (in module decisionengine.framework.logicengine.tests.test_simple_configuration), 64
 N
 name (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db
 attribute), 35
 NotFound (decisionengine.framework.engine.DecisionEngine.StopState
 attribute), 60
 NullDataSource (class in decisionengine.framework.dataspace.datasources.null),
 42
 OFFLINE (decisionengine.framework.taskmanager.ProcessingState.State
 attribute), 72
 orm_as_dict() (in module decisionengine.framework.dataspace.datasources.sqlalchemy_ds.utils),
 35
 P
 Parameter (class in decisionengine.framework.modules.describe), 71
 Parameter (class in decisionengine.framework.modules.Publisher),
 68
 Parameter (class in decisionengine.framework.modules.Source), 69
 Parameter (class in decisionengine.framework.modules.Transform),
 70
 parse_program_options() (in module decisionengine.framework.engine.DecisionEngine),
 60
 PG_DE_DB_WITH_SCHEMA() (in module decisionengine.framework.dataspace.datasources.tests.fixtures),
 39
 PG_DE_DB_WITH_SCHEMA() (in module decisionengine.framework.dataspace.tests.fixtures),
 47
 PG_DE_DB_WITH_SCHEMA() (in module decisionengine.framework.engine.tests.fixtures),
 57
 PG_DE_DB_WITH_SCHEMA() (in module decisionengine.framework.tests.fixtures), 79
 PG_DE_DB_WITHOUT_SCHEMA() (in module decisionengine.framework.dataspace.datasources.tests.fixtures),
 39
 PG_DE_DB_WITHOUT_SCHEMA() (in module decisionengine.framework.dataspace.tests.fixtures),
 47
 PG_DE_DB_WITHOUT_SCHEMA() (in module decisionengine.framework.engine.tests.fixtures), 57
 PG_DE_DB_WITHOUT_SCHEMA() (in module decisionengine.framework.tests.fixtures), 78
 PG_PROG() (in module decisionengine.framework.dataspace.datasources.tests.fixtures),
 40

PG_PROG() (in module decisionengine.framework.dataspace.tests.fixtures), 47
 PG_PROG() (in module decisionengine.framework.engine.tests.fixtures), 57
 PG_PROG() (in module decisionengine.framework.tests.fixtures), 79
 post_create() (decisionengine.framework.modules.Source.Source method), 69
 post_create() (decisionengine.framework.modules.SourceProxy.SourceProxy method), 69
 Postgresql (class in decisionengine.framework.dataspace.datasources.postgresql), 44
 print_channel_config() (decisionengine.framework.config.ChannelConfigHandler.ChannelConfigHandler method), 27
 print_consumes() (in module decisionengine.framework.modules.print_description), 71
 print_produces() (in module decisionengine.framework.modules.print_description), 71
 print_supported_config() (in module decisionengine.framework.modules.print_description), 71
 probably_running() (decisionengine.framework.taskmanager.ProcessingState.ProcessingState method), 72
 process_args() (decisionengine.framework.modules.describe.ModuleProgramOptions.ModuleProgramOptions method), 71
 ProcessingState (class in decisionengine.framework.taskmanager.ProcessingState), 72
 produces() (decisionengine.framework.logicengine.LogicEngine.LogicEngine method), 66
 produces() (in module decisionengine.framework.modules.Module), 68
 produces() (in module decisionengine.framework.modules.Source), 69
 produces() (in module decisionengine.framework.modules.Transform), 70
 ProductRetriever (class in decisionengine.framework.dataspace.datablock), 52
 publish() (decisionengine.framework.modules.Publisher.Publisher method), 68
 publish() (decisionengine.framework.tests.FailingPublisher.FailingPublisher method), 76
 publish() (decisionengine.framework.tests.PublisherNOP.PublisherNOP method), 77
 Publisher (class in decisionengine.framework.modules.Publisher), 68
 PublisherNOP (class in decisionengine.framework.tests.PublisherNOP), 77
 PublisherWithMissingConsumes (class in decisionengine.framework.tests.PublisherWithMissingConsumes), 77
 put() (decisionengine.framework.dataspace.datablock.DataBlock method), 52
R
 reap() (decisionengine.framework.dataspace.maintain.Reaper method), 56
 Reaper (class in decisionengine.framework.dataspace.maintain), 56
 reaper() (in module decisionengine.framework.dataspace.tests.test_Reaper), 48
 reaper_start() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 reaper_status() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 reaper_stop() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 registry (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.sqlalchemy attribute), 33
 RequestHandler (class in decisionengine.framework.engine.DecisionEngine), 60
 required_keys (decisionengine.framework.dataspace.datablock.Header attribute), 52
 required_keys (decisionengine.framework.dataspace.datablock.Metadata attribute), 52
 reset_connections() (decisionengine.framework.dataspace.datasource.DataSource method), 55
 reset_connections() (decisionengine.framework.dataspace.datasources.null.NullDataSource method), 43
 reset_connections() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 46
 reset_connections() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource

method), 32
 reset_connections() (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema attribute), 60
 method), 39
 retention_interval (decisionengine.framework.dataspace.maintain.Reaper property), 56
 rm_channel() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 60
 method), 59
 rpc_block_while() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 rpc_get_channel_log_level() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 rpc_get_log_level() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 rpc_kill_channel() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 65
 method), 59
 rpc_paths (decisionengine.framework.engine.DecisionEngine.RequestHandler attribute), 60
 rpc_print_product() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 61
 method), 59
 rpc_print_products() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 rpc_query_tool() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 rpc_reaper_start() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 rpc_reaper_status() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 rpc_reaper_stop() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 rpc_rm_channel() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 rpc_set_channel_log_level() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 rpc_show_config() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 rpc_show_de_config() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 59
 rpc_start_channel() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 60
 rpc_start_channels() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 60
 rpc_status() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 60
 rpc_stop() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 60
 rpc_stop_channel() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 60
 rpc_stop_channels() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 60
 Rule (class in decisionengine.framework.logicengine.Rule), 66
 rule_for() (decisionengine.framework.logicengine.FactLookup.FactLookup method), 66
 RuleEngine (class in decisionengine.framework.logicengine.RuleEngine), 66
 run() (decisionengine.framework.engine.Workers.Worker method), 73
 run() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 73
 run_logic_engine() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 73
 run_publishers() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 73
 run_source() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 73
 run_transform() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 74
 run_transforms() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 74
 S
 scheduled_create_time (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema attribute), 34
 Schema (class in decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema), 35
 schema (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema attribute), 35

[schema_id \(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Header attribute\), 34](#)
[schema_id \(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Taskmanager SQLALCHEMY_PG_WITH_SCHEMA\(\) \(in module decisionengine.framework.dataspace.datasources.tests.fixtures\), 47](#)
[schema_id \(decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Taskmanager SQLALCHEMY_PG_WITH_SCHEMA\(\) \(in module decisionengine.framework.engine.tests.fixtures\), 57](#)
[SQLALCHEMY_PG_WITH_SCHEMA\(\) \(in module decisionengine.framework.tests.fixtures\), 79](#)
[SQLALCHEMY_TEMPFILE_SQLITE\(\) \(in module decisionengine.framework.dataspace.datasources.tests.fixtures\), 40](#)
[SQLALCHEMY_TEMPFILE_SQLITE\(\) \(in module decisionengine.framework.dataspace.tests.fixtures\), 47](#)
[SQLALCHEMY_TEMPFILE_SQLITE\(\) \(in module decisionengine.framework.engine.tests.fixtures\), 57](#)
[SQLALCHEMY_TEMPFILE_SQLITE\(\) \(in module decisionengine.framework.tests.fixtures\), 79](#)
[SQLAlchemyDS \(class in decisionengine.framework.dataspace.datasources.sqlalchemy_ds\), 36](#)
[SQLAlchemyDS \(class in decisionengine.framework.dataspace.datasources.sqlalchemy_ds.datasource\), 29](#)
[SHUTDOWN \(decisionengine.framework.taskmanager.ProcessingState.State \(decisionengine.framework.dataspace.maintain.Reaper attribute\), 72](#)
[shutdown\(\) \(decisionengine.framework.modules.Publishers.PublishChannel\(\) \(decisionengine.framework.engine.DecisionEngine.DecisionEngine method\), 60](#)
[SHUTTINGDOWN \(decisionengine.framework.taskmanager.ProcessingState.State \(decisionengine.framework.engine.DecisionEngine.DecisionEngine attribute\), 73](#)
[Singleton \(class in decisionengine.framework.util.singleton\), 84](#)
[SingletonABC \(class in decisionengine.framework.util.singleton\), 84](#)
[sorted_rules\(\) \(decisionengine.framework.logicengine.FactLookup.FactLookup method\), 65](#)
[Source \(class in decisionengine.framework.modules.Source\), 69](#)
[SourceNOP \(class in decisionengine.framework.tests.SourceNOP\), 77](#)
[SourceProxy \(class in decisionengine.framework.modules.SourceProxy\), 56](#)

stop_channels() (decisionengine.framework.engine.DecisionEngine.DecisionEngineHeader attribute), 35
 stop_worker() (decisionengine.framework.engine.DecisionEngine.DecisionEngineHeader attribute), 35
 StopState (class in decisionengine.framework.engine.DecisionEngine), 60
 store_taskmanager() (decisionengine.framework.dataspace.datablock.DataBlock.TaskManager method), 52
 store_taskmanager() (decisionengine.framework.dataspace.datasource.DataSource.TaskManager method), 55
 store_taskmanager() (decisionengine.framework.dataspace.datasources.null.NullTaskManager method), 43
 store_taskmanager() (decisionengine.framework.dataspace.datasources.postgresql.PostgreSQLTaskManager method), 46
 store_taskmanager() (decisionengine.framework.dataspace.datasources.sqlalchemy_api SQLAlchemyDS.TaskManager method), 32
 store_taskmanager() (decisionengine.framework.dataspace.datasources.sqlalchemy_api SQLAlchemyDS.TaskManager method), 33
 store_taskmanager() (decisionengine.framework.dataspace.dataspace.DataSpace.TaskManager method), 56
 Summary (class in decisionengine.framework.util.metrics), 83
 supports_config() (in module decisionengine.framework.modules.describe), 71
 supports_config() (in module decisionengine.framework.modules.Publisher), 69
 supports_config() (in module decisionengine.framework.modules.Source), 69
 supports_config() (in module decisionengine.framework.modules.Transform), 70
 SupportsConfig (class in decisionengine.framework.tests.SupportsConfigPublisher), 78
T
 tables (decisionengine.framework.dataspace.datasources.postgresql.PostgreSQL attribute), 46
 take_offline() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 74
 task_dataproduct (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Taskmanager attribute), 46
 taskmanager (class in decisionengine.framework.taskmanager.TaskManager), 73
 taskmanager (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Taskmanager attribute), 33
 taskmanager (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Taskmanager attribute), 34
 taskmanager (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Taskmanager attribute), 35
 taskmanager_id (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Taskmanager attribute), 35
 taskmanager_id (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db_schema.Taskmanager attribute), 35
 taskmanager_table (decisionengine.framework.dataspace.datasource.DataSource attribute), 55
 Terminated (decisionengine.framework.engine.DecisionEngine.StopState attribute), 60
 test() (decisionengine.framework.tests.ModuleProgramOptions.AcquireW method), 76
 test() (decisionengine.framework.tests.ModuleProgramOptions.AcquireW method), 76
 test() (decisionengine.framework.tests.ModuleProgramOptions.ConfigTen method), 76
 test() (decisionengine.framework.tests.ModuleProgramOptions.Describe method), 76
 test() (decisionengine.framework.tests.ModuleProgramOptions.Describe method), 76
 test() (decisionengine.framework.tests.ModuleProgramOptions.Help method), 76
 test_acquire_for_sources() (in module decisionengine.framework.tests.test_module_program_options), 76
 test_acquire_for_sources() (in module decisionengine.framework.tests.test_module_program_options), 76

test_by_nonsense_is_err() (in module decisio- nengine.framework.modules.tests.test_de_logger), 67	26	test_channel_no_modules() (in module decisio- nengine.framework.config.tests.test_config), 67	
test_by_size() (in module decisio- nengine.framework.modules.tests.test_de_logger), 67	26	test_client_can_double_set_de_server_channel_log_level() (in module decisio- nengine.framework.tests.test_sample_config), 81	
test_by_time() (in module decisio- nengine.framework.modules.tests.test_de_logger), 67		test_client_can_get_de_server_channel_config() (in module decisio- nengine.framework.tests.test_sample_config), 81	
test_can_import() (in module decisio- nengine.tests.test_framework_package), 85		test_client_can_get_de_server_channel_log_level() (in module decisio- nengine.framework.tests.test_sample_config), 81	
test_change_port() (in module decisio- nengine.framework.engine.tests.test_startup), 58		test_client_can_get_de_server_reaper_start_delay() (in module decisio- nengine.framework.tests.test_reaper), 80	
test_channel_config_dir() (in module decisio- nengine.framework.config.tests.test_policies), 26		test_client_can_get_de_server_reaper_status() (in module decisio- nengine.framework.tests.test_reaper), 80	
test_channel_empty_config() (in module decisio- nengine.framework.config.tests.test_config), 25		test_client_can_get_de_server_reaper_stop() (in module decisio- nengine.framework.tests.test_reaper), 80	
test_channel_empty_dictionary() (in module deci- sionengine.framework.config.tests.test_config), 25		test_client_can_get_de_server_show_channel_logger_level() (in module decisio- nengine.framework.tests.test_defaults), 80	
test_channel_invalid_modules_list() (in module decisio- nengine.framework.config.tests.test_config), 25		test_client_can_get_de_server_show_config() (in module decisio- nengine.framework.tests.test_sample_config), 81	
test_channel_invalid_modules_no_keys() (in module decisio- nengine.framework.config.tests.test_config), 25		test_client_can_get_de_server_show_logger_level() (in module decisio- nengine.framework.tests.test_sample_config), 81	
test_channel_invalid_modules_string() (in module decisio- nengine.framework.config.tests.test_config), 25		test_client_can_get_de_server_status() (in module decisio- nengine.framework.tests.test_sample_config), 81	
test_channel_loading() (in module decisio- nengine.framework.config.tests.test_config), 25		test_client_can_get_products() (in module decisio- nengine.framework.tests.test_sample_config), 81	
test_channel_module_missing_all() (in module decisio- nengine.framework.config.tests.test_config), 26		test_client_can_get_products_no_channels() (in module decisio- nengine.framework.tests.test_sample_config), 81	
test_channel_module_missing_module() (in module decisio- nengine.framework.config.tests.test_config), 26		test_client_can_get_products_no_channels() (in module decisio- nengine.framework.tests.test_start_with_bad_channels), 82	
test_channel_module_missing_parameters() (in module decisio- nengine.framework.config.tests.test_config), 26		test_client_can_kill_one_channel() (in module decisio-	
test_channel_names() (in module decisio- nengine.framework.config.tests.test_config), 26			
test_channel_no_config_files() (in module deci- sionengine.framework.config.tests.test_config),			

```

    nengine.framework.tests.test_sample_config),
81
test_client_can_kill_one_channel_force()
    (in module decisionengine.framework.tests.test_sample_config),
81
test_client_can_kill_one_channel_timeout()
    (in module decisionengine.framework.tests.test_sample_config),
81
test_client_can_set_de_server_channel_log_level()
    (in module decisionengine.framework.tests.test_sample_config),
81
test_client_can_start_all_channel()
    (in module decisionengine.framework.tests.test_sample_config),
81
test_client_can_start_one_channel()
    (in module decisionengine.framework.tests.test_sample_config),
81
test_client_can_stop_channels()
    (in module decisionengine.framework.tests.test_sample_config),
81
test_client_can_stop_one_channel()
    (in module decisionengine.framework.tests.test_sample_config),
81
test_client_can_stop_server() (in module decisionengine.framework.tests.test_sample_config),
81
test_client_cannot_double_start()
    (in module decisionengine.framework.tests.test_sample_config),
81
test_client_cannot_wait_on_bad_state()
    (in module decisionengine.framework.tests.test_client_errors),
79
test_client_de_config_is_json() (in module decisionengine.framework.tests.test_defaults), 80
test_client_err_returned_as_rc()
    (in module decisionengine.framework.engine.tests.test_client_only),
58
test_client_err_returned_as_rc()
    (in module decisionengine.framework.engine.tests.test_query_tool_only),
58
test_client_err_returned_verbose_as_rc()
    (in module decisionengine.framework.engine.tests.test_client_only),
58
test_client_err_returned_verbose_as_rc()
    (in module decisionengine.framework.engine.tests.test_query_tool_only),
58
test_client_get_channel_log_fails_cleanly()
    (in module decisionengine.framework.tests.test_sample_config),
82
test_client_get_non_real_channel()
    (in module decisionengine.framework.tests.test_sample_config),
82
test_client_help() (in module decisionengine.framework.engine.tests.test_client_only),
58
test_client_print_product() (in module decisionengine.framework.tests.test_client_server), 79
test_client_print_product_columns()
    (in module decisionengine.framework.tests.test_client_server),
79
test_client_print_product_columns_query()
    (in module decisionengine.framework.tests.test_client_server),
79
test_client_print_product_json()
    (in module decisionengine.framework.tests.test_client_server),
79
test_client_print_product_not_real()
    (in module decisionengine.framework.tests.test_client_server),
79
test_client_print_product_query()
    (in module decisionengine.framework.tests.test_client_server),
79
test_client_print_product_types()
    (in module decisionengine.framework.tests.test_client_server),
79
test_client_print_product_vertical()
    (in module decisionengine.framework.tests.test_client_server),
79
test_client_set_channel_log_fails_cleanly()
    (in module decisionengine.framework.tests.test_sample_config),
82
test_client_start_non_real_channel()
    (in module decisionengine.framework.tests.test_sample_config),
82

```

test_client_status_msg_to_stdout() (in module decisionengine.framework.tests.test_client_server), 79	(in module decisionengine.framework.dataspace.tests.test_datablock), 49
test_client_stop_non_real_channel() (in module decisionengine.framework.tests.test_sample_config), 82	test_DataBlock_get_header() (in module decisionengine.framework.dataspace.tests.test_datablock), 49
test_client_wait_timeout_works() (in module decisionengine.framework.tests.test_sample_config), 82	test_DataBlock_get_metadata() (in module decisionengine.framework.dataspace.tests.test_datablock), 49
test_client_with_no_command_says_use_help() (in module decisionengine.framework.engine.tests.test_client_only), 58	test_DataBlock_get_taskmanager() (in module decisionengine.framework.dataspace.tests.test_datablock), 49
test_client_with_no_server() (in module decisionengine.framework.engine.tests.test_client_only), 58	test_DataBlock_is_expired() (in module decisionengine.framework.dataspace.tests.test_datablock), 49
test_client_with_no_server_verbose() (in module decisionengine.framework.engine.tests.test_client_only), 58	test_DataBlock_is_expired_with_key() (in module decisionengine.framework.dataspace.tests.test_datablock), 49
test_compound_fact_with_spaces() (in module decisionengine.framework.logicengine.tests.test_facts), 63	test_DataBlock_key_management() (in module decisionengine.framework.dataspace.tests.test_datablock), 49
test_compress() (in module decisionengine.framework.dataspace.tests.test_datablock_test), 49	test_DataBlock_key_management_change_name() (in module decisionengine.framework.dataspace.tests.test_datablock), 49
test_conditional_fact() (in module decisionengine.framework.logicengine.tests.test_fail_on_test), 63	test_DataBlock_mark_expired() (in module decisionengine.framework.dataspace.tests.test_datablock), 49
test_config_templates() (in module decisionengine.framework.tests.test_module_program_options), 80	test_DataBlock_no_key_by_name() (in module decisionengine.framework.dataspace.tests.test_datablock), 49
test_configuration_with_fact_using_function() (in module decisionengine.framework.logicengine.tests.test_construction), 63	test_DataBlock_to_str() (in module decisionengine.framework.dataspace.tests.test_datablock), 49
test_configuration_with_numpy_facts() (in module decisionengine.framework.logicengine.tests.test_construction), 63	test_dataspace_config_finds_bad() (in module decisionengine.framework.dataspace.tests.test_dataspace), 50
test_create_tables() (in module decisionengine.framework.dataspace.datasources.tests.test_defaults), 40	test_default_config() (in module decisionengine.framework.engine.tests.test_startup), 58
test_DataBlock_constructor() (in module decisionengine.framework.dataspace.tests.test_datablock), 49	test_default_construction() (in module decisionengine.framework.logicengine.tests.test_construction), 63
test_DataBlock_duplicate() (in module decisionengine.framework.dataspace.tests.test_datablock), 49	test_delete_data_older_than_arg() (in module decisionengine.framework.dataspace.datasources.tests.test_datasource), 40
test_DataBlock_get_dataproducts()	test_descriptions() (in module decisionengine.framework.tests.test_module_program_options),


```

80 test_duplicate_datablock() (in module decisio-
engine.framework.dataspace.datasources.tests.test_datasource_api),
40 test_duplicate_datablock() (in module decisio-
engine.framework.dataspace.tests.test_dataspace), 48
50 test_duplicate_fact_names() (in module decisio-
engine.framework.logicengine.tests.test_duplicate_fact_names),
63 test_empty_config() (in module decisio-
engine.framework.config.tests.test_config), 48
26 test_empty_config() (in module decisio-
engine.framework.config.tests.test_validconfig), 48
26 test_empty_dict() (in module decisio-
engine.framework.config.tests.test_config), 63
test_empty_dict_with_leading_comment()
(in module decisio-
engine.framework.config.tests.test_config), 63
26 test_exclusive_options() (in module decisio-
engine.framework.engine.tests.test_client_only), 42
58 test_fact_using_numpy_array() (in module decisio-
engine.framework.logicengine.tests.test_facts), 40
63 test_fact_using_numpy_function()
(in module decisio-
engine.framework.logicengine.tests.test_facts), 50
63 test_fact_with_fail_on_error()
(in module decisio-
engine.framework.logicengine.tests.test_facts), 40
63 test_fact_with_misspecified_attribute()
(in module decisio-
engine.framework.logicengine.tests.test_fail_on_error), 50
63 test_fact_with_nested_names() (in module decisio-
engine.framework.logicengine.tests.test_facts), 40
63 test_fail_bad_config() (in module decisio-
engine.framework.dataspace.tests.test_Reaper), 48
test_fail_missing_config() (in module decisio-
engine.framework.dataspace.tests.test_Reaper), 48
test_fail_missing_config_key()
(in module decisio-
engine.framework.dataspace.tests.test_Reaper), 48
test_fail_on_error() (in module decisio-
engine.framework.logicengine.tests.test_fail_on_error),
test_fail_small_retain() (in module decisio-
engine.framework.dataspace.tests.test_Reaper),
test_fail_small_run_interval()
(in module decisio-
engine.framework.dataspace.tests.test_Reaper),
test_fail_start_two_reapers() (in module decisio-
engine.framework.dataspace.tests.test_Reaper),
test_fail_wrong_config_key() (in module decisio-
engine.framework.dataspace.tests.test_Reaper),
test_false_fact_with_spaces() (in module decisio-
engine.framework.logicengine.tests.test_fail_on_error),
test_false_literal_fact() (in module decisio-
engine.framework.logicengine.tests.test_fail_on_error),
test_generate_insert_query() (in module decisio-
engine.framework.dataspace.datasources.tests.test_postgresql),
test_get_datablock() (in module decisio-
engine.framework.dataspace.datasources.tests.test_datasource_
test_get_datablock() (in module decisio-
engine.framework.dataspace.tests.test_dataspace),
test_get_dataproduct() (in module decisio-
engine.framework.dataspace.datasources.tests.test_datasource_
test_get_dataproduct() (in module decisio-
engine.framework.dataspace.tests.test_dataspace),
test_get_dataproduct_not_exist()
(in module decisio-
engine.framework.dataspace.datasources.tests.test_datasource_
test_get_dataproduct_not_exist()
(in module decisio-
engine.framework.dataspace.tests.test_dataspace),
test_get_dataproducts() (in module decisio-
engine.framework.dataspace.datasources.tests.test_datasource_
test_get_dataproducts() (in module decisio-
engine.framework.dataspace.tests.test_dataspace),
test_get_dataproducts_not_exist()
(in module decisio-
engine.framework.dataspace.datasources.tests.test_datasource_

```

```

41                                     (in module decisio-
test_get_dataproducts_not_exist()      nengine.framework.dataspace.tests.test_dataspace),
(in module decisio-                    50
nengine.framework.dataspace.tests.test_dataspace)
test_get_header() (in module decisio- 41
nengine.framework.dataspace.datasources.tests.test_datasource)
41 test_get_header() (in module decisio-
nengine.framework.dataspace.tests.test_dataspace),
test_get_header() (in module decisio- 50
nengine.framework.dataspace.tests.test_dataspace)
test_get_header_not_exist() (in module decisio-
nengine.framework.dataspace.datasources.tests.test_datasource),
41 test_get_header_not_exist() (in module decisio-
nengine.framework.dataspace.tests.test_dataspace),
50 test_get_header_not_exist() (in module decisio-
nengine.framework.dataspace.datasources.tests.test_datasource),
41 test_get_header_not_exist() (in module decisio-
nengine.framework.dataspace.tests.test_dataspace),
50 test_get_header_not_exist() (in module decisio-
nengine.framework.dataspace.datasources.tests.test_datasource),
test_get_last_generation_id() (in module decisio- test_global_channel_log_level_in_config()
nengine.framework.dataspace.datasources.tests.test_datasource), 41 module decisio-
nengine.framework.tests.test_defaults), 80
test_get_last_generation_id() (in module decisio- test_global_config_dir() (in module decisio-
nengine.framework.dataspace.tests.test_dataspace), nengine.framework.config.tests.test_policies),
50 26
test_get_last_generation_id_not_exist() test_global_config_file() (in module decisio-
(in module decisio- nengine.framework.config.tests.test_policies),
nengine.framework.dataspace.datasources.tests.test_datasource), 41
41 test_get_last_generation_id_not_exist() test_has_config() (in module decisio-
(in module decisio- nengine.framework.dataspace.datasources.tests.test_datasource),
nengine.framework.dataspace.tests.test_dataspace) 41
50 test_get_last_generation_id_not_exist() test_has_config() (in module decisio-
(in module decisio- nengine.framework.dataspace.tests.test_dataspace),
nengine.framework.dataspace.datasources.tests.test_dataspace) 50
test_get_metadata() (in module decisio- test_has_methods_we_expect() (in module decisio-
nengine.framework.dataspace.datasources.tests.test_datasource), 41
nengine.framework.dataspace.tests.test_dataspace) 49
test_get_metadata() (in module decisio- test_Header_constructor() (in module decisio-
nengine.framework.dataspace.tests.test_dataspace) 50 nengine.framework.dataspace.tests.test_datablock),
49
test_get_metadata_not_exist() (in module decisio- test_Header.is_valid() (in module decisio-
nengine.framework.dataspace.datasources.tests.test_datasource), 41 nengine.framework.dataspace.tests.test_datablock),
41 test_get_metadata_not_exist() (in module decisio-
nengine.framework.dataspace.tests.test_dataspace) 49
50 test_get_metadata_not_exist() (in module decisio-
nengine.framework.dataspace.tests.test_dataspace) 80
test_get_taskmanager_exists() (in module decisio- test_index_error() (in module decisio-
nengine.framework.dataspace.datasources.tests.test_dataspace), 41 nengine.framework.logicengine.tests.test_fail_on_error),
41 63
test_get_taskmanager_exists() (in module decisio-
nengine.framework.dataspace.tests.test_dataspace) 50
test_get_taskmanager_not_exists() 41
(in module decisio- test_insert() (in module decisio-
nengine.framework.dataspace.datasources.tests.test_datasource), 50
nengine.framework.dataspace.tests.test_dataspace),
41 50
test_get_taskmanager_not_exists() test_invalid_config() (in module decisio-
nengine.framework.dataspace.datasources.tests.test_datasource),
41 50

```

```

    nengine.framework.config.tests.test_validconfig), 80
26 test_query_tool_help() (in module decisio-
    nengine.framework.engine.tests.test_query_tool_only),
48 test_query_tool_invalid_product()
    (in module decisio-
    nengine.framework.tests.test_query_tool_server),
48 test_query_tool_json() (in module decisio-
    nengine.framework.tests.test_query_tool_server),
49 test_query_tool_since() (in module decisio-
    nengine.framework.tests.test_query_tool_server),
49 test_query_tool_with_no_server()
    (in module decisio-
    nengine.framework.engine.tests.test_query_tool_only),
26 test_query_tool_with_no_server_verbose()
    (in module decisio-
    nengine.framework.engine.tests.test_query_tool_only),
26 test_reap_default_state() (in module decisio-
    nengine.framework.dataspace.tests.test_Reaper),
26 test_reaper_can_reap() (in module decisio-
    nengine.framework.dataspace.tests.test_Reaper),
64 test_reset_connections() (in module decisio-
    nengine.framework.dataspace.datasources.tests.test_datasource_
    41
80 test_restart_channel() (in module decisio-
    nengine.framework.tests.test_restart_channel),
67 test_rule_that_does_not_fire()
    (in module decisio-
    nengine.framework.logicengine.tests.test_cascaded_rules),
68 test_rule_that_does_not_fire()
    (in module decisio-
    nengine.framework.logicengine.tests.test_pandas_fact),
68 test_rule_that_does_not_fire()
    (in module decisio-
    nengine.framework.logicengine.tests.test_rule_with_negated_fact),
64
test_no_such_file() (in module decisio-
    nengine.framework.config.tests.test_validconfig), 26
test_publisher_structure() (in module decisio-
    nengine.framework.modules.tests.test_Publisher), 67
test_query_tool_csv() (in module decisio-
    nengine.framework.tests.test_query_tool_server), 80
test_query_tool_default() (in module decisio-
    nengine.framework.tests.test_query_tool_server), test_rule_that_fires() (in module decisio-
    63
    nengine.framework.logicengine.tests.test_cascaded_rules),
    test_rule_that_fires() (in module decisio-

```



```

        nengine.framework.logicengine.tests.test_pandas_fact),      nengine.framework.logicengine.tests.test_facts),
64                                                                    63
test_rule_that_fires() (in module decisio- test_syntax_error_in_config_names_bad_file()
        nengine.framework.logicengine.tests.test_rule_with_negated_ifact),      module      decisio-
64                                                                    nengine.framework.config.tests.test_config),
test_rule_that_fires() (in module decisio-
        nengine.framework.logicengine.tests.test_simple_configuration),      26
64                                                                    test_transform_structure() (in module decisio-
        nengine.framework.modules.tests.test_Transform),
test_simple_fact() (in module decisio-
        nengine.framework.logicengine.tests.test_facts), test_translate_all() (in module decisio-
63                                                                    nengine.framework.modules.tests.test_translate_product_name),
test_source_fail_can_be_fixed()
        (in module      decisio- test_translate_illegal_characters()
        nengine.framework.dataspace.tests.test_Reaper),      (in module      decisio-
48                                                                    nengine.framework.modules.tests.test_translate_product_name),
test_source_only_channel() (in module decisio-
        nengine.framework.tests.test_error_on_acquire), test_translate_none() (in module decisio-
80                                                                    nengine.framework.modules.tests.test_translate_product_name),
test_source_structure() (in module decisio-
        nengine.framework.modules.tests.test_Source), test_translate_simple() (in module decisio-
67                                                                    nengine.framework.modules.tests.test_translate_product_name),
test_start_delay() (in module decisio-
        nengine.framework.dataspace.tests.test_Reaper), test_translate_with_underscores()
48                                                                    (in module      decisio-
        nengine.framework.modules.tests.test_translate_product_name),
test_start_from_nothing() (in module decisio-
        nengine.framework.tests.test_start_with_no_channels), 68
82                                                                    test_trivial_configuration() (in module decisio-
        nengine.framework.logicengine.tests.test_construction),
test_start_stop() (in module decisio-
        nengine.framework.dataspace.tests.test_Reaper), 63
48                                                                    test_true_fact() (in module      decisio-
        nengine.framework.logicengine.tests.test_fail_on_error),
test_start_stop_stop() (in module decisio-
        nengine.framework.dataspace.tests.test_Reaper), 64
48                                                                    test_true_literal_fact() (in module decisio-
        nengine.framework.logicengine.tests.test_fail_on_error),
test_state_can_be_active() (in module decisio-
        nengine.framework.dataspace.tests.test_Reaper), 64
48                                                                    test_update() (in module      decisio-
        nengine.framework.dataspace.datasources.tests.test_datasource_
test_state_sets_timer_and_uses_it()
        (in module      decisio- 41
        nengine.framework.dataspace.tests.test_Reaper), test_update() (in module      decisio-
48                                                                    nengine.framework.dataspace.tests.test_dataspace),
test_stop_failing_source_proxy()
        (in module      decisio- test_update_bad() (in module      decisio-
        nengine.framework.tests.test_source_proxy),      nengine.framework.dataspace.datasources.tests.test_datasource_
82                                                                    41
test_store_taskmanager() (in module decisio- test_update_bad() (in module      decisio-
        nengine.framework.dataspace.datasources.tests.test_datasource_inapi), nengine.framework.dataspace.tests.test_dataspace),
41                                                                    50
test_store_taskmanager() (in module decisio- test_valid_dir() (in module      decisio-
        nengine.framework.dataspace.tests.test_dataspace),      nengine.framework.config.tests.test_policies),
50                                                                    26
test_supports_config() (in module decisio- test_working_source_proxy() (in module decisio-
        nengine.framework.modules.tests.test_module_decorators), nengine.framework.tests.test_source_proxy), 82
68                                                                    test_wrong_configuration() (in module decisio-
        nengine.framework.logicengine.tests.test_construction),
test_syntax_error() (in module decisio-

```

63
 test_wrong_product_names() (in module decisionengine.framework.modules.tests.test_module_decorators), method), 32
 68
 test_wrong_product_types() (in module decisionengine.framework.modules.tests.test_module_decorators), method), 39
 68
 test_wrong_type() (in module decisionengine.framework.config.tests.test_config), method), 56
 26
 test_wrong_type_config() (in module decisionengine.framework.config.tests.test_validconfig), method), 28
 26
 test_zdumps() (in module decisionengine.framework.dataspace.tests.test_datablock_valid), method), 52
 49
 test_zloads() (in module decisionengine.framework.dataspace.tests.test_datablock_valid), method), 33
 49
 Transform (class in decisionengine.framework.modules.Transform), 70
 transform() (decisionengine.framework.modules.Transform.Transform method), 70
 transform() (decisionengine.framework.tests.TransformNOP.TransformNOP method), 78
 transform() (decisionengine.framework.tests.TransformWithMissingProducesConsumes.TransformWithMissingProducesConsumes method), 78
 TransformNOP (class in decisionengine.framework.tests.TransformNOP), 78
 TransformWithMissingProducesConsumes (class in decisionengine.framework.tests.TransformWithMissingProducesConsumes), 78
 translate() (in module decisionengine.framework.modules.translate_product_name), 71
 translate_all() (in module decisionengine.framework.modules.translate_product_name), 71
 U
 unguarded_access() (decisionengine.framework.engine.Workers.Workers method), 61
 update() (decisionengine.framework.dataspace.datasource.DataSource method), 55
 update() (decisionengine.framework.dataspace.datasources.null.NullDataSource method), 44
 update() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 46
 update() (decisionengine.framework.dataspace.datasources.sqlalchemy.DataSource method), 32
 update() (decisionengine.framework.dataspace.datasources.sqlalchemy.DataSource method), 39
 update() (decisionengine.framework.dataspace.dataspace.DataSpace method), 56
 V
 valid_dir() (in module decisionengine.framework.config.policies), 28
 valid_states (decisionengine.framework.dataspace.datablock.Metadata attribute), 52
 ValidConfig (class in decisionengine.framework.config.ValidConfig), 27
 value (decisionengine.framework.dataspace.datasources.sqlalchemy_ds.db attribute), 33
 verify_products() (in module decisionengine.framework.modules.Module), 68
 W
 wait_for_all() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 74
 wait_for_any() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 74
 wait_for_all() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 61
 wait_for_any() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 72
 wait_while() (decisionengine.framework.engine.Workers.Worker method), 61
 wait_while() (decisionengine.framework.taskmanager.ProcessingState.ProcessingState method), 72
 wait_while() (decisionengine.framework.engine.Workers.Worker method), 61
 wait_while() (decisionengine.framework.taskmanager.ProcessingState.ProcessingState method), 72
 Worker (class in decisionengine.framework.engine.Workers), 61
 Worker (class in decisionengine.framework.taskmanager.TaskManager), 74
 Workers (class in decisionengine.framework.engine.Workers), 61
 Workers.Access (class in decisionengine.framework.engine.Workers), 61
 WorkingSourceProxy (class in decisionengine.framework.tests.WorkingSourceProxy), 78

Z

`zdumps()` (*in module decisionengine.framework.dataspace.datablock*),
[53](#)

`zloads()` (*in module decisionengine.framework.dataspace.datablock*),
[53](#)