Analysis for H1C IDR 2.2 Josh Dillon, 4/5/19 From Commissioning Team List of Bad Antennas RTP Antenna Metrics 4-pol Raw Data zen.{JD}.HH.uvh5 bad_ants/{JD}.txt zen.{JD}.HH.uv.ant_metrics.json Redcal: redcal_run.py Cuts times based on solar altitude and edge channels Finds delays (firstcal) **FirstCal Calibration Solutions Extract Autocorrelations:** - Performs redundant calibration per-time and perzen.{JD}.HH.first.calfits extract_autos.py channel (omnical) Extract autos and write to disk. - Removes antennas with high chi^2 and recalibrates if necessary. **Run FirstCal Metrics:** firstcal_metrics_run.py Assess FirstCal solutions. **Omnical Calibration Solutions Raw 2-pol Autocorrelations Omnical Visibility Solutions** zen.{JD}.HH.autos.uvh5 zen.{JD}.HH.omni_vis.uvh5 zen.{JD}.HH.omni.calfits **FirstCal Metrics** zen. {JD}.HH.first.calfits.firstcal _metrics.hdf5 Abscal: omni_abscal_run.py **Abscal Visibility Model** Use externally calibrated visibilities zen.{JD}.HH.uvRXLS.uvh5 to solve for Omnical degneracies. **Abscal Calibration Solutions** zen.{JD}.HH.abs.calfits Flagging Metadata zen.{JD}.HH.init_xrfi_metrics.h5 zen.{JD}.HH.init_flags.h5 **XRFI** zen.{JD}.HH.final_xrfi_metrics.h5 xrfi_run.py Find and flag RFI based on raw data, Intermediate data products from XRFI Omnical gains and chi^2, Omnical visibility solutions, and Abscal gains and chi^2. Condenses flags to a single waterfall. Legend **Final Flags** zen.{JD}.HH.final_flags.h5 Final set of flags from XRFI **Data with Flagged Absolute External Origin Calibration Solutions** zen.{JD}.HH.flagged_abs.calfits **Visibility Data Product Smoothcal:** smooth_cal_run.py hera_cal process All other absolute calibration Smooth calibration solutions on a solutions for the same day. desired calibration and frequency scale. Also selects a reference antenna. **Calibration Data Product Smoothed Absolute Calibration Solutions** hera_qm process zen.{JD}.HH.smooth_abs.calfits **Metrics Data Product Reflection Fitter:** casa_imaging reflections_fit.py **Noise Estimation:** process **CASA Imaging: Delay Filter:** Use calibrated autocorrelations to noise_from_autos.py delay_filter_run.py sky_image.py model per-antenna cable Use calibrated autocorrelations to Produce 4pol multi-frequency-Remove power inside the foreground reflections that can be multiplied by model per-antenna noise standard **CASA Imaging** synthesis images of each data file. wedge with a wide-band delay CLEAN. the final.calfits deviations on visibilities. **Data Product Analogous Data or** Calibrated, Flagged, and **Calibration Solutions of Calibration from Per-Antenna Noise Standard** 4-pol MFS Images **Deviation from Autocorrelations Just Cable Reflections Delay-Filtered Residual Data** Other Times zen.{JD}.HH.OCRSD.uvh5 zen.{JD}.HH.reflections.calfits zen.{JD}.HH.noise_std.uvh5 zen.{JD}.HH.reflections.npz **LST-Binning Pipeline LST-Binning with Foregrounds LST-Binning Delay-Filtered Data** Istbin_run.py Istbin_run.py All other data (and calibrations) from Combine together data from different days Combine together data from different days a given group of days to LST-bin at the same LSTs using MAD clipping. at the same LSTs using MAD clipping.

Standard Deviation of LST-Binned

Data with Foregrounds

zen.grp{N}.of{M}.STD.{LST in

radians}.HH.OCRSL.uvh5

LST-Binned Data with Foregrounds

zen.grp{N}.of{M}.LST.{LST in

radians}.HH.OCRSL.uvh5

Standard Deviation of LST-Binned,

Delay-Filtered Data

zen.grp{N}.of{M}.STD.{LST in

radians}.HH.OCRSDL.uvh5

LST-Binned, Delay-Filtered Data

zen.grp{N}.of{M}.LST.{LST in

radians}.HH.OCRSDL.uvh5