


TIME WARP - OPTIMISTIC SYNCHRONIZATION ALGORITHM



**GLOBAL VIRTUAL TIME CALCULATION
(GVT) & SAMADI'S ALGORITHM**


**211043-SYEDA RUBAB
211044- EISHA ASHER
211092- TAHA BIN BASHIR**



INTRODUCTION TO TIME WARP ALGORITHM

- What is Time Warp?
 - An optimistic synchronization algorithm used in parallel and distributed discrete-event simulation.
 - Allows out-of-order event execution and resolves inconsistencies via rollback mechanisms.
- Key Features:
 - Event execution optimism: Events are processed immediately without waiting for global time synchronization.
 - Rollback mechanism: Handles incorrect executions caused by events arriving in the past.





CORE COMPONENTS OF TIME WARP

1. Local Virtual Time (LVT):
 - Tracks simulation time at each logical process (LP).
2. Rollback Mechanism:
 - When a late event is received, the LP rolls back to the time of the event.
 - Cancels future events using anti-messages.
3. Global Virtual Time (GVT):
 - The minimum timestamp of all unprocessed and in-transit messages.
 - Ensures no event earlier than GVT can cause a rollback.



GLOBAL VIRTUAL TIME (GVT) CALCULATION



GVT is the minimum of:


- Local Virtual Times (LVT) of all LPs.
- Timestamps of in-transit messages.

Importance of GVT:

- Determines safe points for memory reclamation.
- Prevents further rollbacks beyond this point.

Challenges in GVT Calculation:

- Requires accurate detection of in-transit messages.
- Must account for delays in message propagation.



STEPS FOR GVT CALCULATION



Snapshot Collection:

- Collect LVTs from all LPs.

Account for In-Transit Messages:

- Consider messages in the communication network with timestamps.

Global Minimum:

- Compute the minimum value across LVTs and in-transit messages.

Broadcast GVT:

- Share the computed GVT with all LPs for consistency.



SAMADI'S ALGORITHM

Objective: Efficiently compute GVT in a distributed simulation environment.

Key Idea: Uses a token-passing mechanism to track the minimum LVT and in-transit messages.

Steps in Samadi's Algorithm:

1. Token Initialization:

- A control token is initialized with the maximum time value.

2. Token Passing:

- Each LP updates the token with its LVT and any in-transit message timestamp.

3. Completion:

- Once the token completes a cycle, the GVT is determined.

4. Broadcast:

- The GVT is shared with all LPs.



ADVANTAGES OF SAMADI'S ALGORITHM




- **REDUCES OVERHEAD BY USING A SINGLE TOKEN.**
- **ENSURES ACCURATE GVT COMPUTATION IN DISTRIBUTED ENVIRONMENTS.**
- **HANDLES MESSAGE DELAYS AND NETWORK ASYNCHRONY EFFECTIVELY.**



LIMITATIONS AND TRADE-OFFS

- Potential delays in GVT calculation due to token circulation.
- Requires reliable communication for token passing.



APPLICATIONS OF TIME WARP AND GVT

Parallel Discrete Event Simulation (PDES):

- Simulating large-scale systems like traffic networks, communication systems, etc.

Distributed Simulations:

- Synchronizing state updates across geographically distributed nodes.


Memory Management:

- Safe garbage collection and state restoration.



SUMMARY

- Time Warp allows optimistic event execution with rollback mechanisms.
- GVT ensures consistent state across LPs and is critical for memory management.
- Samadi's Algorithm is an efficient technique for GVT computation in distributed systems.





**THANK
YOU!**