

Configurer le système

Répertoire Home ?

By default, Jenkins stores all of its data in this directory on the file system

Message du système

This message will be displayed at the top of the Jenkins main page. This can be useful for posting notifications to your users

[Plain text] [Prévisualisation](#)

Configuration des projets Maven

MAVEN_OPTS global ?

Local Maven Repository ?

Default ("~/m2/repository", or the value of 'localRepository' in Maven's settings file, if defined) ▾

Nombre d'exécuteurs

2

Libellés

Utilisation ?

Utiliser ce noeud autant que possible ▾

Période d'attente ?

5

Nombre de tentatives de checkout SCM

0

☐ Restreindre le nommage de projet

Jenkins Location

URL de Jenkins ?

http://192.168.60.254:8080/

Adresse email de l'administrateur système ?


Adresse pas encore configurée <nobody@nowhere>

Serve resource files from another domain

Resource Root URL 

Without a resource root URL, resources will be served from the Jenkins URL with Content-Security-Policy set.

Propriétés globales

- ☐ Disable deferred wipeout on this node 
- ☐ Emplacement des outils
- ☐ Variables d'environnement

SonarQube servers

If checked, job administrators will be able to inject a SonarQube server configuration as environment variables in the build.

- ☒ Environment variables Enable injection of SonarQube server configuration as build environment variables

Installations de SonarQube

Liste des installations de SonarQube

Nom 


URL du serveur

Par défaut à http://localhost:9000

Server authentication token

SonarQube authentication token. Mandatory when anonymous access is disabled.

+ Ajouter

Avancé 

Ajouter une installation SonarQube

Pipeline Speed / Durability

Default Speed / Durability Level 

Writes data with every step, using atomic writes for integrity. Provides maximum ability to retain running pipeline data and resume in the event of a Jenkins failure.

Usage Statistics

- ☒ Aidez-nous à améliorer Jenkins en envoyant sous forme anonyme les statistiques d'utilisation et les rapports de crash au projet Jenkins. 

Folder

Health Metrics

List of default health metrics for Folders

Ajouter ▾

Global Build Time Out

☐ Enable Global Time Out

Gradle Enterprise Build Scans

☐ Enable enriched summary ?

Gradle Enterprise integration

☐ Enable auto-injection

Timestamper

System clock time format ?

'HH:mm:ss'

Elapsed time format ?

'HH:mm:ss.S'

☐ Enabled for all Pipeline builds ?

Fingerprints

☐ Disable Fingerprint Cleanup

Administrative monitors configuration

Administrative monitors ▾

Global Build Discarders

≡

Project Build Discarder

×

Build discarders configured for a job are only run after a build finishes. This option runs jobs' configured build discarders periodically, applying configuration changes even when no new builds are run. This option has no effect if there is no build discarder configured for a job.

Ajouter ▾

Global Pipeline Libraries

Sharable libraries available to any Pipeline jobs running on this system. These libraries will be trusted, meaning they run without "sandbox" restrictions and may use @Grab.

Ajouter

JFrog

☐ Use the Credentials Plugin ?

JFrog Platform Instances

List of JFrog platform instances that projects will want to deploy artifacts and build info

JFrog instance details

Instance ID ?

Artifactory Local

JFrog Platform URL ?

http://192.168.60.254:8082

Advanced Configuration ▾

 Edited

Default Deployer Credentials

Username ?

admin

Password ?



Concealed

Change Password

Test Connection

☐ Use Different Resolver Credentials

Add JFrog Platform Instance

JFrog Pipelines server

Report job results to JFrog Pipelines

Integration URL ?

Avancé ▾

 Edited

Credentials

Credentials

- aucun -

+ Ajouter

Test Connection

Build-timeout Plugin > BuildStep Action

☐ Enable BuildStep Action ?

Git plugin

Global Config user.name Value ?

Global Config user.email Value ?

☐ Create new accounts based on author/committer's email ?

☐ Use existing account with same email if found ?

☐ Show the entire commit summary in changes ?

☐ Hide credential usage in job output ?

☐ Disable performance enhancements ?

☐ Preserve second fetch during checkout ?

☐ Add git tag action to jobs ?

Shell

Exécutable pour le Shell ?

Extended E-mail Notification

SMTP server

SMTP Port

Avancé ▾

Default user e-mail suffix ?

Avancé ▾

 Edited

Default Content Type ?

List ID ?

☐ Add 'Precedence: bulk' E-mail Header ?

Default Recipients ?

Reply To List ?

Emergency reroute ?

Allowed Domains ?

Excluded Recipients ?

Default Subject ?

\$PROJECT_NAME - Build # \$BUILD_NUMBER - \$BUILD_STATUS!

Maximum Attachment Size ?

Default Content ?

\$PROJECT_NAME - Build # \$BUILD_NUMBER - \$BUILD_STATUS:
Check console output at \$BUILD_URL to view the results.

Default Pre-send Script ?

Default Post-send Script ?

Additional groovy classpath ?

Ajouter

- ☐ Enable Debug Mode ?
- ☐ Require Administrator for Template Testing ?
- ☐ Enable watching for jobs ?
- ☐ Allow sending to unregistered users ?

Default Triggers

Content Token Reference ?

Notification par email

Serveur SMTP

Suffixe par défaut des emails des utilisateurs ?

Avancé ▾


 Edited

☐ Tester la configuration en envoyant un e-mail de test

Publish over SSH

Jenkins SSH Key ?

Passphrase ?

 Concealed

Change Password

Path to key ?

Key ?

☐ Disable exec ?

SSH Servers

SSH Server

Name ?

Staging Server

Hostname ?

192.168.60.200

Username ?

vagrant

Remote Directory ?

Avancé ▾

Test Configuration

Ajouter

Avancé ▾

Enregistrer

Appliquer

