

Home Search Collections Journals About Contact us My IOPscience

Memristor-based neural networks

This content has been downloaded from IOPscience. Please scroll down to see the full text.

2013 J. Phys. D: Appl. Phys. 46 093001

(http://iopscience.iop.org/0022-3727/46/9/093001)

View the table of contents for this issue, or go to the journal homepage for more

Download details:

IP Address: 203.112.220.2

This content was downloaded on 16/05/2015 at 07:27

Please note that terms and conditions apply.

J. Phys. D: Appl. Phys. 46 (2013) 093001 (12pp)

TOPICAL REVIEW

Memristor-based neural networks

Andy Thomas

Thin films and Physics of Nanostructures, Bielefeld University, Bielefeld, Germany Institut für angewandte Physik, Hamburg University, Hamburg, Germany

E-mail: andy.thomas@uni-bielefeld.de

Received 29 August 2012, in final form 30 November 2012 Published 5 February 2013
Online at stacks.iop.org/JPhysD/46/093001

Abstract

The synapse is a crucial element in biological neural networks, but a simple electronic equivalent has been absent. This complicates the development of hardware that imitates biological architectures in the nervous system. Now, the recent progress in the experimental realization of memristive devices has renewed interest in artificial neural networks. The resistance of a memristive system depends on its past states and exactly this functionality can be used to mimic the synaptic connections in a (human) brain. After a short introduction to memristors, we present and explain the relevant mechanisms in a biological neural network, such as long-term potentiation and spike time-dependent plasticity, and determine the minimal requirements for an artificial neural network. We review the implementations of these processes using basic electric circuits and more complex mechanisms that either imitate biological systems or could act as a model system for them.

(Some figures may appear in colour only in the online journal)

1. Introduction

If we follow Chua's original line of argumentation in his seminal paper in which he introduced the memristor, we find the following concept [1]. There are four fundamental circuit variables, namely, the charge (q), voltage (v), current (i) and flux linkage (φ) . Consequently, there are six two-variable combinations of those four elements. Two of these combinations are defined by $q(t) = \int_{-\infty}^{t} \mathbf{i}(\tau) \, \mathrm{d}\tau$ and $\varphi(t) = \int_{-\infty}^{t} v(\tau) \, \mathrm{d}\tau$.

Three more relationships are given by the resistor (combining i and v), capacitor (q, v) and inductor (φ, i) (figure 1). Consequently, Chua wrote [1] From the logical as well as axiomatic points of view, it is necessary for the sake of completeness to postulate the existence of a fourth basic two-terminal circuit element which is characterized by a φ -q curve [footnote]. This element will henceforth be called the memristor because, as will be shown later, it behaves somewhat like a nonlinear resistor with memory.

Now, we will consider a general definition of discrete memory elements that have time-dependent and non-linear responses. We follow the definitions provided by Di Ventra $et\ al\ [2,3]$. Let u(t) and y(t) be the input and output variables of a system, respectively. u and y are the complementary

1

constitutive circuit variables, such as the current, charge, voltage and flux. Subsequently, an *n*th-order, *u*-controlled memory element can be defined by

$$y(t) = g(x, u, t)u(t)$$

$$\frac{d}{dt}x = f(x, u, t), \tag{1}$$

where x is an n-dimensional vector of the internal state variables, g is the generalized response, and f is a continuous n-dimensional vector function. For a memristive system, equation (1) becomes

$$V_M(t) = R(x, I, t)I(t)$$

$$\frac{\mathrm{d}}{\mathrm{d}t}x = f(x, I, t) \tag{2}$$

where V_M and I indicate the voltage across and current through the device, respectively, and R denotes the memristance [4]. Again, from a symmetry point of view, we can introduce a *meminductive* and a *memcapacitive* system in a similar manner using flux-current and charge–voltage pairs, respectively [2, 3]. However, meminductive and memcapacitive systems are not further discussed in this paper. For a good introduction and




Figure 1. Six 2-variable relationships are possible with four elements (q, i, v, φ) . Two time integrals and the well-known resistor (with resistance R), capacitor (C) and inductor (L) account for five of these relationships. The missing connection was proposed by Chua and named *memristor*.




Figure 2. An idealized *iv*-curve of a memristive system subjected to a periodic voltage $V = V_0 \sin(\omega t)$. The result is a characteristic, pinched hysteresis curve.

an even further generalization of equation (1), please refer to Pershin and Di Ventra [5]. Strictly speaking, a *memristor* is an ideal *memristive system* and we tried to distinguish between the two in this paper.

In the late 1990s, researchers from Hewlett-Packard Laboratories and the University of California (Los Angeles) were studying *electronically configurable molecular-based logic gates* [6]. The concept was further refined by Snider *et al* (HP Labs) when they presented a CMOS-like logic in defective, nanoscale crossbars in 2004 [7], *computing with hysteretic resistor crossbars* in 2005 [8] and *self-organized computation with unreliable, memristive* [sic] *nanodevices* in 2007 [9].

A basic form of a memristive device consists of a junction that can be switched from a low- to a high-resistive state and vice versa. This behaviour can be accomplished with a simple switch. The switch closes above a threshold voltage, opens below a second threshold voltage, and the device breaks well beyond either of the threshold voltages. The nano-switches can be deposited by, e.g., electron-beam evaporation or sputtering and more than 10¹⁰ switching cycles were shown for some of the layer stacks [10, 11]. A memristor usually exhibits a characteristic, pinched hysteresis loop which is illustrated in figure 2.

In 2008, researchers from HP-labs combined the interest in the younger field of nano-ionics [12, 13] with Chua's concept. They reused the term memristor (although for a memristive




Figure 3. Total change in the resistance of a memristive system depending on the flux. The resistance continuously decreases with increasing flux.

system), presented an experimental realization, and created a new research field that resulted in more than 120 publications about memristors and memristive systems by 2011 [14].

A straightforward way to consider a memristor is as a potentiometer, i.e. an adjustable resistor. Every time a certain amount of flux (V s) flows in one direction through the device, the resistance increases. If the current flows in the other direction, the resistance decreases. In an ideal memristor, a pulse that is half the voltage and twice the duration will result in the same change in resistance, because the resistance depends on the flux. This effect is evident in figure 3, which shows one of our memristive tunnel junctions as an example (see [15]). The curvature of the plot is an indication that it is helpful to distinguish between memristive systems and (ideal) memristors.

The growing interest in memristors has resulted in the development of several concepts for the use of these devices, such as utilizing memristive systems for (reconfigurable) logic circuits [16–20], or new computer memory concepts [21–23]. The simulation of memristive behaviour in electric circuits is also possible [24–28].

However, one of the most promising applications for memristors is the emulation of synaptic behaviour. Here, we will investigate memristor-based neural networks with a focus on systems that are inspired by biological processes. For this investigation, we first introduce mechanisms for the biological neural networks, e.g., in the brain. The presented processes have been identified over the past decades to be crucial for learning and memory and were initiated by Hebbs influential work, *The Organization of Behavior* [29]. These mechanisms will be presented in the following section. Then, we will review experiments, and mostly disregard simulations [30–33] that use memristive systems to realize the same processes.

2. Biological mechanisms

In this section, we will introduce the basic components of biological neural networks and their primary features. We begin with the schematic of two interconnected neurons, which is shown in figure 4.

A neuron interacts with a second neuron through an axon terminal, which is connected via synapses to dendrites on the




Figure 4. Schematic representation of two interconnected neurons. The contact areas where the information is transmitted are called synapses. A signal from the presynaptic cell is transmitted through the synapses to the postsynaptic cell.

second neuron. The information is transported by changes in membrane potentials, which can be generated by the influx of positive ions, such as Na⁺. The information flow transported by the membrane potentials is directed from the presynaptic to the postsynaptic cell. A central concept in biology is the plasticity of synaptic junctions. Eccles and McIntyre wrote [34] Plasticity in the central nervous system, that is, the ability of individual synaptic junctions to respond to use and disuse by appropriate changes in transmissive efficacy, is frequently postulated or implied in the discussions on the mechanisms underlying the phenomena of learning and memory [35, 36]. Therefore, we are interested in mimicking this plasticity with an artificial device.

However, achieving a one-to-one relationship between an artificial device and natural neuron connections is a very Hyman and Nestler reported [37] that challenging task. every neuron is usually connected via thousand, sometimes more than several thousand, synapses with other neurons. [...] neurons may release more than one neurotransmitter at any given synapse, adding yet another layer of complexity. Fortunately, exactly imitating nature (i.e. connecting a neuron to a second one via many synapses) is not necessary to mimic the functionality of the neural network. For the moment, we assume a net transmissive efficacy between two neurons that is mediated by the sum of the net synapses and call this efficacy the (global) plasticity of the connection. This process is illustrated in figure 5, which is a further simplification of the two neurons depicted in figure 4. For more information on the interconnection of neurons please see, e.g., Deuchars or Daumas et al [38, 39]. The neurons can interact via excitatory and inhibitory synapses. Curtis and Eccles described how the excitatory and inhibitory synaptic potentials can be integrated within a neuron [40]. This process is further explained in the integrate-and-fire section, in short, signals through excitatory and inhibitory synapses increase and decrease the possibility of the neuron to fire, respectively.

There are several different properties of a neuron that can be emulated by artificial devices, and some of these properties are crucial in an artificial neural network. We will discuss these mechanisms in the following few paragraphs.




Figure 5. Further simplified, schematic representation of two interconnected neurons. The connection between the neurons is mediated through a single synapse with a net transmissive efficacy that represents the net connection strength of the several synapses (three in the case of figure 4) in a biological neuron connection.




Figure 6. An example of LTP. A large stimulus that was delivered after one hour triggered a long-lasting response. Adapted by permission from [43], copyright (1993).

2.1. Long-term potentiation

An important mechanism in biological neural networks is long-term potentiation (LTP) that has [since] been found in all excitatory pathways in the hippocampus, as well as in several other regions of the brain, and there is growing evidence that it underlies at least certain forms of memory [41,42], as indicated by Bliss and Collingridge [43]. LTP designates a long-lasting change in the plasticity of a connection and is defined by the same authors in the following way [43]: Brief trains of high-frequency stimulation to monosynaptic excitatory pathways in the hippocampus cause an abrupt and sustained increase in the efficiency of synaptic transmission. This effect, first described in detail 1973 [44,45], is called long-term potentiation (LTP). An example is shown in figure 6.

Bliss and Collingridge also reported that *LTP* is characterized by three basic properties: cooperativity, associativity and input-specificity [43]. We will discuss these three characteristics in the following paragraphs.

Cooperativity means that there is an intensity threshold to induce LTP, and this threshold is above the stimulus threshold that leads to a minimal synaptic response [46]. This process is illustrated in figure 7. A small-intensity stimulus was used in figure 7(a). While there is a reaction, the potentiation disappeared approximately 5 min after application of the stimulus. This behaviour changes if a stimulus of higher




Figure 7. A low- (a) and high-intensity stimulus (b) was applied to a fibre. The low-intensity stimulus produced a reaction, but it was short lasting. The high-intensity stimulation lasted for a longer time. Reprinted from [46], with permission from Elsevier.




Figure 8. The application of the weak stimulus W or a strong stimulus S does not lead to a potentiation. If W and S are applied at the same time, LTP can be observed. Reprinted from [48], Copyright (1983).

intensity is used (figure 7(b)). The potentiation lasts a longer time, although the initial potentiation is of comparable size. The stimulation in a biological system is usually a tetanus, i.e. rapidly repeated impulses. Therefore, the *threshold for inducing LTP is a complex [complicated] function of the intensity and pattern of the tetanic stimulation* ([43]). This concept is discussed in more detail by [47].

Associativity indicates that many weak tetani in separate but convergent inputs still trigger LTP [49]. Figure 8 depicts the potentiation resulting from the application of two stimuli at the same time. First, the weak stimulus W is used, and no LTP can be observed. The same is true if another strong, solitary stimulus S is applied. However, a combined W plus S tetanus results in a LTP, which is visible in figure 8.

Finally, *input-specificity* means that only the plasticity of the active connection is potentiated [50, 51]. This was

Table 1. Population spike amplitude of tetanized and control pathways before and after stimulation (N = 17). Adapted by permission from [50], copyright (1977).

Post tetanus (min)	Pre	5	10	15
Tetanised pathway (%)	100	390	380	332
Control pathway (%)	100	74	67	73




Figure 9. LTD before and after stimulation. The initial synaptic strength was set to 1. Reprinted from [52], Copyright (1996), with permission from Elsevier.

investigated using a tetanized pathway and a control path in 17 matched-pair experiments by Lynch *et al* [50]. The result is shown in table 1. The tetanized path changed its amplitude by more than a factor of three, while the control pathway remained approximately constant.

2.2. Long-term depression and retention

We have to distinguish two different types of processes to investigate the term long-term depression (LTD) and compare it with LTP. The first process is the antagonist of LTP, which is consequently labelled LTD. The similarity of LTD to LTP is apparent in figure 9 where the current traces were recorded before and after the stimulus. Although the synaptic strength initially remains constant, the stimulus weakens the connection. Afterwards, the synaptic strength recovers over the course of several minutes, but it remains less than its initial value. This result is indeed the analogue of LTP with an opposite sign of the change in connection strength.

The second process is more involved and could possibly be described by the depotentiation (reversal) of the LTP at the single-neuron level. However, beginning with a top-bottom approach may be instructive. Therefore, it appears natural to connect the potentiation of the various synaptic inputs with *learning* and, consequently, the depotentiation with *forgetting*. This process occurs on a more extended timescale and is of great interest to psychological researchers. In their review, Rubin and Wenzel collected one hundred years data regarding forgetting. They provided a quantitative description of retention from 210 published data sets and plotted the probability of correct recalls versus time [53]. This process was performed for short-term (20 s) and long-term (50 years) memory. The typical slope of the retention data is shown in figure 10.

Using these data, we could attribute forgetting to a slow change in the synaptic strength back to its initial value with




Figure 10. Typical retention data from idealized long- and short-term memory experiments.

time, which may best be described as relaxation. However, this model is very simple and does not reflect the results of experiments with, e.g., rats. In these investigations, LTP was depotentiated after the rats were exposed to novel environments [54, 55]. Furthermore, Manahan-Vaughan and Braunewell showed rats a holeboard, i.e. a stimulus-rich environment, and reported [56] The observation that LTD facilitation occurred only during the initial exposure to the holeboard, whereas reexposure had no facilitatory effect on LTD, supports the intriguing possibility that exploratory learning may be associated with LTD expression. Finally, Ge et al reported that hippocampal long-term depression is required for the consolidation of spatial memory [57]. The LTP-blocking GluN2A antagonist had no effect on spatial memory consolidation, whereas two LTD-inhibiting agents disrupted the consolidation.

However, these processes are very difficult to break down to the single-neuron level. Nevertheless, Chang *et al* compared memristor retention loss with the memory loss of a human [58]. They demonstrated that the relaxation of the resistance value could be used to mimic short-term to long-term memory transitions in a biological system. In the following paragraphs, LTD will always be used as the analogue of LTP, with an opposite sign of the change in connection strength.

2.3. Spike timing-dependent plasticity

We have observed that the synaptic connection strength can be modified by LTP and LTD. However, we have to determine the criteria for when to apply the former or the latter to an existing neural connection. These criteria are essential characteristics of a biological neural network. In this context, Bi and Poo wrote [59]: The effects of precise timing of spikes in the presynaptic and postsynaptic neurons may be used in neural networks to decipher information encoded in spike timing [60–62] and to store information relating to the temporal order of various synaptic inputs received by a neuron during learning and memory [63, 64].




Figure 11. (a) A neuron is connected to three preceding neurons 1,2 and 3, and the corresponding connections strengths are α , β and γ , respectively. (b) Spiking timing-dependent induction of synaptic potentiation and depression. A negative delay time leads to depression and a positive time difference to potentiation. Adapted by permission from [65], copyright (2007).

The mechanism that controls the plasticity of a connection is called *spike timing-dependent plasticity* or short STDP. This mechanism is a sophisticated process that can be understood as a causality detector. The basic mechanism is shown in figure 11(a). We assume that a stimulus reaches the neuron through input 1, which is connected with a synaptic strength of α . If that stimulus triggers an output spike, the output spike has a positive time delay. In other words, the output pulse occurs after the input pulse, and the positive delay times increase the synaptic connection strength. If the output pulse is caused by a stimulus of input 2 or 3, it may occur before the input 1 stimulus reaches the neuron. Then, there is no causality between input 1 and the output pulse. Consequently, the connection strength α is weakened in cases of negative delay times. However, if the time delay is very large, we do not know the causality between the previous pulses through input 1 and the outgoing pulse.

This causality detector is observed in biological neurons and is depicted in figure 11(b); negative time delays of up to -25 ms lead to LTD, positive delays of up to 25 ms give rise to LTP, and long delays cause no change in the synaptic connection strength [59].

2.4. Integrate-and-fire

The preceding paragraphs described the change in the synaptic efficacy and its dependence on several parameters. However, the biological neural network has the ability to transport information by initiating spikes, i.e. short pulses of high voltage (figure 4). This process was previously investigated by Lapicque over 100 years ago [66, 67]. This process was originally known as *Lapicque's model* or the *voltage threshold* model, and it was further refined to the model known today as




Figure 12. Integrate-and-fire circuits: the perfect integrate-and-fire model consists of a capacitor, threshold detector and switch (without resistor). Once the voltage reaches a threshold, the spike is fired and the switch is closed to shunt the capacitor. In the leaky version, a resistor is added that slowly drains the capacitor with time. This corresponds to leakage current through a membrane in a living cell.

integrate-and-fire [68–71]. The rather simple model captures two of the most important aspects of neuronal excitability; specifically, the neuron integrates the incoming signals and generates the spikes once a certain threshold is exceeded (figure 12).

This behaviour is often explained using two simple electric circuits [72]. The *perfect integrate-and-fire* circuit consists of a capacitor, threshold detector and switch. Once a spike is fired, the switch closes and shunts the capacitor. An additional resistor is included in the *leaky integrate-and-fire* circuit. The resistor slowly drains the capacitor and corresponds to leakage currents in the membrane. However, the integrate-and-fire functionality of a neural network is considerably simpler to implement than the synaptic efficacy. For example, *oversampled Delta-Sigma modulators*, which are 1-bit analogue- digital converters, can mimic the integrate-and-fire behaviour [73, 74]. Therefore, the following paragraphs primarily describe the use of memristive systems as synapses because the integrate-and-fire functionality can be achieved using conventional CMOS-technology.

2.5. Minimal requirements

We can summarize the primary requirements for a bio-inspired neural network as follows.

- (i) Devices that act as neurons and devices that behave like synapses are needed, and the neurons are interconnected via the synapses.
- (ii) The neurons integrate inhibitory and excitatory incoming signals and fire once a threshold is exceeded.
- (iii) The synapses exhibit LTP (cooperative, associative, and input-specific), LTD, and STDP.

3. Implementations using memristive systems

The question may be asked as to why we want to construct *neuromorphic* systems that emulate the presented biological mechanisms. Carver Mead pioneered a considerable amount




Figure 13. Schematic symbols for synapses and neurons as used in the following paragraphs.

of the research on this topic and explained the reasoning in the following way [75]: For many problems, particularly those in which the input data are ill-conditioned and the computation can be specified in a relative manner, biological solutions are many orders of magnitude more effective than those we have been able to implement using digital methods. [...] Large-scale adaptive analog systems are more robust to component degradation and failure than are more conventional systems, and they use far less power. The need for less power is particularly obvious if we compare the performance of the brain of even an invertebrate with a computer CPU and contrast the power consumption. However, there are some tasks that are difficult for a human and easy for a computer, such as multiplying two long numbers, and other problems that a human can easily solve but computers fail to solve.

In 2008, the use of memristors to mimic biological mechanisms, such as STDP, was already hypothesized [76]. Snider implemented the spike time dependence using memristive nanodevices as *synapses* and conventional CMOS technology as *neurons*. He also suggested two electronic symbols for neurons and synapses [76] that have been adapted by some groups as well as in this paper; the symbols are depicted in figure 13. Furthermore, Snider indicated that we should note that STDP alone might not be sufficient to implement stable learning; more complex synaptic dynamics and additional state variables may be required and refers to work by Carpenter et al [77] as well as Fusi and Abbott [78].

Although Snider suggested a new paradigm that uses large-scale adaptive analogue systems, the approach still uses a global clock signal. In 2010, Pershin and Di Ventra described a small system composed of three neurons and two synapses that is fully asynchronous [79, 80]. The memristive behaviour was emulated by a microcontroller combined with other common electronic components. They demonstrated how Ivan Pavlov's famous experiment [81] can be imitated with the basic circuit depicted in figure 14 [79].

Initially, the output signal (salivation) is recorded in dependence on the *sight of food* or a *bell sound*. Only the sight of food (input signal 1) leads to salivation (neuron 3 output); the bell (input signal 2) is not associated with food. There is a subsequent learning period where the input 1 and input 2 signals are applied simultaneously. Afterwards, both individual input signals induce salivation. The elegant experiment demonstrates how *an important function of the brain, namely associative memory* [79], can be constructed with a circuit, as shown in figure 14.

A similar simulation was conducted by Cantley *et al* using SPICE (UC Berkeley, CA, USA) and MATLAB (Natick, MA, USA), and they noted *Also*, *it should be pointed out that the association as presented* (*in figure 4*) *can be unlearned. This*




Figure 14. Basic circuit consisting of three neurons and two synapses as suggested by Pershin and Di Ventra representing Pavlov's dog. The output signal (salivation) depends on the input signals (sight of food and bell sound), as well as the synaptic efficacy.

will happen when the food is continuously presented without the bell [82].

3.1. STDP, LTP and LTD

Afifi et al revisited STDP in neuromorphic networks and proposed an asynchronous implementation [83]. This asynchronous approach may better represent biological neural networks. These researchers used specifically shaped spikes and back-propagation to adapt this approach to the CMOL platform [84]. Voltage-controlled memristive nanodevices were utilized as synapses, the memristive conductance was used as the synaptic efficacy and the CMOS-based platform used conventional integrate-and-fire neurons [85]. They could demonstrate STDP very similar to the biological neurons in figure 11 in their devices. Afifi et al concluded that the special shaped spike has a vital role in the proposed learning method, and simulation results show that even non-ideal shapes don't destroy the general trend of STDP curve for LTP and LTD. This would help us to simplify the neuron circuit design [83].

Jo et al proposed another neuromorphic system that utilizes CMOS neurons and nanoscale memristive synapses [86]. Their design uses synchronous communication and, therefore, a clock. First, we will discuss the LTP and LTD of the memristive systems. Jo et al used positive 3.2 V pulses with a length of 300 μ s to induce LTP. They exposed a system to 100 subsequent pulses and measured the current through the device after every pulse at a voltage of 1 V. After 100 positive pulses, they treated the device with -2.8 V pulses of equal length, which gives rise to LTD. The current constantly decreases with every pulse, and it eventually reaches its initial value. The combination of LTP and LTD in a spike timing-dependent circuit leads to STDP very similar to the biological STDP in figure 11.

A comparable experiment was conducted by Chang *et al* [87]. These researchers observed LTD and LTP in their devices and simulated the behaviour with the SPICE software package. In another layered system, Choi *et al* experimentally verified the occurrence of LTD, LTP and STDP. These nanocrossbar designs usually consist of metal–insulator–metal (MIM) structures with rather thick (\gtrsim 10 nm) oxide layers. The layer stack was Pd/WO₃/W in the former and Ti/Pt/Cu₂O/W in the latter case. However, the crossbar devices are very similar




Figure 15. Long-term and short-term depression in memristive, magnetic tunnel junctions. The stimulus is delivered after 4 min. The behaviour is equivalent to the biological systems shown in figure 6 (LTP) and figure 9 (LTD) on a different timescale. Stronger or subsequent stimuli can induce up to 6% resistance change.

to tunnel junctions. Tunnel junctions are also MIM devices, but the insulator is thinner (\sim 1–2 nm) allowing the electrons to tunnel from one metal electrode to the other side.

Consequently, we observed STDP in memristive tunnel junctions [15]. LTP and LTD was present in our devices depending on the bias voltage applied to the junctions; this is shown in figure 15. Thus, we also observed STDP, as illustrated in figure 16. Again, this figure is very similar to figure 11, but the time scale is seconds rather than milliseconds. In addition to the observed STDP, we suggested another mechanism that is present in magnetic tunnel junctions for use in artificial neural networks. Magnetic tunnel junctions with very thin (0.7 nm) magnesia tunnel barriers can exhibit current-induced magnetic switching, which is sometimes called spin transfer torque switching [89–91]. The torque carried by the tunnelling electrons switches the counter electrode at high current densities $(10^5-10^6 \,\mathrm{A\,cm^{-2}})$ [91]. Sometimes, the device jumps back and forth between its magnetic configurations, i.e. parallel and anti-parallel alignment of the electrodes. This behaviour is called back-hopping [92, 93] and resembles the behaviour of a spiking neuron [88].

In our earlier work [94,95], we demonstrated that tunnel junctions are an alternative system to nanowire crossbars for observing memristive behaviour. Tunnel junctions are well understood because they have been used in Josephson junctions [96], for spin-polarized tunnelling in superconductors [97] and in magnetic tunnel junctions [98] over the past five decades. These junctions can be reproducibly prepared on the 300 mm wafer scale [99] for use as, e.g. magnetic random access memory [100]. However, crossbar and memristive tunnel junction designs may require lower device-to-device variability to be used as synaptic weights in commercial products with hundreds of thousands of synapses [101].

Nevertheless, the primary advantages of neuromorphic, analogue designs are their robustness to component degradation and moderate variability [75]. For a general




Figure 16. (a) STDP in our memristive, magnetic tunnel junctions. (b) A spiking neuron emulated by back-hopping in tunnel junctions that exhibit current-induced magnetic switching. Spiking neuron inset from Gray *et al* [88], reprinted with permission from AAAS.


introduction to the Synapse project, which aims to develop a neuromorphic computer, please see *From Synapses to Circuitry: Using Memristive Memory to Explore the Electronic Brain* [102]. Erokhin and Fontana discuss the use of organic memristors for biologically inspired information processing [103, 104]. Furthermore, please see the paper by Pershin and Di Ventra for another perspective on memristors and memristor-based learning [105]. For a more computer science view on learning in neural networks, Carpenter provides a good review [106], whereas Snider describes instar/outstar learning with memristive devices in particular [107], and Itoh and Chua discuss *logical operations, image processing operations and complex behaviors* [108].

3.2. Slime molds and mazes

We will now discuss more complex mechanisms that are not necessarily based on LTP, LTD and STDP. We will begin with a discussion on maze-solving techniques. Pershin and Di Ventra provide a nice introduction to mazes as follows [109]: Mazes are a class of graphical puzzles in which, given an entrance point, one has to find the exit via an intricate succession of paths, with the majority leading to a dead end, and only one, or a few, correctly solving the puzzle.

The maze in figure 17 can be solved by an organism as primitive as a *Physarum polycephalum*. To solve the maze, two food sources are placed at the entry and exit points. Then, Nakagaki *et al* observed that to *maximize its* foraging efficiency, and therefore its chances of survival, the plasmodium changes its shape in the maze to form one thick tube covering the shortest distance between the food sources. This remarkable process of cellular computation implies that cellular materials can show a primitive intelligence [111–114].

The learning behaviour of the unicellular organism *Physarum polycephalum* inspired the memristor-based solutions developed by Pershin *et al.* In 2009, they presented a model using an LC oscillator and a memristor, which are both






Figure 17. (a) A maze in two dimensions with the *Physarum* polycephalum in yellow. The blue lines indicate the possible solutions $\alpha 1$ (41 mm); $\alpha 2$ (33 mm); $\beta 1$ (44 mm); $\beta 2$ (45 mm); all ± 1 mm. (b) After food sources (agar blocks, AG) were placed at the start and end points, the organism chose the shortest path after 8 h. Reprinted by permission from [110], copyright 2000.

simple, passive elements, that demonstrated pattern recognition and event prediction [115]. They reported on how the circuit can learn the period of temperature shocks. Furthermore, the circuit was able to predict when subsequent shocks were due. They identified several parameters in the amoeba that are crucial for the learning ability of the organism and established corresponding parameters in the electronic circuit. For example, the information-containing parameters correspond to the veins, and low-viscosity channels in the amoeba correspond to the resistance of the memristor in the circuit. They concluded [115] that this model may be extended to multiple learning elements and may thus find application in neural networks and guide us in understanding the origins of primitive intelligence and adaptive behaviour.

In 2011, Pershin et al returned to the original problem of solving a maze [109]. The maze can be encoded using a periodic array of memristors. The memristors are connected in an alternating head-to-head and tail-to-tail checkerboard pattern. The state of the switches between the crossing points corresponds to the topology of the maze. The maze can be solved by the simple application of a voltage across the entry and exit points. The memristors subsequently change their resistance and not only find a possible solution but also find all of the solutions in multi-path mazes and grade them according to their length. The resistance value of the memristor correlates with the length of the path, where low and high resistances indicate short and long paths, respectively. The advantage of this solution is the requirement of only one computational step; the timescale is given by the timescale of the resistance change in the memristors. Therefore, this solution is a good example of the parallel execution in this type of analogue computer; there is no internal clock. However, the read-out of the solution, as proposed by Pershin and Di Ventra, is slow; all switches are turned to the off state, and a low voltage across a single memristor determines its resistance. This process is repeated for all of the memristors, and the resistances are subsequently mapped to read out the computed solution.

3.3. Giant squid axons

In 1963, the Nobel Prize in Physiology and Medicine was awarded to Sir John Carew Eccles, Alan Lloyd Hodgkin




Figure 18. (a) Electrical circuit (Hodgkin–Huxley model) representing the giant squid axon. Two time- and voltage-dependent channels model the sodium and potassium conductances, and the third channel represents the leak conductance. The membrane capacitance requires C_m . (b) Axon model based on the electrical circuit. Hodgkin–Huxley cells are coupled by dissipative connections.

and Andrew Fielding Huxley for their discoveries concerning the ionic mechanisms involved in excitation and inhibition in the peripheral and central portions of the nerve cell membrane [116]. Hodgkin and Huxley selected a squid for their investigations and developed an electrical circuit model of the axon membrane, which is currently referred to as the Hodgkin–Huxley equations [117]. The squid was selected because of the size of its axon, which is up to 1 mm in diameter [118]. An axon conducts the electrical impulses of a cell, e.g., towards another cell. The size of the squid's axon allows an easy installation of electrodes for measuring voltages. The squid uses this particular axon to quickly expel water initiating short, but fast movements.

The Hodgkin-Huxley electrical circuit is shown in figure 18, where three different currents are displayed: the sodium ion current (I_{Na}) , the potassium ion current (I_K) , the leakage current (I_1) , adding up to the axon membrane current (I) [117]. The same process can be performed for the corresponding voltages and resistances. Hodgkin and Huxley described the large axon as chains of *Hodgkin–Huxley*cells, which are paired by diffusive/dissipative couplings. In certain approximations, this pairing can be described based on standard diffusion mechanisms [119]. The values of the circuit elements, e.g. the voltages, have to be determined experimentally. The resistances $R_{\rm K}$ and $R_{\rm Na}$ are time-In this context, Chua wrote [120] varying resistances. However, the terms 'time-varying resistance' and 'timevarying conductance' chosen by Hodgkin and Huxley are unconventional in the sense that R_K and R_{Na} in the HH Circuit model cannot be prescribed as a function of time, as is generally assumed to be the case in basic circuit theory [121, 122]. There are also additional inconsistencies with the original circuit chosen by Hodgkin and Huxley. Mauro pointed out the following [123]. It was discussed by Cole [124] in 1941 in connection with the interesting discovery in 1940 by Cole and Baker [125] that under certain conditions the squid axon displayed positive reactance in AC bridge measurements. However, in 1972, Cole himself wrote [126] The suggestion of an inductive reactance anywhere in the system was shocking to the point of being unbelievable.




Figure 19. Alternative electrical circuit model for the giant squid axon as suggested by Chua. The time-variable resistors are replaced by first- and second-order memristors for the potassium and sodium channels, respectively.

Recently, Chua took all of these points into consideration and suggested a new electrical circuit to replace the original circuit developed by Hudgkin and Huxley [4, 120, 127], this circuit is shown in figure 19. The two time-variable resistors are replaced by a first-order memristor for the potassium channel and a second-order memristor for the sodium channel. This result reconciles all of the anomalous behaviours in the Hodgkin–Huxley model, such as the absence of rectifiers and large inductances in the brain and the lack of matching magnetic fields.

4. Conclusions

In this paper, we aimed not only to review some of the research in the field of memristor-based neural networks but also to demonstrate the excitement and fast pace that have motivated this field in the past few years. The human brain and associated mechanisms, such as learning and forgetting, are naturally fascinating, and neuromorphic computers that mimic these mechanisms are interesting for technological applications and fundamental science. Although conventional CMOS technology is capable of emulating the integrate-andfire operation of a neuron, the functionality of a synapse is more difficult to mimic in a simple electrical circuit. However, a basic, passive, two-terminal device called a memristor can easily realise synaptic behaviour. On the one hand, this process enables the development of adaptive, analogue computer systems, which are more robust and consume less power than their conventional counterparts. On the other hand, this approach permits the use of basic electrical circuits as a model for biological systems, such as the presented Hodgkin-Huxley model.

Acknowledgments

The authors would like to thank Barbara and Christian Kaltschmidt for many helpful discussions about memristors and its relation to biological systems. They are grateful to Günter Reiss and Andreas Hütten for their continuous support of their work. Also, they would like to thank Patryk Krzysteczko, Jana Münchenberger, Stefan Niehörster, Marius Schirmer and Olga Simon. This work was funded by the

Ministry of Innovation, Science and Research (MIWF) of North Rhine-Westphalia with an independent researcher grant.

References

- [1] Chua L 1971 Memristor—the missing circuit element *IEEE*Trans. Circuit Theory 18 507–19
- [2] Di Ventra M, Pershin Y V and Chua L O 2009 Circuit elements with memory: memristors, memcapacitors, and meminductors *Proc. IEEE* 97 1717–24
- [3] Di Ventra M, Pershin Y V and Chua L O 2009 Putting memory into circuit elements: memristors, memcapacitors, and meminductors *Proc. IEEE* 97 1371–2
- [4] Chua L and Kang S M 1976 Memristive devices and systems Proc. IEEE 64 209–23
- [5] Pershin Y V and Di Ventra M 2011 Memory effects in complex materials and nanoscale systems Adv. Phys. 60 145–227
- [6] Collier C P, Wong E W, Belohradsky M, Raymo F M, Stoddart J F, Kuekes P J, Williams R S and Heath J R 1999 Electronically configurable molecular-based logic gates Science 285 391–4
- [7] Snider G, Kuekes P and Williams R S 2004 CMOS-like logic in defective, nanoscale crossbars *Nanotechnology* 15 881–91
- [8] Snider G 2005 Computing with hysteretic resistor crossbars Appl. Phys. A 80 1165–72
- [9] Snider G S 2007 Self-organized computation with unreliable, memristive nanodevices *Nanotechnology* 18 365202
- [10] Yang J J, Miao F, Pickett M D, Ohlberg D A A, Stewart D R, Lau C N and Williams R S 2009 The mechanism of electroforming of metal oxide memristive switches *Nanotechnology* 20 215201
- [11] Yang J J, Zhang M X, Strachan J P, Miao F, Pickett M D, Kelley R D, Medeiros-Ribeiro G and Williams R S 2010 High switching endurance in TaO_x memristive devices Appl. Phys. Lett. 97 232102
- [12] Waser R and Aono M 2007 Nanoionics-based resistive switching memories *Nature Mater.* 6 833–40
- [13] Despotuli A L and Nikolaichik V I 1993 A step towards nanoionics Solid State Ion. 60 275–8
- [14] Strukov D B, Snider G S, Stewart D R and Williams R S 2008 The missing memristor found *Nature* 453 80–3
- [15] Krzysteczko P, Münchenberger J, Schäfers M, Reiss G and Thomas A 2012 The memristive magnetic tunnel junction as a nanoscopic synapse-neuron system *Adv. Mater.*
- [16] Borghetti J, Snider G S, Kuekes P J, Yang J J, Stewart D R and Williams R S 2010 'Memristive' switches enable 'stateful' logic operations via material implication *Nature* 464 873–6
- [17] Borghetti J, Li Z, Straznicky J, Li X, Ohlberg D A A, Wu W, Stewart D R and Williams R S 2009 A hybrid nanomemristor/transistor logic circuit capable of self-programming *Proc. Natl Acad. Sci.* 106 1699–703
- [18] Xia Q et al 2009 Memristor-CMOS hybrid integrated circuits for reconfigurable logic Nano Lett. 9 3640–5
- [19] Yan H, Choe H S, Nam S W, Hu Y and Das S 2011 Programmable nanowire circuits for nanoprocessors Nature 470 240–4
- [20] Muenchenberger J, Krzysteczko P, Reiss G and Thomas A 2011 Improved reliability of magnetic field programmable gate arrays through the use of memristive tunnel junctions J. Appl. Phys. 110 096105
- [21] Linn E, Rosezin R, Kuegeler C and Waser R 2010 Complementary resistive switches for passive nanocrossbar memories *Nature Mater.* **9** 403–6

- [22] Lee M-J et al 2011 A fast, high-endurance and scalable non-volatile memory device made from asymmetric Ta₂O_{5x}/TaO_{2x} bilayer structures Nature Mater. 10 625–30
- [23] Chen X, Wu G and Dinghua B 2008 Resistive switching behaviour of Pt/Mg0.2Zn0.8O/Pt devices for nonvolatile memory applications Appl. Phys. Lett. 93 093501
- [24] Biolek Z, Biolek D and Biolkova V 2009 SPICE model of memristor with nonlinear dopant drift *Radioengineering* 18 210–4
- [25] Rak A and Cserey G 2010 Macromodeling of the memristor in SPICE IEEE Trans. Comput. Aided Des. 29 632–6
- [26] Shin S and Kim K 2010 Compact models for memristors based an charge-flux constitutive relationships *IEEE Trans. Comput. Aided Des.* 29 590–8
- [27] Kavehei O, Iqbal A, Kim Y S, Eshraghian K, Al-Sarawi S F and Abbott D 2010 The fourth element: characteristics, modelling and electromagnetic theory of the memristor *Proc. R. Soc.* A 466 2175–202
- [28] Batas D and Fiedler H 2011 A memristor SPICE implementation and a new approach for magnetic flux-controlled memristor modeling *IEEE Trans*. *Nanotechnol.* 10 250–5
- [29] Hebb D O 1949 *The Organization of Behavior* A Neuropsychological Theory (New York: Wiley)
- [30] Cantley K D, Subramaniam A, Stiegler H J, Chapman R A and Vogel E M 2011 Hebbian learning in spiking neural networks with nanocrystalline silicon TFTs and memristive synapses *IEEE Trans. Nanotechnol.* 10 1066–73
- [31] Bichler O, Zhao W, Alibart F, Pleutin S, Vuillaume D and Gamrat C 2010 Functional model of a nanoparticle organic memory transistor for use as a spiking synapse *IEEE Trans. Electron Dev.* **57** 3115–22
- [32] Rachmuth G, Shouval H Z, Bear M F and Poon C-S 2011 A biophysically-based neuromorphic model of spike rateand timing-dependent plasticity *Proc. Natl Acad. Sci.* 108 E1266–74
- [33] Kim H, Sah M Pd, Yang C, Roska T and Chua L O 2012 Neural synaptic weighting with a pulse-based memristor circuit *IEEE Trans. Circuits-I* 59 148–58
- [34] Eccles J C and McIntyre A K 1951 Plasticity of mammalian monosynaptic reflexes *Nature* 167 466–8
- [35] Cajal S R 1995 Histology of the Nervous System of Man and Vertebrates (Oxford: Oxford University Press)
- [36] Konorski J 1948 Conditioned Reflexes and Neuron Organization (Cambridge: Cambridge University Press)
- [37] Hyman S E and Nestler E J 1993 *The Molecular Foundations* of *Psychiatry* (American Psychiatric Press)
- [38] Deuchars J, West D C and Thomson A M 1994 Relationships between morphology and physiology of pyramid–pyramid single axon connections in rat neocortex in vitro J. Physiol. 478 423–35
- [39] Daumas S, Ceccom J, Halley H, Frances B and Lassalle J M 2009 Activation of metabotropic glutamate receptor type 2/3 supports the involvement of the hippocampal mossy fiber pathway on contextual fear memory consolidation *Learning Mem.* 16 504–7
- [40] Curtis D R and Eccles J C 1959 The time courses of excitatory and inhibitory synaptic actions J. Physiol. 145 529–46
- [41] Doyere V and Laroche S 1992 Linear relationship between the maintenance of hippocampal long-term potentiation and retention of an associative memory *Hippocampus* 2 39–48
- [42] Morris R G M, Davis S and Butcher S P 1990 Hippocampal synaptic plasticity and nmda receptors—a role in information-storage *Phil. Trans. R. Soc.* B 329 187–204

- [43] Bliss T V P and Collingridge G L 1993 A synaptic model of memory—long-term potentiation in the hippocampus *Nature* 361 31–9
- [44] Bliss T V P and Lømo T 1973 Long-lasting potentiation of synaptic transmission in dentate area of anesthetized rabbit following stimulation of perforant path *J. Physiol.* 232 331–56
- [45] Bliss T V P and Gardner-Medwin A R 1973 Long-lasting potentiation of synaptic transmission in dentate area of unanesthetized rabbit following stimulation of perforant path J. Physiol. 232 357–74
- [46] McNaughton B L, Douglas R M and Goddardd G V 1978 Synaptic enhancement in fascia dentata—cooperativity among coactive afferents *Brain Res.* 157 277–93
- [47] Malenka R C 1991 Postsynaptic factors control the duration of synaptic enhancement in area cal of the hippocampus Neuron 6 53–60
- [48] Barrionuevo G and Brown T H 1983 Associative long-term potentiation in hippocampal slices *Proc. Natl Acad. Sci.* 80 7347–51
- [49] Levy W B and Steward O 1979 Synapses as associative memory elements in the Hippocampal-formation *Brain* Res. 175 233–45
- [50] Lynch G S, Dunwiddie T and Gribkoff V 1977 Heterosynaptic depression—postsynaptic correlate of long-term potentiation *Nature* 266 737–9
- [51] Andersen P, Sundberg S H, Sveen O and Wigström H 1977 Specific long-lasting potentiation of synaptic transmission in hippocampal slices *Nature* 266 736–7
- [52] Goda Y and Stevens C F 1996 Long-term depression properties in a simple system *Neuron* **16** 103–11
- [53] Rubin D C and Wenzel A E 1996 One hundred years of forgetting: A quantitative description of retention *Psychol. Rev.* 103 734–60
- [54] Diamond D M, Fleshner M and Rose G M 1994 Psychological stress repeatedly blocks hippocampal primed burst potentiation inbehaving rats *Behav. Brain* Res. 62 1–9
- [55] Xu L, Anwyl R and Rowan M J 1998 Spatial exploration induces a persistent reversal of long-term potentiation in rat hippocampus *Nature* 394 891–4
- [56] Manahan-Vaughan D and Braunewell K H 1999 Novelty acquisition is associated with induction of hippocampal long-term depression *Proc. Natl Acad. Sci.* 96 8739–44
- [57] Ge Y, Dong Z, Bagot R C, Howland J G, Phillips A G, Wong T P and Wang Y T 2010 Hippocampal long-term depression is required for the consolidation of spatial memory *Proc. Natl Acad. Sci.* 107 16697–702
- [58] Chang T, Jo S H and Lu W 2011 Short-term memory to long-term memory transition in a nanoscale memristor ACS Nano. 5 7669–76
- [59] Bi G-q and Poo M-m 1998 synaptic modifications in cultured hippocampal neurons: dependence on spike timing, synaptic strength, and postsynaptic cell type *J. Neurosci*. 18 10464–72
- [60] Hopfield J J 1995 Pattern-recognition computation using action-potential timing for stimulus representation *Nature* 376 33–6
- [61] Mainen Z F and Sejnowski T J 1995 Reliability of spike timing in neocortical neurons Science 268 1503–6
- [62] de Ruyter van Steveninck R R, Lewen G D, Strong S P, Koberle R and Bialek W 1997 Reproducibility and variability in neural spike trains Science 275 1805–8
- [63] Gerstner W and Abbott L F 1997 Learning navigational maps through potentiation and modulation of hippocampal place cells J. Comput. Neurosci. 4 79–94
- [64] Mehta M R, Barnes C A and McNaughton B L 1997 Experience-dependent, asymmetric expansion of hippocampal placefields *Proc. Natl Acad. Sci.* 94 8918–21

- [65] Cassenaer S and Laurent G 2007 Hebbian STDP in mushroom bodies facilitates the synchronous flow of olfactory information in locusts *Nature* 448 709–12
- [66] Lapicque L 1907 Lapicque: Recherches quantitatives sur l'excitation des nerfs traitée comme une polarisation J. Physiol. Pathol. Gen. 9 620–35
- [67] Lapicque L 1926 *L'excitabilit en fonction du temps* (Paris: Presses Universitaires de France)
- [68] Stein R B 1967 Frequency of nerve action potentials generated by applied currents *Proc. R. Soc. Lond.* B 167 64–86
- [69] Knight B W 1972 Dynamics of encoding in a population of neurons J. Gen. Physiol. 59 734
- [70] Jack J J B, Noble D and Tsien R W 1983 *Electric Current Flow in Excitable Cells* (New York: Oxford)
- [71] Tuckwell H C 2008 Introduction to Theoretical Neurobiology (Cambridge: Cambridge University Press)
- [72] Koch C 1999 Biophysics of Computation (Oxford: Oxford University Press)
- [73] Aziz P M, Sorensen H V and van der Spiegel J 1996 An overview of sigma-delta converters *IEEE Signal Proc.* Mag. 13 61–84
- [74] Wong P W and Gray R M 1990 Sigma-delta modulation with I.I.D. Gaussian inputs *IEEE Trans. Inform. Theory* 36 784–98
- [75] Mead C 1990 Neuromorphic electronic systems *Proc. IEEE* **78** 1629–36
- [76] Snider G S 2008 Spike-timing-dependent learning in memristive nanodevices *IEEE Int. Symp. Nanoscale Architectures (NANOARCH 2008) (Washington, DC,* 12–13 June 2008) pp 85–92
- [77] Carpenter G A, Milenova B L and Noeske B W 1998 Distributed ARTMAP: a neural network for fast distributed supervised learning *Neural Networks* 11 793–813
- [78] Fusi S and Abbott L F 2007 Limits on the memory storage capacity of bounded synapses *Nature Neurosci.* 10 485–93
- [79] Pershin Y V and Di Ventra M 2010 Experimental demonstration of associative memory with memristive neural networks *Neural Networks* 23 881–6
- [80] Pershin Y V and Di Ventra M 2010 Neuromorphic, digital, and quantum computation with memory circuit elements *Proc. IEEE* 100 2071–80
- [81] Pavlov I 1927 Conditioned Reflexes: An Investigation of the Physiological Activity of the Cerebral Cortex (Oxford: Oxford University Press)
- [82] Cantley K D, Subramaniam A, Stiegler H J, Chapman R A and Vogel E M 2012 Neural learning circuits utilizing nano-crystalline silicon transistors and memristors *IEEE Trans. Neur. Net. Lear* 23 565–73
- [83] Afifi A, Ayatollahi A and Raissi F 2009 STDP implementation using memristive nanodevice in CMOS-Nano neuromorphic networks *Ieice. Electron.* Expr. 6 148–53
- [84] Turel O, Lee J H, Ma X L and Likharev K K 2004 Neuromorphic architectures for nanoelectronic circuits *Int. J. Circ. Theor. App.* 32 277–302
- [85] Indiveri G, Chicca E and Douglas R 2006 A VLSI array of low-power spiking neurons and bistable synapses with spike-timing dependent plasticity *IEEE Trans. Neural.* Netw. 17 211–21
- [86] Jo S H, Chang T, Ebong I, Bhadviya B B, Mazumder P and Lu W 2010 Nanoscale memristor device as synapse in neuromorphic systems *Nano Lett.* 10 1297–301
- [87] Chang T, Jo S H, Kim K-H, Sheridan P, Gaba S and Lu W 2011 Synaptic behaviors and modeling of a metal oxide memristive device Appl. Phys. A 102 857–63
- [88] Gray C M and McCormick D A 1996 Chattering cells: superficial pyramidal neurons contributing to the

- generation of synchronous oscillations in the visual cortex *Science* **274** 109–13
- [89] Myers E, Ralph D, Katine J and Louie R 1999 Current-induced switching of domains in magnetic multilayer devices *Science* 285 867–70
- [90] Huai Y, Albert F, Nguyen P, Pakala M and Valet T 2004 Observation of spin-transfer switching in deep submicron-sized and low-resistance magnetic tunnel junctions Appl. Phys. Lett. 84 3118
- [91] Hayakawa J, Ikeda S, Lee Y M, Sasaki R, Meguro T, Matsukura F, Takahashi H and Ohno H 2005 Currentdriven magnetization switching in CoFeB/MgO/CoFeB magnetic tunnel junctions *Japanese J. Appl. Phys.* 44 L1267–70
- [92] Sun J, Gaidis M, Hu G, O'Sullivan E and Brown S 2009 High-bias backhopping in nanosecond time-domain spin-torque switches of MgO-based magnetic tunnel junctions J. Appl. Phys. 105 07D109
- [93] Min T, Sun J, Beach R, Tang D and Wang P 2009 Back-hopping after spin torque transfer induced magnetization switching in magnetic tunneling junction cells J. Appl. Phys. 105 07D126
- [94] Krzysteczko P, Reiss G and Thomas A 2009 Memristive switching of MgO based magnetic tunnel junctions Appl. Phys. Lett. 95 112508
- [95] Krzysteczko P, Kou X, Rott K, Thomas A and Reiss G 2009 Current induced resistance change of magnetic tunnel junctions with ultra-thin MgO tunnel barriers J. Magn. Magn. Mater. 321 144-7
- [96] Josephson B D 1962 Possible new effects in superconductive tunneling *Phys. Lett.* 1 251–3
- [97] Meservey R and Tedrow P M 1994 Spin-polarized electron-tunneling Phys. Rep. 238 173–243
- [98] Moodera J S and Mathon G 1999 Spin polarized tunneling in ferromagnetic junctions J. Magn. Magn. Mater. 200 248–73
- [99] Wrona J, Langer J, Ocker B, Maass W, Kanak J, Stobiecki T and Powroźnik W 2010 Low resistance magnetic tunnel junctions with MgO wedge barrier J. Phys.: Conf. Ser. 200 052032
- [100] Prinz G 1998 Magnetoelectronics Science 282 1660-3
- [101] Likharev K K 2011 Cross nets: neuromorphic hybrid cmos/nanoelectronic networks *Sci. Adv. Mater.* **3** 322–31
- [102] Snider G *et al* 2011 From synapses to circuitry: using memristive memory to explore the electronic brain *Computer* 44 21–8
- [103] Berzina T, Smerieri A, Bernabo M, Pucci A, Ruggeri G, Erokhin V and Fontana M P 2009 Optimization of an organic memristor as an adaptive memory element *J. Appl. Phys.* 105 124515
- [104] Erokhin V, Schuez A and Fontana M P 2010 Organic memristor and bio-inspired information processing *Int. J. Unconv. Comput.* 6 15–32
- [105] Pershin Y V and Di Ventra M 2012 Teaching memory circuit elements via experiment-based learning *IEEE Circut. Syst.* Mag. 12 64–74

- [106] Carpenter G A 1989 Neural network models for pattern recognition and associative memory *Neural Networks* 2 243–57
- [107] Snider G 2011 Instar and outstar learning with memristive nanodevices *Nanotechnol.* **22** 015201
- [108] Itoh M and Chua L O 2009 Memristor cellular automata and memristor discrete-time cellular neural networks *Int. J. Bifurcat. Chaos* 19 3605–56
- [109] Pershin Y V and Di Ventra M 2011 Solving mazes with memristors: A massively parallel approach *Phys. Rev.* E 84 046703
- [110] Nakagaki T, Yamada H and Toth A 2000 Maze-solving by an amoeboid organism *Nature* 407 470–470
- [111] Steels L, Babloyantz and Sepulchre J A 1991 Path finding with nonlinear waves *Proc. Int. Conf. on Artificial Neural Networks (Espoo, Finland)*
- [112] Sepulchre J A and Babloyantz A 1993 Motions of spiral waves in oscillatory media and in the presence of obstacles *Phys. Rev.* E 48 187–95
- [113] Steinbock O, Toth A and Showalter K 1995 Navigating complex labyrinths: optimal paths from chemical waves Science 267 868–71
- [114] Williams G, Showalter K and Steinbock O 1995 Minimal path algorithms—reply *Science* **269** 418–8
- [115] Pershin Y, Fontaine S L and Di Ventra M 2009 Memristive model of amoeba learning *Phys. Rev.* E **80** 021926
- [116] Lindsten J 1998 *Nobel Lectures in Physiology or Medicine* 1971–80 (Singapore: World Scientific)
- [117] Hodgkin A L and Huxley A F 1952 A quantitative description of membrane current and its application to conduction and excitation in nerve J. Physiol. 117 500–44
- [118] Young J Z 1936 The structure of nerve fibres in Cephalopods and Crustacea Proc. R. Soc. Lond. B 121 319–37
- [119] Chua L O 1998 CNN: A Paradigm for Complexity (Singapore: World Scientific)
- [120] Chua L, Sbitnev V and Kim H 2012 Hodgkin–Huxley axon is made of memristors Int. J. Bifurcat. Chaos 22 1230011
- [121] Chua L O 1969 Introduction to Nonlinear Network Theory (New York: McGraw-Hill)
- [122] Chua L O, Desoer C A and Kuh E S 1987 *Linear and Nonlinear Circuits* (New York: McGraw-Hill)
- [123] Mauro A 1961 Anomalous impedance, a phenomenological property of time-variant resistance—an analytic review *Biophys. J.* 1 353–72
- [124] Cole K S 1941 Rectification and inductance in the squid giant axon *J. Gen. Physiol.* **25** 29–51
- [125] Cole K S and Baker R F 1941 Longitudinal impedance of the squid giant axon *J. Gen. Physiol.* **24** 771–88
- [126] Cole K 1972 *Membranes, Ions and Impulses* (Berkeley, CA: University of California Press)
- [127] Chua L, Sbitnev V and Kim H 2012 Neurons are poised near the edge of chaos *Int. J. Bifurcat. Chaos* 22 1250098