

Querying Ticket Status

Interface Function

Query the ticket status. (The ticket details contain the ticket handler information.)

NOTE

If new tenants in IMOC 25.2.RC1 or later are interworked, the system uses the UTC time. Therefore, the time in the request and response messages is the UTC time. If existing tenants in versions earlier than IMOC 25.2.RC1 are interworked, the local time is used.

Request Method

POST

Flow Control

A maximum of 200 requests can be sent per second. If the number of requests exceeds 200, error code 500 is returned, and the following information is displayed: **AccessLimit**
Monitor Client *xxx* **reqUrl** *xxx* **overspeed limit** *xxx* ,**reqTotal** *xxx*.

URI

/eticket/openapi/order/status

Request Message

- Message headers
For details, see [Authentication Mode](#).
- Message body

Table 1 Request parameters

Parameter	Value Type	Mandatory	Value Range	Description
orderNumber	String	Yes	None	Ticket serial number.

- Example of a correct request packet

```
POST /eticket/openapi/order/status HTTP/1.1
```

```
Host: https://<IP address>:<Port number>
```

```
Accept: application/json;charset=UTF-8
```

```
{
  "orderNumber": "hwx190130BGY5"
}
```

Response Message

- Response parameters

Table 2 Parameters of the response message body

Parameter	Value Type	Value Range	Description
code	String	None	Response code. The value 200 indicates success, and the value 500 indicates failure.
data	String	None	Response object.
error	String	None	Exception information.

Table 3 Parameters of the response message data

Parameter	Value Type	Value Range	Description
orderNumber	String	None	Ticket number.
orderName	String	None	Ticket name.

Parameter	Value Type	Value Range	Description
currentStepName	String	None	Current step name.
currentStepNameI18n	JSON object	None	Internationalized name of the current step.
currentStepSeq	Integer	None	Sequence number of the current step.
orderStatus	String	processing: processing; dismissed: rejected; reback: rolled back; completed: completed; suspend: suspended; scrapped: discarded; draft: draft	Ticket status (processing: processing; dismissed: rejected; reback: rolled back; completed: completed; suspend: suspended; scrapped: discarded; draft: draft).
currentStepId	String	None	ID of the node in the current step.
applyUser	String	None	Applicant.
slaStatus	String	None	SLA status (NC: not expired; break: expired).
logList	JSON array	None	Ticket processing record list.
beginTime	String	None	Start time.
endTime	String	None	End time.

Parameter	Value Type	Value Range	Description
processType	String	mainprocess; subprocess	Ticket task type (mainprocess : main task; subprocess : subtask).
submitAble	Boolean	true; false	Whether to enable the quick ticket submission function (true : yes; false : no).

- logList parameters

Parameter	Value Type	Value Range	Description
handleOpinion	String	None	Operation.
handleResult	String	None	Handling suggestion.
handleTime	String	None	Handling time.
handleUser	String	None	Handler.
stepName	String	None	Step name.
stepNameI18n	JSON object	None	Internationalized name of a step.
stepNameI18n.en_US	String	None	Internationalized English name of a step.
stepNameI18n.zh_CN	String	None	Internationalized Chinese name of a step.
stepNameI18n.fr_FR	String	None	Internationalized French name of a step.

- Response example

HTTP/1.1 200

Date: Thu, 29 Aug 2019 08:30:30 GMT

Content-Length: xxx

Content-Type: application/json;charset=UTF-8

```
{
  "code": 200,
  "data": {
    "applyUser": "hxxxxx",
    "beginTime": "2019-01-30 11:53:45",
    "createTime": null,
    "curStep": null,
    "currentStepName": "step 2",
    "currentUser": "hxxxxx",
    "logList": [
      {
        "createTime": null,
        "handleOpinion": "submitted",
        "handleResult": "submit",
        "handleTime": "2019-01-30 11:54:08",
        "handleUser": "hxxxxx",
        "stepName": "step 1"
      }
    ],
    "modifyTime": null,
    "slaStatus": "NC",
    "orderName": "SLA status",
    "orderNumber": "hxxxxx",
    "orderStatus": "processing",
    "processType": "mainprocess"
  }
}
```

- Example of an incorrect response packet

```
{
  "code": "5001",
  "data": "System error. Please contact the administrator."
}
```

Parent Topic: **External eTicket Interfaces**

[< Previous](#) [Next topic >](#)

Copyright © Huawei Technologies Co., Ltd.