

Querying the Ticket List

Function Description

This interface is used to query the ticket list.

NOTE

If new tenants in IMOC 25.2.RC1 or later are interworked, the system uses the UTC time. Therefore, the time in the request and response messages is the UTC time. If existing tenants in versions earlier than IMOC 25.2.RC1 are interworked, the local time is used.

Calling Method

POST

Flow Control

A maximum of 200 requests can be sent per second. If the number of requests exceeds 200, error code 500 is returned, and the following information is displayed: **AccessLimit Monitor Client xxx reqUrl xxx overspeed limit xxx ,reqTotal xxx**.

URI

/eticket/openapi/order/query/{pageSize}/{pageNum}

- Path parameters
None
- Query parameters

Parameter	Value Type	Mandatory	Value Range	Description
pageNum	String	Yes	None	Current page number. The default value is 1 .
pageSize	String	Yes	None	Number of records on the current page. The default value is 15 .

Request Message

- Message headers
For details, see [Authentication Mode](#).
- Message body
Table 1 body parameters

Parameter	Value Type	Mandatory	Value Range	Description
createBy	String	No	None	User name of the creator, handler, and collector. This parameter is used together with handleValue and cannot be used independently.
handleValue	String	No	create, handle, favorites, groupCreate, or groupProcessed , which is used with createBy or authorGroup	Value range: create, handle, favorites, groupCreate, or groupProcessed, which is used with createBy or authorGroup. - Users (createBy) Tickets created by users: create transferred for handleValue and <i>xxx</i> transferred for createBy (createBy) Tickets handled by users: handle transferred for handleValue and <i>xxx</i> transferred for createBy (createBy) Tickets added to favorites by users: favorites transferred for handleValue and <i>xxx</i> transferred for createBy - User groups - Tickets created by a group (<i>xxx</i>) to which the current user belongs: groupCreate transferred for handleValue, <i>xxx</i> transferred for createBy, and <i>xxx</i> transferred for authorGroup - Tickets handled by a group (<i>xxx</i>) to which the current user belongs: groupProcessed transferred for handleValue, <i>xxx</i> transferred for createBy, and <i>xxx</i> transferred for authorGroup NOTE: If authorGroup is not transferred and only handleValue=groupCreate or handleValue=groupProcessed is transferred, the tickets created or handled by the

Parameter	Value Type	Mandatory	Value Range	Description
				group to which the current user belongs are queried.
authorGroup	String	No	None	Group ID of the current user. This parameter is used together with handleValue and createBy and cannot be used independently.
orderStatus	String	No	processing: processing; dismissed: rejected; reback: rolled back; completed: completed; suspend: suspended; scrapped: discarded; draft: draft	Ticket status (processing: processing; dismissed: rejected; reback: rolled back; completed: completed; suspend: suspended; scrapped: discarded; draft: draft).
orderSource	String	No	None	Ticket source.
modelType	String	No	None	Ticket model type.
currentUser	String	No	None	Current handler.
modelName	String	No	None	Model name.
modelId	String	No	None	Model ID.
orderName	String	No	None	Ticket name.
endStartDate	String	No	None	It indicates the start time window for querying the ticket end time. The format is 2019-10-01 00:00:00. (Note: This parameter is available only when the ticket is completed.)
endEndDate	String	No	None	It indicates the end time window for querying the ticket end time. The format is 2019-10-01 00:00:00. (Note: This parameter is available only when the ticket is completed.)
orderNumber	String	No	None	

Parameter	Value Type	Mandatory	Value Range	Description
				Serial number of a work order. Use commas (,) to separate multiple serial numbers.
slaStatus	String	No	NC : not configured; BREAK : expired; NORMAL : not expired	SLA status (NC : not configured; BREAK : expired; NORMAL : not expired).
beginStartDate	String	No	None	It indicates the start time window for querying the ticket start time. The format is 2019-10-01 00:00:00.
beginEndDate	String	No	None	It indicates the end time window for querying the ticket start time. The format is 2019-10-01 00:00:00.
search	List<SearchParam>	No	None	Search by extended field.

Table 2 search parameters

Parameter	Value Type	Mandatory	Value Range	Description
paramKey	String	Yes	None	Field code.
queryMode	String	Yes	eq ; neq	Search mode (eq : exact search; neq : fuzzy search).
paramValue	String	Yes	None	Query keyword.
fieldType	String	No	None	Field type.
modelId	String	No	None	Model ID.

- Request example

POST /eticket/openapi/order/query/ {pageSize}/{pageNum} HTTP/1.1

Host: https://<IP address>:<Port number>

Accept: application/json;charset=UTF-8

```
{
  "createBy": "hxxxxx",
  "orderStatus": "completed",
  "orderSource": "eTicket",
  "modelType": "event",
  "modelName": "",
  "modelId": ""
```

```
"orderName": "",
"endStartDate": "",
"endEndDate": "",
"currentUser": "",
"orderNumber": "",
"slaStatus": "",
"beginStartDate": "",
"beginEndDate": ""
}
```

Response Message

- Response parameters

Table 3 Parameters of the response message body

Parameter	Value Type	Value Range	Description
code	String	200 ; 500	Response code. The value 200 indicates success, and the value 500 indicates failure.
data	String	-	Response object.
error	String	-	Exception information.

Table 4 Parameters of the response message data

Parameter	Value Type	Description
startRow	Integer	First row
hasNextPage	Boolean	Whether there is a next page
hasPreviousPage	Boolean	Whether there is a previous page
prePage	Integer	Previous page
nextPage	Integer	Next page
isFirstPage	Boolean	Whether the page is the first one
isLastPage	Boolean	Whether the page is the last one
endRow	Integer	Row number of the last element on the current page in the database
pageSize	Integer	Number of records on each page
pageNum	Integer	Current page number

Parameter	Value Type	Description
list	List	Ticket list
total	Integer	Total records
pages	Integer	Total pages
size	Integer	Number of records on the current page
navigatePages	Integer	Number of navigation pages
navigatepageNums	Array	Navigation page number
navigateFirstPage	Integer	Page number of the current first page
navigateLastPage	Integer	Page number of the current last page

Table 5 Parameters of the response message list

Parameter	Value Type	Description
applyUser	String	Initiator
beginTime	String	Start time
createBy	String	Creator
createTime	Timestamp	Creation time stamp
currentStepDistribu	String	Allocation mode
currentStepId	String	Current step ID
currentStepName	String	Current step name
currentStepSeq	Integer	Current step No.
currentUser	String	Current handler
endTime	String	End time
modelId	String	Model ID
modelName	String	Model name
orderSource	String	Ticket source
orderStatus	String	Ticket status

Parameter	Value Type	Description
processType	String	Main thread or not
slaStatus	String	SLA status
tenant	String	Tenant
allApplyUser	String	Full name and employee ID of the initiator
allCurrentUser	String	Full name and employee ID of the current handler
createGroupId	String	Creator group ID
createGroupName	String	Creator group name
processGroups	List	Group information of the current handler

Table 6 Parameters of the response message processGroups

Parameter	Value Type	Description
groupId	String	Group ID
groupName	String	Group name
type	String	Personnel field type
groupUserList	String	Set of group types
userList	String	A collection of members (user names and user IDs) in a group
userId	String	User ID
accountFull	String	Full name of the user

- Example of a correct response packet

```

HTTP/1.1 200
Date: Thu, 29 Aug 2019 08:30:30 GMT
Content-Length: xxx
Content-Type: application/json;charset=UTF-8
{
  "code": 200,
  "data": {
    "endRow": 15,
    "hasNextPage": true,
    "hasPreviousPage": false,

```

```

"isFirstPage": true,
"isLastPage": false,
"list": [
  {
    "applyUser": "hxxxx",
    "beginTime": "2019-08-22 15:52:30",
    "createBy": "hxxxx",
    "createTime": 1566460350000,
    "curStep": null,
    "currentStepDistribu": "auto",
    "currentStepId": "cb1640abc4b111e9ae90286ed4898fdc",
    "currentStepName": "3333",
    "currentStepSeq": 3,
    "currentUser": "",
    "enableFlag": "true",
    "endTime": "2019-08-22 15:53:37",
    "isClaim": 0,
    "log": null,
    "modelId": "ab4efc46c4b011e9ae90286ed4898fdc",
    "modelName": "cqh Test to-do",
    "modelType": "event",
    "modifyBy": "hxxxx",
    "modifyTime": 1566460417000,
    "orderId": "cb122736c4b111e9ae90286ed4898fdc",
    "orderName": "Dark room test",
    "orderNumber": "cqh190822UYp0",
    "orderSource": "eTicket",
    "orderStatus": "completed",
    "processType": "mainprocess",
    "slaStatus": "NC",
    "tenant": "eTicket",
    "allApplyUser": "Handling group/zq zq",
    "allCurrentUser": "Handling group/",
    "createGroupId": "FA163E9FF74E511A0AD64947FE0FFAC2",
    "createGroupName": "Handling group test",
    "processGroups": [
      {
        "groupId": "FA163E9FF74E511A0AD64947FE0FFAC2",
        "groupName": "Group name",
        "type": "group_person"
        "groupUserList": [
          {
            "userId": "hadmin01",
            "accountFull": "hxxxx"
          }
        ]
      }
    ],
  },

```

```

    {
      "groupId": "FA163E9FF74E511A0AD64947FE0FFAC2",
      "groupName": "Group name",
      "type": "new_person"
      "userList": [
        {
          "userId": "hxxxxx",
          "accountFull": "hxxxxx"
        }
      ]
    },
    ...
  ],
  "navigateFirstPage": 1,
  "navigateLastPage": 8,
  "navigatePages": 8,
  "navigatepageNums": [
    1,
    2,
    3,
    4,
    5,
    6,
    7,
    8
  ],
  "nextPage": 2,
  "pageNum": 1,
  "pageSize": 15,
  "pages": 33,
  "prePage": 0,
  "size": 15,
  "startRow": 1,
  "total": 494
}
}

```

- Example of an incorrect response packet

```

{
  "code": "5001",
  "data": "System error. Please contact the administrator."
}

```

Copyright © Huawei Technologies Co., Ltd.