

Project Notes: E-Commerce RAG Chatbot

"Ye project ka sabse interesting part hoga. Samajh kar banana hai, sirf copy-paste nahi."

1. SABSE PEHLE RAG SAMAJHTE HAIN

Normal chatbot:

User



Gemini



Answer

Problem: Gemini ko tumhare products, orders ya policies ka kuch nahi pata.

RAG Chatbot:

User



Backend (/api/chat)



Embedding



Vector Database



Relevant Information



Gemini



Answer

Yani: Gemini ko pehle tumhare project ki information di jayegi, phir wo answer dega.

2. HAMARE E-COMMERCE PROJECT ME CHATBOT KYA KAREGA? (EXAMPLES)

Example 1:

User puche: "Return policy kya hai?"

Chatbot Flow:

Documents me search karega



Return policy ka paragraph nikalega



Gemini ko dega



Natural language me answer dega

Example 2:

User: "Phone category me sabse sasta product kaunsa hai?"

Backend Flow:

MongoDB



Products fetch



Gemini



Answer

3. TECH STACK (RECOMMENDED)

✓ Gemini 2.5 Flash (Free)

✓ LangChain.js

✓ ChromaDB

✓ MongoDB

✓ Express

Note: Ye sab JavaScript me hoga. Python ki zarurat nahi.

4. PROJECT STRUCTURE & FILE EXPLANATION

```

server | ├── src | ├── controllers | └── chat.controller.js | ├── routes | └──
chat.routes.js | ├── services | └── rag.service.js | ├── ai | ├── embeddings.js | ├──
vectorStore.js | ├── gemini.js | ├── documents | ├── policies.txt | ├── faq.txt | └──
shipping.txt | └── ...

```

controllers/chat.controller.js

Chat API ke request aur response ko handle karta hai. Frontend se aane wale message ko receive karta hai aur answer wapas bhejta hai.

routes/chat.routes.js

Chatbot ke API endpoints (jaise /api/chat) define karta hai aur requests ko controller se jodta hai.

services/rag.service.js

RAG ka main logic yahan rehta hai—query ke anusar documents search karna, relevant context banana aur Gemini ko bhej kar answer generate karwana.

ai/embeddings.js

Text data ko numerical vectors (embeddings) me convert karne ka kaam karta hai taaki similarity search ho sake.

ai/vectorStore.js

ChromaDB vector database ke sath connection aur document embeddings ko store/search karne ka setup karta hai.

ai/gemini.js

Gemini 2.5 Flash model ka configuration aur LangChain / Google AI client ka setup sambhalta hai.

documents/ (policies.txt, faq.txt, shipping.txt)

Project ke raw knowledge documents jisme Return policy, FAQs aur Shipping details likhi hoti hain jise Vector DB me store kiya jata hai.

5. HUM KYA KYA BANAYENGE (PHASES)

Phase 1: Basic AI Chat

User ↓ Gemini ↓ Answer

Phase 2: RAG

TXT / PDF ↓ Embeddings ↓ Vector DB ↓ Gemini ↓ Answer

Phase 3: Database-aware AI

User ↓ MongoDB ↓ Gemini ↓ Answer

Example: User: "How many products are available?" ↓ MongoDB Count ↓ Gemini ↓ "There are 156 products available."

Phase 4: Smart Assistant

User: "Where is my order?"

AI: Logged in user ↓ Orders collection ↓ Current status ↓ Answer

6. ISSE INTERVIEW ME IMPACT

Tum keh sakte ho:

"I built a MERN E-commerce platform with JWT Authentication, RBAC, Cart, Orders, and integrated a Retrieval-Augmented Generation (RAG) chatbot using Gemini and LangChain."

Ye kaafi strong project lagega.

7. MAIN SUGGESTION (LANGCHAIN.JS + GEMINI + CHROMADB)

Hum **LangChain.js + Gemini + ChromaDB** use karenge. Ye:

- ✓ Free tier me chal sakta hai.
- ✓ JavaScript based hai (tumhare MERN stack ke saath perfectly fit).
- ✓ Industry me kaafi use hota hai.
- ✓ Future me OpenAI ya Pinecone par migrate karna bhi aasaan hoga.

8. PEHLA STEP (WORKFLOW EXECUTION)

Ab coding se pehle hum **AI folder setup, Gemini API, aur LangChain installation** karenge.

Uske baad pehla `/api/chat` endpoint banayenge jo Gemini se baat karega.

Jab ye chal jayega, tab usme **RAG add karenge**.

Is order me chaloge to har concept clearly samajh aayega.


Project Roadmap Notes: 4-Phase AI Chatbot

Step-by-step implementation guide — Gemini API to Smart Database-Aware AI

PHASE 1

Gemini API Integration

Pehle ek normal AI chatbot banayenge.




 **Stage Note:** Is stage me abhi RAG nahi hoga.

PHASE 2

LangChain


LangChain ko connect karenge.



PHASE 3

RAG (Retrieval-Augmented Generation)

Apne documents add karenge.




 **Result:** Ab chatbot sirf apne documents ke basis par answer dega.

PHASE 4

Smart AI

AI directly MongoDB se data bhi read karega.

Example Flow:



PROJECT START

Implementing RAG AI Chat Bot in E-Com Website

STEP 1: STRUCTURE OF FOLDER & FILES

```
server | ├── src | ├── controllers | └── chat.controller.js | ├── routes | └──  
chat.routes.js | ├── services | └── rag.service.js | ├── ai | ├── embeddings.js |  
└── vectorStore.js | └── gemini.js | ├── documents | ├── policies.txt | ├── faq.txt  
| └── shipping.txt | └── ...
```

STEP 2: PACKAGE INSTALL

```
npm install @google/genai
```

STEP 3: ENVIRONMENT VARIABLE

```
GEMINI_API_KEY=your_api_key
```

STEP 4: FILE STRUCTURE

```
src | ├── ai | └── gemini.js | ├── controllers | └── chat.controller.js | ├──  
routes | └── chat.routes.js | └── services | └── chat.service.js
```

STEP 5: MODULES TO CREATE

- Create Route
- Controller
- Services
- AI Module

STEP 6: CREATE SRC/AI/GEMINI.JS

```
import { GoogleGenAI } from "@google/genai"; const ai = new GoogleGenAI({ apiKey: process.env.GEMINI_API_KEY, }); export default ai;
```

LINE BY LINE EXPLANATION

1. Import Google GenAI

```
import { GoogleGenAI } from "@google/genai";
```

Ye Google ke official SDK ko import kar raha hai.

Jaise MongoDB ke liye: `import mongoose from "mongoose";` waise hi Gemini ke liye ye import hai.

2. Create AI Object

```
const ai = new GoogleGenAI({
```

Yahan Gemini ka object ban raha hai.

Jaise: `const app = express();` Express ka object banta hai.

3. API Key Binding

```
apiKey: process.env.GEMINI_API_KEY
```

.env me jo key rakhi hai usse read kar raha hai:

```
GEMINI_API_KEY=xxxxxxxxxxxxxxxxxxxx
```

4. Export AI Instance

```
export default ai;
```

Ab ye object project me kahin bhi use kar sakte ho.


Jaise: `import ai from "../ai/gemini.js";`

Folder:

```
src └─ ai └─ gemini.js
```



AB SERVICE BANAYENGE (SRC/SERVICES/CHAT.SERVICE.JS)

Iska kaam hoga:



⚠ Controller kabhi bhi directly Gemini ko call nahi karega. Ye MVC ka ek bahut important principle hai.

Socho flow:



✅ Yehi industry standard architecture hai.

STEP 7: SRC/SERVICES/CHAT.SERVICE.JS

```
import ai from "../ai/gemini.js"; export const chatWithGemini = async (message) => {  
  const response = await ai.models.generateContent({ model: "gemini-3.6-flash",  
  contents: message, }); return response.text; };
```

LINE BY LINE EXPLANATION

1. Import AI Instance

```
import ai from "../ai/gemini.js";
```

Yahan humne jo Gemini object banaya tha usko import kar liya.

Ye wahi object hai jisme API key lagi hui hai.

2. Service Function Declaration

```
export const chatWithGemini = async (message) => {
```

Ek function bana rahe hain. Ye function ek input lega.

Example: `message = "Hello"` ya `message = "What is React?"`

3. Request Call to Gemini

```
const response = await ai.models.generateContent({
```

Yahan Gemini ko request bhej rahe hain.

Jaise MongoDB me likhte ho: `await Product.find();` waise hi

```
await ai.models.generateContent();
```

 Gemini ko call karta hai.

4. Model Selection

```
model: "gemini-2.5-flash",
```

Kaunsa model use karna hai. Abhi hum Flash use karenge. Ye:

- Fast
- Free tier me available
- RAG ke liye best

hai.

5. Pass User Contents

```
contents: message,
```

Jo user ne message bheja hai woh Gemini ko bhej diya.


Example: User: `Hello` → Gemini ko bhi `Hello` jayega.

6. Return Filtered Text

```
return response.text;
```


Gemini bahut bada object return karta hai. Hume sirf answer chahiye. Isliye sirf `response.text` return kar diya.

FLOW



MVC ARCHITECTURE

Abhi tak hamara flow ban gaya hai:



Controller me AI ki ek bhi line nahi hogi. Ye clean architecture hai aur interviews me bhi isi tarah ka separation expect kiya jata hai.

STEP 8: CHAT.CONTROLLER.JS

```

import { chatWithGemini } from "../services/chat.service.js"; export const chat =
async (req, res) => { try { const { message } = req.body; if (!message) { return
res.status(400).json({ success: false, message: "Please enter a message" }); } const
result = await chatWithGemini(message); return res.status(200).json({ success: true,
result }); } catch (error) { return res.status(500).json({ success: false, message:
error.message }); } }
  
```

STEP 9: CHAT.ROUTES.JS

```
import express from 'express'; import { chat } from '../controllers/
chat.controller.js'; const router = express.Router(); router.post("/chat", chat);
export default router;
```

STEP 10: MOUNT IN APP.JS

Ab app.js me mount karo:

```
import chatRoute from "../routes/chat.routes.js";
```

Aur middleware ke niche:

```
app.use("/api/ai", chatRoute);
```

Ab final endpoint ban jayega:

```
POST /api/ai/chat
```

STEP 11: GEMINI.JS

```
import { GoogleGenAI } from "@google/genai"; const ai = new GoogleGenAI({ apiKey:
process.env.GEMINI_API_KEY, }); export default ai;
```

STEP 12: CREATE API KEY (SAHI TARIKA)

- Jao: <https://aistudio.google.com/app/apikey>
- **Create API Key** par click karo.
- Jo key milegi wo AIzaSy... se start hogi.

.env me:

```
GEMINI_API_KEY=AIzaSyXXXXXXXXXXXXXXXXXXXXXXXXXX
```

Server restart karo.

STEP 13: CREATE ENV.JS (SRC/CONFIG/ENV.JS)

```
import dotenv from "dotenv"; dotenv.config();
```

STEP 14: GEMINI.JS (UPDATED WITH ENV.JS)

```
import "../config/env.js"; import { GoogleGenAI } from "@google/genai"; const ai = new GoogleGenAI({ apiKey: process.env.GEMINI_API_KEY, }); export default ai;
```

STEP 15: SERVER.JS

```
import "../config/env.js"; import app from "../app.js"; import connectDB from "../config/db.js";
```

STEP 16: IF COME GEMINI (NO LONGER) RELATED ERROR

- Jao: <https://aistudio.google.com>
- Phir: **Models** section kholo.
- Ya API documentation me available models dekh lo.

STEP 17: POSTMAN TESTING

POST /api/ai/chat

Method: POST

URL: <http://localhost:5000/api/ai/chat>

(Port jo bhi tumhara server use kar raha ho.)

Body (JSON):

```
{ "message": "Hello Gemini" }
```

NOTES: ISKE BAAD KYA?


Jab normal chatbot chal jayega, tab hum actual RAG start karenge. Usme hum ye seekhenge:

- **Embeddings:** Text ko vectors me convert karna.
- **Vector Database (ChromaDB):** Documents store karna.
- **Retriever:** User ke question ke hisaab se relevant document nikalna.
- **Gemini + Context:** Gemini ko sirf wahi relevant information dena.
- **PDF aur TXT upload:** Chatbot apne documents ke basis par answer dega.
- **MongoDB RAG:** Chatbot tumhare products, orders aur users ke data ke basis par bhi intelligent answers de sakega.

REAL RAG STARTS NOWW


Ab asli RAG start hota hai 🚀

ABHI TUMHARA CHATBOT AISA HAI



⚠️ Isme Gemini ko tumhare project ke products ya orders ke baare me kuch nahi pata.

RAG ME FLOW HOGA



EXAMPLE

User puche: "Mere cart me kitne products hain?"

✗ Abhi Gemini nahi bata payega.

Lekin RAG ke baad:




HUM KIS TYPE KA RAG BANAYENGE?


Phase 1 (Easy): MongoDB RAG

Gemini se pehle database se data fetch karenge.

Example:



Phase 2: PDF RAG



Phase 3: Complete AI Assistant

Ye answer dega:

- Products
- Orders
- Cart
- FAQs

- PDF
- Company Policies

Sab combine.

AGLA STEP

Main recommend karunga ki pehle **MongoDB RAG** implement karein.

Isse tum seekhoge:

- AI + Database integration
- Dynamic prompts
- Context injection

Aur uske baad Embeddings + ChromaDB add karenge.

Ye sequence industry me bhi isi tarah use hota hai.

RESUME PITCH

Is project ke baad tumhare resume me confidently likh sakte ho:


"Built an AI-powered MERN E-commerce backend with JWT authentication, order management, and Retrieval-Augmented Generation (RAG) chatbot using Google Gemini."

PHASE 1: MONGODB RAG SHURU KARTE HAIN

Bilkul! Ab hum Phase 1: MongoDB RAG shuru karte hain.


Dhyan rahe: abhi hum vector database ya embeddings nahi use karenge. Pehle RAG ka concept samajhte hain.

Abhi Chatbot Ka Flow:



Problem: User puche: *"Mere cart me kitne products hain?"* → Gemini bolega: *"Mujhe nahi pata."*

Phase 1 Ke Baad:



CART DATA EXAMPLE FLOW

User: How many items are in my cart?

Controller:

```
const cart = await Cart.findOne({ userId });
```

Database:

```
{ "items": [ { "productName": "iPhone", "quantity": 2 }, { "productName": "Laptop",  
"quantity": 1 } ] }
```

Ab Gemini ko ye data bhejenge:

```
User Cart iPhone x2 Laptop x1 Question: How many items are in my cart?
```

Gemini answer: "You currently have 3 items in your cart."

Yahi RAG ka basic idea hai.

PEHLA STEP: QUESTION IDENTIFY KARNA

Abhi AI ko ye identify karna hoga ki user kis cheez ke baare me puch raha hai:

- my cart ya cart → **Cart** collection fetch hogi.
- my orders → **Order** collection fetch hogi.
- my products → **Product** collection fetch hogi.


FOLDER STRUCTURE & RAG.SERVICE.JS KA KAAM

Main suggest karunga:

```
controllers chat.controller.js services chat.service.js rag.service.js ← NEW models  
Cart.js Order.js Product.js
```

rag.service.js ka kaam:

Ye Gemini se pehle database se data nikalega.



HUM STEP BY STEP KARENGE

- Step 1: rag.service.js
- Step 2: Question classify karna (cart, orders, products)
- Step 3: Database query
- Step 4: Context banana
- Step 5: Gemini ko context dena

HEADING START:-

Phase 1: MongoDB RAG Implementation & Service Integration

STEP 1: STRUCTURE OF FILE & FOLDER

```
controllers chat.controller.js services chat.service.js rag.service.js ← NEW models  
Cart.js Order.js Product.js
```

STEP 2: CREATE RAG.SERVICE.JS

```
import Cart from "../models/cart.js"; import Order from "../models/order.js"; import  
Product from "../models/product.js"; export const getContext = async (message, userId)  
=> { };
```

STEP 3: RAG.SERVICE.JS

```
import Cart from '../models/cart.js'; import Product from '../models/product.js';  
import Order from '../models/order.js'; export const getContext = async (message,  
userId) => { if (message.toLowerCase().includes("cart")) { const cartDetail = await  
Cart.findOne({ userId }); return cartDetail; } else if  
(message.toLowerCase().includes("order")) { const orderDetail = await Order.find({  
userId }); return orderDetail; } else if (message.toLowerCase().includes("product"))  
{ const productDetail = await Product.find({ sellerId: userId }); return  
productDetail; } else { return null; } };
```

STEP 4: PRODUCTION IMPROVEMENT (POPULATE)

Excellent! 🔥 Ab ye service bilkul sahi direction me hai. Is stage par main ise 8.5/10 dunga. Ab ek chhota sa improvement batata hoon jo production projects me use hota hai.

Cart

Abhi:

```
const cartDetail = await Cart.findOne({ userId });
```

Better:

```
const cartDetail = await Cart.findOne({ userId }) .populate("items.productId",
"productName productPrice productStock");
```

Kyun?

Abhi productId me sirf ObjectId milega:

```
{ "productId": "689b3f8c4..." }
```

Populate ke baad:

```
{ "productId": { "_id": "...", "productName": "iPhone 16", "productPrice": 95000,
"productStock": 12 } }
```

Gemini ko ye data samajhna bahut aasaan ho jayega.

Orders

Same yahan bhi:


```
Order.find({ userId }).populate( "items.productId", "productName productPrice" );
```

Products

Yahan populate ki zarurat nahi hai kyunki Product collection hi fetch ho rahi hai.


STEP 5: AUGMENTED GENERATION CONCEPT

Ab tak humne sirf Retrieve kiya hai:



Ab Augmented Generation karenge.

Flow:



Ab chat.service.js ko modify karenge.

Abhi tumhara code hai:

```
export const chatWithGemini = async (message) => { }
```

Ab ise aisa banana hoga:

```
export const chatWithGemini = async ( message, context ) => { }
```

Yaani Gemini ko 2 cheezein milengi:

- User ka question
- Database se aaya context

STEP 6: CREATE CHAT.SERVICE.JS LOGIC

Step 1: Pehle ek prompt banao.

Example:

```
const prompt = ` You are an AI assistant for an e-commerce application. Database Context: ${JSON.stringify(context)} User Question: ${message} Answer only using the database context whenever possible. `;
```


Yahan:

- **context** = MongoDB se aaya data
- **message** = User ka question

Step 2: Ab Gemini ko ye prompt bhejna hai.

```
const response = await ai.models.generateContent({ model: "gemini-3.6-flash", contents: prompt, });
```

Ab flow aisa hoga:



🤔 Lekin ek aur improvement baaki hai:

JSON.stringify(context) kaam karega, lekin professional RAG me hum raw JSON nahi bhejte. Hum context ko readable text banate hain.

Example:

```
Cart Details: 1. Laptop Quantity: 2 Price: ₹50000 2. Mouse Quantity: 1 Price: ₹800
```

Ye Gemini ko raw JSON se bhi better samajh aata hai.

STEP 7: CHAT.SERVICE.JS (UPDATED CODE)

```
import ai from "../ai/gemini.js"; export const chatWithGemini = async (message, context) => { const prompt = ` You are an AI assistant for an e-commerce application. Database Context: \${JSON.stringify(context)} User Question: \${message} Answer only using the database context whenever possible. `; const response = await ai.models.generateContent({ model: "gemini-2.5-flash-lite", // ya jo model tum use kar rahe ho contents: prompt, }); return response.text; };
```

PROJECT IMPLEMENTATION NOTES

Step 8 to Step 9, Testing, Keyword Limits & Token Error Debugging


STEP 8: AB CHAT.CONTROLLER.JS MODIFY KARNA HAI

Abhi tumhara controller kuch aisa hai:

```
const result = await chatWithGemini(message);
```

Ab isse pehle context lana padega.

Flow:



Yaani controller me:


- `getContext()` import hoga.
- `const context = await getContext(message, req.user.id);`
- `chatWithGemini(message, context);`

STEP 9: CHAT.CONTROLLER.JS

```
import { chatWithGemini } from '../services/chat.service.js'; import { getContext }
from '../services/rag.service.js'; export const chat = async (req, res) => { try {
const { message } = req.body; if (!message) { return res.status(400).json({ success:
false, message: "please enter a message" }); } const context = await
getContext(message, req.user.id); const result = await chatWithGemini(message,
context); return res.status(200).json({ success: true, result }); } catch (error) {
return res.status(500).json({ success: false, message: error.message }); } };
```

NOTES: COMPLETE FLOW & PROFESSIONAL IMPROVEMENT

✓ Tumhara flow ab:



Yehi basic RAG architecture hota hai. 🧠

EK IMPROVEMENT

Abhi agar user pucho: Hello to `getContext()` **null** return karega.

Prompt banega:

```
Database Context: null User Question: Hello
```

Ye chalega, lekin aur professional tarika hai controller me:

```
const context = await getContext(message, req.user.id); const result = await chatWithGemini( message, context || "No database context available." );
```

(Ya `chat.service.js` me handle kar sakte ho.)

AB TEST KARO (TESTING PAYLOADS)

Cart:

```
{ "message": "Show my cart" }
```

Orders:

```
{ "message": "Show my orders" }
```

Products:

```
{ "message": "Show my products" }
```

Normal:

```
{ "message": "Hello" }
```

Agar sabka response aa raha hai to 🎉 MongoDB RAG Phase-1 complete.

LEKIN... 🤔 (KYUN YE TRUE RAG NAHI HAI?)

Tum sirf keyword match kar rahe ho: `message.includes("cart")`


Agar user likhe:

- "What have I added?"
- "Items I selected"
- "Basket"
- "Shopping cart"

To RAG fail ho jayega. Industry me iske liye **Embeddings + Vector Search** use hota hai.

AB PHASE-2 ME KYA HOGA?

Hum ye karenge:



Uske baad user agar puche: "How do refunds work?"

To chatbot sirf Gemini se guess nahi karega, balki tumhari company ki refund policy PDF padhkar jawab dega.

🎯 Is point par tumhare project me:

- ☒ MERN Backend
- ☒ JWT Authentication
- ☒ Seller Panel
- ☒ Cart
- ☒ Orders
- ☒ AI Chatbot
- ☒ Basic MongoDB RAG

DEBUGGING: CANNOT READ PROPERTIES OF UNDEFINED (READING 'ID')

Ye error bahut clear hai: Cannot read properties of undefined (reading 'id')

Matlab: req.user undefined hai aur tum req.user.id access kar rahe ho.

Sabse Pehla Question:

Tumhare chat route me verifyToken laga hai ya nahi? Mujhe apna chat.routes.js dikhao.

Usme kuch aisa hona chahiye:

```
import express from "express"; import { verifyToken } from "../middlewares/verifyToken.js"; import { chat } from "../controllers/chat.controller.js"; const router = express.Router(); router.post("/chat", verifyToken, chat); export default router;
```

Agar tumhare route me sirf router.post("/chat", chat); hai, to req.user kabhi set hi nahi hoga.

Dusra Check:

Controller me temporarily ye print karo:

```
console.log(req.user);
```

Aur API hit karo. Agar output undefined aata hai, to 100% verifyToken execute nahi ho raha.

Teesra Check:

app.js me route kaise register kiya hai? Example:

```
app.use("/api/chat", chatRoutes);
```

STEP 10: PROFESSIONAL CONTEXT FORMATTER & POPULATE IMPROVEMENT

Perfect! 😊 Ab hum Phase-1 ko Professional banayenge. Ye bahut important step hai.
Abhi tum Gemini ko raw JSON bhej rahe ho:

```
Database Context: { "items":[...] }
```

Industry me aisa nahi karte. Hum pehle data ko human-readable context me convert karte hain.

Step 1: Context Formatter

rag.service.js me direct database object return karne ki jagah readable string return karenge.

Example: Agar cart me ye data hai:

```
[ { "productName":"Laptop", "price":50000, "quantity":2 }, { "productName":"Mouse",  
  "price":800, "quantity":1 } ]
```

To Gemini ko ye mile:

```
Cart Details: 1. Laptop Quantity: 2 Price: ₹50000 2. Mouse Quantity: 1 Price: ₹800
```

Ye prompt engineering ka part hai aur AI isse zyada accurately answer deta hai.

Lekin isse pehle ek improvement (Populate)

Abhi tumhare getContext() me Cart.findOne({ userId }) me sirf productId milta hai. Hume product ka naam aur price bhi chahiye. Isliye:

```
const cartDetail = await Cart.findOne({ userId }) .populate("items.productId"); const  
orderDetail = await Order.find({ userId }) .populate("items.productId");
```

Code:

```
import Cart from '../models/cart.js'; import Product from '../models/product.js'; import  
Order from '../models/order.js'; export const getContext = async (message, userId) => {  
  if (message.toLowerCase().includes("cart")) { const cartDetail = await Cart.findOne({  
    userId }) .populate("items.productId"); return cartDetail; } else if  
    (message.toLowerCase().includes("order")) { const orderDetail = await Order.find({  
      userId }) .populate("items.productId"); return orderDetail; } else if  
      (message.toLowerCase().includes("product")) { const productDetail = await  
        Product.find({ sellerId: userId }); return productDetail; } else { return null; } };
```

Notes on Populate:

Ab productId ke andar poora product object aa jayega.

Pehle:

```
{ "productId": "6899ab12..." }
```

Ab:

```
{ "productId": { "_id": "...", "productName": "Laptop", "productPrice": 50000,  
  "productStock": 10 } }
```

PROFESSIONAL PROMPT ENGINEERING: FORMATCONTEXT()

Ab hum `formatContext()` function banayenge jo MongoDB object ko AI-friendly text me convert karega:

Output Examples:

Agar Cart hai:

```
Cart Details: 1. Laptop Quantity: 2 Price: ₹50000 2. Mouse Quantity: 1 Price: ₹800
```

Agar Orders hain:

```
Your Orders: Order 1 Status: Pending Total: ₹2500 Products: - Shoes x2 - T-Shirt x1
```

Agar Products hain:

```
Your Products: 1. Laptop Price: ₹50000 Stock: 12 2. Mouse Price: ₹800 Stock: 40
```

Phir `chat.service.js` me `JSON.stringify(context)` ki jagah `formatContext(context)` use karenge.



Ye kyun important hai?

Raw JSON vs Readable text: Readable text se AI ka response aur natural aur accurate hota hai.



KAISE PATA CHALEGA KI CONTEXT CART KA HAI YA ORDER KA?

Option 1 (Easy - Recommended):

Function ka parameter hi change kar do: `formatContext(context, message)`

```
if (message.toLowerCase().includes("cart")) { ... }
```

Controller me: `const formattedContext = formatContext(context, message);` (Sabse simple aur readable approach).

Option 2 (Professional):

`getContext()` type aur data dono return kare: `{ type: "cart", data: cartDetail }` (Industry standard).




Learning Decision: Hum Option 1 se hi challenge: `export const formatContext = (context, message) => { ... }`

STEP 11: CHAT.CONTROLLER.JS

```
import { chatWithGemini } from '../services/chat.service.js'; import { formatContext,
getContext } from '../services/rag.service.js'; export const chat = async (req, res) =>
{ try { const { message } = req.body; if (!message) { return res.status(400).json({
success: false, message: "please enter a message" }); } const context = await
getContext(message, req.user.id); const formattedContext = formatContext(context,
message); const result = await chatWithGemini(message, formattedContext); return
res.status(200).json({ success: true, result }); } catch (error) { return
res.status(500).json({ success: false, message: error.message }); } };
```

Ab controller proper architecture follow kar raha hai:



STEP 12: RAG.SERVICES.JS (FIRST IMPLEMENTATION & FEEDBACK)

```
import Cart from '../models/cart.js'; import Product from '../models/product.js'; import
Order from '../models/order.js'; export const getContext = async (message, userId) => {
  if (message.toLowerCase().includes("cart")) { const cartDetail = await Cart.findOne({
    userId }).populate("items.productId"); return cartDetail; } else if
    (message.toLowerCase().includes("order")) { const orderDetail = await Order.find({
      userId }).populate("items.productId"); return orderDetail; } else if
      (message.toLowerCase().includes("product")) { const productDetail = await
        Product.find({ sellerId: userId }); return productDetail; } else { return null; } };
    export const formatContext = (context, message) => { if (!context) { return "No relevant
      database context available."; } else if (message.toLowerCase().includes("cart")) { let
        text = "Cart Details: "; for (const item of context.items) { text += `Product: \${
          item.productId.productName} `; text += `Quantity: \${item.quantity} `; text += `Price:
            \${item.productId.productPrice} `; } return text; } else if
              (message.toLowerCase().includes("order")) { let text = "Your Orders : "; for (const
                order of context) { for (const item of order.items) { text += `Order Status : \${
                  order.status} `; text += `Total Amount : \${order.totalAmount} `; text += `Product: \${
                    item.productId.productName} `; text += `Quantity: \${item.quantity} `; text += `Price:
                      \${item.productId.productPrice} `; } return text; } } else if
                        (message.toLowerCase().includes("product")) { let text = "Your Products : "; for (const
                          product of context) { text += `\${product.productName} `; text += `Price : \${
                            product.productPrice} `; text += `Stock : \${product.productStock} `; } return
                          text; } };
```

DETAILED NOTES & FIXES IDENTIFIED

- ✓ **2. return text galat jagah hai:** Outer loop ke andar return text; hone se sirf pehla order return hota. Sahi tarika: loop ke bahar return text; karna.
- ✓ **3. Products ke beech spacing:** Output me double newline dekar spacing maintain karna.
- ✓ **4. Cart me total dikhana:** Total: ₹\${item.quantity * item.productId.productPrice} add karna.
- ✓ **5. Orders me product total:** Individual product total calculate karna.
- ✓ **6. Empty Products handling:** if (context.length === 0) check lagana.

★ Overall Review:

Part	Rating
getContext()	★★★★★★ (10/10)
populate()	★★★★★★
formatContext()	★★★★★☆ (8.5/10)
Prompt Engineering	★★★★★☆
Overall RAG Phase-1	★★★★★★ (9/10)

🚀 Next Step Suggestions:

- formatContext() ko polish karo (fixes ke sath).
- Conversation History add karo (AI previous questions yaad rakhe).
- Embeddings + ChromaDB add karo (Real RAG).
- Razorpay Payment Integration.


STEP 13: RAG.SERVICES.JS (POLISHED PRODUCTION CODE)

```
import Cart from '../models/cart.js'; import Product from '../models/product.js'; import
Order from '../models/order.js'; export const getContext = async (message, userId) => {
  if (message.toLowerCase().includes("cart")) { const cartDetail = await Cart.findOne({
    userId }).populate("items.productId"); return cartDetail; } else if
    (message.toLowerCase().includes("order")) { const orderDetail = await Order.find({
      userId }).populate("items.productId"); return orderDetail; } else if
      (message.toLowerCase().includes("product")) { const productDetail = await
        Product.find({ sellerId: userId }); return productDetail; } else { return null; } };
  export const formatContext = (context, message) => { if (!context) { return "No relevant
    database context available."; } else if (message.toLowerCase().includes("cart")) { let
      text = "Cart Details: "; if (context.items.length === 0) { return "Your cart is
        empty"; } for (const item of context.items) { text += `Product: \${
          item.productId.productName} `; text += `Quantity: \${item.quantity} `; text += `Price:
            \${item.productId.productPrice} `; text += `Total Amount: \${item.quantity *
              item.productId.productPrice} `; } return text; } else if
              (message.toLowerCase().includes("order")) { let text = "Your Orders : "; if
                (context.length === 0) { return "You don't have any Order"; } let orderNumber = 1; for
                  (const order of context) { text += `Order #\${orderNumber} `; text += `Order Status : \${
                    order.status} `; text += `Total Amount : \${order.totalAmount} `; for (const item of
                      order.items) { text += `Products: `; text += ` - \${item.productId.productName} `; text
                        += `Quantity: \${item.quantity} `; text += `Price: \${item.productId.productPrice} `;
                          text += `Total Price : \${item.quantity * item.productId.productPrice} `; } text +=
                            "----- "; orderNumber++; } return text; } else if
                            (message.toLowerCase().includes("product")) { let text = "Your Products : "; if
                              (context.length === 0) { return "You don't have any Products"; } for (const product of
                                context) { text += ` \${product.productName} `; text += `Price : \${product.productPrice}
                                  `; text += `Stock : \${product.productStock} `; } return text; } else { return "No
                                    relevant database context available."; } };
```

FINAL POLISHING NOTES (CURRENCY & NON-REPETITIVE HEADERS)

- ✓ **1. Currency Symbol:** ₹ $\{item.productId.productPrice\}$ symbol use karna clear representation ke liye.
- ✓ **2. "Products:" Repetition Fix:** Order loop ke bahar text += "Products: "; likhna taaki har item par header repeat na ho.
- ✓ **3. Cart/Product Formatting:** Structured lines with totals for maximum Gemini comprehension.

★ Overall Architecture Flow:





Personalized Response



Final Review Checklist:

Backend: ☒ JWT Authentication, ☒ Product CRUD, ☒ Cart CRUD, ☒ Order Management, ☒ Seller Management

AI: ☒ Gemini Integration, ☒ Context Retrieval, ☒ Prompt Engineering, ☒ Human-readable Context Formatting, ☒

Basic RAG

Code Quality: ☒ Service Separation, ☒ MVC Pattern, ☒ Readable Code, ☒ Good Naming