SAMSUNG ELECTRONICS

Installation Manual for SMDK6410 (Windows Embedded CE 6.0 iROM SD/MMC)

S3C6410

January 29, 2009

(Preliminary) REV 0.0

Important Notice

The information in this publication has been carefully checked and is believed to be entirely accurate at the time of publication. Samsung assumes no responsibility, however, for possible errors or omissions, or for any consequences resulting from the use of the information contained herein.

Samsung reserves the right to make changes in its products or product specifications with the intent to improve function or design at any time and without notice and is not required to update this documentation to reflect such changes.

This publication does not convey to a purchaser of semiconductor devices described herein any license under the patent rights of Samsung or others.

Samsung makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does Samsung assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation any consequential or incidental damages.

"Typical" parameters can and do vary in different applications. All operating parameters, including "Typical" must be validated for each customer application by the customer's technical experts.

Samsung products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, for other applications intended to support or sustain life, or for any other application in which the failure of the Samsung product could create a situation where personal injury or death may occur.

Should the Buyer purchase or use a Samsung product for any such unintended or unauthorized application, the Buyer shall indemnify and hold Samsung and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, expenses, and reasonable attorney fees arising out of, either directly or indirectly, any claim of personal injury or death that may be associated with such unintended or unauthorized use, even if such claim alleges that Samsung was negligent regarding the design or manufacture of said product

S3C6410 RISC Microprocessor
Installation Manual

Samsung Electronics Co., Ltd.
San #24 Nongseo-Dong, Giheung-Gu
Yongin-City Gyeonggi-Do, Korea
446-711

Home Page: http://www.samsungsemi.com/

E-Mail: mobilesol.cs@samsung.com

Printed in the Republic of Korea

Revision History

Revision No	Description of Change	Refer to	Author(s)	Date
0.0	Preliminary draft	-	WinCE Team	2009-01-29

NOTE: **REVISED PARTS ARE WRITTEN IN BLUE.**

Contents

Figures

1 Overview

This Installation Manual guides you to install the Samsung SMDK6410 Windows Embedded CE 6.0 BSP for internalROM(iROM) with SD/MMC.

The manual explains the following topics:

- Copying BSP and Setting up Platform Builder
- Creating a New OS Design
- Building OS Image – Without KITL
- Running NK.nb0 Image
- Fusing WinCE Image on NAND Flash via USB with DNW tools

The detail information of each topic is explained in the following chapters. and about connectivity to platform builder, please read "SMDK6410_Platform_builder_Connectivity.doc" document. This help you how to download and connect your device with OS image to platform builder.

2 Copying BSP and Setting up Visual Studio 2005

In this chapter, you can understand how to copy the Samsung SMDK6410 Windows Embedded CE 6.0 BSP and setup the Platform Builder. There are two distribution types. One is MSI (MS installer) distribution, another one is old-style zip-archived distribution. With MSI, you can just run the MSI file, and then follow the instruction on installer. Here are contents only for old-style zip-archived.

1. To start the BSP installation, Extract zip-archived file into $(WINCEROOT)\PLATFORM. See the picture describes folder structure. In archives, PLATFORM folder has two sub folders. One is SMDK6410, and another one is COMMON/SRC/SOC/S3C6410_SEC_V1.
   For example, copy extracted **SMDK6410_WinCE60_XX_XX\PLATFORM** BSP folder to **X:\WINCE600\PLATFORM** directory on your host PC. Make sure that catalog file and batch file in **X:\WINCE600\PLATFORM\SMDK6410** directory has the same name as that of the BSP, i.e. **SMDK6410.pbcxml** and **SMDK6410.bat**.

Note: About PQOAL & SOC Folder Structure, Please refer to porting guide, If you don't know the difference between PQOAL and non-PQOAL structure, read first porting guide.



Figure 2-1 SMDK6410 BSP Files

2. To start SMDK6410 Windows Embedded CE 6.0 BSP Porting, on your host PC click **Start**, point to **All Programs**, point to **Microsoft Visual Studio 2005** and then click on **Microsoft Visual Studio 2005.** The following window appears on your screen.



Figure 2-2 Visual Studio 2005 Window

3 Creating a New OS Design

In this chapter, you can understand how to create a new OS Design using the Visual Studio 2005.

1. On the **File** menu in the **Visual Studio 2005** window, click **New /Project** as shown in figure 3-1.



Figure 3-1 Creating New Project

2. The following window appears on your screen. Click **OK** button to continue.



Figure 3-2 New Project for WinCE6.0

3. The **Windows Embedded CE 6.0 OS Design Wizard** appears on your screen as below figure. Click **NEXT** button to continue .



Figure 3-3 Windows Embedded CE 6.0 OS Design Wizard

4. The **Board Support Packages (BSPs)** window appears on your screen. Select **SMDK6410: ARMV4I** and then click **Next** button.



Figure 3-4 Windows Embedded CE 6.0 OS Design Wizard – Step 1

5. The **Design Template Wizard** window appears on your screen. Please select **PDA Device** from **Available design templates** list and then click **Next** button.



Figure 3-5 Windows Embedded CE 6.0 OS Design Wizard - Step 2

6. The **Design Template Variants** window appears on your screen. Please select **Mobile Handheld** from **Available design Variants** list and then click **Next** button.



Figure 3-6 Windows Embedded CE 6.0 OS Design Wizard – Step 3

7. The following window appears on your screen. Here you can select the **Application & Media** you want to include in your platform and then click **Next** button.



Figure 3-7 Windows Embedded CE 6.0 OS Design Wizard - Step 4

8. The **Networking & Communications** wizard window appears on your screen. Click **Finish** button.



Figure 3-8 Windows Embedded CE 6.0 OS Design Wizard – Step 5

9. The following window appears on your screen. Please read all the security warnings and then click **Acknowledge** button.

Figure 3-9 Windows Embedded CE 6.0 OS Design Wizard - Step 6

4 Building OS Image – Without KITL

1. In the **Visual Studio 2005** window on your host PC, you can see the new OS Design along with its various sub-directories on the left hand side **Catalog Items View** as shown in figure 4-1. Here, you can choose items what you want to include in your OS design. The chosen items in this instruction are only for sample purpose.



Figure 4-1 Catalog Items View

2. You can change build mode (release or debug mode) as below figures. Select **SMDK6410_ARMV4I Release**.



Figure 4-2 Build Mode in Visual Studio 2005

3. Expand **File Systems and Data Store** node in the Core OS node in **Catalog Items View**, then select some items as shown in the figure below.

   File System-RAM and ROM File System

   Registry Storage-Hive-based Registry(recommended) **or RAM-based Registry**

   Storage Manager-Binary Rom Image file System

   Storage Manager-exFAT File System

   Storage Manager-Storage Manager Control Panel Applet

   Storage Manager-TFAT File System



Figure 4-3 Adding File System and Data store Item to OS Design

4. Expand **Core OS** node in **Catalog Items View window,** then expand **Graphics and Multimedia Technologies.** Select some items as shown in the figure below.

Graphics-Direct3D Mobile

Graphics-DirectDraw (Required for Display Driver)

Media-Video Codecs and Renderers-WMV/MPEG-4 Video Codec (Required for MFC)

Media-Windows Media Player (Required for MFC)

Media-DirectShow Video Capture (Required for Camera)



Figure 4-4 Adding Graphics and Multimedia Technologies Item to OS Design

5. Expand **Core OS Services** node in the Core OS node in **Catalog Items View**, then expand **USB Host Support**. Select some items as shown in the figure below.

USB Function Driver

USB Host Support

USB Human Input Device(HID) Class Driver (recommended)

USB HID Keyboard and Mouse

USB Storage Class Driver



Figure 4-5 Adding Core OS Services Item to OS Design

6. Expand **Applications and Services Development** node in **Catalog Items View window,** then expand **OBEX Server.**

   Select **OBEX File Brower** and **OBEX Inbox**.



Figure 4-6 Adding Core OS Services Item to OS Design

7. Expand **Device Drivers** node in **Catalog Items View window,** then expand **USB Function.** Select Some Items as shown in the figure below.

   USB Function Clients-Mass Storage

   USB Function Clients-serial

   Select **SD Bus Driver in SD**, **SD Memory in SDIO and Windows Embedded CE Test Kit**.



Figure 4-7 Adding Device Drivers Item to OS Design

8. Expand **Device Drivers** node in **Catalog Items View window,** then expand **Networking.** Select **Serial Infrared (SIR)** as shown in the figure below.



Figure 4-8 Adding Networking Item to OS Design

9. On the top of **Visual Studio 2005,** You can see the Project menu as below figure. And then select **Properties...**



Figure 4-12 Properties of OS Design

10. The **OS Design Properties Pages** window appears on your screen. Select **Locale** tab and click **Clear All** button. It clears all the language settings in your platform. Now select **English (United States)** as shown in figure 4-10.



Figure 4-13 Selecting Language in the Property Pages Window

11. Now please uncheck the square boxes **Enable KITL (no IMGNOKITL=1)** in the **Build Options Properties** in **OS Design Properties Pages** window and then click **OK** button.



Figure 4-14 Removing KITL Setting in OS Design Properties Window

12. On the **Build** menu, click **Build OSDesign1** as shown in figure 4-12 to build the **Eboot** and **OS image**.



Figure 4-15 Build OS Design

13. The arrow pointing to the icon in the following figure indicates the **Building process**.



Figure 4-16 Building Process

Note: Building process may take some time depending on your system capability. So, please wait for the build process to be completed. It might take around 1 hour.

14. After completion of build process, following messages appear as shown in figure 4-12. **EBOOT.nb0, EBOOT.bin, STEPLDR./nb0, NK.bin** and **NK.nb0** are now available in **X:\WINCE600\OSDesigns \[OS Design Name]\ [OS Design Name]\RelDir\SMDK6410_ARMV4I_Release** directory.



Figure 4-17 After Building the OS Image

5 Running NK.nb0 Image (Available on the Single-XIP only)

In this chapter, you can understand how to download and run the NK.nb0 image.

1. Before you download the WinCE Image through the USB, you must have **6410_OtgMon.bin** image on your AMD Flash. (The image was already fused on your AMD Flash in the board before release)

2. Configure DIP switch CFG0 on the CPU Board and CFGB1 on the CPU board properly for booting from AMD Flash. (For more information, Read SMDK6410 Board User's Manual in Document folder…)

3. Please install the USB Driver and DNW application on your host PC.

4. After installing the USB driver, run **dnw.exe** on the host PC. The following window appears on your screen.



Figure 5-1 DNW Window

5. On the **Configuration** menu, click **Options** to set the UART/USB options. The following window appears on your screen. Select Baud Rate and COM Port as shown in figure 5-2, enter the download address as (S3C6410 Single:**0x50100000,** S3C6410 XD POP: **0x60100000**) and then click **OK** button.



Figure 5-2 UART/USB Options

6. On the **Serial Port** menu, click **Connect**. Switch **ON** the board and then press any key. The DNW window appears as shown in figure 5-3.



Figure 5-3 DNW Window after Board Power ON

7. Press any key to see USB OTG Mon menu. Now DNW window appears as shown below.



Figure 5-4 USB OTG Mon Menu

8. Enter **0** to download and run the Image on the board. DNW window appears as shown in figure 5-5.



Figure 5-5 Download & Run

9. On the **USB Port** menu, click **Transmit** and the following window appears on your screen. Select **NK.nb0** from **X:\WINCE600\OSDesins\[OS Design name]\[OS Design name]\RelDir\SMDK6410_ARMV4I_Release** directory and then click **Open** button.



Figure 5-6 Selecting NK.nb0 for Download

10. Once download begins, a download status bar appears on your screen as shown in figure 5-7. After **NK.nb0** download is over, **Windows Embedded CE 6.0** boots on the target Board



Figure 5-7 Downloading Status of NK.nb0

6 Fusing WinCE Image to SD/MMC via USB with DNW

In this chapter, you can understand how to fuse WinCE image to NAND Flash via USB with DNW

1. First of all, a SD card or MMC should be inserted in the SDMMC slot.

2. Before you download the WinCE Image through the USB, you must have **6410_OtgMon.bin** image on your AMD Flash. (The image was already fused on your AMD Flash in the board before release)

3. Configure switches on the SMDK Board properly for booting from AMD Flash. (For more information, Read SMDK6410 Board User's Manual in Document folder…)

4. Please install the USB Driver and DNW application on your host PC.

5. Run **dnw.exe** on the host PC. The following window appears on your screen.

Figure 6-1 DNW Window

6. On the **Configuration** menu in the DNW window, click **Options** to set the UART/USB options. The following window appears on your screen. Select Baud Rate and COM Port as shown in figure 7-4, enter the download address as (S3C6410 Single:**0x50030000**, S3C6410 XD POP:**0x60030000**) that is preconfigured address in SMDK6410\inc\image_cfg.h, SMDK6410\inc\image_cfg.inc, EBOOT\eboot.bib for Bootloader and then click **OK** button.



Figure 6-2 UART/USB Options

7. On the **Serial Port** menu, click **Connect**. Switch **ON** the board and then press any key. The DNW window appears as shown in figure 6-3.



Figure 6-3 DNW Window after Board Power ON

8. Press any key to see USB OTG Mon menu. Now DNW window appears as shown below.



Figure 6-4 usb OTG Mon menu

9. Enter **0** to download and run the Image on the board. DNW window appears as shown in figure 6-5.



Figure 6-5 Download & Run

10. On the **USB Port** menu, click **Transmit** and the following window appears on your screen. Select **IROM_SDMMCBoot.nb0** file from **X:\WINCE600\OSDesigns\[OSDesign name] \[OSDesign name]\RelDir\SMDK6410_ARMV4I _Release** directory and then click **Open** button.



Figure 6-6 Selecting IROM_SDMMCBoot.nb0 for Download

11. As soon as **IROM_SDMMCBoot.nb0** download is over, the following messages appear in the DNW window**.** This message can differ from yours, if you had changed some message option in EBOOT code. and different Bootloader version also can show you different messages.



Figure 6-7 After IROM_SDMMCBoot.nb0 Download

12. Please hit the **SPACE BAR** key to view the current Ethernet Boot Loader Configuration. Then there will be the Main Menu to set some KITL option, and Flash Fusing Options. This menu is changed from previous version to support various connection options.



Figure 6-8 Ethernet Boot Loader Configuration - Before

13. Configure the Ethernet Boot loader as follows by entering the respective options:

- Enter **[0]** to enter SMDK6410 Board **IP address**
- Enter **[1]** to enter SMDK6410 Board **Subnet mask**
- Enter **[2]** to change **DHCP mode** to **DISABLED**. Default value is ENABLED**.**
- Enter **[3]** to enter SMDK6410 Board **MAC Address.**
- Enter **[5]** to change **Startup action after Boot Delay** to **Launch Existing OS image from Storage**. Default value is Download New image
- Enter **[T]** to change **Download Target** to **Write to SDMMC Storage**. Default value is Download to RAM.
- Enter **[K]** to change **KITL Configuration to DISABLED**. Default value is ENABLED**.**
- Enter **[W]** to **Write Configuration Right Now**
- **Keep Boot Device as USB_DNW. Default value is** USB_DNW



Figure 6-9 Ethernet Boot Loader Configuration - After

14. Change the **IP address** and **Subnet Mask** manually on your **Host PC** in **TCP/IP properties** before you start to download the OS image to the target board. For example, if the Target Board IP Address is 192.168.1.200, then set Host PC IP address as 192.168.1.100. Set the subnet mask as 255.255.255.0 **(You can skip this step for downloading via USB)**

And **then Enter [D]** for download image. If so, You can see the below window.



Figure 6-10 Preparing to download image through USB

15. On the **USB Port** menu click **UBOOT** and the following window appears on your screen. Select **IROM_SDMMCStepldr.nb0** from **X:\WINCE600\OSDesigns\[OSDesign name]\[OSDesign name]\ RelDir\SMDK6410_ARMV4I _Release** directory and then click **Open** button.



Figure 6-11 Selecting IROM_SDMMCStepldr.nb0 for Download

16. You can see the following messages on the DNW window after **IROM_SDMMCStepldr.nb0** download is over.



Figure 6-12 Messages via UART Port after IROM_SDMMCStepldr.nb0 Download

17. Reset the board. DNW window appears as shown in figure 6-13.



Figure 6-13 DNW Window after reset

18. On the **USB Port** menu, click **Transmit** and the following window appears on your screen. Select **IROM_SDMMCBoot.nb0** file from **X:\WINCE600\OSDesigns\[OSDesign name] \[OSDesign name]\RelDir\SMDK6410_ARMV4I _Release** directory and then click **Open** button.



Figure 6-14 Selecting IROM_SDMMCBoot.nb0 for Download

19. As soon as **IROM_SDMMCBoot.nb0** download is over, the following messages appear in the DNW window.



Figure 6-15 After IROM_SDMMCBoot.nb0 Download

20. Please hit the **SPACE BAR** key to view the current Ethernet Boot Loader Configuration.



Figure 6-16 Ethernet Boot Loader Configuration

21. Enter **[D]** to **Download image,** the following messages appear in the DNW window.



Figure 6-17 Preparing to download image through USB

22. On the **USB Port** menu click **UBOOT** and the following window appears on your screen. Select **IROM_SDMMCBoot.bin** from **X:\WINCE600\OSDesigns\[OSDesign name]\[OSDesign name]\ RelDir\SMDK6410_ARMV4I _Release** directory and then click **Open** button.



Figure 6-18 Selecting IROM_SDMMCBoot.bin for Download

23. You can see the following messages on the DNW window after **IROM_SDMMCBoot.bin** download.



Figure 6-19 Messages via UART Port after IROM_SDMMCBoot.bin Download

24. Reset the board. DNW window appears as shown in figure 6-20.



Figure 6-20 DNW Window after reset

25. On the **USB Port** menu, click **Transmit** and the following window appears on your screen. Select **IROM_SDMMCBoot.nb0** file from **X:\WINCE600\OSDesigns\[OSDesign name] \[OSDesign name]\RelDir\SMDK6410_ARMV4I _Release** directory and then click **Open** button.



Figure 6-21 Selecting IROM_SDMMCBoot.nb0 for Download

26. As soon as **IROM_SDMMCBoot.nb0** download is over, the following messages appear in the DNW window.



Figure 6-22 After IROM_SDMMCBoot.nb0 Download

27. Please hit the **SPACE BAR** key to view the current Ethernet Boot Loader Configuration.



Figure 6-23 Ethernet Boot Loader Configuration

28. Enter **[D]** to **Download image,** the following messages appear in the DNW window.



Figure 6-24 Preparing to download image through USB

29. On the **USB Port** menu click **UBOOT** and the following window appears on your screen. Select **NK.bin** from **X:\WINCE600\OSDesigns\[OSDesign name]\[OSDesign name]\ RelDir\SMDK6410_ARMV4I _Release** directory and then click **Open** button.

- Single-XIP (no IMGMULTIXIP) : Select NK.bin
- Multiple-XIP (IMGMULTIXIP=1) : Select chain.lst



Figure 6-25 Selecting NK.bin for Download (no IMGMULTIXIP)



Figure 6-26 Selecting chain.lst for Download (IMGMULTIXIP=1)

30. You can see the following messages on the DNW window after **NK.bin(Chain.lst)** download.



Figure 6-27 Messages via UART Port during NK.bin Download



Figure 6-28 Messages via UART Port during chain.lst Download (IMGMULTIXIP=1)

31. After **NK.bin** download is over, **Windows Embedded CE 6.0** boots on the target Board.

32. Power **OFF** the board and Configure jumpers and switches on the CPU Board and the BASE board properly for SDMMC iROM boot. (For more information about board configuration, Read SMDK6410 Board User's Manual)

On CPU board:

CFG3		1	2	3	4	5	6
Boot Mode	**iROM boot**	**OFF**	**ON**	**ON**	**ON**	**ON**	**ON**

On Base Board:

SDMMC channel 1 :

Description	J8	J7	J6
SDMMC1 iROM boot	**2-3**	**2-3**	**2-3**

SDMMC channel 0 :

Description	J8	J7	J6
SDMMC0 iROM boot	1-2	1-2	1-2

33. Power **ON** the board. You can see **Windows Embedded CE 6.0** boots on the target board.

7 Building and Running OS Image – With KITL

In this chapter, you can understand how to build, download and run the OS image with KITL. For each Transport media type, please read SMDK6410_Platform_Build_Connectivity.doc. Please Refer to MSDN how to use KITL, download images, connecti to PlatformBuilder. This document will not cover common usage.

1. To enable KITL, on the left side of **Visual Studio 2005,** You can see the Solution Explorer as below figure. And then right click on OSDesign1 and select **Properties**.



Figure 7-1 OSDesign Properties

2. OSDesign1 Property Pages winow appears on your screen. Check square **boxes Enable kernel debugger(no IMGNODEBUGGER=1)** and **Enable KITL (no IMGNOKITL=1)** in the **Build Options** and then click **OK** button.



Figure 7-2 Property Pages for KITL

7.1 USB Serial KITL Connection with USB DNW Download

There is nothing to change code for using USB Serial KITL. KITL transport selection is configured in Bootloader Configuration Argument and these values will be sent to OAL. OAL will wait for connection from Platform Builder with proper KITL transport setting. The image building is exactly same to non-KITL image except for disabling IMG_NOKITL. The connection procedure also is almost same through all each supported connection media, USB Serial, USB RNDIS, Ethernet.

1. On the **Build** menu, click **Build OSDesign1** as shown in figure 7-16 to build the **Eboot** and **OS image.**



Figure 7-3 Build OSDesign

Note: Building process may take some time depending on your system capability. So, please wait for the build process to be completed. It might take around 1 hour.

2. After completion of build process, **IROM_SDMMCBoot.nb0, IROM_SDMMCBoot.bin, IROM_SDMMCStepldr.bin, IROM_SDMMCStepldr.nb0, NK.bin** and **NK.nb0** are now available in **X:\WINCE600\OSDesigns \[OS Design Name]\ [OS Design Name]\RelDir\smdk6410_ARMV4I_Release** directory.

3. Please install the USB Driver and DNW application on your host PC if it is not installed before.

4. Please refer to chapter 6 Fusing WinCE image to SMC via USB in this documentation. And fuse to SMC along to Steps in Chapter 6.

5. Reset the board. DNW window appears as shown in figure 7-17.



Figure 7-4 DNW Window after reset

6. On the **USB Port** menu, click **Transmit** and the following window appears on your screen. Select **IROM_SDMMCBoot.nb0** file from **X:\WINCE600\OSDesigns\[OSDesign name] \[OSDesign name]\RelDir\smdk6410_ARMV4I _Release** directory and then click **Open** button.



Figure 7-5 Selecting IROM_SDMMCBoot.nb0 for Download

7. As soon as **IROM_SDMMCBoot.nb0** download is over, the following messages appear in the DNW window**.**



Figure 7-6 After IROM_SDMMCBoot.nb0 Download

8. Please hit the **SPACE BAR** key to view the current Ethernet Boot Loader Configuration. Configure the Ethernet Boot Loader as follows by entering the respective options:

- Keep **KITL Configuration:** ENABLED
- Enter **[L]** to **LAUNCH existing Boot Media image. This assume the user already fusing KITL enabled image to NAND storage.**



Figure 7-7 Ethernet Boot Loader Configuration

9. On the **Target** menu in the **Visual Studio 2005** window, click **Connectivity Options...** as shown below. **Target Device Connectivity Options** window appears on your screen as shown in figure 7-22.



Figure 7-8 Target Connectivity Option

10. On the **Target Device Connectivity Options** window, select **USB** option from **Transport** drop down menu box.



Figure 7-9 Target Device Connectivity Options Window Before Transport Select

11. Configure the **KdStub** option in **Debugger** drop down menu box.



Figure 7-10 Target Device Connectivity Options Window After Transport Select

12. On the **Target** menu in **Visual Studio 2005** window, click **Attach Device** as shown below.



Figure 7-11 Attach Device

13. You can see the following messages on the DNW window. With DNW. the system will run in polling mode to connect through KITL



Figure 7-12 Messages via UART Port

14. **Windows Embedded CE 6.0** boots on the target board and platform builder window appears as shown below.



Figure 7-13 Visual Studio 2005 Window after USB Serial KITL connected

8 Appendix I – DIP Switch Settings for Booting Mode

Table 8-1 and 8-2 explains the DIP Switch configuration on the SMDK6410 board for Booting mode.

AMD NOR/SROM Boot

Description	CFG3[6:1]				
	[6]	[5]	[4]	[3]	[2]
NOR Boot (8bit Data Width)	Don't Care	OFF	**ON**	OFF	OFF
NOR Boot (16bit Data Width)	Don't Care	OFF	**ON**	OFF	**ON**

Table 8-1 DIP Switch setting for AMD Flash Boot (NOR Flash)

NAND Boot

Description	CFG3[6:1]				
	[6]	[5]	[4]	[3]	[2]
Normal NAND, 512-byte page, 3 addr. Cycle	**ON**	OFF	OFF	OFF	OFF
Normal NAND, 512-byte page, 4 addr. Cycle	**ON**	OFF	OFF	OFF	**ON**
Advanced NAND, 2K-byte page, 4 addr. Cycle	**ON**	OFF	OFF	**ON**	OFF
Advanced NAND, 2K-byte page, 5 addr. Cycle	**ON**	OFF	OFF	**ON**	**ON**

Description	CFGB3[4:1]			
	[4]	[3]	[2]	[1]
Connected NandFlash to Xm0CSn2	OFF	OFF	OFF	**ON**
Connected XD Picture Card to Xm0CSn2	OFF	OFF	**ON**	OFF

Table 8-2 DIP Switch setting for NAND Flash Boot

Note: For more information about board configuration, Please check again SMDK6410 Board Manual in DOC folder. For each board revision, these DIP switch's and Jumper's mapping can change.