

第 4 章 上下文无关语言

(Part 2 of 2)

王 鑫

wangx@tju.edu.cn

天津大学 智能与计算学部



Outline

- 1 Context-Free Grammars
- 2 Pushdown Automata
- 3 Non-Context-Free Languages

Context-Free Languages

regular languages 正则语言

- finite automata: DFA / NFA
- regular expressions

some simple languages, such as $\{0^n 1^n \mid n \geq 0\}$, are **not** regular languages.

Context-Free Languages

regular languages 正则语言

- finite automata: DFA / NFA
- regular expressions

some simple languages, such as $\{0^n 1^n \mid n \geq 0\}$, are **not** regular languages.

context-free languages 上下文无关语言

- pushdown automata 下推自动机
- first used in the study of human languages
- in the specification and compilation of programming languages
 - **parser**
 - the construction of a parser from a context-free grammar

Outline

1 Context-Free Grammars

- Formal Definition of a Context-Free Grammar
- Examples of a Context-Free Grammar
- Designing Context-Free Grammars
- Ambiguity
- Chomsky Normal Form

2 Pushdown Automata

3 Non-Context-Free Languages

Outline

1 Context-Free Grammars

2 Pushdown Automata

- Formal Definition of a Pushdown Automaton
- Examples of Pushdown Automata
- Equivalence With Context-Free Grammars

3 Non-Context-Free Languages

Pushdown Automata 下推自动机

Pushdown Automata (PDA): we introduce a new type of computational model.

- like NFA but have an extra component called a ***stack***.

Pushdown Automata 下推自动机

Pushdown Automata (PDA): we introduce a new type of computational model.

- like NFA but have an extra component called a ***stack***.
- the stack provides additional memory beyond the finite amount available in the control.

Pushdown Automata 下推自动机

Pushdown Automata (PDA): we introduce a new type of computational model.


- like NFA but have an extra component called a **stack**.
- the stack provides additional memory beyond the finite amount available in the control.
- the stack allows PDA to recognize some nonregular languages.

PDA are equivalent in power to CFG

- two options for proving that a language is context free
 - give either a CFG generating it (generator)
 - or a PDA recognizing it (recognizer)

Pushdown Automata 下推自动机


DFA/NFA vs. PDA




Schematic of DFA/NFA

Pushdown Automata 下推自动机

DFA/NFA vs. PDA



Schematic of DFA/NFA



Schematic of PDA

Pushdown Automata 下推自动机

PDA can write symbols on the stack and read them back later.

Writing a symbol “**pushes down**” all the other symbols on the stack.

- all access to the stack may be done only at the top: “last in, first out”
- **pushing**: writing a symbol on the top of the stack
- **popping**: removing a symbol on the top of the stack

A stack can hold an unlimited amount of information.

the language $\{0^n 1^n \mid n \geq 0\}$

- a DFA/NFA is unable to recognize it.
- A PDA is able to recognize it.

Pushdown Automata 下推自动机

Deterministic and nondeterministic PDA are **not** equivalent in power.

- Nondeterministic PDA recognize certain languages that **no** deterministic PDA can recognize.
- Recall that DFA and NFA do recognize the same class of languages.
- So the pushdown automata situation is different.
- We focus on nondeterministic PDA because these automata are equivalent in power to CFG.

Formal Definition of a Pushdown Automaton

定义 (PDA (下推自动机))

Formal Definition of a Pushdown Automaton

定义 (PDA (下推自动机))

A ***pushdown automaton*** (PDA) is a 6-tuple $(Q, \Sigma, \Gamma, \delta, q_0, F)$, where

Formal Definition of a Pushdown Automaton

定义 (PDA (下推自动机))

A **pushdown automaton** (PDA) is a 6-tuple $(Q, \Sigma, \Gamma, \delta, q_0, F)$, where

- 1 Q is a finite set of **states**,

Formal Definition of a Pushdown Automaton

定义 (PDA (下推自动机))

A **pushdown automaton** (PDA) is a 6-tuple $(Q, \Sigma, \Gamma, \delta, q_0, F)$, where

- 1 Q is a finite set of **states**,
- 2 Σ is a finite set called the **input alphabet**,

Formal Definition of a Pushdown Automaton

定义 (PDA (下推自动机))

A **pushdown automaton** (PDA) is a 6-tuple $(Q, \Sigma, \Gamma, \delta, q_0, F)$, where

- 1 Q is a finite set of **states**,
- 2 Σ is a finite set called the **input alphabet**,
- 3 Γ is a finite set called the **stack alphabet**,

Formal Definition of a Pushdown Automaton

定义 (PDA (下推自动机))

A **pushdown automaton** (PDA) is a 6-tuple $(Q, \Sigma, \Gamma, \delta, q_0, F)$, where

- ① Q is a finite set of **states**,
- ② Σ is a finite set called the **input alphabet**,
- ③ Γ is a finite set called the **stack alphabet**,
- ④ $\delta : Q \times \Sigma_{\varepsilon} \times \Gamma_{\varepsilon} \rightarrow \mathcal{P}(Q \times \Gamma_{\varepsilon})$ is the **transition function**,

Formal Definition of a Pushdown Automaton

定义 (PDA (下推自动机))

A **pushdown automaton** (PDA) is a 6-tuple $(Q, \Sigma, \Gamma, \delta, q_0, F)$, where

- 1 Q is a finite set of **states**,
- 2 Σ is a finite set called the **input alphabet**,
- 3 Γ is a finite set called the **stack alphabet**,
- 4 $\delta : Q \times \Sigma_{\varepsilon} \times \Gamma_{\varepsilon} \rightarrow \mathcal{P}(Q \times \Gamma_{\varepsilon})$ is the **transition function**,
- 5 $q_0 \in Q$ is the **start state**, and

Formal Definition of a Pushdown Automaton

定义 (PDA (下推自动机))

A **pushdown automaton** (PDA) is a 6-tuple $(Q, \Sigma, \Gamma, \delta, q_0, F)$, where

- 1 Q is a finite set of **states**,
- 2 Σ is a finite set called the **input alphabet**,
- 3 Γ is a finite set called the **stack alphabet**,
- 4 $\delta : Q \times \Sigma_{\varepsilon} \times \Gamma_{\varepsilon} \rightarrow \mathcal{P}(Q \times \Gamma_{\varepsilon})$ is the **transition function**,
- 5 $q_0 \in Q$ is the **start state**, and
- 6 $F \subseteq Q$ is the set of **accept states**.

Formal Definition of Computation for a PDA

A PDA $M = (Q, \Sigma, \Gamma, \delta, q_0, F)$ computes as follows.

- It accepts input w if w can be written as $w = a_1 a_2 \cdots a_m$, where $a_i \in \Sigma_\varepsilon$ and

Formal Definition of Computation for a PDA

A PDA $M = (Q, \Sigma, \Gamma, \delta, q_0, F)$ computes as follows.

- It accepts input w if w can be written as $w = a_1 a_2 \cdots a_m$, where $a_i \in \Sigma_\varepsilon$ and
- sequences of states $r_0, r_1, \dots, r_m \in Q$ and strings $s_0, s_1, \dots, s_m \in \Gamma^*$ exist that satisfy the following three conditions.

Formal Definition of Computation for a PDA

A PDA $M = (Q, \Sigma, \Gamma, \delta, q_0, F)$ computes as follows.

- It accepts input w if w can be written as $w = a_1 a_2 \cdots a_m$, where $a_i \in \Sigma_\varepsilon$ and
- sequences of states $r_0, r_1, \dots, r_m \in Q$ and strings $s_0, s_1, \dots, s_m \in \Gamma^*$ exist that satisfy the following three conditions.
- The strings s_i represent the sequence of stack contents that M has on the accepting branch of the computation.

Formal Definition of Computation for a PDA

A PDA $M = (Q, \Sigma, \Gamma, \delta, q_0, F)$ computes as follows.

- It accepts input w if w can be written as $w = a_1 a_2 \cdots a_m$, where $a_i \in \Sigma_\varepsilon$ and
- sequences of states $r_0, r_1, \dots, r_m \in Q$ and strings $s_0, s_1, \dots, s_m \in \Gamma^*$ exist that satisfy the following three conditions.
- The strings s_i represent the sequence of stack contents that M has on the accepting branch of the computation.
 - ① $r_0 = q_0$ and $s_0 = \varepsilon$

Formal Definition of Computation for a PDA

A PDA $M = (Q, \Sigma, \Gamma, \delta, q_0, F)$ computes as follows.

- It accepts input w if w can be written as $w = a_1 a_2 \cdots a_m$, where $a_i \in \Sigma_\varepsilon$ and
- sequences of states $r_0, r_1, \dots, r_m \in Q$ and strings $s_0, s_1, \dots, s_m \in \Gamma^*$ exist that satisfy the following three conditions.
- The strings s_i represent the sequence of stack contents that M has on the accepting branch of the computation.
 - ① $r_0 = q_0$ and $s_0 = \varepsilon$
 - ② For $i = 0, \dots, m-1$, we have $(r_{i+1}, b) \in \delta(r_i, a_{i+1}, a)$, where $s_i = at$ and $s_{i+1} = bt$ for some $a, b \in \Gamma_\varepsilon$ and $t \in \Gamma^*$

Formal Definition of Computation for a PDA

A PDA $M = (Q, \Sigma, \Gamma, \delta, q_0, F)$ computes as follows.

- It accepts input w if w can be written as $w = a_1 a_2 \cdots a_m$, where $a_i \in \Sigma_\varepsilon$ and
- sequences of states $r_0, r_1, \dots, r_m \in Q$ and strings $s_0, s_1, \dots, s_m \in \Gamma^*$ exist that satisfy the following three conditions.
- The strings s_i represent the sequence of stack contents that M has on the accepting branch of the computation.
 - ① $r_0 = q_0$ and $s_0 = \varepsilon$
 - ② For $i = 0, \dots, m-1$, we have $(r_{i+1}, b) \in \delta(r_i, a_{i+1}, a)$, where $s_i = at$ and $s_{i+1} = bt$ for some $a, b \in \Gamma_\varepsilon$ and $t \in \Gamma^*$
 - ③ $r_m \in F$

Examples of Pushdown Automata

例 (PDA M_1 recognizes the language $\{0^n 1^n \mid n \geq 0\}$)

Let M_1 be $(Q, \Sigma, \Gamma, \delta, q_1, F)$, where

$$Q = \{q_1, q_2, q_3, q_4\}$$

$$\Sigma = \{0, 1\}$$

$$\Gamma = \{0, \$\}$$

$$F = \{q_1, q_4\}, \text{ and}$$

δ is given by the following table, wherein blank entries signify \emptyset

Examples of Pushdown Automata

例 (PDA M_1 recognizes the language $\{0^n 1^n \mid n \geq 0\}$)

Let M_1 be $(Q, \Sigma, \Gamma, \delta, q_1, F)$, where

$$Q = \{q_1, q_2, q_3, q_4\}$$

$$\Sigma = \{0, 1\}$$

$$\Gamma = \{0, \$\}$$

$$F = \{q_1, q_4\}, \text{ and}$$

δ is given by the following table, wherein blank entries signify \emptyset

Input:	0			1			ϵ		
Stack:	0	\$	ϵ	0	\$	ϵ	0	\$	ϵ
q_1									$\{(q_2, \$)\}$
q_2			$\{(q_2, 0)\}$			$\{(q_3, \epsilon)\}$			
q_3						$\{(q_3, \epsilon)\}$			$\{(q_4, \epsilon)\}$
q_4									

Examples of Pushdown Automata

例 (PDA M_1 recognizes the language $\{0^n 1^n \mid n \geq 0\}$)

Let M_1 be $(Q, \Sigma, \Gamma, \delta, q_1, F)$, where

$$Q = \{q_1, q_2, q_3, q_4\}$$

$$\Sigma = \{0, 1\} \quad \Gamma = \{0, \$\} \quad F = \{q_1, q_4\}, \text{ and}$$

State diagram for the PDA M_1

Examples of Pushdown Automata


例 (PDA M_1 recognizes the language $\{0^n 1^n \mid n \geq 0\}$)

Let M_1 be $(Q, \Sigma, \Gamma, \delta, q_1, F)$, where

$$Q = \{q_1, q_2, q_3, q_4\}$$

$$\Sigma = \{0, 1\} \quad \Gamma = \{0, \$\} \quad F = \{q_1, q_4\}, \text{ and}$$

State diagram for the PDA M_1



Examples of Pushdown Automata

例 (PDA M_2)

A pushdown automaton that recognizes the language


$$\{a^i b^j c^k \mid i, j, k \geq 0 \text{ and } i = j \text{ or } i = k\}$$

Examples of Pushdown Automata

例 (PDA M_2)

A pushdown automaton that recognizes the language

$$\{a^i b^j c^k \mid i, j, k \geq 0 \text{ and } i = j \text{ or } i = k\}$$



Examples of Pushdown Automata

例 (PDA M_3)

A pushdown automaton that recognizes the language


$$\{ww^R \mid w \in \{0,1\}^*\}$$

Examples of Pushdown Automata

例 (PDA M_3)

A pushdown automaton that recognizes the language

$$\{ww^R \mid w \in \{0,1\}^*\}$$



Equivalence With Context-Free Grammars

定理

A language is context free if and only if some pushdown automaton recognizes it.

Equivalence With Context-Free Grammars

定理

A language is context free if and only if some pushdown automaton recognizes it.

引理

If a language is context free, then some pushdown automaton recognizes it.

Equivalence With Context-Free Grammars

定理

A language is context free if and only if some pushdown automaton recognizes it.

引理

If a language is context free, then some pushdown automaton recognizes it.

引理

If a pushdown automaton recognizes some language, then it is context free.

Equivalence With Context-Free Grammars


推论

Every regular language is context free.

Equivalence With Context-Free Grammars

推论

Every regular language is context free.



Outline

- 1 Context-Free Grammars
- 2 Pushdown Automata
- 3 Non-Context-Free Languages
 - The Pumping Lemma for Context-Free Languages

The Pumping Lemma for Context-Free Languages

定理 (Pumping lemma for context-free languages 泵引理)

If A is a context-free language, then there is a number p (the pumping length) where, if s is any string in A of length at least p , then s may be divided into five pieces, $s = uvxyz$, satisfying the conditions:

The Pumping Lemma for Context-Free Languages

定理 (Pumping lemma for context-free languages 泵引理)

If A is a context-free language, then there is a number p (the pumping length) where, if s is any string in A of length at least p , then s may be divided into five pieces, $s = uvxyz$, satisfying the conditions:

- 1 *for each $i \geq 0$, $uv^i xy^i z \in A$,*

The Pumping Lemma for Context-Free Languages

定理 (Pumping lemma for context-free languages 泵引理)

If A is a context-free language, then there is a number p (the pumping length) where, if s is any string in A of length at least p , then s may be divided into five pieces, $s = uvxyz$, satisfying the conditions:

- ① *for each $i \geq 0$, $uv^i xy^i z \in A$,*
- ② *$|vy| > 0$, and*

The Pumping Lemma for Context-Free Languages

定理 (Pumping lemma for context-free languages 泵引理)

If A is a context-free language, then there is a number p (the pumping length) where, if s is any string in A of length at least p , then s may be divided into five pieces, $s = uvxyz$, satisfying the conditions:

- ① *for each $i \geq 0$, $uv^i xy^i z \in A$,*
- ② *$|vy| > 0$, and*
- ③ *$|vxy| \leq p$.*