

5

SQL: QUERIES, CONSTRAINTS, TRIGGERS

Exercise 5.1 Consider the following relations:

```
Student(snum: integer, sname: string, major: string, level: string, age: integer)
Class(name: string, meets_at: string, room: string, fid: integer)
Enrolled(snum: integer, cname: string)
Faculty(fid: integer, fname: string, deptid: integer)
```

The meaning of these relations is straightforward; for example, Enrolled has one record per student-class pair such that the student is enrolled in the class.

Write the following queries in SQL. No duplicates should be printed in any of the answers.

1. Find the names of all Juniors (level = JR) who are enrolled in a class taught by I. Teach.
2. Find the age of the oldest student who is either a History major or enrolled in a course taught by I. Teach.
3. Find the names of all classes that either meet in room R128 or have five or more students enrolled.
4. Find the names of all students who are enrolled in two classes that meet at the same time.

5. Find the names of faculty members who teach in every room in which some class is taught.
6. Find the names of faculty members for whom the combined enrollment of the courses that they teach is less than five.
7. For each level, print the level and the average age of students for that level.
8. For all levels except JR, print the level and the average age of students for that level.
9. For each faculty member that has taught classes only in room R128, print the faculty member's name and the total number of classes she or he has taught.
10. Find the names of students enrolled in the maximum number of classes.
11. Find the names of students not enrolled in any class.
12. For each age value that appears in Students, find the level value that appears most often. For example, if there are more FR level students aged 18 than SR, JR, or SO students aged 18, you should print the pair (18, FR).

Answer 5.1 The answers are given below:

1.


```
SELECT DISTINCT S.Sname
FROM   Student S, Class C, Enrolled E, Faculty F
WHERE  S.snum = E.snum AND E.cname = C.name AND C.fid = F.fid AND
       F.fname = 'I.Teach' AND S.level = 'JR'
```
2.


```
SELECT MAX(S.age)
FROM   Student S
WHERE  (S.major = 'History')
       OR S.snum IN (SELECT E.snum
                     FROM   Class C, Enrolled E, Faculty F
                     WHERE  E.cname = C.name AND C.fid = F.fid
                           AND F.fname = 'I.Teach' )
```
3.


```
SELECT  C.name
FROM    Class C
WHERE   C.room = 'R128'
       OR C.name IN (SELECT  E.cname
                     FROM    Enrolled E
                     GROUP BY E.cname
                     HAVING  COUNT (*) >= 5)
```

4.

```
SELECT DISTINCT S.sname
FROM   Student S
WHERE  S.snum IN (SELECT E1.snum
                  FROM   Enrolled E1, Enrolled E2, Class C1, Class C2
                  WHERE  E1.snum = E2.snum AND E1.cname <> E2.cname
                  AND    E1.cname = C1.name
                  AND    E2.cname = C2.name AND C1.meets_at = C2.meets_at)
```
5.

```
SELECT DISTINCT F.fname
FROM   Faculty F
WHERE  NOT EXISTS (( SELECT *
                    FROM   Class C )
                  EXCEPT
                  (SELECT C1.room
                   FROM   Class C1
                   WHERE  C1.fid = F.fid ))
```
6.

```
SELECT  DISTINCT F.fname
FROM    Faculty F
WHERE   5 > (SELECT COUNT (E.snum)
            FROM    Class C, Enrolled E
            WHERE   C.name = E.cname
            AND     C.fid = F.fid)
```
7.

```
SELECT  S.level, AVG(S.age)
FROM    Student S
GROUP BY S.level
```
8.

```
SELECT  S.level, AVG(S.age)
FROM    Student S
WHERE   S.level <> 'JR'
GROUP BY S.level
```
9.

```
SELECT  F.fname, COUNT(*) AS CourseCount
FROM    Faculty F, Class C
WHERE   F.fid = C.fid
GROUP BY F.fid, F.fname
HAVING  EVERY ( C.room = 'R128' )
```
10.

```
SELECT  DISTINCT S.sname
FROM    Student S
WHERE   S.snum IN (SELECT  E.snum
                  FROM    Enrolled E
                  GROUP BY E.snum)
```

```

HAVING COUNT (*) >= ALL (SELECT COUNT (*)
                           FROM   Enrolled E2
                           GROUP BY E2.snum ))

11.  SELECT DISTINCT S.sname
      FROM   Student S
      WHERE  S.snum NOT IN (SELECT E.snum
                           FROM   Enrolled E )

12.  SELECT  S.age, S.level
      FROM    Student S
      GROUP BY S.age, S.level,
      HAVING  S.level IN (SELECT  S1.level
                        FROM      Student S1
                        WHERE     S1.age = S.age
                        GROUP BY  S1.level, S1.age
                        HAVING    COUNT (*) >= ALL (SELECT  COUNT (*)
                                                    FROM      Student S2
                                                    WHERE   s1.age = S2.age
                                                    GROUP BY  S2.level, S2.age))

```

Exercise 5.2 Consider the following schema:

```

Suppliers(sid: integer, sname: string, address: string)
Parts(pid: integer, pname: string, color: string)
Catalog(sid: integer, pid: integer, cost: real)

```

The Catalog relation lists the prices charged for parts by Suppliers. Write the following queries in SQL:

1. Find the *pnames* of parts for which there is some supplier.
2. Find the *snames* of suppliers who supply every part.
3. Find the *snames* of suppliers who supply every red part.
4. Find the *pnames* of parts supplied by Acme Widget Suppliers and no one else.
5. Find the *sids* of suppliers who charge more for some part than the average cost of that part (averaged over all the suppliers who supply that part).
6. For each part, find the *sname* of the supplier who charges the most for that part.
7. Find the *sids* of suppliers who supply only red parts.
8. Find the *sids* of suppliers who supply a red part and a green part.

9. Find the *sids* of suppliers who supply a red part or a green part.
10. For every supplier that only supplies green parts, print the name of the supplier and the total number of parts that she supplies.
11. For every supplier that supplies a green part and a red part, print the name and price of the most expensive part that she supplies.

Answer 5.2 The answers are given below:

1.


```
SELECT DISTINCT P.pname
FROM   Parts P, Catalog C
WHERE  P.pid = C.pid
```
2.


```
SELECT S.sname
FROM   Suppliers S
WHERE  NOT EXISTS (( SELECT P.pid
                     FROM   Parts P )
                  EXCEPT
                  ( SELECT C.pid
                    FROM   Catalog C
                    WHERE  C.sid = S.sid ))
```
3.


```
SELECT S.sname
FROM   Suppliers S
WHERE  NOT EXISTS (( SELECT P.pid
                     FROM   Parts P
                     WHERE  P.color = 'Red' )
                  EXCEPT
                  ( SELECT C.pid
                    FROM   Catalog C, Parts P
                    WHERE  C.sid = S.sid AND
                          C.pid = P.pid AND P.color = 'Red' ))
```
4.


```
SELECT P.pname
FROM   Parts P, Catalog C, Suppliers S
WHERE  P.pid = C.pid AND C.sid = S.sid
AND    S.sname = 'Acme Widget Suppliers'
AND    NOT EXISTS ( SELECT *
                   FROM   Catalog C1, Suppliers S1
                   WHERE  P.pid = C1.pid AND C1.sid = S1.sid AND
                          S1.sname <> 'Acme Widget Suppliers' )
```
5.


```
SELECT DISTINCT C.sid
FROM   Catalog C
```

- ```

WHERE C.cost > (SELECT AVG (C1.cost)
 FROM Catalog C1
 WHERE C1.pid = C.pid)

```
6.     SELECT P.pid, S.sname  
        FROM   Parts P, Suppliers S, Catalog C  
        WHERE   C.pid = P.pid  
        AND     C.sid = S.sid  
        AND     C.cost = (SELECT MAX (C1.cost)  
                           FROM   Catalog C1  
                           WHERE   C1.pid = P.pid)
7.     SELECT DISTINCT C.sid  
        FROM   Catalog C  
        WHERE   NOT EXISTS ( SELECT \*  
                               FROM   Parts P  
                               WHERE   P.pid = C.pid AND P.color <> 'Red' )
8.     SELECT DISTINCT C.sid  
        FROM   Catalog C, Parts P  
        WHERE   C.pid = P.pid AND P.color = 'Red'  
        INTERSECT  
        SELECT DISTINCT C1.sid  
        FROM   Catalog C1, Parts P1  
        WHERE   C1.pid = P1.pid AND P1.color = 'Green'
9.     SELECT DISTINCT C.sid  
        FROM   Catalog C, Parts P  
        WHERE   C.pid = P.pid AND P.color = 'Red'  
        UNION  
        SELECT DISTINCT C1.sid  
        FROM   Catalog C1, Parts P1  
        WHERE   C1.pid = P1.pid AND P1.color = 'Green'
10.    SELECT   S.sname, COUNT(\*) as PartCount  
        FROM     Suppliers S, Parts P, Catalog C  
        WHERE    P.pid = C.pid AND C.sid = S.sid  
        GROUP BY S.sname, S.sid  
        HAVING   EVERY (P.color='Green')
11.    SELECT   S.sname, MAX(C.cost) as MaxCost  
        FROM     Suppliers S, Parts P, Catalog C  
        WHERE    P.pid = C.pid AND C.sid = S.sid

```
GROUP BY S.sname, S.sid
HAVING ANY (P.color='green') AND ANY (P.color = 'red')
```

**Exercise 5.3** The following relations keep track of airline flight information:

```
Flights(fno: integer, from: string, to: string, distance: integer,
 departs: time, arrives: time, price: real)
Aircraft(aid: integer, aname: string, cruisingrange: integer)
Certified(eid: integer, aid: integer)
Employees(eid: integer, ename: string, salary: integer)
```

Note that the Employees relation describes pilots and other kinds of employees as well; every pilot is certified for some aircraft, and only pilots are certified to fly. Write each of the following queries in SQL. (*Additional queries using the same schema are listed in the exercises for Chapter 4.*)

1. Find the names of aircraft such that all pilots certified to operate them have salaries more than \$80,000.
2. For each pilot who is certified for more than three aircraft, find the *eid* and the maximum *cruisingrange* of the aircraft for which she or he is certified.
3. Find the names of pilots whose *salary* is less than the price of the cheapest route from Los Angeles to Honolulu.
4. For all aircraft with *cruisingrange* over 1000 miles, find the name of the aircraft and the average salary of all pilots certified for this aircraft.
5. Find the names of pilots certified for some Boeing aircraft.
6. Find the *aids* of all aircraft that can be used on routes from Los Angeles to Chicago.
7. Identify the routes that can be piloted by every pilot who makes more than \$100,000.
8. Print the *enames* of pilots who can operate planes with *cruisingrange* greater than 3000 miles but are not certified on any Boeing aircraft.
9. A customer wants to travel from Madison to New York with no more than two changes of flight. List the choice of departure times from Madison if the customer wants to arrive in New York by 6 p.m.
10. Compute the difference between the average salary of a pilot and the average salary of all employees (including pilots).

11. Print the name and salary of every nonpilot whose salary is more than the average salary for pilots.
12. Print the names of employees who are certified only on aircrafts with cruising range longer than 1000 miles.
13. Print the names of employees who are certified only on aircrafts with cruising range longer than 1000 miles, but on at least two such aircrafts.
14. Print the names of employees who are certified only on aircrafts with cruising range longer than 1000 miles and who are certified on some Boeing aircraft.

**Answer 5.3** The answers are given below:

1.
 

```
SELECT DISTINCT A.aname
FROM Aircraft A
WHERE A.Aid IN (SELECT C.aid
 FROM Certified C, Employees E
 WHERE C.eid = E.eid AND
 NOT EXISTS (SELECT *
 FROM Employees E1
 WHERE E1.eid = E.eid AND E1.salary < 80000))
```
2.
 

```
SELECT C.eid, MAX (A.cruisingrange)
FROM Certified C, Aircraft A
WHERE C.aid = A.aid
GROUP BY C.eid
HAVING COUNT (*) > 3
```
3.
 

```
SELECT DISTINCT E.ename
FROM Employees E
WHERE E.salary < (SELECT MIN (F.price)
 FROM Flights F
 WHERE F.from = 'Los Angeles' AND F.to = 'Honolulu')
```
4. Observe that *aid* is the key for Aircraft, but the question asks for aircraft names; we deal with this complication by using an intermediate relation Temp:
 

```
SELECT Temp.name, Temp.AvgSalary
FROM (SELECT A.aid, A.aname AS name,
 AVG (E.salary) AS AvgSalary
 FROM Aircraft A, Certified C, Employees E
 WHERE A.aid = C.aid AND
 C.eid = E.eid AND A.cruisingrange > 1000
 GROUP BY A.aid, A.aname) AS Temp
```



5.
 

```

SELECT DISTINCT E.ename
FROM Employees E, Certified C, Aircraft A
WHERE E.eid = C.eid AND
 C.aid = A.aid AND
 A.aname LIKE 'Boeing%'

```
6.
 

```

SELECT A.aid
FROM Aircraft A
WHERE A.cruisingrange > (SELECT MIN (F.distance)
 FROM Flights F
 WHERE F.from = 'Los Angeles' AND F.to = 'Chicago')

```
7.
 

```

SELECT DISTINCT F.from, F.to
FROM Flights F
WHERE NOT EXISTS (SELECT *
 FROM Employees E
 WHERE E.salary > 100000
 AND
 NOT EXISTS (SELECT *
 FROM Aircraft A, Certified C
 WHERE A.cruisingrange > F.distance
 AND E.eid = C.eid
 AND A.aid = C.aid))

```
8.
 

```

SELECT DISTINCT E.ename
FROM Employees E
WHERE E.eid IN ((SELECT C.eid
 FROM Certified C
 WHERE EXISTS (SELECT A.aid
 FROM Aircraft A
 WHERE A.aid = C.aid
 AND A.cruisingrange > 3000)
 AND
 NOT EXISTS (SELECT A1.aid
 FROM Aircraft A1
 WHERE A1.aid = C.aid
 AND A1.aname LIKE 'Boeing%'))

```
9.
 

```

SELECT F.departs
FROM Flights F
WHERE F.fno IN ((SELECT F0.fno

```

- ```

FROM    Flights F0
WHERE   F0.from = 'Madison' AND F0.to = 'New York'
        AND F0.arrives < '18:00' )
UNION
( SELECT F0.fno
  FROM   Flights F0, Flights F1
  WHERE  F0.from = 'Madison' AND F0.to <> 'New York'
        AND F0.to = F1.from AND F1.to = 'New York'
        AND F1.departs > F0.arrives
        AND F1.arrives < '18:00' )
UNION
( SELECT F0.fno
  FROM   Flights F0, Flights F1, Flights F2
  WHERE  F0.from = 'Madison'
        AND F0.to = F1.from
        AND F1.to = F2.from
        AND F2.to = 'New York'
        AND F0.to <> 'New York'
        AND F1.to <> 'New York'
        AND F1.departs > F0.arrives
        AND F2.departs > F1.arrives
        AND F2.arrives < '18:00' ))

```
10. SELECT Temp1.avg - Temp2.avg
 FROM (SELECT AVG (E.salary) AS avg
 FROM Employees E
 WHERE E.eid IN (SELECT DISTINCT C.eid
 FROM Certified C)) AS Temp1,
 (SELECT AVG (E1.salary) AS avg
 FROM Employees E1) AS Temp2
11. SELECT E.ename, E.salary
 FROM Employees E
 WHERE E.eid NOT IN (SELECT DISTINCT C.eid
 FROM Certified C)
 AND E.salary > (SELECT AVG (E1.salary)
 FROM Employees E1
 WHERE E1.eid IN
 (SELECT DISTINCT C1.eid
 FROM Certified C1))
12. SELECT E.ename

- ```
FROM Employees E, Certified C, Aircraft A
WHERE C.aid = A.aid AND E.aid = C.aid
GROUP BY E.aid, E.ename
HAVING EVERY (A.cruisingrange > 1000)
```
13. 

```
SELECT E.ename
FROM Employees E, Certified C, Aircraft A
WHERE C.aid = A.aid AND E.aid = C.aid
GROUP BY E.aid, E.ename
HAVING EVERY (A.cruisingrange > 1000) AND COUNT (*) > 1
```
14. 

```
SELECT E.ename
FROM Employees E, Certified C, Aircraft A
WHERE C.aid = A.aid AND E.aid = C.aid
GROUP BY E.aid, E.ename
HAVING EVERY (A.cruisingrange > 1000) AND ANY (A.aname = 'Boeing')
```