

Contents

1	Basic	1
1.1	Run	1
1.2	Default	1
1.3	Black Magic	1
2	Data Structure	1
2.1	Disjoint Set	1
2.2	BIT RARSQ	2
2.3	zkw RMQ	2
3	Graph	2
3.1	Dijkstra	2
3.2	SPFA(negative cycle)	2
3.3	Floyd Warshall	3
3.4	Topological Sort	3
4	Flow & Matching	3
4.1	KM	3
5	String	4
5.1	Manacher	4
6	DP	4
6.1	LIS	4
7	Math	4
7.1	Extended GCD	4

1 Basic

1.1 Run

```
1 #use -> sh run.sh {name}
2 g++ -O2 -std=c++14 -Wall -Wextra -Wshadow -o $1 $1.cpp
3 ./$1 < t.in > t.out
```

1.2 Default

```
1 #include <bits/stdc++.h>
2 using namespace std;
3 using LL = long long;
4 #define IOS ios_base::sync_with_stdio(0); cin.tie(0);
5 #define pb push_back
6 #define eb emplace_back
7 const int INF = 1e9;
8 const int MOD = 1e9 + 7;
9 const double EPS = 1e-6;
10 const int MAXN = 0;
11
12 int main() {
13
14 }
```

1.3 Black Magic

```
1 #include <bits/stdc++.h>
2 #include <ext/pb_ds/assoc_container.hpp>
3 #include <ext/pb_ds/tree_policy.hpp>
4 #include <ext/pb_ds/priority_queue.hpp>
5 using namespace std;
6 using namespace __gnu_pbds;
7 using set_t =
8     tree<int, null_type, less<int>, rb_tree_tag,
9     tree_order_statistics_node_update>;
10 using map_t =
11     tree<int, int, less<int>, rb_tree_tag,
12     tree_order_statistics_node_update>;
13 using heap_t =
14     __gnu_pbds::priority_queue<int>;
15 using ht_t =
16     gp_hash_table<int, int>;
17 int main() {
```

```
18 //set-----
19 set_t st;
20 st.insert(5); st.insert(6);
21 st.insert(3); st.insert(1);
22
23 // the smallest is (0), biggest is (n-1), kth small
24 // is (k-1)
25 int num = *st.find_by_order(0);
26 cout << num << '\n'; // print 1
27
28 num = *st.find_by_order(st.size() - 1);
29 cout << num << '\n'; // print 6
30
31 // find the index
32 int index = st.order_of_key(6);
33 cout << index << '\n'; // print 3
34
35 // check if there exists x
36 int x = 5;
37 int check = st.erase(x);
38 if (check == 0) printf("st not contain 5\n");
39 else if (check == 1) printf("st contain 5\n");
40
41 //tree policy like set
42 st.insert(5); st.insert(5);
43 cout << st.size() << '\n'; // print 4
44
45 //map-----
46 map_t mp;
47 mp[1] = 2;
48 cout << mp[1] << '\n';
49 auto tmp = *mp.find_by_order(0); // pair
50 cout << tmp.first << " " << tmp.second << '\n';
51
52 //heap-----
53 heap_t h1, h2;
54 h1.push(1); h1.push(3);
55 h2.push(2); h2.push(4);
56 h1.join(h2);
57 cout << h1.size() << h2.size() << h1.top() << '\n';
58 // 404
59
60 //hash-table-----
61 ht_t ht;
62 ht[85] = 5;
63 ht[89975] = 234;
64 for (auto i : ht) {
65     cout << i.first << " " << i.second << '\n';
66 }
```

2 Data Structure

2.1 Disjoint Set

```
1 // 0-base
2 const int MAXN = 1000;
3 int boss[MAXN];
4 void init(int n) {
5     for (int i = 0; i < n; i++) {
6         boss[i] = -1;
7     }
8 }
9 int find(int x) {
10     if (boss[x] < 0) {
11         return x;
12     }
13     return boss[x] = find(boss[x]);
14 }
15 bool uni(int a, int b) {
16     a = find(a);
17     b = find(b);
18     if (a == b) {
19         return false;
20     }
```

```

20 }
21 if (boss[a] > boss[b]) {
22     swap(a, b);
23 }
24 boss[a] += boss[b];
25 boss[b] = a;
26 return true;
27 }

```

2.2 BIT RARSQ

```

1 // 1-base
2 #define lowbit(k) (k & -k)
3
4 int n;
5 vector<int> B1, B2;
6
7 void add(vector<int> &tr, int id, int val) {
8     for (; id <= n; id += lowbit(id)) {
9         tr[id] += val;
10    }
11 }
12 void range_add(int l, int r, int val) {
13     add(B1, l, val);
14     add(B1, r + 1, -val);
15     add(B2, l, val * (1 - 1));
16     add(B2, r + 1, -val * r);
17 }
18 int sum(vector<int> &tr, int id) {
19     int ret = 0;
20     for (; id >= 1; id -= lowbit(id)) {
21         ret += tr[id];
22     }
23     return ret;
24 }
25 int prefix_sum(int id) {
26     return sum(B1, id) * id - sum(B2, id);
27 }
28 int range_sum(int l, int r) {
29     return prefix_sum(r) - prefix_sum(l - 1);
30 }

```

2.3 zkw RMQ

```

1 // 0-base
2 const int INF = 1e9;
3 const int MAXN = ;
4
5 int n;
6 int a[MAXN], tr[MAXN << 1];
7
8 // !!! remember to call this function
9 void build() {
10     for (int i = 0; i < n; i++) {
11         tr[i + n] = a[i];
12     }
13     for (int i = n - 1; i > 0; i--) {
14         tr[i] = max(tr[i << 1], tr[i << 1 | 1]);
15     }
16 }
17 void update(int id, int val) {
18     for (tr[id += n] = val; id > 1; id >>= 1) {
19         tr[id >> 1] = max(tr[id], tr[id ^ 1]);
20     }
21 }
22 int query(int l, int r) { // [l, r)
23     int ret = -INF;
24     for (l += n, r += n; l < r; l >>= 1, r >>= 1) {
25         if (l & 1) {
26             ret = max(ret, tr[l++]);
27         }
28         if (r & 1) {
29             ret = max(ret, tr[--r]);
30         }
31     }
32     return ret;
33 }

```

```

30 }
31 }
32 return ret;
33 }

```

3 Graph

3.1 Dijkstra

```

1 // 0-base
2 const LL INF = 1e18;
3 const int MAXN = ;
4 struct Edge {
5     int at;
6     LL cost;
7     bool operator < (const Edge &other) const {
8         return cost > other.cost;
9     }
10 };
11
12 int n;
13 LL dis[MAXN];
14 vector<Edge> G[MAXN];
15
16 void init() {
17     for (int i = 0; i < n; i++) {
18         G[i].clear();
19         dis[i] = INF;
20     }
21 }
22 void Dijkstra(int st, int ed = -1) {
23     priority_queue<Edge> pq;
24     pq.push({ st, 0 });
25     dis[st] = 0;
26     while (!pq.empty()) {
27         auto now = pq.top();
28         pq.pop();
29         if (now.at == ed) {
30             return;
31         }
32         if (now.cost > dis[now.at]) {
33             continue;
34         }
35         for (auto &e : G[now.at]) {
36             if (dis[e.at] > now.cost + e.cost) {
37                 dis[e.at] = now.cost + e.cost;
38                 pq.push({ e.at, dis[e.at] });
39             }
40         }
41     }
42 }

```

3.2 SPFA(negative cycle)

```

1 // 0-base
2 const LL INF = 1e18;
3 const int MAXN = ;
4 struct Edge {
5     int at;
6     LL cost;
7 };
8
9 int n;
10 LL dis[MAXN];
11 vector<Edge> G[MAXN];
12
13 void init() {
14     for (int i = 0; i < n; i++) {
15         G[i].clear();
16         dis[i] = INF;
17     }
18 }

```

```

19 bool SPFA(int st) {
20     vector<int> cnt(n, 0);
21     vector<bool> inq(n, false);
22     queue<int> q;
23
24     q.push(st);
25     dis[st] = 0;
26     inq[st] = true;
27     while (!q.empty()) {
28         int now = q.front();
29         q.pop();
30         inq[now] = false;
31         for (auto &e : G[now]) {
32             if (dis[e.at] > dis[now] + e.cost) {
33                 dis[e.at] = dis[now] + e.cost;
34                 if (!inq[e.at]) {
35                     cnt[e.at]++;
36                     if (cnt[e.at] > n) {
37                         // negative cycle
38                         return false;
39                     }
40                     inq[e.at] = true;
41                     q.push(e.at);
42                 }
43             }
44         }
45     }
46     return true;
47 }

```

3.3 Floyd Warshall

```

1 // 0-base
2 // G[i][i] < 0 -> negative cycle
3 const LL INF = 1e18;
4 const int MAXN = ;
5
6 int n;
7 LL G[MAXN][MAXN];
8
9 void init() {
10     for (int i = 0; i < n; i++) {
11         for (int j = 0; j < n; j++) {
12             G[i][j] = INF;
13         }
14         G[i][i] = 0;
15     }
16 }
17 void floyd() {
18     for (int k = 0; k < n; k++) {
19         for (int i = 0; i < n; i++) {
20             for (int j = 0; j < n; j++) {
21                 if (G[i][k] != INF && G[k][j] != INF) {
22                     G[i][j] = min(G[i][j], G[i][k] + G[k][j]);
23                 }
24             }
25         }
26     }
27 }

```

3.4 Topological Sort

```

1 // 0-base
2 // if ret.size < n -> cycle
3 int n;
4 vector<vector<int>> G;
5
6 vector<int> topoSort() {
7     vector<int> indeg(n), ret;
8     for (auto &li : G) {
9         for (int x : li) {
10             ++indeg[x];
11         }

```

```

12     }
13     // use priority queue for lexic. largest ans
14     queue<int> q;
15     for (int i = 0; i < n; i++) {
16         if (!indeg[i]) {
17             q.push(i);
18         }
19     }
20     while (!q.empty()) {
21         int u = q.front();
22         q.pop();
23         ret.pb(u);
24         for (int v : G[u]) {
25             if (--indeg[v] == 0) {
26                 q.push(v);
27             }
28         }
29     }
30     return ret;
31 }

```

4 Flow & Matching

4.1 KM

```

1 const int INF = 1e9;
2 const int MAXN = ;
3 struct KM { //1-base
4     int n, G[MAXN][MAXN];
5     int lx[MAXN], ly[MAXN], my[MAXN];
6     bool vx[MAXN], vy[MAXN];
7     void init(int _n) {
8         n = _n;
9         for (int i = 1; i <= n; i++) {
10             for (int j = 1; j <= n; j++) {
11                 G[i][j] = 0;
12             }
13         }
14     }
15     bool match(int i) {
16         vx[i] = true;
17         for (int j = 1; j <= n; j++) {
18             if (lx[i] + ly[j] == G[i][j] && !vy[j]) {
19                 vy[j] = true;
20                 if (!my[j] || match(my[j])) {
21                     my[j] = i;
22                     return true;
23                 }
24             }
25         }
26         return false;
27     }
28     void update() {
29         int delta = INF;
30         for (int i = 1; i <= n; i++) {
31             if (vx[i]) {
32                 for (int j = 1; j <= n; j++) {
33                     if (!vy[j]) {
34                         delta = min(delta, lx[i] + ly[j] - G[i][j]);
35                     }
36                 }
37             }
38         }
39         for (int i = 1; i <= n; i++) {
40             if (vx[i]) {
41                 lx[i] -= delta;
42             }
43             if (vy[i]) {
44                 ly[i] += delta;
45             }
46         }
47     }
48     int run() {

```

```

49     for (int i = 1; i <= n; i++) {
50         lx[i] = ly[i] = my[i] = 0;
51         for (int j = 1; j <= n; j++) {
52             lx[i] = max(lx[i], G[i][j]);
53         }
54     }
55     for (int i = 1; i <= n; i++) {
56         while (true) {
57             for (int i = 1; i <= n; i++) {
58                 vx[i] = vy[i] = 0;
59             }
60             if (match(i)) {
61                 break;
62             } else {
63                 update();
64             }
65         }
66     }
67     int ans = 0;
68     for (int i = 1; i <= n; i++) {
69         ans += lx[i] + ly[i];
70     }
71     return ans;
72 }
73 };

```

5 String

5.1 Manacher

```

1 int p[2 * MAXN];
2 int Manacher(const string &s) {
3     string st = "@#";
4     for (char c : s) {
5         st += c;
6         st += '#';
7     }
8     st += '$';
9     int id = 0, mx = 0, ans = 0;
10    for (int i = 1; i < st.length() - 1; i++) {
11        p[i] = (mx > i ? min(p[2 * id - i], mx - i) : 1);
12        for (; st[i - p[i]] == st[i + p[i]]; p[i]++);
13        if (mx < i + p[i]) {
14            mx = i + p[i];
15            id = i;
16        }
17        ans = max(ans, p[i] - 1);
18    }
19    return ans;
20 }

```

6 DP

6.1 LIS

```

1 int LIS(vector<int> &a) {
2     vector<int> s;
3     for (int i = 0; i < a.size(); i++) {
4         if (s.empty() || s.back() < a[i]) {
5             s.push_back(a[i]);
6         } else {
7             *lower_bound(s.begin(), s.end(), a[i],
8                 [](int x, int y) {return x < y;}) = a[i];
9         }
10    }
11    return s.size();
12 }

```

7 Math

7.1 Extended GCD

```

1 // ax + by = c
2 int extgcd(int a, int b, int c, int &x, int &y) {
3     if (b == 0) {
4         x = c / a;
5         y = 0;
6         return a;
7     }
8     int d = extgcd(b, a % b, c, x, y);
9     int tmp = x;
10    x = y;
11    y = tmp - (a / b) * y;
12    return d;
13 }

```