

Contents

1	Basic	
1.1	Run	
1.2	Default	
1.3	Black Magic	
1.4	Binary Search	
2	Data Structure	
2.1	Disjoint Set	
2.2	BIT RARSQ	
2.3	zkw RMQ	
3	Graph	
3.1	Dijkstra	
3.2	SPFA(negative cycle)	
3.3	Floyd Warshall	
3.4	Topological Sort	
3.5	Kosaraju SCC	
3.6	Tree Diameter	
3.7	Directed MST	
4	Flow & Matching	
4.1	Bipartite Matching	
4.2	KM	
4.3	Dinic	
4.4	MCMF	
5	String	
5.1	Manacher	
6	DP	
6.1	LIS	
6.2	LCS	
7	Math	
7.1	Extended GCD	
8	Geometry	
8.1	Point	
8.2	Line	
8.3	Area	

1 Basic

1.1 Run

```
1 #use -> sh run.sh {name}
2 g++ -O2 -std=c++14 -Wall -Wextra -Wshadow -o $1 $1.cpp
3 ./ $1 < t.in > t.out
```

1.2 Default

```
1 #include <bits/stdc++.h>
2 using namespace std;
3 using LL = long long;
4 #define IOS ios_base::sync_with_stdio(0); cin.tie(0);
5 #define pb push_back
6 #define eb emplace_back
7 const int INF = 1e9;
8 const int MOD = 1e9 + 7;
9 const double EPS = 1e-6;
10 const int MAXN = 0;
11
12 int main() {
13
14 }
```

1.3 Black Magic

```
1 #include <bits/stdc++.h>
2 #include <ext/pb_ds/assoc_container.hpp>
3 #include <ext/pb_ds/tree_policy.hpp>
4 #include <ext/pb_ds/priority_queue.hpp>
5 using namespace std;
6 using namespace __gnu_pbds;
```

```
7 using set_t =
8     tree<int, null_type, less<int>, rb_tree_tag,
9         tree_order_statistics_node_update>;
10 using map_t =
11     tree<int, int, less<int>, rb_tree_tag,
12         tree_order_statistics_node_update>;
13 using heap_t =
14     __gnu_pbds::priority_queue<int>;
15 using ht_t =
16     gp_hash_table<int, int>;
17 int main() {
18     //set-----
19     set_t st;
20     st.insert(5); st.insert(6);
21     st.insert(3); st.insert(1);
22
23     // the smallest is (0), biggest is (n-1), kth small
24     // is (k-1)
25     int num = *st.find_by_order(0);
26     cout << num << '\n'; // print 1
27
28     num = *st.find_by_order(st.size() - 1);
29     cout << num << '\n'; // print 6
30
31     // find the index
32     int index = st.order_of_key(6);
33     cout << index << '\n'; // print 3
34
35     // check if there exists x
36     int x = 5;
37     int check = st.erase(x);
38     if (check == 0) printf("st not contain 5\n");
39     else if (check == 1) printf("st contain 5\n");
40
41     //tree policy like set
42     st.insert(5); st.insert(5);
43     cout << st.size() << '\n'; // print 4
44
45     //map-----
46     map_t mp;
47     mp[1] = 2;
48     cout << mp[1] << '\n';
49     auto tmp = *mp.find_by_order(0); // pair
50     cout << tmp.first << " " << tmp.second << '\n';
51
52     //heap-----
53     heap_t h1, h2;
54     h1.push(1); h1.push(3);
55     h2.push(2); h2.push(4);
56     h1.join(h2);
57     cout << h1.size() << h2.size() << h1.top() << '\n';
58     // 404
59
60     //hash-table-----
61     ht_t ht;
62     ht[85] = 5;
63     ht[89975] = 234;
64     for (auto i : ht) {
65         cout << i.first << " " << i.second << '\n';
66     }
```

1.4 Binary Search

```
1 lower_bound(a, a + n, k); //最左邊 ≥ k 的位置
2 upper_bound(a, a + n, k); //最左邊 > k 的位置
3 upper_bound(a, a + n, k) - 1; //最右邊 ≤ k 的位置
4 lower_bound(a, a + n, k) - 1; //最右邊 < k 的位置
5 [lower_bound, upper_bound) //等於 k 的範圍
6 equal_range(a, a + n, k);
```

2 Data Structure

2.1 Disjoint Set

```

1 // 0-base
2 const int MAXN = 1000;
3 int boss[MAXN];
4 void init(int n) {
5     for (int i = 0; i < n; i++) {
6         boss[i] = -1;
7     }
8 }
9 int find(int x) {
10     if (boss[x] < 0) {
11         return x;
12     }
13     return boss[x] = find(boss[x]);
14 }
15 bool uni(int a, int b) {
16     a = find(a);
17     b = find(b);
18     if (a == b) {
19         return false;
20     }
21     if (boss[a] > boss[b]) {
22         swap(a, b);
23     }
24     boss[a] += boss[b];
25     boss[b] = a;
26     return true;
27 }

```

2.2 BIT RARSQ

```

1 // 1-base
2 #define lowbit(k) (k & -k)
3
4 int n;
5 vector<int> B1, B2;
6
7 void add(vector<int> &tr, int id, int val) {
8     for (; id <= n; id += lowbit(id)) {
9         tr[id] += val;
10    }
11 }
12 void range_add(int l, int r, int val) {
13     add(B1, l, val);
14     add(B1, r + 1, -val);
15     add(B2, l, val * (1 - 1));
16     add(B2, r + 1, -val * r);
17 }
18 int sum(vector<int> &tr, int id) {
19     int ret = 0;
20     for (; id >= 1; id -= lowbit(id)) {
21         ret += tr[id];
22     }
23     return ret;
24 }
25 int prefix_sum(int id) {
26     return sum(B1, id) * id - sum(B2, id);
27 }
28 int range_sum(int l, int r) {
29     return prefix_sum(r) - prefix_sum(l - 1);
30 }

```

2.3 zkw RMQ

```

1 // 0-base
2 const int INF = 1e9;
3 const int MAXN = ;
4
5 int n;

```

```

6 int a[MAXN], tr[MAXN << 1];
7
8 // !!! remember to call this function
9 void build() {
10     for (int i = 0; i < n; i++) {
11         tr[i + n] = a[i];
12     }
13     for (int i = n - 1; i > 0; i--) {
14         tr[i] = max(tr[i << 1], tr[i << 1 | 1]);
15     }
16 }
17 void update(int id, int val) {
18     for (tr[id += n] = val; id > 1; id >>= 1) {
19         tr[id >> 1] = max(tr[id], tr[id ^ 1]);
20     }
21 }
22 int query(int l, int r) { // [l, r)
23     int ret = -INF;
24     for (l += n, r += n; l < r; l >>= 1, r >>= 1) {
25         if (l & 1) {
26             ret = max(ret, tr[l++]);
27         }
28         if (r & 1) {
29             ret = max(ret, tr[--r]);
30         }
31     }
32     return ret;
33 }

```

3 Graph

3.1 Dijkstra

```

1 // 0-base
2 const LL INF = 1e18;
3 const int MAXN = ;
4 struct Edge {
5     int to;
6     LL cost;
7     Edge(int v, LL c) : to(v), cost(c) {}
8     bool operator < (const Edge &other) const {
9         return cost > other.cost;
10    }
11 };
12
13 int n;
14 LL dis[MAXN];
15 vector<Edge> G[MAXN];
16
17 void init() {
18     for (int i = 0; i < n; i++) {
19         G[i].clear();
20         dis[i] = INF;
21     }
22 }
23 void Dijkstra(int st, int ed = -1) {
24     priority_queue<Edge> pq;
25     pq.emplace(st, 0);
26     dis[st] = 0;
27     while (!pq.empty()) {
28         auto now = pq.top();
29         pq.pop();
30         if (now.to == ed) {
31             return;
32         }
33         if (now.cost > dis[now.to]) {
34             continue;
35         }
36         for (auto &e : G[now.to]) {
37             if (dis[e.to] > now.cost + e.cost) {
38                 dis[e.to] = now.cost + e.cost;
39                 pq.emplace(e.to, dis[e.to]);
40             }
41         }
42     }
43 }

```

```
42 }
43 }
```

3.2 SPFA(negative cycle)

```
1 // 0-base
2 const LL INF = 1e18;
3 const int MAXN = ;
4 struct Edge {
5     int to;
6     LL cost;
7     Edge(int v, LL c) : to(v), cost(c) {}
8 };
9
10 int n;
11 LL dis[MAXN];
12 vector<Edge> G[MAXN];
13
14 void init() {
15     for (int i = 0; i < n; i++) {
16         G[i].clear();
17         dis[i] = INF;
18     }
19 }
20 bool SPFA(int st) {
21     vector<int> cnt(n, 0);
22     vector<bool> inq(n, false);
23     queue<int> q;
24
25     q.push(st);
26     dis[st] = 0;
27     inq[st] = true;
28     while (!q.empty()) {
29         int now = q.front();
30         q.pop();
31         inq[now] = false;
32         for (auto &e : G[now]) {
33             if (dis[e.to] > dis[now] + e.cost) {
34                 dis[e.to] = dis[now] + e.cost;
35                 if (!inq[e.to]) {
36                     cnt[e.to]++;
37                     if (cnt[e.to] > n) {
38                         // negative cycle
39                         return false;
40                     }
41                     inq[e.to] = true;
42                     q.push(e.to);
43                 }
44             }
45         }
46     }
47     return true;
48 }
```

3.3 Floyd Warshall

```
1 // 0-base
2 // G[i][i] < 0 -> negative cycle
3 const LL INF = 1e18;
4 const int MAXN = ;
5
6 int n;
7 LL G[MAXN][MAXN];
8
9 void init() {
10     for (int i = 0; i < n; i++) {
11         for (int j = 0; j < n; j++) {
12             G[i][j] = INF;
13         }
14         G[i][i] = 0;
15     }
16 }
17 void floyd() {
```

```
18     for (int k = 0; k < n; k++) {
19         for (int i = 0; i < n; i++) {
20             for (int j = 0; j < n; j++) {
21                 if (G[i][k] != INF && G[k][j] != INF) {
22                     G[i][j] = min(G[i][j], G[i][k] + G[k][j]);
23                 }
24             }
25         }
26     }
27 }
```

3.4 Topological Sort

```
1 // 0-base
2 // if ret.size < n -> cycle
3 int n;
4 vector<vector<int>> G;
5
6 vector<int> topoSort() {
7     vector<int> indeg(n), ret;
8     for (auto &li : G) {
9         for (int x : li) {
10             ++indeg[x];
11         }
12     }
13     // use priority queue for lexic. largest ans
14     queue<int> q;
15     for (int i = 0; i < n; i++) {
16         if (!indeg[i]) {
17             q.push(i);
18         }
19     }
20     while (!q.empty()) {
21         int u = q.front();
22         q.pop();
23         ret.pb(u);
24         for (int v : G[u]) {
25             if (--indeg[v] == 0) {
26                 q.push(v);
27             }
28         }
29     }
30     return ret;
31 }
```

3.5 Kosaraju SCC

```
1 // 0-base
2 int n;
3 vector<vector<int>> G, G2; // G2 = G rev
4 vector<bool> vis;
5 vector<int> s, color;
6 int sccCnt;
7 void dfs1(int u) {
8     vis[u] = true;
9     for (int v : G[u]) {
10         if (!vis[v]) {
11             dfs1(v);
12         }
13     }
14     s.pb(u);
15 }
16 void dfs2(int u) {
17     color[u] = sccCnt;
18     for (int v : G2[u]) {
19         if (!color[v]) {
20             dfs2(v);
21         }
22     }
23 }
24 void Kosaraju() {
25     sccCnt = 0;
26     for (int i = 0; i < n; i++) {
```

```

27     if (!vis[i]) {
28         dfs1(i);
29     }
30 }
31 for (int i = n - 1; i >= 0; i--) {
32     if (!color[s[i]]) {
33         ++sccCnt;
34         dfs2(s[i]);
35     }
36 }
37 }

```

3.6 Tree Diameter

```

1 // 0-base;
2 const int MAXN = ;
3
4 struct Edge {
5     int to;
6     int cost;
7     Edge(int v, int c) : to(v), cost(c) {}
8 };
9
10 int n, d = 0;
11 int d1[MAXN], d2[MAXN];
12 vector<Edge> G[MAXN];
13 // dfs(0, -1);
14 void dfs(int u, int from) {
15     d1[u] = d2[u] = 0;
16     for (auto e : G[u]) {
17         if (e.to == from) {
18             continue;
19         }
20         dfs(e.to, u);
21         int t = d1[e.to] + e.cost;
22         if (t > d1[u]) {
23             d2[u] = d1[u];
24             d1[u] = t;
25         } else if (t > d2[u]) {
26             d2[u] = t;
27         }
28     }
29     d = max(d, d1[u] + d2[u]);
30 }

```

3.7 Directed MST

```

1 // 0-base
2 const LL INF = 1e18;
3 const int MAXN = ;
4
5 struct Edge {
6     int from;
7     int to;
8     LL cost;
9     Edge(int u, int v, LL c) : from(u), to(v), cost(c) {}
10 };
11
12 struct DMST {
13     int n;
14     int vis[MAXN], pre[MAXN], id[MAXN];
15     LL in[MAXN];
16     vector<Edge> edges;
17     void init(int _n) {
18         n = _n;
19         edges.clear();
20     }
21     void add_edge(int from, int to, LL cost) {
22         edges.eb(from, to, cost);
23     }
24     LL run(int root) {
25         LL ret = 0;

```

```

26 while (true) {
27     for (int i = 0; i < n; i++) {
28         in[i] = INF;
29     }
30
31     // find in edge
32     for (auto &e : edges) {
33         if (e.cost < in[e.to] && e.from != e.to) {
34             pre[e.to] = e.from;
35             in[e.to] = e.cost;
36         }
37     }
38
39     // check in edge
40     for (int i = 0; i < n; i++) {
41         if (i == root) {
42             continue;
43         }
44         if (in[i] == INF) {
45             return -1;
46         }
47     }
48
49     int nodenum = 0;
50     memset(id, -1, sizeof(id));
51     memset(vis, -1, sizeof(vis));
52     in[root] = 0;
53
54     // find cycles
55     for (int i = 0; i < n; i++) {
56         ret += in[i];
57         int v = i;
58         while (vis[v] != i && id[v] == -1 && v !=
59             root) {
60             vis[v] = i;
61             v = pre[v];
62         }
63         if (id[v] == -1 && v != root) {
64             for (int j = pre[v]; j != v; j = pre[j]) {
65                 id[j] = nodenum;
66             }
67             id[v] = nodenum++;
68         }
69     }
70
71     // no cycle
72     if (nodenum == 0) {
73         break;
74     }
75
76     for (int i = 0; i < n; i++) {
77         if (id[i] == -1) {
78             id[i] = nodenum++;
79         }
80     }
81
82     // grouping the vertices
83     for (auto &e : edges) {
84         int to = e.to;
85         e.from = id[e.from];
86         e.to = id[e.to];
87         if (e.from != e.to) {
88             e.cost -= in[to]; //!!!
89         }
90     }
91
92     n = nodenum;
93     root = id[root];
94 }
95 return ret;
96 };

```

4 Flow & Matching

4.1 Bipartite Matching

```

1 // 0-base
2 const int MAXN = ;
3 int n;
4 vector<int> G[MAXN];
5 int vy[MAXN], my[MAXN];
6
7 bool match(int u) {
8     for (int v : G[u]) {
9         if (vy[v]) {
10             continue;
11         }
12         vy[v] = true;
13         if (my[v] == -1 || match(my[v])) {
14             my[v] = u;
15             return true;
16         }
17     }
18     return false;
19 }
20 int sol() {
21     int cnt = 0;
22     memset(my, -1, sizeof(my));
23     for (int i = 0; i < n; i++) {
24         memset(vy, 0, sizeof(vy));
25         if (match(i)) {
26             cnt++;
27         }
28     }
29     return cnt;
30 }

```

4.2 KM

```

1 const int INF = 1e9;
2 const int MAXN = ;
3 struct KM { //1-base
4     int n, G[MAXN][MAXN];
5     int lx[MAXN], ly[MAXN], my[MAXN];
6     bool vx[MAXN], vy[MAXN];
7     void init(int _n) {
8         n = _n;
9         for (int i = 1; i <= n; i++) {
10             for (int j = 1; j <= n; j++) {
11                 G[i][j] = 0;
12             }
13         }
14     }
15     bool match(int i) {
16         vx[i] = true;
17         for (int j = 1; j <= n; j++) {
18             if (lx[i] + ly[j] == G[i][j] && !vy[j]) {
19                 vy[j] = true;
20                 if (!my[j] || match(my[j])) {
21                     my[j] = i;
22                     return true;
23                 }
24             }
25         }
26         return false;
27     }
28     void update() {
29         int delta = INF;
30         for (int i = 1; i <= n; i++) {
31             if (vx[i]) {
32                 for (int j = 1; j <= n; j++) {
33                     if (!vy[j]) {
34                         delta = min(delta, lx[i] + ly[j] - G[i][j]);
35                     }
36                 }
37             }
38         }
39     }

```

```

37     }
38 }
39 for (int i = 1; i <= n; i++) {
40     if (vx[i]) {
41         lx[i] -= delta;
42     }
43     if (vy[i]) {
44         ly[i] += delta;
45     }
46 }
47 }
48 int run() {
49     for (int i = 1; i <= n; i++) {
50         lx[i] = ly[i] = my[i] = 0;
51         for (int j = 1; j <= n; j++) {
52             lx[i] = max(lx[i], G[i][j]);
53         }
54     }
55     for (int i = 1; i <= n; i++) {
56         while (true) {
57             for (int i = 1; i <= n; i++) {
58                 vx[i] = vy[i] = 0;
59             }
60             if (match(i)) {
61                 break;
62             } else {
63                 update();
64             }
65         }
66     }
67     int ans = 0;
68     for (int i = 1; i <= n; i++) {
69         ans += lx[i] + ly[i];
70     }
71     return ans;
72 }
73 };

```

4.3 Dinic

```

1 #define eb emplace_back
2 const LL INF = 1e18;
3 const int MAXN = ;
4 struct Edge {
5     int to;
6     LL cap;
7     int rev;
8     Edge(int v, LL c, int r) : to(v), cap(c), rev(r) {}
9 };
10 struct Dinic {
11     int n;
12     int level[MAXN], now[MAXN];
13     vector<Edge> G[MAXN];
14     void init(int _n) {
15         n = _n;
16         for (int i = 0; i <= n; i++) {
17             G[i].clear();
18         }
19     }
20     void add_edge(int u, int v, LL c) {
21         G[u].eb(v, c, G[v].size());
22         // directed graph
23         G[v].eb(u, 0, G[u].size() - 1);
24         // undirected graph
25         // G[v].eb(u, c, G[u].size() - 1);
26     }
27     bool bfs(int st, int ed) {
28         fill(level, level + n + 1, -1);
29         queue<int> q;
30         q.push(st);
31         level[st] = 0;
32         while (!q.empty()) {
33             int u = q.front();
34             q.pop();
35             for (const auto &e : G[u]) {
36                 if (e.cap > 0 && level[e.to] == -1) {

```

```

37     level[e.to] = level[u] + 1;
38     q.push(e.to);
39 }
40 }
41 }
42 return level[ed] != -1;
43 }
44 LL dfs(int u, int ed, LL limit) {
45     if (u == ed) {
46         return limit;
47     }
48     LL ret = 0;
49     for (int &i = now[u]; i < G[u].size(); i++) {
50         auto &e = G[u][i];
51         if (e.cap > 0 && level[e.to] == level[u] + 1) {
52             LL f = dfs(e.to, ed, min(limit, e.cap));
53             ret += f;
54             limit -= f;
55             e.cap -= f;
56             G[e.to][e.rev].cap += f;
57             if (!limit) {
58                 return ret;
59             }
60         }
61     }
62     if (!ret) {
63         level[u] = -1;
64     }
65     return ret;
66 }
67 LL flow(int st, int ed) {
68     LL ret = 0;
69     while (bfs(st, ed)) {
70         fill(now, now + n + 1, 0);
71         ret += dfs(st, ed, INF);
72     }
73     return ret;
74 }
75 };

```

4.4 MCMF

```

1 // 0-base
2 const LL INF = 1e18;
3 const int MAXN = ;
4 struct Edge {
5     int u, v;
6     LL cost;
7     LL cap;
8     Edge(int _u, int _v, LL _c, LL _cap) : u(_u),
9         v(_v), cost(_c), cap(_cap) {}
10 };
11 struct MCMF { // inq times
12     int n, pre[MAXN], cnt[MAXN];
13     LL ans_flow, ans_cost, dis[MAXN];
14     bool inq[MAXN];
15     vector<int> G[MAXN];
16     vector<Edge> edges;
17     void init(int _n) {
18         n = _n;
19         edges.clear();
20         for (int i = 0; i < n; i++) {
21             G[i].clear();
22         }
23     }
24     void add_edge(int u, int v, LL c, LL cap) {
25         // directed
26         G[u].pb(edges.size());
27         edges.pb(u, v, c, cap);
28         G[v].pb(edges.size());
29         edges.pb(v, u, -c, 0);
30     }
31     bool SPFA(int st, int ed) {
32         for (int i = 0; i < n; i++) {
33             pre[i] = -1;
34             dis[i] = INF;

```

```

34         cnt[i] = 0;
35         inq[i] = false;
36     }
37     queue<int> q;
38     bool negcycle = false;
39
40     dis[st] = 0;
41     cnt[st] = 1;
42     inq[st] = true;
43     q.push(st);
44
45     while (!q.empty() && !negcycle) {
46         int u = q.front();
47         q.pop();
48         inq[u] = false;
49         for (int i : G[u]) {
50             int v = edges[i].v;
51             LL cost = edges[i].cost;
52             LL cap = edges[i].cap;
53
54             if (dis[v] > dis[u] + cost && cap > 0) {
55                 dis[v] = dis[u] + cost;
56                 pre[v] = i;
57                 if (!inq[v]) {
58                     q.push(v);
59                     cnt[v]++;
60                     inq[v] = true;
61
62                     if (cnt[v] == n + 2) {
63                         negcycle = true;
64                         break;
65                     }
66                 }
67             }
68         }
69     }
70
71     return dis[ed] != INF;
72 }
73 LL sendFlow(int v, LL curFlow) {
74     if (pre[v] == -1) {
75         return curFlow;
76     }
77     int i = pre[v];
78     int u = edges[i].u;
79     LL cost = edges[i].cost;
80
81     LL f = sendFlow(u, min(curFlow, edges[i].cap));
82
83     ans_cost += f * cost;
84     edges[i].cap -= f;
85     edges[i ^ 1].cap += f;
86     return f;
87 }
88 pair<LL, LL> run(int st, int ed) {
89     ans_flow = ans_cost = 0;
90     while (SPFA(st, ed)) {
91         ans_flow += sendFlow(ed, INF);
92     }
93     return make_pair(ans_flow, ans_cost);
94 }
95 };

```

5 String

5.1 Manacher

```

1 int p[2 * MAXN];
2 int Manacher(const string &s) {
3     string st = "@#";
4     for (char c : s) {
5         st += c;
6         st += '#';
7     }

```

```

8 | st += '$';
9 | int id = 0, mx = 0, ans = 0;
10 | for (int i = 1; i < st.length() - 1; i++) {
11 |     p[i] = (mx > i ? min(p[2 * id - i], mx - i) : 1);
12 |     for (; st[i - p[i]] == st[i + p[i]]; p[i]++);
13 |     if (mx < i + p[i]) {
14 |         mx = i + p[i];
15 |         id = i;
16 |     }
17 |     ans = max(ans, p[i] - 1);
18 | }
19 | return ans;
20 | }

```

6 DP

6.1 LIS

```

1 | int LIS(vector<int> &a) {
2 |     vector<int> s;
3 |     for (int i = 0; i < a.size(); i++) {
4 |         if (s.empty() || s.back() < a[i]) {
5 |             s.push_back(a[i]);
6 |         } else {
7 |             *lower_bound(s.begin(), s.end(), a[i],
8 |                 [](int x, int y) {return x < y;}) = a[i];
9 |         }
10 |     }
11 |     return s.size();
12 | }

```

6.2 LCS

```

1 | int LCS(string s1, string s2) {
2 |     int n1 = s1.size(), n2 = s2.size();
3 |     vector<vector<int>> dp(n1 + 1, vector<int>(n2 + 1,
4 |         0));
5 |     for (int i = 1; i <= n1; i++) {
6 |         for (int j = 1; j <= n2; j++) {
7 |             if (s1[i - 1] == s2[j - 1]) {
8 |                 dp[i][j] = dp[i - 1][j - 1] + 1;
9 |             } else {
10 |                 dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
11 |             }
12 |         }
13 |     }
14 |     return dp[n1][n2];
15 | }

```

7 Math

7.1 Extended GCD

```

1 | // ax + by = c
2 | int extgcd(int a, int b, int c, int &x, int &y) {
3 |     if (b == 0) {
4 |         x = c / a;
5 |         y = 0;
6 |         return a;
7 |     }
8 |     int d = extgcd(b, a % b, c, y, x);
9 |     y -= (a / b) * x;
10 |     return d;
11 | }

```

8 Geometry

8.1 Point

```

1 | // notice point type!!!
2 | using dvt = int;
3 | const double EPS = 1e-6;
4 | const double PI = acos(-1);
5 |
6 | struct Pt {
7 |     dvt x;
8 |     dvt y;
9 | };
10 | bool operator < (const Pt &a, const Pt &b) {
11 |     return a.x == b.x ? a.y < b.y : a.x < b.x;
12 | }
13 | bool operator == (const Pt &a, const Pt &b) {
14 |     return a.x == b.x && a.y == b.y;
15 | }
16 | Pt operator + (const Pt &a, const Pt &b) {
17 |     return {a.x + b.x, a.y + b.y};
18 | }
19 | Pt operator - (const Pt &a, const Pt &b) {
20 |     return {a.x - b.x, a.y - b.y};
21 | }
22 | // multiply constant
23 | Pt operator * (const Pt &a, const dvt c) {
24 |     return {a.x * c, a.y * c};
25 | }
26 | Pt operator / (const Pt &a, const dvt c) {
27 |     return {a.x / c, a.y / c};
28 | }
29 | // |a| x |b| x cos(x)
30 | dvt iproduct(const Pt &a, const Pt &b) {
31 |     return a.x * b.x + a.y * b.y;
32 | }
33 | // |a| x |b| x sin(x)
34 | dvt cross(const Pt &a, const Pt &b) {
35 |     return a.x * b.y - a.y * b.x;
36 | }
37 | dvt dis_pp(const Pt &a, const Pt &b) {
38 |     dvt dx = a.x - b.x;
39 |     dvt dy = a.y - b.y;
40 |     return sqrt(dx * dx + dy * dy);
41 | }

```

8.2 Line

```

1 | struct Line {
2 |     Pt st;
3 |     Pt ed;
4 | };
5 | // return point side
6 | // left, on line, right -> 1, 0, -1
7 | int side(Line l, Pt a) {
8 |     dvt cross_val = cross(a - l.st, l.ed - l.st);
9 |     if (cross_val > EPS) {
10 |         return 1;
11 |     } else if (cross_val < -EPS) {
12 |         return -1;
13 |     } else {
14 |         return 0;
15 |     }
16 | }
17 | // AB infinity, CD segment
18 | bool has_intersection(Line AB, Line CD) {
19 |     int c = side(AB, CD.st);
20 |     int d = side(AB, CD.ed);
21 |     if (c == 0 || d == 0) {
22 |         return true;
23 |     } else {
24 |         // different side
25 |         return c == -d;
26 |     }
27 | }

```

```

27 }
28 // find intersection point, two line, not seg
29 pair<int, Pt> intersection(Line a, Line b) {
30     Pt A = a.ed - a.st;
31     Pt B = b.ed - b.st;
32     Pt C = b.st - a.st;
33     dvt mom = cross(A, B);
34     dvt son = cross(C, B);
35     if (std::abs(mom) <= EPS) {
36         if (std::abs(son) <= EPS) {
37             return {1, {}}; // same line
38         } else {
39             return {2, {}}; // parallel
40         }
41     } else { // ok
42         return {0, a.st + A * (son / mom)};
43     }
44 }
45 // line to point distance
46 dvt dis_lp(Line l, Pt a) {
47     return area3x2(l.st, l.ed, a) / dis_pp(l.st, l.ed);
48 }

```

8.3 Area

```

1 // triangle
2 dvt area3(Pt a, Pt b, Pt c) {
3     return std::abs(cross(b - a, c - a) / 2);
4 }
5 dvt area3x2(Pt a, Pt b, Pt c) { // for integer
6     return std::abs(cross(b - a, c - a));
7 }
8 // simple convex area(can in)
9 dvt area(vector<Pt> &a) {
10     dvt ret = 0;
11     for (int i = 0, sz = a.size(); i < sz; i++) {
12         ret += cross(a[i], a[(i + 1) % sz]);
13     }
14     return std::abs(ret) / 2;
15 }
16 // check point in/out a convex
17 int io_convex(vector<Pt> convex, Pt q) {
18     // convex is Counterclockwise
19     for (int i = 0, sz = convex.size(); i < sz; i++) {
20         Pt cur = convex[i] - q;
21         Pt nex = convex[(i + 1) % sz] - q;
22         dvt cross_val = cross(cur, nex);
23         if (std::abs(cross_val) <= EPS) {
24             return 0; // on edge
25         }
26         if (cross_val < 0) {
27             return -1; // outside
28         }
29     }
30     return 1; // inside
31 }

```