

Installation

```
pip install taichi
ti example
```

Quick start

API

```
import taichi as ti
ti.init()

@ti.kernel
def monte_carlo_pi() -> float:
    total = 0
    for i in range(100000):
        x = ti.random()
        y = ti.random()
        if (x*x + y*y) < 1:
            total += 1

    return 4 * total / n
```

Supported backends

ti.cpu, ti.cuda, ti.metal, ti.opengl, ti.vulkan  
Choose a backend

```
ti.init(arch=ti.cuda)
```

Run in debug mode

```
ti.init(debug=True)
```

Data types

API

```
primitive tyes

i8, i16, i32, i64, u8, u16, u32, u64, f16, f32, f64
```

```
types.vector(n, dtype)

vec3 = ti.types.vector(3, float)
v = vec3(1, 2, 3)
```

```
types.matrix(n, m, dtype)

mat2x2 = ti.types.matrix(2, 2, float)
m = mat2x2(1, 2, 3, 4)
```

```
types.struct(**kwargs)

sphere = ti.types.struct(center=vec3, radius=float)
s = sphere(vec3(1, 2, 3), 1.0)
```

Quant types

API

```
u5 = ti.types.quant.int(bits=5, signed=False)
fixed_a = ti.types.quant.fixed(bits=10, max_value=20.0)
float_b = ti.types.quant.float(exp=6, frac=9, signed=False)
```

```
typecating

x = 1.0
y = ti.u8(x)
v = vec3(0.5, 1.0, 1.5)
w = v.cast(int)
```

Operators

API

comparison operators  
==, !=, >, <, >=, <=

logical operators  
not, or, and

bitwise operators  
~, &, ^, |, <<, >>

Data container

API

```
field(dtype, shape, ...)

f = ti.field(int, shape=(3, 3, 3))
```

```
Vector.field(dim, dtype, shape, ...)

f = ti.Vector.field(3, float, (10, 10))
```

```
Matrix.field(dim, dtype, shape, ...)

f = ti.Matrix.field(3, 3, float, shape=(10, 10))
```

```
Struct.field(dict, shape)

sphere = ti.types.struct(center=vec3, radius=float)
s = sphere.field(shape=100)
```

```
fill(val) to set a field

f.fill(1)
```

```
from_numpy(arr) to copy data from a NumPy array

f.from_numpy(arr)
```

```
to_numpy(arr) to convert to a NumPy array

arr = f.to_numpy()
```

Kernels and functions

@ti.kernel : Called from Python scope. Require type hints for arguments and return values. Can return scalar, vector and matrix. Allow at most one return value.

@ti.func : Called from Taichi scope. Recommend type hints for arguments and return values. Can return scalar, vector, matrix and struct. Allow multiple return values

```
Top level for loops in a kernel are automatically parallelized

x = ti.field(int, 100)
@ti.kernel
def example():
    for i in range(100):
        ...

        for j in x:
            x[j] = j
```

```
Force a top level for loop to execute in serialize

x = ti.field(int, 100)
@ti.kernel
def example():
    ti.loop_config(serialize=True)
    for i in range(100):
        ...
```

Interactive with Numpy arrays

API

```
arr = numpy.arange(12).reshape(3, 4)

@ti.kernel
def example(x: ti.types.ndarray()):
    for i, j in ti.ndrange(arr.shape[0], arr.shape[1]):
        arr[i, j] = i + j
```

Data-oriented programming

API

data-oriented class  
A data-oriented class is used when your data is actively updated in the Python scope (such as current time and user input events) and tracked in Taichi kernels.

```
@ti.data_oriented
class TiArray:
    def __init__(self, n):
        self.x = ti.field(dtype=ti.i32, shape=n)

    @ti.kernel # Defines Taichi kernels in the data-oriented Python class
    def inc(self):
        for i in self.x:
            self.x[i] += 1

a = TiArray(32)
a.inc()
```

dataclass  
A dataclass is a wrapper of 'ti.types.struct'. You can define Taichi functions as its methods and call these methods in the Taichi scope.

```
@ti.dataclass
class Sphere:
    center: vec3
    radius: float

    @ti.func
    def area(self): # Defines a Taichi function as method
        return 4 * math.pi * self.radius**2

@ti.kernel
def test():
    sphere = Sphere(vec3(0), radius=1.0)
    print(sphere.area())
```

Commonly-used math functions

API

ti.acos(x), ti.asin(x), ti.atan2(x), ti.ceil(x), ti.clamp(x, xmin, xmax), ti.cos(x), ti.cross(x, y), ti.dot(x,y), ti.exp(x), ti.floor(x),ti.fract(x), ti.inverse(mat), ti.norm(x), ti.log(x), ti.max(x, y, ...), ti.min(x, y, ...), tm.mod(x,y), tm.normalize(x), tm.pow(x, a), ti.round(x), ti.sign(x), ti.sin(x), tm.smoothstep(e0, e1, x), ti.sqrt(x), tm.step(edge, x),ti.tan(x), ti.tanh(x), tm.degrees(x), tm.radians(x)

Global settings

API

```
Set default precision

ti.init(default_fp=ti.f64)
ti.init(default_ip=ti.i64)
```

```
Set random seed

ti.init(random_seed=0)
```

```
Set offline-cache

ti.init(offline_cache=False)
```

```
Set packed mode

ti.init(packed=True)
```

Visualization

GUI system

API

```
gui = ti.GUI('Window Title', (640, 360)) # Creates a window
while not gui.get_event(ti.GUI.ESCAPE, ti.GUI.EXIT):
    gui.show() # Displays the window
```

GGUI system

API

```
pixels = ti.Vector.field(3, float, (640, 480))
window = ti.ui.Window("Window Title", (640, 360)) # Creates a window
canvas = window.get_canvas() # Creates a canvas

while window.running:
    canvas.set_image(pixels)
    window.show()

window.save_imgae(filename)
```

```
2D Canvas drawing API

canvas.set_background_color(color)
canvas.triangles(vertices, color, indices, per_vertex_color)
canvas.circles(vertices, radius, color, per_vertex_color)
canvas.lines(vertices, width, indices, color, per_vertex_color)
```

```
3D scene drawing API

scene.lines(vertices, width, indices, color, per_vertex_color)
scene.mesh(vertices, indices, normals, color, per_vertex_color)
scene.particles(vertices, radius, color, per_vertex_color)
```

Performance tuning

API

```
Kernel profiler (CPU and CUDA only):
To analyze the performance of Taichi kernels

ti.init(ti.cpu, kernel_profiler=True)
ti.profiler.print_kernel_profiler_info()
```

Configure loops:  
To serialize the outermost for loop that immediately follows the line

```
ti.loop_config(serialize=True)
```

```
To designate No. of threads on the CPU backend

ti.loop_config(parallelize=8)
```

```
To designate No. of threads in each block of the GPU backend

ti.loop_config(block_dim=16)
```

## Debugging

[API](#)

Activate debug mode:

```
ti.init(arch=ti.cpu, debug=True)
```

Runtime print in Taichi scope:

```
@ti.kernel
def inside_taichi_scope():
    x = 256
    print('hello', x) #=> hello 256
```

Runtime assert in Taichi scope:

```
ti.init(arch=ti.cpu, debug=True)

x = ti.field(ti.f32, 128)

@ti.kernel
def do_sqrt_all():
    for i in x:
        assert x[i] >= 0
        x[i] = ti.sqrt(x[i])
```

Compile-time static-print:

```
x = ti.field(ti.f32, (2, 3))
y = 1

@ti.kernel
def inside_taichi_scope():
    ti.static_print(y) # => 1
    ti.static_print(x.shape) # => (2, 3)
    ti.static_print(x.dtype) # => DataType.
        float32
```

Compile-time static-assert:

```
@ti.func
def copy(dst: ti.template(), src: ti.template()
):
    ti.static_assert(dst.shape == src.shape, "
        copy() needs src and dst fields to
        be same shape")
    for I in ti.grouped(src):
        dst[I] = src[I]
```

Serial execution:

To serialize the program

```
ti.init(arch=ti.cpu, cpu_max_num_threads=1)
```

To serializes the for loop that immediately follows the line

```
ti.loop_config(serialize=True)
```

Access a conciser version of traceback message:

```
import sys
sys.tracebacklimit = 0
```

## FAQ

... Can I use recursion?

→ You cannot use recursions in Taichi functions and kernels.

... Can I pass a dict to a kernel?

→ You cannot directly pass a Python dictionary to the Taichi scope, for a work around you can put the dict into a struct.